Predicting Free vs Paid Games on Steam

Group 15: Buyang Daffa, Cathy Zhang, Elaine Tao, Thê Quach

Summary

This project uses machine learning to predict whether a Steam game is free-to-play or paid based on its attributes. Using a snapshot of approximately 5,000 Steam games collected in August 2025 (vintagedon (2025)), we train a cross-validated logistic regression classifier. The final model achieves 95.9% accuracy and a ROC AUC of 0.923 on the held-out test set, substantially outperforming a majority-class baseline of 79.4%.

Introduction

Steam is the world's largest PC game distribution platform, with over 10,000 annual releases (Statista Research Department (2026)) and around 20 million daily active users (Steam (n.d.)). Being able to predict whether a game will be free or not helps developers make pre-launch pricing decisions, helps publishers evaluate projects, and helps researchers study quality signals in large content marketplaces.

The dataset used is the Steam 2025 5K Games Dataset (vintagedon (2025)): a gzip-compressed JSON snapshot of approximately 5,000 Steam game records taken on August 31, 2025. Key fields include `steam_appid`, `name`, `is_free` (the target variable), `genres`, `categories`, `platforms`, `release_date`, `required_age`, and `developer`.

Specifically, we ask:

1. What game attributes differ most between free-to-play and paid titles?
2. Can a machine learning classifier accurately distinguish free and paid games using only pre-launch observable features?
3. Which features contribute most to that classification?

Methods & Results

The R programming language (R Core Team (2024)) and the following R packages were used to perform the analysis: tidyverse (Wickham et al. (2019)), caret (Kuhn (2024)), pROC (Robin et al. (2011)), janitor (Firke (2023)), lubridate (Grolemund and Wickham (2011)), scales (Wickham, Pedersen, and Seidel (2023)), patchwork (Pedersen (2024)), jsonlite (Ooms (2023)), and Quarto (Allaire et al. (2022)).

Data were loaded, cleaned, and feature-engineered using `scripts/02_data-preprocessing.R`. Column names were simplified, `is_free` was recoded as a two-level factor, platform flags were cast to logical and summed into `platform_count`, and the top 15 most-frequent game categories were one-hot encoded as indicator columns. Missing values were imputed with sensible defaults, keeping data loss below 10%.

Data Validation

Exploratory Data Analysis

The dataset is heavily imbalanced: paid games account for 79.4% of records and free games for only 20.6% (Figure 1). This means a naive majority-class classifier would already achieve ~79% accuracy, so model accuracy must be interpreted alongside sensitivity and specificity.

Figure 2 shows distributions of the four key numeric predictors. `n_categories` is right-skewed: most games belong to just a few categories. `platform_count` clusters at 1, reflecting that most titles are Windows-only. `release_year` rises sharply post-2015 as Steam's catalogue expanded. `required_age` is concentrated at 0, as most games carry no age restriction.

Figure 3 presents further feature relationships by class. Release-year distributions are similarly shaped for both classes, but paid games dominate throughout. The binary feature panel shows that paid games are far more likely to have DLC or a demo, consistent with using demos to drive paid conversions.

Figure 4 shows the difference in category prevalence between free and paid games. Single-player games strongly skew paid, while multiplayer and Steam leaderboard games tilt slightly toward free — consistent with free-to-play titles relying on large player pools for engagement.

Modeling and Evaluation

The dataset was split 80/20 into training and test sets using stratified sampling to preserve the class ratio. A majority-class baseline — predicting "Paid" for every observation — yields 79.4% accuracy. Logistic regression was trained using `caret` (Kuhn (2024)) with 5-fold cross-validation optimising for ROC AUC. Only pre-launch observable features were included as predictors.



Figure 1: Class distribution of the target variable. Paid games outnumber free games roughly 4:1.



Figure 2: Distributions of the four key numeric predictors, faceted by free vs paid class.



Figure 3: Release year trends and binary feature rates broken down by free vs paid status.



Figure 4: Difference in category prevalence between free and paid games.

Classification metrics for the model on the held-out test set are shown in Table 1.

Table 1: Classification metrics for the logistic regression model on the held-out test set.

metric	value
Baseline accuracy (majority class)	0.7940
Model accuracy	0.9585
Cohen's Kappa	0.8667
Sensitivity (Free recall)	0.8323
Specificity (Paid recall)	0.9913
Balanced accuracy	0.9118
ROC AUC	0.9230

The model improves on the baseline by 16 percentage points. Specificity is near-perfect at 0.991, while sensitivity reaches 0.832. Cohen's Kappa of 0.867 confirms performance well beyond chance (Cadili, Fyson, and Widmann (2015)). Balanced accuracy of 0.912 indicates the model handles both classes reasonably despite the imbalance (Silva (2024)).

In Figure 5 we show the ROC curve, which hugs the top-left corner (AUC = 0.923), confirming strong discriminative ability across all decision thresholds.



Figure 5: ROC curve on the held-out test set (AUC = 0.923).

The confusion matrix in Figure 6 shows the raw prediction counts. The model correctly identifies the vast majority of paid games, while missing a smaller proportion of free games due to class imbalance.



Figure 6: Confusion matrix on the held-out test set.

The top 15 variable importance scores are presented in Table 2. The five most important predictors are family sharing, single-player, Steam leaderboards, multiplayer, and demo availability.

Table 2: Top 15 variable importance scores from the logistic regression model.

term	Estimate	odds_ratio	Pr(>|z|)
game_typeseries	-39.3360210	0.0000000	0.9951821
game_typedemo	-32.9848849	0.0000000	0.9943019
game_typemod	-31.9277191	0.0000000	0.9953197
windows_supportTRUE	-16.6667177	0.0000001	0.9968516
game_typegame	-14.8650142	0.0000004	0.9974284
game_typeepisode	-14.6994101	0.0000004	0.9974571
game_typevideo	-13.5617122	0.0000013	0.9976539
game_typedlc	-13.0116513	0.0000022	0.9977491
game_typemusic	-12.5921752	0.0000034	0.9978216
cat_family_sharingTRUE	4.6434380	103.9009423	0.0000000
cat_single_playerTRUE	-2.2241078	0.1081639	0.0000000

Table 2: Top 15 variable importance scores from the logistic regression model.

term	Estimate	odds_ratio	Pr(>|z|)
cat_steam_leaderboardsTRUE	1.0063257	2.7355314	0.0001426
cat_multi_playerTRUE	-0.8675205	0.4199916	0.0007529
has_demoTRUE	0.7684477	2.1564162	0.0049835
linux_supportTRUE	-0.4929977	0.6107927	0.0176968

Discussion

The logistic regression classifier achieves strong overall performance (accuracy 0.959, AUC 0.923), but the asymmetry between sensitivity (0.832) and specificity (0.991) warrants careful interpretation. The model is more reliable at identifying paid games than free ones — a consequence of the 4:1 class imbalance in the training data.

The variable importance results are counterintuitive in places. Family sharing emerges as the single strongest predictor of a game being *free*, yet the EDA showed that paid games have family sharing enabled more often in absolute frequency. The logistic regression coefficient captures the conditional relationship after controlling for all other variables, which can reverse marginal associations — a known consequence of multivariate adjustment.

The strong influence of the single-player category on predicting *paid* games aligns with industry convention: narrative or campaign-driven titles typically require a purchase, whereas free-to-play games rely on multiplayer engagement and microtransactions.

An interesting follow-up analysis would be to define multiplayer sub-categories (MOBA, MMORPG, co-op) to determine whether finer genre distinctions improve predictive power, or to extend the target variable beyond binary free/paid to capture the full pricing distribution.

References

Allaire, J. J., Charles Teague, Carlos Scheidegger, Yihui Xie, and Christophe Dervieux. 2022. "Quarto." https://doi.org/10.5281/zenodo.5960048.

Cadili, Rodrigo, Hannah Fyson, and Moritz Widmann. 2015. "What Is Cohen's Kappa? How and When to Use It (Plus Common Pitfalls to Avoid)." KNIME. https://www.knime.com/blog/cohens-kappa-an-overview.

Firke, Sam. 2023. "Janitor: Simple Tools for Examining and Cleaning Dirty Data." https://CRAN.R-project.org/package=janitor.

Grolemund, Garrett, and Hadley Wickham. 2011. "Dates and Times Made Easy with lubridate." https://CRAN.R-project.org/package=lubridate.

Kuhn, Max. 2024. "Caret: Classification and Regression Training." https://CRAN.R-project.org/package=caret.

Ooms, Jeroen. 2023. "Jsonlite: A Simple and Robust JSON Parser and Generator for R." https://CRAN.R-project.org/package=jsonlite.

Pedersen, Thomas Lin. 2024. "Patchwork: The Composer of Plots." https://CRAN.R-project.org/package=patchwork.

R Core Team. 2024. *R: A Language and Environment for Statistical Computing*. Vienna, Austria: R Foundation for Statistical Computing. https://www.R-project.org/.

Robin, Xavier, Natacha Turck, Alexandre Hainard, Natalia Tiberti, Frédérique Lisacek, Jean-Charles Sanchez, and Markus Müller. 2011. "pROC: An Open-Source Package for R and S+ to Analyze and Compare ROC Curves." *BMC Bioinformatics* 12: 77. https://doi.org/10.1186/1471-2105-12-77.

Silva, Caina Max Couto de. 2024. "A Data Scientist's Guide to Balanced Accuracy." Train in Data. https://www.blog.trainindata.com/a-data-scientists-guide-to-balanced-accuracy/.

Statista Research Department. 2026. "Number of Games Released on Steam Worldwide from 2004 to 2025." Statista. https://www.statista.com/statistics/552623/number-games-released-steam/.

Steam. n.d. "Charts Overview." https://store.steampowered.com/charts/.

vintagedon. 2025. "Steam 2025 5K Games Dataset." GitHub. https://github.com/vintagedon.

Wickham, Hadley, Mara Averick, Jennifer Bryan, Winston Chang, Lucy D'Agostino McGowan, Romain François, Garrett Grolemund, et al. 2019. "Welcome to the tidyverse." *Journal of Open Source Software* 4 (43): 1686. https://doi.org/10.21105/joss.01686.

Wickham, Hadley, Thomas Lin Pedersen, and Dana Seidel. 2023. "Scales: Scale Functions for Visualization." https://CRAN.R-project.org/package=scales.