

Environment & Test Data Details — Project Pegasus

Field	Value
Date	2026-04-09
Prepared by	QA Team
Status	Living Document

1. Dev Environment URLs

All dev services are deployed on a VPS (EC2) with Docker Compose orchestration.

#	Service	URL	Status
1	Partner Gateway	https://dev-partner-gw.onecluster.co	DOWN
2	Admin Gateway	https://dev-admin-gw.onecluster.co	UP
3	User Management	https://dev-user-mgmt.onecluster.co	UP
4	Admin Auth	https://dev-admin-auth.onecluster.co	UP
5	Billing	https://dev-billing.onecluster.co	DOWN
6	Wallet	https://dev-wallet.onecluster.co	DOWN
7	Customer	https://dev-customer.onecluster.co	DOWN
8	Webhook	https://dev-webhook.onecluster.co	DOWN
9	KYC	https://dev-kyc.onecluster.co	DOWN
10	Account	https://dev-account.onecluster.co	DOWN
11	Payment	https://dev-payment.onecluster.co	DOWN
12	Collection	https://dev-collection.onecluster.co	DOWN
13	Bank Adapter	https://dev-bank-adapter.onecluster.co	DOWN
14	Notification	https://dev-notification.onecluster.co	DOWN
15	Partner Portal	https://dev-partner.onecluster.co	UP
16	Admin Portal	https://dev-admin.onecluster.co	UP

Summary: 7 services UP, 9 services DOWN (all banking domain services unreachable).

2. Production Environment URLs

#	Service	URL
1	Partner Gateway	https://api.onecluster.co
2	Admin Gateway	https://admin-api.onecluster.co
3	Partner Portal	https://partner.onecluster.co

4	Admin Portal	https://admin.onecluster.co
5	Documentation	https://docs.onecluster.co

Note: Production is not yet live. These URLs are reserved and will be configured once staging validation is complete.

3. Infrastructure

3.1 Redis

Property	Value
Version	Redis 7.2
Port	6379
Usage	Session caching, rate limiting, idempotency key storage, distributed locking
Connection	redis://localhost:6379 (dev), managed Redis in production

3.2 SQL Server

Property	Value
Version	SQL Server 2022 / Azure SQL Managed Instance
Host	ubn-db-33351.database.windows.net
Port	1433
Authentication	SQL Authentication (credentials in environment variables)
TLS	Required (Encrypt=True;TrustServerCertificate=False)

3.3 Kafka

Property	Value
Port	9092
Usage	Event-driven communication between services (payment events, webhook dispatch, collection notifications)
Topics	payment-events, collection-events, webhook-dispatch, notification-events

4. Database Names Per Service

Each service owns its own database to enforce bounded context separation.

#	Service	Database Name
1	User Management	PegasusUserMgmtDb
2	Admin Auth	PegasusAdminAuthDb
3	Webhook	PegasusWebhookDb
4	Billing	PegasusBillingDb
5	Wallet	PegasusWalletDb

6	Customer	PegasusCustomerDb
---	----------	-------------------

Note: Services such as Account, Payment, Collection, KYC, Bank Adapter, and Notification may share databases or use the above databases depending on the domain model. Refer to each service's `appsettings.json` for the exact connection string.

5. Test Data

5.1 Sandbox Demo API Key

```
ubn_sb_demo_key_XXXXXXXXXXXXXXXXXXXX
```

This is the pre-provisioned sandbox API key used for testing. It is bound to the demo partner account and has access to all sandbox endpoints. The `XX` portion represents the actual key value, which is stored securely and provided to testers on request.

5.2 Sandbox Test Accounts

Account Number	Type	Balance	Status
0100000001	Savings	₦1,000,000.00	Active
0100000002	Current	₦500,000.00	Active
0199999999	—	₦0.00	Closed

These accounts are pre-seeded in the sandbox environment and reset on each deployment. They are designed to exercise various account states:

- **0100000001** — Standard active savings account with sufficient balance for transfer tests.
- **0100000002** — Standard active current account for receiving transfers and testing account enquiry.
- **0199999999** — Closed account used to test error handling (expected error: `ACCOUNT_CLOSED`).

5.3 Payment Test Bank Codes

Bank Code	Bank Name	Type
044	Union Bank of Nigeria	Live (sandbox mock)
058	GTBank	Mock

In sandbox mode, transfers to bank code `044` simulate Union Bank processing. Transfers to bank code `058` simulate GTBank and return mock success responses.

6. Sandbox Mock Responses

The sandbox environment returns deterministic mock responses for third-party integrations.

6.1 Account Balance

```
{
  "success": true,
  "responseCode": "00",
  "message": "Balance retrieved successfully",
  "data": {
    "accountNumber": "0100000001",
    "availableBalance": 500000,
  }
}
```

```
    "currency": "NGN",
    "ledgerBalance": 500000
  }
}
```

6.2 BVN Verification

```
{
  "success": true,
  "responseCode": "00",
  "message": "BVN verification successful",
  "data": {
    "bvn": "22200000000",
    "matchStatus": "FULL_MATCH",
    "firstName": "DEMO",
    "lastName": "USER"
  }
}
```

6.3 CAC Lookup

```
{
  "success": true,
  "responseCode": "00",
  "message": "CAC lookup successful",
  "data": {
    "rcNumber": "RC000001",
    "companyName": "SANDBOX TEST COMPANY LTD",
    "status": "ACTIVE",
    "registrationDate": "2020-01-15"
  }
}
```

7. Admin Test Accounts

7.1 DemoAdAuthClient

A pre-configured OAuth client for the Admin Auth service used in testing.

Property	Value
Client ID	DemoAdAuthClient
Grant Type	client_credentials
Scope	admin.read admin.write

7.2 Seed Data — ad-users.json

Admin user accounts are seeded from the `ad-users.json` file located in the Admin Auth service's data directory. This file contains pre-configured admin users with the following roles:

Username	Role	Purpose
----------	------	---------

admin@onecluster.co	Owner	Full platform access
reviewer@onecluster.co	Reviewer	Production access request reviews
support@onecluster.co	Support	Read-only access for support operations

Note: Passwords for seed accounts are set via environment variables and are not stored in the JSON file.

8. Environment Variables Reference

The following table lists key environment variables required by each service category. Actual values are stored in GitHub Secrets and injected at deployment time.

8.1 Common (All Services)

Variable	Description
ASPNETCORE_ENVIRONMENT	Runtime environment (Development, Staging, Production)
ConnectionStrings__DefaultConnection	SQL Server connection string
Redis__ConnectionString	Redis connection string (localhost:6379)
Kafka__BootstrapServers	Kafka broker address (localhost:9092)

8.2 Authentication Services (Admin Auth, User Management)

Variable	Description
Jwt__Issuer	JWT token issuer URI
Jwt__Audience	JWT token audience
Jwt__SigningKey	RSA private key for RS256 signing (base64-encoded)
Jwt__ExpiryMinutes	Token expiry duration

8.3 Gateway Services (Partner Gateway, Admin Gateway)

Variable	Description
ReverseProxy__Clusters__*	YARP reverse proxy cluster destinations
RateLimiting__PermitLimit	Requests per window
RateLimiting__WindowSeconds	Rate limit window duration

8.4 Domain Services (Account, Payment, Collection, KYC)

Variable	Description
BankAdapter__BaseUrl	Bank Adapter service URL
Webhook__BaseUrl	Webhook service URL
Notification__BaseUrl	Notification service URL

8.5 Frontend Services (Partner Portal, Admin Portal)

Variable	Description
NEXT_PUBLIC_API_URL	Backend API base URL
NEXT_PUBLIC_ENVIRONMENT	Frontend environment label
NEXTAUTH_SECRET	NextAuth.js session secret

9. Data Cleanup

Sandbox data is ephemeral. No manual cleanup is required.

- Test accounts (`0100000001` , `0100000002` , `0199999999`) are re-seeded on each deployment.
- Transaction history in sandbox mode is not persisted across container restarts.
- The sandbox demo API key remains stable across deployments (it is seeded idempotently).
- Admin seed users are upserted on startup — existing records are updated, not duplicated.

For manual data reset during testing, restart the relevant service container:

```
docker compose restart <service-name>
```

This triggers the database migration and seed data pipeline on startup.