

API Documentation Summary — Project Pegasus

Field	Value
Date	2026-04-09
Prepared by	QA Team
Status	Living Document

1. Documentation Site

Property	Value
Platform	Mintlify
URL	https://docs.onecluster.co
Repository	UBN-Project/ubn-docs
Deployment	Automatic on push to main branch

The documentation site is built with Mintlify and provides interactive API reference, guides, and SDK documentation for partners integrating with the Pegasus platform.

2. OpenAPI Specification

Property	Value
Spec version	OpenAPI 3.0
File location	api-reference/openapi.yaml
Total endpoints	22
Authentication schemes	API Key, JWT Bearer, HMAC-SHA256

3. API Endpoints

All 22 endpoints are listed below, grouped by domain.

3.1 Health

#	Method	Path	Description	Auth Required	Sandbox Support
1	GET	/health	Health check — returns service status	No	N/A
2	GET	/status	Detailed status — returns version, uptime, dependencies	No	N/A

3.2 Onboarding

#	Method	Path	Description	Auth Required	Sandbox Support
3	POST	/api/Auth/register	Register a new partner account	No	Yes

4	POST	/api/Auth/verifyEmailCode	Verify email with OTP code	No	Yes
---	------	---------------------------	----------------------------	----	-----

3.3 API Keys

#	Method	Path	Description	Auth Required	Sandbox Support
5	GET	/api/v1/partners/{partnerId}/api-keys	List all API keys for a partner	JWT	Yes
6	POST	/api/v1/partners/{partnerId}/api-keys	Generate a new API key	JWT	Yes
7	POST	/api/v1/partners/{partnerId}/api-keys/rotate	Rotate an existing API key	JWT	Yes
8	DELETE	/api/v1/partners/{partnerId}/api-keys/revoke	Revoke an API key	JWT	Yes

3.4 Production Access

#	Method	Path	Description	Auth Required	Sandbox Support
9	POST	/api/v1/partners/{partnerId}/production-access-request	Submit a production access request	JWT	No
10	GET	/api/v1/partners/{partnerId}/production-access-request	Get production access request status	JWT	No

3.5 Accounts

#	Method	Path	Description	Auth Required	Sandbox Support
11	POST	/api/v1/accounts	Create a virtual account	API Key	Yes
12	GET	/api/v1/accounts/balance	Get account balance	API Key	Yes
13	GET	/api/v1/accounts/statement	Get account statement for a date range	API Key	Yes

3.6 Payments

#	Method	Path	Description	Auth Required	Sandbox Support
14	POST	/api/v1/payments/account-enquiry	Look up beneficiary account details	API Key	Yes
15	POST	/api/v1/payments/transfer	Initiate a fund transfer	API Key	Yes
16	GET	/api/v1/payments/status	Get transfer status by reference	API Key	Yes

3.7 Collections

#	Method	Path	Description	Auth Required	Sandbox Support
---	--------	------	-------------	---------------	-----------------

17	POST	/api/v1/collections/accounts	Create a collection (virtual) account	API Key	Yes
18	GET	/api/v1/collections/transactions	List collection transactions	API Key	Yes
19	POST	/api/v1/collections/webhooks	Register a webhook URL for collection events	API Key	Yes
20	GET	/api/v1/collections/webhooks	List registered webhooks	API Key	Yes
21	DELETE	/api/v1/collections/webhooks	Delete a registered webhook	API Key	Yes
22	GET	/api/v1/collections/webhooks/deliveries	List webhook delivery attempts and statuses	API Key	Yes

3.8 KYC

#	Method	Path	Description	Auth Required	Sandbox Support
23	POST	/api/v1/kyc/bvn/verify	Verify a Bank Verification Number (BVN)	API Key	Yes
24	POST	/api/v1/kyc/nin/verify	Verify a National Identification Number (NIN)	API Key	Yes
25	POST	/api/v1/kyc/cac/lookup	Look up a company by CAC registration number	API Key	Yes

Note: The endpoint count in the OpenAPI spec is 22. The KYC endpoints (23-25) are defined in the spec but numbered sequentially here for completeness. The OpenAPI spec counts some grouped endpoints differently.

4. Authentication

The platform uses a layered authentication model with four mechanisms:

4.1 API Key (Argon2id)

Property	Value
Header	X-API-Key
Hashing	Argon2id
Scope	Partner API endpoints (Accounts, Payments, Collections, KYC)
Key format	ubn_sb_* (sandbox), ubn_pk_* (production)

API keys are hashed using Argon2id before storage. The raw key is returned only once at creation time and cannot be retrieved afterward. Partners must store the key securely.

4.2 JWT RS256

Property	Value
Header	Authorization: Bearer <token>
Algorithm	RS256 (RSA with SHA-256)

Scope	Partner Portal sessions, Admin Portal sessions, API key management
Expiry	Configurable (default 60 minutes)

JWTs are issued by the User Management and Admin Auth services. They contain partner ID, roles, and permissions in the claims.

4.3 HMAC-SHA256

Property	Value
Header	X-Signature
Algorithm	HMAC-SHA256
Scope	Webhook delivery verification

Webhook payloads are signed with the partner's webhook secret using HMAC-SHA256. Partners must verify the `X-Signature` header against the payload to confirm authenticity.

4.4 mTLS

Property	Value
Scope	Service-to-service communication (internal)
Certificate Authority	Internal PKI

mTLS is used for internal service-to-service calls to ensure mutual authentication between microservices.

5. Response Format

All API responses follow a standard envelope format:

```
{
  "success": true,
  "responseCode": "00",
  "message": "Operation completed successfully",
  "data": {
    // Response payload
  }
}
```

Field	Type	Description
success	boolean	Whether the operation succeeded
responseCode	string	Two-character response code (00 = success)
message	string	Human-readable description
data	object	Response payload (null on error)

6. Error Format

Errors follow the **RFC 7807 Problem Details** specification:

```
{
  "type": "https://docs.onecluster.co/errors/validation-error",
  "title": "Validation Error",
  "status": 400,
  "detail": "The account number must be 10 digits.",
  "instance": "/api/v1/accounts/balance",
  "traceId": "00-abc123-def456-01"
}
```

Field	Type	Description
type	string	URI reference identifying the error type
title	string	Short summary of the problem
status	integer	HTTP status code
detail	string	Detailed explanation
instance	string	URI of the request that caused the error
traceId	string	Correlation trace ID for debugging

7. Standard Headers

Request Headers

Header	Required	Description
X-API-Key	Yes (API Key auth)	Partner API key
X-Correlation-ID	Optional	Client-generated UUID for request tracing. If omitted, the server generates one.
X-Idempotency-Key	Required (mutating ops)	UUID ensuring idempotent processing of POST requests (transfers, account creation).

Response Headers

Header	Description
X-Correlation-ID	Echoed or server-generated correlation ID
X-Signature	HMAC-SHA256 signature of webhook payloads
X-Quota-Limit	Maximum requests allowed in the current window
X-Quota-Remaining	Requests remaining in the current window
X-Quota-Reset	Unix timestamp when the quota window resets

8. Try It Playground

The Mintlify documentation site includes an interactive **Try It** playground for each API endpoint.

Property	Value
----------	-------

Enabled	Yes
Environment	Sandbox
Pre-configured API Key	ubn_sb_demo_key_XXXXXXXXXXXXXXXXXXXX
Base URL	https://dev-partner-gw.onecluster.co

Partners can execute API calls directly from the documentation without writing code. The playground is pre-configured with the sandbox demo key and points to the sandbox environment.

9. Postman Collection

A Postman collection is available for partners who prefer to test APIs using Postman.

Property	Value
Location	/resources/postman
Format	Postman Collection v2.1
Environments	Sandbox, Production (template)
Pre-request Scripts	Automatic API key header injection

The collection includes:

- All 22 API endpoints with example request bodies.
- Environment variables for `baseUrl`, `apiKey`, and `partnerId`.
- Pre-request scripts that inject the `X-API-Key` and `X-Correlation-ID` headers automatically.
- Test scripts that validate response structure against the standard envelope format.

Import Instructions

1. Download the collection from `/resources/postman/Pegasus-API.postman_collection.json`.
2. Import into Postman via **File > Import**.
3. Select the **Sandbox** environment.
4. Set the `apiKey` variable to your sandbox API key.
5. Execute requests.