

## HyperLink Wireless 5.1 to 5.8 GHz 32 dBi Dual Polarity & X Polarized/Dual Feed Dish Antenna - Model: HG5158DP-32D

### Applications

- 5.1/5.3/5.4/5.8 GHz ISM and UNII Band Applications
- Supports 1x2 and 2x2 MIMO AP/Routers
- 802.11a and 802.11 n MIMO Applications
- WiMAX Applications
- Long Distance Backhaul and Point to Point Data Links

### Features

- Wide bandwidth
- Aluminum reflector dish with UV stable light gray polymer finish
- Adjustable Dual and X Polarity feed horn system with (2) N-Female connectors
- Perforated dish helps reduce wind loading
- Includes tilt and swivel mast mount kit



### Description

The HyperGain model HG5158DP-32D is a high performance broadband dual polarized solid dish antenna. Because of its' superb electrical performance and mechanical stability, the parabolic dish antenna can be used in a wide variety of high performance 5 GHz range (5.1/5.3/5.4/5.8GHz) wireless applications. The wide band design of this antenna eliminates the need to purchase different antennas for each frequency. This simplifies installations since the same antenna can be used for a wide array of wireless applications. This antenna features 32 dBi of gain with a 3.5° horizontal beam-width and 3.5° vertical beam-width.

### Adjustable Dual Polarity Feed Horn System

The HG5158DP-32D features an adjustable dual polarity feed horn system which allows the antenna to be configured for Dual Polarization (horizontal and vertical) or for X-Polarization (+45° and -45°). It is fed via two N-Female connectors, one for each polarized signals. This feature makes it ideal for MIMO/802.11n and polarization diversity systems.

### Rugged and Weatherproof

The reflector dish of the HG5158DP-32D is constructed from high quality aluminum which gives it superior strength. The dish is coated in a light gray UV-inhibited polymer for durability and aesthetics. Perforated holes in the dish helps minimize wind loading.



The HG5158DP-32D is supplied with a tilt and swivel mast mount kit. This allows installation at various degrees of incline for easy alignment. It can be adjusted up or down from 0° to 30°.

## Specifications

### Electrical Specifications

|                                        |                                                                                      |
|----------------------------------------|--------------------------------------------------------------------------------------|
| <b>Frequency</b>                       | 5150 – 5850MHz                                                                       |
| <b>Gain</b>                            | 32 dBi                                                                               |
| <b>Polarization</b>                    | Adjustable - Dual Polarized (Vertical and Horizontal) or X-Polarized (+45° and -45°) |
| <b>Horizontal /Vertical Beam-width</b> | 3.5°/ 3.5°                                                                           |
| <b>F/B ratio</b>                       | ≥40dB                                                                                |
| <b>Cross-pol Isolation</b>             | ≥28dB                                                                                |
| <b>Max Input Power</b>                 | 100 watts                                                                            |
| <b>Impedance</b>                       | 50 Ohm                                                                               |
| <b>VSWR</b>                            | < 1.5:1 avg.                                                                         |

### Mechanical Specifications

|                            |                      |
|----------------------------|----------------------|
| <b>Connector Interface</b> | (2) N Female         |
| <b>Diameter</b>            | 35.43 in (900mm)     |
| <b>Weight</b>              | 23.1 lbs (10.5kg)    |
| <b>Mounting Mast Size</b>  | 1.6 - 3 in (40-75mm) |

### Wind Loading Data

| <b>Wind Speed (MPH)</b> | <b>Loading</b> |
|-------------------------|----------------|
| 100                     | 266 lbs        |
| 125                     | 400 lbs        |

### RF Antenna Patterns

