

# **Mechatronics and Making Mid Project Report Exoskeleton Robotic Hand With Wolf Claw Mechanism**

Bryan Li<sup>1</sup> — SN 25003123  
Yan Pei Zhu — SN 25001234  
Nolan Yu — SN 25001234

October 31, 2025

# Contents

|          |  |          |
|----------|--|----------|
| <b>1</b> | <b>Introduction</b>  | <b>2</b> |
| 1.1      | Project Objectives and Description . . . . .                 | 2        |
| 1.2      | Similar Mechanisms . . . . .                                 | 2        |
| 1.3      | Industrial Applications . . . . .                            | 2        |
| <b>2</b> | <b>Mechanical and Mechanism Analysis</b>                     | <b>2</b> |
| 2.1      | Drive Method and Transmission . . . . .                      | 2        |
| 2.1.1    | Transmission Process Details . . . . .                       | 3        |
| 2.1.2    | Key Design Advantages . . . . .                              | 3        |
| 2.1.3    | Kinematic Performance . . . . .                              | 4        |
| 2.2      | Fingers and Wrist Mechanisms . . . . .                       | 4        |
| 2.3      | Wolf Claw Mechanism Comparison . . . . .                     | 4        |
| 2.3.1    | Version 1: Planetary Gear . . . . .                          | 4        |
| 2.3.2    | Version 2: Compound Gear Train . . . . .                     | 4        |
| <b>3</b> | <b>Mathematical Modelling and Analysis</b>                   | <b>4</b> |
| 3.1      | Fingers and Wrist Modelling . . . . .                        | 4        |
| 3.2      | Wolf Claw Mechanism Version 1: Planetary Gear . . . . .      | 4        |
| 3.3      | Wolf Claw Mechanism Version 2: Compound Gear Train . . . . . | 4        |
| <b>4</b> | <b>Conclusion and Future Work</b>                            | <b>4</b> |

# 1 Introduction

## 1.1 Project Objectives and Description


## 1.2 Similar Mechanisms

## 1.3 Industrial Applications

# 2 Mechanical and Mechanism Analysis

## 2.1 Drive Method and Transmission

The exoskeleton robotic hand employs an acceleration-based transmission system where finger movements are amplified through a planetary gear mechanism to achieve significant blade extension. Below is the detailed transmission process illustrated through a flowchart:



### 2.1.1 Transmission Process Details

#### 1. Biomechanical Input (Finger Flexion):

- Natural finger flexion creates geometric displacement
- Overhead tendon routing on finger dorsal side
- Tendon displacement:  $\Delta L_t = k_f \cdot \theta_f$

#### 2. Tendon to Rotary Conversion:

- Tendon wraps around drum connected to ring gear
- Linear displacement converted to rotational input
- Ring gear rotation:  $\theta_r = \frac{\Delta L_t}{r_d}$

#### 3. Planetary Gear Acceleration:

- Ring gear serves as input (unconventional configuration)
- Planet gears transfer motion to sun gear
- 12.66:1 acceleration ratio:  $\theta_s = 12.66 \cdot \theta_r$
- Sun gear outputs high-speed, low-torque rotation

#### 4. Pulley and Belt Transmission:

- Sun gear shaft drives dual synchronized pulleys
- Timing belts maintain parallel blade alignment
- Three blades mounted perpendicular between belts

#### 5. Final Blade Deployment:

- Belt movement translates to linear blade extension
- Total amplification:  $12.66 \times$  finger movement
- Final extension:  $L_b = 12.66 \cdot \frac{k_f \cdot \theta_f}{r_d} \cdot r_p$

### 2.1.2 Key Design Advantages

- **Amplification Efficiency:**  $12.66 \times$  mechanical advantage enables significant blade extension from subtle finger movements
- **Compact Design:** Planetary gear system provides high ratio in minimal space
- **Intuitive Control:** Direct relationship between finger position and blade extension
- **Safety:** Acceleration mechanism requires minimal finger force, reducing user fatigue

### 2.1.3 Kinematic Performance

The complete transmission system achieves:

$$\text{Overall Ratio} = \underbrace{\frac{k_f}{r_d}}_{\text{Tendon}} \times \underbrace{12.66}_{\text{Planetary}} \times \underbrace{r_p}_{\text{Pulley}} = 12.66 \cdot \frac{k_f \cdot r_p}{r_d} \quad (1)$$

Where small finger movements ( $\theta_f$ ) result in proportionally larger blade extensions ( $L_b$ ), making the system both responsive and precise for its intended applications.

This acceleration-based transmission represents an innovative approach to exoskeleton tool deployment, leveraging planetary gear mechanics to amplify natural human movements into effective tool operations.

## 2.2 Fingers and Wrist Mechanisms

## 2.3 Wolf Claw Mechanism Comparison

### 2.3.1 Version 1: Planetary Gear

### 2.3.2 Version 2: Compound Gear Train

## 3 Mathematical Modelling and Analysis

### 3.1 Fingers and Wrist Modelling

### 3.2 Wolf Claw Mechanism Version 1: Planetary Gear

### 3.3 Wolf Claw Mechanism Version 2: Compound Gear Train

## 4 Conclusion and Future Work

## References

- [1] author. title. In editor, editor, *booktitle*, year.