

CSE 114A: Fall 2021

Introduction to Functional Programming

Environments and closures

Owen Arden
UC Santa Cruz

Based on course materials developed by Nadia Polikarpova

Roadmap

Past weeks:

- How do we *use* a functional language?

Next weeks:

- How do we *implement* a functional language?
- ... in a functional language (of course)

WHY??

- ***Master*** the concepts of functional languages by implementing them!
- ***Practice*** problem solving using Haskell

This week: Interpreter

- How do we *evaluate* a program given its abstract syntax tree (AST)?
- How do we *prove properties* about our interpreter (e.g. that certain programs never crash)?

2

The Nano Language

Features of Nano:

1. Arithmetic expressions
2. Variables and let-bindings
3. Functions
4. Recursion

3

Reminder: Calculator

Arithmetic expressions:

```
e ::= n
    | e1 + e2
    | e1 - e2
    | e1 * e2
```

Example:

```
4 + 13
==> 17
```

4

Reminder: Calculator

Haskell datatype to *represent* arithmetic expressions:

```
data Expr = Num Int
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

Haskell function to *evaluate* an expression:

```
eval :: Expr -> Int
eval (Num n)      = n
eval (Add e1 e2)  = eval e1 + eval e2
eval (Sub e1 e2)  = eval e1 - eval e2
eval (Mul e1 e2)  = eval e1 * eval e2
```

5

Reminder: Calculator

Alternative representation:

```
data Binop = Add | Sub | Mul
```

```
data Expr = Num Int           -- number
          | Bin Binop Expr Expr -- binary expression
```

Evaluator for alternative representation:

```
eval :: Expr -> Int
eval (Num n)      = n
eval (Bin Add e1 e2) = eval e1 + eval e2
eval (Bin Sub e1 e2) = eval e1 - eval e2
eval (Bin Mul e1 e2) = eval e1 * eval e2
```

6

The Nano Language

Features of Nano:

1. Arithmetic expressions [done]
2. Variables and let-bindings
3. Functions
4. Recursion

7

Extension: variables

Let's add variables and **let** bindings!

```
e ::= n | x
    | e1 + e2 | e1 - e2 | e1 * e2
    | let x = e1 in e2
```

Example:

```
let x = 4 + 13 in  -- 17
let y = 7 - 5 in  -- 2
x * y

==> 34
```

8

Extension: variables

Haskell representation:

```
data Expr = Num Int           -- number
          | ???               -- variable
          | Bin Binop Expr Expr -- binary expression
          | ???               -- let expression
```

9

Extension: variables

```
type Id = String
```

```
data Expr = Num Int           -- number
          | Var Id            -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr  -- let expression
```

Haskell function to *evaluate* an expression:

```
eval :: Expr -> Int
eval (Num n)      = n
eval (Var x)      = ???
...
```

10

Extension: variables

```
type Id = String
```

```
data Expr = Num Int           -- number
          | Var Id            -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr  -- let expression
```

Haskell function

```
eval :: Expr -> Int
eval (Num n)      = n
eval (Var x)      = ???
...
```

How do we evaluate a variable?

We have to remember
which *value* it was bound to!

11

Environment

An expression is evaluated in an **environment**, which maps all its *free variables* to *values*

Examples:

```
x * y
=[x:17, y:2]=> 34
```

```
x * y
=[x:17]=> Error: unbound variable y
```

```
x * (let y = 2 in y)
=[x:17]=> 34
```

- How should we represent the environment?
- Which operations does it support?

12

Extension: variables

What does this evaluate to? *

```
let x = 5 in
let y = x + z in
let z = 10 in
y
```

- ☐ (A) 15
- ☐ (B) 5
- ☐ (C) Error: unbound variable x
- ☐ (D) Error: unbound variable y
- ☐ (E) Error: unbound variable z



<http://tiny.cc/cse116-vars-ind>

13

Extension: variables

What does this evaluate to? *

```
let x = 5 in
let y = x + z in
let z = 10 in
y
```

- ☐ (A) 15
- ☐ (B) 5
- ☐ (C) Error: unbound variable x
- ☐ (D) Error: unbound variable y
- ☐ (E) Error: unbound variable z



<http://tiny.cc/cse116-vars-grp>

14

Environment: API

To evaluate `let x = e1 in e2` in env:

- evaluate `e2` in an extended environment `env + [x:v]`
- where `v` is the result of evaluating `e1`

To evaluate `x` in env:

- **lookup** the most recently added binding for `x`

```
type Value = Int
```

```
data Env = ... -- representation not that important
```

```
-- | Add a new binding
```

```
add :: Id -> Value -> Env -> Env
```

```
-- | Lookup the most recently added binding
```

```
lookup :: Id -> Env -> Value
```

15

Evaluating expressions

Back to our expressions... now with environments!

```
data Expr = Num Int           -- number
          | Var Id            -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr  -- let expression
```

16

Evaluating expressions

Haskell function to *evaluate* an expression:

```
eval :: Env -> Expr -> Value
eval env (Num n)      = n
eval env (Var x)      = lookup x env
eval env (Bin op e1 e2) = f v1 v2
  where
    v1 = eval env e1
    v2 = eval env e2
    f = case op of
        Add -> (+)
        Sub -> (-)
        Mul -> (*)
eval env (Let x e1 e2) = eval env' e2
  where
    v    = eval env e1
    env' = add x v env
```

17

Example evaluation

Nano expression

```
let x = 1 in
let y = (let x = 2 in x) + x in
let x = 3 in
x + y
```

is represented in Haskell as:

```
exp1 = Let "x"
      (Num 1)
      (Let "y"
        (Add
          (Let "x" (Num 2) (Var x))
          (Let "x"
            (Num 3)
            (Add (Var x) (Var y))))
        (Var x))
      (Let "x"
        (Num 3)
        (Add (Var x) (Var y))))
      exp2
```

18

Example evaluation

```
eval [] exp1
=> eval [] (Let "x" (Num 1) exp2)
=> eval [{"x",eval [] (Num 1)}] exp2
=> eval [{"x",1}]
    (Let "y" (Add exp3 exp4) exp5)
=> eval [{"y", (eval [{"x",1}] (Add exp3 exp4))}, {"x",1}]
    exp5
=> eval [{"y", (eval [{"x",1}] (Let "x" (Num 2) (Var "x")))
        + eval [{"x",1}] (Var "x"))}, {"x",1}]
    exp5
=> eval [{"y", (eval [{"x",2}, {"x",1}] (Var "x") -- new binding for x
        + 1)}, {"x",1}]
    exp5
=> eval [{"y", (2 -- use latest binding for x
        + 1)}, {"x",1}]
    exp5
=> eval [{"y",3}, {"x",1}]
    (Let "x" (Num 3) (Add (Var "x") (Var "y")))
```

19

Example evaluation

```
=> eval [{"y",3}, {"x",1}]
    (Let "x" (Num 3) (Add (Var "x") (Var "y")))
=> eval [{"x",3}, {"y",3}, {"x",1}] -- new binding for x
    (Add (Var "x") (Var "y"))
=> eval [{"x",3}, {"y",3}, {"x",1}] (Var "x")
    + eval [{"x",3}, {"y",3}, {"x",1}] (Var "y")
=> 3 + 3
=> 6
```

20

Example evaluation

Same evaluation in a simplified format (Haskell `Expr` terms replaced by their “pretty-printed version”):

```
eval []
{let x = 1 in let y = (let x = 2 in x) + x in let x = 3 in x + y}
=> eval [x:(eval [] 1)]
    {let y = (let x = 2 in x) + x in let x = 3 in x + y}
=> eval [x:1]
    {let y = (let x = 2 in x) + x in let x = 3 in x + y}
=> eval [y:(eval [x:1] {(let x = 2 in x) + x}), x:1]
    {let x = 3 in x + y}
=> eval [y:(eval [x:1] {let x = 2 in x} + eval [x:1] {x}), x:1]
    {let x = 3 in x + y}
-- new binding for x:
=> eval [y:(eval [x:2,x:1] {x}) + eval [x:1] {x}), x:1]
    {let x = 3 in x + y}
-- use latest binding for x:
=> eval [y:(2 + eval [x:1] {x}), x:1]
    {let x = 3 in x + y}
=> eval [y:(2 + 1), x:1]
    {let x = 3 in x + y}
```

21

Example evaluation

```
=> eval [y:(2 + 1), x:1] {let x = 3 in x + y}
=> eval [y:3, x:1] {let x = 3 in x + y}
-- new binding for x:
=> eval [x:3, y:3, x:1] {x + y}
=> eval [x:3, y:3, x:1] x + eval [x:3, y:3, x:1] y
-- use latest binding for x:
=> 3 + 3
=> 6
```

22

Runtime errors

Haskell function to *evaluate* an expression:

```
eval :: Env -> Expr -> Value
eval env (Num n)      = n
eval env (Var x)      = lookup x env -- can fail!
eval env (Bin op e1 e2) = f v1 v2
  where
    v1 = eval env e1
    v2 = eval env e2
    f = case op of
        Add -> (+)
        Sub -> (-)
        Mul -> (*)
eval env (Let x e1 e2) = eval env' e2
  where
    v = eval env e1
    env' = add x v env
```

How do we make sure lookup doesn't cause a run-time error?

23

Free vs bound variables

In `eval env e`, `env` must contain bindings for *all free variables* of `e`!

- an occurrence of `x` is **free** if it is not **bound**
- an occurrence of `x` is **bound** if it's inside `e2` where `let x = e1 in e2`
- evaluation succeeds when an expression is **closed**!

24

QUIZ

Which variables are free in the expression? *

```
let y = (let x = 2 in x) + x in
let x = 3 in
x + y
```

- ☐ (A) None
- ☐ (B) x
- ☐ (C) y
- ☐ (D) x y



<http://tiny.cc/cse116-free-ind>

25

QUIZ

Which variables are free in the expression? *

```
let y = (let x = 2 in x) + x in
let x = 3 in
x + y
```

- ☐ (A) None
- ☐ (B) x
- ☐ (C) y
- ☐ (D) x y



<http://tiny.cc/cse116-free-grp>

26

The Nano Language

Features of Nano:

1. Arithmetic expressions [done]
2. Variables and let-bindings [done]
3. Functions
4. Recursion

27

Extension: functions

Let's add lambda abstraction and function application!

```
e ::= n | x
    | e1 + e2 | e1 - e2 | e1 * e2
    | let x = e1 in e2
    | \x -> e    -- abstraction
    | e1 e2      -- application
```

Example:

```
let c = 42 in
let cTimes = \x -> c * x in
cTimes 2
==> 84
```

28

Extension: functions

Haskell representation:

```
data Expr = Num Int           -- number
          | Var Id             -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr   -- Let expression
          | ???                -- abstraction
          | ???                -- application
```

29

Extension: functions

Haskell representation:

```
data Expr = Num Int           -- number
          | Var Id             -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr   -- Let expression
          | Lam Id Expr        -- abstraction
          | App Expr Expr      -- application
```

30

Extension: functions

Example:

```
let c = 42 in
let cTimes = \x -> c * x in
cTimes 2
```

represented as:

```
Let "c"
  (Num 42)
(Let "cTimes"
  (Lam "x" (Mul (Var "c") (Var "x"))))
(App (Var "cTimes") (Num 2)))
```

31

Extension: functions

Example:

```
let c = 42 in
let cTimes = \x -> c * x in
cTimes 2
```

How should we evaluate this expression?

```
eval []
  {let c = 42 in let cTimes = \x -> c * x in cTimes 2}
=> eval [c:42]
      {let cTimes = \x -> c * x in cTimes 2}
=> eval [cTimes:???, c:42]
      {cTimes 2}
```

What is the value of cTimes???

32

Rethinking our values

Until now: a program *evaluates* to an integer (or fails)

```
type Value = Int

type Env = [(Id, Value)]

eval :: Env -> Expr -> Value
```

33

Rethinking our values

What do these programs evaluate to?

```
(1)
\ x -> 2 * x
==> ???
```

```
(2)
let f = \ x -> \ y -> 2 * (x + y) in
f 5
==> ???
```

Conceptually, (1) evaluates to itself (not exactly, see later). while (2) evaluates to something equivalent to `\ y -> 2 * (5 + y)`

34

Rethinking our values

Now: a program evaluates to an integer or a *lambda abstraction* (or fails)

- Remember: functions are *first-class* values

Let's change our definition of values!

```
data Value = VNum Int
           | VLam ??? -- What info do we need to store?
```

```
-- Other types stay the same
```

```
type Env = [(Id, Value)]
```

```
eval :: Env -> Expr -> Value
```

35

Function values

How should we represent a function value?

```
let c = 42 in
let cTimes = \ x -> c * x in
cTimes 2
```

We need to store enough information about `cTimes` so that we can later evaluate any *application* of `cTimes` (like `cTimes 2`)!

First attempt:

```
data Value = VNum Int
           | VLam Id Expr -- formal + body
```

36

Function values

Let's try this!

```
eval []
{let c = 42 in let cTimes = \x -> c * x in cTimes 2}
=> eval [c:42]
      {let cTimes = \x -> c * x in cTimes 2}
=> eval [cTimes:(\x -> c*x), c:42]
      {cTimes 2}
      -- evaluate the function:
=> eval [cTimes:(\x -> c*x), c:42]
      {(\x -> c * x) 2}
      -- evaluate the argument, bind to x, evaluate body:
=> eval [x:2, cTimes:(\x -> c*x), c:42]
      {c * x}
=>      42 * 2
=>      84
```

Looks good... can you spot a problem?

37

QUIZ

What should this evaluate to? *

```
let c = 42 in
let cTimes = \x -> c * x in -- but which c???
let c = 5 in
cTimes 2
```

- ☐ (A) 84
- ☐ (B) 10
- ☐ (C) Error: multiple definitions of c



<http://tiny.cc/cse116-cscope-ind>

38

QUIZ

What should this evaluate to? *

```
let c = 42 in
let cTimes = \x -> c * x in -- but which c???
let c = 5 in
cTimes 2
```

- ☐ (A) 84
- ☐ (B) 10
- ☐ (C) Error: multiple definitions of c



<http://tiny.cc/cse116-cscope-grp>

39

Static vs Dynamic Scoping

What we want:

```
let c = 42 in
let cTimes = \x -> c * x in
let c = 5 in
cTimes 2
=> 84
```

Lexical (or static) scoping:

- each occurrence of a variable refers to the most recent binding *in the program text*
- definition of each variable is unique and known *statically*
- good for readability and debugging: don't have to figure out where a variable got "assigned"

40

Static vs Dynamic Scoping

What we **don't** want:

```
let c = 42 in
let cTimes = \x -> c * x in
let c = 5 in
cTimes 2
=> 10
```

Dynamic scoping:

- each occurrence of a variable refers to the most recent binding *during program execution*
- can't tell where a variable is defined just by looking at the function body
- nightmare for readability and debugging:

41

Static vs Dynamic Scoping

Dynamic scoping:

- each occurrence of a variable refers to the most recent binding *during program execution*
- can't tell where a variable is defined just by looking at the function body
- nightmare for readability and debugging:

```
let cTimes = \x -> c * x in
let c = 5 in
let res1 = cTimes 2 in -- ==> 10
let c = 10 in
let res2 = cTimes 2 in -- ==> 20!!!
res2 - res1
```

42

Function values

```
data Value = VNum Int
           | VLam Id Expr -- formal + body
```

This representation can only implement dynamic scoping!

```
let c = 42 in
let cTimes = \x -> c * x in
let c = 5 in
cTimes 2
```

evaluates as:

```
eval []
{let c = 42 in let cTimes = \x -> c * x in let c = 5 in cTimes 2}
```

43

Function values

```
eval []
{let c = 42 in let cTimes = \x -> c * x in let c = 5 in cTimes 2}
=> eval [c:42]
    {let cTimes = \x -> c * x in let c = 5 in cTimes 2}
=> eval [cTimes:(\x -> c*x), c:42]
    {let c = 5 in cTimes 2}
=> eval [c:5, cTimes:(\x -> c*x), c:42]
    {cTimes 2}
=> eval [c:5, cTimes:(\x -> c*x), c:42]
    {(\x -> c * x) 2}
=> eval [x:2, c:5, cTimes:(\x -> c*x), c:42]
    {c * x}
-- Latest binding for c is 5!
=> 5 * 2
=> 10
```

Lesson learned: need to remember what c was bound to when cTimes was defined!

- i.e. “freeze” the environment at function definition

44

Closures

To implement lexical scoping, we will represent function values as *closures*

Closure = *lambda abstraction* (formal + body) + *environment* at function definition

```
data Value = VNum Int
           | VClos Env Id Expr -- env + formal + body
```

45

Closures

Our example:

```
eval []
{let c = 42 in let cTimes = \x -> c * x in let c = 5 in cTimes 2}
=> eval [c:42]
      {let cTimes = \x -> c * x in let c = 5 in cTimes 2}
-- remember current env:
=> eval [cTimes:<[c:42], \x -> c*x>, c:42]
      {let c = 5 in cTimes 2}
=> eval [c:5, cTimes:<[c:42], \x -> c*x>, c:42]
      {cTimes 2}
=> eval [c:5, cTimes:<[c:42], \x -> c*x>, c:42]
      {<[c:42], \x -> c * x> 2}
-- restore env to the one inside the closure, then bind 2 to x:
=> eval [x:2, c:42]
      {c * x}
      42 * 2
      84
=>
```

46

QUIZ

Which variables should be saved in the closure environment of f? *

```
let a = 20 in
let f =
  \x -> let y = x + 1 in
        let g = \z -> y + z in
        a + g x
in ...
```

- ☐ (A) a
- ☐ (B) a x
- ☐ (C) y g
- ☐ (D) a y g
- ☐ (E) a x y g z



<http://tiny.cc/cse116-env-ind>

47

QUIZ

Which variables should be saved in the closure environment of f? *

```
let a = 20 in
let f =
  \x -> let y = x + 1 in
        let g = \z -> y + z in
        a + g x
in ...
```

- ☐ (A) a
- ☐ (B) a x
- ☐ (C) y g
- ☐ (D) a y g
- ☐ (E) a x y g z



<http://tiny.cc/cse116-env-grp>

48

Free vs bound variables

- An occurrence of `x` is **free** if it is not **bound**
- An occurrence of `x` is **bound** if it's inside
 - `e2` where `let x = e1 in e2`
 - `e` where `\x -> e`
- A closure environment has to save *all free variables* of a function definition!

```
let a = 20 in
let f =
  \x -> let y = x + 1 in
        let g = \z -> y + z in
        a + g x -- a is the only free variable!
in ...
```

49

Evaluator

Let's modify our evaluator to handle functions!

```
data Value = VNum Int
           | VClos Env Id Expr -- env + formal + body

eval :: Env -> Expr -> Value
eval env (Num n)      = VNum n -- must wrap in VNum now!
eval env (Var x)      = lookup x env
eval env (Bin op e1 e2) = VNum (f v1 v2)
  where
    (VNum v1) = eval env e1
    (VNum v2) = eval env e2
    f = ... -- as before
eval env (Let x e1 e2) = eval env' e2
  where
    v = eval env e1
    env' = add x v env
eval env (Lam x body) = ??? -- construct a closure
eval env (App fun arg) = ??? -- eval fun, then arg, then apply
```

50

Evaluator

Evaluating functions:

- **Construct a closure**: save environment at function definition
- **Apply a closure**: restore saved environment, add formal, evaluate the body

```
eval :: Env -> Expr -> Value
...
eval env (Lam x body) = VClos env x body
eval env (App fun arg) = eval bodyEnv body
  where
    (VClos closEnv x body) = eval env fun -- eval function to closure
    vArg                  = eval env arg -- eval argument
    bodyEnv                = add x vArg closEnv
```

51

Evaluator

Evaluating functions:

- **Construct a closure:** save environment at function definition
- **Apply a closure:** restore saved environment, add formal, evaluate the body

```
eval :: Env -> Expr -> Value
...
eval env (Lam x body) = VClos env x body
eval env (App fun arg) =
  let vArg = eval env arg in -- eval argument
  let (VClos closEnv x body) = (eval env fun) in
  let bodyEnv = add x vArg closEnv in
  eval bodyEnv body
```

52

Quiz

With eval as defined above, what does this evaluate to? *

```
let f = \x -> x + y in
let y = 10 in
f 5
```

- ☐ (A) 15
- ☐ (B) 5
- ☐ (C) Error: unbound variable x
- ☐ (D) Error: unbound variable y
- ☐ (E) Error: unbound variable f



<http://tiny.cc/cse116-enveval-ind>

53

Quiz

With eval as defined above, what does this evaluate to? *

```
let f = \x -> x + y in
let y = 10 in
f 5
```

- ☐ (A) 15
- ☐ (B) 5
- ☐ (C) Error: unbound variable x
- ☐ (D) Error: unbound variable y
- ☐ (E) Error: unbound variable f



<http://tiny.cc/cse116-enveval-grp>

54

Evaluator

```
eval []
  {let f = \x -> x + y in let y = 10 in f 5}
=> eval [f:<[], \x -> x + y>]
      {let y = 10 in f 5}
=> eval [y:10, f:<[], \x -> x + y>]
      {f 5}
=> eval [y:10, f:<[], \x -> x + y>]
      {<[], \x -> x + y> 5}
=> eval [x:5] -- env got replaced by closure env + formal!
           {x + y} -- y is unbound!
```

55

Quiz

With eval as defined above, what does this evaluate to? *

```
let f = \n -> n * f (n - 1) in
f 5
```

- ☐ (A) 120
- ☐ (B) Evaluation does not terminate
- ☐ (C) Error: unbound variable f



<http://tiny.cc/cse116-enveval2-ind>

56

Quiz

With eval as defined above, what does this evaluate to? *

```
let f = \n -> n * f (n - 1) in
f 5
```

- ☐ (A) 120
- ☐ (B) Evaluation does not terminate
- ☐ (C) Error: unbound variable f



<http://tiny.cc/cse116-enveval2-grp>

57

Evaluator

```
eval []
  {let f = \n -> n * f (n - 1) in f 5}
=> eval [f:<[], \n -> n * f (n - 1)>]
      {f 5}
=> eval [f:<[], \n -> n * f (n - 1)>]
      {<[], \n -> n * f (n - 1)> 5}
=> eval [n:5] -- env got replaced by closure env + formal!
      {n * f (n - 1)} -- f is unbound!
```

Lesson learned: to support recursion, we need a different way of constructing the closure environment!