

CMPS 116: Fall 2019

Introduction to Functional Programming

Course review

Owen Arden
UC Santa Cruz

Based on course materials developed by Ranjit Jhala

The Lambda Calculus

- Lambda calculus terms
 - variables, abstractions, & applications
- Variable scope
 - Free vs bound variables
- Evaluation
 - Alpha renaming
 - Beta reduction
 - Normal form
- Church encodings
 - numbers, booleans, etc
- Recursion
 - Fixed-point combinator

2

Haskell

- A **typed, lazy, purely functional** programming language
 - Haskell = λ -calculus +
 - Better syntax
 - Types
 - Built-in features
 - Booleans, numbers, characters
 - Records (tuples)
 - Lists
 - Recursion
 - ...

3

Haskell topics

- Haskell's type system
 - Recognizing / understanding relationship between Haskell expressions and their types
- Algebraic data types
 - Records
 - Sum types
 - Recursive ADTs
- Pattern matching
 - Overlapped / missing patterns
- Writing algorithms on (recursive) ADTs
 - Base cases + inductive cases

4

Higher Order Functions

Iteration patterns over collections:

- **Filter** values in a collection given a *predicate*
- **Map** (iterate) a given *transformation* over a collection
- **Fold** (reduce) a collection into a value, given a *binary operation* to combine results

Useful helper HOFs:

- **Flip** the order of function's (first two) arguments
- **Compose** two functions

5

Evaluating Nano1

Back to our expressions... now with environments!

```
data Expr = Num Int           -- number
          | Var Id            -- variable
          | Bin Binop Expr Expr -- binary expression
          | Let Id Expr Expr  -- let expression
```

6

Static vs Dynamic Scoping

Dynamic scoping:

- each occurrence of a variable refers to the most recent binding *during program execution*
- can't tell where a variable is defined just by looking at the function body
- nightmare for readability and debugging:

```
let cTimes = \x -> c * x in
let c = 5 in
let res1 = cTimes 2 in -- ==> 10
let c = 10 in
let res2 = cTimes 2 in -- ==> 20!!!
res2 - res1
```

7

Static vs Dynamic Scoping

What we want:

```
let c = 42 in
let cTimes = \x -> c * x in
let c = 5 in
cTimes 2
=> 84
```

Lexical (or static) scoping:

- each occurrence of a variable refers to the most recent binding *in the program text*
- definition of each variable is unique and known *statically*
- good for readability and debugging: don't have to figure out where a variable got "assigned"

8

Static vs Dynamic Scoping

What we **don't** want:

```
let c = 42 in
let cTimes = \x -> c * x in
let c = 5 in
cTimes 2
=> 10
```

Dynamic scoping:

- each occurrence of a variable refers to the most recent binding *during program execution*
- can't tell where a variable is defined just by looking at the function body
- nightmare for readability and debugging:

9

Static vs Dynamic Scoping

Dynamic scoping:

- each occurrence of a variable refers to the most recent binding *during program execution*
- can't tell where a variable is defined just by looking at the function body
- nightmare for readability and debugging:

```
let cTimes = \x -> c * x in
let c = 5 in
let res1 = cTimes 2 in -- ==> 10
let c = 10 in
let res2 = cTimes 2 in -- ==> 20!!!
res2 - res1
```

10

Closures

To implement lexical scoping, we will represent function values as *closures*

Closure = *lambda abstraction* (formal + body) + *environment* at function definition

```
data Value = VNum Int
           | VClos Env Id Expr -- env + formal + body
```

11

Formalizing Nano

Goal: we want to guarantee properties about programs, such as:

- evaluation is deterministic
- all programs terminate
- certain programs never fail at run time
- etc.

To prove theorems about programs we first need to define formally

- their *syntax* (what programs look like)
- their *semantics* (what it means to run a program)

12

Type system for Nano2

A **type system** defines what types an expression can have

To define a type system we need to define:

- the *syntax* of types: what do types look like?
- the *static semantics* of our language (i.e. the typing rules): assign types to expressions

$G \vdash e :: T$

An expression e has type T in G if we can derive $G \vdash e :: T$ using these rules

An expression e is **well-typed** in G if we can derive $G \vdash e :: T$ for some type T

- and **ill-typed** otherwise

13

Double identity

```
let id = \x -> x in
let y = id 5 in
id (\z -> z + y)
```

Intuitively this program looks okay, but our type system *rejects* it:

- in the first application, `id` needs to have type `Int -> Int`
- in the second application, `id` needs to have type `(Int -> Int) -> (Int -> Int)`
- the type system forces us to pick *just one type* for each variable, such as `id` :(

What can we do?

14

Inference with polymorphic types

With polymorphic types, we can derive $e :: \text{Int} \rightarrow \text{Int}$ where e is

```
let id = \x -> x in
let y = id 5 in
id (\z -> z + y)
```

At a high level, inference works as follows:

1. When we have to pick a type T for x , we pick a **fresh type variable** a
2. So the type of `\x -> x` comes out as `a -> a`
3. We can **generalize** this type to **forall** $a . a \rightarrow a$
4. When we apply `id` the first time, we **instantiate** this polymorphic type with `Int`
5. When we apply `id` the second time, we **instantiate** this polymorphic type with `Int -> Int`

Let's formalize this intuition as a type system!

15

Typing rules

We need to change the typing rules so that:

1. Variables (and their definitions) can have polymorphic types

[T-Var] $G \vdash x :: S \quad \text{if } x:S \text{ in } G$

[T-Let]
$$\frac{G \vdash e1 :: S \quad G, x:S \vdash e2 :: T}{G \vdash \text{let } x = e1 \text{ in } e2 :: T}$$

16

Typing rules

2. We can *instantiate* a type scheme into a type

[T-Inst]
$$\frac{G \vdash e :: \text{forall } a . S}{G \vdash e :: [a / T] S}$$

3. We can *generalize* a type with free type variables into a type scheme

[T-Gen]
$$\frac{G \vdash e :: S}{G \vdash e :: \text{forall } a . S} \quad \text{if not } (a \text{ in } \text{FTV}(G))$$

17

Typing rules

The rest of the rules are the same:

[T-Num] $G \vdash n :: \text{Int}$

[T-Add]
$$\frac{G \vdash e1 :: \text{Int} \quad G \vdash e2 :: \text{Int}}{G \vdash e1 + e2 :: \text{Int}}$$

[T-Abs]
$$\frac{G, x:T1 \vdash e :: T2}{G \vdash \lambda x . e :: T1 \rightarrow T2}$$

[T-App]
$$\frac{G \vdash e1 :: T1 \rightarrow T2 \quad G \vdash e2 :: T1}{G \vdash e1 e2 :: T2}$$

18

Nano1: Operational Semantics

We define the step relation *inductively* through a set of *rules*:

```
[Add-L]  
$$\frac{e1 \Rightarrow e1'}{e1 + e2 \Rightarrow e1' + e2}$$
  -- premise -- conclusion

[Add-R]  
$$\frac{e2 \Rightarrow e2'}{n1 + e2 \Rightarrow n1 + e2'}$$


[Add]    
$$n1 + n2 \Rightarrow n \quad \text{where } n == n1 + n2$$


[Let-Def] 
$$\frac{e1 \Rightarrow e1'}{\text{let } x = e1 \text{ in } e2 \Rightarrow \text{let } x = e1' \text{ in } e2}$$


[Let]    
$$\text{let } x = v \text{ in } e2 \Rightarrow e2[x := v]$$

```

19

Operational semantics

We need to extend our reduction relation with rules for abstraction and application:

```
[App-L]  
$$\frac{e1 \Rightarrow e1'}{e1 \ e2 \Rightarrow e1' \ e2}$$


[App-R]  
$$\frac{e \Rightarrow e'}{v \ e \Rightarrow v \ e'}$$


[App]    
$$(\lambda x \rightarrow e) \ v \Rightarrow e[x := v]$$

```

20

Spring 19 final review

21

Now what?

Did you like what you learned here? Want to learn more?

- **CSE 114 (not 116) Functional Programming**
 - Someday?
- **CSE 110A Fundamentals of Compiler Design**
 - Fall 2019, Spring 2020, Wesley Mackey
 - Winter 2020, me
- **CSE 210A: Programming languages**
 - Winter 2020, Cormac Flanagan
- **CSE 210B: Adv. Programming languages**
 - Spring 2020, me

22

Thanks and good luck!

23
