

CSE 116: Fall 2019

Introduction to Functional Programming

Datatypes and Recursion

Owen Arden
UC Santa Cruz

Based on course materials developed by Nadia Polikarpova

What is Haskell?

- **Last week:**
 - built-in *data types*
 - base types, tuples, lists (and strings)
 - writing functions using pattern matching and recursion
- **This week:**
 - user-defined *data types*
 - and how to manipulate them using pattern matching and recursion
 - more details about recursion

2

Representing complex data

- **We've seen:**
 - *base types*: `Bool`, `Int`, `Integer`, `Float`
 - some ways to *build up* types: given types `T1`, `T2`
 - functions: `T1 -> T2`
 - tuples: `(T1, T2)`
 - lists: `[T1]`
- **Algebraic Data Types**: a single, powerful technique for building up types to represent complex data
 - lets you define your own data types
 - subsumes tuples and lists!

3

Product types

- Tuples can do the job but there are two problems...

```
deadlineDate :: (Int, Int, Int)
deadlineDate = (2, 4, 2019)
```

```
deadlineTime :: (Int, Int, Int)
deadlineTime = (11, 59, 59)
```

```
-- | Deadline date extended by one day
extension :: (Int, Int, Int) -> (Int, Int, Int)
extension = ...
```

- Can you spot them?

4

1. Verbose and unreadable

```
type Date = (Int, Int, Int)
type Time = (Int, Int, Int)
```

```
deadlineDate :: Date
deadlineDate = (2, 4, 2019)
```

```
deadlineTime :: Time
deadlineTime = (11, 59, 59)
```

```
-- | Deadline date extended by one day
extension :: Date -> Date
extension = ...
```

A type synonym for `T`: a name that can be used interchangeably with `T`

5

2. Unsafe

- We want this to fail at compile time!!!
extension deadlineTime
- **Solution:** construct two different **datatypes**

```
data Date = Date Int Int Int
data Time = Time Int Int Int
-- constructor^    ^parameter types
```

```
deadlineDate :: Date
deadlineDate = (2, 4, 2019)
```

```
deadlineTime :: Time
deadlineTime = (11, 59, 59)
```

6

Record Syntax

- Haskell's **record syntax** allows you to *name* the constructor parameters:

- Instead of

```
data Date = Date Int Int Int
```

- You can write:

```
data Date = Date {  
  month :: Int,  
  day   :: Int,  
  year  :: Int  
}
```

Use the *field name* as a function to access part of the data

```
deadlineDate = Date 1 1 2019  
deadlineMonth = month deadlineDate
```

7

Building data types

- Three key ways to build complex types/values:
 - Product types (each-of):** a value of **T** contains a value of **T1** and a value of **T2** [done]
 - Sum types (one-of):** a value of **T** contains a value of **T1** or a value of **T2**
 - Recursive types:** a value of **T** contains a *sub-value* of the same type **Ts**

8

Example: NanoMD

- Suppose I want to represent a *text document* with simple markup. Each paragraph is either:

- plain text (**String**)
- heading: level and text (**Int** and **String**)
- list: ordered? and items (**Bool** and [**String**])

- I want to store all paragraphs in a *list*

```
doc = [ (1, "Notes from 130")           -- Lvl 1 heading  
      , "There are two types of languages:" -- Plain text  
      , (True, ["purely functional", "purely evil"])  
      ] -- ^^ Ordered List  
      ] -- But this doesn't type check!!!
```

9

Sum Types

- Solution: construct a new type for paragraphs that is a *sum* (*one-of*) the three options!
 - plain text (`String`)
 - heading: level and text (`Int` and `String`)
 - list: ordered? and items (`Bool` and `[String]`)
- I want to store all paragraphs in a *list*

```
data Paragraph =  
  Text String      -- 3 constructors,  
  | Heading Int String -- each with different  
  | List Bool [String] -- parameters
```

10

QUIZ

What would GHCi say? *

```
data Paragraph =  
  Text String | Heading Int String | List Bool [String]
```

What would GHCi say to

```
>:t Text "Hey there!"
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. [Paragraph]
- ☐ E. [String]



<http://tiny.cc/cse116-para-ind>

11

QUIZ

What would GHCi say? *

```
data Paragraph =  
  Text String | Heading Int String | List Bool [String]
```

What would GHCi say to

```
>:t Text "Hey there!"
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. [Paragraph]
- ☐ E. [String]



<http://tiny.cc/cse116-para-grp>

12

Constructing datatypes

```
data T =  
  C1 T11 .. T1k  
  | C2 T21 .. T2l  
  | ..  
  | Cn Tn1 .. Tnm
```

T is the new **datatype**

C1 .. Cn are the **constructors** of **T**

A **value** of type **T** is

- *either* **C1** **v1** .. **vk** with **vi** :: **T1i**
- *or* **C2** **v1** .. **vl** with **vi** :: **T2i**
- *or* ...
- *or* **Cn** **v1** .. **vm** with **vi** :: **Tni**

13

Constructing datatypes

You can think of a **T** value as a **box**:

- *either* a box labeled **C1** with values of types **T11** .. **T1k** inside
- *or* a box labeled **C2** with values of types **T21** .. **T2l** inside
- *or* ...
- *or* a box labeled **Cn** with values of types **Tn1** .. **Tnm** inside

Apply a constructor = pack some values into a box (and label it)

- **Text** "Hey there!"
 - put "Hey there!" in a box labeled **Text**
- **Heading 1** "Introduction"
 - put **1** and "Introduction" in a box labeled **Heading**
- Boxes have different labels but same type (**Paragraph**)

14

QUIZ

```
data Paragraph =  
  Text String | Heading Int String | List Bool [String]
```

What would GHCi say to

```
>:t [Heading 1 "Introduction", Text "Hey there!"]
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. [Paragraph]
- ☐ E. [String]



<http://tiny.cc/cse116-adt-ind>

15

QUIZ

What is the type of `*`

```
data Paragraph =  
  Text String | Heading Int String | List Bool [String]
```

What would GHCi say to

```
>:t [Heading 1 "Introduction", Text "Hey there!"]
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. [Paragraph]
- ☐ E. [String]



<http://tiny.cc/cse116-adt-grp>

16

Example: NanoMD

```
data Paragraph =  
  Text String | Heading Int String | List Bool [String]
```

Now I can create a document like so:

```
doc :: [Paragraph]
```

```
doc = [
```

```
  Heading 1 "Notes from 130"
```

```
  , Text "There are two types of languages:"
```

```
  , List True ["purely functional", "purely evil"]
```

```
]
```

17

Example: NanoMD

Now I want convert documents in to HTML.

I need to write a function:

```
html :: Paragraph -> String
```

```
html p = ??? -- depends on the kind of  
paragraph!
```

How to tell what's in the box?

- Look at the label!

18

Pattern Matching

Pattern matching = looking at the label and extracting values from the box

- we've seen it before
- but now for arbitrary datatypes

```
html :: Paragraph -> String
html (Text str)      = ...
  -- It's a plain text! Get string
html (Heading lvl str) = ...
  -- It's a heading! Get level and string
html (List ord items) = ...
  -- It's a list! Get ordered and items
```

19

Dangers of pattern matching (1)

```
html :: Paragraph -> String
html (Text str) = ...
html (List ord items) = ...
```

What would GHCi say to:

```
html (Heading 1 "Introduction")
```

Answer: Runtime error (no matching pattern)

20

Dangers of pattern matching (1)

Beware of **missing** and **overlapped** patterns

- GHC warns you about *overlapped* patterns
- GHC warns you about *missing* patterns when called with `-W` (use `:set -W` in GHCi)

21

Pattern matching expression

We've seen: pattern matching in *equations*

You can also pattern-match *inside your program* using the **case** expression:

```
html :: Paragraph -> String
html p =
  case p of
    Text str -> unlines [open "p", str, close "p"]
    Heading lvl str -> ...
    List ord items -> ...
```

22

QUIZ

What is the type of *****

```
let p = Text "Hey there!"
in case p of
  Text str -> str
  Heading lvl _ -> lvl
  List ord _ -> ord
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. String
- ☐ D. Paragraph
- ☐ E. Paragraph -> String



<http://tiny.cc/cse116-case-ind>

23

QUIZ

What is the type of *****

```
let p = Text "Hey there!"
in case p of
  Text str -> str
  Heading lvl _ -> lvl
  List ord _ -> ord
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. String
- ☐ D. Paragraph
- ☐ E. Paragraph -> String



<http://tiny.cc/cse116-case-grp>

24

Pattern matching expression: typing

The **case** expression

```
case e of
  pattern1 -> e1
  pattern2 -> e2
  ...
  patternN -> eN
```

has type **T** if

- each $e_1 \dots e_N$ has type **T**
- e has some type **D**
- each $\text{pattern}_1 \dots \text{pattern}_N$ is a *valid pattern* for **D**
 - i.e. a variable or a constructor of **D** applied to other patterns

The expression e is called the *match scrutinee*

25

QUIZ

What is the type of *****

```
let p = Text "Hey there!"
in case p of
  Text _ -> 1
  Heading _ _ -> 2
  List _ _ -> 3
```



<http://tiny.cc/cse116-case2-ind>

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. Int
- ☐ E. Paragraph -> Int

26

QUIZ

What is the type of *****

```
let p = Text "Hey there!"
in case p of
  Text _ -> 1
  Heading _ _ -> 2
  List _ _ -> 3
```



<http://tiny.cc/cse116-case2-grp>

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. Paragraph
- ☐ D. Int
- ☐ E. Paragraph -> Int

27

Building data types

- Three key ways to build complex types/values:
 1. **Product types (each-of)**: a value of **T** contains a value of **T1** *and* a value of **T2** **[done]**
 2. **Sum types (one-of)**: a value of **T** contains a value of **T1** *or* a value of **T2** **[done]**
 3. **Recursive types**: a value of **T** contains a *sub-value* of the same type **Ts**

28

Recursive types

Let's define **natural numbers** from scratch:

```
data Nat = ???
```

29

Recursive types

```
data Nat = Zero | Succ Nat
```

A **Nat** value is:

- either an *empty* box labeled **Zero**
- or a box labeled **Succ** with another **Nat** in it!

Some **Nat** values:

```
Zero           -- 0
Succ Zero      -- 1
Succ (Succ Zero) -- 2
Succ (Succ (Succ Zero)) -- 3
...
```

30

Functions on recursive types

Principle: Recursive code mirrors recursive data

31

1. Recursive type as a parameter

```
data Nat = Zero      -- base constructor
         | Succ Nat  -- inductive constructor
```

Step 1: add a pattern per constructor

```
toInt :: Nat -> Int
toInt Zero      = ... -- base case
toInt (Succ n) = ... -- inductive case
                  -- (recursive call goes here)
```

32

1. Recursive type as a parameter

```
data Nat = Zero      -- base constructor
         | Succ Nat  -- inductive constructor
```

Step 2: fill in base case

```
toInt :: Nat -> Int
toInt Zero      = 0    -- base case
toInt (Succ n) = ...  -- inductive case
                  -- (recursive call goes here)
```

33

1. Recursive type as a parameter

```
data Nat = Zero      -- base constructor
         | Succ Nat -- inductive constructor
```

Step 3: fill in inductive case using a recursive call:

```
toInt :: Nat -> Int
toInt Zero      = 0      -- base case
toInt (Succ n) = 1 + toInt n -- inductive case
```

34

QUIZ

What does this evaluate to? *

```
let foo i = if i <= 0 then Zero else Succ (foo (i - 1))
in foo 2
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. 2
- ☐ D. Succ Zero
- ☐ E. Succ (Succ Zero)



<http://tiny.cc/cse116-rectype-ind>

35

QUIZ

What does this evaluate to? *

```
let foo i = if i <= 0 then Zero else Succ (foo (i - 1))
in foo 2
```

- ☐ A. Syntax error
- ☐ B. Type error
- ☐ C. 2
- ☐ D. Succ Zero
- ☐ E. Succ (Succ Zero)



<http://tiny.cc/cse116-rectype-grp>

36

2. Recursive type as a result

```
data Nat = Zero      -- base constructor
          | Succ Nat -- inductive constructor

fromInt :: Int -> Nat
fromInt n
  | n <= 0  = Zero      -- base case
  | otherwise = Succ (fromInt (n - 1)) -- inductive case
```

37

2. Putting the two together

```
data Nat = Zero      -- base constructor
          | Succ Nat -- inductive constructor

add :: Nat -> Nat -> Nat
add Zero m = m      -- base case
add (Succ n) m = Succ (add n m) -- inductive case

sub :: Nat -> Nat -> Nat
sub n Zero = n      -- base case 1
sub Zero _ = Zero    -- base case 2
sub (Succ n) (Succ m) = sub n m -- inductive case
```

38

2. Putting the two together

```
data Nat = Zero      -- base constructor
          | Succ Nat -- inductive constructor

add :: Nat -> Nat -> Nat
add Zero m = m      -- base case
add (Succ n) m = Succ (add n m) -- inductive case

sub :: Nat -> Nat -> Nat
sub n Zero = n      -- base case 1
sub Zero _ = Zero    -- base case 2
sub (Succ n) (Succ m) = sub n m -- inductive case
```

Lessons learned:

- Recursive code mirrors recursive data
- With multiple arguments of a recursive type, which one should I recurse on?
- The name of the game is to pick the right inductive strategy!

39

Lists

Lists aren't built-in! They are an *algebraic data type* like any other:

```
data List = Nil           -- base constructor
          | Cons Int List -- inductive constructor
```

- List [1, 2, 3] is *represented* as Cons 1 (Cons 2 (Cons 3 Nil))
- Built-in list constructors [] and (:) are just fancy syntax for Nil and Cons

Functions on lists follow the same general strategy:

```
length :: List -> Int
length Nil      = 0           -- base case
length (Cons _ xs) = 1 + length xs -- inductive case
```

40

Lists

What is the right *inductive strategy* for appending two lists?

```
append :: List -> List -> List
append ??? ??? = ???
```

41

Lists

What is the right *inductive strategy* for appending two lists?

```
append :: List -> List -> List
append Nil ys = ys
append ??? ??? = ???
```

42

Lists

What is the right *inductive strategy* for appending two lists?

```
append :: List -> List -> List
append Nil ys = ys
append (Cons x xs) ys = Cons x (append xs ys)
```

43

Trees

Lists are *unary trees* with elements stored in the nodes:

```
1 - 2 - 3 - ()
data List = Nil | Cons Int List
```

How do we represent *binary trees* with elements stored in the nodes?

```
1 - 2 - 3 - ()
|   |   \ ()
|   \   \ ()
\ 4 - ()
   \ ()
```

44

QUIZ

What is a Haskell datatype for binary trees with elements stored in the nodes? *

```
1 - 2 - 3 - ()
|   |   \ ()
|   \   \ ()
\ 4 - ()
   \ ()
```



- (A) `data Tree = Leaf | Node Int Tree`
- (B) `data Tree = Leaf | Node Tree Tree`
- (C) `data Tree = Leaf | Node Int Tree Tree` <http://tiny.cc/cse116-tree-ind>
- (D) `data Tree = Leaf Int | Node Tree Tree`
- (E) `data Tree = Leaf Int | Node Int Tree Tree`

45

QUIZ

What is a Haskell datatype for binary trees with elements stored in the nodes? *

```
1 - 2 - 3 - ()
|   |   \ ()
|   \ ()
\ 4 - ()
   \ ()
```



- (A) `data Tree = Leaf | Node Int Tree`
(B) `data Tree = Leaf | Node Tree Tree`
(C) `data Tree = Leaf | Node Int Tree Tree` <http://tiny.cc/cse116-tree-grp>
(D) `data Tree = Leaf Int | Node Tree Tree`
(E) `data Tree = Leaf Int | Node Int Tree Tree`

46

Trees

```
1 - 2 - 3 - ()
|   |   \ ()
|   \ ()
\ 4 - ()
   \ ()
```

```
data Tree = Leaf | Node Int Tree Tree
```

```
t1234 = Node 1
      (Node 2 (Node 3 Leaf Leaf) Leaf)
      (Node 4 Leaf Leaf)
```

47

Functions on trees

```
depth :: Tree -> Int
depth Leaf = 0
depth (Node _ l r) = 1 + max (depth l) (depth r)
```

48

QUIZ

What is a Haskell datatype for binary trees with elements stored in the leaves? *

```
() - () - () - 1
 |   |   \ 2
 |   \ 3
 \ () - 4
      \ 5
```



- (A) `data Tree = Leaf | Node Int Tree`
(B) `data Tree = Leaf | Node Tree Tree`
(C) `data Tree = Leaf | Node Int Tree Tree`
(D) `data Tree = Leaf Int | Node Tree Tree`
(E) `data Tree = Leaf Int | Node Int Tree Tree`

<http://tiny.cc/cse116-leaves-ind>

49

QUIZ

What is a Haskell datatype for binary trees with elements stored in the leaves? *

```
() - () - () - 1
 |   |   \ 2
 |   \ 3
 \ () - 4
      \ 5
```



- (A) `data Tree = Leaf | Node Int Tree`
(B) `data Tree = Leaf | Node Tree Tree`
(C) `data Tree = Leaf | Node Int Tree Tree`
(D) `data Tree = Leaf Int | Node Tree Tree`
(E) `data Tree = Leaf Int | Node Int Tree Tree`

<http://tiny.cc/cse116-leaves-grp>

50

Binary trees

```
() - () - () - 1
 |   |   \ 2
 |   \ 3
 \ () - 4
      \ 5
```

```
data Tree = Leaf Int | Node Tree Tree
```

```
t12345 = Node
```

```
  (Node (Node (Leaf 1) (Leaf 2)) (Leaf 3))
  (Node (Leaf 4) (Leaf 5))
```

51

Example: Calculator

I want to implement an arithmetic calculator to evaluate expressions like:

- $4.0 + 2.9$
- $3.78 - 5.92$
- $(4.0 + 2.9) * (3.78 - 5.92)$

What is a Haskell datatype to *represent* these expressions?

```
data Expr = ???
```

52

Example: Calculator

```
data Expr = Num Float
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

How do we write a function to *evaluate* an expression?

```
eval :: Expr -> Float
```

53

Example: Calculator

```
data Expr = Num Float
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

How do we write a function to *evaluate* an expression?

```
eval :: Expr -> Float
eval (Num f)    = f
```

54

Example: Calculator

```
data Expr = Num Float
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

How do we write a function to *evaluate* an expression?

```
eval :: Expr -> Float
eval (Num f)      = f
eval (Add e1 e2) = eval e1 + eval e2
```

55

Example: Calculator

```
data Expr = Num Float
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

How do we write a function to *evaluate* an expression?

```
eval :: Expr -> Float
eval (Num f)      = f
eval (Add e1 e2) = eval e1 + eval e2
eval (Sub e1 e2) = eval e1 - eval e2
```

56

Example: Calculator

```
data Expr = Num Float
          | Add Expr Expr
          | Sub Expr Expr
          | Mul Expr Expr
```

How do we write a function to *evaluate* an expression?

```
eval :: Expr -> Float
eval (Num f)      = f
eval (Add e1 e2) = eval e1 + eval e2
eval (Sub e1 e2) = eval e1 - eval e2
eval (Mul e1 e2) = eval e1 * eval e2
```

57

Recursion is...

Building solutions for *big problems* from solutions for *sub-problems*

- **Base case:** what is the *simplest version* of this problem and how do I solve it?
- **Inductive strategy:** how do I *break down* this problem into sub-problems?
- **Inductive case:** how do I solve the problem *given* the solutions for subproblems?

58

Why use Recursion?

1. Often far simpler and cleaner than loops
 - But not always...
2. Structure often forced by recursive data
3. Forces you to factor code into reusable units (recursive functions)

59

Why *not* use Recursion?

1. Slow
2. Can cause stack overflow

60

Example: factorial

```
fac :: Int -> Int
fac n
  | n <= 1  = 1
  | otherwise = n * fac (n - 1)

<fac 4>
==> <4 * <fac 3>>          -- recursively call `fact 3`
==> <4 * <3 * <fac 2>>>      -- recursively call `fact 2`
==> <4 * <3 * <2 * <fac 1>>>> -- recursively call `fact 1`
==> <4 * <3 * <2 * 1>>>     -- multiply 2 to result
==> <4 * <3 * 2>>          -- multiply 3 to result
==> <4 * 6>               -- multiply 4 to result
==> 24
```

61

Example: factorial

```
<fac 4>
==> <4 * <fac 3>>          -- recursively call `fact 3`
==> <4 * <3 * <fac 2>>>      -- recursively call `fact 2`
==> <4 * <3 * <2 * <fac 1>>>> -- recursively call `fact 1`
==> <4 * <3 * <2 * 1>>>     -- multiply 2 to result
==> <4 * <3 * 2>>          -- multiply 3 to result
==> <4 * 6>               -- multiply 4 to result
==> 24
```

Each *function call* <> allocates a frame on the *call stack*

- expensive
- the stack has a finite size

Can we do recursion without allocating stack frames?

62

Tail recursion

Recursive call is the *top-most* sub-expression in the function body

- i.e. no computations allowed on recursively returned value
- i.e. value returned by the recursive call == value returned by function

63

QUIZ

Is this function tail recursive? *

```
fac :: Int -> Int
fac n
  | n <= 1    = 1
  | otherwise = n * fac (n - 1)
```

- ☐ (A) Yes
- ☐ (B) No



<http://tiny.cc/cse116-tail-ind>

64

QUIZ

Is this function tail recursive? *

```
fac :: Int -> Int
fac n
  | n <= 1    = 1
  | otherwise = n * fac (n - 1)
```

- ☐ (A) Yes
- ☐ (B) No



<http://tiny.cc/cse116-tail-grp>

65

Tail recursive factorial

Let's write a tail-recursive factorial!

```
facTR :: Int -> Int
facTR n = loop 1 n
  where
    loop :: Int -> Int -> Int
    loop acc n
      | n <= 1    = acc
      | otherwise = loop (acc * n) (n - 1)
```

66

Tail recursive factorial

```
loop acc n
| n <= 1    = acc
| otherwise = loop (acc * n) (n - 1)

<facTR 4>
==>    <<loop 1 4>> -- call loop 1 4
==>    <<<loop 4 3>>> -- rec call loop 4 3
==>    <<<<loop 12 2>>>> -- rec call loop 12 2
==>    <<<<<loop 24 1>>>>> -- rec call loop 24 1
==>    24                -- return result 24!
```

Each recursive call **directly** returns the result

- without further computation
- no need to remember what to do next!
- no need to store the “empty” stack frames!

67

Tail recursive factorial

Because the *compiler* can transform it into a *fast loop*

```
facTR n = loop 1 n
  where
    loop acc n
    | n <= 1    = acc
    | otherwise = loop (acc * n) (n - 1)

function facTR(n){
  var acc = 1;
  while (true) {
    if (n <= 1) { return acc ; }
    else      { acc = acc * n; n = n - 1; }
  }
}
```

68

Tail recursive factorial

```
function facTR(n){
  var acc = 1;
  while (true) {
    if (n <= 1) { return acc ; }
    else      { acc = acc * n; n = n - 1; }
  }
}
```

- Tail recursive calls can be optimized as a **loop**
 - no stack frames needed!
- Part of the language specification of most functional languages
 - compiler **guarantees** to optimize tail calls

69

That's all folks!
