

CSE 116: Fall 2019

# Introduction to Functional Programming

## *Higher-Order Functions*

Owen Arden

UC Santa Cruz

*Based on course materials developed by Nadia Polikarpova*

# Plan for this week

---

## Last week:

- user-defined *data types*
  - and how to manipulate them using *pattern matching* and *recursion*
- how to make recursive functions more efficient with *tail recursion*

## This week:

- code reuse with *higher-order functions* (HOFs)
- some useful HOFs: `map`, `filter`, and `fold`

# Recursion is good

---

- Recursive code mirrors recursive data
  - Base constructor -> Base case
  - Inductive constructor -> Inductive case (with recursive call)
- But it can get kinda repetitive!

# Example: evens

---

Let's write a function evens:

```
-- evens [] ==> []  
-- evens [1,2,3,4] ==> [2,4]  
evens      :: [Int] -> [Int]  
evens []   = ...  
evens (x:xs) = ...
```

# Example: four-letter words

---

Let's write a function `fourChars`:

```
-- fourChars [] ==> []  
-- fourChars ["i", "must", "do", "work"] ==> ["must", "work"]  
fourChars :: [String] -> [String]  
fourChars []      = ...  
fourChars (x:xs) = ...
```

# Yikes, Most Code is the Same!

---

```
foo [] = []  
foo (x:xs)  
  | x mod 2 == 0 = x : foo xs  
  | otherwise   =      foo xs
```

```
foo [] = []  
foo (x:xs)  
  | length x == 4 = x : foo xs  
  | otherwise     =      foo xs
```

Only difference is **condition**

- `x mod 2 == 0` vs `length x == 4`

# Moral of the day

---

**D.R.Y. Don't Repeat Yourself!**

Can we

- *reuse* the general pattern and
- *substitute in* the custom condition?

# HOFs to the rescue!

---

## General Pattern

- expressed as a *higher-order function*
- takes customizable operations as *arguments*

## Specific Operation

- passed in as an argument to the HOF



# The “filter” pattern

---

```
evens [] = []  
evens (x:xs)  
  | x `mod` 2 == 0 = x : evens xs  
  | otherwise     =     evens xs
```

```
fourChars [] = []  
fourChars (x:xs)  
  | length x == 4 = x : fourChars xs  
  | otherwise     =     fourChars xs
```

```
filter f [] = []  
filter f (x:xs)  
  | f x = x : filter f xs  
  | otherwise =     filter f xs
```

Use the **filter** pattern  
to avoid duplicating code!

# The “filter” pattern

---

## General Pattern

- HOF filter
- Recursively traverse list and pick out elements that satisfy a predicate

## Specific Operation

- Predicates `isEven` and `isFour`

```
filter f []      = []  
filter f (x:xs)  =  
  | f x          = x : filter f xs  
  | otherwise    =      filter f xs
```

```
evens      = filter isEven  
  where  
    isEven x = x `mod` 2 == 0
```

```
fourChars  = filter isFour  
  where  
    isFour x = length x == 4
```

# Let's talk about types

---

```
-- evens [1,2,3,4] ==> [2,4]
evens :: [Int] -> [Int]
evens xs = filter isEven xs
  where
    isEven :: Int -> Bool
    isEven x = x `mod` 2 == 0
filter :: ???
```

# Let's talk about types

---

```
-- evens [1,2,3,4] ==> [2,4]
evens :: [Int] -> [Int]
evens xs = filter isEven xs
  where
    isEven :: Int -> Bool
    isEven x = x `mod` 2 == 0
filter :: ???
```

# Let's talk about types

---

```
-- fourChars ["i","must","do","work"] ==> ["must","work"]
fourChars :: [String] -> [String]
fourChars xs = filter isFour xs
  where
    isFour :: String -> Bool
    isFour x = length x == 4
filter :: ???
```

# Let's talk about types

---

Uh oh! So what's the type of `filter`?

```
filter :: (Int -> Bool) -> [Int] -> [Int] -- ???
```

```
filter :: (String -> Bool) -> [String] -> [String] -- ???
```

- It *does not care* what the list elements are
  - as long as the predicate can handle them
- It's type is **polymorphic** (generic) in the type of list elements

```
-- For any type `a`
```

```
--   if you give me a predicate on `a`s
```

```
--   and a list of `a`s,
```

```
--   I'll give you back a list of `a`s
```

```
filter :: (a -> Bool) -> [a] -> [a]
```

# Example: all caps

---

Lets write a function shout:

```
-- shout [] ==> []  
-- shout ['h','e','l','l','o'] ==> ['H','E','L','L','O']  
shout :: [Char] -> [Char]  
shout [] = ...  
shout (x:xs) = ...
```

# Example: squares

---

Lets write a function squares:

```
-- squares []          ==> []  
-- squares [1,2,3,4] ==> [1,4,9,16]  
squares :: [Int] -> [Int]  
squares []          = ...  
squares (x:xs)      = ...
```



# Yikes, Most Code is the Same!

---

Lets rename the functions to foo:

```
-- shout
```

```
foo [] = []
```

```
foo (x:xs) = toUpper x : foo xs
```

```
-- squares
```

```
foo [] = []
```

```
foo (x:xs) = (x * x) : foo xs
```

Lets refactor into the common pattern

```
pattern = ...
```

# The “map” pattern

---

```
shout [] = []  
shout (x:xs) = toUpper x : shout xs
```

```
squares [] = []  
squares (x:xs) = (x*x) : squares xs
```

```
map f [] = []  
map f (x:xs) = f x : map f xs
```

The map Pattern

## General Pattern

- HOF map
- Apply a transformation  $f$  to each element of a list

## Specific Operations

- Transformations `toUpper` and  $\backslash x \rightarrow x * x$

# The “map” pattern

---

```
map f [] = []
```

```
map f (x:xs) = f x : map f xs
```

Lets refactor shout and squares

```
shout = map ...
```

```
squares = map ...
```

```
map f [] = []  
map f (x:xs) = f x : map f xs
```

```
shout = map (\x -> toUpper x)
```

```
squares = map (\x -> x*x)
```

# QUIZ

---

What is the type of map? \*

```
map f []      = []  
map f (x:xs) = f x : map f xs
```

- (A) (Char -> Char) -> [Char] -> [Char]
- (B) (Int -> Int) -> [Int] -> [Int]
- (C) (a -> a) -> [a] -> [a]
- (D) (a -> b) -> [a] -> [b]
- (E) (a -> b) -> [c] -> [d]



<http://tiny.cc/cse116-map-ind>

# QUIZ

---

What is the type of map? \*

```
map f []      = []  
map f (x:xs) = f x : map f xs
```

- (A) (Char -> Char) -> [Char] -> [Char]
- (B) (Int -> Int) -> [Int] -> [Int]
- (C) (a -> a) -> [a] -> [a]
- (D) (a -> b) -> [a] -> [b]
- (E) (a -> b) -> [c] -> [d]



<http://tiny.cc/cse116-map-grp>

# The “map” pattern

---

```
-- For any types `a` and `b`  
--   if you give me a transformation from `a` to `b`  
--   and a list of `a`s,  
--   I'll give you back a list of `b`s  
map :: (a -> b) -> [a] -> [b]
```

## Type says it all!

- The only meaningful thing a function of this type can do is apply its first argument to elements of the list (Hooogle it!)

## Things to try at home:

- can you write a function `map' :: (a -> b) -> [a] -> [b]` whose behavior is different from `map`?
- can you write a function `map' :: (a -> b) -> [a] -> [b]` such that `map' f xs` returns a list whose elements are not in `map f xs`?

# QUIZ

---

What is the value of quiz? \*

```
map :: (a -> b) -> [a] -> [b]
```

```
quiz = map (\(x, y) -> x + y) [1, 2, 3]
```

- ☐ (A) [2, 4, 6]
- ☐ (B) [3, 5]
- ☐ (C) Syntax Error
- ☐ (D) Type Error
- ☐ (E) None of the above



<http://tiny.cc/cse116-quiz-ind>

# QUIZ

---

What is the value of quiz? \*

```
map :: (a -> b) -> [a] -> [b]
```

```
quiz = map (\(x, y) -> x + y) [1, 2, 3]
```

- ☐ (A) [2, 4, 6]
- ☐ (B) [3, 5]
- ☐ (C) Syntax Error
- ☐ (D) Type Error
- ☐ (E) None of the above



<http://tiny.cc/cse116-quiz-grp>



# Don't Repeat Yourself

---

Benefits of **factoring** code with HOFs:

- Reuse iteration pattern
  - think in terms of standard patterns
  - less to write
  - easier to communicate
- Avoid bugs due to repetition

# Recall: length of a list

---

```
-- len []          ==> 0
-- len ["carne","asada"] ==> 2
len :: [a] -> Int
len []          = 0
len (x:xs)     = 1 + len xs
```

# Recall: summing a list

---

```
-- sum [] ==> 0
-- sum [1,2,3] ==> 6
sum :: [Int] -> Int
sum [] = 0
sum (x:xs) = x + sum xs
```

# Example: string concatenation

---

Let's write a function `cat`:

```
-- cat [] ==> ""  
-- cat ["carne", "asada", "torta"] ==> "carneasadatorta"  
cat :: [String] -> String  
cat []      = ...  
cat (x:xs)  = ...
```

# Can you spot the pattern?

---

-- *len*

foo [] = 0

foo (x:xs) = 1 + foo xs

-- *sum*

foo [] = 0

foo (x:xs) = x + foo xs

-- *cat*

foo [] = ""

foo (x:xs) = x ++ foo xs

pattern = ...

# The “fold-right” pattern

---

```
len []      = 0
len (x:xs) = 1 + len xs
```

```
sum []      = 0
sum (x:xs) = x + sum xs
```

```
cat []      = ""
cat (x:xs) = x ++ sum xs
```

```
foldr f b []      = b
foldr f b (x:xs) = f x (foldr f b xs)
```

The foldr Pattern

## General Pattern

- Recurse on tail
- Combine result with the head using some binary operation

# The “fold-right” pattern

---

```
foldr f b []      = b
foldr f b (x:xs) = f x (foldr f b xs)
```

Let's refactor sum, len and cat:

```
sum = foldr ... ..
```

```
cat = foldr ... ..
```

```
len = foldr ... ..
```

Factor the recursion out!

# The “fold-right” pattern

---

```
foldr f b []      = b  
foldr f b (x:xs) = f x (foldr f b xs)
```

```
len = foldr (\x n -> 1 + n) 0
```

```
sum = foldr (\x n -> x + n) 0
```

```
cat = foldr (\x s -> x ++ s) ""
```

You can write it more clearly as

```
sum = foldr (+) 0
```

```
cat = foldr (++) ""
```



# The “fold-right” pattern

---

```
foldr f b []      = b  
foldr f b (x:xs) = f x (foldr f b xs)
```

```
len = foldr (\x n -> 1 + n) 0
```

```
sum = foldr (\x n -> x + n) 0
```

```
cat = foldr (\x s -> x ++ s) ""
```

You can write it more clearly as

```
sum = foldr (+) 0
```

```
cat = foldr (++) ""
```

# QUIZ

---

What does this evaluate to? \*

```
foldr f b []      = b
foldr f b (x:xs) = f x (foldr f b xs)
```

```
quiz = foldr (:) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☐ (E) [[1],[2],[3]]



<http://tiny.cc/cse116-foldeval-ind>

# QUIZ

---

What does this evaluate to? \*

```
foldr f b []      = b
foldr f b (x:xs) = f x (foldr f b xs)
```

```
quiz = foldr (:) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☐ (E) [[1],[2],[3]]



<http://tiny.cc/cse116-foldeval-grp>

# The “fold-right” pattern

---

```
foldr f b [] = b
```

```
foldr f b (x:xs) = f x (foldr f b xs)
```

```
foldr (:) [] [1,2,3]
```

```
==> (:) 1 (foldr (:) [] [2, 3])
```

```
==> (:) 1 ((:) 2 (foldr (:) [] [3]))
```

```
==> (:) 1 ((:) 2 ((:) 3 (foldr (:) [] [])))
```

```
==> (:) 1 ((:) 2 ((:) 3 []))
```

```
== 1 : (2 : (3 : []))
```

```
== [1,2,3]
```

# The “fold-right” pattern

---

```
foldr f b [x1, x2, x3, x4]
==> f x1 (foldr f b [x2, x3, x4])
==> f x1 (f x2 (foldr f b [x3, x4]))
==> f x1 (f x2 (f x3 (foldr f b [x4])))
==> f x1 (f x2 (f x3 (f x4 (foldr f b []))))
==> f x1 (f x2 (f x3 (f x4 b)))
```

Accumulate the values from the **right**

For example:

```
foldr (+) 0 [1, 2, 3, 4]
==> 1 + (foldr (+) 1 [2, 3, 4])
==> 1 + (2 + (foldr (+) 0 [3, 4]))
==> 1 + (2 + (3 + (foldr (+) 0 [4])))
==> 1 + (2 + (3 + (4 + (foldr (+) 0 []))))
==> 1 + (2 + (3 + (4 + 0)))
```

# QUIZ

---

What is the most general type of foldr? \*

`foldr f b [] = b`

`foldr f b (x:xs) = f x (foldr f b xs)`

- ☐ (A)  $(a \rightarrow a \rightarrow a) \rightarrow a \rightarrow [a] \rightarrow a$
- ☐ (B)  $(a \rightarrow a \rightarrow b) \rightarrow a \rightarrow [a] \rightarrow b$
- ☐ (C)  $(a \rightarrow b \rightarrow a) \rightarrow b \rightarrow [a] \rightarrow b$
- ☐ (D)  $(a \rightarrow b \rightarrow b) \rightarrow b \rightarrow [a] \rightarrow b$
- ☐ (E)  $(b \rightarrow a \rightarrow b) \rightarrow b \rightarrow [a] \rightarrow b$



<http://tiny.cc/cse116-foldtype-ind>

# QUIZ

---

What is the most general type of foldr? \*

`foldr f b [] = b`

`foldr f b (x:xs) = f x (foldr f b xs)`

- ☐ (A)  $(a \rightarrow a \rightarrow a) \rightarrow a \rightarrow [a] \rightarrow a$
- ☐ (B)  $(a \rightarrow a \rightarrow b) \rightarrow a \rightarrow [a] \rightarrow b$
- ☐ (C)  $(a \rightarrow b \rightarrow a) \rightarrow b \rightarrow [a] \rightarrow b$
- ☐ (D)  $(a \rightarrow b \rightarrow b) \rightarrow b \rightarrow [a] \rightarrow b$
- ☐ (E)  $(b \rightarrow a \rightarrow b) \rightarrow b \rightarrow [a] \rightarrow b$



<http://tiny.cc/cse116-foldtype-grp>

# The “fold-right” pattern

---

Is `foldr` tail recursive?

*Answer:* No! It calls the binary operations on the results of the recursive call



# What about tail-recursive versions?

---

Let's write tail-recursive sum!

```
sumTR :: [Int] -> Int
```

```
sumTR = ...
```

# What about tail-recursive versions?

---

Let's write tail-recursive sum!

```
sumTR :: [Int] -> Int
```

```
sumTR xs = helper 0 xs
```

```
  where
```

```
    helper acc []      = acc
```

```
    helper acc (x:xs) = helper (acc + x) xs
```

# What about tail-recursive versions?

---

Lets run sumTR to see how it works

```
sumTR [1,2,3]
==> helper 0 [1,2,3]
==> helper 1 [2,3]    -- 0 + 1 ==> 1
==> helper 3 [3]      -- 1 + 2 ==> 3
==> helper 6 []       -- 3 + 3 ==> 6
==> 6
```

**Note:** helper directly returns the result of recursive call!

# What about tail-recursive versions?

---

Let's write tail-recursive cat!

```
catTR :: [String] -> String
```

```
catTR = ...
```

# What about tail-recursive versions?

---

Let's write tail-recursive cat!

```
catTR :: [String] -> String
catTR xs = helper "" xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (acc ++ x) xs
```

# What about tail-recursive versions?

---

Lets run catTR to see how it works

```
catTR                                ["carne", "asada", "torta"]
==> helper ""                        ["carne", "asada", "torta"]
==> helper "carne"                    ["asada", "torta"]
==> helper "carneasada"                ["torta"]
==> helper "carneasadatorta"          []
==> "carneasadatorta"
```

**Note:** helper directly returns the result of recursive call!

# Can you spot the pattern?

---

*-- sumTR*

```
foo xs = helper 0 xs
  where
    helper acc [] = acc
    helper acc (x:xs) = helper (acc + x) xs
```

*-- catTR*

```
foo xs = helper "" xs
  where
    helper acc [] = acc
    helper acc (x:xs) = helper (acc ++ x) xs
```

pattern = ...

# The “fold-left” pattern

```
sum xs          = helper 0 xs
  where
    helper acc [] = acc
    helper acc (x:xs) = helper (acc + x) xs
```

```
cat xs          = helper "" xs
  where
    helper acc [] = acc
    helper acc (x:xs) = helper (acc ++ x) xs
```

```
foldl f b xs    = helper b xs
  where
    helper acc [] = acc
    helper acc (x:xs) = helper (f acc x) xs
```

## The foldl Pattern

### General Pattern

- Use a helper function with an extra accumulator argument
- To compute new accumulator, combine current accumulator with the head using some binary operation



# The “fold-left” pattern

---

```
foldl f b xs          = helper b xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (f acc x) xs
```

Let’s refactor sumTR and catTR:

```
sumTR = foldl ... ..
```

```
catTR = foldl ... ..
```

Factor the tail-recursion out!

# QUIZ

---

What does this evaluate to? \*

```
foldl f b xs          = helper b xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (f acc x) xs
```

```
quiz = foldl (:) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☐ (E) [[1],[2],[3]]



<http://tiny.cc/cse116-foldl-ind>

# QUIZ

---

What does this evaluate to? \*

```
foldl f b xs          = helper b xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (f acc x) xs
```

```
quiz = foldl (:) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☐ (E) [[1],[2],[3]]



<http://tiny.cc/cse116-foldl-grp>

# QUIZ

---

What does this evaluate to? \*

```
foldl f b xs          = helper b xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (f acc x) xs
```

```
quiz = foldl (\xs x -> x : xs) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☒ (E) [[1],[2],[3]]



# QUIZ

---

What does this evaluate to? \*

```
foldl f b xs          = helper b xs
  where
    helper acc []      = acc
    helper acc (x:xs) = helper (f acc x) xs
```

```
quiz = foldl (\xs x -> x : xs) [] [1,2,3]
```

- ☐ (A) Type error
- ☐ (B) [1,2,3]
- ☐ (C) [3,2,1]
- ☐ (D) [[3],[2],[1]]
- ☐ (E) [[1],[2],[3]]



# The “fold-left” pattern

---

```
foldl f b                [x1, x2, x3, x4]
==> helper b             [x1, x2, x3, x4]
==> helper (f b x1)       [x2, x3, x4]
==> helper (f (f b x1) x2) [x3, x4]
==> helper (f (f (f b x1) x2) x3) [x4]
==> helper (f (f (f (f b x1) x2) x3) x4) []
==> (f (f (f (f b x1) x2) x3) x4)
```

Accumulate the values from the **left**

For example:

```
foldl (+) 0              [1, 2, 3, 4]
==> helper 0              [1, 2, 3, 4]
==> helper (0 + 1)         [2, 3, 4]
==> helper ((0 + 1) + 2)    [3, 4]
==> helper (((0 + 1) + 2) + 3) [4]
==> helper ((((0 + 1) + 2) + 3) + 4) []
==> (((((0 + 1) + 2) + 3) + 4)
```

# Left vs. Right

---

`foldl f b [x1, x2, x3] ==> f (f (f b x1) x2) x3 -- Left`

`foldr f b [x1, x2, x3] ==> f x1 (f x2 (f x3 b)) -- Right`

For example:

`foldl (+) 0 [1, 2, 3] ==> ((0 + 1) + 2) + 3 -- Left`

`foldr (+) 0 [1, 2, 3] ==> 1 + (2 + (3 + 0)) -- Right`

Different types!

`foldl :: (b -> a -> b) -> b -> [a] -> b -- Left`

`foldr :: (a -> b -> b) -> b -> [a] -> b -- Right`

# Useful HOF: flip

---

*-- you can write*

```
foldl (\xs x -> x : xs) [] [1,2,3]
```

*-- more concisely like so:*

```
foldl (flip (:)) [] [1,2,3]
```

What is the type of flip?

```
flip :: (a -> b -> c) -> b -> a -> c
```



# Useful HOF: compose

---

*-- you can write*

```
map (\x -> f (g x)) ys
```

*-- more concisely like so:*

```
map (f . g) ys
```

What is the type of `(.)`?

```
(.) :: (b -> c) -> (a -> b) -> a -> c
```

# Higher Order Functions

---

Iteration patterns over collections:

- **Filter** values in a collection given a *predicate*
- **Map** (iterate) a given *transformation* over a collection
- **Fold** (reduce) a collection into a value, given a *binary operation* to combine results

Useful helper HOFs:

- **Flip** the order of function's (first two) arguments
- **Compose** two functions

# Higher Order Functions

---

HOFs can be put into libraries to enable modularity

- Data structure **library** implements `map`, `filter`, `fold` for its collections
  - generic efficient implementation
  - generic optimizations: `map f (map g xs) --> map (f.g) xs`
- Data structure **clients** use HOFs with specific operations
  - no need to know the implementation of the collection

Enabled the “big data” revolution e.g. *MapReduce*, *Spark*

# That's all folks!

---