CSE 114A

Foundations of Programming Languages

Polymorphism and Type Inference

Owen Arden

UC Santa Cruz

Based on course materials developed by Nadia Polikarpova

Roadmap

Past two weeks:

How do we *implement* a tiny functional language?

1. *Interpreter*: how do we *evaluate* a program given its AST?
2. *Parser*: how do we convert strings to ASTs?

This week: adding types

How do we check statically if our programs "make sense"?

1. *Type system:* formalizing the intuition about which expressions have which types
2. *Type inference*: computing the type of an expression

Reminder: Nano2

```
e ::= n | x              -- numbers, vars
    | e1 + e2            -- arithmetic
    | \x -> e            -- abstraction
    | e1 e2              -- application
    | let x = e1 in e2   -- let binding
```

Reminder: Nano2

Which one of these Nano2 programs is well-typed? *

- (A) (\x -> x) + 1
- (B) 1 2
- (C) let f = \x -> x + 1 in f (\y -> y)
- (D) \x -> \y -> x y
- (D) (\y -> 1 + y) (1 + 2) => 1 + 1 + 2
- (E) \x -> x x

http://tiny.cc/cse116-nanotype-ind

Reminder: Nano2

Which one of these Nano2 programs is well-typed? *

- (A) (\x -> x) + 1
- (B) 1 2
- (C) let f = \x -> x + 1 in f (\y -> y)
- (D) \x -> \y -> x y
- (D) (\y -> 1 + y) (1 + 2) => 1 + 1 + 2
- (E) \x -> x x

http://tiny.cc/cse116-nanotype-grp

QUIZ

Answer: **D.**

A adds a function;

B applies a number;

C defines f to take an Int and then passes in a function;

E requires a type T that is equal to T -> T, which doesn't exit.

Type system for Nano2

A **type system** defines what types an expression can have

To define a type system we need to define:

- the *syntax* of types: what do types look like?
- the *static semantics* of our language (i.e. the typing rules): assign types to expressions

Type system: take 1

Syntax of types:

```
T ::= Int        -- integers
    | T1 -> T2   -- function types
```

Now we want to define a *typing relation* e :: T (e has type T)

We define this relation *inductively* through a set of *typing rules*:

```
[T-Num]  n :: Int

         e1 :: Int    e2 :: Int   -- premises
[T-Add]  ---------------------
            e1 + e2 :: Int        -- conclusion

[T-Var]   x :: ???
```

What is the type of a variable?

We have to remember what type of expression it was bound to!

Type Environment

An expression has a type in a given **type environment** (also called **context**), which maps all its *free variables* to their *types*

G = x1:T1, x2:T2, ..., xn:Tn

Our *typing relation* should include the context G:

G |- e :: T (e has type T in context G)

Typing rules: take 2

```
[T-Num]  G |- n :: Int

         G |- e1 :: Int   G |- e2 :: Int
[T-Add]  ------------------------------
             G |- e1 + e2 :: Int

[T-Var]  G |- x :: T          if x:T in G

         G,x:T1 |- e :: T2
[T-Abs] ------------------------
        G |- \x -> e :: T1 -> T2

        G |- e1 :: T1 -> T2   G |- e2 :: T1
[T-App] ----------------------------------
               G |- e1 e2 :: T2

        G |- e1 :: T1   G,x:T1 |- e2 :: T2
[T-Let] ----------------------------------
         G |- let x = e1 in e2 :: T2
```

Typing rules

G |- e :: T

An expression e **has type** T in G if we can derive G |- e :: T using these rules

An expression e is **well-typed** in G if we can derive G |- e :: T for some type T

- and **ill-typed** otherwise

Examples

Example 1:

Let's derive: [] |- (\x -> x) 2 :: Int

```
[T-Var] ------------------
        [x:Int] |- x :: Int
[T-Abs] ------------------          -------------- [T-Num]
        [] |- \x -> x :: Int -> Int    [] |- 2 :: Int
[T-App] ---------------------------------------------
        [] |- (\x -> x) 2 :: Int
```

But we *cannot* derive: [] |- 1 2 :: T for any type T

- Why?
- T-App only applies when LHS has a function type, but there's no rule to derive a function type for 1

Examples

Example 2:

Let's derive: [] |- **let** x = 1 **in** x + 2 :: Int

```
                [T-Var]----------------   ----------------[T-Num]
                      x:Int |- x :: Int   x:Int |- 2 :: Int
[T-Num] --------------   ----------------------------------[T-Add]
      [] |- 1 :: Int   x:Int |- x + 2 :: Int
[T-Let] ---------------------------------
      [] |- let x = 1 in x + 2 :: Int
```

But we *cannot* derive: [] |- **let** x = \y -> y **in** x + 2 :: T for any type T

The [T-Var] rule above will fail to derive x :: Int

Examples

Example 3:

We cannot derive: [] |- (\x -> x x) :: T for any type T

We cannot find any type T to fill in for x, because it has to be equal to T -> T

A note about typing rules

According to these rules, an expression can have *zero*, *one*, or *many* types

- examples?

1 2 has no types; 1 has one type (Int)

\x -> x has many types:

- we can derive [] |- \x -> x :: Int -> Int
- or [] |- \x -> x :: (Int -> Int) -> (Int -> Int)
- or T -> T for any concrete T

We would like every well-typed expression to have a single **most general** type!

- most general type = allows most uses
- infer type once and reuse later

QUIZ

Is this program well-typed according to your intuition and according to our rules? *

```
let id = \x -> x in
  let y = id 5 in
    id (\z -> z + y)
```

- (A) Me: okay, rules: okay
- (B) Me: okay, rules: nope
- (C) Me: nope, rules: okay
- (D) Me: nope, rules: nope

http://tiny.cc/cse116-typed-ind

QUIZ

Is this program well-typed according to your intuition and according to our rules? *

```
let id = \x -> x in
  let y = id 5 in
    id (\z -> z + y)
```

- (A) Me: okay, rules: okay
- (B) Me: okay, rules: nope
- (C) Me: nope, rules: okay
- (D) Me: nope, rules: nope

http://tiny.cc/cse116-typed-grp

QUIZ

Answer: **B.**

Double identity

```
let id = \x -> x in
  let y = id 5 in
    id (\z -> z + y)
```

Intuitively this program looks okay, but our type system *rejects* it:

- in the first application, id needs to have type Int -> Int
- in the second application, id needs to have type (Int -> Int) -> (Int -> Int)
- the type system forces us to pick *just one type* for each variable, such as id :(

What can we do?

Polymorphic types

Intuitively, we can describe the type of id like this:

- it's a function type where
- the argument type can be any type T
- the return type is then also T

Polymorphic types

We formalize this intuition as a **polymorphic type**: forall a . a -> a

- where a is a (bound) type variable
- also called a **type scheme**
- Haskell also has polymorphic types, but you don't usually write forall a.

We can **instantiate** this scheme into different types by replacing a in the body with some type, e.g.

- instantiating with Int yields Int -> Int
- instantiating with Int -> Int yields (Int -> Int) -> Int -> Int
- etc.

Inference with polymorphic types

With polymorphic types, we can derive e :: Int -> Int where e is

```
let id = \x -> x in
  let y = id 5 in
    id (\z -> z + y)
```

At a high level, inference works as follows:

1. When we have to pick a type T for x, we pick a **fresh type variable** a
2. So the type of \x -> x comes out as a -> a
3. We can **generalize** this type to forall a . a -> a
4. When we apply id the first time, we **instantiate** this polymorphic type with Int
5. When we apply id the second time, we **instantiate** this polymorphic type with Int ->Int

Let's formalize this intuition as a type system!

Type system: take 3

Syntax of types

```
-- Mono-types
T ::= Int        -- integers
    | T1 -> T2   -- function types
    | a          -- NEW: type variable

-- NEW: Poly-types (type schemes)
S ::= T              -- mono-type
    | forall a . S -- polymorphic type
```

where $a \in TVar$, $T \in Type$, $S \in Poly$

Type Environment

The type environment now maps variables to poly-types: G : Var -> Poly

- example, G = [z: Int, id: forall a . a -> a]

Type system: take 3

Type Substitutions

We need a mechanism for replacing all type variables in a type with another type

A **type substitution** is a finite map from type variables to types: U : TVar -> Type

- example: U1 = [a / Int, b / (c -> c)]

To **apply** a substitution U to a type T means replace all type vars in T with whatever they are mapped to in U

- example 1: U1 (a -> a) = Int -> Int
- example 2: U1 Int = Int

QUIZ

What is the result of the following substitution application? *

```
[a / Int, b / c -> c] (b -> d -> b)
```

- (A) c -> d -> c
- (B) (c -> c) -> d -> (c -> c)
- (C) Error: no mapping for type variable d
- (D) Error: type variable a is unused

http://tiny.cc/cse116-subst-ind

QUIZ

What is the result of the following substitution application? *

```
[a / Int, b / c -> c] (b -> d -> b)
```

- (A) c -> d -> c
- (B) (c -> c) -> d -> (c -> c)
- (C) Error: no mapping for type variable d
- (D) Error: type variable a is unused

http://tiny.cc/cse116-subst-grp

QUIZ

(B) (c -> c) -> d -> (c -> c)

Answer: B

Typing rules

We need to change the typing rules so that:

1. Variables (and their definitions) can have polymorphic types

[T-Var] G |- x :: S **if** x:S **in** G

```
        G |- e1 :: S   G, x:S |- e2 :: T
[T-Let] ------------------------------------
          G |- let x = e1 in e2 :: T
```

Typing rules

2. We can *instantiate* a type scheme into a type

```
        G |- e :: forall a . S
[T-Inst] ----------------------
        G |- e :: [a / T] S
```

3. We can *generalize* a type with free type variables into a type scheme

```
          G |- e :: S
[T-Gen] ---------------------- if not (a in FTV(G))
        G |- e :: forall a . S
```

Typing rules

The rest of the rules are the same:

```
[T-Num]  G |- n :: Int

         G |- e1 :: Int   G |- e2 :: Int
[T-Add]  ------------------------------
             G |- e1 + e2 :: Int

         G, x:T1 |- e :: T2
[T-Abs] ------------------------
       G |- \x -> e :: T1 -> T2

       G |- e1 :: T1 -> T2   G |- e2 :: T1
[T-App] ----------------------------------
              G |- e1 e2 :: T2
```

Examples

Example 1

Let's derive: [] |- \x -> x :: forall a . a -> a

[T-Var] ----------

[x:a] |- x :: a

[T-Abs] ----------

[] |- \x -> x :: a -> a

[T-Gen] ---------- not (a **in** FTV([]))

[] |- \x -> x :: forall a . a -> a

Can we derive: [x:a] |- x :: forall a . a?

No! The side condition of [T-Gen] is violated because a **is present** in the context

Examples

Example 2

Let's derive: G1 |- id 5 :: Int where G1 = [id : (forall a . a -> a)]:

```
[T-Var]------------------------
    G1 |- id :: forall a.a -> a
[T-Inst]-----------------------   --------------[T-Num]
      G1 |- id :: Int -> Int     G1 |- 5 :: Int
[T-App] -------------------------------------
      G1 |- id 5 :: Int
```

Examples

Example 3

Finally, we can derive:

```
(let id = \x -> x in
 let y = id 5 in
   id (\z -> z + y)) :: Int -> Int
```

Examples

```
                                        easy
  [T-Var]-------------------------     ------------------ [Add]
       G2 |- id::forall a.a -> a       G3 |- z + y :: Int
[T-Inst]-----------------------------  -------------------------[T-Abs]
      G2 |- id::(Int->Int)->Int->Int  G2 |- \z -> z+y :: Int->Int
                          |                      |
           example 2      |                      |
         -----------------  ---------------------------------[T-App]
         G1 |- id 5 :: Int   G2 |- id (\z -> z+y) :: Int -> Int
  [T-Let] ---------------------------------------------------
                        G1 |- let y = id 5 in ... :: Int -> Int
                                            |
              example 1                     |
[T-Abs] -------------------------------     |
      [] |- \x -> x :: forall a.a -> a      |
[T-Let] -------------------------------------------------------
      [] |- let id = \x -> x in ... :: Int -> Int
```

- G1 = [id : (forall a . a -> a)]
- G2 = [y : Int, id : (forall a . a -> a)]
- G3 = [z : Int, y : Int, id : (forall a . a -> a)]

Type inference algorithm

Our ultimate goal is to implement a Haskell function infer which

- given a context G and an expression e
- returns a type T such that G |- e :: T
- *or* reports a type error if e is ill-typed in G

Representing types

First, let's define a Haskell datatype to represent Nano2 types:

```
data Type
  = TInt              -- Int
  | Type :=> Type     -- T1 -> T2
  | TVar String       -- a, b, c

data Poly = Mono Type
          | Forall TVar Poly

type TVar = String
type TEnv = [(Id, Poly)]     -- type environment
type Subst = [(String, Type)] -- type substitution
```

Inference: main idea

Let's implement infer like this:

1. Depending on what kind of expression e is, find a typing rule that applies to it
2. If the rule has premises, recursively call infer to obtain the types of sub-expressions
3. Combine the types of sub-expression according to the conclusion of the rule
4. If no rule applies, report a type error

Inference: main idea

```
-- | This is not the final version!!!
infer :: TypeEnv -> Expr -> Type
infer _    (ENum _)     = TInt
infer tEnv (EVar var)   = lookup var tEnv
infer tEnv (EAdd e1 e2) =
  if t1 == TInt && t2 == TInt
    then return TInt
    else throw "type error: + expects Int operands"
  where
    t1 = infer tEnv e1
    t2 = infer tEnv e2
...
```

This doesn't quite work (for other cases). Why?

Inference: tricky bits

The trouble is that our typing rules are *nondeterministic*!

- When building derivations, sometimes we had to *guess* how to proceed

Problem 1: Guessing a type

```
    -- oh, now we know!
[T-Var]---------------
    [x:?] |- x: Int    [x:?] |- 1 :: Int
[T-Add]---------------------------
    [x:?] |- x + 1 :: ?? -- what should "?" be?
[T-Abs]-----------------------------
    [] |- (\x -> x + 1) :: ? -> ??
```

Inference: tricky bits

Problem 1: Guessing a type

So, if we want to implement

```
infer tEnv (ELam x e) = tX :=> tBody
  where
    tEnv'  = extendTEnv x tX tEnv
    tX     = ??? -- what do we put here?
    tBody  = infer tEnv' e
...
```

Inference: tricky bits

Problem 2: Guessing when to generalize

In the derivation for

```
(let id = \x -> x in
 let y = id 5 in
   id (\z -> z + y)) :: Int -> Int
```

we had to *guess* that the type of id should be generalized into

```
forall a . a -> a
```

Let's deal with problem 1 first

Constraint-based type inference

```
    -- oh, now we know!
[T-Var]----------------
    [x:?] |- x: Int    [x:?] |- 1 :: Int
[T-Add]----------------------------
    [x:?] |- x + 1 :: ?? -- what should "?" be?
[T-Abs]------------------------------
    [] |- (\x -> x + 1) :: ? -> ??
```

Main idea:

1. Whenever you need to “guess” a type, don’t.
   - just return a **fresh** type variable
   - *fresh* = not used anywhere else in the program
2. Whenever a rule *imposes a constraint* on a type (i.e. says it should have certain form):
   - try to find the right *substitution* for the free type vars to satisfy the constraint

Example

Let's infer the type of \x -> x + 1:

--	TEnv	Expression	Step	Subst	Inferred type
1	[]	\x -> x + 1	[T-Abs]	[]	
2	[x:a0]	x + 1	[T-Add]		
3		x	[T-Var]		a0
4		x + 1	unify a0 Int	[a0/Int]	
5	[x:Int]	1	[T-Num]		Int
6		x + 1	unify Int Int		
7		x + 1			Int
8	[]	\x -> x + 1			Int -> Int

Example

1. Infer the type of (\x -> x + 1) in [] (apply [T-Abs])
2. For the type of x, pick *fresh type variable* (say, a0); infer the type of x + 1 in [x:a0](apply [T-Add])
3. Infer the type of x in [x:a0] (apply [T-Var]); result: a0
4. [T-Add] *imposes a constraint*: its LHS must be of type Int, so *unify* a0 and Int and update the *current substitution* to [a0 / Int]
5. *Apply* the current substitution [a0/Int] to the type environment [x:a0] to get [x:Int]. Infer the type of 1 in [x:Int] (apply [T-Num]); result: Int
6. [T-Add] *imposes a constraint*: its RHS must be of type Int, so *unify* Int and Int; current substitution doesn't change\
7. By conclusion of [T-Add]: return Int as the inferred type\
8. By conclusion of [T-Lam]: return Int -> Int as the inferred type

Unification

The **unification** problem: given two types T1 and T2, find a type substitution U such that U T1 =U T2.

Such a substitution is called a *unifier* of T1 and T2

Examples:

The unifier of:

a and Int is [a / Int]

a -> a and Int -> Int is [a / Int]

a -> Int and Int -> b is [a / Int, b / Int]

Int and Int is []

a and a is []

Int and Int -> Int cannot unify!

Int and a -> a cannot unify!

a and a -> a cannot unify!

QUIZ

What is the unifier of the following two types? *

```
1. a -> Int -> Int
2. b -> c
```

- (A) Cannot unify
- (B) [a / Int, b / Int -> Int, c / Int]
- (C) [a / Int, b / Int, c / Int -> Int]
- (D) [b / a, c / Int -> Int]
- (E) [a / b, c / Int -> Int]

http://tiny.cc/cse116-unify-ind

QUIZ

What is the unifier of the following two types? *

```
1. a -> Int -> Int
2. b -> c
```

- (A) Cannot unify
- (B) [a / Int, b / Int -> Int, c / Int]
- (C) [a / Int, b / Int, c / Int -> Int]
- (D) [b / a, c / Int -> Int]
- (E) [a / b, c / Int -> Int]

http://tiny.cc/cse116-unify-grp

QUIZ

(C), (D) and (E) are all unifiers!

But somehow (D) and (E) are *better* than (C)

- they make the *least commitment* required to make these types equal
- this is called **the most general unifier**

Infer: take 2

Let's add constraint-based typing to infer!

```
-- I Now has to keep track of current substitution!
infer :: Subst -> TypeEnv -> Expr -> (Subst, Type)
infer sub _    (ENum _)     = (sub, TInt)
infer sub tEnv (EVar var)   = (sub, lookup var tEnv)

-- Lambda case: simply generate fresh type variable!
infer sub tEnv (ELam x e) = (sub1, tX' :=> tBody)
  where
    tEnv'          = extendTEnv x tX tEnv
    tX             = freshTV -- we'll get to this
    (sub1, tBody)  = infer sub tEnv' e
    tX'            = apply sub1 tX
```

Infer: take 2

```
-- Add case: recursively infer types of operands
-- and enforce constraint that they are both Int
infer sub tEnv (EAdd e1 e2) = (sub4, TInt)
  where
    (sub1, t1) = infer sub tEnv e1    -- 1. infer type of e1
    sub2       = unify sub1 t1 Int    -- 2. constraint: t1 is Int
    tEnv'      = apply sub2 tEnv      -- 3. apply subst to context
    (sub3, t2) = infer sub2 tEnv' e2  -- 4. infer e2 type in new ctx
    sub4       = unify sub3 t2 Int    -- 5. constraint: t2 is Int
```

Why are all these steps necessary? Can't we just return (sub, TInt)?

QUIZ

Which of these programs will type-check if we skip step 3? *

```
infer sub tEnv (EAdd e1 e2) = (sub4, TInt)
  where
    (sub1, t1) = infer sub tEnv e1    -- 1. infer type of e1
    sub2       = unify sub1 t1 Int    -- 2. enforce constraint: t1 is Int
    tEnv'      = apply sub2 tEnv      -- 3. apply substitution to context
    (sub3, t2) = infer sub2 tEnv' e2 -- 4. infer type of e2 in new ctx
    sub4       = unify sub3 t2 Int    -- 5. enforce constraint: t2 is Int
```

- (A) 1 2 + 3
- (B) 1 + 2 3
- (C) (\x -> x) + 1
- (D) 1 + (\x -> x)
- (E) \x -> x + x 5

http://tiny.cc/cse116-infer-ind

QUIZ

Which of these programs will type-check if we skip step 3? *

```
infer sub tEnv (EAdd e1 e2) = (sub4, TInt)
  where
    (sub1, t1) = infer sub tEnv e1    -- 1. infer type of e1
    sub2       = unify sub1 t1 Int    -- 2. enforce constraint: t1 is Int
    tEnv'      = apply sub2 tEnv      -- 3. apply substitution to context
    (sub3, t2) = infer sub2 tEnv' e2 -- 4. infer type of e2 in new ctx
    sub4       = unify sub3 t2 Int    -- 5. enforce constraint: t2 is Int
```

- (A) 1 2 + 3
- (B) 1 + 2 3
- (C) (\x -> x) + 1
- (D) 1 + (\x -> x)
- (E) \x -> x + x 5

http://tiny.cc/cse116-infer-grp

QUIZ

Answer: E.

A fails in step 1 (LHS is ill-typed);

B fails in step 4 (RHS is ill-typed);

C fails in step 2 (LHS is not Int);

D fails in step 5 (RHS is not Int);

finally, E should fails because LHS and RHS by themselves are fine, but not together!

Fresh type variables

```
-- I Now has to keep track of current substitution!
infer :: Subst -> TypeEnv -> Expr -> (Subst, Type)

-- Lambda case: simply generate fresh type variable!
infer tEnv (ELam x e) = tX :=> tBody
  where
    tEnv'  = extendTEnv x tX tEnv
    tX     = freshTV -- how do we do this?
    tBody  = infer tEnv' e
```

Intended behavior:

- First time we call freshTV it returns a0
- Second time it returns a1
- .. and so on

Can we do that in Haskell?

No, Haskell is pure. Have to thread the counter through :(

Polymorphism: the final frontier

Back to double identity:

```
let id = \x -> x in    -- Must generalize the type of id
  let y = id 5 in      -- Instantiate with Int
    id (\z -> z + y)   -- Instantiate with (Int -> Int)
```

- When should we to generalize a type like a -> a into a polymorphic type like forall a .a -> a?
- When should we instantiate a polymorphic type like forall a . a -> a and with what?

Polymorphism: the final frontier

Generalization and instantiation:

- Whenever we infer a type for a let-defined variable, generalize it!
  - it's safe to do so, even when not strictly necessary
- Whenever we see a variable with a polymorphic type, instantiate it
  - with what type?
  - well, what do we use when we don't know what type to use?
  - *fresh type variables!*

Example

Let's infer the type of **let** id = \x -> x **in** id 5:

```
-- TEnv   Expression          Step          Subst          Type

1  []     let id=\x->x in id 5   [T-Let]       []
2               \x->x          [T-Abs]
3  [x:a0]          x           [T-Var]                     a0
4               \x->x                                   a0 -> a0
5  []     let id=\x->x in id 5   generalize a0
6  tEnv                  id 5   [T-App]
7                      id     [T-Var]
8                      id     instantiate                 a1 -> a1
9                        5   [T-Num]                     Int
10                     id 5   unify (a1->a1)
                                (Int->a2) [a1/Int,a2/Int]
10                     id 5                           Int
11 []     let id=\x->x in id 5                            Int
```

Here tEnv = [id : forall a0.a0->a0]

What we learned this week

Type system: a set of rules about which expressions have which types

Type environment (or context): a mapping of variables to their types

Polymorphic type: a type parameterized with type variables that can be instantiated with any concrete type

Type substitution: a mapping of type variables to types; you can **apply** a substitution to a type by replacing all its variables with their values in the substitution

Unifier of two types: a substitution that makes them equal; **unification** is the process of finding a unifier

What we learned this week

Type inference: an algorithm to determine the type of an expression

Constraint-based type inference: a type inference technique that uses fresh type variables and unification

Generalization: turning a mono-type with free type variables into a polymorphic type (by binding its variables with a forall)

Instantiation: turning a polymorphic type into a mono-type by substituting type variables in its body with some types