

# DEV-各服務啟動關閉方式

### 停機流程建議

- 1. 觀察服務狀態
- 2. 關閉服務
- 3. 觀察服務狀態
- 4. 確認停機準備結束再啟用服務
- 5. 觀察服務狀態

#### Gitlab @

Gitlab 啟動較久,服務顯示啟動還是需要等待段時間。

### 啟動 Gitlab 服務 ⊘

1 systemctl start gitlab-runsvdir.service

### 關閉 Gitlab 服務 🖉

1 systemctl stop gitlab-runsvdir.service

### 檢查 Gitlab 服務 ∅

1 systemctl status gitlab-runsvdir.service

```
Calculation (Calculation Australian Australian process
Local Liber (Calculation)

All Calculation (Calculation)

All Calcula
```

Gitlab 服務



### 啟動 Jenkins 服務 🖉

1 systemctl start jenkins

### 關閉 Jenkins 服務 🖉

1 systemctl stop jenkins

# 檢查 Jenkins 服務 ∅

1 systemctl status jenkins

Jenkins 服務

# Nexus (由 Nginx 代理) ②

啟動 Nexus (啟動 Nginx 即可) 🕜

1 systemctl start nginx

# 關閉 Nexus (關閉 Nginx 即可) 🕜

1 systemctl stop nginx

# 檢查 Nexus (檢查 Nginx 即可) ⊘

1 systemctl status nginx



Nexus服務 (Nginx 代理)

# Harbor (使用 docker compose) ∅

### 啟動 Harbor 服務 🖉

- 1 cd /datam/harbor/
- 2 docker compose up -d

# 關閉 Harbor 服務 🖉

- 1 cd /datam/harbor/
- 2 docker compose down

# 檢查 Harbor 服務 ℰ

1 docker compose ps



```
| The content of the
```

Harbor 服務

# SonarQube (由 Nginx 代理) ②

啟動 SonarQube (啟動 Nginx 即可) 🖉

1 systemctl start nginx

# 關閉 SonarQube (關閉 Nginx 即可) 🕜

1 systemctl stop nginx

# 檢查 SonarQube(檢查 Nginx 即可) ②

1 systemctl status nginx



```
## 12 202277 commonths betrieflight between protest services and protest prote
```

Sonarqube服務 (Nginx 代理)

# Redmine (由 Nginx 代理) ∅

啟動 Redmine (啟動 Nginx 即可) ⊘

1 systemctl start nginx

# 關閉 Redmine (關閉 Nginx 即可) 🕜

1 systemctl stop nginx

# 檢查 Redmine(檢查 Nginx 即可) ⊘

1 systemctl status nginx



```
residence 1. 19 system; Status spin-service property of the party of t
```

Redmine服務(Nginx代理)