CICD 掃描報告

專案名稱	CICD
掃描開始	2026年3月5日 上午 10:11:34
預設集合	Checkmarx Default
掃描時間	00h:09m:10s
被掃描的程式行數	429718
被掃描的檔案數	2892
報告建立時間	2026年3月5日 上午 10:21:38
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979
團隊	planning
Checkmarx版本	9.6.5.1001 HF20
掃描類別	完整的
來源	LocalPath
漏洞密度	1/1000 (漏洞/LOC)
可見性	公開
掃描自訂欄位	

過濾器設置

嚴重程度：

包含在內: 高風險, 中風險, 低風險, 資訊

排除在外: 無

結果狀態：

包含在內: 校驗, 不可利用, 確認, 緊急, 推薦不可用

排除在外: 無

被分配給

包含在內: 全部

類別

包含在內:

未分類	全部
Custom	全部
PCI DSS v3.2.1	全部
OWASP Top 10 2013	全部
FISMA 2014	全部
NIST SP 800-53	全部
OWASP Top 10 2017	全部
OWASP Mobile Top 10 2016	全部
OWASP Top 10 API	全部
ASD STIG 4.10	全部
OWASP Top 10 2010	全部
CWE top 25	全部
MOIS(KISA) Secure	全部

Coding 2021	
OWASP ASVS	全部
OWASP Top 10 2021	全部
SANS top 25	全部
ASA Mobile Premium	全部
ASA Premium	全部
Top Tier	全部
ASD STIG 5.3	全部
Base Preset	全部
OWASP Top 10 API 2023	全部
PCI DSS v4.0	全部

排除在外:

未分類	無
Custom	無
PCI DSS v3.2.1	無
OWASP Top 10 2013	無
FISMA 2014	無
NIST SP 800-53	無
OWASP Top 10 2017	無
OWASP Mobile Top 10 2016	無
OWASP Top 10 API	無
ASD STIG 4.10	無
OWASP Top 10 2010	無
CWE top 25	無
MOIS(KISA) Secure Coding 2021	無
OWASP ASVS	無
OWASP Top 10 2021	無
SANS top 25	無
ASA Mobile Premium	無
ASA Premium	無
Top Tier	無
ASD STIG 5.3	無
Base Preset	無
OWASP Top 10 API 2023	無

PCI DSS v4.0 無

結果限制

每次查詢的結果限制設置為 50

選取的查詢

選取的查詢列出在 掃描結果摘要

掃描結果摘要



最容易受攻擊的檔案



數量最多的前5類漏洞



掃描總結 - OWASP Top 10 2017

有關可見性和風險的詳細資訊及闡述參見： OWASP Top 10 2017

Category	Threat Agent	Exploitability	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection*	App. Specific	EASY	COMMON	EASY	SEVERE	App. Specific	9	6
A2-Broken Authentication*	App. Specific	EASY	COMMON	AVERAGE	SEVERE	App. Specific	1	1
A3-Sensitive Data Exposure*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	App. Specific	24	9
A4-XML External Entities (XXE)	App. Specific	AVERAGE	COMMON	EASY	SEVERE	App. Specific	0	0
A5-Broken Access Control*	App. Specific	AVERAGE	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A6-Security Misconfiguration *	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	18	18
A7-Cross-Site Scripting (XSS)*	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	1	1
A8-Insecure Deserialization	App. Specific	DIFFICULT	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A9-Using Components with Known Vulnerabilities*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	MODERATE	App. Specific	0	0
A10-Insufficient Logging & Monitoring	App. Specific	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	App. Specific	0	0

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Top 10 2021

Category	Issues Found	Best Fix Locations
A1-Broken Access Control*	16	3
A2-Cryptographic Failures	54	54
A3-Injection*	7	4
A4-Insecure Design*	67	65
A5-Security Misconfiguration*	0	0
A6-Vulnerable and Outdated Components*	0	0
A7-Identification and Authentication Failures*	326	326
A8-Software and Data Integrity Failures*	0	0
A9-Security Logging and Monitoring Failures	551	548
A10-Server-Side Request Forgery	0	0

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Top 10 2013

有關可見性和風險的詳細資訊及闡述參見： OWASP Top 10 2013

Category	Threat Agent	Attack Vectors	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection*	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	AVERAGE	SEVERE	ALL DATA	1	1
A2-Broken Authentication and Session Management*	EXTERNAL, INTERNAL USERS	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	AFFECTED DATA AND FUNCTIONS	1	1
A3-Cross-Site Scripting (XSS)*	EXTERNAL, INTERNAL, ADMIN USERS	AVERAGE	VERY WIDESPREAD	EASY	MODERATE	AFFECTED DATA AND SYSTEM	1	1
A4-Insecure Direct Object References*	SYSTEM USERS	EASY	COMMON	EASY	MODERATE	EXPOSED DATA	0	0
A5-Security Misconfiguration *	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	EASY	MODERATE	ALL DATA AND SYSTEM	1	1
A6-Sensitive Data Exposure*	EXTERNAL, INTERNAL, ADMIN USERS, USERS BROWSERS	DIFFICULT	UNCOMMON	AVERAGE	SEVERE	EXPOSED DATA	70	55
A7-Missing Function Level Access Control*	EXTERNAL, INTERNAL USERS	EASY	COMMON	AVERAGE	MODERATE	EXPOSED DATA AND FUNCTIONS	0	0
A8-Cross-Site Request Forgery (CSRF)	USERS BROWSERS	AVERAGE	COMMON	EASY	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A9-Using Components with Known Vulnerabilities*	EXTERNAL USERS, AUTOMATED TOOLS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A10-Unvalidated Redirects and Forwards	USERS BROWSERS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - PCI DSS v3.2.1

Category	Issues Found	Best Fix Locations
PCI DSS (3.2.1) - 6.5.1 - Injection flaws - particularly SQL injection	22	6
PCI DSS (3.2.1) - 6.5.2 - Buffer overflows	0	0
PCI DSS (3.2.1) - 6.5.3 - Insecure cryptographic storage*	0	0
PCI DSS (3.2.1) - 6.5.4 - Insecure communications*	0	0
PCI DSS (3.2.1) - 6.5.5 - Improper error handling*	41	41
PCI DSS (3.2.1) - 6.5.7 - Cross-site scripting (XSS)*	1	1
PCI DSS (3.2.1) - 6.5.8 - Improper access control*	0	0
PCI DSS (3.2.1) - 6.5.9 - Cross-site request forgery	0	0
PCI DSS (3.2.1) - 6.5.10 - Broken authentication and session management	1	1

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - FISMA 2014

Category	Description	Issues Found	Best Fix Locations
Access Control*	Organizations must limit information system access to authorized users, processes acting on behalf of authorized users, or devices (including other information systems) and to the types of transactions and functions that authorized users are permitted to exercise.	17	17
Audit And Accountability*	Organizations must: (i) create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity; and (ii) ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.	0	0
Configuration Management*	Organizations must: (i) establish and maintain baseline configurations and inventories of organizational information systems (including hardware, software, firmware, and documentation) throughout the respective system development life cycles; and (ii) establish and enforce security configuration settings for information technology products employed in organizational information systems.	1	1
Identification And Authentication*	Organizations must identify information system users, processes acting on behalf of users, or devices and authenticate (or verify) the identities of those users, processes, or devices, as a prerequisite to allowing access to organizational information systems.	16	3
Media Protection	Organizations must: (i) protect information system media, both paper and digital; (ii) limit access to information on information system media to authorized users; and (iii) sanitize or destroy information system media before disposal or release for reuse.	2	2
System And Communications Protection	Organizations must: (i) monitor, control, and protect organizational communications (i.e., information transmitted or received by organizational information systems) at the external boundaries and key internal boundaries of the information systems; and (ii) employ architectural designs, software development techniques, and systems engineering principles that promote effective information security within organizational information systems.	0	0
System And Information Integrity*	Organizations must: (i) identify, report, and correct information and information system flaws in a timely manner; (ii) provide protection from malicious code at appropriate locations within organizational information systems; and (iii) monitor information system security alerts and advisories and take appropriate actions in response.	40	16

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - NIST SP 800-53

Category	Issues Found	Best Fix Locations
AC-12 Session Termination (P2)	0	0
AC-3 Access Enforcement (P1)*	17	17
AC-4 Information Flow Enforcement (P1)	0	0
AC-6 Least Privilege (P1)	0	0
AU-9 Protection of Audit Information (P1)	8	5
CM-6 Configuration Settings (P2)	0	0
IA-5 Authenticator Management (P1)	0	0
IA-6 Authenticator Feedback (P2)	0	0
IA-8 Identification and Authentication (Non-Organizational Users) (P1)	0	0
SC-12 Cryptographic Key Establishment and Management (P1)	0	0
SC-13 Cryptographic Protection (P1)	2	2
SC-17 Public Key Infrastructure Certificates (P1)	0	0
SC-18 Mobile Code (P2)	0	0
SC-23 Session Authenticity (P1)*	0	0
SC-28 Protection of Information at Rest (P1)*	1	1
SC-4 Information in Shared Resources (P1)	14	1
SC-5 Denial of Service Protection (P1)*	41	41
SC-8 Transmission Confidentiality and Integrity (P1)	0	0
SI-10 Information Input Validation (P1)*	31	10
SI-11 Error Handling (P2)*	1	1
SI-15 Information Output Filtering (P0)*	1	1
SI-16 Memory Protection (P1)*	1	1

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Mobile Top 10 2016

Category	Description	Issues Found	Best Fix Locations
M1-Improper Platform Usage*	This category covers misuse of a platform feature or failure to use platform security controls. It might include Android intents, platform permissions, misuse of TouchID, the Keychain, or some other security control that is part of the mobile operating system. There are several ways that mobile apps can experience this risk.	0	0
M2-Insecure Data Storage*	This category covers insecure data storage and unintended data leakage.	0	0
M3-Insecure Communication*	This category covers poor handshaking, incorrect SSL versions, weak negotiation, cleartext communication of sensitive assets, etc.	0	0
M4-Insecure Authentication*	This category captures notions of authenticating the end user or bad session management. This can include: -Failing to identify the user at all when that should be required -Failure to maintain the user's identity when it is required -Weaknesses in session management	0	0
M5-Insufficient Cryptography*	The code applies cryptography to a sensitive information asset. However, the cryptography is insufficient in some way. Note that anything and everything related to TLS or SSL goes in M3. Also, if the app fails to use cryptography at all when it should, that probably belongs in M2. This category is for issues where cryptography was attempted, but it wasnt done correctly.	0	0
M6-Insecure Authorization*	This is a category to capture any failures in authorization (e.g., authorization decisions in the client side, forced browsing, etc.). It is distinct from authentication issues (e.g., device enrolment, user identification, etc.). If the app does not authenticate users at all in a situation where it should (e.g., granting anonymous access to some resource or service when authenticated and authorized access is required), then that is an authentication failure not an authorization failure.	0	0
M7-Client Code Quality*	This category is the catch-all for code-level implementation problems in the mobile client. That's distinct from server-side coding mistakes. This would capture things like buffer overflows, format string vulnerabilities, and various other code-level mistakes where the solution is to rewrite some code that's running on the mobile device.	69	24
M8-Code Tampering*	This category covers binary patching, local resource modification, method hooking, method swizzling, and dynamic memory modification. Once the application is delivered to the mobile device, the code and data resources are resident there. An attacker can either directly modify the code, change the contents of memory dynamically, change or replace the system APIs that the application uses, or	0	0

	modify the application's data and resources. This can provide the attacker a direct method of subverting the intended use of the software for personal or monetary gain.		
M9-Reverse Engineering*	This category includes analysis of the final core binary to determine its source code, libraries, algorithms, and other assets. Software such as IDA Pro, Hopper, otool, and other binary inspection tools give the attacker insight into the inner workings of the application. This may be used to exploit other nascent vulnerabilities in the application, as well as revealing information about back end servers, cryptographic constants and ciphers, and intellectual property.	1	1
M10-Extraneous Functionality*	Often, developers include hidden backdoor functionality or other internal development security controls that are not intended to be released into a production environment. For example, a developer may accidentally include a password as a comment in a hybrid app. Another example includes disabling of 2-factor authentication during testing.	0	0

***** 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Top 10 API

Category	Issues Found	Best Fix Locations
API1-Broken Object Level Authorization	0	0
API2-Broken Authentication*	2	2
API3-Excessive Data Exposure	1	1
API4-Lack of Resources and Rate Limiting	5	2
API5-Broken Function Level Authorization	0	0
API6-Mass Assignment	0	0
API7-Security Misconfiguration*	0	0
API8-Injection*	0	0
API9-Improper Assets Management	0	0
API10-Insufficient Logging and Monitoring	0	0

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - Custom

Category	Issues Found	Best Fix Locations
Must audit	0	0
Check	0	0
Optional	0	0

掃描總結 - PCI DSS v4.0

Category	Issues Found	Best Fix Locations
PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development*	460	418

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - ASD STIG 4.10

Category	Issues Found	Best Fix Locations
APSC-DV-000640 - CAT II The application must provide audit record generation capability for the renewal of session IDs.	0	0
APSC-DV-000650 - CAT II The application must not write sensitive data into the application logs.	0	0
APSC-DV-000660 - CAT II The application must provide audit record generation capability for session timeouts.	0	0
APSC-DV-000670 - CAT II The application must record a time stamp indicating when the event occurred.	0	0
APSC-DV-000680 - CAT II The application must provide audit record generation capability for HTTP headers including User-Agent, Referer, GET, and POST.	0	0
APSC-DV-000690 - CAT II The application must provide audit record generation capability for connecting system IP addresses.	0	0
APSC-DV-000700 - CAT II The application must record the username or user ID of the user associated with the event.	0	0
APSC-DV-000710 - CAT II The application must generate audit records when successful/unsuccessful attempts to grant privileges occur.	0	0
APSC-DV-000720 - CAT II The application must generate audit records when successful/unsuccessful attempts to access security objects occur.	0	0
APSC-DV-000730 - CAT II The application must generate audit records when successful/unsuccessful attempts to access security levels occur.	0	0
APSC-DV-000740 - CAT II The application must generate audit records when successful/unsuccessful attempts to access categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000750 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify privileges occur.	0	0
APSC-DV-000760 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify security objects occur.	0	0
APSC-DV-000770 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify security levels occur.	0	0
APSC-DV-000780 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000790 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete privileges occur.	0	0
APSC-DV-000800 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete security levels occur.	0	0
APSC-DV-000810 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete application database security objects occur.	0	0
APSC-DV-000820 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000830 - CAT II The application must generate audit records when successful/unsuccessful logon attempts occur.	0	0
APSC-DV-000840 - CAT II The application must generate audit records for privileged activities or other system-level access.	0	0
APSC-DV-000850 - CAT II The application must generate audit records showing starting and ending time for user access to the system.	0	0
APSC-DV-000860 - CAT II The application must generate audit records when successful/unsuccessful accesses to objects occur.	0	0

APSC-DV-000870 - CAT II The application must generate audit records for all direct access to the information system.	0	0
APSC-DV-000880 - CAT II The application must generate audit records for all account creations, modifications, disabling, and termination events.	0	0
APSC-DV-000910 - CAT II The application must initiate session auditing upon startup.	0	0
APSC-DV-000940 - CAT II The application must log application shutdown events.	0	0
APSC-DV-000950 - CAT II The application must log destination IP addresses.	0	0
APSC-DV-000960 - CAT II The application must log user actions involving access to data.	0	0
APSC-DV-000970 - CAT II The application must log user actions involving changes to data.	0	0
APSC-DV-000980 - CAT II The application must produce audit records containing information to establish when (date and time) the events occurred.	0	0
APSC-DV-000990 - CAT II The application must produce audit records containing enough information to establish which component, feature or function of the application triggered the audit event.	0	0
APSC-DV-001000 - CAT II When using centralized logging; the application must include a unique identifier in order to distinguish itself from other application logs.	0	0
APSC-DV-001010 - CAT II The application must produce audit records that contain information to establish the outcome of the events.	0	0
APSC-DV-001020 - CAT II The application must generate audit records containing information that establishes the identity of any individual or process associated with the event.	0	0
APSC-DV-001030 - CAT II The application must generate audit records containing the full-text recording of privileged commands or the individual identities of group account users.	0	0
APSC-DV-001040 - CAT II The application must implement transaction recovery logs when transaction based.	0	0
APSC-DV-001050 - CAT II The application must provide centralized management and configuration of the content to be captured in audit records generated by all application components.	0	0
APSC-DV-001070 - CAT II The application must off-load audit records onto a different system or media than the system being audited.	0	0
APSC-DV-001080 - CAT II The application must be configured to write application logs to a centralized log repository.	0	0
APSC-DV-001090 - CAT II The application must provide an immediate warning to the SA and ISSO (at a minimum) when allocated audit record storage volume reaches 75% of repository maximum audit record storage capacity.	0	0
APSC-DV-001100 - CAT II Applications categorized as having a moderate or high impact must provide an immediate real-time alert to the SA and ISSO (at a minimum) for all audit failure events.	0	0
APSC-DV-001110 - CAT II The application must alert the ISSO and SA (at a minimum) in the event of an audit processing failure.	0	0
APSC-DV-001120 - CAT II The application must shut down by default upon audit failure (unless availability is an overriding concern).	0	0
APSC-DV-001130 - CAT II The application must provide the capability to centrally review and analyze audit records from multiple components within the system.	0	0
APSC-DV-001140 - CAT II The application must provide the capability to filter audit records for events of interest based upon organization-defined criteria.	0	0
APSC-DV-001150 - CAT II The application must provide an audit reduction capability that supports on-demand reporting requirements.	0	0
APSC-DV-001160 - CAT II The application must provide an audit reduction capability that supports on-demand audit review and analysis.	0	0
APSC-DV-001170 - CAT II The application must provide an audit reduction capability that supports after-the-fact investigations of security incidents.	0	0
APSC-DV-001180 - CAT II The application must provide a report generation capability that supports on-demand audit review and analysis.	0	0

APSC-DV-001190 - CAT II The application must provide a report generation capability that supports on-demand reporting requirements.	0	0
APSC-DV-001200 - CAT II The application must provide a report generation capability that supports after-the-fact investigations of security incidents.	0	0
APSC-DV-001210 - CAT II The application must provide an audit reduction capability that does not alter original content or time ordering of audit records.	0	0
APSC-DV-001220 - CAT II The application must provide a report generation capability that does not alter original content or time ordering of audit records.	0	0
APSC-DV-001250 - CAT II The applications must use internal system clocks to generate time stamps for audit records.	0	0
APSC-DV-001260 - CAT II The application must record time stamps for audit records that can be mapped to Coordinated Universal Time (UTC) or Greenwich Mean Time (GMT).	0	0
APSC-DV-001270 - CAT II The application must record time stamps for audit records that meet a granularity of one second for a minimum degree of precision.	0	0
APSC-DV-001280 - CAT II The application must protect audit information from any type of unauthorized read access.	0	0
APSC-DV-001290 - CAT II The application must protect audit information from unauthorized modification.	0	0
APSC-DV-001300 - CAT II The application must protect audit information from unauthorized deletion.	0	0
APSC-DV-001310 - CAT II The application must protect audit tools from unauthorized access.	0	0
APSC-DV-001320 - CAT II The application must protect audit tools from unauthorized modification.	0	0
APSC-DV-001330 - CAT II The application must protect audit tools from unauthorized deletion.	0	0
APSC-DV-001340 - CAT II The application must back up audit records at least every seven days onto a different system or system component than the system or component being audited.	0	0
APSC-DV-001570 - CAT II The application must electronically verify Personal Identity Verification (PIV) credentials.	0	0
APSC-DV-001350 - CAT II The application must use cryptographic mechanisms to protect the integrity of audit information.	0	0
APSC-DV-001360 - CAT II Application audit tools must be cryptographically hashed.	0	0
APSC-DV-001370 - CAT II The integrity of the audit tools must be validated by checking the files for changes in the cryptographic hash value.	0	0
APSC-DV-001390 - CAT II The application must prohibit user installation of software without explicit privileged status.	0	0
APSC-DV-001410 - CAT II The application must enforce access restrictions associated with changes to application configuration.	0	0
APSC-DV-001420 - CAT II The application must audit who makes configuration changes to the application.	0	0
APSC-DV-001430 - CAT II The application must have the capability to prevent the installation of patches, service packs, or application components without verification the software component has been digitally signed using a certificate that is recognized and approved by the orga	0	0
APSC-DV-001440 - CAT II The applications must limit privileges to change the software resident within software libraries.	0	0
APSC-DV-001460 - CAT II An application vulnerability assessment must be conducted.	0	0
APSC-DV-001480 - CAT II The application must prevent program execution in accordance with organization-defined policies regarding software program usage and restrictions, and/or rules authorizing the terms and conditions of software program usage.	0	0
APSC-DV-001490 - CAT II The application must employ a deny-all, permit-by-exception (whitelist) policy to allow the execution of authorized software programs.	0	0
APSC-DV-001500 - CAT II The application must be configured to disable non-essential capabilities.	0	0
APSC-DV-001510 - CAT II The application must be configured to use only functions, ports, and protocols permitted to it in the PPSM CAL.	0	0

APSC-DV-001520 - CAT II The application must require users to reauthenticate when organization-defined circumstances or situations require reauthentication.	0	0
APSC-DV-001530 - CAT II The application must require devices to reauthenticate when organization-defined circumstances or situations requiring reauthentication.	0	0
APSC-DV-001540 - CAT I The application must uniquely identify and authenticate organizational users (or processes acting on behalf of organizational users).	0	0
APSC-DV-001550 - CAT II The application must use multifactor (Alt. Token) authentication for network access to privileged accounts.	0	0
APSC-DV-001560 - CAT II The application must accept Personal Identity Verification (PIV) credentials.	0	0
APSC-DV-001580 - CAT II The application must use multifactor (e.g., CAC, Alt. Token) authentication for network access to non-privileged accounts.	0	0
APSC-DV-001590 - CAT II The application must use multifactor (Alt. Token) authentication for local access to privileged accounts.	0	0
APSC-DV-001600 - CAT II The application must use multifactor (e.g., CAC, Alt. Token) authentication for local access to non-privileged accounts.	0	0
APSC-DV-001610 - CAT II The application must ensure users are authenticated with an individual authenticator prior to using a group authenticator.	0	0
APSC-DV-001620 - CAT II The application must implement replay-resistant authentication mechanisms for network access to privileged accounts.	0	0
APSC-DV-001630 - CAT II The application must implement replay-resistant authentication mechanisms for network access to non-privileged accounts.	0	0
APSC-DV-001640 - CAT II The application must utilize mutual authentication when endpoint device non-repudiation protections are required by DoD policy or by the data owner.	0	0
APSC-DV-001650 - CAT II The application must authenticate all network connected endpoint devices before establishing any connection.	0	0
APSC-DV-001660 - CAT II Service-Oriented Applications handling non-releasable data must authenticate endpoint devices via mutual SSL/TLS.	0	0
APSC-DV-001670 - CAT II The application must disable device identifiers after 35 days of inactivity unless a cryptographic certificate is used for authentication.	0	0
APSC-DV-001680 - CAT I The application must enforce a minimum 15-character password length.	0	0
APSC-DV-001690 - CAT II The application must enforce password complexity by requiring that at least one upper-case character be used.	0	0
APSC-DV-001700 - CAT II The application must enforce password complexity by requiring that at least one lower-case character be used.	0	0
APSC-DV-001710 - CAT II The application must enforce password complexity by requiring that at least one numeric character be used.	0	0
APSC-DV-001720 - CAT II The application must enforce password complexity by requiring that at least one special character be used.	0	0
APSC-DV-001730 - CAT II The application must require the change of at least 8 of the total number of characters when passwords are changed.	0	0
APSC-DV-001740 - CAT I The application must only store cryptographic representations of passwords.	0	0
APSC-DV-001850 - CAT I The application must not display passwords/PINs as clear text.	0	0
APSC-DV-001750 - CAT I The application must transmit only cryptographically-protected passwords.	0	0
APSC-DV-001760 - CAT II The application must enforce 24 hours/1 day as the minimum password lifetime.	0	0
APSC-DV-001770 - CAT II The application must enforce a 60-day maximum password lifetime restriction.	0	0
APSC-DV-001780 - CAT II The application must prohibit password reuse for a minimum of five generations.	0	0
APSC-DV-001790 - CAT II The application must allow the use of a temporary password for system logons with an immediate change to a permanent password.	0	0

APSC-DV-001795 - CAT II The application password must not be changeable by users other than the administrator or the user with which the password is associated.	0	0
APSC-DV-001800 - CAT II The application must terminate existing user sessions upon account deletion.	0	0
APSC-DV-001820 - CAT I The application, when using PKI-based authentication, must enforce authorized access to the corresponding private key.	0	0
APSC-DV-001830 - CAT II The application must map the authenticated identity to the individual user or group account for PKI-based authentication.	0	0
APSC-DV-001870 - CAT II The application must uniquely identify and authenticate non-organizational users (or processes acting on behalf of non-organizational users).	0	0
APSC-DV-001810 - CAT I The application, when utilizing PKI-based authentication, must validate certificates by constructing a certification path (which includes status information) to an accepted trust anchor.	0	0
APSC-DV-001840 - CAT II The application, for PKI-based authentication, must implement a local cache of revocation data to support path discovery and validation in case of the inability to access revocation information via the network.	0	0
APSC-DV-001860 - CAT II The application must use mechanisms meeting the requirements of applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance for authentication to a cryptographic module.	0	0
APSC-DV-001880 - CAT II The application must accept Personal Identity Verification (PIV) credentials from other federal agencies.	0	0
APSC-DV-001890 - CAT II The application must electronically verify Personal Identity Verification (PIV) credentials from other federal agencies.	0	0
APSC-DV-002050 - CAT II Applications making SAML assertions must use FIPS-approved random numbers in the generation of SessionIndex in the SAML element AuthnStatement.	0	0
APSC-DV-001900 - CAT II The application must accept FICAM-approved third-party credentials.	0	0
APSC-DV-001910 - CAT II The application must conform to FICAM-issued profiles.	0	0
APSC-DV-001930 - CAT II Applications used for non-local maintenance sessions must audit non-local maintenance and diagnostic sessions for organization-defined auditable events.	0	0
APSC-DV-000310 - CAT III The application must have a process, feature or function that prevents removal or disabling of emergency accounts.	0	0
APSC-DV-001940 - CAT II Applications used for non-local maintenance sessions must implement cryptographic mechanisms to protect the integrity of non-local maintenance and diagnostic communications.	0	0
APSC-DV-001950 - CAT II Applications used for non-local maintenance sessions must implement cryptographic mechanisms to protect the confidentiality of non-local maintenance and diagnostic communications.	0	0
APSC-DV-001960 - CAT II Applications used for non-local maintenance sessions must verify remote disconnection at the termination of non-local maintenance and diagnostic sessions.	0	0
APSC-DV-001970 - CAT II The application must employ strong authenticators in the establishment of non-local maintenance and diagnostic sessions.	0	0
APSC-DV-001980 - CAT II The application must terminate all sessions and network connections when non-local maintenance is completed.	0	0
APSC-DV-001995 - CAT II The application must not be vulnerable to race conditions.	0	0
APSC-DV-002000 - CAT II The application must terminate all network connections associated with a communications session at the end of the session.	0	0
APSC-DV-002010 - CAT II The application must implement NSA-approved cryptography to protect classified information in accordance with applicable federal laws, Executive Orders, directives, policies, regulations, and standards.	0	0
APSC-DV-002020 - CAT II The application must utilize FIPS-validated cryptographic modules when signing application components.	0	0
APSC-DV-002030 - CAT II The application must utilize FIPS-validated cryptographic modules when generating cryptographic hashes.	0	0

APSC-DV-002040 - CAT II The application must utilize FIPS-validated cryptographic modules when protecting unclassified information that requires cryptographic protection.	0	0
APSC-DV-002150 - CAT II The application user interface must be either physically or logically separated from data storage and management interfaces.	0	0
APSC-DV-002210 - CAT II The application must set the HTTPOnly flag on session cookies.	0	0
APSC-DV-002220 - CAT II The application must set the secure flag on session cookies.	0	0
APSC-DV-002230 - CAT I The application must not expose session IDs.	0	0
APSC-DV-002240 - CAT I The application must destroy the session ID value and/or cookie on logoff or browser close.	0	0
APSC-DV-002250 - CAT II Applications must use system-generated session identifiers that protect against session fixation.	0	0
APSC-DV-002260 - CAT II Applications must validate session identifiers.	0	0
APSC-DV-002270 - CAT II Applications must not use URL embedded session IDs.	0	0
APSC-DV-002280 - CAT II The application must not re-use or recycle session IDs.	0	0
APSC-DV-002290 - CAT II The application must use the Federal Information Processing Standard (FIPS) 140-2-validated cryptographic modules and random number generator if the application implements encryption, key exchange, digital signature, and hash functionality.	0	0
APSC-DV-002300 - CAT II The application must only allow the use of DoD-approved certificate authorities for verification of the establishment of protected sessions.	0	0
APSC-DV-002310 - CAT I The application must fail to a secure state if system initialization fails, shutdown fails, or aborts fail.	0	0
APSC-DV-002320 - CAT II In the event of a system failure, applications must preserve any information necessary to determine cause of failure and any information necessary to return to operations with least disruption to mission processes.	0	0
APSC-DV-002330 - CAT II The application must protect the confidentiality and integrity of stored information when required by DoD policy or the information owner.	0	0
APSC-DV-002340 - CAT II The application must implement approved cryptographic mechanisms to prevent unauthorized modification of organization-defined information at rest on organization-defined information system components.	0	0
APSC-DV-002350 - CAT II The application must use appropriate cryptography in order to protect stored DoD information when required by the information owner or DoD policy.	0	0
APSC-DV-002360 - CAT II The application must isolate security functions from non-security functions.	0	0
APSC-DV-002370 - CAT II The application must maintain a separate execution domain for each executing process.	0	0
APSC-DV-002380 - CAT II Applications must prevent unauthorized and unintended information transfer via shared system resources.	0	0
APSC-DV-002390 - CAT II XML-based applications must mitigate DoS attacks by using XML filters, parser options, or gateways.	0	0
APSC-DV-002400 - CAT II The application must restrict the ability to launch Denial of Service (DoS) attacks against itself or other information systems.	0	0
APSC-DV-002410 - CAT II The web service design must include redundancy mechanisms when used with high-availability systems.	0	0
APSC-DV-002420 - CAT II An XML firewall function must be deployed to protect web services when exposed to untrusted networks.	0	0
APSC-DV-002610 - CAT II The application must remove organization-defined software components after updated versions have been installed.	0	0
APSC-DV-002440 - CAT I The application must protect the confidentiality and integrity of transmitted information.	0	0
APSC-DV-002450 - CAT II The application must implement cryptographic mechanisms to prevent unauthorized disclosure of information and/or detect changes to information during transmission unless otherwise protected by alternative physical safeguards, such as, at a minimum, a Prot	0	0

APSC-DV-002460 - CAT II The application must maintain the confidentiality and integrity of information during preparation for transmission.	0	0
APSC-DV-002470 - CAT II The application must maintain the confidentiality and integrity of information during reception.	0	0
APSC-DV-002480 - CAT II The application must not disclose unnecessary information to users.	0	0
APSC-DV-002485 - CAT I The application must not store sensitive information in hidden fields.	0	0
APSC-DV-002490 - CAT I The application must protect from Cross-Site Scripting (XSS) vulnerabilities.	0	0
APSC-DV-002500 - CAT II The application must protect from Cross-Site Request Forgery (CSRF) vulnerabilities.	0	0
APSC-DV-002510 - CAT I The application must protect from command injection.	0	0
APSC-DV-002520 - CAT II The application must protect from canonical representation vulnerabilities.	0	0
APSC-DV-002530 - CAT II The application must validate all input.	0	0
APSC-DV-002540 - CAT I The application must not be vulnerable to SQL Injection.	0	0
APSC-DV-002550 - CAT I The application must not be vulnerable to XML-oriented attacks.	0	0
APSC-DV-002560 - CAT I The application must not be subject to input handling vulnerabilities.	0	0
APSC-DV-002570 - CAT II The application must generate error messages that provide information necessary for corrective actions without revealing information that could be exploited by adversaries.	0	0
APSC-DV-002580 - CAT II The application must reveal error messages only to the ISSO, ISSM, or SA.	0	0
APSC-DV-002590 - CAT I The application must not be vulnerable to overflow attacks.	0	0
APSC-DV-002630 - CAT II Security-relevant software updates and patches must be kept up to date.	0	0
APSC-DV-002760 - CAT II The application performing organization-defined security functions must verify correct operation of security functions.	0	0
APSC-DV-002900 - CAT II The ISSO must ensure application audit trails are retained for at least 1 year for applications without SAMI data, and 5 years for applications including SAMI data.	0	0
APSC-DV-002770 - CAT II The application must perform verification of the correct operation of security functions: upon system startup and/or restart; upon command by a user with privileged access; and/or every 30 days.	0	0
APSC-DV-002780 - CAT III The application must notify the ISSO and ISSM of failed security verification tests.	0	0
APSC-DV-002870 - CAT II Unsigned Category 1A mobile code must not be used in the application in accordance with DoD policy.	0	0
APSC-DV-002880 - CAT II The ISSO must ensure an account management process is implemented, verifying only authorized users can gain access to the application, and individual accounts designated as inactive, suspended, or terminated are promptly removed.	0	0
APSC-DV-002890 - CAT I Application web servers must be on a separate network segment from the application and database servers if it is a tiered application operating in the DoD DMZ.	0	0
APSC-DV-002910 - CAT II The ISSO must review audit trails periodically based on system documentation recommendations or immediately upon system security events.	0	0
APSC-DV-002920 - CAT II The ISSO must report all suspected violations of IA policies in accordance with DoD information system IA procedures.	0	0
APSC-DV-002930 - CAT II The ISSO must ensure active vulnerability testing is performed.	0	0
APSC-DV-002980 - CAT II New IP addresses, data services, and associated ports used by the application must be submitted to the appropriate approving authority for the organization, which in turn will be submitted through the DoD Ports, Protocols, and Services Management (DoD PPS	0	0
APSC-DV-002950 - CAT II Execution flow diagrams and design documents must be created to show how deadlock and recursion issues in web services are being mitigated.	0	0
APSC-DV-002960 - CAT II The designer must ensure the application does not store configuration and control files in the same directory as user data.	0	0
APSC-DV-002970 - CAT II The ISSO must ensure if a DoD STIG or NSA guide is not available, a third-party	0	0

product will be configured by following available guidance.		
APSC-DV-002990 - CAT II The application must be registered with the DoD Ports and Protocols Database.	0	0
APSC-DV-002990 - CAT II The application must be registered with the DoD Ports and Protocols Database.	0	0
APSC-DV-002995 - CAT II The Configuration Management (CM) repository must be properly patched and STIG compliant.	0	0
APSC-DV-003000 - CAT II Access privileges to the Configuration Management (CM) repository must be reviewed every three months.	0	0
APSC-DV-003010 - CAT II A Software Configuration Management (SCM) plan describing the configuration control and change management process of application objects developed by the organization and the roles and responsibilities of the organization must be created and maintained.	0	0
APSC-DV-003020 - CAT II A Configuration Control Board (CCB) that meets at least every release cycle, for managing the Configuration Management (CM) process must be established.	0	0
APSC-DV-003030 - CAT II The application services and interfaces must be compatible with and ready for IPv6 networks.	0	0
APSC-DV-003040 - CAT II The application must not be hosted on a general purpose machine if the application is designated as critical or high availability by the ISSO.	0	0
APSC-DV-003050 - CAT II A disaster recovery/continuity plan must exist in accordance with DoD policy based on the applications availability requirements.	0	0
APSC-DV-003060 - CAT II Recovery procedures and technical system features must exist so recovery is performed in a secure and verifiable manner. The ISSO will document circumstances inhibiting a trusted recovery.	0	0
APSC-DV-003070 - CAT II Data backup must be performed at required intervals in accordance with DoD policy.	0	0
APSC-DV-003080 - CAT II Back-up copies of the application software or source code must be stored in a fire-rated container or stored separately (offsite).	0	0
APSC-DV-003090 - CAT II Procedures must be in place to assure the appropriate physical and technical protection of the backup and restoration of the application.	0	0
APSC-DV-003100 - CAT II The application must use encryption to implement key exchange and authenticate endpoints prior to establishing a communication channel for key exchange.	0	0
APSC-DV-003110 - CAT I The application must not contain embedded authentication data.	0	0
APSC-DV-003120 - CAT I The application must have the capability to mark sensitive/classified output when required.	0	0
APSC-DV-003130 - CAT III Prior to each release of the application, updates to system, or applying patches; tests plans and procedures must be created and executed.	0	0
APSC-DV-003150 - CAT II At least one tester must be designated to test for security flaws in addition to functional testing.	0	0
APSC-DV-003140 - CAT II Application files must be cryptographically hashed prior to deploying to DoD operational networks.	0	0
APSC-DV-003160 - CAT III Test procedures must be created and at least annually executed to ensure system initialization, shutdown, and aborts are configured to verify the system remains in a secure state.	0	0
APSC-DV-003170 - CAT II An application code review must be performed on the application.	0	0
APSC-DV-003180 - CAT III Code coverage statistics must be maintained for each release of the application.	0	0
APSC-DV-003190 - CAT II Flaws found during a code review must be tracked in a defect tracking system.	0	0
APSC-DV-003200 - CAT II The changes to the application must be assessed for IA and accreditation impact prior to implementation.	0	0
APSC-DV-003210 - CAT II Security flaws must be fixed or addressed in the project plan.	0	0
APSC-DV-003215 - CAT III The application development team must follow a set of coding standards.	0	0
APSC-DV-003220 - CAT III The designer must create and update the Design Document for each release of the application.	0	0

APSC-DV-003230 - CAT II Threat models must be documented and reviewed for each application release and updated as required by design and functionality changes or when new threats are discovered.	0	0
APSC-DV-003235 - CAT II The application must not be subject to error handling vulnerabilities.	0	0
APSC-DV-003250 - CAT I The application must be decommissioned when maintenance or support is no longer available.	0	0
APSC-DV-003236 - CAT II The application development team must provide an application incident response plan.	0	0
APSC-DV-003240 - CAT I All products must be supported by the vendor or the development team.	0	0
APSC-DV-003260 - CAT III Procedures must be in place to notify users when an application is decommissioned.	0	0
APSC-DV-003270 - CAT II Unnecessary built-in application accounts must be disabled.	0	0
APSC-DV-003280 - CAT I Default passwords must be changed.	0	0
APSC-DV-003330 - CAT II The system must alert an administrator when low resource conditions are encountered.	0	0
APSC-DV-003285 - CAT II An Application Configuration Guide must be created and included with the application.	0	0
APSC-DV-003290 - CAT II If the application contains classified data, a Security Classification Guide must exist containing data elements and their classification.	0	0
APSC-DV-003300 - CAT II The designer must ensure uncategorized or emerging mobile code is not used in applications.	0	0
APSC-DV-003310 - CAT II Production database exports must have database administration credentials and sensitive data removed before releasing the export.	0	0
APSC-DV-003320 - CAT II Protections against DoS attacks must be implemented.	0	0
APSC-DV-003340 - CAT III At least one application administrator must be registered to receive update notifications, or security alerts, when automated alerts are available.	0	0
APSC-DV-003360 - CAT III The application must generate audit records when concurrent logons from different workstations occur.	0	0
APSC-DV-003345 - CAT III The application must provide notifications or alerts when product update and security related patches are available.	0	0
APSC-DV-003350 - CAT II Connections between the DoD enclave and the Internet or other public or commercial wide area networks must require a DMZ.	0	0
APSC-DV-003400 - CAT II The Program Manager must verify all levels of program management, designers, developers, and testers receive annual security training pertaining to their job function.	0	0
APSC-DV-000010 - CAT II The application must provide a capability to limit the number of logon sessions per user.	0	0
APSC-DV-000060 - CAT II The application must clear temporary storage and cookies when the session is terminated.	0	0
APSC-DV-000070 - CAT II The application must automatically terminate the non-privileged user session and log off non-privileged users after a 15 minute idle time period has elapsed.	0	0
APSC-DV-000080 - CAT II The application must automatically terminate the admin user session and log off admin users after a 10 minute idle time period is exceeded.	0	0
APSC-DV-000090 - CAT II Applications requiring user access authentication must provide a logoff capability for user initiated communication session.	0	0
APSC-DV-000100 - CAT III The application must display an explicit logoff message to users indicating the reliable termination of authenticated communications sessions.	0	0
APSC-DV-000110 - CAT II The application must associate organization-defined types of security attributes having organization-defined security attribute values with information in storage.	0	0
APSC-DV-000120 - CAT II The application must associate organization-defined types of security attributes having organization-defined security attribute values with information in process.	0	0
APSC-DV-000130 - CAT II The application must associate organization-defined types of security attributes	0	0

having organization-defined security attribute values with information in transmission.		
APSC-DV-000160 - CAT II The application must implement DoD-approved encryption to protect the confidentiality of remote access sessions.	0	0
APSC-DV-000170 - CAT II The application must implement cryptographic mechanisms to protect the integrity of remote access sessions.	0	0
APSC-DV-000190 - CAT I Messages protected with WS_Security must use time stamps with creation and expiration times.	0	0
APSC-DV-000180 - CAT II Applications with SOAP messages requiring integrity must include the following message elements:-Message ID-Service Request-Timestamp-SAML Assertion (optionally included in messages) and all elements of the message must be digitally signed.	0	0
APSC-DV-000200 - CAT I Validity periods must be verified on all application messages using WS-Security or SAML assertions.	0	0
APSC-DV-000210 - CAT II The application must ensure each unique asserting party provides unique assertion ID references for each SAML assertion.	0	0
APSC-DV-000220 - CAT II The application must ensure encrypted assertions, or equivalent confidentiality protections are used when assertion data is passed through an intermediary, and confidentiality of the assertion data is required when passing through the intermediary.	0	0
APSC-DV-000230 - CAT I The application must use the NotOnOrAfter condition when using the SubjectConfirmation element in a SAML assertion.	0	0
APSC-DV-000240 - CAT I The application must use both the NotBefore and NotOnOrAfter elements or OneTimeUse element when using the Conditions element in a SAML assertion.	0	0
APSC-DV-000250 - CAT II The application must ensure if a OneTimeUse element is used in an assertion, there is only one of the same used in the Conditions element portion of an assertion.	0	0
APSC-DV-000260 - CAT II The application must ensure messages are encrypted when the SessionIndex is tied to privacy data.	0	0
APSC-DV-000290 - CAT II Shared/group account credentials must be terminated when members leave the group.	0	0
APSC-DV-000280 - CAT II The application must provide automated mechanisms for supporting account management functions.	0	0
APSC-DV-000300 - CAT II The application must automatically remove or disable temporary user accounts 72 hours after account creation.	0	0
APSC-DV-000320 - CAT III The application must automatically disable accounts after a 35 day period of account inactivity.	0	0
APSC-DV-000330 - CAT II Unnecessary application accounts must be disabled, or deleted.	0	0
APSC-DV-000420 - CAT II The application must automatically audit account enabling actions.	0	0
APSC-DV-000340 - CAT II The application must automatically audit account creation.	0	0
APSC-DV-000350 - CAT II The application must automatically audit account modification.	0	0
APSC-DV-000360 - CAT II The application must automatically audit account disabling actions.	0	0
APSC-DV-000370 - CAT II The application must automatically audit account removal actions.	0	0
APSC-DV-000380 - CAT III The application must notify System Administrators and Information System Security Officers when accounts are created.	0	0
APSC-DV-000390 - CAT III The application must notify System Administrators and Information System Security Officers when accounts are modified.	0	0
APSC-DV-000400 - CAT III The application must notify System Administrators and Information System Security Officers of account disabling actions.	0	0
APSC-DV-000410 - CAT III The application must notify System Administrators and Information System Security Officers of account removal actions.	0	0
APSC-DV-000430 - CAT III The application must notify System Administrators and Information System Security Officers of account enabling actions.	0	0
APSC-DV-000440 - CAT II Application data protection requirements must be identified and documented.	0	0

APSC-DV-000520 - CAT II The application must audit the execution of privileged functions.	0	0
APSC-DV-000450 - CAT II The application must utilize organization-defined data mining detection techniques for organization-defined data storage objects to adequately detect data mining attempts.	0	0
APSC-DV-000460 - CAT I The application must enforce approved authorizations for logical access to information and system resources in accordance with applicable access control policies.	0	0
APSC-DV-000470 - CAT II The application must enforce organization-defined discretionary access control policies over defined subjects and objects.	0	0
APSC-DV-000480 - CAT II The application must enforce approved authorizations for controlling the flow of information within the system based on organization-defined information flow control policies.	0	0
APSC-DV-000490 - CAT II The application must enforce approved authorizations for controlling the flow of information between interconnected systems based on organization-defined information flow control policies.	0	0
APSC-DV-000500 - CAT II The application must prevent non-privileged users from executing privileged functions to include disabling, circumventing, or altering implemented security safeguards/countermeasures.	0	0
APSC-DV-000510 - CAT I The application must execute without excessive account permissions.	0	0
APSC-DV-000530 - CAT I The application must enforce the limit of three consecutive invalid logon attempts by a user during a 15 minute time period.	0	0
APSC-DV-000560 - CAT III The application must retain the Standard Mandatory DoD Notice and Consent Banner on the screen until users acknowledge the usage conditions and take explicit actions to log on for further access.	0	0
APSC-DV-000540 - CAT II The application administrator must follow an approved process to unlock locked user accounts.	0	0
APSC-DV-000550 - CAT III The application must display the Standard Mandatory DoD Notice and Consent Banner before granting access to the application.	0	0
APSC-DV-000570 - CAT III The publicly accessible application must display the Standard Mandatory DoD Notice and Consent Banner before granting access to the application.	0	0
APSC-DV-000580 - CAT III The application must display the time and date of the users last successful logon.	0	0
APSC-DV-000630 - CAT II The application must provide audit record generation capability for the destruction of session IDs.	0	0
APSC-DV-000590 - CAT II The application must protect against an individual (or process acting on behalf of an individual) falsely denying having performed organization-defined actions to be covered by non-repudiation.	0	0
APSC-DV-000600 - CAT II For applications providing audit record aggregation, the application must compile audit records from organization-defined information system components into a system-wide audit trail that is time-correlated with an organization-defined level of tolerance	0	0
APSC-DV-000610 - CAT II The application must provide the capability for organization-identified individuals or roles to change the auditing to be performed on all application components, based on all selectable event criteria within organization-defined time thresholds.	0	0
APSC-DV-000620 - CAT II The application must provide audit record generation capability for the creation of session IDs.	0	0

掃描總結 - ASD STIG 5.3

Category	Issues Found	Best Fix Locations
APSC-DV-000640 - CAT II The application must provide audit record generation capability for the renewal of session IDs.	0	0
APSC-DV-000650 - CAT II The application must not write sensitive data into the application logs.	0	0
APSC-DV-000660 - CAT II The application must provide audit record generation capability for session timeouts.	0	0
APSC-DV-000670 - CAT II The application must record a time stamp indicating when the event occurred.	0	0
APSC-DV-000680 - CAT II The application must provide audit record generation capability for HTTP headers including User-Agent, Referer, GET, and POST.	0	0
APSC-DV-000690 - CAT II The application must provide audit record generation capability for connecting system IP addresses.	0	0
APSC-DV-000700 - CAT II The application must record the username or user ID of the user associated with the event.	0	0
APSC-DV-000710 - CAT II The application must generate audit records when successful/unsuccessful attempts to grant privileges occur.	0	0
APSC-DV-000720 - CAT II The application must generate audit records when successful/unsuccessful attempts to access security objects occur.	0	0
APSC-DV-000730 - CAT II The application must generate audit records when successful/unsuccessful attempts to access security levels occur.	0	0
APSC-DV-000740 - CAT II The application must generate audit records when successful/unsuccessful attempts to access categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000750 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify privileges occur.	0	0
APSC-DV-000760 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify security objects occur.	0	0
APSC-DV-000770 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify security levels occur.	0	0
APSC-DV-000780 - CAT II The application must generate audit records when successful/unsuccessful attempts to modify categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000790 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete privileges occur.	0	0
APSC-DV-000800 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete security levels occur.	0	0
APSC-DV-000810 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete application database security objects occur.	0	0
APSC-DV-000820 - CAT II The application must generate audit records when successful/unsuccessful attempts to delete categories of information (e.g., classification levels) occur.	0	0
APSC-DV-000830 - CAT II The application must generate audit records when successful/unsuccessful logon attempts occur.	0	0
APSC-DV-000840 - CAT II The application must generate audit records for privileged activities or other system-level access.	0	0
APSC-DV-000850 - CAT II The application must generate audit records showing starting and ending time for user access to the system.	0	0
APSC-DV-000860 - CAT II The application must generate audit records when successful/unsuccessful accesses to objects occur.	0	0

APSC-DV-000870 - CAT II The application must generate audit records for all direct access to the information system.	0	0
APSC-DV-000880 - CAT II The application must generate audit records for all account creations, modifications, disabling, and termination events.	0	0
APSC-DV-000910 - CAT II The application must initiate session auditing upon startup.	0	0
APSC-DV-000940 - CAT II The application must log application shutdown events.	0	0
APSC-DV-000950 - CAT II The application must log destination IP addresses.	0	0
APSC-DV-000960 - CAT II The application must log user actions involving access to data.	0	0
APSC-DV-000970 - CAT II The application must log user actions involving changes to data.	0	0
APSC-DV-000980 - CAT II The application must produce audit records containing information to establish when (date and time) the events occurred.	0	0
APSC-DV-000990 - CAT II The application must produce audit records containing enough information to establish which component, feature or function of the application triggered the audit event.	0	0
APSC-DV-001000 - CAT II When using centralized logging; the application must include a unique identifier in order to distinguish itself from other application logs.	0	0
APSC-DV-001010 - CAT II The application must produce audit records that contain information to establish the outcome of the events.	0	0
APSC-DV-001020 - CAT II The application must generate audit records containing information that establishes the identity of any individual or process associated with the event.	0	0
APSC-DV-001030 - CAT II The application must generate audit records containing the full-text recording of privileged commands or the individual identities of group account users.	0	0
APSC-DV-001040 - CAT II The application must implement transaction recovery logs when transaction based.	0	0
APSC-DV-001050 - CAT II The application must provide centralized management and configuration of the content to be captured in audit records generated by all application components.	0	0
APSC-DV-001070 - CAT II The application must off-load audit records onto a different system or media than the system being audited.	0	0
APSC-DV-001080 - CAT II The application must be configured to write application logs to a centralized log repository.	0	0
APSC-DV-001090 - CAT II The application must provide an immediate warning to the SA and ISSO (at a minimum) when allocated audit record storage volume reaches 75% of repository maximum audit record storage capacity.	0	0
APSC-DV-001100 - CAT II Applications categorized as having a moderate or high impact must provide an immediate real-time alert to the SA and ISSO (at a minimum) for all audit failure events.	0	0
APSC-DV-001110 - CAT II The application must alert the ISSO and SA (at a minimum) in the event of an audit processing failure.	0	0
APSC-DV-001120 - CAT II The application must shut down by default upon audit failure (unless availability is an overriding concern).	0	0
APSC-DV-001130 - CAT II The application must provide the capability to centrally review and analyze audit records from multiple components within the system.	0	0
APSC-DV-001140 - CAT II The application must provide the capability to filter audit records for events of interest based upon organization-defined criteria.	0	0
APSC-DV-001150 - CAT II The application must provide an audit reduction capability that supports on-demand reporting requirements.	0	0
APSC-DV-001160 - CAT II The application must provide an audit reduction capability that supports on-demand audit review and analysis.	0	0
APSC-DV-001170 - CAT II The application must provide an audit reduction capability that supports after-the-fact investigations of security incidents.	0	0
APSC-DV-001180 - CAT II The application must provide a report generation capability that supports on-demand audit review and analysis.	0	0

APSC-DV-001190 - CAT II The application must provide a report generation capability that supports on-demand reporting requirements.	0	0
APSC-DV-001200 - CAT II The application must provide a report generation capability that supports after-the-fact investigations of security incidents.	0	0
APSC-DV-001210 - CAT II The application must provide an audit reduction capability that does not alter original content or time ordering of audit records.	0	0
APSC-DV-001220 - CAT II The application must provide a report generation capability that does not alter original content or time ordering of audit records.	0	0
APSC-DV-001250 - CAT II The applications must use internal system clocks to generate time stamps for audit records.	0	0
APSC-DV-001260 - CAT II The application must record time stamps for audit records that can be mapped to Coordinated Universal Time (UTC) or Greenwich Mean Time (GMT).	0	0
APSC-DV-001270 - CAT II The application must record time stamps for audit records that meet a granularity of one second for a minimum degree of precision.	0	0
APSC-DV-001280 - CAT II The application must protect audit information from any type of unauthorized read access.	0	0
APSC-DV-001290 - CAT II The application must protect audit information from unauthorized modification.	0	0
APSC-DV-001300 - CAT II The application must protect audit information from unauthorized deletion.	0	0
APSC-DV-001310 - CAT II The application must protect audit tools from unauthorized access.	0	0
APSC-DV-001320 - CAT II The application must protect audit tools from unauthorized modification.	0	0
APSC-DV-001330 - CAT II The application must protect audit tools from unauthorized deletion.	0	0
APSC-DV-001340 - CAT II The application must back up audit records at least every seven days onto a different system or system component than the system or component being audited.	0	0
APSC-DV-001570 - CAT II The application must electronically verify Personal Identity Verification (PIV) credentials.	0	0
APSC-DV-001350 - CAT II The application must use cryptographic mechanisms to protect the integrity of audit information.	0	0
APSC-DV-001360 - CAT II Application audit tools must be cryptographically hashed.	0	0
APSC-DV-001370 - CAT II The integrity of the audit tools must be validated by checking the files for changes in the cryptographic hash value.	0	0
APSC-DV-001390 - CAT II The application must prohibit user installation of software without explicit privileged status.	0	0
APSC-DV-001410 - CAT II The application must enforce access restrictions associated with changes to application configuration.	0	0
APSC-DV-001420 - CAT II The application must audit who makes configuration changes to the application.	0	0
APSC-DV-001430 - CAT II The application must have the capability to prevent the installation of patches, service packs, or application components without verification the software component has been digitally signed using a certificate that is recognized and approved by the orga	0	0
APSC-DV-001440 - CAT II The applications must limit privileges to change the software resident within software libraries.	0	0
APSC-DV-001460 - CAT II An application vulnerability assessment must be conducted.	0	0
APSC-DV-001480 - CAT II The application must prevent program execution in accordance with organization-defined policies regarding software program usage and restrictions, and/or rules authorizing the terms and conditions of software program usage.	0	0
APSC-DV-001490 - CAT II The application must employ a deny-all, permit-by-exception (whitelist) policy to allow the execution of authorized software programs.	0	0
APSC-DV-001500 - CAT II The application must be configured to disable non-essential capabilities.	0	0
APSC-DV-001510 - CAT II The application must be configured to use only functions, ports, and protocols permitted to it in the PPSM CAL.	0	0

APSC-DV-001520 - CAT II The application must require users to reauthenticate when organization-defined circumstances or situations require reauthentication.	0	0
APSC-DV-001530 - CAT II The application must require devices to reauthenticate when organization-defined circumstances or situations requiring reauthentication.	0	0
APSC-DV-001540 - CAT I The application must uniquely identify and authenticate organizational users (or processes acting on behalf of organizational users).	0	0
APSC-DV-001550 - CAT II The application must use multifactor (Alt. Token) authentication for network access to privileged accounts.	0	0
APSC-DV-001560 - CAT II The application must accept Personal Identity Verification (PIV) credentials.	0	0
APSC-DV-001580 - CAT II The application must use multifactor (e.g., CAC, Alt. Token) authentication for network access to non-privileged accounts.	0	0
APSC-DV-001590 - CAT II The application must use multifactor (Alt. Token) authentication for local access to privileged accounts.	0	0
APSC-DV-001600 - CAT II The application must use multifactor (e.g., CAC, Alt. Token) authentication for local access to non-privileged accounts.	0	0
APSC-DV-001610 - CAT II The application must ensure users are authenticated with an individual authenticator prior to using a group authenticator.	0	0
APSC-DV-001620 - CAT II The application must implement replay-resistant authentication mechanisms for network access to privileged accounts.	0	0
APSC-DV-001630 - CAT II The application must implement replay-resistant authentication mechanisms for network access to non-privileged accounts.	0	0
APSC-DV-001640 - CAT II The application must utilize mutual authentication when endpoint device non-repudiation protections are required by DoD policy or by the data owner.	0	0
APSC-DV-001650 - CAT II The application must authenticate all network connected endpoint devices before establishing any connection.	0	0
APSC-DV-001660 - CAT II Service-Oriented Applications handling non-releasable data must authenticate endpoint devices via mutual SSL/TLS.	0	0
APSC-DV-001670 - CAT II The application must disable device identifiers after 35 days of inactivity unless a cryptographic certificate is used for authentication.	0	0
APSC-DV-001680 - CAT I The application must enforce a minimum 15-character password length.	0	0
APSC-DV-001690 - CAT II The application must enforce password complexity by requiring that at least one upper-case character be used.	0	0
APSC-DV-001700 - CAT II The application must enforce password complexity by requiring that at least one lower-case character be used.	0	0
APSC-DV-001710 - CAT II The application must enforce password complexity by requiring that at least one numeric character be used.	0	0
APSC-DV-001720 - CAT II The application must enforce password complexity by requiring that at least one special character be used.	0	0
APSC-DV-001730 - CAT II The application must require the change of at least 8 of the total number of characters when passwords are changed.	0	0
APSC-DV-001740 - CAT I The application must only store cryptographic representations of passwords.	1	1
APSC-DV-001850 - CAT I The application must not display passwords/PINs as clear text.	0	0
APSC-DV-001750 - CAT I The application must transmit only cryptographically-protected passwords.	0	0
APSC-DV-001760 - CAT II The application must enforce 24 hours/1 day as the minimum password lifetime.	0	0
APSC-DV-001770 - CAT II The application must enforce a 60-day maximum password lifetime restriction.	0	0
APSC-DV-001780 - CAT II The application must prohibit password reuse for a minimum of five generations.	0	0
APSC-DV-001790 - CAT II The application must allow the use of a temporary password for system logons with an immediate change to a permanent password.	0	0

APSC-DV-001795 - CAT II The application password must not be changeable by users other than the administrator or the user with which the password is associated.	0	0
APSC-DV-001800 - CAT II The application must terminate existing user sessions upon account deletion.	0	0
APSC-DV-001820 - CAT I The application, when using PKI-based authentication, must enforce authorized access to the corresponding private key.	0	0
APSC-DV-001830 - CAT II The application must map the authenticated identity to the individual user or group account for PKI-based authentication.	0	0
APSC-DV-001870 - CAT II The application must uniquely identify and authenticate non-organizational users (or processes acting on behalf of non-organizational users).	0	0
APSC-DV-001810 - CAT I The application, when utilizing PKI-based authentication, must validate certificates by constructing a certification path (which includes status information) to an accepted trust anchor.	0	0
APSC-DV-001840 - CAT II The application, for PKI-based authentication, must implement a local cache of revocation data to support path discovery and validation in case of the inability to access revocation information via the network.	0	0
APSC-DV-001860 - CAT II The application must use mechanisms meeting the requirements of applicable federal laws, Executive Orders, directives, policies, regulations, standards, and guidance for authentication to a cryptographic module.	0	0
APSC-DV-001880 - CAT II The application must accept Personal Identity Verification (PIV) credentials from other federal agencies.	0	0
APSC-DV-001890 - CAT II The application must electronically verify Personal Identity Verification (PIV) credentials from other federal agencies.	0	0
APSC-DV-002050 - CAT II Applications making SAML assertions must use FIPS-approved random numbers in the generation of SessionIndex in the SAML element AuthnStatement.	0	0
APSC-DV-001900 - CAT II The application must accept FICAM-approved third-party credentials.	0	0
APSC-DV-001910 - CAT II The application must conform to FICAM-issued profiles.	0	0
APSC-DV-001930 - CAT II Applications used for non-local maintenance sessions must audit non-local maintenance and diagnostic sessions for organization-defined auditable events.	0	0
APSC-DV-000310 - CAT III The application must have a process, feature or function that prevents removal or disabling of emergency accounts.	0	0
APSC-DV-001940 - CAT II Applications used for non-local maintenance sessions must implement cryptographic mechanisms to protect the integrity of non-local maintenance and diagnostic communications.	0	0
APSC-DV-001950 - CAT II Applications used for non-local maintenance sessions must implement cryptographic mechanisms to protect the confidentiality of non-local maintenance and diagnostic communications.	0	0
APSC-DV-001960 - CAT II Applications used for non-local maintenance sessions must verify remote disconnection at the termination of non-local maintenance and diagnostic sessions.	0	0
APSC-DV-001970 - CAT II The application must employ strong authenticators in the establishment of non-local maintenance and diagnostic sessions.	0	0
APSC-DV-001980 - CAT II The application must terminate all sessions and network connections when non-local maintenance is completed.	0	0
APSC-DV-001995 - CAT II The application must not be vulnerable to race conditions.	0	0
APSC-DV-002000 - CAT II The application must terminate all network connections associated with a communications session at the end of the session.	0	0
APSC-DV-002010 - CAT II The application must implement NSA-approved cryptography to protect classified information in accordance with applicable federal laws, Executive Orders, directives, policies, regulations, and standards.	0	0
APSC-DV-002020 - CAT II The application must utilize FIPS-validated cryptographic modules when signing application components.	0	0
APSC-DV-002030 - CAT II The application must utilize FIPS-validated cryptographic modules when generating cryptographic hashes.	0	0

APSC-DV-002040 - CAT II The application must utilize FIPS-validated cryptographic modules when protecting unclassified information that requires cryptographic protection.	0	0
APSC-DV-002150 - CAT II The application user interface must be either physically or logically separated from data storage and management interfaces.	0	0
APSC-DV-002210 - CAT II The application must set the HTTPOnly flag on session cookies.*	0	0
APSC-DV-002220 - CAT II The application must set the secure flag on session cookies.	0	0
APSC-DV-002230 - CAT I The application must not expose session IDs.*	0	0
APSC-DV-002240 - CAT I The application must destroy the session ID value and/or cookie on logoff or browser close.	0	0
APSC-DV-002250 - CAT II Applications must use system-generated session identifiers that protect against session fixation.	0	0
APSC-DV-002260 - CAT II Applications must validate session identifiers.	0	0
APSC-DV-002270 - CAT II Applications must not use URL embedded session IDs.	0	0
APSC-DV-002280 - CAT II The application must not re-use or recycle session IDs.	0	0
APSC-DV-002290 - CAT II The application must use the Federal Information Processing Standard (FIPS) 140-2-validated cryptographic modules and random number generator if the application implements encryption, key exchange, digital signature, and hash functionality.	0	0
APSC-DV-002300 - CAT II The application must only allow the use of DoD-approved certificate authorities for verification of the establishment of protected sessions.	0	0
APSC-DV-002310 - CAT I The application must fail to a secure state if system initialization fails, shutdown fails, or aborts fail.	0	0
APSC-DV-002320 - CAT II In the event of a system failure, applications must preserve any information necessary to determine cause of failure and any information necessary to return to operations with least disruption to mission processes.	0	0
APSC-DV-002330 - CAT II The application must protect the confidentiality and integrity of stored information when required by DoD policy or the information owner.	60	47
APSC-DV-002340 - CAT II The application must implement approved cryptographic mechanisms to prevent unauthorized modification of organization-defined information at rest on organization-defined information system components.	0	0
APSC-DV-002350 - CAT II The application must use appropriate cryptography in order to protect stored DoD information when required by the information owner or DoD policy.	0	0
APSC-DV-002360 - CAT II The application must isolate security functions from non-security functions.	0	0
APSC-DV-002370 - CAT II The application must maintain a separate execution domain for each executing process.	0	0
APSC-DV-002380 - CAT II Applications must prevent unauthorized and unintended information transfer via shared system resources.	0	0
APSC-DV-002390 - CAT II XML-based applications must mitigate DoS attacks by using XML filters, parser options, or gateways.	0	0
APSC-DV-002400 - CAT II The application must restrict the ability to launch Denial of Service (DoS) attacks against itself or other information systems.	1	1
APSC-DV-002410 - CAT II The web service design must include redundancy mechanisms when used with high-availability systems.	0	0
APSC-DV-002420 - CAT II An XML firewall function must be deployed to protect web services when exposed to untrusted networks.	0	0
APSC-DV-002610 - CAT II The application must remove organization-defined software components after updated versions have been installed.	0	0
APSC-DV-002440 - CAT I The application must protect the confidentiality and integrity of transmitted information.	0	0
APSC-DV-002450 - CAT II The application must implement cryptographic mechanisms to prevent unauthorized disclosure of information and/or detect changes to information during transmission unless otherwise protected by alternative physical safeguards, such as, at a minimum, a Prot	0	0

APSC-DV-002460 - CAT II The application must maintain the confidentiality and integrity of information during preparation for transmission.	0	0
APSC-DV-002470 - CAT II The application must maintain the confidentiality and integrity of information during reception.	0	0
APSC-DV-002480 - CAT II The application must not disclose unnecessary information to users.	0	0
APSC-DV-002485 - CAT I The application must not store sensitive information in hidden fields.	0	0
APSC-DV-002490 - CAT I The application must protect from Cross-Site Scripting (XSS) vulnerabilities.*	1	1
APSC-DV-002500 - CAT II The application must protect from Cross-Site Request Forgery (CSRF) vulnerabilities.	0	0
APSC-DV-002510 - CAT I The application must protect from command injection.	0	0
APSC-DV-002520 - CAT II The application must protect from canonical representation vulnerabilities.	0	0
APSC-DV-002530 - CAT II The application must validate all input.	5	2
APSC-DV-002540 - CAT I The application must not be vulnerable to SQL Injection.*	0	0
APSC-DV-002550 - CAT I The application must not be vulnerable to XML-oriented attacks.	0	0
APSC-DV-002560 - CAT I The application must not be subject to input handling vulnerabilities.*	7	4
APSC-DV-002570 - CAT II The application must generate error messages that provide information necessary for corrective actions without revealing information that could be exploited by adversaries.*	41	41
APSC-DV-002580 - CAT II The application must reveal error messages only to the ISSO, ISSM, or SA.	0	0
APSC-DV-002590 - CAT I The application must not be vulnerable to overflow attacks.	31	10
APSC-DV-002630 - CAT II Security-relevant software updates and patches must be kept up to date.	0	0
APSC-DV-002760 - CAT II The application performing organization-defined security functions must verify correct operation of security functions.	0	0
APSC-DV-002900 - CAT II The ISSO must ensure application audit trails are retained for at least 1 year for applications without SAMI data, and 5 years for applications including SAMI data.	0	0
APSC-DV-002770 - CAT II The application must perform verification of the correct operation of security functions: upon system startup and/or restart; upon command by a user with privileged access; and/or every 30 days.	0	0
APSC-DV-002780 - CAT III The application must notify the ISSO and ISSM of failed security verification tests.	0	0
APSC-DV-002870 - CAT II Unsigned Category 1A mobile code must not be used in the application in accordance with DoD policy.	0	0
APSC-DV-002880 - CAT II The ISSO must ensure an account management process is implemented, verifying only authorized users can gain access to the application, and individual accounts designated as inactive, suspended, or terminated are promptly removed.	0	0
APSC-DV-002890 - CAT I Application web servers must be on a separate network segment from the application and database servers if it is a tiered application operating in the DoD DMZ.	0	0
APSC-DV-002910 - CAT II The ISSO must review audit trails periodically based on system documentation recommendations or immediately upon system security events.	0	0
APSC-DV-002920 - CAT II The ISSO must report all suspected violations of IA policies in accordance with DoD information system IA procedures.	0	0
APSC-DV-002930 - CAT II The ISSO must ensure active vulnerability testing is performed.	0	0
APSC-DV-002980 - CAT II New IP addresses, data services, and associated ports used by the application must be submitted to the appropriate approving authority for the organization, which in turn will be submitted through the DoD Ports, Protocols, and Services Management (DoD PPS	0	0
APSC-DV-002950 - CAT II Execution flow diagrams and design documents must be created to show how deadlock and recursion issues in web services are being mitigated.	0	0
APSC-DV-002960 - CAT II The designer must ensure the application does not store configuration and control files in the same directory as user data.	0	0
APSC-DV-002970 - CAT II The ISSO must ensure if a DoD STIG or NSA guide is not available, a third-party	0	0

product will be configured by following available guidance.		
APSC-DV-002990 - CAT II The application must be registered with the DoD Ports and Protocols Database.	0	0
APSC-DV-002995 - CAT II The Configuration Management (CM) repository must be properly patched and STIG compliant.	0	0
APSC-DV-003000 - CAT II Access privileges to the Configuration Management (CM) repository must be reviewed every three months.	0	0
APSC-DV-003010 - CAT II A Software Configuration Management (SCM) plan describing the configuration control and change management process of application objects developed by the organization and the roles and responsibilities of the organization must be created and maintained.	0	0
APSC-DV-003020 - CAT II A Configuration Control Board (CCB) that meets at least every release cycle, for managing the Configuration Management (CM) process must be established.	0	0
APSC-DV-003030 - CAT II The application services and interfaces must be compatible with and ready for IPv6 networks.	0	0
APSC-DV-003040 - CAT II The application must not be hosted on a general purpose machine if the application is designated as critical or high availability by the ISSO.	0	0
APSC-DV-003050 - CAT II A disaster recovery/continuity plan must exist in accordance with DoD policy based on the applications availability requirements.	0	0
APSC-DV-003060 - CAT II Recovery procedures and technical system features must exist so recovery is performed in a secure and verifiable manner. The ISSO will document circumstances inhibiting a trusted recovery.	0	0
APSC-DV-003070 - CAT II Data backup must be performed at required intervals in accordance with DoD policy.	0	0
APSC-DV-003080 - CAT II Back-up copies of the application software or source code must be stored in a fire-rated container or stored separately (offsite).	0	0
APSC-DV-003090 - CAT II Procedures must be in place to assure the appropriate physical and technical protection of the backup and restoration of the application.	0	0
APSC-DV-003100 - CAT II The application must use encryption to implement key exchange and authenticate endpoints prior to establishing a communication channel for key exchange.	0	0
APSC-DV-003110 - CAT I The application must not contain embedded authentication data.	0	0
APSC-DV-003120 - CAT I The application must have the capability to mark sensitive/classified output when required.	0	0
APSC-DV-003130 - CAT III Prior to each release of the application, updates to system, or applying patches; tests plans and procedures must be created and executed.	0	0
APSC-DV-003150 - CAT II At least one tester must be designated to test for security flaws in addition to functional testing.	0	0
APSC-DV-003140 - CAT II Application files must be cryptographically hashed prior to deploying to DoD operational networks.	0	0
APSC-DV-003160 - CAT III Test procedures must be created and at least annually executed to ensure system initialization, shutdown, and aborts are configured to verify the system remains in a secure state.	0	0
APSC-DV-003170 - CAT II An application code review must be performed on the application.	0	0
APSC-DV-003180 - CAT III Code coverage statistics must be maintained for each release of the application.	0	0
APSC-DV-003190 - CAT II Flaws found during a code review must be tracked in a defect tracking system.	0	0
APSC-DV-003200 - CAT II The changes to the application must be assessed for IA and accreditation impact prior to implementation.	0	0
APSC-DV-003210 - CAT II Security flaws must be fixed or addressed in the project plan.	0	0
APSC-DV-003215 - CAT III The application development team must follow a set of coding standards.	0	0
APSC-DV-003220 - CAT III The designer must create and update the Design Document for each release of the application.	0	0
APSC-DV-003230 - CAT II Threat models must be documented and reviewed for each application release	0	0

and updated as required by design and functionality changes or when new threats are discovered.		
APSC-DV-003235 - CAT II The application must not be subject to error handling vulnerabilities.*	0	0
APSC-DV-003250 - CAT I The application must be decommissioned when maintenance or support is no longer available.	0	0
APSC-DV-003236 - CAT II The application development team must provide an application incident response plan.	0	0
APSC-DV-003240 - CAT I All products must be supported by the vendor or the development team.	0	0
APSC-DV-003260 - CAT III Procedures must be in place to notify users when an application is decommissioned.	0	0
APSC-DV-003270 - CAT II Unnecessary built-in application accounts must be disabled.	0	0
APSC-DV-003280 - CAT I Default passwords must be changed.	0	0
APSC-DV-003330 - CAT II The system must alert an administrator when low resource conditions are encountered.	0	0
APSC-DV-003285 - CAT II An Application Configuration Guide must be created and included with the application.	0	0
APSC-DV-003290 - CAT II If the application contains classified data, a Security Classification Guide must exist containing data elements and their classification.	0	0
APSC-DV-003300 - CAT II The designer must ensure uncategorized or emerging mobile code is not used in applications.	0	0
APSC-DV-003310 - CAT II Production database exports must have database administration credentials and sensitive data removed before releasing the export.	0	0
APSC-DV-003320 - CAT II Protections against DoS attacks must be implemented.	0	0
APSC-DV-003340 - CAT III At least one application administrator must be registered to receive update notifications, or security alerts, when automated alerts are available.	0	0
APSC-DV-003360 - CAT III The application must generate audit records when concurrent logons from different workstations occur.	0	0
APSC-DV-003345 - CAT III The application must provide notifications or alerts when product update and security related patches are available.	0	0
APSC-DV-003350 - CAT II Connections between the DoD enclave and the Internet or other public or commercial wide area networks must require a DMZ.	0	0
APSC-DV-003400 - CAT II The Program Manager must verify all levels of program management, designers, developers, and testers receive annual security training pertaining to their job function.	0	0
APSC-DV-000010 - CAT II The application must provide a capability to limit the number of logon sessions per user.	0	0
APSC-DV-000060 - CAT II The application must clear temporary storage and cookies when the session is terminated.	0	0
APSC-DV-000070 - CAT II The application must automatically terminate the non-privileged user session and log off non-privileged users after a 15 minute idle time period has elapsed.	0	0
APSC-DV-000080 - CAT II The application must automatically terminate the admin user session and log off admin users after a 10 minute idle time period is exceeded.	0	0
APSC-DV-000090 - CAT II Applications requiring user access authentication must provide a logoff capability for user initiated communication session.	0	0
APSC-DV-000100 - CAT III The application must display an explicit logoff message to users indicating the reliable termination of authenticated communications sessions.	0	0
APSC-DV-000110 - CAT II The application must associate organization-defined types of security attributes having organization-defined security attribute values with information in storage.	0	0
APSC-DV-000120 - CAT II The application must associate organization-defined types of security attributes having organization-defined security attribute values with information in process.	0	0
APSC-DV-000130 - CAT II The application must associate organization-defined types of security attributes having organization-defined security attribute values with information in transmission.	0	0

APSC-DV-000160 - CAT II The application must implement DoD-approved encryption to protect the confidentiality of remote access sessions.	0	0
APSC-DV-000170 - CAT II The application must implement cryptographic mechanisms to protect the integrity of remote access sessions.	0	0
APSC-DV-000190 - CAT I Messages protected with WS_Security must use time stamps with creation and expiration times.	0	0
APSC-DV-000180 - CAT II Applications with SOAP messages requiring integrity must include the following message elements:-Message ID-Service Request-Timestamp-SAML Assertion (optionally included in messages) and all elements of the message must be digitally signed.	0	0
APSC-DV-000200 - CAT I Validity periods must be verified on all application messages using WS-Security or SAML assertions.	0	0
APSC-DV-000210 - CAT II The application must ensure each unique asserting party provides unique assertion ID references for each SAML assertion.	0	0
APSC-DV-000220 - CAT II The application must ensure encrypted assertions, or equivalent confidentiality protections are used when assertion data is passed through an intermediary, and confidentiality of the assertion data is required when passing through the intermediary.	0	0
APSC-DV-000230 - CAT I The application must use the NotOnOrAfter condition when using the SubjectConfirmation element in a SAML assertion.	0	0
APSC-DV-000240 - CAT I The application must use both the NotBefore and NotOnOrAfter elements or OneTimeUse element when using the Conditions element in a SAML assertion.	0	0
APSC-DV-000250 - CAT II The application must ensure if a OneTimeUse element is used in an assertion, there is only one of the same used in the Conditions element portion of an assertion.	0	0
APSC-DV-000260 - CAT II The application must ensure messages are encrypted when the SessionIndex is tied to privacy data.	0	0
APSC-DV-000290 - CAT II Shared/group account credentials must be terminated when members leave the group.	0	0
APSC-DV-000280 - CAT II The application must provide automated mechanisms for supporting account management functions.	0	0
APSC-DV-000300 - CAT II The application must automatically remove or disable temporary user accounts 72 hours after account creation.	0	0
APSC-DV-000320 - CAT III The application must automatically disable accounts after a 35 day period of account inactivity.	0	0
APSC-DV-000330 - CAT II Unnecessary application accounts must be disabled, or deleted.	0	0
APSC-DV-000420 - CAT II The application must automatically audit account enabling actions.	0	0
APSC-DV-000340 - CAT II The application must automatically audit account creation.	0	0
APSC-DV-000350 - CAT II The application must automatically audit account modification.	0	0
APSC-DV-000360 - CAT II The application must automatically audit account disabling actions.	0	0
APSC-DV-000370 - CAT II The application must automatically audit account removal actions.	0	0
APSC-DV-000380 - CAT III The application must notify System Administrators and Information System Security Officers when accounts are created.	0	0
APSC-DV-000390 - CAT III The application must notify System Administrators and Information System Security Officers when accounts are modified.	0	0
APSC-DV-000400 - CAT III The application must notify System Administrators and Information System Security Officers of account disabling actions.	0	0
APSC-DV-000410 - CAT III The application must notify System Administrators and Information System Security Officers of account removal actions.	0	0
APSC-DV-000430 - CAT III The application must notify System Administrators and Information System Security Officers of account enabling actions.	0	0
APSC-DV-000440 - CAT II Application data protection requirements must be identified and documented.	0	0
APSC-DV-000520 - CAT II The application must audit the execution of privileged functions.	0	0

APSC-DV-000450 - CAT II The application must utilize organization-defined data mining detection techniques for organization-defined data storage objects to adequately detect data mining attempts.	0	0
APSC-DV-000460 - CAT I The application must enforce approved authorizations for logical access to information and system resources in accordance with applicable access control policies.*	0	0
APSC-DV-000470 - CAT II The application must enforce organization-defined discretionary access control policies over defined subjects and objects.*	0	0
APSC-DV-000480 - CAT II The application must enforce approved authorizations for controlling the flow of information within the system based on organization-defined information flow control policies.	0	0
APSC-DV-000490 - CAT II The application must enforce approved authorizations for controlling the flow of information between interconnected systems based on organization-defined information flow control policies.	0	0
APSC-DV-000500 - CAT II The application must prevent non-privileged users from executing privileged functions to include disabling, circumventing, or altering implemented security safeguards/countermeasures.	0	0
APSC-DV-000510 - CAT I The application must execute without excessive account permissions.	0	0
APSC-DV-000530 - CAT I The application must enforce the limit of three consecutive invalid logon attempts by a user during a 15 minute time period.	0	0
APSC-DV-000560 - CAT III The application must retain the Standard Mandatory DoD Notice and Consent Banner on the screen until users acknowledge the usage conditions and take explicit actions to log on for further access.	0	0
APSC-DV-000540 - CAT II The application administrator must follow an approved process to unlock locked user accounts.	0	0
APSC-DV-000550 - CAT III The application must display the Standard Mandatory DoD Notice and Consent Banner before granting access to the application.	0	0
APSC-DV-000570 - CAT III The publicly accessible application must display the Standard Mandatory DoD Notice and Consent Banner before granting access to the application.	0	0
APSC-DV-000580 - CAT III The application must display the time and date of the users last successful logon.	0	0
APSC-DV-000630 - CAT II The application must provide audit record generation capability for the destruction of session IDs.	0	0
APSC-DV-000590 - CAT II The application must protect against an individual (or process acting on behalf of an individual) falsely denying having performed organization-defined actions to be covered by non-repudiation.	0	0
APSC-DV-000600 - CAT II For applications providing audit record aggregation, the application must compile audit records from organization-defined information system components into a system-wide audit trail that is time-correlated with an organization-defined level of tolerance	0	0
APSC-DV-000610 - CAT II The application must provide the capability for organization-identified individuals or roles to change the auditing to be performed on all application components, based on all selectable event criteria within organization-defined time thresholds.	0	0
APSC-DV-000620 - CAT II The application must provide audit record generation capability for the creation of session IDs.	0	0

***** 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Top 10 2010

Category	Issues Found	Best Fix Locations
A1-Injection	0	0
A2-Cross-Site Scripting (XSS)	0	0
A3-Broken Authentication and Session Management*	0	0
A4-Insecure Direct Object References	0	0
A5-Cross-Site Request Forgery (CSRF)	0	0
A6-Security Misconfiguration	0	0
A7-Insecure Cryptographic Storage	0	0
A8-Failure to Restrict URL Access	0	0
A9-Insufficient Transport Layer Protection	0	0
A10-Unvalidated Redirects and Forwards	0	0

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - OWASP Top 10 API 2023

Category	Issues Found	Best Fix Locations
API1-Broken Object Level Authorization	0	0
API2-Broken Authentication	1	1
API3-Broken Object Property Level Authorization*	2	2
API4-Unrestricted Resource Consumption	6	3
API5-Broken Function Level Authorization	0	0
API6-Unrestricted Access to Sensitive Business Flows	0	0
API7-Server Side Request Forgery	0	0
API8-Security Misconfiguration*	341	341
API9-Improper Inventory Management	0	0
API10-Unsafe Consumption of APIs	0	0

***** 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - MOIS(KISA) Secure Coding 2021

Category	Issues Found	Best Fix Locations
MOIS(KISA) API misuse*	0	0
MOIS(KISA) Code error*	0	0
MOIS(KISA) Encapsulation*	0	0
MOIS(KISA) Error processing*	41	41
MOIS(KISA) Security Functions*	47	32
MOIS(KISA) Time and status*	0	0
MOIS(KISA) Verification and representation of input data*	64	22

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - SANS top 25

Category	Issues Found	Best Fix Locations
SANS top 25*	98	43

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - CWE top 25

Category	Issues Found	Best Fix Locations
CWE top 25*	98	43

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - Top Tier

Category	Issues Found	Best Fix Locations
Top Tier	0	0

掃描總結 - OWASP ASVS

Category	Issues Found	Best Fix Locations
V01 Architecture, Design and Threat Modeling*	300	300
V02 Authentication*	7	7
V03 Session Management*	2	2
V04 Access Control	17	17
V05 Validation, Sanitization and Encoding*	63	21
V06 Stored Cryptography*	1	1
V07 Error Handling and Logging*	551	548
V08 Data Protection*	46	46
V09 Communication*	8	6
V10 Malicious Code	14	1
V11 Business Logic*	0	0
V12 Files and Resources*	1	1
V13 API and Web Service	0	0
V14 Configuration*	365	365

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - ASA Mobile Premium

Category	Issues Found	Best Fix Locations
ASA Mobile Premium*	8	5

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - ASA Premium

Category	Issues Found	Best Fix Locations
ASA Premium*	73	54

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描總結 - Base Preset

Category	Issues Found	Best Fix Locations
Base Preset*	14	1

* 專案掃描結果不包括所有相關的查詢。應該變更預設和/或篩選器以包括所有相關的標準查詢。

掃描結果分佈

與2026/3/4 下午 04:40的專案掃描比較

	高風險	中風險	低風險	資訊	總共
新問題	0	23	520	850	1,393
反覆出現的問題	0	0	0	0	0
總共	0	23	520	850	1,393
已修復的問題	0	0	0	0	0



掃描結果分佈

	高風險	中風險	低風險	資訊	總共
校驗	0	23	520	850	1,393
不可利用	0	0	0	0	0
確認	0	0	0	0	0
緊急	0	0	0	0	0
推薦不可用	0	0	0	0	0
總共	0	23	520	850	1,393

掃描結果摘要

漏洞類別	事件	嚴重程度：
Privacy Violation	14	中風險
Unchecked Input for Loop Condition	5	中風險
Excessive Data Exposure	2	中風險
CGI Stored XSS	1	中風險
ReDoS From Regex Injection	1	中風險

Spring Overly Permissive Cross Origin Resource Sharing Policy	323	低風險
Heap Inspection	46	低風險
Improper Exception Handling	40	低風險
Integer Overflow	31	低風險
Integer Underflow	31	低風險
Incorrect Permission Assignment For Critical Resources	17	低風險
Serializable Class Containing Sensitive Data	8	低風險
Log Forging	7	低風險
Use of Non Cryptographic Random	6	低風險
Portability Flaw Locale Dependent Comparison	3	低風險
Reversible One Way Hash	2	低風險
Information Exposure Through an Error Message	1	低風險
Off by One Error	1	低風險
Spring Missing Content Security Policy	1	低風險
Stored Log Forging	1	低風險
TruffleHog Regex Matches	1	低風險
Use Of Hardcoded Password	1	低風險
Insufficient Logging of Exceptions	533	資訊
Undocumented API	300	資訊
Insufficient Logging of Database Actions	10	資訊
Portability Flaw In File Separator	7	資訊

10個最容易受攻擊的檔案

高級和中級漏洞

檔案名稱	找到的問題
uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java	14
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/BaseDepService.java	10
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/cmn/AccountApiHelper.java	9
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java	4
uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	4
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java	4
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java	3
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java	2
uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java	2

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java	2

掃描結果詳細資料

Privacy Violation

查詢路徑:

Java\Cx\Java Medium Threat\Privacy Violation 版本:14

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.1 - Injection flaws - particularly SQL injection
OWASP Top 10 2013: A6-Sensitive Data Exposure
FISMA 2014: Identification And Authentication
NIST SP 800-53: SC-4 Information in Shared Resources (P1)
OWASP Top 10 2017: A3-Sensitive Data Exposure
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V10 Malicious Code
OWASP Top 10 2021: A1-Broken Access Control
SANS top 25: SANS top 25
ASA Premium: ASA Premium
ASD STIG 5.3: APSC-DV-002330 - CAT II The application must protect the confidentiality and integrity of stored information when required by DoD policy or the information owner.
Base Preset: Base Preset
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Privacy Violation\路徑 1:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=5
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java 的181 行的 findAaArrAccountId 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	181	66
物件	accountNo	TxnException

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java
方法	private String findAaArrAccountId(String arrangementId, String accountNo, String currency) {

```
....
181.  MidMessageUtils.raiseTxError(CodeEnum.DEP00108, accountNo,
currency);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 2:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=6
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java 的83 行的validateSingleTransferAccount 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	83	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java

方法 private AccountBean validateSingleTransferAccount(String accountNo, String currency, boolean isTwd) {

```
....
83.  private AccountBean validateSingleTransferAccount(String accountNo,
String currency, boolean isTwd) {
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 3:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=7
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java 的213 行的 readAccountBalance 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	213	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java

方法 public ServiceRs<AccountBalanceRs> readAccountBalance(@NotBlank(message = "查詢帳號不可為空") String accountNo, @NotBlank(message = "查詢幣別不可為空") String currency, @NotBlank(message = "查詢理由不可為空") String queryReason, String hrFlag) {

```
....
213.  public ServiceRs<AccountBalanceRs>
readAccountBalance(@NotBlank(message = "查詢帳號不可為空") String
accountNo, @NotBlank(message = "查詢幣別不可為空") String currency,
@NotBlank(message = "查詢理由不可為空") String queryReason, String hrFlag)
{
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 4:

嚴重程度：	中風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=8
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java 的261 行的 readAccountBalance 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	261	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java

方法 public ServiceRs<AccountBalanceRs> readAccountBalance(@NotBlank(message = "查詢帳號不可為空") String accountNo, @NotBlank(message = "查詢幣別不可為空") String currency, @NotBlank(message = "查詢理由不可為空") String queryReason, String hrFlag) {

```
....
261.  String aaArrAccountId = findAaArrAccountId(aaArrangement.getId(),
accountNo, currency);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 5:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=9
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java 的278 行的 readAccountBalance 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	278	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/BalanceService.java

方法 public ServiceRs<AccountBalanceRs> readAccountBalance(@NotBlank(message = "查詢帳號不可為空") String accountNo, @NotBlank(message = "查詢幣別不可為空") String currency, @NotBlank(message = "查詢理由不可為空") String queryReason, String hrFlag) {

```
....
278.  aaArrAccountId = findAaArrAccountId(arrangementId, accountNo,
currency);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 6:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=10
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java的105 行的validateSingleTransferAccount 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	105	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java

方法 private AccountBean validateSingleTransferAccount(String accountNo, String currency, boolean isTwd) {

```
....
105.  accountBean = getAccountDetailsByAccountNo(accountNo, currency);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 7:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=11
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java的123 行的validateSingleTransferAccount 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	123	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/ptf/BasePtfService.java

方法 private AccountBean validateSingleTransferAccount(String accountNo, String currency, boolean isTwd) {

```
....
123.  accountBean = getAccountDetailsByAccountNo(accountNo, "");
```

檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
方法	public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 8:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=12
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java 的338 行的 printInterestPaid 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	338	66
物件	accountNo	TxnException

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java
方法	public ServiceRs<ReportDataRs> printInterestPaid(@NotNull(message = "查詢帳號不可為空") String accountNo, LocalDate startDate, LocalDate endDate) throws Throwable {

```
....
338.  public ServiceRs<ReportDataRs> printInterestPaid(@NotNull(message
= "查詢帳號不可為空") String accountNo, LocalDate startDate, LocalDate
endDate) throws Throwable {
```

檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
方法	public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 9:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=13
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java 的65 行的 validate 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	65	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java

方法 private void validate(ApplyPasswordArg arg) {

```
....
65.  validateAccount(accountNo, pazzwordType);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 10:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=14
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java 的84 行的 validate 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	84	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/ApplyPasswordService.java

方法 private void validate(ApplyPasswordNs20Arg arg) {

```
....
84.  validateAccount(customerNo, accountNo, pazzwordType);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 11:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=15
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java 的140 行的 convertActiveEventsToRs 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	140	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java

方法	private List<EventQueryDetails> convertActiveEventsToRs(String accountNo, List<AccountActiveEventsResponseBody.ScsbEventCodes> scsbEventCodesList, Map<String, String> branchMap) {

```
....
140.  private List<EventQueryDetails> convertActiveEventsToRs(String
accountNo, List<AccountActiveEventsResponseBody.ScsbEventCodes>
scsbEventCodesList, Map<String, String> branchMap) {
```

檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
方法	public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 12:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=16
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java 的170 行的 convertEventsLogToRs 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	170	66
物件	accountNo	TxnException

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/event/EventService.java
方法	private List<EventQueryDetails> convertEventsLogToRs(String accountNo, List<AccountEventsLogResponseBody.ScsbEventCodes> scsbEventCodesList, Map<String, String> branchMap) {

```
....
170.  private List<EventQueryDetails> convertEventsLogToRs(String
accountNo, List<AccountEventsLogResponseBody.ScsbEventCodes>
scsbEventCodesList, Map<String, String> branchMap) {
```

檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
方法	public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 13:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=17
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java 的345 行的 printInterestPaid 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	345	66
物件	accountNo	TxnException

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillDetailService.java
方法	public ServiceRs<ReportDataRs> printInterestPaid(@NotNull(message = "查詢帳號不可為空") String accountNo, LocalDate startDate, LocalDate endDate) throws Throwable {

```
....
345.  SCSBCustomerResponseBody customerResponseBody =
getCustomerDetailsByAccountNo(accountNo);
```

檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
方法	public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Privacy Violation\路徑 14:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=18
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/BaseDepService.java 的147 行的getCustomerDetailsByAccountNo 方法將使用者敏感資訊發送到應用程式外部。 這可能構成隱私侵犯。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/BaseDepService.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java
行	147	66
物件	accountNo	TxnException

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/BaseDepService.java

方法 public SCSBCustomerResponseBody getCustomerDetailsByAccountNo(String accountNo) {

```
....
147.  String branchCode = getAccountCompany(accountNo);
```

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/utils/MidMessageUtils.java

方法 public static void raiseTxError(IReturnCodeDescEnum codeEnum, Object... args) {

```
....
66.  throw new TxnException(codeEnum, args);
```

Unchecked Input for Loop Condition

查詢路徑:

Java\Cx\Java Medium Threat\Unchecked Input for Loop Condition 版本:6

類別

OWASP Top 10 API: API4-Lack of Resources and Rate Limiting
OWASP Top 10 2021: A3-Injection
ASA Premium: ASA Premium
ASD STIG 5.3: APSC-DV-002530 - CAT II The application must validate all input.
OWASP Top 10 API 2023: API4-Unrestricted Resource Consumption
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Unchecked Input for Loop Condition\路徑 1:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=19
狀態	新的
Detection Date	1/23/2026 6:44:38 PM

方法readAccountBalance在uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 第52 行，從元素apiRequest 取得使用者輸入。該元素的值流經程式碼沒有被驗證，並最終於uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java 的第816 行processMissingDailyBalToMonthlyAvgBal 方法，用於迴圈條件中。這構成一個未經檢查迴圈條件(Unchecked Input for Loop Condition)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java
行	52	816
物件	apiRequest	arg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java

方法 public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java

方法 private Map<String, BigDecimal> processMissingDailyBalToMonthlyAvgBal(List<DailyBalanceBean> dailyBalanceBeanList, AccountArg arg) {

```
....
816.  while (arg.getBaselineDate().isBefore(endDate) && currentIteration
< maxIterations) {
```

Unchecked Input for Loop Condition\路徑 2:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=20
狀態	新的

Detection Date	1/23/2026 6:44:38 PM

方法readAccountBalance在uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 第52 行，從元素 apiRequest 取得使用者輸入。該元素的值流經程式碼沒有被驗證，並最終於uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java 的第816 行 processMissingDailyBalToMonthlyAvgBal 方法，用於迴圈條件中。這構成一個未經檢查迴圈條件(Unchecked Input for Loop Condition)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java
行	52	816
物件	apiRequest	endDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java

方法 public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java

方法 private Map<String, BigDecimal> processMissingDailyBalToMonthlyAvgBal(List<DailyBalanceBean> dailyBalanceBeanList, AccountArg arg) {

```
....
816.  while (arg.getBaselineDate().isBefore(endDate) && currentIteration
< maxIterations) {
```

Unchecked Input for Loop Condition\路徑 3:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=21
狀態	新的
Detection Date	1/23/2026 6:44:38 PM

方法readAccountBalance在uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 第52 行，從元素 apiRequest 取得使用者輸入。該元素的值流經程式碼沒有被驗證，並最終於uatFiles/ncbs-mid-repo-

p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java 的第642 行 getMonthlyAvgBalanceFromDB 方法，用於迴圈條件中。這構成一個未經檢查迴圈條件(Unchecked Input for Loop Condition)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java
行	52	642
物件	apiRequest	queryEndDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java

方法 public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java

方法 private Map<String, BigDecimal> getMonthlyAvgBalanceFromDB(AccountBean accountBean, AccountArg arg) {

```
....
642.  while (baselineDate.isBefore(queryEndDate) && currentIteration <
maxIterations) {
```

Unchecked Input for Loop Condition\路徑 4:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=22
狀態	新的
Detection Date	1/23/2026 6:44:38 PM

方法readAccountBalance在uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 第52 行，從元素 apiRequest 取得使用者輸入。該元素的值流經程式碼沒有被驗證，並最終於uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java 的第642 行 getMonthlyAvgBalanceFromDB 方法，用於迴圈條件中。這構成一個未經檢查迴圈條件(Unchecked Input for Loop Condition)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-	uatFiles/ncbs-mid-repo-p2/dep/dep-

	app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java
行	52	642
物件	apiRequest	baselineDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java

方法 public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/account/AccountService.java

方法 private Map<String, BigDecimal> getMonthlyAvgBalanceFromDB(AccountBean accountBean, AccountArg arg) {

```
....
642.  while (baselineDate.isBefore(queryEndDate) && currentIteration <
maxIterations) {
```

Unchecked Input for Loop Condition\路徑 5:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=23
狀態	新的
Detection Date	3/5/2026 10:19:28 AM

方法read在uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java 第48 行，從元素apiRequest 取得使用者輸入。該元素的值流經程式碼沒有被驗證，並最終於uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java 的第75 行getScsbCustomerDailyThreQuota 方法，用於迴圈條件中。這構成一個未經檢查迴圈條件(Unchecked Input for Loop Condition)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java
行	48	75
物件	apiRequest	totalPages

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java

方法 public ApiResponse<ServiceRs<BranchFxSettlementReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchFxSettlementReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java

方法 public List<SCSBCustomerDailyThreQuotaResponseBody> getScsbCustomerDailyThreQuota(BaseL20035Arg arg, int pageSize) {

```
....
75.  for (int page = 0; page < totalPages; page++) {
```

Excessive Data Exposure

查詢路徑:

Java\Cx\Java Medium Threat\Excessive Data Exposure 版本:6

類別

OWASP ASVS: V03 Session Management
OWASP Top 10 2021: A1-Broken Access Control
OWASP Top 10 API 2023: API3-Broken Object Property Level Authorization
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Excessive Data Exposure\路徑 1:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=2
狀態	新的
Detection Date	1/23/2026 6:44:10 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 的第 132 行中的 rs 內的資料可能是敏感的。通過位於 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 的第 132 行中的rs 中的API 來暴露上述敏感資訊。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

行	132	132
物件	rs	rs

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702CreditPagingRs>> queryCredit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
132.  return ApiResponseBuilder.success(ServiceRsBuilder.success(rs));
```

Excessive Data Exposure\路徑 2:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=3
狀態	新的
Detection Date	12/19/2025 4:49:25 PM

uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/txnb/TxnbController.java 的第 106 行中的 arg 內的資料可能是敏感的。通過位於 uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/txnb/TxnbController.java 的第 106 行中的arg 中的API 來暴露上述敏感資訊。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/txnb/TxnbController.java	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/txnb/TxnbController.java
行	106	106
物件	arg	arg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/txnb/TxnbController.java

方法 public ApiResponse<ServiceRs<Nb04Rs>> nb04(@RequestBody ApiRequest<ServiceRq<Nb04Rq>> apiRequest) {

```
....
106.  return ApiResponseBuilder.success(nb04Service.create(arg));
```

CGI Stored XSS

查詢路徑:

Java\Cx\Java Medium Threat\CGI Stored XSS 版本:11

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.7 - Cross-site scripting (XSS)
OWASP Top 10 2013: A3-Cross-Site Scripting (XSS)
FISMA 2014: System And Information Integrity
NIST SP 800-53: SI-15 Information Output Filtering (P0)
OWASP Top 10 2017: A7-Cross-Site Scripting (XSS)
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Verification and representation of input data
OWASP ASVS: V05 Validation, Sanitization and Encoding
OWASP Top 10 2021: A3-Injection
SANS top 25: SANS top 25
ASD STIG 5.3: APSC-DV-002490 - CAT I The application must protect from Cross-Site Scripting (XSS) vulnerabilities.
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

CGI Stored XSS\路徑 1:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=1
狀態	新的
Detection Date	12/19/2025 4:49:20 PM

方法base64ToPdf在uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java的第110行使用BinaryExpr將不受信任的資料嵌入生成的輸出。這些不受信任的資料被嵌入輸出而沒有進行適當的消毒或編碼，使攻擊者能夠將惡意程式碼注入生成的網頁。
攻擊者可以透過事先儲存惡意的數值，來改變輸出資料。接著，攻擊者的修改資料會被 base64ToPdf 方法使用 getAbsolutePath 在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java 的第 110 行從儲存的位置讀取。這個不受信任的資料接著隨著程式碼，在未經過濾的情況下，即輸出至控制台或標準輸出。在某些情況下，這個輸出還會傳送至使用者的瀏覽器。如果程式碼的控制台輸出被應用程式用作網頁的一部分，如 CGI script 常見的情況，這可能會導致儲存型跨站腳本攻擊 (Stored Cross-Site Scripting, XSS)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java
行	110	110
物件	getAbsolutePath	BinaryExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java

方法 protected String base64ToPdf(String base64Content, String fileName) {

```
....
110.  System.out.println("PDF 文件已生成: " +
outputFile.getAbsolutePath());
```

ReDoS From Regex Injection

查詢路徑:

Java\Cx\Java Medium Threat\ReDoS From Regex Injection 版本:4

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.1 - Injection flaws - particularly SQL injection
OWASP Top 10 2013: A1-Injection
FISMA 2014: Identification And Authentication
NIST SP 800-53: SC-5 Denial of Service Protection (P1)
OWASP Top 10 2017: A1-Injection
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Verification and representation of input data
OWASP ASVS: V12 Files and Resources
OWASP Top 10 2021: A3-Injection
SANS top 25: SANS top 25
ASD STIG 5.3: APSC-DV-002400 - CAT II The application must restrict the ability to launch Denial of Service (DoS) attacks against itself or other information systems.
OWASP Top 10 API 2023: API4-Unrestricted Resource Consumption
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

ReDoS From Regex Injection\路徑 1:

嚴重程度：	中風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=4
狀態	新的
Detection Date	3/5/2026 10:19:27 AM

應用程式在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/TimeDepController.java 中第 91 行使用了使用者輸入 apiRequest，作為用於搜尋和比較與位於 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillService.java 第 1074 行的 mcySubAccountBean 相關資料的正規表示式型樣的一部分。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/TimeDepController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillService.java
行	91	1074
物件	apiRequest	mcySubAccountBean

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/TimeDepController.java
方法	public ApiResponse<ServiceRs<List<ApplicationFormInfoRs>>> readApplicationForm(@RequestBody ApiRequest<ServiceRq<TdbReadRq>> apiRequest) {

```
....
91.  public ApiResponse<ServiceRs<List<ApplicationFormInfoRs>>>
readApplicationForm(@RequestBody ApiRequest<ServiceRq<TdbReadRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/TimeDepBillService.java

方法 private List<ApplicationFormInfoRs> getApplicationFormInfoRs(

```
....
1074.
dep0018Rs.setAlternateAccountId(MidStringUtils.replace(mainAccountBean.g
etAlternateAccountId(), mcySubAccountBean.getCurrency(), ""));
```

Spring Overly Permissive Cross Origin Resource Sharing Policy

查詢路徑:

Java\Cx\Java Spring\Spring Overly Permissive Cross Origin Resource Sharing Policy 版本:2

類別

OWASP ASVS: V14 Configuration
OWASP Top 10 2021: A7-Identification and Authentication Failures
OWASP Top 10 API 2023: API8-Security Misconfiguration
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=220
狀態	新的
Detection Date	3/5/2026 10:20:11 AM

uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/controller/MidHealthController.java 文件第 24 行上的 health 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/controller/MidHealthController.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/controller/MidHealthController.java
行	24	24
物件	health	health

代碼片斷

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/controller/MidHealthController.java

方法	public String health() {

```
....
24.  public String health() {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=221
狀態	新的
Detection Date	3/5/2026 10:20:11 AM

uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java 文件第 22 行上的 send 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java
行	22	22
物件	send	send

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java
方法	ApiResponse<ServiceRs<MessageRs>> send(URI baseURI, @RequestBody ApiRequest<ServiceRq<MessageRq>> apiRequest);

```
....
22.  ApiResponse<ServiceRs<MessageRs>> send(URI baseURI, @RequestBody
ApiRequest<ServiceRq<MessageRq>> apiRequest);
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=222
狀態	新的
Detection Date	3/5/2026 10:20:11 AM

uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java 文件第 42 行上的 send 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-	uatFiles/ncbs-mid-foundation-repo-p2/mid-

	integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java	integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java
行	42	42
物件	send	send

代碼片斷

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java

方法 public ApiResponse<ServiceRs<MessageRs>> send(@RequestBody ApiRequest<ServiceRq<MessageRq>> apiRequest) {

```
....
42.  public ApiResponse<ServiceRs<MessageRs>> send(@RequestBody
ApiRequest<ServiceRq<MessageRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=223
狀態	新的
Detection Date	3/5/2026 10:20:11 AM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java 文件第 48 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java
行	48	48
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java

方法 public ApiResponse<ServiceRs<BranchDataInquiryReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchDataInquiryReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchDataInquiryReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchDataInquiryReadRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 5:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=224
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java 文件第 48 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java
行	48	48
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java

方法 public ApiResponse<ServiceRs<BranchFxSettlementReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchFxSettlementReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=225
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 59 行上的 create 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	59	59
物件	create	create

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
方法	public ApiResponse<ServiceRs<CbrDataModCreateRs>> create(@RequestBody ApiRequest<ServiceRq<CbrDataModCreateRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<CbrDataModCreateRs>>
create(@RequestBody ApiRequest<ServiceRq<CbrDataModCreateRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=226
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 73 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	73	73
物件	read	read

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
方法	public ApiResponse<ServiceRs<CbrDataModReadRs>> read(@RequestBody ApiRequest<ServiceRq<CbrDataModReadRq>> apiRequest) {

```
....
73.  public ApiResponse<ServiceRs<CbrDataModReadRs>> read(@RequestBody
ApiRequest<ServiceRq<CbrDataModReadRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=227
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 87 行上的 update 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	87	87
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<CbrDataModUpdateRs>> update(@RequestBody ApiRequest<ServiceRq<CbrDataModUpdateRq>> apiRequest) {

```
....
87.  public ApiResponse<ServiceRs<CbrDataModUpdateRs>>
update(@RequestBody ApiRequest<ServiceRq<CbrDataModUpdateRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=228
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 101 行上的 delete 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	101	101
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<CbrDataModDeleteRq>> apiRequest) {

```
....
101.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<CbrDataModDeleteRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 10:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=229
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 115 行上的 reject 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	115	115
物件	reject	reject

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> reject(@RequestBody ApiRequest<ServiceRq<CbrDataModRejectRq>> apiRequest) {

```
....
115.  public ApiResponse<ServiceRs<EmptyRs>> reject(@RequestBody
ApiRequest<ServiceRq<CbrDataModRejectRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=230
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java 文件第 129 行上的 amend 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controll	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controll

	er/data/CbrDataModController.java	er/data/CbrDataModController.java
行	129	129
物件	amend	amend

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
方法 public ApiResponse<ServiceRs<CbrDataModAmendRs>> amend(@RequestBody ApiRequest<ServiceRq<CbrDataModAmendRq>> apiRequest) {

```
....
129.  public ApiResponse<ServiceRs<CbrDataModAmendRs>>
amend(@RequestBody ApiRequest<ServiceRq<CbrDataModAmendRq>> apiRequest)
{
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 12:

嚴重程度： 低風險
結果狀態： 校驗
線上結果 http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=231
狀態 新的
Detection Date 9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java 文件第 28 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java
行	28	28
物件	read	read

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java
方法 ApiResponse<ServiceRs<BdayNextReadRs>> read(@RequestBody ApiRequest<ServiceRq<BdayNextReadRq>> apiRequest);

```
....
28.  ApiResponse<ServiceRs<BdayNextReadRs>> read(@RequestBody
ApiRequest<ServiceRq<BdayNextReadRq>> apiRequest);
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 13:

嚴重程度： 低風險
結果狀態： 校驗
線上結果 http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=232
狀態	新的
Detection Date	1/8/2026 10:17:19 AM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java 文件第 37 行上的 create 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java
行	37	37
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java

方法 public ApiResponse<?> create(@RequestBody ApiRequest<ServiceRq<EcifLogCreateRq>> apiRequest) {

```
....
37.  public ApiResponse<?> create(@RequestBody
ApiRequest<ServiceRq<EcifLogCreateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=233
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 53 行上的 create 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	53	53
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法	public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<NtfEmailVerCreateRq>> apiRequest) {

```
....
53.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerCreateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=234
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 60 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	60	60
物件	read	read

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
方法	public ApiResponse<ServiceRs<NtfEmailVerReadRs>> read(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadRq>> apiRequest) {

```
....
60.  public ApiResponse<ServiceRs<NtfEmailVerReadRs>> read(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerReadRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=235
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 67 行上的 reverify 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	67	67
物件	reverify	reverify

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> reverify(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReverifyRq>> apiRequest) {

```
....
67.  public ApiResponse<ServiceRs<EmptyRs>> reverify(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerReverifyRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 17:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=236
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 74 行上的 update 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	74	74
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<NtfEmailVerUpdateRq>> apiRequest) {

```
....
74.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerUpdateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 18:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=237
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 81 行上的 delete 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	81	81
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<NtfEmailVerDeleteRq>> apiRequest) {

```
....
81.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerDeleteRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 19:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=238
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java 文件第 88 行上的 readStatus 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	88	88
物件	readStatus	readStatus

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
方法	public ApiResponse<ServiceRs<NtfEmailVerReadStatusRs>> readStatus(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadStatusRq>> apiRequest) {

```
....
88.  public ApiResponse<ServiceRs<NtfEmailVerReadStatusRs>>
readStatus(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadStatusRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 20:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=239
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java 文件第 51 行上的 create 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	51	51
物件	create	create

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
方法	public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<TextCodeDescCreateRq>> apiRequest) {

```
....
51.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<TextCodeDescCreateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 21:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=240
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java 文件第 58 行上的 update 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	58	58
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<TextCodeDescUpdateRq>> apiRequest) {

```
....
58.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<TextCodeDescUpdateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 22:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=241
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java 文件第 65 行上的 delete 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	65	65
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法	public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<TextCodeDescDeleteRq>> apiRequest) {

```
....
65.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<TextCodeDescDeleteRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 23:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=242
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java 文件第 72 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	72	72
物件	read	read

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
方法	public ApiResponse<ServiceRs<TextCodeDescReadRs>> read(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadRq>> apiRequest) {

```
....
72.  public ApiResponse<ServiceRs<TextCodeDescReadRs>> read(@RequestBody
ApiRequest<ServiceRq<TextCodeDescReadRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 24:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=243
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java 文件第 79 行上的 readList 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	79	79
物件	readList	readList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法 public ApiResponse<ServiceRs<TextCodeDescReadListRs>> readList(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadListRq>> apiRequest) {

```
....
79.  public ApiResponse<ServiceRs<TextCodeDescReadListRs>>
readList(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadListRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 25:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=244
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java 文件第 50 行上的 create 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	50	50
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateCreateRq>> apiRequest) {

```
....
50.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateCreateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 26:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=245
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java 文件第 58 行上的 read 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	58	58
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<IntRateProjectRelateReadRs>> read(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadRq>> apiRequest) {

```
....
58.  public ApiResponse<ServiceRs<IntRateProjectRelateReadRs>>
read(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 27:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=246
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java 文件第 66 行上的 update 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	66	66
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateUpdateRq>> apiRequest) {

```
....
66.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateUpdateRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 28:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=247
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java 文件第 74 行上的 delete 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	74	74
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateDeleteRq>> apiRequest) {

```
....
74.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateDeleteRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 29:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=248
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java 文件第 82 行上的 readList 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	82	82
物件	readList	readList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<IntRateProjectRelateReadListRs>> readList(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadListRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<IntRateProjectRelateReadListRs>>
readList(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateReadListRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 30:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=249
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java 文件第 22 行上的 daccProcess 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java
行	22	22
物件	daccProcess	daccProcess

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java

方法 public ApiResponse<ServiceRs<MarketingPreferencesRs>> daccProcess(@RequestBody ApiRequest<ServiceRq<DepDaccProcessRq>> rq);

```
....
22.  public ApiResponse<ServiceRs<MarketingPreferencesRs>>
daccProcess(@RequestBody ApiRequest<ServiceRq<DepDaccProcessRq>> rq);
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 31:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=250
狀態	新的
Detection Date	12/19/2025 4:53:39 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java 文件第 20 行上的 notifyCalypso 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java
行	20	20
物件	notifyCalypso	notifyCalypso

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java

方法 public ApiResponse<ServiceRs<Cim11NotifyRs>> notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>> rq);

```
....
20.  public ApiResponse<ServiceRs<Cim11NotifyRs>>
notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>> rq);
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 32:

嚴重程度： 低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=251
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 文件第 52 行上的 readAccountBalance 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
行	52	52
物件	readAccountBalance	readAccountBalance

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java

方法 public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 33:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=252
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java 文件第 70 行上的 readBalance 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
行	70	70
物件	readBalance	readBalance

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
方法	public ApiResponse<ServiceRs<AccountBalanceRs>> readBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
70.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 34:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=253
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java 文件第 59 行上的 query 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java
行	59	59
物件	query	query

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java
方法	public ApiResponse<ServiceRs<Customer3702Rs>> query(@RequestBody ApiRequest<ServiceRq<CustomerRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<Customer3702Rs>> query(@RequestBody
ApiRequest<ServiceRq<CustomerRq>> apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 35:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=254
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 59 行上的 queryPaging 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	59	59
物件	queryPaging	queryPaging

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702PagingRs>> queryPaging(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<Customer3702PagingRs>>
queryPaging(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 36:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=255
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 67 行上的 querySpecialMsg 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	67	67
物件	querySpecialMsg	querySpecialMsg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法	public ApiResponse<ServiceRs<Customer3702SpecialMsgPagingRs>> querySpecialMsg(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
67.  public ApiResponse<ServiceRs<Customer3702SpecialMsgPagingRs>>
querySpecialMsg(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 37:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=256
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 77 行上的 queryDep 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	77	77
物件	queryDep	queryDep

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
方法	public ApiResponse<ServiceRs<Customer3702DepPagingRs>> queryDep(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
77.  public ApiResponse<ServiceRs<Customer3702DepPagingRs>>
queryDep(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 38:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=257
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 87 行上的 queryLoan 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	87	87
物件	queryLoan	queryLoan

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702LoanPagingRs>> queryLoan(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
87.  public ApiResponse<ServiceRs<Customer3702LoanPagingRs>>
queryLoan(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 39:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=258
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 97 行上的 queryGuarantor 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	97	97
物件	queryGuarantor	queryGuarantor

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法	public ApiResponse<ServiceRs<Customer3702GuarantorPagingRs>> queryGuarantor(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
97.  public ApiResponse<ServiceRs<Customer3702GuarantorPagingRs>>
queryGuarantor(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 40:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=259
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 107 行上的 queryLimit 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	107	107
物件	queryLimit	queryLimit

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
方法	public ApiResponse<ServiceRs<Customer3702LimitPagingRs>> queryLimit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
107.  public ApiResponse<ServiceRs<Customer3702LimitPagingRs>>
queryLimit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 41:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=260
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 117 行上的 queryBill 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	117	117
物件	queryBill	queryBill

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702BillPagingRs>> queryBill(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<Customer3702BillPagingRs>>
queryBill(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 42:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=261
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 127 行上的 queryCredit 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	127	127
物件	queryCredit	queryCredit

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法	public ApiResponse<ServiceRs<Customer3702CreditPagingRs>> queryCredit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
127.  public ApiResponse<ServiceRs<Customer3702CreditPagingRs>>
queryCredit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 43:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=262
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 137 行上的 queryBond 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	137	137
物件	queryBond	queryBond

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
方法	public ApiResponse<ServiceRs<Customer3702BondPagingRs>> queryBond(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
137.  public ApiResponse<ServiceRs<Customer3702BondPagingRs>>
queryBond(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 44:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=263
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 147 行上的 queryCompany 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	147	147
物件	queryCompany	queryCompany

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702CompanyPagingRs>> queryCompany(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
147.  public ApiResponse<ServiceRs<Customer3702CompanyPagingRs>>
queryCompany(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 45:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=264
狀態	新的
Detection Date	1/23/2026 6:48:38 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java 文件第 157 行上的 queryObu 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	157	157
物件	queryObu	queryObu

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法	public ApiResponse<ServiceRs<Customer3702ObuPagingRs>> queryObu(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
157.  public ApiResponse<ServiceRs<Customer3702ObuPagingRs>>
queryObu(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 46:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=265
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java 文件第 52 行上的 process1554 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	52	52
物件	process1554	process1554

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
方法	public ApiResponse<ServiceRs<CrrRecordsRs>> process1554(@RequestBody ApiRequest<ServiceRq<CrrRecordsRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<CrrRecordsRs>>
process1554(@RequestBody ApiRequest<ServiceRq<CrrRecordsRq>> apiRequest)
{
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 47:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=266
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java 文件第 65 行上的 readCharge 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	65	65
物件	readCharge	readCharge

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<List<ChargeStatusInfoRs>>> readCharge(@RequestBody ApiRequest<ServiceRq<CrrReadChargeRq>> apiRequest) {

```
....
65.  public ApiResponse<ServiceRs<List<ChargeStatusInfoRs>>>
readCharge(@RequestBody ApiRequest<ServiceRq<CrrReadChargeRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 48:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=267
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java 文件第 77 行上的 readChargeDetail 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	77	77
物件	readChargeDetail	readChargeDetail

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<CrrReadChargeDetailRs>> readChargeDetail(@RequestBody ApiRequest<ServiceRq<CrrReadChargeDetail>> apiRequest) {

```
....
77.  public ApiResponse<ServiceRs<CrrReadChargeDetailRs>>
readChargeDetail(@RequestBody ApiRequest<ServiceRq<CrrReadChargeDetail>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 49:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=268
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java 文件第 89 行上的 createCharge 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	89	89
物件	createCharge	createCharge

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<ChargeStatusInfoRs>> createCharge(@RequestBody ApiRequest<ServiceRq<CrrCreateChargeRq>> apiRequest) {

```
....
89.  public ApiResponse<ServiceRs<ChargeStatusInfoRs>>
createCharge(@RequestBody ApiRequest<ServiceRq<CrrCreateChargeRq>>
apiRequest) {
```

Spring Overly Permissive Cross Origin Resource Sharing Policy\路徑 50:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=269
狀態	新的
Detection Date	9/22/2025 6:07:39 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java 文件第 101 行上的 reverseCharge 方法設置了過度寬鬆的 CORS 訪問控制來源標頭。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	101	101
物件	reverseCharge	reverseCharge

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法	public ApiResponse<ServiceRs<ChargeStatusInfoRs>> reverseCharge(@RequestBody ApiRequest<ServiceRq<CrrReverseChargeRq>> apiRequest) {

```
....
101.  public ApiResponse<ServiceRs<ChargeStatusInfoRs>>
reverseCharge(@RequestBody ApiRequest<ServiceRq<CrrReverseChargeRq>>
apiRequest) {
```

Heap Inspection

查詢路徑:

Java\Cx\Java Low Visibility\Heap Inspection 版本:9

類別

OWASP Top 10 2013: A6-Sensitive Data Exposure
OWASP ASVS: V08 Data Protection
OWASP Top 10 2021: A2-Cryptographic Failures
ASA Premium: ASA Premium
ASD STIG 5.3: APSC-DV-002330 - CAT II The application must protect the confidentiality and integrity of stored information when required by DoD policy or the information owner.

描述

Heap Inspection\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=64
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java第358行的processPasswordForNtfButypes方法定義了 password，其中包含user passwords。雖然plaintext passwords 稍後assign給password，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java
行	358	358
物件	password	password

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java
方法	private void processPasswordForNtfButypes(NtfMessageCreateArg arg) {

```
....
358.  String password = (custId.length() == 10 || custId.length() == 8)
? custIdSubstring : MidStringUtils.EMPTY;
```

Heap Inspection\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=65
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java第26行的createSSLContext方法定義了 keyPassword，其中包含user passwords。雖然plaintext passwords 稍後assign給keyPassword，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java
行	26	26
物件	keyPassword	keyPassword

代碼片斷

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java

方法 public SSLContext createSSLContext() throws GeneralSecurityException, IOException {

```
....
26.  char[] keyPassword =
properties.getKeyStorePassword().toCharArray();
```

Heap Inspection\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=66
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java第63行的createKeyStore方法定義了 keyStorePassword，其中包含user passwords。雖然plaintext passwords 稍後assign給keyStorePassword，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java

行	63	63
物件	keyStorePassword	keyStorePassword

代碼片斷

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-foundation-parent/mid-foundation-core/src/main/java/com/scsb/ncbs/core/ssl/SslContextFactory.java

方法 public KeyStore createKeyStore() throws GeneralSecurityException, IOException {

```
....
63.  char[] keyStorePassword =
properties.getKeyStorePassword().toCharArray();
```

Heap Inspection\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=67
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/balance/BalanceQueryService.java第77行的query方法定義了 passwordNs20Arg，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordNs20Arg，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/balance/BalanceQueryService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/balance/BalanceQueryService.java
行	77	77
物件	passwordNs20Arg	passwordNs20Arg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/balance/BalanceQueryService.java

方法 public ServiceRs<BalanceQueryRs> query(@Valid BalanceQueryArg arg) {

```
....
77.  VerifyPasswordNs20Arg passwordNs20Arg = new
VerifyPasswordNs20Arg();
```

Heap Inspection\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=68
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java第133行的validatePassword方法定義了 depQueryPasswordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給depQueryPasswordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java
行	133	133
物件	depQueryPasswordEntity	depQueryPasswordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java

方法 protected boolean validatePassword(String customerNo, String accountNo, String pazzwordType, String sessionKey, String password) {

```
....
133.  DepQueryPasswordEntity depQueryPasswordEntity = optional.get();
```

Heap Inspection\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=69
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java第152行的validatePassword方法定義了 depQueryPasswordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給depQueryPasswordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java
行	152	152
物件	depQueryPasswordEntity	depQueryPasswordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java

方法 protected boolean validatePassword(String accountNo, String pazzwordType, String sessionKey, String password) {

```
....
152.  DepQueryPasswordEntity depQueryPasswordEntity = optional.get();
```

Heap Inspection\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=70
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java第653行的saveLogDB方法定義了 passwordLogEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordLogEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java
行	653	653
物件	passwordLogEntity	passwordLogEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java

方法 protected void saveLogDB(DepQueryPasswordEntity passwordEntity) {

```
....
653.  DepQueryPasswordLogEntity passwordLogEntity = new
DepQueryPasswordLogEntity();
```

Heap Inspection\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=71
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java第677行的cancelDB方法定義了 passwordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/servi	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/servi

	ce/query/password/BasePasswordService.java	ce/query/password/BasePasswordService.java
行	677	677
物件	passwordEntity	passwordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java

方法 protected void cancelDB(String accountNo, String pazzwordType) {

```
....
677.  DepQueryPasswordEntity passwordEntity = optional.get();
```

Heap Inspection\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=72
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java第700行的cancelDB方法定義了 passwordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java
行	700	700
物件	passwordEntity	passwordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/password/BasePasswordService.java

方法 protected void cancelDB(String customerNo, String accountNo, String pazzwordType) {

```
....
700.  DepQueryPasswordEntity passwordEntity = optional.get();
```

Heap Inspection\路徑 10:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=73
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/registeredaccount/RegisteredAccountService.java第88行的querytwd方法定義了 passwordArg，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordArg，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/registeredaccount/RegisteredAccountService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/registeredaccount/RegisteredAccountService.java
行	88	88
物件	passwordArg	passwordArg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/registeredaccount/RegisteredAccountService.java

方法 public ServiceRs<RegisteredAccountTwdRs> querytwd(@Valid RegisteredAccountTwdArg arg) {

```
....
88.  VerifyPasswordArg passwordArg = new VerifyPasswordArg();
```

Heap Inspection\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=74
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/statement/StatementQueryService.java第104行的query方法定義了 passwordArg，其中包含user passwords。雖然plaintext passwords 稍後assign給passwordArg，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/statement/StatementQueryService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/statement/StatementQueryService.java
行	104	104
物件	passwordArg	passwordArg

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/statement/StatementQueryService.java
方法	public ServiceRs<StatementQueryRs> query(@Valid StatementQueryArg arg) {

```
....
104.  VerifyPasswordArg passwordArg = new VerifyPasswordArg();
```

Heap Inspection\路徑 12:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=75
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第70行的maintainPassbook方法定義了 passbookStatus，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookStatus，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	70	70
物件	passbookStatus	passbookStatus

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
方法	public MaintainPassbookRs maintainPassbook(MaintainPassbookArg arg) {

```
....
70.  String passbookStatus = arg.getPssbkStatus();
```

Heap Inspection\路徑 13:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=76
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第90行的

maintainNoPassbook方法定義了 passbookStatus，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookStatus，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	90	90
物件	passbookStatus	passbookStatus

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java

方法 public MaintainPassbookRs maintainNoPassbook(MaintainPassbookArg arg) {

```
....
90.  String passbookStatus = arg.getPssbkStatus();
```

Heap Inspection\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=77
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第132行的validatePassbook方法定義了 passbookRef，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRef，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	132	132
物件	passbookRef	passbookRef

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java

方法 private void validatePassbook(String passbookStatus, String newPassbook, AccountBean t24Account, String supervisorAId, String supervisorBId) {

```
....
132.  String passbookRef = t24Account.getScsbPassbookReq();
```

Heap Inspection\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=78
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/PassbookStatusService.java第58行的validate方法定義了 passbookReq，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookReq，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/PassbookStatusService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/PassbookStatusService.java
行	58	58
物件	passbookReq	passbookReq

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/PassbookStatusService.java

方法 private void validate(String accountNo, String passbookStatus, AccountBean t24Account) {

```
....
58.  String passbookReq = t24Account.getScsbPassbookReq();
```

Heap Inspection\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=79
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java第179行的validate方法定義了 passbookLine，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLine，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/servi	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/servi

	ce/query/printpassbook/FcTermDepositService.java	ce/query/printpassbook/FcTermDepositService.java
行	179	179
物件	passbookLine	passbookLine

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void validate(FcTermDepositArg arg) {

```
....
179.  String passbookLine = arg.getPazzbookLine();
```

Heap Inspection\路徑 17:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=80
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java第36行的process方法定義了 passbookLine，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLine，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java
行	36	36
物件	passbookLine	passbookLine

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java

方法 public ServiceRs<PassbookLineRs> process(String actNo, String pazzbookNo) {

```
....
36.  String passbookLine = "";
```

Heap Inspection\路徑 18:

嚴重程度：	低風險
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=81
狀態	新的
Detection Date	1/23/2026 6:45:29 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java第44行的process方法定義了 passbookLineM，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLineM，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java
行	44	44
物件	passbookLineM	passbookLineM

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java

方法 public ServiceRs<PassbookLineRs> process(String actNo, String pazzbookNo) {

```
....
44.  String passbookLineM = "";
```

Heap Inspection\路徑 19:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=82
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java第174行的validate方法定義了 passbookLine，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLine，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	174	174
物件	passbookLine	passbookLine

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
方法	private void validate(TwCompositeDepositArg arg) {

```
....
174.  String passbookLine = arg.getPazzbookLine();
```

Heap Inspection\路徑 20:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=83
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java第170行的validate方法定義了 passbookLine，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLine，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	170	170
物件	passbookLine	passbookLine

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
方法	private void validate(TwSmallDepositArg arg) {

```
....
170.  String passbookLine = arg.getPazzbookLine();
```

Heap Inspection\路徑 21:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=84
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java第174行的

validate方法定義了 passbookLine，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLine，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	174	174
物件	passbookLine	passbookLine

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void validate(TwTermDepositArg arg) {

```
....
174.  String passbookLine = arg.getPazzbookLine();
```

Heap Inspection\路徑 22:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=85
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java第68行的maintainPassbook方法定義了 passbookStatus，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookStatus，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java
行	68	68
物件	passbookStatus	passbookStatus

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java

方法 public MaintainPassbookRs maintainPassbook(MaintainPassbookArg arg) {

```
....
68.  String passbookStatus = arg.getPssbkStatus();
```

Heap Inspection\路徑 23:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=86
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java第105行的validatePassbook方法定義了 passbookRef，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRef，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java
行	105	105
物件	passbookRef	passbookRef

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java

方法 private void validatePassbook(String passbookStatus, String newPassbook, AccountBean t24Account, String supervisorAId, String supervisorBId) {

```
....
105.  String passbookRef = t24Account.getScsbPassbookReq();
```

Heap Inspection\路徑 24:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=87
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java第136行的getAccountTxnNotOnPassbook方法定義了 passbookRecordOpt，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRecordOpt，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java
行	136	136

物件	passbookRecordOpt	passbookRecordOpt

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java
方法 public List<StmtAccountTxnBean> getAccountTxnNotOnPassbook(String accountId, String accountNo) {

```
....
136.  Optional<DepPassbookRecordEntity> passbookRecordOpt =
passbookRecordRepository.readFirstByAccountNoOrderByCreatedTimestampDesc
(accountNo);
```

Heap Inspection\路徑 25:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=88
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第371行的updatePassbookDB方法定義了 passbookEntityOpt，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntityOpt，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	371	371
物件	passbookEntityOpt	passbookEntityOpt

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
方法 private Long updatePassbookDB(String accountNo, String newPassbook, String oldPassbook, String funType) {

```
....
371.  Optional<DepQueryPassbookEntity> passbookEntityOpt =
passbookRepository.readByAccountNo(accountNo);
```

Heap Inspection\路徑 26:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=89
狀態	新的
Detection Date	1/13/2026 2:21:33 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第372行的updatePassbookDB方法定義了 passbookBakEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookBakEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	372	372
物件	passbookBakEntity	passbookBakEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java

方法 private Long updatePassbookDB(String accountNo, String newPassbook, String oldPassbook, String funType) {

```
....
372.  DepQueryPassbookLogEntity passbookBakEntity = new
DepQueryPassbookLogEntity();
```

Heap Inspection\路徑 27:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=90
狀態	新的
Detection Date	1/13/2026 2:21:33 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第375行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	375	375
物件	passbookEntity	passbookEntity

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
方法	private Long updatePassbookDB(String accountNo, String newPassbook, String oldPassbook, String funType) {

```
....
375.  DepQueryPassbookEntity passbookEntity = passbookEntityOpt.get();
```

Heap Inspection\路徑 28:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=91
狀態	新的
Detection Date	1/13/2026 2:21:33 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第390行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	390	390
物件	passbookEntity	passbookEntity

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
方法	private Long updatePassbookDB(String accountNo, String newPassbook, String oldPassbook, String funType) {

```
....
390.  DepQueryPassbookEntity passbookEntity = new
DepQueryPassbookEntity();
```

Heap Inspection\路徑 29:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=92
狀態	新的
Detection Date	1/13/2026 2:21:33 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第409行的restore方法定義了 passbookBakEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookBakEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	409	409
物件	passbookBakEntity	passbookBakEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java

方法 public ServiceRs<EmptyRs> restore(String accountNo, Long backupId) {

```
....
409.  DepQueryPassbookLogEntity passbookBakEntity =
passbookBakRepository.readByListIdAndAccountNo(listId,accountNo).orElseT
hrow(() -> new TxnException(CodeEnum.DEPQR015));
```

Heap Inspection\路徑 30:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=93
狀態	新的
Detection Date	1/13/2026 2:21:33 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java第410行的restore方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
行	410	410
物件	passbookEntity	passbookEntity

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/ChangePassbookService.java
方法	public ServiceRs<EmptyRs> restore(String accountNo, Long backupId) {

```
....
410.  DepQueryPassbookEntity passbookEntity =
passbookRepository.readByAccountNo(accountNo).orElseThrow(() -> new
TxnException(CodeEnum.DEPQR015));
```

Heap Inspection\路徑 31:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=94
狀態	新的
Detection Date	9/22/2025 6:04:49 PM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第174行的updatePassbookDB方法定義了 passbookEntityOpt，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntityOpt，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	174	174
物件	passbookEntityOpt	passbookEntityOpt

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
方法	private Long updatePassbookDB(String accountNo, String newPassbook, String funType) {

```
....
174.  Optional<DepQueryPassbookEntity> passbookEntityOpt =
passbookRepository.readByAccountNo(accountNo);
```

Heap Inspection\路徑 32:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=95
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第176行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	176	176
物件	passbookEntity	passbookEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java

方法 private Long updatePassbookDB(String accountNo, String newPassbook, String funType) {

```
....
176.  DepQueryPassbookEntity passbookEntity = passbookEntityOpt.get();
```

Heap Inspection\路徑 33:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=96
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第177行的updatePassbookDB方法定義了 passbookBakEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookBakEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	177	177
物件	passbookBakEntity	passbookBakEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java

方法 private Long updatePassbookDB(String accountNo, String newPassbook, String funType) {

```
....
177.  DepQueryPassbookLogEntity passbookBakEntity = new
DepQueryPassbookLogEntity();
```

Heap Inspection\路徑 34:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=97
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java第191行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java
行	191	191
物件	passbookEntity	passbookEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/passbook/MaintainPassbookService.java

方法 private Long updatePassbookDB(String accountNo, String newPassbook, String funType) {

```
....
191.  DepQueryPassbookEntity passbookEntity = new
DepQueryPassbookEntity();
```

Heap Inspection\路徑 35:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=98
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java第37行的process方法定義了 passbookRecordOpt，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRecordOpt，但該值永遠不會從memory中清除。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java
行	37	37
物件	passbookRecordOpt	passbookRecordOpt

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java

方法 public ServiceRs<PassbookLineRs> process(String actNo, String pazzbookNo) {

```
....
37.  Optional<DepPassbookRecordEntity> passbookRecordOpt =
passbookRecordRepository.readFirstByAccountNoOrderByCreatedTimestampDesc
(actNo);
```

Heap Inspection\路徑 36:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=99
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java第45行的process方法定義了 passbookTdRecordOpt，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookTdRecordOpt，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java
行	45	45
物件	passbookTdRecordOpt	passbookTdRecordOpt

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/PassbookLineService.java

方法 public ServiceRs<PassbookLineRs> process(String actNo, String pazzbookNo) {

```
....
45.  Optional<DepPassbookTdRecordEntity> passbookTdRecordOpt =
passbookTdRecordRepository.readFirstByAccountNoOrderByCreatedTimestampDe
sc(actNo);
```

Heap Inspection\路徑 37:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=100
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/BaseXauService.java第344行的getLatestEndTxnDateTime方法定義了 passbookRecordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRecordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/BaseXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/BaseXauService.java
行	344	344
物件	passbookRecordEntity	passbookRecordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/BaseXauService.java

方法 private void getLatestEndTxnDateTime(GoldArg arg) {

```
....
344.  XauPassbookRecordEntity passbookRecordEntity =
getLatestPrintPassbook(arg.getAccountNo());
```

Heap Inspection\路徑 38:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=101
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/basicinfo/BasicInfoService.java第493行的getLatestEndTxnDateTime方法定義了 passbookRecordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRecordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-	uatFiles/ncbs-mid-repo-p2/xau/xau-

	service/src/main/java/com/scsb/ncbs/xau/service/basicinfo/BasicInfoService.java	service/src/main/java/com/scsb/ncbs/xau/service/basicinfo/BasicInfoService.java
行	493	493
物件	passbookRecordEntity	passbookRecordEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/basicinfo/BasicInfoService.java

方法 private void getLatestEndTxnDateTime(GoldArg arg) {

```
....
493.  XauPassbookRecordEntity passbookRecordEntity =
getLatestPrintPassbook(arg.getAccountNo());
```

Heap Inspection\路徑 39:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=102
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java第131行的updatePassbookDB方法定義了 passbookLogEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookLogEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
行	131	131
物件	passbookLogEntity	passbookLogEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java

方法 private Long updatePassbookDB(ChangePassbookXauArg arg) {

```
....
131.  DepQueryPassbookLogEntity passbookLogEntity = new
DepQueryPassbookLogEntity();
```

Heap Inspection\路徑 40:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=103
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java第134行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
行	134	134
物件	passbookEntity	passbookEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java

方法 private Long updatePassbookDB(ChangePassbookXauArg arg) {

```
....
134.  DepQueryPassbookEntity passbookEntity = optional.get();
```

Heap Inspection\路徑 41:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=104
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java第149行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
行	149	149
物件	passbookEntity	passbookEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java

方法 private Long updatePassbookDB(ChangePassbookXauArg arg) {

```
....
149.  DepQueryPassbookEntity passbookEntity = new
DepQueryPassbookEntity();
```

Heap Inspection\路徑 42:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=105
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java第168行的restore方法定義了 passbookBakEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookBakEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
行	168	168
物件	passbookBakEntity	passbookBakEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java

方法 public ServiceRs<EmptyRs> restore(String accountNo, Long backupId) {

```
....
168.  DepQueryPassbookLogEntity passbookBakEntity =
passbookLogRepository.readByListIdAndAccountNo(listId,accountNo).orElseT
hrow(() -> new TxnException(CodeEnum.DEPQR015));
```

Heap Inspection\路徑 43:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=106
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java第169行的restore方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
行	169	169
物件	passbookEntity	passbookEntity

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/ChangePassbookXauService.java
方法 public ServiceRs<EmptyRs> restore(String accountNo, Long backupId) {

```
....
169.  DepQueryPassbookEntity passbookEntity =
passbookRepository.readByAccountNo(accountNo).orElseThrow(() -> new
TxnException(CodeEnum.DEPQR015));
```

Heap Inspection\路徑 44:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=107
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java第143行的updatePassbookDB方法定義了 passbookEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java
行	143	143
物件	passbookEntity	passbookEntity

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java
方法 private Long updatePassbookDB(String accountNo, String newPassbook) {

```
....
143.  DepQueryPassbookEntity passbookEntity=
passbookRepository.readByAccountNo(accountNo).orElseThrow(() -> new
TxnException(CodeEnum.DEPQR035));
```

Heap Inspection\路徑 45:

嚴重程度： 低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=108
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java第145行的updatePassbookDB方法定義了 passbookBakEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookBakEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java
行	145	145
物件	passbookBakEntity	passbookBakEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/MaintainPassbookService.java

方法 private Long updatePassbookDB(String accountNo, String newPassbook) {

```
....
145.  DepQueryPassbookLogEntity passbookBakEntity = new
DepQueryPassbookLogEntity();
```

Heap Inspection\路徑 46:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=109
狀態	新的
Detection Date	3/5/2026 10:19:38 AM

uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java第242行的generateFirstRecord方法定義了 passbookRecordEntity，其中包含user passwords。雖然plaintext passwords 稍後assign給passbookRecordEntity，但該值永遠不會從memory中清除。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	242	242
物件	passbookRecordEntity	passbookRecordEntity

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
方法	private PrintPassbookDetail generateFirstRecord(PrintPassbookArg arg) {

```
....
242.  XauPassbookRecordEntity passbookRecordEntity =
getLatestPrintPassbook(arg.getPazzbookNo());
```

Improper Exception Handling

查詢路徑:

Java\Cx\Java Low Visibility\Improper Exception Handling 版本:1

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.5 - Improper error handling
NIST SP 800-53: SC-5 Denial of Service Protection (P1)
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Error processing
OWASP ASVS: V14 Configuration
OWASP Top 10 2021: A4-Insecure Design
ASD STIG 5.3: APSC-DV-002570 - CAT II The application must generate error messages that provide information necessary for corrective actions without revealing information that could be exploited by adversaries.
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Improper Exception Handling\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=24
狀態	新的
Detection Date	9/22/2025 6:04:50 PM

方法getUri在uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/dacc/DaccService.java第2715 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/dacc/DaccService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/dacc/DaccService.java
行	2715	2715
物件	getAnnotation	getAnnotation

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/dacc/DaccService.java
方法	private String getUri(Class<?> apiClass, String methodName, Class<?>... paramTypes) {

```
....
2715.  MidApiClient clientAnno =
apiClass.getAnnotation(MidApiClient.class);
```

Improper Exception Handling\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=25
狀態	新的
Detection Date	10/20/2025 12:35:10 PM

方法getSubAccount在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt04JobConfig.java第300 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt04JobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt04JobConfig.java
行	300	300
物件	query	query

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt04JobConfig.java

方法 private List<StmtDataBean> getSubAccount(String mainAccountNo) {

```
....
300.  return jdbcTemplate.query(
```

Improper Exception Handling\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=26
狀態	新的
Detection Date	10/20/2025 12:35:10 PM

方法getSubAccount在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt12JobConfig.java第220 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt12JobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt12JobConfig.java

行	220	220
物件	query	query

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportPhysicalStmt12JobConfig.java

方法 private List<StmtDataBean> getSubAccount(String mainAccountNo) {

```
....
220.  return jdbcTemplate.query(
```

Improper Exception Handling\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=27
狀態	新的
Detection Date	10/20/2025 12:35:10 PM

方法getAccountTxnFromMvAndBalance在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java第213 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java
行	213	213
物件	query	query

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/helper/StmtHelper.java

方法 private List<StmtAccountTxnBean> getAccountTxnFromMvAndBalance(String accountId, LocalDate startDate, LocalDate endDate) {

```
....
213.  return jdbcTemplate.query(
```

Improper Exception Handling\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=28
狀態	新的
Detection Date	9/22/2025 6:04:50 PM

方法fetchStmtData在uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java第107 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java
行	107	107
物件	query	query

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java

方法 public Map<Tuple3<String, String, String>, MutablePair<ExpGlaSubsidiaryLedgerItem, ExpGlaSubsidiaryLedgerItem>> fetchStmtData(LocalDate runDate) {

```
....
107.  List<ExpGlaSubsidiaryLedgerItem> stmts = midJdbcTemplate.query(
```

Improper Exception Handling\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=29
狀態	新的
Detection Date	9/22/2025 6:04:50 PM

方法deleteAmlCase在uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java第113 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java
行	113	113
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java

方法 private int deleteAmlCase() {

```
....
113.  return jdbcTemplate.update(sql);
```

Improper Exception Handling\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=30
狀態	新的
Detection Date	1/23/2026 6:45:31 PM

方法obtainClosedAccount在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/persistence/repository/len/LenAccountClosedRepository.java第147行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/persistence/repository/len/LenAccountClosedRepository.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/persistence/repository/len/LenAccountClosedRepository.java
行	147	147
物件	getResultList	getResultList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/persistence/repository/len/LenAccountClosedRepository.java

方法 default List<LenAccountClosedEntity> obtainClosedAccount(QueryLenAccountClosedArg arg) {

```
....
147.  return getEntityManager().createQuery(cq).getResultList();
```

Improper Exception Handling\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=31
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法buildExportQuery在uatFiles/ncbs-mid-repo-p2/try/try-bat/src/main/java/com/scsb/ncbs/treasury/batch/job/Bir30ExportJob.java第151 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/try/try-bat/src/main/java/com/scsb/ncbs/treasury/batch/job/Bir30ExportJob.java	uatFiles/ncbs-mid-repo-p2/try/try-bat/src/main/java/com/scsb/ncbs/treasury/batch/job/Bir30ExportJob.java
行	151	151
物件	createQuery	createQuery

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-bat/src/main/java/com/scsb/ncbs/treasury/batch/job/Bir30ExportJob.java
方法 public Query buildExportQuery(EntityManager em) {

```
....
151.  .createQuery("SELECT limit,cust,collateralRight,collateral FROM
MvMidLimitEntity limit"
```

Improper Exception Handling\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=32
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法findByCustomerId在uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/persistence/repository/si/TrySiKycExpirationCustomRepositoryImpl.java第39 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/persistence/repository/si/TrySiKycExpirationCustomRepositoryImpl.java	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/persistence/repository/si/TrySiKycExpirationCustomRepositoryImpl.java
行	39	39
物件	createQuery	createQuery

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/persistence/repository/si/TrySiKycExpirationCustomRepositoryImpl.java
方法 private TrySiKycExpirationEntity findByCustomerId(String customerId) {

```
....
39.  return entityManager.createQuery(query)
```

Improper Exception Handling\路徑 10:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=33
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法updateCumulativeData在uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java第164 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java
行	164	164
物件	findCustomerCumulativeData	findCustomerCumulativeData

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java

方法 public boolean updateCumulativeData(@NotNull CbrDataModEntity cbrDataMod, @NotNull Customer customer, @NotNull CbrDataOperationEnum operation) {

```
....
164.  cbrDailythresholdAccuRepo.findCustomerCumulativeData(customerId,
List.of(txDate), purchaseOrSell)
```

Improper Exception Handling\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=34
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法fetchMidCumulativeAmount在uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeTwdUsdHelper.java第107 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeTwdUsdHelper.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeTwdUsdHelper.java
行	107	107
物件	findCustomerCumulativeData	findCustomerCumulativeData

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeTwdUsdHelper.java
方法	public CbrCumulativeTwdUsdData fetchMidCumulativeAmount(

```
....
107.  CbrDailythresholdAccuEntity accuEntity =
cbrDailythresholdAccuRepo.findCustomerCumulativeData(customerId,
List.of(txDate), purchaseOrSell)
```

Improper Exception Handling\路徑 12:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=35
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法fetchMidCumulativeAmount在uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeCnyHelper.java第98 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeCnyHelper.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeCnyHelper.java
行	98	98
物件	findCumulativeAmount	findCumulativeAmount

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/validation/validator/helper/CbrCumulativeCnyHelper.java
方法	public CbrCumulativeCnyData fetchMidCumulativeAmount(

```
....
98.  BigDecimal amount =
cbrScsbLimitUpdateRepo.findCumulativeAmount(customerId, txDate,
purchaseOrSell)
```

Improper Exception Handling\路徑 13:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=36
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法updateCumulativeData在uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java第228 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java
行	228	228
物件	findCustomerCumulativeData	findCustomerCumulativeData

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/data/CbrCumulativeDataService.java

方法 public boolean updateCumulativeData(@NotNull CbrDataModEntity cbrDataMod, @NotNull Customer customer, @NotNull CbrDataOperationEnum operation) {

```
....
228.  cbrScsbLimitUpdateRepo.findCustomerCumulativeData(customerId,
List.of(txDate), purchaseOrSell)
```

Improper Exception Handling\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=37
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法midJobBuilderFactory.buildTaskletStep在uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java第213 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java
行	213	213
物件	deleteByRunDate	deleteByRunDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java

方法 return midJobBuilderFactory.buildTaskletStep(STEP_NAME + "Init1", (contribution, chunkContext) -> {

```
....
213.  txnErrorRepository.deleteByRunDate(midJobParameter.getRunDate());
```

Improper Exception Handling\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=38
狀態	新的
Detection Date	3/5/2026 10:19:37 AM

方法midJobBuilderFactory.buildTaskletStep在uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java第212 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java
行	212	212
物件	deleteByRunDate	deleteByRunDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java

方法 return midJobBuilderFactory.buildTaskletStep(STEP_NAME + "Init1", (contribution, chunkContext) -> {

```
....
212.  txnTempRepository.deleteByRunDate(midJobParameter.getRunDate());
```

Improper Exception Handling\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=39
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法update在uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java第152 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/serv	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/serv

	ice/pric/intrate/intrateprojrel/IntRateProjectRelateService.java	ice/pric/intrate/intrateprojrel/IntRateProjectRelateService.java
行	152	152
物件	delByBusiness	delByBusiness

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java
方法 public ServiceRs<EmptyRs> update(@NotNull @Valid IntRateProjectRelateUpdateArg arg) {

```
....
152.  cmnPricIntRateProjRelRepository.delByBusiness(business);
```

Improper Exception Handling\路徑 17:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=40
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法delete在uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java第179 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java
行	179	179
物件	delByBusiness	delByBusiness

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java
方法 public ServiceRs<EmptyRs> delete(@NotNull @Valid IntRateProjectRelateDeleteArg arg) {

```
....
179.  cmnPricIntRateProjRelRepository.delByBusiness(business);
```

Improper Exception Handling\路徑 18:

嚴重程度：	低風險
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=41
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法readList在uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java第195 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java
行	195	195
物件	obtainItrRelationList	obtainItrRelationList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/pric/intrate/intrateprojrel/IntRateProjectRelateService.java

方法 public ServiceRs<IntRateProjectRelateReadListRs> readList(@NotNull @Valid IntRateProjectRelateReadListArg arg) {

```
....
195.  List<String> businessList =
cmnPricIntRateProjRelRepository.obtainItrRelationList(arg.getBusiness())
.stream()
```

Improper Exception Handling\路徑 19:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=42
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountDailyBalanceJobConfig.java第136 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountDailyBalanceJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountDailyBalanceJobConfig.java
行	136	136
物件	truncateTable	truncateTable

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountDailyBalanceJobConfig.java
方法	return (jobExecution, stepExecution) -> {

```
....
136.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 20:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=43
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java第198 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java
行	198	198
物件	truncateTable	truncateTable

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java
方法	return (jobExecution, stepExecution) -> {

```
....
198.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 21:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=44
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java第197 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java
行	197	197
物件	truncateTable	truncateTable

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAccountTxnJobConfig.java
方法 return (jobExecution, stepExecution) -> {

```
....
197.  txnTempRepository.truncateTable();
```

Improper Exception Handling\路徑 22:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=45
狀態	新的
Detection Date	12/19/2025 4:50:43 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java第210 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java
行	210	210
物件	truncateTable	truncateTable

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java
方法 return (jobExecution, stepExecution) -> {

```
....
210.  errorLogRepository.truncateTable(); // truncate error log table
```

Improper Exception Handling\路徑 23:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=46
狀態	新的

Detection Date	12/19/2025 4:50:43 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java第209 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java
行	209	209
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/account/AccountAvgBalJobConfig.java

方法 return (jobExecution, stepExecution) -> {

```
....
209.  tempRepository.truncateTable(); // truncate temp table
```

Improper Exception Handling\路徑 24:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=47
狀態	新的
Detection Date	12/19/2025 4:50:43 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java第152 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java
行	152	152
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java

方法 return (jobExecution, stepExecution) -> {

```
....
152.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 25:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=48
狀態	新的
Detection Date	12/19/2025 4:50:43 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java第151 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java
行	151	151
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/bond/ImportBondTradeRecordsJobConfig.java

方法 return (jobExecution, stepExecution) -> {

```
....
151.  repository.truncateTable();
```

Improper Exception Handling\路徑 26:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=49
狀態	新的
Detection Date	12/19/2025 4:50:43 PM

方法queryDep在uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/customer/CustomerService.java第251 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-	uatFiles/ncbs-mid-repo-p2/dep/dep-

	service/src/main/java/com/scsb/ncbs/dep/service/adi/customer/CustomerService.java	service/src/main/java/com/scsb/ncbs/dep/service/adi/customer/CustomerService.java
行	251	251
物件	getUnClosedChequeAccountList	getUnClosedChequeAccountList

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/adi/customer/CustomerService.java
方法 private List<CustDepBean> queryDep(CustomerArg arg) {

```
....
251.  List<String> unClosedChequeAccountList =
Optional.ofNullable(ccsRecordsRepository.getUnClosedChequeAccountList(arg.getCustId())).orElse(new
ArrayList<>()).stream().map(DepCdiQueryDepEntity::getChequeActNo).collect(Collectors.toList());
```

Improper Exception Handling\路徑 27:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=50
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java第188 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
行	188	188
物件	truncateTable	truncateTable

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
方法 return (jobExecution, stepExecution) -> {

```
....
188.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 28:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=51
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java第190 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
行	190	190
物件	truncateTable	truncateTable

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
方法	return (jobExecution, stepExecution) -> {

```
....
190.  hisErrorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 29:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=52
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java第191 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
行	191	191
物件	truncateTable	truncateTable

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
方法	return (jobExecution, stepExecution) -> {

```
....
191.  hisRepository.truncateTable();
```

Improper Exception Handling\路徑 30:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=53
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java第189 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java
行	189	189
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenAaArrangementActivityConfig.java

方法 return (jobExecution, stepExecution) -> {

```
....
189.  repository.truncateTable();
```

Improper Exception Handling\路徑 31:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=54
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java第141 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java
行	141	141

物件	truncateTable	truncateTable

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java
方法 return (jobExecution, stepExecution) -> {

```
....
141.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 32:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=55
狀態	新的
Detection Date	9/26/2025 6:26:06 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java第142 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java
行	142	142
物件	truncateTable	truncateTable

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/len/LenEbContractBalancesConfig.java
方法 return (jobExecution, stepExecution) -> {

```
....
142.  repository.truncateTable();
```

Improper Exception Handling\路徑 33:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=56
狀態	新的
Detection Date	10/13/2025 3:53:36 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/ewb/EwbBat2JobConfig.java第153 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/ewb/EwbBat2JobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/ewb/EwbBat2JobConfig.java
行	153	153
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/ewb/EwbBat2JobConfig.java

方法 return (jobExecution, stepExecution) -> {

```
....
153.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 34:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=57
狀態	新的
Detection Date	9/22/2025 6:04:50 PM

方法midJobBuilderFactory.buildTaskletStep在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportDigitalStmt07JobConfig.java第86 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportDigitalStmt07JobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportDigitalStmt07JobConfig.java
行	86	86
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/ExportDigitalStmt07JobConfig.java

方法 return midJobBuilderFactory.buildTaskletStep(TRUNCATE_STEP_NAME, (stepContribution, chunkContext) -> {

```
....
86.  edwDepFnrecintRepository.truncateTable();
```

Improper Exception Handling\路徑 35:

嚴重程度：	低風險
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=58
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法obtainVrTxnDetails在uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java第101 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java
行	101	101
物件	obtainVrTxnDetailsByBusinessDate	obtainVrTxnDetailsByBusinessDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java

方法 default List<VirtualAccountTxnDetailsDto> obtainVrTxnDetails(VirtualAccountTxnArg arg) {

```
....
101.  return obtainVrTxnDetailsByBusinessDate(arg);
```

Improper Exception Handling\路徑 36:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=59
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法obtainVrTxnDetails在uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java第105 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java
行	105	105
物件	obtainVrTxnDetailsByTxnDateTime	obtainVrTxnDetailsByTxnDateTime

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/repository/query/va/DepVirtualAccountTxnRepository.java
方法	default List<VirtualAccountTxnDetailsDto> obtainVrTxnDetails(VirtualAccountTxnArg arg) {

```
....
105.  return obtainVrTxnDetailsByTxnDateTime(arg);
```

Improper Exception Handling\路徑 37:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=60
狀態	新的
Detection Date	1/23/2026 6:45:31 PM

方法return在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/StmtMt940JobConfig.java第131 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/StmtMt940JobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/StmtMt940JobConfig.java
行	131	131
物件	truncateTable	truncateTable

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/stmt/StmtMt940JobConfig.java
方法	return (jobExecution, stepExecution) -> {

```
....
131.  errorLogRepository.truncateTable();
```

Improper Exception Handling\路徑 38:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=61
狀態	新的
Detection Date	1/23/2026 6:45:31 PM

方法midJobBuilderFactory.buildTaskletStep在uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/media/ImportDpWhtJobConfig.java第109 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/media/ImportDpWhtJobConfig.java	uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/media/ImportDpWhtJobConfig.java
行	109	109
物件	truncateTable	truncateTable

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-bat/src/main/java/com/scsb/ncbs/dep/batch/job/media/ImportDpWhtJobConfig.java

方法 return midJobBuilderFactory.buildTaskletStep(DELETE_STEP_NAME, (stepContribution, chunkContext) -> {

```
....
109.  depDpWhtRepository.truncateTable();
```

Improper Exception Handling\路徑 39:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=62
狀態	新的
Detection Date	9/22/2025 6:04:50 PM

方法read在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java第 106 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java
行	106	106
物件	readByBeneficiaryStartingWith	readByBeneficiaryStartingWith

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java

方法 public ServiceRs<LcAdvisingCustNoteReadRs> read(@NotNull @Valid LcAdvisingCustNoteReadArg arg) {

```
....
106.  List<LcAdvisingCustNote> datas =
advisingCustNoteRepository.readByBeneficiaryStartingWith(arg.getBenefici
ary())
```

Improper Exception Handling\路徑 40:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=63
狀態	新的
Detection Date	11/17/2025 11:22:19 AM

方法hasBeneCif在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/checker/BaseLcAdvisingCustNoteChecker.java第36 行執行可預期拋出異常的操作，但未正確包裹在try-catch區塊中。這構成不當異常處理(Improper Exception Handling)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/checker/BaseLcAdvisingCustNoteChecker.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/checker/BaseLcAdvisingCustNoteChecker.java
行	36	36
物件	readByBeneCif	readByBeneCif

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/checker/BaseLcAdvisingCustNoteChecker.java

方法 public boolean hasBeneCif(String beneCif) {

```
....
36.  return
!MidObjectUtils.isEmpty(advisingCustNoteRepository.readByBeneCif(beneCif
));
```

Integer Overflow

查詢路徑:

Java\Cx\Java Low Visibility\Integer Overflow 版本:3

類別

FISMA 2014: System And Information Integrity
NIST SP 800-53: SI-10 Information Input Validation (P1)
OWASP Mobile Top 10 2016: M7-Client Code Quality
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Verification and representation of input data
OWASP ASVS: V05 Validation, Sanitization and Encoding
SANS top 25: SANS top 25
ASD STIG 5.3: APSC-DV-002590 - CAT I The application must not be vulnerable to overflow attacks.
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Integer Overflow\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=135
狀態	新的
Detection Date	9/22/2025 6:05:39 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java中的第 49行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java中的第 183行 parsedYear算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java
行	49	183
物件	apiRequest	parsedYear

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java

方法 public ApiResponse<ServiceRs<PrintWithholdingRs>> print(@RequestBody ApiRequest<ServiceRq<PrintWithholdingRq>> apiRequest) {

```
....
49.  public ApiResponse<ServiceRs<PrintWithholdingRs>>
print(@RequestBody ApiRequest<ServiceRq<PrintWithholdingRq>> apiRequest)
{
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java

方法 public ServiceRs<PrintWithholdingRs> print(@Valid WithholdingArg withholdingArg) {

```
....
183.  int parsedYear =
MidLocalDateUtils.parseToLocalDate(withholdingArg.getInterestPaymentYear
() + "0101",
```

Integer Overflow\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=136
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第96行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第153行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	96	153
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
96.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
153.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=137
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第103行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第153行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	103	153
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
103.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
153.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=138
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第96行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第155行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

行	96	155
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
96.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
155.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=139
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第103行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第155行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	103	155
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twTermDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
103.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
方法	private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
155.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=140
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第117行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第148行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	117	148
物件	apiRequest	AssignExpr

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

方法 private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
148.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=141
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第124行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第148行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	124	148
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
124.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
方法	private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
148.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=142
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第117行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第150行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	117	150
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
方法	private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
150.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=143
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第124行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第150行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	124	150
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
124.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

方法 private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
150.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 10:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=144
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 62行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 200行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	62	200
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
62.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
200.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=145
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 71行

apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 200行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	71	200
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
71.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
200.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 12:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=146
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 62行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 202行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

行	62	202
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
62.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
202.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 13:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=147
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 71行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 202行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	71	202
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
71.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
202.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=148
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 75行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 217行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	75	217
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
75.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
方法	private void generatePassbookDetail(TwDemandArg arg) {

```
....
217.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=149
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 82行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 217行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	82	217
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
方法	private void generatePassbookDetail(TwDemandArg arg) {

```
....
217.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=150
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 75行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 219行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	75	219
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
75.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java

方法 private void generatePassbookDetail(TwDemandArg arg) {

```
....
219.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 17:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=151
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 82行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 219行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	82	219
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java

方法 private void generatePassbookDetail(TwDemandArg arg) {

```
....
219.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 18:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=152
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 131行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 152行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	131	152
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
131.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

方法 private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
152.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 19:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=153
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 138行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 152行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	138	152
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
138.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

方法 private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
152.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 20:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=154
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第131行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 154行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

行	131	154
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
131.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

方法 private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
154.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 21:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=155
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第138行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 154行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	138	154
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
138.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
方法	private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
154.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 22:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=156
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第151行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 172行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	151	172
物件	apiRequest	AssignExpr

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
151.  public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

方法 private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
172.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 23:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=157
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第158行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 172行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	158	172
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
158.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
方法	private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
172.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 24:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=158
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 151行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 174行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	151	174
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
151.  public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
方法	private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
174.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 25:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=159
狀態	新的
Detection Date	12/19/2025 4:51:38 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 158行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 174行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	158	174
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
158.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

方法 private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
174.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 26:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=160
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第179行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第157行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	179	157
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
179.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
157.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 27:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=161
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第186行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第157行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	186	157
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
186.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
157.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Overflow\路徑 28:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=162
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第179行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第159行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	179	159
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
179.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
159.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 29:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=163
狀態	新的
Detection Date	1/23/2026 6:46:33 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第186行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第159行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

行	186	159
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
186.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
159.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Overflow\路徑 30:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=164
狀態	新的
Detection Date	3/5/2026 10:19:45 AM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java中的第 32行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java中的第 233行 integerDigits算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java
行	32	233
物件	apiRequest	integerDigits

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java

方法	public ApiResponse<ServiceRs<InterestAmtQueryRs>> query(@RequestBody ApiRequest<ServiceRq<InterestAmtQueryRq>> apiRequest) {

```
....
32.  public ApiResponse<ServiceRs<InterestAmtQueryRs>>
query(@RequestBody ApiRequest<ServiceRq<InterestAmtQueryRq>> apiRequest)
{
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java
方法	private void validateInterestRate(BigDecimal interestRate) {

```
....
233.  int integerDigits = interestRate.precision() - scale;
```

Integer Overflow\路徑 31:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=165
狀態	新的
Detection Date	3/5/2026 10:19:45 AM

在 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java中的第 48行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java中的第 70行 totalPages算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java
行	48	70
物件	apiRequest	totalPages

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java
方法	public ApiResponse<ServiceRs<BranchFxSettlementReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchFxSettlementReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java
方法	public List<SCSBCustomerDailyThreQuotaResponseBody> getScsbCustomerDailyThreQuota(BaseL20035Arg arg, int pageSize) {

```
....
70.  int totalPages = (int) Math.ceil((double) effectiveSize /
pageSize);
```

Integer Underflow

查詢路徑:

Java\Cx\Java Low Visibility\Integer Underflow 版本:3

類別

OWASP Mobile Top 10 2016: M7-Client Code Quality
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Verification and representation of input data
OWASP ASVS: V05 Validation, Sanitization and Encoding
SANS top 25: SANS top 25

描述

Integer Underflow\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=166
狀態	新的
Detection Date	9/22/2025 6:05:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java中的第 49行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java中的第 183行 parsedYear算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java
行	49	183
物件	apiRequest	parsedYear

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/witholding/WithholdingController.java
方法	public ApiResponse<ServiceRs<PrintWithholdingRs>> print(@RequestBody ApiRequest<ServiceRq<PrintWithholdingRq>> apiRequest) {

```
....
49.  public ApiResponse<ServiceRs<PrintWithholdingRs>>
print(@RequestBody ApiRequest<ServiceRq<PrintWithholdingRq>> apiRequest)
{
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/withholding/WithholdingService.java

方法 public ServiceRs<PrintWithholdingRs> print(@Valid WithholdingArg withholdingArg) {

```
....
183.  int parsedYear =
MidLocalDateUtils.parseToLocalDate(withholdingArg.getInterestPaymentYear
() + "0101",
```

Integer Underflow\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=167
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第96行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第153行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	96	153
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
96.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
方法	private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
153.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=168
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第103行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第153行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	103	153
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twTermDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
103.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest)  {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
方法	private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
153.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=169
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第96行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第155行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	96	155
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
96.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
155.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=170
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第103行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java中的第155行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java
行	103	155
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twTermDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
103.  public ApiResponse<ServiceRs<FixedFormatRs>>
twTermDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwTermDepositService.java

方法 private void generatePassbookFixedDetail(TwTermDepositArg arg) {

```
....
155.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=171
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第117行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第148行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	117	148
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

方法 private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
148.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=172
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第124行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第148行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	124	148
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
124.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

方法 private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
148.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=173
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第117行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第150行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

行	117	150
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java

方法 private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
150.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=174
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第124行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java中的第150行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
行	124	150
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twSmallDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
124.  public ApiResponse<ServiceRs<FixedFormatRs>>
twSmallDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwSmallDepositService.java
方法	private void generatePassbookDetail(TwSmallDepositArg arg) {

```
....
150.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 10:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=175
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 62行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 200行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	62	200
物件	apiRequest	AssignExpr

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
62.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
200.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=176
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 71行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 200行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	71	200
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
71.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法	private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
200.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 12:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=177
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 62行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 202行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	62	202
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
62.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbook(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
方法	private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
202.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 13:

嚴重程度：	低風險
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=178
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java中的第 71行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java中的第 202行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java
行	71	202
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-app/src/main/java/com/scsb/ncbs/xau/controller/customer/XauCustomerController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
71.  public ApiResponse<ServiceRs<FixedFormatRs>>
printPassbookM(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/customer/PrintPassbookService.java

方法 private void generatePassbookDetail(PrintPassbookArg arg) {

```
....
202.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=179
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 75行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-

service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 217行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	75	217
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
75.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest)  {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java

方法 private void generatePassbookDetail(TwDemandArg arg) {

```
....
217.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=180
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 82行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 217行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookControll	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.jav

	er.java	a
行	82	217
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java

方法 private void generatePassbookDetail(TwDemandArg arg) {

```
....
217.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=181
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 75行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 219行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	75	219
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
75.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
方法	private void generatePassbookDetail(TwDemandArg arg) {

```
....
219.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 17:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=182
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 82行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java中的第 219行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java
行	82	219
物件	apiRequest	AssignExpr

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<FixedFormatRs>> twDemandm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwDemandService.java

方法 private void generatePassbookDetail(TwDemandArg arg) {

```
....
219.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 18:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=183
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第131行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 152行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	131	152
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
131.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
方法	private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
152.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 19:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=184
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第138行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 152行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	138	152
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
138.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
方法	private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
152.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 20:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=185
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 131行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 154行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	131	154
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
131.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

方法 private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
154.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 21:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=186
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第138行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java中的第 154行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java
行	138	154
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> twCompositeDepositM(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
138.  public ApiResponse<ServiceRs<FixedFormatRs>>
twCompositeDepositM(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/TwCompositeDepositService.java

方法 private void generatePassbookFixedDetail(TwCompositeDepositArg arg) {

```
....
154.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 22:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=187
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 151行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 172行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	151	172
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
151.  public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

方法 private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
172.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 23:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=188
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第 158行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 172行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	158	172
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
158.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

方法 private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
172.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 24:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=189
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第151行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 174行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

行	151	174
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
151.  public ApiResponse<ServiceRs<FixedFormatRs>> fcDemand(@RequestBody
ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java

方法 private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
174.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 25:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=190
狀態	新的
Detection Date	12/19/2025 4:51:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第158行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java中的第 174行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
行	158	174
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>> apiRequest) {

```
....
158.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcDemandm(@RequestBody ApiRequest<ServiceRq<PrintPassbookRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcDemandService.java
方法	private void generatePassbookDetail(FcPrintPassbookArg arg) {

```
....
174.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 26:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=191
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第179行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第157行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	179	157
物件	apiRequest	AssignExpr

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
179.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
157.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 27:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=192
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第186行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第157行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	186	157
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
186.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
方法	private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
157.  nextLineNo = nextLineNo + PAZZBOOK_LINE_BUFFER - remainingLineNo;
```

Integer Underflow\路徑 28:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=193
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第179行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第159行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為“整數溢出”）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	179	159
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java
方法	public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDeposit(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
179.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDeposit(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
方法	private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
159.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 29:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=194
狀態	新的
Detection Date	1/23/2026 6:46:49 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java中的第186行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java中的第159行 AssignExpr算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java
行	186	159
物件	apiRequest	AssignExpr

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/query/printpassbook/PrintPassbookController.java

方法 public ApiResponse<ServiceRs<FixedFormatRs>> fcTermDepositm(@RequestBody ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {

```
....
186.  public ApiResponse<ServiceRs<FixedFormatRs>>
fcTermDepositm(@RequestBody
ApiRequest<ServiceRq<PrintPassbookTermDepositRq>> apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/query/printpassbook/FcTermDepositService.java

方法 private void generatePassbookFixedDetail(FcTermDepositArg arg) {

```
....
159.  nextLineNo = nextLineNo + PAZZBOOK_LINE_COUNT - remainingLineNo;
```

Integer Underflow\路徑 30:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=195
狀態	新的
Detection Date	3/5/2026 10:19:45 AM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java中的第 32行 apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java中的第 233行 integerDigits算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java
行	32	233
物件	apiRequest	integerDigits

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/tdb/InterestAmtController.java

方法 public ApiResponse<ServiceRs<InterestAmtQueryRs>> query(@RequestBody ApiRequest<ServiceRq<InterestAmtQueryRq>> apiRequest) {

```
....
32.  public ApiResponse<ServiceRs<InterestAmtQueryRs>>
query(@RequestBody ApiRequest<ServiceRq<InterestAmtQueryRq>> apiRequest)
{
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/tdb/InterestAmtService.java

方法 private void validateInterestRate(BigDecimal interestRate) {

```
....
233.  int integerDigits = interestRate.precision() - scale;
```

Integer Underflow\路徑 31:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=196
狀態	新的
Detection Date	3/5/2026 10:19:45 AM

在 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java中的第 48行

apiRequest 的值被使用在 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java中的第 70行 totalPages算數運算沒有經過驗證，可能會導致算術溢出（俗稱 作為"整數溢出"）。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java
行	48	70
物件	apiRequest	totalPages

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java

方法 public ApiResponse<ServiceRs<BranchFxSettlementReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchFxSettlementReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/t24/l20035/CbrL20035T24Client.java

方法 public List<SCSBCustomerDailyThreQuotaResponseBody> getScsbCustomerDailyThreQuota(BaseL20035Arg arg, int pageSize) {

```
....
70.  int totalPages = (int) Math.ceil((double) effectiveSize /
pageSize);
```

Incorrect Permission Assignment For Critical Resources

查詢路徑:

Java\Cx\Java Low Visibility\Incorrect Permission Assignment For Critical Resources 版本:6

類別

FISMA 2014: Access Control
NIST SP 800-53: AC-3 Access Enforcement (P1)
OWASP Top 10 2017: A6-Security Misconfiguration
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V04 Access Control
OWASP Top 10 2021: A4-Insecure Design
SANS top 25: SANS top 25
OWASP Top 10 API 2023: API8-Security Misconfiguration
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Incorrect Permission Assignment For Critical Resources\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=111
狀態	新的
Detection Date	3/5/2026 10:19:42 AM

檔案系統中由 uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java 第 21 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java
行	21	21
物件	path	path

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/client/MidMessageClient.java
方法	ApiResponse<ServiceRs<MessageRs>> send(URI baseURI, @RequestBody ApiRequest<ServiceRq<MessageRq>> apiRequest);

```
....
21.  @PostMapping(path = "/mid/message/send", consumes =
"application/json", produces = "application/json")
```

Incorrect Permission Assignment For Critical Resources\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=112
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java 第 19 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java
行	19	19
物件	path	path

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/client/cmn/BdayNextApi.java
方法	@MidApiClient(application = "cmn", name = "BdayNextApi", path = "bday/bdayNext")

```
....
19.  @MidApiClient(application = "cmn", name = "BdayNextApi", path =
"bday/bdayNext")
```

Incorrect Permission Assignment For Critical Resources\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=113
狀態	新的
Detection Date	1/23/2026 6:45:57 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java 第 13 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java
行	13	13
物件	path	path

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/DepDaccApi.java
方法	@MidApiClient(application = "dep", name = "DepDaccApi", path = "dacc")

```
....
13.  @MidApiClient(application = "dep", name = "DepDaccApi", path =
"dacc")
```

Incorrect Permission Assignment For Critical Resources\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=114
狀態	新的
Detection Date	12/19/2025 4:51:07 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java 第 13 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java
行	13	13
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/client/TryCim11Api.java

方法 @MidApiClient(application = "try", name = "TryCim11Api", path = "calypso/cim11")

```
....
13.  @MidApiClient(application = "try", name = "TryCim11Api", path =
"calypso/cim11")
```

Incorrect Permission Assignment For Critical Resources\路徑 5:

嚴重程度： 低風險
結果狀態： 校驗
線上結果 http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=115
狀態 新的
Detection Date 11/3/2025 5:04:37 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoBranchApi.java 第 12 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoBranchApi.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoBranchApi.java
行	12	12
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoBranchApi.java

方法 @MidApiClient(application = "bco", name = "BcoBranchApi", path = "branch")

```
....
12.  @MidApiClient(application = "bco", name = "BcoBranchApi", path =
"branch")
```

Incorrect Permission Assignment For Critical Resources\路徑 6:

嚴重程度： 低風險
結果狀態： 校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=116
狀態	新的
Detection Date	11/3/2025 5:04:37 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoMidApi.java 第 15 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoMidApi.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoMidApi.java
行	15	15
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/bco/BcoMidApi.java

方法 @MidApiClient(application = "bco", name = "BcoMidApi", path = "mid")

```
....
15.  @MidApiClient(application = "bco", name = "BcoMidApi", path =
"mid")
```

Incorrect Permission Assignment For Critical Resources\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=117
狀態	新的
Detection Date	10/13/2025 3:53:59 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java 第 22 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java
行	22	22
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java

方法	@MidApiClient(application = "fep", name = "FepOtherApi", path = "server/branch/other/recv/apic")

```
....
22.  @MidApiClient(application = "fep", name = "FepOtherApi", path =
"server/branch/other/recv/apic")
```

Incorrect Permission Assignment For Critical Resources\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=118
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNearApi.java 第 19 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNearApi.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNearApi.java
行	19	19
物件	path	path

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNearApi.java
方法	@MidApiClient(application = "cmn", name = "BdayNearApi", path = "bday/bdayNear")

```
....
19.  @MidApiClient(application = "cmn", name = "BdayNearApi", path =
"bday/bdayNear")
```

Incorrect Permission Assignment For Critical Resources\路徑 9:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=119
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNextApi.java 第 19 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-	uatFiles/ncbs-mid-repo-p2/len/len-

	service/src/main/java/com/scsb/ncbs/len/service/api/BdayNextApi.java	service/src/main/java/com/scsb/ncbs/len/service/api/BdayNextApi.java
行	19	19
物件	path	path

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/BdayNextApi.java
方法 @MidApiClient(application = "cmn", name = "BdayNextApi", path = "bday/bdayNext")

```
....
19.  @MidApiClient(application = "cmn", name = "BdayNextApi", path =
"bday/bdayNext")
```

Incorrect Permission Assignment For Critical Resources\路徑 10:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=120
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/NtfMessageApi.java 第 16 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/NtfMessageApi.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/NtfMessageApi.java
行	16	16
物件	path	path

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/api/NtfMessageApi.java
方法 @MidApiClient(application = "cmn", name = "NtfMessageApi", path = "ntf/ntfMessage")

```
....
16.  @MidApiClient(application = "cmn", name = "NtfMessageApi", path =
"ntf/ntfMessage")
```

Incorrect Permission Assignment For Critical Resources\路徑 11:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=121

狀態	新的
Detection Date	12/19/2025 4:51:07 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/api/BawSwiftApiClient.java 第 23 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/api/BawSwiftApiClient.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/api/BawSwiftApiClient.java
行	23	23
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/api/BawSwiftApiClient.java

方法 @MidApiClient(application = "baw", name = "BawSwiftApiClient", path = "bawctl/baw/apis/mid")

```
....
23.  @MidApiClient(application = "baw", name = "BawSwiftApiClient", path
= "bawctl/baw/apis/mid")
```

Incorrect Permission Assignment For Critical Resources\路徑 12:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=122
狀態	新的
Detection Date	12/19/2025 4:51:07 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/main/java/com/scsb/ncbs/sgw/api/BawSwiftApiClient.java 第 23 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/main/java/com/scsb/ncbs/sgw/api/BawSwiftApiClient.java	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/main/java/com/scsb/ncbs/sgw/api/BawSwiftApiClient.java
行	23	23
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/main/java/com/scsb/ncbs/sgw/api/BawSwiftApiClient.java

方法 @MidApiClient(application = "baw", name = "BawSwiftApiClient", path = "bawctl/baw/apis/mid")

```
....
23.  @MidApiClient(application = "baw", name = "BawSwiftApiClient", path
= "bawctl/baw/apis/mid")
```

Incorrect Permission Assignment For Critical Resources\路徑 13:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=123
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayInfoApi.java 第 19 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayInfoApi.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayInfoApi.java
行	19	19
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayInfoApi.java

方法 @MidApiClient(application = "cmn", name = "BdayInfoApi", path = "bday/bdayInfo")

```
....
19.  @MidApiClient(application = "cmn", name = "BdayInfoApi", path =
"bday/bdayInfo")
```

Incorrect Permission Assignment For Critical Resources\路徑 14:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=124
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNearApi.java 第 18 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNearApi.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNearApi.java

行	18	18
物件	path	path

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNearApi.java
方法 @MidApiClient(application = "cmn", name = "BdayNearApi", path = "bday/bdayNear")

```
....
18.  @MidApiClient(application = "cmn", name = "BdayNearApi", path =
"bday/bdayNear")
```

Incorrect Permission Assignment For Critical Resources\路徑 15:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=125
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNextApi.java 第 18 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNextApi.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNextApi.java
行	18	18
物件	path	path

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/cmn/BdayNextApi.java
方法 @MidApiClient(application = "cmn", name = "BdayNextApi", path = "bday/bdayNext")

```
....
18.  @MidApiClient(application = "cmn", name = "BdayNextApi", path =
"bday/bdayNext")
```

Incorrect Permission Assignment For Critical Resources\路徑 16:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=126
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidPostedExRateApi.java 第 13 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidPostedExRateApi.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidPostedExRateApi.java
行	13	13
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidPostedExRateApi.java

方法 @MidApiClient(application = "rem", name = "RbidPostedExRateApi", path = "postedexrate")

```
....
13.  @MidApiClient(application = "rem", name = "RbidPostedExRateApi",
path = "postedexrate")
```

Incorrect Permission Assignment For Critical Resources\路徑 17:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=127
狀態	新的
Detection Date	9/22/2025 6:05:08 PM

檔案系統中由 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidSpecialExRateApi.java 第 18 行的 path 建立一個具有潛在危險權限的檔案。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidSpecialExRateApi.java	uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidSpecialExRateApi.java
行	18	18
物件	path	path

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/xau/xau-service/src/main/java/com/scsb/ncbs/xau/service/mid/rem/RbidSpecialExRateApi.java

方法 @MidApiClient(application = "rem", name = "RbidSpecialExRateApi", path = "specialexrate")

```
....
18.  @MidApiClient(application = "rem", name = "RbidSpecialExRateApi",
path = "specialexrate")
```

Serializable Class Containing Sensitive Data

查詢路徑:

Java\Cx\Java Low Visibility\Serializable Class Containing Sensitive Data 版本:5

類別

OWASP Top 10 2013: A6-Sensitive Data Exposure
OWASP Top 10 2017: A3-Sensitive Data Exposure
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V09 Communication
OWASP Top 10 2021: A4-Insecure Design
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Serializable Class Containing Sensitive Data\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=203
狀態	新的
Detection Date	9/22/2025 6:06:37 PM

敏感資訊的欄位 lSalaryCode 在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java 的第 62 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java 的第 16 行中的 MvMidAaArrAccountEntity 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java
行	62	16
物件	lSalaryCode	MvMidAaArrAccountEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java

方法 private String lSalaryCode;

```
....
62.  private String lSalaryCode;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidAaArrAccountEntity.java

方法 @Data

```
....
16.  @Data
```

Serializable Class Containing Sensitive Data\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=204
狀態	新的
Detection Date	9/22/2025 6:06:37 PM

敏感資訊的欄位 lMailAddress 在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java 的第 102 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java 的第 14 行中的 MvMidCustomerEntity 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java
行	102	14
物件	lMailAddress	MvMidCustomerEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java

方法 private String lMailAddress;

```
....
102.  private String lMailAddress;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/persistence/entity/t24view/MvMidCustomerEntity.java

方法 @Data

```
....
14.  @Data
```

Serializable Class Containing Sensitive Data\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=205
狀態	新的
Detection Date	11/17/2025 11:24:10 AM

敏感資訊的欄位 accountNo 在 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 47 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 17 行中的 GlaRccBatchItem 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java
行	47	17
物件	accountNo	GlaRccBatchItem

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 private String accountNo;

```
....
47.  private String accountNo;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 @Data

```
....
17.  @Data
```

Serializable Class Containing Sensitive Data\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=206
狀態	新的
Detection Date	11/17/2025 11:24:10 AM

敏感資訊的欄位 debitCreditType 在 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 52 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 17 行中的 GlaRccBatchItem 欄位。

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java
行	52	17
物件	debitCreditType	GlaRccBatchItem

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 private String debitCreditType;

```
....
52.  private String debitCreditType;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 @Data

```
....
17.  @Data
```

Serializable Class Containing Sensitive Data\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=207
狀態	新的
Detection Date	11/17/2025 11:24:10 AM

敏感資訊的欄位 creditAmount 在 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 62 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java 的第 17 行中的 GlaRccBatchItem 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java
行	62	17
物件	creditAmount	GlaRccBatchItem

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 private BigDecimal creditAmount;

```
....
62.  private BigDecimal creditAmount;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaRccBatchItem.java

方法 @Data

```
....
17.  @Data
```

Serializable Class Containing Sensitive Data\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=208
狀態	新的
Detection Date	9/22/2025 6:06:37 PM

敏感資訊的欄位 accountNo 在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java 的第 40 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java 的第 15 行中的 Mt940Rs 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java
行	40	15
物件	accountNo	Mt940Rs

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java

方法 private String accountNo;

```
....
40.  private String accountNo;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/smt/bean/Mt940Rs.java

方法 @Data

```
....
15.  @Data
```

Serializable Class Containing Sensitive Data\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=209
狀態	新的
Detection Date	9/22/2025 6:06:37 PM

敏感資訊的欄位 accountNumber 在 uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java 的第 226 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java 的第 22 行中的 GlaCgljtxEntity 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java	uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java
行	226	22
物件	accountNumber	GlaCgljtxEntity

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java

方法 private String accountNumber;

```
....
226.  private String accountNumber;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-api/src/main/java/com/scsb/ncbs/gla/cgl/persistence/entity/GlaCgljtxEntity.java

方法 @Entity

```
....
22.  @Entity
```

Serializable Class Containing Sensitive Data\路徑 8:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=210
狀態	新的
Detection Date	9/22/2025 6:06:37 PM

敏感資訊的欄位 accountNumber 在 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java 的第 183 行，被插入到可序列化物件 uatFiles/ncbs-mid-repo-p2/gla/gla-

bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java 的第 16 行中的 GlaCgljtxBatchItem 欄位。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java
行	183	16
物件	accountNumber	GlaCgljtxBatchItem

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java

方法 private String accountNumber;

```
....
183.  private String accountNumber;
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/bean/reconciliation/GlaCgljtxBatchItem.java

方法 @Data

```
....
16.  @Data
```

Log Forging

查詢路徑:

Java\Cx\Java Low Visibility\Log Forging 版本:5

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.1 - Injection flaws - particularly SQL injection
FISMA 2014: System And Information Integrity
NIST SP 800-53: AU-9 Protection of Audit Information (P1)
OWASP Top 10 2017: A1-Injection
OWASP Mobile Top 10 2016: M7-Client Code Quality
OWASP ASVS: V07 Error Handling and Logging
OWASP Top 10 2021: A9-Security Logging and Monitoring Failures
ASA Mobile Premium: ASA Mobile Premium
ASA Premium: ASA Premium
ASD STIG 5.3: APSC-DV-002560 - CAT I The application must not be subject to input handling vulnerabilities.
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Log Forging\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=128

狀態	新的
Detection Date	9/22/2025 6:05:53 PM

位於uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java的224行的getImpExpIntegrationDtlLg方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java中2337行的getImpExpIntegrationDtlLg方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
行	224	2337
物件	apiRequest	info

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java

方法 public ApiResponse<ServiceRs<GetImpExpIntegrationDtlLgRs>> getImpExpIntegrationDtlLg(

```
....
224.  @RequestBody ApiRequest<ServiceRq<GetImpExpIntegrationDtlRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java

方法 public ServiceRs<GetImpExpIntegrationDtlLgRs> getImpExpIntegrationDtlLg(

```
....
2337.  log.info("getMdDealLivArg:{}", JsonUtils.toPrettyJson(argMdLiv));
```

Log Forging\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=129
狀態	新的
Detection Date	11/17/2025 11:23:23 AM

位於uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/cim11/Cim11Controller.java的41行的notifyCalypso方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/try/try-

service/src/main/java/com/scsb/ncbs/treasury/service/cim11/Cim11Service.java中71行的notifyCalypso方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/cim11/Cim11Controller.java	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/cim11/Cim11Service.java
行	41	71
物件	apiRequest	info

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/cim11/Cim11Controller.java

方法 public ApiResponse<ServiceRs<Cim11NotifyRs>> notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>> apiRequest) {

```
....
41.  public ApiResponse<ServiceRs<Cim11NotifyRs>>
notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>>
apiRequest)  {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/cim11/Cim11Service.java

方法 private void notifyCalypso(SCSBCustomerResponseBody customer) {

```
....
71.  log.info("customer={}", MidJsonUtils.toJson(customer));
```

Log Forging\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=130
狀態	新的
Detection Date	11/17/2025 11:23:23 AM

位於uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/cim11/Cim11Controller.java的41行的notifyCalypso方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/cim11/Cim11Service.java中193行的notifyCalypso方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/co	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/

	ntroller/cim11/Cim11Controller.java	service/cim11/Cim11Service.java
行	41	193
物件	apiRequest	info

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/cim11/Cim11Controller.java

方法 public ApiResponse<ServiceRs<Cim11NotifyRs>> notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>> apiRequest) {

```
....
41.  public ApiResponse<ServiceRs<Cim11NotifyRs>>
notifyCalypso(@RequestBody ApiRequest<ServiceRq<Cim11NotifyRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/cim11/Cim11Service.java

方法 public void notifyCalypso(Cim11Notify cim11Notify) {

```
....
193.  log.info("cim11Notify={}", message);
```

Log Forging\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=131
狀態	新的
Detection Date	9/22/2025 6:05:53 PM

位於uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java的210行的getImpExpIntegrationDtlLc方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java中2165行的getImpExpIntegrationDtlLc方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
行	210	2165
物件	apiRequest	info

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java
方法	public ApiResponse<ServiceRs<GetImpExpIntegrationDtlLcRs>> getImpExpIntegrationDtlLc(

```
....
210.  @RequestBody ApiRequest<ServiceRq<GetImpExpIntegrationDtlRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
方法	public ServiceRs<GetImpExpIntegrationDtlLcRs> getImpExpIntegrationDtlLc(

```
....
2165.  log.info("getLetterOfCreditHisArg:{}",
JsonUtils.toPrettyJson(argLcHis));
```

Log Forging\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=132
狀態	新的
Detection Date	9/22/2025 6:05:53 PM

位於uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java的210行的getImpExpIntegrationDtlLc方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java中2016行的getImpExpIntegrationDtlLc方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
行	210	2016
物件	apiRequest	info

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java
方法	public ApiResponse<ServiceRs<GetImpExpIntegrationDtlLcRs>> getImpExpIntegrationDtlLc(

```
....
210.  @RequestBody ApiRequest<ServiceRq<GetImpExpIntegrationDtlRq>>
apiRequest) {
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java

方法 public ServiceRs<GetImpExpIntegrationDtlLcRs> getImpExpIntegrationDtlLc(

```
....
2016.  log.info("getLetterOfCreditLivArg:{}",
JsonUtils.toPrettyJson(argLcLiv));
```

Log Forging\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=133
狀態	新的
Detection Date	11/17/2025 11:23:23 AM

位於uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/bir30/Bir30Controller.java的41行的notifyCalypso方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/bir30/Bir30Service.java中88行的notifyCalypso方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/bir30/Bir30Controller.java	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/bir30/Bir30Service.java
行	41	88
物件	apiRequest	info

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-app/src/main/java/com/scsb/ncbs/treasury/controller/bir30/Bir30Controller.java

方法 public ApiResponse<ServiceRs<Bir30NotifyRs>> notifyCalypso(@RequestBody ApiRequest<ServiceRq<Bir30NotifyRq>> apiRequest) {

```
....
41.  public ApiResponse<ServiceRs<Bir30NotifyRs>>
notifyCalypso(@RequestBody ApiRequest<ServiceRq<Bir30NotifyRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/bir30/Bir30Service.java
方法	private void notifyCalypso(SCSBSecuredLimitResponseBody limit) {

```
....
88.  log.info("Limit={}", MidJsonUtils.toJson(limit));
```

Log Forging\路徑 7:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=134
狀態	新的
Detection Date	9/22/2025 6:05:53 PM

位於uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java的224行的getImpExpIntegrationDtlLg方法，從元素apiRequest中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java中2430行的getImpExpIntegrationDtlLg方法中用於寫入稽核日誌。
這可能會導致稽核日誌偽造攻擊(Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
行	224	2430
物件	apiRequest	info

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/rem/rem-app/src/main/java/com/scsb/ncbs/rem/controller/cinq/ImpIntegrationController.java
方法	public ApiResponse<ServiceRs<GetImpExpIntegrationDtlLgRs>> getImpExpIntegrationDtlLg(

```
....
224.  @RequestBody ApiRequest<ServiceRq<GetImpExpIntegrationDtlRq>>
apiRequest) {
```

檔案名稱	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/complextradeinquiry/ComplexTradeInquiryService.java
方法	public ServiceRs<GetImpExpIntegrationDtlLgRs> getImpExpIntegrationDtlLg(

```
....
2430.  log.info("getMdDealHisArg:{}", JsonUtils.toPrettyJson(argMdHis));
```

Use of Non Cryptographic Random

查詢路徑:

Java\Cx\Java Low Visibility\Use of Non Cryptographic Random 版本:1

類別

MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V02 Authentication
OWASP Top 10 2021: A2-Cryptographic Failures
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Use of Non Cryptographic Random\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=212
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 63 行的 .randomize 方法使用了一種弱方法 nextInt 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 63 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	63	63
物件	nextInt	nextInt

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java

方法 .randomize(Integer.class, () -> ThreadLocalRandom.current().nextInt(1, 1001))

```
....
63.  .randomize(Integer.class, () ->
ThreadLocalRandom.current().nextInt(1, 1001))
```

Use of Non Cryptographic Random\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathi

	d=213
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 65 行的 .randomize 方法使用了一種弱方法 nextDouble 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 65 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	65	65
物件	nextDouble	nextDouble

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java

方法 .randomize(BigDecimal.class, () -> BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01, 1000.01))

```
....
65.  .randomize(BigDecimal.class, () ->
BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01,
1000.01))
```

Use of Non Cryptographic Random\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=214
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 97 行的 .randomize 方法使用了一種弱方法 nextInt 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 97 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	97	97
物件	nextInt	nextInt

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
方法	.randomize(Integer.class, () -> ThreadLocalRandom.current().nextInt(1, 1001))

```
....
97.  .randomize(Integer.class, () ->
ThreadLocalRandom.current().nextInt(1, 1001))
```

Use of Non Cryptographic Random\路徑 4:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=215
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 99 行的 .randomize 方法使用了一種弱方法 nextDouble 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 99 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	99	99
物件	nextDouble	nextDouble

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
方法	.randomize(BigDecimal.class, () -> BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01, 1000.01))

```
....
99.  .randomize(BigDecimal.class, () ->
BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01,
1000.01))
```

Use of Non Cryptographic Random\路徑 5:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=216
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 162 行的 .randomize 方法使用了一種弱方法 nextInt 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 162 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	162	162
物件	nextInt	nextInt

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java

方法 .randomize(Integer.class, () -> ThreadLocalRandom.current().nextInt(1, 1001))

```
....
162.  .randomize(Integer.class, () ->
ThreadLocalRandom.current().nextInt(1, 1001))
```

Use of Non Cryptographic Random\路徑 6:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=217
狀態	新的
Detection Date	12/19/2025 4:53:30 PM

位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 164 行的 .randomize 方法使用了一種弱方法 nextDouble 來生成隨機值。這些值隨後由位於 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java 中第 164 行的 .randomize 方法用作加密變數。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java	uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java
行	164	164
物件	nextDouble	nextDouble

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-service/src/main/java/com/scsb/ncbs/gla/service/teller/TellerEodDailyInOutService.java

方法 .randomize(BigDecimal.class, () -> BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01, 1000.01))

```
....
164.  .randomize(BigDecimal.class, () ->
BigDecimal.valueOf(ThreadLocalRandom.current().nextDouble(0.01,
1000.01))
```

Portability Flaw Locale Dependent Comparison

查詢路徑:

Java\Cx\Java Low Visibility\Portability Flaw Locale Dependent Comparison 版本:4

描述

Portability Flaw Locale Dependent Comparison\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=198
狀態	新的
Detection Date	3/5/2026 10:19:50 AM

應用程式在處理字串時未指定特定語系。特別是在文件uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/query/PaymentCalculationService.java中的第273行的sumPropertiesMatch方法呼叫toUpperCase時。這個字串經處理後的結果與文件uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/query/PaymentCalculationService.java中的第273行的sumPropertiesMatch方法的contains進行比較。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/query/PaymentCalculationService.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/query/PaymentCalculationService.java
行	273	273
物件	toUpperCase	contains

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/len/len-service/src/main/java/com/scsb/ncbs/len/service/query/PaymentCalculationService.java

方法 BigDecimal feeTotal = sumPropertiesMatch(simulationLatestBody.getProperties(), prop -> prop.toUpperCase().contains("FEE"));

```
....
273.  BigDecimal feeTotal =
sumPropertiesMatch(simulationLatestBody.getProperties(), prop ->
prop.toUpperCase().contains("FEE"));
```

Portability Flaw Locale Dependent Comparison\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=199
狀態	新的
Detection Date	3/5/2026 10:19:50 AM

應用程式在處理字串時未指定特定語系。特別是在文件uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java中的第44行的generateSeqValue方法呼叫toUpperCase時。這個字串經處理後的結果與文件uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java中的第92行的print方法的isBlank進行比較。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java
行	44	92
物件	toUpperCase	isBlank

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java

方法 public String generateSeqValue(SeqContext context, SeqConfig config) {

```
....
44.  .append(Long.toString(seqNo1, 36).toUpperCase())
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java

方法 public ServiceRs<WithHoldingTaxPrintRs> print(WithHoldingTaxPrintArg arg) {

```
....
92.  if (StringUtils.isBlank(rs.getCountryCode()) &&
"TW".equals(rs.getCountryCode())) {
```

Portability Flaw Locale Dependent Comparison\路徑 3:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=200
狀態	新的
Detection Date	3/5/2026 10:19:50 AM

應用程式在處理字串時未指定特定語系。特別是在文件uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java中的第44行的generateSeqValue方法呼叫toUpperCase時。這個字串經處理後的結果與文件uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java中的第92行的print方法的equals進行比較。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java	uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java

行	44	92
物件	toUpperCase	equals

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/utils/seq/WithholdingTaxSeqGenerator.java

方法 public String generateSeqValue(SeqContext context, SeqConfig config) {

```
....
44.  .append(Long.toString(seqNo1, 36).toUpperCase())
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/try/try-service/src/main/java/com/scsb/ncbs/treasury/service/si/WithholdingTaxService.java

方法 public ServiceRs<WithHoldingTaxPrintRs> print(WithHoldingTaxPrintArg arg) {

```
....
92.  if (StringUtils.isBlank(rs.getCountryCode()) &&
"TW".equals(rs.getCountryCode())) {
```

Reversible One Way Hash

查詢路徑:

Java\Cx\Java Low Visibility\Reversible One Way Hash 版本:4

類別

OWASP Top 10 2013: A6-Sensitive Data Exposure
FISMA 2014: Media Protection
NIST SP 800-53: SC-13 Cryptographic Protection (P1)
OWASP Top 10 2017: A3-Sensitive Data Exposure
OWASP Top 10 API: API2-Broken Authentication
OWASP Top 10 2021: A2-Cryptographic Failures

描述

Reversible One Way Hash\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=201
狀態	新的
Detection Date	3/5/2026 10:19:54 AM

應用程式在32 行的uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/DefaultMessageDigester.java 中使用弱 Hashing primitivegetSha1Digest

	來源	目的地
檔案	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/DefaultMessageDigester.ja	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/DefaultMessageDigester.ja

	va	va
行	32	32
物件	getSha1Digest	getSha1Digest

代碼片斷

檔案名稱 uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/DefaultMessageDigester.java

方法 private String computeDigest(String message) {

```
....
32.  MessageDigest messageDigest = DigestUtils.getSha1Digest();
```

Reversible One Way Hash\路徑 2:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=202
狀態	新的
Detection Date	3/5/2026 10:19:54 AM

應用程式在107 行的uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/TotpMessageDigester.java 中使用弱 Hashing primitivegetSha1Digest

	來源	目的地
檔案	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/TotpMessageDigester.java	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/TotpMessageDigester.java
行	107	107
物件	getSha1Digest	getSha1Digest

代碼片斷

檔案名稱 uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/codec/TotpMessageDigester.java

方法 protected byte[] computeMessageKey(String message, byte[] saltBytes) {

```
....
107.  MessageDigest messageDigest = DigestUtils.getSha1Digest();
```

Information Exposure Through an Error Message

查詢路徑:

Java\Cx\Java Low Visibility\Information Exposure Through an Error Message 版本:6

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.5 - Improper error handling

OWASP Top 10 2013: A5-Security Misconfiguration
FISMA 2014: Configuration Management
NIST SP 800-53: SI-11 Error Handling (P2)
OWASP Top 10 2017: A6-Security Misconfiguration
OWASP Top 10 API: API3-Excessive Data Exposure
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Error processing
OWASP ASVS: V14 Configuration
OWASP Top 10 2021: A4-Insecure Design
SANS top 25: SANS top 25
ASD STIG 5.3: APSC-DV-002570 - CAT II The application must generate error messages that provide information necessary for corrective actions without revealing information that could be exploited by adversaries.
OWASP Top 10 API 2023: API8-Security Misconfiguration
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Information Exposure Through an Error Message\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=110
狀態	新的
Detection Date	12/19/2025 4:51:03 PM

在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java 第 112 行的 base64ToPdf 方法處理了例外或執行錯誤 e。 在例外處理期間，應用程式在 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java base64ToPdf 方法中將例外詳細資訊 printStackTrace 揭露。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java
行	112	114
物件	e	printStackTrace

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/test/java/com/scsb/ncbs/dep/service/BaseServiceIT.java
方法	protected String base64ToPdf(String base64Content, String fileName) {

```
....
112.  } catch (Exception e) {
....
114.  e.printStackTrace();
```

Off by One Error

查詢路徑:

Java\Cx\Java Low Visibility\Off by One Error 版本:5

類別

NIST SP 800-53: SI-16 Memory Protection (P1)
OWASP Top 10 2021: A4-Insecure Design

描述

Off by One Error\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=197
狀態	新的
Detection Date	9/22/2025 6:06:03 PM

在 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/pazzword/CbrPazzwordUpdateBatchService.java 的第 82 行使用可能存在偏差的迭代器對 lastPazzwordList 中的資料集進行迭代。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/pazzword/CbrPazzwordUpdateBatchService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/pazzword/CbrPazzwordUpdateBatchService.java
行	82	82
物件	lastPazzwordList	lastPazzwordList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/pazzword/CbrPazzwordUpdateBatchService.java

方法 public void updatePazzword(String actNo) {

```
....
82.  if (!lastPazzwordList.contains(newPazzword)) {
```

Stored Log Forging

查詢路徑:

Java\Cx\Java Low Visibility\Stored Log Forging 版本:5

類別

FISMA 2014: System And Information Integrity
NIST SP 800-53: AU-9 Protection of Audit Information (P1)
OWASP Top 10 2017: A1-Injection
OWASP ASVS: V07 Error Handling and Logging
OWASP Top 10 2021: A9-Security Logging and Monitoring Failures
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Stored Log Forging\路徑 1:

嚴重程度：	低風險

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=211
狀態	新的
Detection Date	9/22/2025 6:06:43 PM

位於uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java的106行的read方法，從元素readByBeneficiaryStartingWith中獲取了使用者輸入。該元素的值在程式碼中未經適當的消毒或驗證即被傳遞，最終在uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteServiceIT.java中81行的assertDoesNotThrow方法中用於寫入稽核日誌。
這可能會導致儲存型稽核日誌偽造攻擊(Stored Log Forging)。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteServiceIT.java
行	106	81
物件	readByBeneficiaryStartingWith	info

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/main/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteService.java

方法 public ServiceRs<LcAdvisingCustNoteReadRs> read(@NotNull @Valid LcAdvisingCustNoteReadArg arg) {

```
....
106.  List<LcAdvisingCustNote> datas =
advisingCustNoteRepository.readByBeneficiaryStartingWith(arg.getBenefici
ary())
```

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/tfsf/lcadvisingcustnote/LcAdvisingCustNoteServiceIT.java

方法 assertDoesNotThrow(() -> {

```
....
81.  log.info("查詢結果： {}", svrRs.getContent());
```

Use Of Hardcoded Password

查詢路徑:

Java\Cx\Java Low Visibility\Use Of Hardcoded Password 版本:8

類別

PCI DSS v3.2.1: PCI DSS (3.2.1) - 6.5.10 - Broken authentication and session management

OWASP Top 10 2013: A2-Broken Authentication and Session Management
FISMA 2014: Identification And Authentication
NIST SP 800-53: SC-28 Protection of Information at Rest (P1)
OWASP Top 10 2017: A2-Broken Authentication
OWASP Mobile Top 10 2016: M9-Reverse Engineering
CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V02 Authentication
OWASP Top 10 2021: A7-Identification and Authentication Failures
SANS top 25: SANS top 25
ASA Mobile Premium: ASA Mobile Premium
ASA Premium: ASA Premium
ASD STIG 5.3: APSC-DV-001740 - CAT I The application must only store cryptographic representations of passwords.
OWASP Top 10 API 2023: API2-Broken Authentication
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Use Of Hardcoded Password\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=218
狀態	新的
Detection Date	9/22/2025 6:07:31 PM

應用程式使用寫死的密碼 OPT_MSG_FLD_PASSWORD 來進行身分驗證或存取其他遠端系統。uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java 第 125 行的密碼出現在程式碼中，這意味著任何可以存取原始碼的人都可以輕易的存取這組密碼，而且除非應用程式重建，否則這組密碼會無法進行更改。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java
行	125	125
物件	OPT_MSG_FLD_PASSWORD	OPT_MSG_FLD_PASSWORD

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/service/ntf/message/NtfMessageService.java

方法 private static final String OPT_MSG_FLD_PASSWORD = "PASSWORD";

```
....
125.  private static final String OPT_MSG_FLD_PASSWORD = "PASSWORD";
```

Spring Missing Content Security Policy

查詢路徑:

Java\Cx\Java Spring\Spring Missing Content Security Policy 版本:4

類別

OWASP ASVS: V14 Configuration
OWASP Top 10 2021: A7-Identification and Authentication Failures
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

Spring Missing Content Security Policy\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=219
狀態	新的
Detection Date	3/5/2026 10:20:10 AM

Web 應用程式中未明確定義內容安全性原則。

	來源	目的地
檔案	uatFiles/cbmp-fabric/cbmp-fabric-boot-autoconfigure/src/main/java/com/ibm/cbmp/fabric/autoconfigure/api/ExceptionHandlerAutoConfiguration.java	uatFiles/cbmp-fabric/cbmp-fabric-boot-autoconfigure/src/main/java/com/ibm/cbmp/fabric/autoconfigure/api/ExceptionHandlerAutoConfiguration.java
行	3	3
物件	autoconfigure	autoconfigure

代碼片斷

檔案名稱 uatFiles/cbmp-fabric/cbmp-fabric-boot-autoconfigure/src/main/java/com/ibm/cbmp/fabric/autoconfigure/api/ExceptionHandlerAutoConfiguration.java

方法 import org.springframework.boot.autoconfigure.AutoConfiguration;

```
....
3.  import org.springframework.boot.autoconfigure.AutoConfiguration;
```

TruffleHog Regex Matches

查詢路徑:

Java\Cx\Java Low Visibility\TruffleHog Regex Matches 版本:1

類別

CWE top 25: CWE top 25
MOIS(KISA) Secure Coding 2021: MOIS(KISA) Security Functions
OWASP ASVS: V06 Stored Cryptography
OWASP Top 10 2021: A7-Identification and Authentication Failures
SANS top 25: SANS top 25
PCI DSS v4.0: PCI DSS (4.0) - 6.2.4 Vulnerabilities in software development

描述

TruffleHog Regex Matches\路徑 1:

嚴重程度：	低風險
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=543
狀態	新的
Detection Date	1/23/2026 6:48:40 PM

應用程式使用寫死的密碼

apiKey":[]}],"paths":{"/enterprise/scsbdp0154/create/{id}":{"post":{"tags":["RETAIL"],"summary":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","description":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","operationId":"inputSCSBChequeRegisterSupplement" 來進行身分驗證或存取其他遠端系統。uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/resources/t24/scsb-dp0154-v1.0.0.json 第 1 行的密碼出現在程式碼中，這意味著任何可以存取原始碼的人都可以輕易的存取這組密碼，而且除非應用程式重建，否則這組密碼會無法進行更改。

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/resources/t24/scsb-dp0154-v1.0.0.json	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/resources/t24/scsb-dp0154-v1.0.0.json
行	1	1
物件	apiKey":[]}],"paths":{"/enterprise/scsbdp0154/create/{id}":{"post":{"tags":["RETAIL"],"summary":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","description":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","operationId":"inputSCSBChequeRegisterSupplement"	apiKey":[]}],"paths":{"/enterprise/scsbdp0154/create/{id}":{"post":{"tags":["RETAIL"],"summary":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","description":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","operationId":"inputSCSBChequeRegisterSupplement"

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/resources/t24/scsb-dp0154-v1.0.0.json

方法 ...,"basePath":"/api/v1.0.0/","tags":[{"name":"RETAIL"}],"schemes":["http","https"],"security":[{"basicAuth":[]},{"apiKey":[]}],"paths":{"/enterprise/scsbdp0154/create/{id}":{"post":{"tags":["RETAIL"],"summary":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","description":"CHEQUE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","operationId":"inputSCSBChequeRegisterSupplement","produces":["application/json"],"parameters":[{"name":"id","in":"path","de...

```
....
1.
...,"basePath":"/api/v1.0.0/","tags":[{"name":"RETAIL"}],"schemes":["http
p","https"],"security":[{"basicAuth":[]},{"apiKey":[]}],"paths":{"/enter
prise/scsbdp0154/create/{id}":{"post":{"tags":["RETAIL"],"summary":"CHEQ
UE.REGISTER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","description":"CHEQUE.REGI
STER.SUPPLEMENT,CQ.API.SCSB.INP.1.0.0","operationId":"inputSCSBChequeReg
isterSupplement","produces":["application/json"],"parameters":[{"name":"
id","in":"path","de...
```

Insufficient Logging of Exceptions

查詢路徑:

Java\Cx\Java Best Coding Practice\Insufficient Logging of Exceptions 版本:2

類別

OWASP ASVS: V07 Error Handling and Logging
OWASP Top 10 2021: A9-Security Logging and Monitoring Failures

描述

Insufficient Logging of Exceptions\路徑 1:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=861
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 102, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java
行	102	102
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java

方法 public boolean validateHmacHex(String hmac) {

```
....
102.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 2:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=862
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 115, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java	uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java
行	115	115
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/cbmp-fabric/cbmp-fabric-foundation/src/main/java/com/ibm/cbmp/fabric/foundation/toolkit/TotpHelper.java

方法	public boolean validateHmacBase64(String hmac) {

```
....
115.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 3:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=863
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 25, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java
行	25	25
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java
方法	public static T24Notify parseNotifitionXML(String xml) {

```
....
25.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 4:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=864
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 39, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java

行	39	39
物件	catch	catch

代碼片斷
檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java
方法 public static T24Customer parseCustomerXML(String xml) {

```
....
39.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 5:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=865
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 51, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java
行	51	51
物件	catch	catch

代碼片斷
檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-notify-t24/src/main/java/com/scsb/ncbs/notify/t24/T24NotifyParser.java
方法 public static T24Bargain parseBargainXML(String xml) {

```
....
51.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 6:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=866
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 105, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java
行	105	105
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java

方法 private void processData() {

```
....
105.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 7:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=867
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 128, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java
行	128	128
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrDailyThresholdAccuSyncTasklet.java

方法 private List<CbrMvDailyThresholdAccuBean> fetchCbrMvDailyThresholdAccu(LocalDate dataDate) {

```
....
128.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 8:

嚴重程度：	資訊

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=868
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 103, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java
行	103	103
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java

方法 private void processData() {

```
....
103.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 9:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=869
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 125, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java
行	125	125
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/accu/CbrScsbLimitUpdateSyncTasklet.java

方法 private List<CbrMvScsbLimitUpdateBean> fetchMvScsbLimitUpdate(LocalDate dataDate) {

```
....
125.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 10:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=870
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 110, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java
行	110	110
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java

方法 private void processData() {

```
....
110.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 11:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=871
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 132, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java
行	132	132
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/file/FileMDataSrcSyncTasklet.java
方法	private List<SCSBCbrFcyDepositsRep> fetchScsbCbrFcyDepositsRep(LocalDate dataDate) {

```
....
132.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 12:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=872
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 518, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java
行	518	518
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/raw/CbrRawDataSyncJobConfig.java
方法	private BigDecimal getNumber(String amt) {

```
....
518.  } catch (NumberFormatException e) {
```

Insufficient Logging of Exceptions\路徑 13:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=873
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 130, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/jo	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/jo

	b/rcv/CbrReceiveFVEXC03Tasklet.java	b/rcv/CbrReceiveFVEXC03Tasklet.java
行	130	130
物件	catch	catch

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrReceiveFVEXC03Tasklet.java
方法 private void loadFile(StepContribution contribution) {

```
....
130.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 14:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=874
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 128, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrReceiveVSFEINBTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrReceiveVSFEINBTasklet.java
行	128	128
物件	catch	catch

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrReceiveVSFEINBTasklet.java
方法 private void loadFile(StepContribution contribution) {

```
....
128.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 15:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=875
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 84, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java
行	84	84
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java

方法 private void processData(StepContribution contribution) {

```
....
84.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 16:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=876
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 100, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java
行	100	100
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteFVEXC03ToDataSrcTasklet.java

方法 public void saveToDataSrc(List<CbrFvexc03TmpEntity> items) {

```
....
100.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 17:

嚴重程度：	資訊
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=877
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 110, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java
行	110	110
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java

方法 private void processData(StepContribution contribution) {

```
....
110.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 18:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=878
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 126, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java
行	126	126
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/main/java/com/scsb/ncbs/cbr/batch/job/rcv/CbrWriteVSFEINBToDataSrcTasklet.java

方法 public void saveToDataSrc(List<CbrVsfeinbMergedTmpEntity> items) {

```
....
126.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 19:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=879
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 28, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrDailyThresholdAccuSyncIT.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrDailyThresholdAccuSyncIT.java
行	28	28
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrDailyThresholdAccuSyncIT.java

方法 public void testTaskletJob() throws JobExecutionException {

```
....
28.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 20:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=880
狀態	新的
Detection Date	1/23/2026 6:50:08 PM

In line 28, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrScsbLimitUpdateSyncIT.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrScsbLimitUpdateSyncIT.java
行	28	28
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/accu/CbrScsbLimitUpdateSyncIT.java
方法	public void testTasklet Job() throws JobExecutionException {

```
....
28.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 21:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=881
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 36, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/file/FileMDataSrcSyncIT.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/file/FileMDataSrcSyncIT.java
行	36	36
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-bat/src/test/java/com/scsb/ncbs/cbr/file/FileMDataSrcSyncIT.java
方法	public void testTasklet Job() throws JobExecutionException {

```
....
36.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 22:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=882
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 192, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/persi	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/persi

	stence/repository/data/CbrDataModRepository.java	stence/repository/data/CbrDataModRepository.java
行	192	192
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/persistence/repository/data/CbrDataModRepository.java

方法 default long readCountByCbrDateAndDataNoAndDeleteFlag(LocalDate cbrDate, String dataNo, boolean deleteFlag) {

```
....
192.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 23:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=883
狀態	新的
Detection Date	3/5/2026 10:20:38 AM

In line 179, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/branch/helper/CoreCbrDataHelper.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/branch/helper/CoreCbrDataHelper.java
行	179	179
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/branch/helper/CoreCbrDataHelper.java

方法 private BigDecimal getAmt(String sign, String amt) {

```
....
179.  } catch (NumberFormatException e) {
```

Insufficient Logging of Exceptions\路徑 24:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=884
狀態	新的

Detection Date	9/22/2025 6:08:43 PM

In line 570, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
行	570	570
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java

方法 private CbrFileCompilationSummary compileData(@NotNull LocalDate maxCompletedCbrDate, @NotNull LocalDate nextCbrDate, boolean batchProcess) {

```
....
570.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 25:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=885
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 920, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
行	920	920
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java

方法 private List<Long> createFileA(@NotNull final Long cbrFileMasterListId, @NotNull @Valid List<CbrFileA> fileAs) {

```
....
920.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 26:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=886
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 948, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
行	948	948
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java

方法 private List<Long> createFileB(@NotNull final Long cbrFileMasterListId, @NotNull @Valid List<CbrFileB> fileBs) {

```
....
948.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 27:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=887
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 976, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
行	976	976
物件	catch	catch

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
方法	private List<Long> createFileF(@NotNull final Long cbrFileMasterListId, @NotNull @Valid List<CbrFileF> fileFs) {

```
....
976.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 28:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=888
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1004, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
行	1004	1004
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java
方法	private List<Long> createFileG(@NotNull final Long cbrFileMasterListId, @NotNull @Valid List<CbrFileG> fileGs) {

```
....
1004.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 29:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=889
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1032, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/servi	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/servi

	ce/file/CbrFileCompilationService.java	ce/file/CbrFileCompilationService.java
行	1032	1032
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileCompilationService.java

方法 private List<Long> createFileK(@NotNull final Long cbrFileMasterListId, @NotNull @Valid List<CbrFileK> fileKs) {

```
....
1032.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 30:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=890
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 109, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java
行	109	109
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java

方法 public LocalDate getMaxCompletedCbrDate() {

```
....
109.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 31:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=891
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 155, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java
行	155	155
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileMasterService.java

方法 private LocalDate nextBizDate(LocalDate baseDate) {

```
....
155.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 32:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=892
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1401, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java
行	1401	1401
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java

方法 public void deleteFileAByCbrDataModListId(long cbrDataModListId) {

```
....
1401.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 33:

嚴重程度：	資訊
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=893
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1437, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java
行	1437	1437
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java

方法 public void deleteFileBByCbrDataModListId(long cbrDataModListId) {

```
....
1437.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 34:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=894
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1473, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java
行	1473	1473
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java

方法 public void deleteFileFByCbrDataModListId(long cbrDataModListId) {

```
....
1473.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 35:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=895
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 1509, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java
行	1509	1509
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/service/file/CbrFileService.java

方法 public void deleteFileGByCbrDataModListId(long cbrDataModListId) {

```
....
1509.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 36:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=896
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 21, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java
行	21	21
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java
方法	public static boolean isValidDateString(String dateValue) {

```
....
21.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 37:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=897
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 35, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java
行	35	35
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-service/src/main/java/com/scsb/ncbs/cbr/utils/CbrCoreDataUtils.java
方法	public static LocalDate stringToLocalDate(String dateValue) {

```
....
35.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 38:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=898
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 93, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/j	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/j

	ob/branchmapping/BranchMappingTasklet.java	ob/branchmapping/BranchMappingTasklet.java
行	93	93
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/branchmapping/BranchMappingTasklet.java

方法 private List<String> importToCmnBranchMapping(List<BranchMappingResponseBody> branchMappingList) {

```
....
93.  } catch (InsertFailureException e) {
```

Insufficient Logging of Exceptions\路徑 39:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=899
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 96, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/branchmapping/BranchMappingTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/branchmapping/BranchMappingTasklet.java
行	96	96
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/branchmapping/BranchMappingTasklet.java

方法 private List<String> importToCmnBranchMapping(List<BranchMappingResponseBody> branchMappingList) {

```
....
96.  } catch (UpdateFailureException e) {
```

Insufficient Logging of Exceptions\路徑 40:

嚴重程度：	資訊
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=900
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 187, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java
行	187	187
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java

方法 private void updateT24LostCustomerDetails(String custId, LocalDate runDate) {

```
....
187.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 41:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=901
狀態	新的
Detection Date	9/22/2025 6:08:43 PM

In line 252, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java
行	252	252
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java

方法 private void updateT24LostCustomerDetails(String custId, LocalDate runDate) {

```
....
252.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 42:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=902
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 267, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java
行	267	267
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ntf/PendMailVerifyBatchService.java

方法 private void notifyTryCalypsoCim11(String custId) {

```
....
267.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 43:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=903
狀態	新的
Detection Date	9/26/2025 6:30:03 PM

In line 104, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterBatchTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterBatchTasklet.java
行	104	104
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterBatchTasklet.java
方法	protected void doProcess(StepContribution contribution, ChunkContext chunkContext) {

```
....
104.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 44:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=904
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 101, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java
行	101	101
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java
方法	public boolean refreshMvAsync(LocalDate runDate, LocalDateTime runDatetime) {

```
....
101.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 45:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=905
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 122, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java
行	122	122
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java

方法 public boolean checkMvSyncCompleted() {

```
....
122.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 46:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=906
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 139, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java
行	139	139
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchAfterMvUpdatedJobConfig.java

方法 public String getLatestMvStatus() {

```
....
139.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 47:

嚴重程度：	資訊
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=907
狀態	新的
Detection Date	9/26/2025 6:30:03 PM

In line 116, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartEodTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartEodTasklet.java
行	116	116
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartEodTasklet.java

方法 protected void doProcess(StepContribution contribution, ChunkContext chunkContext) {

```
....
116.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 48:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=908
狀態	新的
Detection Date	9/26/2025 6:30:03 PM

In line 85, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartReportingTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartReportingTasklet.java
行	85	85
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartReportingTasklet.java

方法 protected void doProcess(StepContribution contribution, ChunkContext chunkContext) {

```
....
85.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 49:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=909
狀態	新的
Detection Date	9/26/2025 6:30:03 PM

In line 115, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartSodTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartSodTasklet.java
行	115	115
物件	catch	catch

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/t24batch/WatchStartSodTasklet.java

方法 protected void doProcess(StepContribution contribution, ChunkContext chunkContext) {

```
....
115.  } catch (Exception e) {
```

Insufficient Logging of Exceptions\路徑 50:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=910
狀態	新的
Detection Date	12/19/2025 4:55:03 PM

In line 342, the security-critical event is not logged properly and, therefore,the error message has some important details omitted.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/listener/MdsNotifyListener.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/listener/MdsNotifyListener.java
行	342	342
物件	catch	catch

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-service/src/main/java/com/scsb/ncbs/cmn/listener/MdsNotifyListener.java
方法	private String getDefaultDateTime(Date date, boolean isDate) {

```
....
342.  } catch (DateTimeParseException e) {
```

Undocumented API

查詢路徑:

Java\Cx\Java Best Coding Practice\Undocumented API 版本:3

類別

OWASP ASVS: V01 Architecture, Design and Threat Modeling

描述

Undocumented API\路徑 1:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=554
狀態	新的
Detection Date	11/3/2025 5:07:20 PM

The application's getFiscTxDate method (line 35) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java
行	35	35
物件	getFiscTxDate	getFiscTxDate

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-service/src/main/java/com/scsb/ncbs/dep/service/fep/FepOtherApi.java
方法	QueryFiscTxDateRs getFiscTxDate();

```
....
35.  QueryFiscTxDateRs getFiscTxDate();
```

Undocumented API\路徑 2:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=555
狀態	新的
Detection Date	3/5/2026 10:20:16 AM

The application's send method (line 42) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java	uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java
行	42	42
物件	send	send

代碼片斷

檔案名稱 uatFiles/ncbs-mid-foundation-repo-p2/mid-integration-parent/mid-integration-message/src/main/java/com/scsb/ncbs/intg/message/controller/MidMessageController.java

方法 public ApiResponse<ServiceRs<MessageRs>> send(@RequestBody ApiRequest<ServiceRq<MessageRq>> apiRequest) {

```
....
42.  public ApiResponse<ServiceRs<MessageRs>> send(@RequestBody
ApiRequest<ServiceRq<MessageRq>> apiRequest) {
```

Undocumented API\路徑 3:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=556
狀態	新的
Detection Date	3/5/2026 10:20:16 AM

The application's read method (line 48) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java
行	48	48
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchDataInquiryController.java

方法 public ApiResponse<ServiceRs<BranchDataInquiryReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchDataInquiryReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchDataInquiryReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchDataInquiryReadRq>>
apiRequest) {
```

Undocumented API\路徑 4:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=557
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's read method (line 48) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java
行	48	48
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/branch/BranchFxSettlementController.java

方法 public ApiResponse<ServiceRs<BranchFxSettlementReadRs>> read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>> apiRequest) {

```
....
48.  public ApiResponse<ServiceRs<BranchFxSettlementReadRs>>
read(@RequestBody ApiRequest<ServiceRq<BranchFxSettlementReadRq>>
apiRequest) {
```

Undocumented API\路徑 5:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=558
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's create method (line 59) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

行	59	59
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<CbrDataModCreateRs>> create(@RequestBody ApiRequest<ServiceRq<CbrDataModCreateRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<CbrDataModCreateRs>>
create(@RequestBody ApiRequest<ServiceRq<CbrDataModCreateRq>>
apiRequest) {
```

Undocumented API\路徑 6:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=559
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's read method (line 73) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	73	73
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<CbrDataModReadRs>> read(@RequestBody ApiRequest<ServiceRq<CbrDataModReadRq>> apiRequest) {

```
....
73.  public ApiResponse<ServiceRs<CbrDataModReadRs>> read(@RequestBody
ApiRequest<ServiceRq<CbrDataModReadRq>> apiRequest) {
```

Undocumented API\路徑 7:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=560
狀態	新的

Detection Date	9/22/2025 6:07:47 PM

The application's update method (line 87) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	87	87
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<CbrDataModUpdateRs>> update(@RequestBody ApiRequest<ServiceRq<CbrDataModUpdateRq>> apiRequest) {

```
....
87.  public ApiResponse<ServiceRs<CbrDataModUpdateRs>>
update(@RequestBody ApiRequest<ServiceRq<CbrDataModUpdateRq>>
apiRequest) {
```

Undocumented API\路徑 8:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=561
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's delete method (line 101) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	101	101
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<CbrDataModDeleteRq>> apiRequest) {

```
....
101.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<CbrDataModDeleteRq>> apiRequest) {
```

Undocumented API\路徑 9:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=562
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's reject method (line 115) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	115	115
物件	reject	reject

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> reject(@RequestBody ApiRequest<ServiceRq<CbrDataModRejectRq>> apiRequest) {

```
....
115.  public ApiResponse<ServiceRs<EmptyRs>> reject(@RequestBody
ApiRequest<ServiceRq<CbrDataModRejectRq>> apiRequest) {
```

Undocumented API\路徑 10:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=563
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's amend method (line 129) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
行	129	129

物件	amend	amend

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cbr/cbr-app/src/main/java/com/scsb/ncbs/cbr/controller/data/CbrDataModController.java
方法	public ApiResponse<ServiceRs<CbrDataModAmendRs>> amend(@RequestBody ApiRequest<ServiceRq<CbrDataModAmendRq>> apiRequest) {

```
....
129.  public ApiResponse<ServiceRs<CbrDataModAmendRs>>
amend(@RequestBody ApiRequest<ServiceRq<CbrDataModAmendRq>> apiRequest)
{
```

Undocumented API\路徑 11:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=564
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's create method (line 37) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java
行	37	37
物件	create	create

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ecif/eciflog/EcifLogController.java
方法	public ApiResponse<?> create(@RequestBody ApiRequest<ServiceRq<EcifLogCreateRq>> apiRequest) {

```
....
37.  public ApiResponse<?> create(@RequestBody
ApiRequest<ServiceRq<EcifLogCreateRq>> apiRequest)  {
```

Undocumented API\路徑 12:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=565
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's create method (line 53) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	53	53
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<NtfEmailVerCreateRq>> apiRequest) {

```
....
53.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerCreateRq>> apiRequest) {
```

Undocumented API\路徑 13:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=566
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's read method (line 60) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	60	60
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<NtfEmailVerReadRs>> read(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadRq>> apiRequest) {

```
....
60.  public ApiResponse<ServiceRs<NtfEmailVerReadRs>> read(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerReadRq>> apiRequest) {
```

Undocumented API\路徑 14:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=567
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's reverify method (line 67) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	67	67
物件	reverify	reverify

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
方法	public ApiResponse<ServiceRs<EmptyRs>> reverify(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReverifyRq>> apiRequest) {

```
....
67.  public ApiResponse<ServiceRs<EmptyRs>> reverify(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerReverifyRq>> apiRequest) {
```

Undocumented API\路徑 15:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=568
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's update method (line 74) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	74	74
物件	update	update

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
方法	public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<NtfEmailVerUpdateRq>> apiRequest) {

```
....
74.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerUpdateRq>> apiRequest) {
```

Undocumented API\路徑 16:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=569
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's delete method (line 81) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	81	81
物件	delete	delete

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
方法	public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<NtfEmailVerDeleteRq>> apiRequest) {

```
....
81.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<NtfEmailVerDeleteRq>> apiRequest) {
```

Undocumented API\路徑 17:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=570
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's readStatus method (line 88) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java
行	88	88
物件	readStatus	readStatus

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/ntf/emailver/NtfEmailVerController.java

方法 public ApiResponse<ServiceRs<NtfEmailVerReadStatusRs>> readStatus(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadStatusRq>> apiRequest) {

```
....
88.  public ApiResponse<ServiceRs<NtfEmailVerReadStatusRs>>
readStatus(@RequestBody ApiRequest<ServiceRq<NtfEmailVerReadStatusRq>>
apiRequest) {
```

Undocumented API\路徑 18:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=571
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's create method (line 51) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	51	51
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<TextCodeDescCreateRq>> apiRequest) {

```
....
51.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<TextCodeDescCreateRq>> apiRequest) {
```

Undocumented API\路徑 19:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=572
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's update method (line 58) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	58	58
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<TextCodeDescUpdateRq>> apiRequest) {

```
....
58.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<TextCodeDescUpdateRq>> apiRequest) {
```

Undocumented API\路徑 20:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=573
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's delete method (line 65) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	65	65
物件	delete	delete

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
方法	public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<TextCodeDescDeleteRq>> apiRequest) {

```
....
65.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<TextCodeDescDeleteRq>> apiRequest) {
```

Undocumented API\路徑 21:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=574
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's read method (line 72) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	72	72
物件	read	read

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
方法	public ApiResponse<ServiceRs<TextCodeDescReadRs>> read(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadRq>> apiRequest) {

```
....
72.  public ApiResponse<ServiceRs<TextCodeDescReadRs>> read(@RequestBody
ApiRequest<ServiceRq<TextCodeDescReadRq>> apiRequest) {
```

Undocumented API\路徑 22:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=575
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's readList method (line 79) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java
行	79	79
物件	readList	readList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/parm/textcode/TextCodeDescController.java

方法 public ApiResponse<ServiceRs<TextCodeDescReadListRs>> readList(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadListRq>> apiRequest) {

```
....
79.  public ApiResponse<ServiceRs<TextCodeDescReadListRs>>
readList(@RequestBody ApiRequest<ServiceRq<TextCodeDescReadListRq>>
apiRequest) {
```

Undocumented API\路徑 23:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=576
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's create method (line 50) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	50	50
物件	create	create

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateCreateRq>> apiRequest) {

```
....
50.  public ApiResponse<ServiceRs<EmptyRs>> create(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateCreateRq>> apiRequest) {
```

Undocumented API\路徑 24:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=577
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's read method (line 58) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	58	58
物件	read	read

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<IntRateProjectRelateReadRs>> read(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadRq>> apiRequest) {

```
....
58.  public ApiResponse<ServiceRs<IntRateProjectRelateReadRs>>
read(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadRq>>
apiRequest) {
```

Undocumented API\路徑 25:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=578
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's update method (line 66) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-	uatFiles/ncbs-mid-repo-p2/cmn/cmn-

	app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	66	66
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateUpdateRq>> apiRequest) {

```
....
66.  public ApiResponse<ServiceRs<EmptyRs>> update(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateUpdateRq>> apiRequest) {
```

Undocumented API\路徑 26:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=579
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's delete method (line 74) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	74	74
物件	delete	delete

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java

方法 public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateDeleteRq>> apiRequest) {

```
....
74.  public ApiResponse<ServiceRs<EmptyRs>> delete(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateDeleteRq>> apiRequest) {
```

Undocumented API\路徑 27:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=580
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readList method (line 82) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
行	82	82
物件	readList	readList

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/cmn/cmn-app/src/main/java/com/scsb/ncbs/cmn/controller/pric/intrate/intrateprojrel/IntRateProjectRelateController.java
方法	public ApiResponse<ServiceRs<IntRateProjectRelateReadListRs>> readList(@RequestBody ApiRequest<ServiceRq<IntRateProjectRelateReadListRq>> apiRequest) {

```
....
82.  public ApiResponse<ServiceRs<IntRateProjectRelateReadListRs>>
readList(@RequestBody
ApiRequest<ServiceRq<IntRateProjectRelateReadListRq>> apiRequest) {
```

Undocumented API\路徑 28:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=581
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readAccountBalance method (line 52) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
行	52	52
物件	readAccountBalance	readAccountBalance

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
方法	public ApiResponse<ServiceRs<AccountBalanceRs>> readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readAccountBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

Undocumented API\路徑 29:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=582
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readBalance method (line 70) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
行	70	70
物件	readBalance	readBalance

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/account/AccountController.java
方法	public ApiResponse<ServiceRs<AccountBalanceRs>> readBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>> apiRequest) {

```
....
70.  public ApiResponse<ServiceRs<AccountBalanceRs>>
readBalance(@RequestBody ApiRequest<ServiceRq<AccountBalanceRq>>
apiRequest) {
```

Undocumented API\路徑 30:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=583
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's query method (line 59) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java
行	59	59
物件	query	query

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerController.java

方法 public ApiResponse<ServiceRs<Customer3702Rs>> query(@RequestBody ApiRequest<ServiceRq<CustomerRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<Customer3702Rs>> query(@RequestBody
ApiRequest<ServiceRq<CustomerRq>> apiRequest) {
```

Undocumented API\路徑 31:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=584
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryPaging method (line 59) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	59	59
物件	queryPaging	queryPaging

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702PagingRs>> queryPaging(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
59.  public ApiResponse<ServiceRs<Customer3702PagingRs>>
queryPaging(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 32:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=585
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's querySpecialMsg method (line 67) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	67	67
物件	querySpecialMsg	querySpecialMsg

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702SpecialMsgPagingRs>> querySpecialMsg(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
67.  public ApiResponse<ServiceRs<Customer3702SpecialMsgPagingRs>>
querySpecialMsg(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 33:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=586
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryDep method (line 77) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

行	77	77
物件	queryDep	queryDep

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702DepPagingRs>> queryDep(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
77.  public ApiResponse<ServiceRs<Customer3702DepPagingRs>>
queryDep(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 34:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=587
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryLoan method (line 87) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	87	87
物件	queryLoan	queryLoan

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702LoanPagingRs>> queryLoan(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
87.  public ApiResponse<ServiceRs<Customer3702LoanPagingRs>>
queryLoan(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 35:

嚴重程度：	資訊

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=588
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryGuarantor method (line 97) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	97	97
物件	queryGuarantor	queryGuarantor

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702GuarantorPagingRs>> queryGuarantor(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
97.  public ApiResponse<ServiceRs<Customer3702GuarantorPagingRs>>
queryGuarantor(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 36:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=589
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryLimit method (line 107) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	107	107
物件	queryLimit	queryLimit

代碼片斷

檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
方法	public ApiResponse<ServiceRs<Customer3702LimitPagingRs>> queryLimit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
107.  public ApiResponse<ServiceRs<Customer3702LimitPagingRs>>
queryLimit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 37:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=590
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryBill method (line 117) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	117	117
物件	queryBill	queryBill

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
方法	public ApiResponse<ServiceRs<Customer3702BillPagingRs>> queryBill(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
117.  public ApiResponse<ServiceRs<Customer3702BillPagingRs>>
queryBill(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 38:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=591
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryCredit method (line 127) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	127	127
物件	queryCredit	queryCredit

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702CreditPagingRs>> queryCredit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
127.  public ApiResponse<ServiceRs<Customer3702CreditPagingRs>>
queryCredit(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 39:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=592
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryBond method (line 137) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	137	137
物件	queryBond	queryBond

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702BondPagingRs>> queryBond(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
137.  public ApiResponse<ServiceRs<Customer3702BondPagingRs>>
queryBond(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 40:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=593
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryCompany method (line 147) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	147	147
物件	queryCompany	queryCompany

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702CompanyPagingRs>> queryCompany(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
147.  public ApiResponse<ServiceRs<Customer3702CompanyPagingRs>>
queryCompany(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 41:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=594
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's queryObu method (line 157) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-	uatFiles/ncbs-mid-repo-p2/dep/dep-

	app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java	app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java
行	157	157
物件	queryObu	queryObu

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/adi/customer/CustomerPagingController.java

方法 public ApiResponse<ServiceRs<Customer3702ObuPagingRs>> queryObu(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>> apiRequest) {

```
....
157.  public ApiResponse<ServiceRs<Customer3702ObuPagingRs>>
queryObu(@RequestBody ApiRequest<ServiceRq<CustomerPagingRq>>
apiRequest) {
```

Undocumented API\路徑 42:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=595
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's process1554 method (line 52) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	52	52
物件	process1554	process1554

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<CrrRecordsRs>> process1554(@RequestBody ApiRequest<ServiceRq<CrrRecordsRq>> apiRequest) {

```
....
52.  public ApiResponse<ServiceRs<CrrRecordsRs>>
process1554(@RequestBody ApiRequest<ServiceRq<CrrRecordsRq>> apiRequest)
{
```

Undocumented API\路徑 43:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=596
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readCharge method (line 65) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	65	65
物件	readCharge	readCharge

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<List<ChargeStatusInfoRs>>> readCharge(@RequestBody ApiRequest<ServiceRq<CrrReadChargeRq>> apiRequest) {

```
....
65.  public ApiResponse<ServiceRs<List<ChargeStatusInfoRs>>>
readCharge(@RequestBody ApiRequest<ServiceRq<CrrReadChargeRq>>
apiRequest) {
```

Undocumented API\路徑 44:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=597
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readChargeDetail method (line 77) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	77	77
物件	readChargeDetail	readChargeDetail

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法	public ApiResponse<ServiceRs<CrrReadChargeDetailRs>> readChargeDetail(@RequestBody ApiRequest<ServiceRq<CrrReadChargeDetail>> apiRequest) {

```
....
77.  public ApiResponse<ServiceRs<CrrReadChargeDetailRs>>
readChargeDetail(@RequestBody ApiRequest<ServiceRq<CrrReadChargeDetail>>
apiRequest) {
```

Undocumented API\路徑 45:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=598
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's createCharge method (line 89) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	89	89
物件	createCharge	createCharge

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
方法	public ApiResponse<ServiceRs<ChargeStatusInfoRs>> createCharge(@RequestBody ApiRequest<ServiceRq<CrrCreateChargeRq>> apiRequest) {

```
....
89.  public ApiResponse<ServiceRs<ChargeStatusInfoRs>>
createCharge(@RequestBody ApiRequest<ServiceRq<CrrCreateChargeRq>>
apiRequest) {
```

Undocumented API\路徑 46:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=599
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's reverseCharge method (line 101) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-	uatFiles/ncbs-mid-repo-p2/dep/dep-

	app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	101	101
物件	reverseCharge	reverseCharge

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<ChargeStatusInfoRs>> reverseCharge(@RequestBody ApiRequest<ServiceRq<CrrReverseChargeRq>> apiRequest) {

```
....
101.  public ApiResponse<ServiceRs<ChargeStatusInfoRs>>
reverseCharge(@RequestBody ApiRequest<ServiceRq<CrrReverseChargeRq>>
apiRequest) {
```

Undocumented API\路徑 47:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=600
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

The application's readRecordsList method (line 114) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	114	114
物件	readRecordsList	readRecordsList

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<CrrReadRecordsRs>> readRecordsList(@RequestBody ApiRequest<ServiceRq<CrrReadRecordsRq>> apiRequest) {

```
....
114.  public ApiResponse<ServiceRs<CrrReadRecordsRs>>
readRecordsList(@RequestBody ApiRequest<ServiceRq<CrrReadRecordsRq>>
apiRequest) {
```

Undocumented API\路徑 48:

嚴重程度：	資訊
結果狀態：	校驗

線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=601
狀態	新的
Detection Date	10/13/2025 3:56:40 PM

The application's readRecordsListPaging method (line 126) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java
行	126	126
物件	readRecordsListPaging	readRecordsListPaging

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/crr/CrrController.java

方法 public ApiResponse<ServiceRs<CrrReadRecordsRs>> readRecordsListPaging(@RequestBody ApiRequest<ServiceRq<CrrReadRecordsRq>> apiRequest) {

```
....
126.  public ApiResponse<ServiceRs<CrrReadRecordsRs>>
readRecordsListPaging(@RequestBody
ApiRequest<ServiceRq<CrrReadRecordsRq>> apiRequest)  {
```

Undocumented API\路徑 49:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=602
狀態	新的
Detection Date	1/23/2026 6:48:48 PM

The application's process method (line 39) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/dacc/DaccProcessController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/dacc/DaccProcessController.java
行	39	39
物件	process	process

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/dacc/DaccProcessController.java

方法 public ApiResponse<ServiceRs<MarketingPreferencesRs>> process(@RequestBody ApiRequest<ServiceRq<DepDaccProcessRq>> apiRequest) {

```
....
39.  public ApiResponse<ServiceRs<MarketingPreferencesRs>>
process(@RequestBody ApiRequest<ServiceRq<DepDaccProcessRq>> apiRequest)
{
```

Undocumented API\路徑 50:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=603
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

The application's query5931 method (line 35) is an undocumented API endpoint. This is not a best practice and may lead to unintended behavior.

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/debitcard/DebitPaymentController.java	uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/debitcard/DebitPaymentController.java
行	35	35
物件	query5931	query5931

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/dep/dep-app/src/main/java/com/scsb/ncbs/dep/controller/debitcard/DebitPaymentController.java

方法 public ApiResponse<ServiceRs<DebitPaymentQuery5931Rs>> query5931(@RequestBody ApiRequest<ServiceRq<DebitPaymentQuery5931Rq>> apiRequest) {

```
....
35.  public ApiResponse<ServiceRs<DebitPaymentQuery5931Rs>>
query5931(@RequestBody ApiRequest<ServiceRq<DebitPaymentQuery5931Rq>>
apiRequest) {
```

Insufficient Logging of Database Actions

查詢路徑:

Java\Cx\Java Best Coding Practice\Insufficient Logging of Database Actions 版本:1

類別

OWASP ASVS: V07 Error Handling and Logging
OWASP Top 10 2021: A9-Security Logging and Monitoring Failures

描述

Insufficient Logging of Database Actions\路徑 1:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=544
狀態	新的

Detection Date	9/22/2025 6:07:43 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java
行	76	76
物件	saveExpStmtData	saveExpStmtData

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/preapproved/PreApprovedDepLoanBalStep.java

方法 public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
76.  saveExpStmtData(runDate, daysUntilEndOfMonth, map);
```

Insufficient Logging of Database Actions\路徑 2:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=545
狀態	新的
Detection Date	9/22/2025 6:07:43 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/GenReconciliationNoStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/GenReconciliationNoStep.java
行	60	60
物件	saveAndFlush	saveAndFlush

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/GenReconciliationNoStep.java

方法 glaReconciliationDetailEntities.forEach(glaReconciliationDetailEntity -> {

```
....
60.  repository.saveAndFlush(glaReconciliationDetailEntity);
```

Insufficient Logging of Database Actions\路徑 3:

嚴重程度：	資訊

結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=546
狀態	新的
Detection Date	11/17/2025 11:25:17 AM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java
行	61	61
物件	deleteByTransactionDateLessThanAndReconciliatedFlag	deleteByTransactionDateLessThanAndReconciliatedFlag

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java

方法 public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
61.
repository.deleteByTransactionDateLessThanAndReconciliatedFlag(cleanDate
60, "Y");
```

Insufficient Logging of Database Actions\路徑 4:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=547
狀態	新的
Detection Date	9/22/2025 6:07:43 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java
行	47	47
物件	deleteByTransactionDate	deleteByTransactionDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/reconciliation/ReconciliationBeforeStep.java

方法 public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
47.  repository.deleteByTransactionDate(runDate);
```

Insufficient Logging of Database Actions\路徑 5:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=548
狀態	新的
Detection Date	11/17/2025 11:25:17 AM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
行	75	75
物件	deleteByTransactionDateLessThan	deleteByTransactionDateLessThan

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java

方法 public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
75.  glaAccfgtxRepository.deleteByTransactionDateLessThan(cleanDate60);
```

Insufficient Logging of Database Actions\路徑 6:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=549
狀態	新的
Detection Date	11/17/2025 11:25:17 AM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
行	74	74
物件	deleteByTransactionDateLessThan	deleteByTransactionDateLessThan

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
方法	public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
74.
glaSubsidiaryLedgerRepository.deleteByTransactionDateLessThan(cleanDate6
0);
```

Insufficient Logging of Database Actions\路徑 7:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=550
狀態	新的
Detection Date	11/17/2025 11:25:17 AM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
行	57	57
物件	deleteByTransactionDate	deleteByTransactionDate

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
方法	public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
57.  glaAccfgtxRepository.deleteByTransactionDate(runDate);
```

Insufficient Logging of Database Actions\路徑 8:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=551
狀態	新的
Detection Date	11/17/2025 11:25:17 AM

來源	目的地

檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java
行	56	56
物件	deleteByTransactionDate	deleteByTransactionDate

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/subsidiaryledger/SubsidiaryLedgerBeforeStep.java

方法 public RepeatStatus execute(StepContribution stepContribution, ChunkContext chunkContext) throws Exception {

```
....
56.  glaSubsidiaryLedgerRepository.deleteByTransactionDate(runDate);
```

Insufficient Logging of Database Actions\路徑 9:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=552
狀態	新的
Detection Date	9/22/2025 6:07:43 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/account/AccountBeforeStep.java	uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/account/AccountBeforeStep.java
行	35	35
物件	createNativeQuery	createNativeQuery

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/gla/gla-bat/src/main/java/com/scsb/ncbs/gla/batch/job/account/AccountBeforeStep.java

方法 public RepeatStatus execute(StepContribution stepContribution,

```
....
35.  entityManager.createNativeQuery(truncateSql).executeUpdate();
```

Insufficient Logging of Database Actions\路徑 10:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=553
狀態	新的

Detection Date	9/22/2025 6:07:43 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java	uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java
行	113	113
物件	update	update

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/cmn/cmn-bat/src/main/java/com/scsb/ncbs/cmn/batch/job/ecif/specmsg/SpecMsgAmlTasklet.java

方法 private int deleteAmlCase() {

```
....
113.  return jdbcTemplate.update(sql);
```

Portability Flaw In File Separator

查詢路徑:

Java\Cx\Java Best Coding Practice\Portability Flaw In File Separator 版本:9

描述

Portability Flaw In File Separator\路徑 1:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=854
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java
行	81	81
物件	""./rpt/collateral/RCILX006.pdf""	File

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java

方法 void print() throws Throwable {

```
....
81.  MidFileUtils.writeByteArrayToFile(new
File("./rpt/collateral/RCILX006.pdf"), bytes);
```

Portability Flaw In File Separator\路徑 2:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=855
狀態	新的
Detection Date	9/22/2025 6:07:47 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java
行	97	97
物件	""./rpt/collateral/RCIBD101.pdf""	File

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java
方法	void print3625() throws Throwable {

```
....
97.  MidFileUtils.writeByteArrayToFile(new
File("./rpt/collateral/RCIBD101.pdf"), bytes);
```

Portability Flaw In File Separator\路徑 3:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=856
狀態	新的
Detection Date	10/13/2025 3:56:40 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java
行	113	113
物件	""./rpt/collateral/RCILX005.pdf""	File

代碼片斷	
檔案名稱	uatFiles/ncbs-mid-repo-p2/len/len-service/src/test/java/com/scsb/ncbs/len/service/rpt/ReportServiceIT.java
方法	void print3513() throws Throwable {

```
....
113.  MidFileUtils.writeByteArrayToFile(new
File("./rpt/collateral/RCILX005.pdf"), bytes);
```

Portability Flaw In File Separator\路徑 4:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=857
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java
行	51	54
物件	""swift/MT103.png""	readAllBytes

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java

方法 void Test_Baw_Api_Inbound() {

```
....
51.  ClassPathResource imgFile = new
ClassPathResource("swift/MT103.png");
....
54.  bytes = Files.readAllBytes(imgFile.getFile().toPath());
```

Portability Flaw In File Separator\路徑 5:

嚴重程度：	資訊
結果狀態：	校驗
線上結果	http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=858
狀態	新的
Detection Date	12/19/2025 4:53:49 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/service/bedt/SwiftServiceTest.java	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/service/bedt/SwiftServiceTest.java
行	55	58
物件	""swift/MT103.png""	readAllBytes

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/service/bedt/SwiftServiceTest.java
方法 void Test_Baw_Api_Inbound() {

```
....
55.  ClassPathResource imgFile = new
ClassPathResource("swift/MT103.png");
....
58.  bytes = Files.readAllBytes(imgFile.getFile().toPath());
```

Portability Flaw In File Separator\路徑 6:

嚴重程度： 資訊
結果狀態： 校驗
線上結果 http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=859
狀態 新的
Detection Date 12/19/2025 4:53:49 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java	uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java
行	92	95
物件	""swift/MT103.png""	readAllBytes

代碼片斷
檔案名稱 uatFiles/ncbs-mid-repo-p2/rem/rem-service/src/test/java/com/scsb/ncbs/rem/service/bedt/SwiftServiceTest.java
方法 void Test_Baw_Api_Outbound() {

```
....
92.  ClassPathResource imgFile = new
ClassPathResource("swift/MT103.png");
....
95.  bytes = Files.readAllBytes(imgFile.getFile().toPath());
```

Portability Flaw In File Separator\路徑 7:

嚴重程度： 資訊
結果狀態： 校驗
線上結果 http://10.10.2.164/CxWebClient/ViewerMain.aspx?scanid=98802&projectid=31979&pathid=860
狀態 新的
Detection Date 12/19/2025 4:53:49 PM

	來源	目的地
檔案	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/servic	uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/servic

	e/bedt/SwiftServiceTest.java	e/bedt/SwiftServiceTest.java
行	96	99
物件	""swift/MT103.png""	readAllBytes

代碼片斷

檔案名稱 uatFiles/ncbs-mid-repo-p2/sgw/sgw-service/src/test/java/com/scsb/ncbs/sgw/service/bedt/SwiftServiceTest.java

方法 void Test_Baw_Api_Outbound() {

```
....
96.  ClassPathResource imgFile = new
ClassPathResource("swift/MT103.png");
....
99.  bytes = Files.readAllBytes(imgFile.getFile().toPath());
```

CGI Stored XSS

風險

可能發生什麼問題

成功的跨站腳本 (XSS) 攻擊可讓攻擊者重寫網頁並插入惡意腳本，從而改變原本的輸出。這包括 HTML 片段、CSS 樣式規則、任意 JavaScript 或第三方程式碼的引用。攻擊者可以利用此漏洞來竊取使用者的密碼，收集個人資料，例如信用卡詳細訊息，提供虛假訊息或運行惡意軟件。從受害者的角度來看，這是由正確的網站執行，並且受害者會責怪網站造成的損害。

攻擊者可以利用合法的應用程式存取權限，該資料將由應用程式儲存至某地中。這些存儲的資料將用於動態生成通用的輸出 - 在某些情況下，例如使用 CGI 腳本，這些輸出將直接發送到使用者的瀏覽器，從而觸發攻擊。

原因

如何發生

該應用程式建立的網頁包含不受信任的資料，無論是從使用者輸入、應用程式資料庫或其他外部來源。這些不受信任的資料直接嵌入頁面的 HTML 中，導致瀏覽器將其顯示為網頁的一部分。如果輸入包含 HTML 片段或 JavaScript，這些也會被顯示，而使用者無法判斷這不是預期的網頁。此漏洞是由於直接嵌入任意資料，而未先將其編碼為防止瀏覽器將其視為 HTML 或程式碼而非純文本的格式所導致。

為了利用這個漏洞，攻擊者會通常透過其他網頁上的常規表單，載入惡意的負載到資料庫。然後，應用程式會從資料庫中讀取這些資料，並將其嵌入顯示給另一個使用者的網頁中。

一般建議

如何避免

- 在輸出前，必須將所有動態資料完全編碼，不論來源為何。
- 編碼應該是對上下文敏感的。例如：
  - 對於HTML內容使用HTML編碼
  - 對於輸出到屬性值的資料使用HTML屬性編碼
  - 對於伺服器生成的JavaScript使用JavaScript編碼
- 建議使用平台提供的編碼功能，或已知的安全庫來編碼輸出。
- 實施Content Security Policy（CSP），僅為應用程序的資源明確白名單。
- 作為額外的保護層，無論來源如何，驗證所有不受信任的資料（注意，這不是編碼的替代）。驗證應基於白名單：僅接受符合指定結構的資料，而不是拒絕不良模式。檢查：
  - 資料類型
  - 大小
  - 範圍

  - 格式
  - 預期值
- 在Content-Type HTTP回應標頭中，明確定義整個頁面的字符編碼（字符集）。
- 為"深度防禦"，在會話cookie上設置HTTPOnly標誌，以防止任何成功的XSS攻擊竊取cookie。

程式碼範例

Java

CGI Script Vulnerable to Stored XSS

```
ResultSet rs = getUserProfileFromDB();
String name = rs.getString("name");
System.out.println("Content-Type: text/html\n\n");
System.out.println("<h1>Hello " + name + "!</h1>");
```

Using Regex to Remove All Special Characters, Except Spaces, From Database Results to Mitigate Potential XSS

```
ResultSet rs = getUserProfileFromDB();
String name = rs.getString("name");
System.out.println("Content-Type: text/html\n\n");
name = name.replaceAll("[^\\w\\s]", "");
System.out.println("<h1>Hello " + name + "!</h1>");
```

Excessive Data Exposure

風險

可能發生什麼問題

API 通常在回應時向客戶端提供物件，供其使用。有時，這些物件可能包含的訊息超過客戶端需要或打算使用的訊息。如果返回給客戶端的物件有這些多餘數據並且該數據是敏感資訊，它就會暴露給 API 的潛在惡意客戶端。

原因

如何發生

API 返回一個具有潛在敏感資訊字段的物件，而沒有排除、過濾或取消所述敏感資訊 - 就會在 API 回應中將其暴露。

一般建議

如何避免

- 從 API 返回保存數據的物件時，請始終考慮返回數據的類型和上下文 - 例如 API 的使用者是否需要它，以及它是否敏感
- 選擇將允許的數據列入白名單從而控制數據流並去除多餘數據

程式碼範例

Java

Exposing a Sensitive Field in a Spring REST API Response

```
// POJO with Sensitive Data
@Entity
public class User {
    @Id
    @GeneratedValue
    private Long id;
    private String username;
    // Field will be exposed if User object is returned as-is from API:
    private String encryptedPassword;
    // ... public constructors getters and setters ... //
}

// Spring REST Controller Mapped Method
@GetMapping("/users/{id}")
User findOne(@PathVariable Long id) {
    User user = repository.findById(id).orElseThrow(() -> new UserNotFoundException(id));
    return user;
}
```

Using a DTO and ModelMapper To Whitelist Desired Output Fields in a Spring REST API

```
// POJO with Sensitive Data
@Entity
public class User {
    @Id
    @GeneratedValue
    private Long id;
```

```
    private String username;
    private String encryptedPassword;
    // ... public constructors getters and setters ... //
}

// DTO without Sensitive Data
public class UserDTO {
    private Long id;
    private String username;
    // ... public constructors getters and setters ... //
}

// Spring REST Controller Mapped Method
@GetMapping("/users/{id}")
User findOne(@PathVariable Long id) {
    User user = repository.findById(id).orElseThrow(() -> new UserNotFoundException(id));
    UserDTO userDTO = modelMapper.map(user, UserDTO.class);
    return userDTO;
}
```

Spring Annotation Used to Exclude A Field from JSON Entirely - Can Also Be Set on Getter Individually to Allow Setting a Value While Preventing Exposure

```
// POJO with Sensitive Data
@Entity
public class User {
    @Id
    @GeneratedValue
    private Long id;
    private String username;
    @JsonIgnore
    private String encryptedPassword;
    // ... public constructors getters and setters ... //
}
```

ReDoS From Regex Injection

風險

可能發生什麼問題

ReDoS（正規表示式拒絕服務）可以使用複雜的表示式導致拒絕服務（DoS）。對於某些表示式，處理時間可能根據輸入大小呈指數增長。攻擊者可以使用這些正規表示式使應用程式在資料集上處理正規表示式時花費大量計算時間，導致應用程式停滯。

原因

如何發生

ReDoS（正規表示式拒絕服務）是一種演算法複雜性攻擊，利用了最壞情況下的時間複雜度。具體而言，某些正規表示式型樣 - 無論是在應用程式中直接撰寫的，或是從使用者輸入中接受並用於搜尋文字 - 可能導致對某些輸入文字產生極高的處理負載。例如，`(a+)+` 將在輸入一長串 "aaaaaaaaaaaaaaaaaaaaaaaa!" 時停滯。

一般建議

如何避免

- 不要使用輸入來建構正規表示式。
- 確保所有 Hardcoded 正規表示式不容易受到ReDoS攻擊，特別是確保最壞情況的時間複雜度不會導致應用程式停滯。
- 避免不必要的複雜表示式；建構盡可能簡單的正規表示式。

程式碼範例

Java

Using User Input String As A Regex Pattern

```
/* In this sample, a question that is a string of "a" followed by any other
 * character would take very long for the regex .*(?=^(a|aa)+$).*
 */

// Ensure security answer is not in the body of the question
public static Boolean isAnswerInQuestion(String securityQuestion, String securityAnswer) {
    return securityQuestion.toLowerCase().matches(".*"+securityAnswer.toLowerCase()+".*");
}
```

Using Alternatives to User-Controlled Regex

```
// Ensure security answer is not in the body of the question
public static Boolean isAnswerInQuestion(String securityQuestion, String securityAnswer) {
      return securityQuestion.toLowerCase().contains(securityAnswer.toLowerCase());
}
```

Privacy Violation

風險

可能發生什麼問題

惡意的程式人員或攔截資料的攻擊者都可能會竊取使用者的個人資訊。

原因

如何發生

應用程式將使用者資訊（例如密碼、帳號資訊或信用卡號）發送到應用程式外部，例如將其寫入本地文字檔或日誌檔或將其發送到外部網路服務。

一般建議

如何避免

1. 在寫入日誌或其他檔案之前應刪除個人資料。
2. 審查每個將個資發送到遠端網路服務的必要性和理由。

程式碼範例

Java

Leaking a Password Back to the User Constitutes a Privacy Violation

```
public void doPost (HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
      PrintWriter out = response.getWriter();
      HttpSession session = request.getSession();
      boolean isAuthenticated = session.getAttribute("isAuthenticated");
      if (isAuthenticated) {
            byte[] password = request.getParameter("password").getBytes();
            updatePassword(session, password);
      out.println("New password is " + (new String(password));
      } else {
            out.println("Authentication Failed");
      }
}
```

Unchecked Input for Loop Condition

風險

可能發生什麼問題

攻擊者可能會輸入非常高的值，從而可能導致阻斷式服務攻擊 (DoS)。

原因

如何發生

應用程式在執行一些重複的任務時，根據使用者的輸入來定義循環次數。一個非常高的值可能會導致應用程式陷入循環，將無法繼續進行其他操作。

一般建議

如何避免

理想情況下，不使用使用者提供的循環設定。如果有必要的話，使用者輸入必須先驗證且應限制其範圍。

程式碼範例

Java

Loop Condition Is Not Bounded By Any Value

```
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    int loopCount = 0;
    try{
        loopCount = Integer.parseInt(request.getParameter("loopCount"));
    } catch(NumberFormatException e){
        return DEFAULT_VAL;
    }
    for(int i=0; i < loopCount; i++){
        //Do Something
    }
}
```

Loop Condition is Bounded With MAX_LOOPS

```
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    int loopCount = 0;
    try{
        loopCount = Integer.parseInt(request.getParameter("loopCount"));
    } catch(NumberFormatException e){
        return DEFAULT_VAL;
    }
    if(loopCount > MAX_LOOPS){
        loopCount = MAX_LOOPS;
    }
    for(int i=0; i < loopCount; i++){
        //Do Something
```

```
        }
    }
```

Improper Exception Handling

風險

可能發生什麼問題

●攻擊者可能會導致應用程式異常的崩潰，且造成拒絕服務(DoS)攻擊。 ●應用程式可能發生偶發性的崩潰。

原因

如何發生

'應用程式執行如資料庫或文件存取，這可能會引發一些異常狀況。若應用程式未妥善處理異常狀況，可能會當機。

一般建議

如何避免

可能導致異常的任何方法應包裝在一個try-catch區塊: ● 明確地處理預期的異常 ●包含一個預設的解決方案，以處理突發異常

程式碼範例

Java

Loading a Library without Catching

```
public static void loadLib() {
      System.loadLibrary(LIB_NAME); // If LIB_NAME does not exist, an unhandled exception will be thrown
}
```

Handle All Possible Exceptions within the Error-Prone Method

```
public static void loadLib() {
      try {
            System.loadLibrary(LIB_NAME);
    } catch (SecurityException se) {
                  // Handle SecurityException
      } catch (UnsatisfiedLinkError sle) {
                  // Handle UnsatisfiedLinkError
      } catch (NullPointerException npe) {
                  // Handle NullPointerException
      }
}
```

Aggregate Potential Exceptions to Calling Code

```
public static void loadLib() throws UnsatisfiedLinkError, NullPointerException, SecurityException {
      System.loadLibrary(LIB_NAME);
}
```

Heap Inspection

風險

可能發生什麼問題

應用程式在未加密的memory中存儲的所有變數都可能被主機特權User(privileged access)未經授權的檢索。例如，特權攻擊者可以對正在執行的process掛上debugger，也可能從swapfile或crash dump file中檢索process's memory。
一旦攻擊者在Memory中找到User的密碼，就可以輕鬆的假冒User進入系統。

原因

如何發生

字串變數是不變的(immutable) - 換句話說，一旦分配了字串變數，就無法更改或刪除其值。因此，這些字串可能會無限期的留存在memory中，而且可能分散在多個位置中，直到垃圾收集器(garbage collector)將其刪除。敏感資訊，例如密碼，將作為明文在memory中暴露，無法控制其生命週期。

一般建議

如何避免

- 不要將敏感資訊(如password或encryption key)以明文形式存儲在memory中，時間再短都不要。
- 建議使用專為store encrypted memory設計的Class。
- 或者，將機敏資訊存在可變類型中(如byte array)，使用完立即將array中每個byte位歸零。

- 在Java中，不要將密碼儲存在不可變的string中 - 建議使用encrypted memory object，例如SealedObject。

程式碼範例

Java

Plaintext Password in Immutable String

```
class Heap_Inspection
{
  private String password;
  public void setPassword(String password)
 {
      this.password = password;
  }
}
```

Password Protected in Memory

```
class Heap_Inspection_Fixed
{
```

```
  private SealedObject password;

  public void setPassword(Character[] input)

 {

     Key key = getKeyFromConfiguration();
            Cipher c = Cipher.getInstance(CIPHER_NAME);
            c.init(Cipher.ENCRYPT_MODE, key);
            List<Character> characterList = Arrays.asList(input);
            password = new SealedObject((Serializable) characterList, c);
            Arrays.fill(input, '\0'); // Zero out input. Will also overwrite the values in
characterList by reference.
  }
}
```

Information Exposure Through an Error Message

風險

可能發生什麼問題

透露關於程式的環境、使用者或相關資訊 (例如：stack trace) 將會讓攻擊者找到其他的缺失也幫助攻擊者來發起攻擊。這也可能會使機密資料洩露，例如：密碼或資料庫欄位。

原因

如何發生

應用程式以不安全的方式處理例外(exception)，包括直接在 error message 中顯示完整的原始詳細訊息。這在幾個狀況下都可能會發生：不處理 exception；直接將 exception 輸出到頁面或檔案中；顯式return exception 物件；設定檔設定不嚴謹。這些 exception 細節可能包含機密資訊，並隨著 Runtime Error 而流出。

一般建議

如何避免

- 不將 excecption 資訊直接輸出或是透露給使用者，建議回傳一個制式化的錯誤訊息。Exception細節則應記錄於Log機制內。
- 任何會拋出 exception 的函式都應該要被包在處理 exception 的區塊內，而處理的方式有:
  - 明確的處理預期內的exception。
  - 包含了一個預設的解決方式來處理無預期的exceptions。
- 設定一個全域處理器來避免無處理的錯誤被送至使用者端。

程式碼範例

Java

Handle Exception by Printing To Output

```
private void wrapCallToDB_Unsafe(HttpServletRequest request)
            throws ServletException, IOException {
      String paramValue = request.getParameter("Param");

      try {
            callDbProc(paramValue);
      } catch (SQLException ex) {
            ex.printStackTrace();
      }
}
```

Write Exception Details to Log, Send Generic Error Message

```
private void wrapCallToDB_SafePrintToLog(HttpServletRequest request)
            throws ServletException, IOException {
      String paramValue = request.getParameter("Param");

      try {
```

```
            callDbProc(paramValue);
        } catch (SQLException ex) {
            writeExceptionToLog(ex);
            System.err.println("Database Error, see log for details");
        }
    }
```

Incorrect Permission Assignment For Critical Resources

風險

可能發生什麼問題

具有危險權限的檔案可能允許攻擊者從這些檔案的內容中擷取敏感資訊、篡改其內容或潛在地執行它們。

原因

如何發生

檔案或目錄被創建時具有危險的權限，可能是有設置這些權限，不然就是依賴於不安全的默認權限。

一般建議

如何避免

- 請始終明確設定檔案的權限
- 請勿將危險權限設定在檔案上
  - 當決定使用者可以讀取、寫入或執行哪些檔案時，請始終考慮最小權限原則，並且只在必要時授予這些權限

程式碼範例

Java

Writing A File with Implicit Permissions

```
File tempFile = File.createTempFile(TEMP_FILE_PREFIX,TEMP_FILE_SUFFIX, new
File(TEMP_FOLDER));
FileWriter fw = new FileWriter(tempFile);
fw.write(CONTENT);
```

Writing A File with Explicit Permissions

```
File tempFile = File.createTempFile(TEMP_FILE_PREFIX,TEMP_FILE_SUFFIX, new
File(TEMP_FOLDER));
FileWriter fw = new FileWriter(tempFile);
tempFile.setExecutable(false);
tempFile.setReadable(true);
tempFile.setWritable(true);
fw.write(CONTENT);
```

Log Forging

風險

可能發生什麼問題

攻擊者可以偽造安全敏感動作的稽核記錄，並留下虛假的稽核軌跡，可能會牽連無辜的使用者或隱藏事件。

原因

如何發生

當應用程式執行安全與敏感性的動作時，會記錄稽核日誌(audit log)。由於稽核日誌中包含使用者輸入的內容，這些內容既沒有經過驗證資料類型，也沒有經過適當的處理，因此該輸入可能包含假資訊，假裝成合法的稽核日誌資料。

一般建議

如何避免

1. 不管來源為何所有輸入都要進行驗證，且驗證要根據白名單：只接受符合指定格式的資料，而不是使用黑名單。請檢查：
    - 資料型態(Data type)
    - 資料大小(Size)
    - 資料範圍(Range)
    - 資料格式(Format)
2. 驗證不能取代 encode。不論來源為何要將所有的外部資料進行 encode 後才能寫進 Log。
3. 使用安全的 Logging 機制。

程式碼範例

Java

User Input Affects Logging

```
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    String color = request.getParameter("color");
    logger.info("{} was picked", color);
      if colorList.contains(color){
      // Handle Response
    }else{
      // Handle Response
    }
}
```

User Input Encoded Prior Logging

```
protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {

    String color = request.getParameter("color");
      cleanColor = color.replace('\t', '_').replace('\n', '_').replace('\r', '_');
    logger.info("{} was picked", cleanColor);
```

```
      if colorList.contains(cleanColor){
      // Handle Response
    }else{
      // Handle Response
    }
}
```

Integer Overflow

風險

可能發生什麼問題

算術溢出將導致未定義的行為和意外影響，例如資料損壞（例如值環繞，其中最大值變為最小值）；系統崩潰；無限迴圈；邏輯錯誤，例如繞過安全機制；資料截斷或遺失；當使用溢出的數值執行記憶體操作時，甚至緩衝區溢位導致任意程式碼執行。

原因

如何發生

所有數字資料類型都有按位元表示。 如果在算數運算之後，一個值超過了它的位元表示的位數，那麼被添加的最高有效數字將被簡單地截斷，截斷後保留的值是環繞操作的剩餘部分 - 這被稱為"算術溢出"或其常見的誤稱 - "整數溢出"，這是誤導性的，因為這適用於許多其他類型。 如果可以溢出的資料類型低於它們的最小值，它們將在通常稱為下溢的情況下反向回繞。

例如，如果一個無符號的 32 位元整數設置為 4,294,967,295 並且 1 是 如果它是一個帶符號的 32 位元整數，值為 2,147,483,647 並且添加 1，它將溢出並返回到 0。

為了確保程式碼正確性，檢查必須使值在預期範圍內，以便算數運算的結果不會溢出或下溢。

一般建議

如何避免

- 在對可能包含任何值的資料執行算數運算時，考慮添加檢查以確保此資料在這些運算的乘積不會導致上溢或下溢的範圍內。
- 考慮為所有算數運算創建包裝器，以便對異常情況進行特定處理；例如，如果檢查顯示已經或將要發生溢出，則拋出異常。

程式碼範例

Java

Addition Vulnerable to Overflow and Underflow

```
public static int vuln_addition1(int a, int b)
{
  return a + b;
}
```

Incorrect Check - Vulnerable to Underflow, and Incorrect Negative Value Handling

```
public static int vuln_addition2(int a, int b)
{
  if(a+b < 0)
   throw new RuntimeException ("Integer overflow!");
  return a + b;
}
```

Addition That will Throw Exception in Case of Overflow or Underflow

```
public static int safe_addition1(int a, int b)
{
   if (a > 0 && b > 0 && a + b < 0)
     throw new RuntimeException ("Integer overflow!");

   if (a < 0 && b < 0 && a + b > 0)
     throw new RuntimeException ("Integer underflow!");

   return a+b;
}
```

Using a bigger data type to hold all the possible result values

```
public static short safe_addition2(short a, short b)
{
  int tot = a+b;
  if(tot > Short.MAX_VALUE)
   return Short.MAX_VALUE;

  if(tot < Short.MIN_VALUE)
   return Short.MIN_VALUE;

  return (short)tot;
}
```

Integer Underflow

風險

可能發生什麼問題

算術溢出將導致未定義的行為和意外影響，例如資料損壞（例如值環繞，其中最大值變為最小值）；系統崩潰；無限迴圈；邏輯錯誤，例如繞過安全機制；資料截斷或遺失；當使用溢出的數值執行記憶體操作時，甚至緩衝區溢位導致任意程式碼執行。

原因

如何發生

所有數字資料類型都有按位元表示。 如果在算數運算之後，一個值超過了它的位元表示的位數，那麼被添加的最高有效數字將被簡單地截斷，截斷後保留的值是環繞操作的剩餘部分 - 這被稱為“算術溢出”或其常見的誤稱 - “整數溢出”，這是誤導性的，因為這適用於許多其他類型。 如果可以溢出的資料類型低於它們的最小值，它們將在通常稱為下溢的情況下反向回繞。

例如，如果一個無符號的 32 位元整數設置為 4,294,967,295 並且 1 是 如果它是一個帶符號的 32 位元整數，值為 2,147,483,647 並且添加 1，它將溢出並返回到 0。

為了確保程式碼正確性，檢查必須使值在預期範圍內，以便算數運算的結果不會溢出或下溢。

一般建議

如何避免

- 在對可能包含任何值的資料執行算數運算時，考慮添加檢查以確保此資料在這些運算的乘積不會導致上溢或下溢的範圍內。
- 考慮為所有算數運算創建包裝器，以便對異常情況進行特定處理；例如，如果檢查顯示已經或將要發生溢出，則拋出異常。

程式碼範例

Off by One Error

風險

可能發生什麼問題

Off-by-one errors 常常導致意外的行為，取決於實作方式。Off-by-One errors 的最常見風險是未處理的例外情況。

原因

如何發生

用於訪問資料集的迭代器使用了不正確的算術比較器，導致迭代次數計算錯誤並出現off-by-one error。

一般建議

如何避免

當使用運算式做為判斷停止的條件時，必須考慮到資料集的大小，因為資料集的第一個元素會佔據一個位置。因此，資料集的最後一個儲存位置通常會比實際的資料集大小減1。

程式碼範例

Java

Off-by-One Error in Array, If TERMINATION_MEMBER Is Not in Array

```
for (int i = 0; i <= arr.length; i++) { // arr[arr.length] is never set, and will always result in an exception
      if (arr[i].equals(TERMINATION_MEMBER) { // Assumes some member of "arr" is intentionally set to terminate the iteration
            break; // This will avoid an exception, but only if arr contains the expected termination member
    }
      doSomething(arr[i]); // If TERMINATION_MEMBER is not in array "arr", an exception will occur trying to dereference arr[arr.length]
}
```

Array Properly Functions, Even if TERMINATION_MEMBER is Not Set in "arr"

```
for (int i = 0; i < arr.length; i++) {
      if (arr[i].equals(TERMINATION_MEMBER) { // Assumes some member of "arr" is intentionally set to terminate the iteration
            break;
    }
      doSomething(arr[i]); // Will work for every i in arr
}
```

Portability Flaw Locale Dependent Comparison

風險

可能發生什麼問題

對字串型態的變數進行處理時沒有指定語系，會導致非預期的結果。造成驗證繞過攻擊、格式化字串攻擊。以及其他可能的，以字串為攻擊基礎的漏洞：XSS、SQL Injection、DoS

原因

如何發生

不同語系的符號、字元、日期或數字，其排列方式、寫法不盡相同。但有許多的方法在使用時，不會強制開發者設定語系，而使用預設的語系設定。
然而，依賴預設設定，可能會導致非預期的結果。例如大小寫轉換：

```
public String tagProcessor(String tag){
      if (tag.toUpperCase().equals("SCRIPT")){
            return null;
      }
      //...
}
```

若語系為Turkish(土耳其語)，則小寫英文字母`'i'`將會被轉換為"上方帶點的大寫拉丁字母 `İ`"(Unicode編號 `0130`)，顯然與預期的結果`'I'`不同，因而發生預期外的結果。

一般建議

如何避免

- 永遠使用locale-sensitive功能來處理特定字串。
- 在Java中，推薦使用`Locale.ROOT`進行語系設定。

程式碼範例

Java

Locale Ignorant String Comparison

```
private bool validateInput(String input) {
    if (input.toUpperCase().indexOf("SCRIPT") < 0)
        return true;    // Input string does not contain any form of SCRIPT
    else
        return false;
}
```

Locale-Neutral String Comparison

```
private bool validateInput(String input) {
    if (input.toUpperCase(Locale.ROOT).indexOf("SCRIPT") < 0)
        return true;    // Input string does not contain any form of SCRIPT
    else
        return false;
}
```

Reversible One Way Hash

風險

可能發生什麼問題

應用程式依賴密碼學來保護秘密和其他敏感或個人身份資料。當加密中存在弱點時，它可能會危及應用程式資料的完整性、真實性或機密性。

哈希函數(Hashing functions)在密碼學中有多種用途，但主要與密鑰函數和簽名相關聯。當以不安全的方式使用哈希函數(Hashing functions)時，密碼hash或簽名的完整性和機密性可能會受到威脅。

當應用程式依賴弱或被破解的哈希函數(Hashing functions)來執行加密操作以提供完整性或身份驗證功能時，攻擊者可以利用針對它們的已知攻擊來破壞簽名或密碼hash。這可能會導致資料的機密性、完整性和真實性喪失。

原因

如何發生

應用程式的加密相關功能存在問題。

應用程式正在使用弱散列原語。 MD4、MD5、SHA-1 等已被發現存在衝突和其他弱點，因此不適合當前部署。

一般建議

如何避免

將哈希函數(Hashing functions)更新為更安全的替代方法，例如：

- BLAKE2B（軟體速度快、可安全抵禦長度擴展攻擊）
- SHA-2 Family hashes（SHA-256、SHA-384、SHA-512）
- SHA-3 Family hashesSHA3-224、SHA3-256、SHA3-384、SHA3-512）

程式碼範例

Java

Hashing Data With a Reversible Hash - MD5

```
import java.security.MessageDigest;

public static byte[] hashBytes(byte[] data) {
    try {
        MessageDigest md = MessageDigest.getInstance("MD5");
        byte[] hash = md.digest(data);
        return hash;
    } catch (NoSuchAlgorithmException nsae) {
        // Handle exception
    }
}
```

Hashing Data With a Non-Reversible Hash - SHA256

```
import java.security.MessageDigest;

public static byte[] hashBytes(byte[] data) {
    try {
        MessageDigest md = MessageDigest.getInstance("SHA256");
```

```
        byte[] hash = md.digest(data);
        return hash;
    } catch (NoSuchAlgorithmException nsae) {
        // Handle exception
    }
}
```

Serializable Class Containing Sensitive Data

風險

可能發生什麼問題

敏感資訊可能透過可序列化物件洩漏。

原因

如何發生

序列化是將記憶體中的物件轉換為序列化形式的過程，例如位元串、XML、JSON等。它通常用於傳輸或儲存資料，這可能會在某些時候暴露其內容。不建議將任何敏感資訊保存在序列化物件中，因為根據其定義，它們能以可復原且可讀的格式儲存或傳輸這些資料。

一般建議

如何避免

- 不要將敏感資訊存放在序列化物件中。
- 如果絕對需要儲存或傳輸包含敏感資訊的序列化物件，請確保不會危及內容的方式進行。在處理包含敏感資訊的序列化物件時，請始終考慮資料靜態與資料傳輸的原則。

程式碼範例

Java

"Purchase" Class Contains Credit Card Information, and Implements Serializable, Implying Credit Card will be Transmitted or Stored

```
public class Purchase implements Serializable {
      private String creditCard;
    private Date expDate;
      private int CCV;
      // .. //
}
```

Stored Log Forging

風險

可能發生什麼問題

攻擊者可以偽造安全敏感動作的稽核記錄，並留下虛假的稽核軌跡，可能會牽連無辜的使用者或隱藏事件。

原因

如何發生

當應用程式執行安全與敏感性的動作時，會記錄稽核日誌(audit log)。由於稽核日誌中包含使用者輸入的內容，這些內容既沒有經過驗證資料類型，也沒有經過適當的處理，因此該輸入可能包含假資訊，假裝成合法的稽核日誌資料。

一般建議

如何避免

1. 不管來源為何所有輸入都要進行驗證，且驗證要根據白名單：只接受符合指定格式的資料，而不是使用黑名單。請檢查：
    - 資料型態(Data type)
    - 資料大小(Size)
    - 資料範圍(Range)
    - 資料格式(Format)
2. 驗證不能取代 encode。不論來源為何要將所有的外部資料進行 encode 後才能寫進 Log。
3. 使用安全的 Logging 機制。

程式碼範例

Java

Logging Untrusted Data

```
private int readUserId(ResultSet rs) {
    String dbValue = rs.getString("UserId");
    int userId = 0;

    try {
        userId = Integer.parseInt(dbValue);
    } catch (NumberFormatException nfe) {
        log.error("User Id: " + userId + " raised an error: " + nfe.getMessage());
    }
    return userId;
}
```

Logging Only Sanitized Data

```
private int readUserId(ResultSet rs) {
    String dbValue = rs.getString("UserId");
    int userId = 0;

    try {
        userId = Integer.parseInt(dbValue);
```

```
    } catch (NumberFormatException nfe) {
        log.error("User Id: " + userId.replace('\r', '').replace('\n', '') +
                    " raised an error: " + nfe.getMessage());
    }
    return userId;
}
```

Use of Non Cryptographic Random

風險

可能發生什麼問題

根據這個隨機值的使用方式，攻擊者若了解如何使用偽隨機數生成器（PRNG），將能夠預測下一個生成的值，或者基於常用的某種隨機性來源，預測之前生成的值。儘管這些值可能看似隨機，但大型統計樣本將顯示它們的隨機性不足，產生的"隨機"值空間比真正的隨機樣本小得多。在加密的前後文中，這可能使攻擊者能夠推論或猜測該值，從而破解加密機制或輸出值。

原因

如何發生

該應用程式使用一種弱方法來生成偽隨機值，導致其他數字可以從相對較小的樣本中被確定。由於所使用的偽隨機數生成器旨在實現統計上均勻分佈的值，因此它在某種程度上是可預測的。因此，在收集到幾個生成的值之後，攻擊者可以計算過去或未來的值。這些值隨後被用作密碼學函數的參數。如果攻擊者能夠獲取從弱偽隨機數生成器中產生的原始值，他們可能做到預測或破解由密碼學函數產生的值。

一般建議

如何避免

- 在處理安全相關的情境，特別是在使用密碼學函數時，應始終使用具有加密安全性的偽隨機數生成器，而不是基本的隨機方法。
- 使用內建於您的語言或平台的加密隨機數生成器，並確保它以安全的方式進行種子初始化。不要使用弱、非隨機的種子來初始化生成器（大多數情況下，默認值是安全隨機的）。
- 確保使用足夠長的隨機值，從而使暴力攻擊變得不可行。

程式碼範例

Java

Use of Cryptographically Insecure PRNG

```
Random random = new Random();
Long sessNum = random.nextLong();
String sessionId = sessNum.toString();
```

Use of Cryptographically Secure PRNG

```
SecureRandom random = new SecureRandom();
byte sessBytes[] = new byte[32];
random.nextBytes(sessBytes);
String sessionId = new String(sessBytes);
```

Use Of Hardcoded Password

風險

可能發生什麼問題

直接寫入的密碼會造成密碼的洩漏。如果攻擊者可以取得程式原始碼，他便可取得密碼，並利用它們來冒充合法使用者。攻擊者可以冒充自己是應用程式的末端使用者，或假裝應用程式登入遠端系統，例如資料庫或網路服務。 一旦攻擊者成功冒充使用者或應用程式，他便可取得完整的控制權，並做到任何能做的事。

原因

如何發生

應用程式程式庫含有嵌入在原始碼內的字串型態的密碼。這個直接寫入的值被直接使用或是用來和使用者輸入做驗證比對。或驗證末端程式連線到遠端系統（如資料庫或網路服務）。 攻擊者只需要取得原始碼即可揭露被直接寫入的密碼。同樣的，攻擊者也可以進行逆向工程反編譯應用程式的二進位程式碼，並簡單的取得寫入的密碼。一旦被發現，攻擊者可以很容易的使用這個密碼進行假冒攻擊，無論是對應用程式或遠端系統。 此外，一旦被偷取，將無法簡單的更改來預防更進一步的濫用，除非應用程式重新編譯過。此外，這個應用程式如果被分配到多個系統，從一個系統竊取的密碼可以自動允許在所有被部屬的系統上使用。

一般建議

如何避免

不要將機密資料直接寫入程式碼內。 特別是，用戶的密碼應該儲存在資料庫或是目錄服務，並使用夠強的雜湊演算法進行加密保護。(如 bcrypt, scrypt, PBKDF2, or Argon2)。不要用直接寫入的值進行比對。 系統密碼應該儲存在配置文件或資料庫，並以強大的加密方法保護（例如AES-256）。加密金鑰應該被安全的保護。

程式碼範例

Java

Hardcoded Admin Password

```
bool isAdmin(String username, String password) {
    bool isMatch = false;

    if (username.equals("admin")) {
        if (password.equals("P@ssw0rd"))
            return isMatch = true;
    }

    return isMatch;
}
```

No Hardcoded Credentials

```
bool isAdmin(String username, String password) {
    bool adminPrivs = false;

    if (authenticateUser(username, password)) {
        UserPrivileges privs = getUserPrivileges(username);

        if (privs.isAdmin)
            adminPrivs = true;
    }
```

```
    return adminPrivs;
}
```

Spring Missing Content Security Policy

風險

可能發生什麼問題

Content-Security-Policy header 強制內容的來源，例如腳本的來源、嵌入（子）框架、嵌入（父）框架或圖像，被當前網頁信任和允許；如果在網頁中，內容的來源不遵守嚴格的內容安全性原則，瀏覽器會立即拒絕該內容。 未定義策略可能會使應用程式的使用者暴露於跨網站腳本 (XSS) 攻擊、點擊劫持攻擊、內容偽造等。

原因

如何發生

Content-Security-Policy header被現代瀏覽器用作可信內容來源的指示器，包括媒體、圖像、腳本、框架等。 如果未明確定義這些策略，則默認瀏覽器行為將允許不受信任的內容。

應用程式創建 Web response，但未正確設置 Content-Security-Policy 標頭。

一般建議

如何避免

建議根據業務需求和外部檔案託管服務的部署，明確地設定合適的CSP標頭(框架、腳本、表單、腳本、媒體、圖片等...)，具體來說，不要使用萬用字元"*"來指定這些策略，因為這將允許來自外部的任何資源內容。
CSP可以在網頁應用程序代碼中明確定義，作為由web-server 配置所管理的標頭，或在HTML<head>下的 <meta>標籤中定義。

程式碼範例

Java

Adding CSP Header Using Spring Security Java Configuration

```
@Configuration
public class SpringSecurityConfig extends WebSecurityConfigurerAdapter {

    @Override
    protected void configure(HttpSecurity http) throws Exception {
        // Add CSP headers
        http.headers()
            .contentSecurityPolicy("script-src 'self' https://example.com; object-src
https://example.com; report-uri /csp-report-endpoint/");
    }
}
```

XML

Adding CSP Header Using Spring Security XML Configuration

```
<http>
   <!-- ... -->

    <headers>
```

```
    <content-security-policy policy-directives="script-src 'self' https://apis.example.com">
        </content-security-policy>
    </headers>
</http>
```

Spring Overly Permissive Cross Origin Resource Sharing Policy

風險

可能發生什麼問題

過於寬鬆的跨域資源共享 (CORS) 標頭 "Access-Control-Allow-Origin" 可能會使其他網站的腳本可以訪問、甚至篡改受影響的 web 應用程式上的資源。這些資源包括頁面內容、Token 等，因此可能受到跨站點請求偽造 (CSRF) 或跨站點腳本 (XSS) 攻擊、假冒用戶執行操作，如更改密碼或違反用戶隱私。

原因

如何發生

程式碼中的 Access-Control-Allow-Origin 被錯誤地設置為不安全的值。
默認情況下，現代瀏覽器會根據同源策略 (SOP) 禁止不同域之間的資源共享訪問彼此的 DOM 內容、cookie jar 和其他資源，這是為了避免惡意 Web 應用程序攻擊合法的 Web 應用程式及其用戶。例如——網站 A 默認無法檢索網站 B 的內容，因為這違反了 SOP。使用具體標頭定義的跨域資源共享 (CORS) 策略可以放鬆這個嚴格的默認行為，允許跨站點通信。但是，如果使用不當，CORS 可能會允許過度地廣泛信任 Web 應用程式，使其能夠提交請求並獲得 Web 應用程式的回應，從而執行意外的或潛在惡意的行為。

一般建議

如何避免

如果沒有顯示需求，請不要設置任何 CORS 標頭。如果有需要，請考慮設置這些標頭的業務需求，然後選擇最嚴格的配置，例如可信任的白名單、安全和允許的域訪問，同時使用其他 CORS 標頭嚴格地提供所需的和預期的功能。
Spring Security 具有內置機制，可使用 @CrossOrigin 註釋來配置 CORS 標頭。
Spring 的默認允許來源過於寬鬆，建議手動指定允許的來源。

程式碼範例

Java

Default 'origins' Parameter Allowing All Origins in a Specific Endpoint

```
@RestController
@RequestMapping("/resource")
public class ResourceController {

      @CrossOrigin
      @GetMapping("/{id}")
      public Resource retrieve(@PathVariable Long id) {
            //  ...
      }
}
```

Setting an 'origins' Parameter on a Specific Controller

```
@CrossOrigin(origins = "https://example.com", maxAge = 3600)
@RestController
```

```
@RequestMapping("/resource")
public class ResourceController {

      @GetMapping("/{id}")
      public Resource retrieve(@PathVariable Long id) {
            //  ...
      }
}
```

Applying the CORS Header to Every Endpoint Using Spring Security's Java Configuration

```
@EnableWebSecurity
public class WebSecurityConfig extends WebSecurityConfigurerAdapter {

      @Override
      protected void configure(HttpSecurity http) throws Exception {
            http
                  // by default uses a Bean by the name of corsConfigurationSource
                  .cors();
      }

      @Bean
      CorsConfigurationSource corsConfigurationSource() {
            CorsConfiguration configuration = new CorsConfiguration();
            configuration.setAllowedOrigins(Arrays.asList("https://example.com"));
            configuration.setAllowedMethods(Arrays.asList("GET","POST"));
            UrlBasedCorsConfigurationSource source = new UrlBasedCorsConfigurationSource();
        // Applying the CORS to all endpoints
        source.registerCorsConfiguration("/**", configuration);
            return source;
      }
}
```

XML

Applying Spring Security's Default CORS with an Overly Permissive Configuration

```
<http>
      <cors />
</http>
```

TruffleHog Regex Matches

風險

可能發生什麼問題

直接寫入的密碼會造成密碼的洩漏。如果攻擊者可以取得程式原始碼，他便可取得密碼，並利用它們來冒充合法使用者。攻擊者可以冒充自己是應用程式的末端使用者，或假裝應用程式登入遠端系統，例如資料庫或網路服務。 一旦攻擊者成功冒充使用者或應用程式，他便可取得完整的控制權，並做到任何能做的事。

原因

如何發生

應用程式程式庫含有嵌入在原始碼內的字串型態的密碼。這個直接寫入的值被直接使用或是用來和使用者輸入做驗證比對。或驗證末端程式連線到遠端系統（如資料庫或網路服務）。 攻擊者只需要取得原始碼即可揭露被直接寫入的密碼。同樣的，攻擊者也可以進行逆向工程反編譯應用程式的二進位程式碼，並簡單的取得寫入的密碼。一旦被發現，攻擊者可以很容易的使用這個密碼進行假冒攻擊，無論是對應用程式或遠端系統。 此外，一旦被偷取，將無法簡單的更改來預防更進一步的濫用，除非應用程式重新編譯過。此外，這個應用程式如果被分配到多個系統，從一個系統竊取的密碼可以自動允許在所有被部屬的系統上使用。

一般建議

如何避免

不要將機密資料直接寫入程式碼內。 特別是，用戶的密碼應該儲存在資料庫或是目錄服務，並使用夠強的雜湊演算法進行加密保護。(如 bcrypt, scrypt, PBKDF2, or Argon2)。不要用直接寫入的值進行比對。 系統密碼應該儲存在配置文件或資料庫，並以強大的加密方法保護（例如AES-256）。加密金鑰應該被安全的保護。

程式碼範例

Insufficient Logging

Weakness ID: 778 *(Weakness Base)* **Status:** Draft

Description

Description Summary

When a security-critical event occurs, the software either does not record the event or omits important details about the event when logging it.

Extended Description

When security-critical events are not logged properly, such as a failed login attempt, this can make malicious behavior more difficult to detect and may hinder forensic analysis after an attack succeeds.

Time of Introduction

- Operation

Applicable Platforms

Languages

Language-independent

Common Consequences

Scope	Effect
Accountability	If security critical information is not recorded, there will be no trail for forensic analysis and discovering the cause of problems or the source of attacks may become more difficult or impossible.

Likelihood of Exploit

Medium

Demonstrative Examples

Example 1

The example below shows a configuration for the service security audit feature in the Windows Communication Foundation (WCF).

(Bad Code)

Example Language: **XML**

```
<system.serviceModel>
<behaviors>
<serviceBehaviors>
<behavior name="NewBehavior">
<serviceSecurityAudit auditLogLocation="Default"
suppressAuditFailure="false"
serviceAuthorizationAuditLevel="None"
messageAuthenticationAuditLevel="None" />
...
</system.serviceModel>
```

The previous configuration file has effectively disabled the recording of security-critical events, which would force the administrator to look to other sources during debug or recovery efforts.

Logging failed authentication attempts can warn administrators of potential brute force attacks. Similarly, logging successful authentication events can provide a useful audit trail when a legitimate account is compromised. The following configuration shows appropriate settings, assuming that the site does not have excessive traffic, which could fill the logs if there are a large number of success or failure events (CWE-779).

(Good Code)

Example Language: **XML**

```
<system.serviceModel>
<behaviors>
<serviceBehaviors>
<behavior name="NewBehavior">
<serviceSecurityAudit auditLogLocation="Default"
suppressAuditFailure="false"
serviceAuthorizationAuditLevel="SuccessAndFailure"
messageAuthenticationAuditLevel="SuccessAndFailure" />
...
</system.serviceModel>
```

Observed Examples

Reference	Description
CVE-2008-4315	server does not log failed authentication attempts, making it easier for attackers to perform brute force password guessing without being detected
CVE-2008-1203	admin interface does not log failed authentication attempts, making it easier for attackers to perform brute force password guessing without being detected
CVE-2007-3730	default configuration for POP server does not log source IP or username for login attempts
CVE-2007-1225	proxy does not log requests without "http://" in the URL, allowing web surfers to access restricted web content without detection
CVE-2003-1566	web server does not log requests for a non-standard request type

Potential Mitigations

Phase: Architecture and Design

Use a centralized logging mechanism that supports multiple levels of detail. Ensure that all security-related successes and failures can be logged.

Phase: Operation

Be sure to set the level of logging appropriately in a production environment. Sufficient data should be logged to enable system administrators to detect attacks, diagnose errors, and recover from attacks. At the same time, logging too much data (CWE-779) can cause the same problems.

Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Base	223	Omission of Security-relevant Information	**Development Concepts (primary)699 Research Concepts (primary)1000**
ChildOf	Category	254	Security Features	Development Concepts699
ChildOf	Weakness Class	693	Protection Mechanism Failure	Research Concepts1000

Content History

Submissions			
Submission Date	**Submitter**	**Organization**	**Source**
2009-07-02			Internal CWE Team
Contributions			
Contribution Date	**Contributor**	**Organization**	**Source**
2009-07-02		Fortify Software	Content
	Provided code example and additional information for description and consequences.		

BACK TO TOP

Undocumented API

風險

可能發生什麼問題

Undocumented or outdated documentation on API endpoints make it more difficult to find and/or fix vulnerabilities.

原因

如何發生

No automatic documentation is being used or if the documentation is being manually specified, some methods are not being correctly documented.

一般建議

如何避免

Generate documentation automatically by adopting open standards. Include the documentation build in your CI/CD pipeline.Document all aspects of your API such as authentication, errors, redirects, rate limiting, cross-origin resource sharing (CORS) policy and endpoints, including their parameters, requests, and responses.

程式碼範例

Java

API Endpoint correctly documented in separate file

```
@Controller
@RequestMapping("/pet")
public class DeferredResultController {

      @GetMapping("/id")
      public @ResponseBody Pet getPetNameById(int id) {
             return context.getPetNameById(id);
    }
}

// OpenAPI specification (openapi.json)
{
  "openapi" : "3.0.1",
  "paths" : {
    "/pet/id" : {
      "get" : {
        "summary" : "Get an existing pet",
        "requestBody" : {
          "description" : "Pet object that needs to be added to the store",
        },
        "responses" : {
          "400" : {
            "description" : "Invalid ID supplied",
            "content" : { }
          }
        }
      }
    }
  }
}
```

API Endpoint not documented

```
@Controller
@RequestMapping("/pet")
public class DeferredResultController {

    @GetMapping("/id")
      public @ResponseBody Pet getPetNameById(int id) {
             return context.getPetNameById(id);
    }

    // This method is not listed on the OpenApi specification file (see below)
    @DeleteMapping("/id")
      public @ResponseBody String deletePetNameById(int id) {
             return context.deletePetNameById(id);
    }
}

// OpenAPI specification (openapi.json)
{
  "openapi" : "3.0.1",
  "paths" : {
    "/pet/id" : {
      "get" : {
        "summary" : "Get an existing pet",
        "requestBody" : {
          "description" : "Pet object that needs to be added to the store",
        },
        "responses" : {
          "400" : {
            "description" : "Invalid ID supplied",
            "content" : { }
          }
        }
      }
    }
  }
}
```

Documentation being automatically generated

```
@Configuration
@EnableSwagger2
public class SpringFoxConfig {
    @Bean
    public Docket api() {
        return new Docket(DocumentationType.SWAGGER_2)
          .select()
          .apis(RequestHandlerSelectors.any())
          .paths(PathSelectors.any())
          .build();
    }
}
```

Use of Function with Inconsistent Implementations

Weakness ID: 474 *(Weakness Base)* **Status:** Draft

Description

Description Summary

The code uses a function that has inconsistent implementations across operating systems and versions, which might cause security-relevant portability problems.

Time of Introduction

- Architecture and Design
- Implementation

Applicable Platforms

Languages

C: *(Often)*

PHP: *(Often)*

All

Potential Mitigations

Do not accept inconsistent behavior from the API specifications when the deviant behavior increase the risk level.

Other Notes

The behavior of functions in this category varies by operating system, and at times, even by operating system version. Implementation differences can include:

- Slight differences in the way parameters are interpreted leading to inconsistent results.
- Some implementations of the function carry significant security risks.
- The function might not be defined on all platforms.

Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	398	Indicator of Poor Code Quality	**Development Concepts (primary)699 Seven Pernicious Kingdoms (primary)700 Research Concepts (primary)1000**
ParentOf	Weakness Variant	589	Call to Non-ubiquitous API	**Research Concepts (primary)1000**

Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Inconsistent Implementations

Content History

Submissions

Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined

Modifications

Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Potential Mitigations, Time of Introduction		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Relationships, Other Notes, Taxonomy Mappings		

Previous Entry Names

Change Date	Previous Entry Name
2008-04-11	Inconsistent Implementations

BACK TO TOP

Insufficient Logging of Exceptions

風險

可能發生什麼問題

If security-critical information is not recorded, there will be no trail for forensic analysis and discovering the cause of problems or the source of attacks may become more difficult or impossible.

原因

如何發生

Error's stack trace is not fully printed.

一般建議

如何避免

Use a centralized logging mechanism that supports multiple levels of detail.Be sure to set the level of logging appropriately in a production environment. Sufficient data should be logged to enable system administrators to detect attacks, diagnose errors, and recover from attacks.

程式碼範例

Java

Print Stack Trace

```
public class Example1{
      public String login(Model model, String username, String password) {
            try {
                  // attempt to login user
                  userService.login(username, password);
            } catch (Exception ex) {
                  ex.printStackTrace();
            }
            return "login";
      }
}
```

Log Error

```
public class Example{
      public String login(Model model, String username, String password) {
            try {
                  // attempt to login user
                  userService.login(username, password);
            } catch (Exception ex) {
                  log.error("Exception looking up customer by name: " + ex.getMessage());
            }
            return "login";
      }
}
```

Log Error

```
public class Example{
      public String login(Model model, String username, String password) {
            try {
                  userService.login(username, password);
            } catch (Exception ex) {
                  log.error("Exception looking up customer by name: " + ex.getMessage(), ex);
            }
            return "login";
      }
}
```

檢測的語言

語言	HASH值	變更的日期
Java	2159688030130788	2025/7/22
JavaScript	0825762690119392	2025/7/22
Common	3640194344930224	2025/7/22