

BT Wait: use stock `UBTTask_Wait`

IN SHORT

UE 5.8 ships `UBTTask_Wait`. Use it.

Pattern

1. In your BT graph: right-click → Add Task → "Wait".
2. Set `WaitTime` (seconds) + optional `RandomDeviation`.
3. Task returns `Succeeded` after the timer.

For a wait that depends on a blackboard-stored time, use `UBTTask_WaitBlackboardTime` instead.

Why we didn't ship `LCM_BTTask_Wait`

Bit-identical functionality. BT has had a Wait task since 4.x, so a custom LCM Nav3D variant adds nothing.

The StateTree side is different, which is why `FLcmSTTask_Wait` is shipped. UE 5.8 does have a stock "Delay Task" (`FStateTreeDelayTask`), and because it is reflected you can pick it in the StateTree asset editor like any other node. It lives in `StateTreeModule/Private/`, though, so no other module can reference it from C++. If you are authoring purely in the editor, prefer the stock Delay Task; reach for `FLcmSTTask_Wait` when you need to construct or subclass the task in your own code.

LCM Nav3D-specific wait variant

If you want to wait for a **specific LCM Nav3D condition** (e.g. "wait until the chunk at position X is loaded"), use the LCM Nav3D-unique:

- `LCM_BTTask_ChunkPrewarm`: waits for chunk readiness with a configurable timeout, proactively enqueues the chunk for generation

Chapter 12, section 1 of the LCM Nav3D User Manual.

The complete manual is `LCM_Nav3D_Manual.pdf`, in this folder alongside every other document in the set. Start from `README.pdf`.

LCM Nav3D: True Volumetric 3D Navigation for Unreal Engine. Version 2.05 · Unreal Engine 5.8.

Copyright © 2026 L.Charitha Madhushanka. All Rights Reserved. Proprietary and confidential. Licensed, not sold; use is governed by the licence that accompanies this software. Unreal Engine is a trademark of Epic Games, Inc. All trademarks are the property of their respective owners.