```
#include<winsock2.h>
#include<stdio.h>
#include <time.h>//计时需要用到的头文件
#pragma comment(lib,"ws2 32.lib")
#include <time.h>//计时需要用到的头文件
clock_t start,end;//程序运行的起始和结束时间
float costtime;//程序耗时
void usage(void)
printf("\tusage: tcpscan RemoteIP StartPort-EndPort\n");
printf("\tExample: tcpscan 192.168.1.1 80-100\n");
int main(int argc,char **argv)
char *host;
int startport, endport;
    char *p;
if(argc!=3)
usage();
return 0;
p=argv[2];//处理端口参数
    if(strstr(argv[2],"-"))
          startport=atoi(argv[2]);
         for(;*p;)
             if(*(p++)=='-')break;
         endport=atoi(p);
         if(startport<1 || endport>65535)
              printf("Port Error!\n");
             return 0;
host=argv[1];
    WSADATA ws;
SOCKET s;
struct sockaddr in addr;
int result;
```

```
long lresult;
lresult=WSAStartup(MAKEWORD(1,1), &ws);
addr.sin family =AF INET;
addr.sin_addr.s_addr =inet_addr(host);
    start=clock();//开始计时
for (int i=startport;i<endport;i++)
s=socket(AF INET, SOCK STREAM, 0);
         addr.sin_port = htons(i);
if(s==INVALID_SOCKET)break;
result=connect(s, (struct sockaddr*)&addr,sizeof(addr));
if(result==0)
printf("%s %d\n",host,i);
closesocket(s);
end=clock();//计时结束
costtime= (float)(end - start) / CLOCKS_PER_SEC; //转换时间格式
printf("Cost time:%f second",costtime);//显示耗时
WSACleanup();
return 0;
```