

Ranking Models

Language Models

Rodrygo L. T. Santos
rodrygo@dcc.ufmg.br

The ranking problem



Ranking models recap

Boolean model

- Boolean query
- Set-based retrieval (no actual ranking)

Vector space models

- Query and documents as vectors
- Similarity-based ranking

Probabilistic ranking models

Probabilistic relevance models

- Query and documents as random variables
- Ranking based on probability of relevance

$$f(q, d) = P(R|d, q)$$

Language modeling approach

Key intuition

- Users who try to think of a good query, think of words that are likely to appear in relevant documents
- A document is a good match to a query if it uses the same underlying *language* as the query

Statistical language model

A probability distribution over word sequences

- $P(\text{"Today is Wednesday"}) \approx 0.001$
- $P(\text{"Today Wednesday is"}) \approx 0.00000000000001$
- $P(\text{"The eigenvalue is positive"}) \approx 0.00001$

Can also be regarded as a probabilistic mechanism for "generating" text, thus also called a "generative" model

Types of language models

Full dependence model

$$P(w_1 \dots w_k) = P(w_1)P(w_2|w_1) \dots P(w_k|w_1 \dots w_{k-1})$$

Infeasible in practice

- Expensive computation
- Weak estimates (data sparsity)

Types of language models

Tunable dependence via n-grams

- 3-gram ("trigram")

$$P(w_1 \dots w_k) = P(w_1)P(w_2|w_1) \dots P(w_k|w_{k-2}, w_{k-1})$$

- 2-gram ("bigram")

$$P(w_1 \dots w_k) = P(w_1)P(w_2|w_1) \dots P(w_k|w_{k-1})$$


- 1-gram ("unigram")

$$P(w_1 \dots w_k) = P(w_1)P(w_2) \dots P(w_k)$$


Unigram language model

The simplest language model

- A one-state probabilistic finite automaton



Example text generation



Evaluation of language models

Direct evaluation criterion

- Goodness of fit: data likelihood, perplexity, cross entropy, Kullback-Leibler divergence

Indirect evaluation criterion

- Task-dependent: we hope more "reasonable" LMs would achieve better task performance

Applications of language models

Language modeling offers a principled way to quantify the uncertainties associated with natural language

Speech recognition

- Given that we see "John" and "feels", how likely will we see "happy" as opposed to "habit" next?

Applications of language models

Language modeling offers a principled way to quantify the uncertainties associated with natural language

Text categorization

- Given that we see “baseball” three times and “game” once in an article, how likely is it about “sports”?

Applications of language models

Language modeling offers a principled way to quantify the uncertainties associated with natural language

Document ranking

- Given that a user is interested in sports news, how likely would he or she use “baseball” in a query?

Language models for ranking

$$\begin{aligned} f(q, d) &= P(R|d, q) && \text{PRP} \\ &\propto P(q, d|R) && \text{Bayes' rule} \\ &\approx P(q, d) \end{aligned}$$

Relevance assumed implicitly!

Query likelihood model

$$\begin{aligned} f(q, d) &\approx P(q, d) \\ &= P(q|d)P(d) && \text{Bayes' rule} \end{aligned}$$

Two core components

- $P(q|d)$: query likelihood
- $P(d)$: document prior

Computing $P(d)$

Uninformative (uniform) prior

- $P(d) = 1/n$, for n documents in the corpus

Informative prior


- Authoritativeness (e.g., PageRank)
- Accessibility (e.g., URL length)
- Readability (e.g., avg. sentence length)

Computing $P(q|d)$


Generative process

- Intuitively, the probability that a user who likes document d (modeled by θ_d) will pose query q

Ranking via query likelihood



Ranking via query likelihood



Computing $P(q|d)$

Under a unigram (term independence) assumption

$$P(q|\theta_d) = \prod_{t \in q} P(t|\theta_d)^{\text{tf}_{t,q}}$$

$$\propto \sum_{t \in q} \text{tf}_{t,q} \log P(t|\theta_d)$$

How to
estimate
 $P(t|\theta_d)$?

Maximum likelihood estimation (MLE)

Simply count observed occurrences

$$P_{\text{MLE}}(t|\theta_d) = \frac{\text{tf}_{t,d}}{|d|}$$

Problems

- Observed terms will be scored too optimistically
- Unobserved terms will receive zero probability


Smoothing probabilities

Smooth probabilities in language models

- Discount the probability of seen words
- Give some probability mass to unseen words

The probability of a non-occurring term should be close to its probability of occurrence in the corpus C

Smoothing probabilities



Smoothing probabilities

General form

$$P(t|\theta_d) = (1 - \alpha) P_{\text{MLE}}(t|\theta_d) + \alpha P_{\text{MLE}}(t|\theta_c)$$

Smoothing controlled through parameter α

$$\text{Jelinek-Mercer: } \alpha = \lambda, 0 < \lambda < 1$$

Jelinek-Mercer smoothed model

$$\begin{aligned} f(q, d) &\propto \prod_{t \in q} P(t|\theta_d)^{\text{tf}_{t,q}} \\ &= \prod_{t \in q} \left((1 - \lambda) \frac{\text{tf}_{t,d}}{|d|} + \lambda \frac{\text{tf}_{t,c}}{|C|} \right)^{\text{tf}_{t,q}} \end{aligned}$$

Jelinek-Mercer example ($\lambda = 1/2$)

q : [michael jackson]

d_1 : Jackson was a gifted entertainer

d_2 : Michael Jackson anointed himself King of Pop

$$P(q|\theta_1) = \left[\frac{0/5 + 1/12}{2} \right] \times \left[\frac{1/5 + 2/12}{2} \right] \approx 0.008$$

$$P(q|\theta_2) = \left[\frac{1/7 + 1/12}{2} \right] \times \left[\frac{1/7 + 2/12}{2} \right] \approx 0.018$$

Where is tf-idf weighting?

$$\begin{aligned} f(q, d) &\propto \sum_{t \in q} \text{tf}_{t,q} \log P(t|\theta_d) \\ &= \sum_{t \in q} \text{tf}_{t,q} \log \left((1 - \lambda) \frac{\text{tf}_{t,d}}{|d|} + \lambda \frac{\text{tf}_{t,c}}{|C|} \right) \end{aligned}$$

Where is tf-idf weighting?

$$f(q, d) \propto \sum_{t \in q} \text{tf}_{t,q} \log \left(\frac{(1 - \lambda) \frac{\text{tf}_{t,d}}{|d|}}{\lambda \frac{\text{tf}_{t,c}}{|C|}} + 1 \right)$$

Where is tf-idf weighting?

$$f(q, d) \propto \sum_{t \in q} \text{tf}_{t,q} \log \left(\frac{(1 - \lambda) \frac{\text{tf}_{t,d}}{|d|}}{\lambda \frac{\text{tf}_{t,c}}{|C|}} + 1 \right)$$

- Proportional to term frequency: tf effect
- Inv. proportional to collection frequency: idf effect

How about document length?

General form

$$\circ P(t|\theta_d) = (1 - \alpha) P_{\text{MLE}}(t|\theta_d) + \alpha P_{\text{MLE}}(t|\theta_c)$$

Smoothing controlled through parameter α

$$\circ \text{Jelinek-Mercer: } \alpha = \lambda, 0 < \lambda < 1$$

$$\circ \text{Dirichlet: } \alpha = \frac{\mu}{|d| + \mu} \quad \begin{array}{l} |d| \rightarrow 0 \therefore \alpha \rightarrow 1 \\ |d| \rightarrow \infty \therefore \alpha \rightarrow 0 \end{array}$$

How effective are these?


Dirichlet smoothing works the best

- Particularly effective for keyword queries

Length-adjusted smoothing

- Shorter documents get more smoothing
- Longer documents get less smoothing

Extended approaches



Document likelihood model

$$\begin{aligned} f(q, d) &\approx P(q, d) \\ &= P(d|q)P(q) \quad \text{Bayes' rule} \\ &\propto P(d|\theta_q) \end{aligned}$$

Problem: queries are short

- Poor estimation of θ_q

Solution: improve query model via feedback

Model comparison

Two steps

- Build both θ_q and θ_d
- Measure how much they **diverge**

Divergence-based ranking

$$\circ f(q, d) = -D(\theta_q || \theta_d)$$

Model comparison

Kullback-Leibler (KL) divergence

- Asymmetric measure $[0, \infty]$

$$f(q, d) = -D_{\text{KL}}(\theta_q || \theta_d)$$

$$= - \sum_t P(t|\theta_q) \log \frac{P(t|\theta_q)}{P(t|\theta_d)}$$

Summary

Principled ranking approach

- Statistical foundations (better parameter setting)

Effectiveness through smoothing

- Add key ranking components (idf, document length)

Flexible and extendable

- Relevance feedback, priors, other tasks

References

[Introduction to Information Retrieval](#), Ch. 12

Manning et al., 2008

[Search Engines: Information Retrieval in Practice](#), Ch. 7

Croft et al., 2009

[Statistical Language Models for Information Retrieval](#)

Zhai, FNTIR 2008

References

[A language modeling approach to information retrieval](#)

Ponte and Croft, SIGIR 1998

[A study of smoothing methods for language models applied to information retrieval](#)

Zhai and Lafferty, SIGIR 2001



Coming next...

Information-theoretic Models

Rodrygo L. T. Santos
rodrygo@dcc.ufmg.br