

Computer Architecture Practical Exercise

7 Cache Blocking 2D

Kenan Gündogan¹ Philipp Gündisch¹

¹Friedrich-Alexander Universität Erlangen-Nürnberg, Chair of Computer Science 3
(Computer Architecture)

December 16, 2024

L1 Cache Blocking




Motivation

- L1 Cache enables the fastest memory access
- Usually very small cache sizes
- *Cache Prefetching* cannot be ignored for these very small cache sizes


Cache Prefetching

- Hardware prefetcher tries to guess upcoming memory addresses to *prefetch* data from slow memory
- Works similar to branch prediction but for memory access patterns
- **Issue:** Additional data is filling up the cache but is not accessed before displacement



Solution


- Stop block iteration before prefetched data gets displaced
- Block in d_x and d_y direction
- The block of size $b_x \cdot b_y$ is called a **tile**
- For L1 blocking, keep the **whole tile** and the prefetched data within the cache



Advanced L1 Blocking

Grid Iteration

- When the tile is processed proceed with the tile to the east
- Once a row of tiles is completed proceed to the south



Task 7.1: Cache Blocking



Blocking Parameters

Due to the unknown prefetching size it is difficult to estimate the blocking factor in b_x and b_y direction. Additionally, a modification of b_x does not have the same impact as a modification of b_y but both influence each other. Therefore, we will determine these blocking factors empirically.

- Determine a reasonable theoretical maximum and minimum for b_x and b_y
- Implement L1 cache blocking by extending the solution of the last exercise
- Make b_x and b_y compile time constants
- Choose a significantly large GridSize of 1 GiB
- Determine (roughly) the best b_x, b_y combination while benchmarking for a **reasonable time**
- **OPTIONAL** Visualize your results as a heatmap with b_x and b_y as the axis and MUp/s as the coloration (similar to the jacobi ppm file)

Task 7.2: Cache Blocking



Benchmark

- Benchmark your implementation with the best b_x, b_y combination from 7.1
- Benchmark from 1 GiB to 128 GiB
- Create the performance plots as usual with MUp/s and ArraySize as axis
- Compare the this version against the best blocked version from previous exercise 6
- *Hint: 50K x 50K grid: $\geq 850 \cdot 10^6$ Updates/s*

- E 7.1: Blocking Parameters
 - Determine the optimal blocking parameter combination for b_x and b_y
- E 7.2: L1 Cache Blocking
 - Benchmark the updated implementation from 1GiB - 128GiB

Performance Optimization (1/2)

During the timeline of this class new bullet points will be added. Recently added entries are bold.

- Compiling
 - Choice of the compiler (`icx`)
 - Compiler flag to optimize aggressively (e.g. `-O3`)
 - Compiler flag to adapt for specific hardware (e.g. `-xHost`)
- Programming Techniques (if applicable)
 - Use `#define` and `const` instead of variables
 - Data type aware programming
 - Use aligned memory (e.g. with `_mm_malloc()` or `posix_memalign()`)
 - Consecutive address iteration
 - Variable declarations outside of loops
 - Reduce function calls
 - Use intrinsics (to utilize SIMD)
 - Cache aware programming (Spatial Blocking)
 - **Prefetcher aware programming (L1 Cache Blocking)**

Appendix: Checklist



Performance Optimization (2/2)

During the timeline of this class new bullet points will be added. Recently added entries are bold.

- Measurement
 - Reasonable benchmark time
 - Reasonable benchmark workload
 - Reduce interference factors to a minimum
- Optimization Process
 - Check assembler code while optimizing
 - Check performance gains while optimizing
 - Use profiling tools
 - Ensure correctness of code
 - Optimize iteratively

Merry Christmas



and a happy new year!

This is the last appointment this year!

- Monday 6th is still a public holiday
- The next appointment is on Monday 13th / Tuesday 14th
- We have one final optimization step left for Jacobi on the CPU: **Parallelization**
- After that we switch to the GPU

We wish you a nice and joyful holiday and a good start into 2025.