## HPC-101 - Cheatsheet

### Sean Cleveland Ph.D, Ron Merrill Ph.D, David Schanzenbach M.S.

University of Hawai'i Information Technology Services – Cyberinfrastructure

January 21, 2016

## 1 Directory Navigation

cd <Directory>

Change to directory specified

ls <Path>

List the contents of the specified path

ls -1 <Path>

This flag list the paths content in long form

ls -lh <Path>

Make the filesize humanreable

ls -a <Path>

Show hidden directories and files

# 2 SSH/SCP

- ssh <user>@<host>
- ssh -Y <user>@<host>

Enable X11 forwarding

• scp <file> <user>@<host>:<remote path>

Copy a file to a remote location

• scp -r <dir> <user>@<host>:<remote path>

Recursivly copy a directory to a remote location

### 3 SLURM

#### 3.1 Management And Monitoring

sbatch <slurm\_script>

Submit a slurm script to the scheduler for batch processing

sbatch -array=[#-#] <slurm\_script>

Submit a job array to the scheduler

srun

Used in submitting an interactive job, or also used within a slurm script

srun.x11

Used in submitting an interactive job, that also forwards the X, if you logged in while enabling X forwarding

• squeue

Display all jobs running or waiting on the cluster

squeue -u<user>

Only display jobs for the specified user

sinfo

Display the partitions and nodes state

scancel <jobid>

Cancel the specified job

#### 3.2 Details and Profiling

scontrol show jobid <jobid>

Show job details of a waiting or running job

 $\begin{tabular}{ll} scontrol & show parition & <partition \\ name > & \\ \end{tabular}$ 

Show details of the specified partition

scontrol show node <node name>

Show details of the specified node

 ${\tt sacct}$  -l -j <jobid>

Show usage details of a job

sacct -u <user>

Show all jobs from a given user

## 4 Miscellaneous

#### 4.1 Commands

less <file>

Show contents of file Navigate using up/down arrow keys, spacebar, or pageup/pagedown keys Press 'q' to exit out of less

less -S <file>

Show contents of file without line wrap Navigate using up/down arrow keys, spacebar, or pageup/pagedown keys Press 'q' to exit out of less

#### 4.2 Operators

I

Pipe operator is used between two commands, in which you wish to pass the output of the 1st command to the input of the 2nd command

 $Ex. sacct -l -j 467 \mid less -S$ 

#### 4.3 Hosts

login-0001 - uhhpc1.its.hawaii.edu

login-0002 - uhhpc2.its.hawaii.edu

### 4.4 Globus Endpoints

login-0001 - hawaiiUHHPC1

login-0002 - hawaiiUHHPC2