

AstraQuantum Tech

Summer of Cybersecurity 2026 — Week 5

Penetration Testing & Professional Security Reporting

Evidence-based learning and VAPT report

Student Name: Muhammad Umar Imran

Student ID: AQT-1170

Date: 15 September 2026

Classification: Academic submission — authorized training-lab work only

GitHub Repository: [htb-week5-penetration-testing-report](#)

LinkedIn Post: [Week 5 cybersecurity update](#)

This report documents learning and observations from authorized Hack The Box Academy exercises. It is not a report of testing against any production system.

Contents

1. Executive Summary
2. Scope and Rules of Engagement
3. Methodology
4. Tools and Techniques Observed
5. Module Summaries
6. Findings and Risk Assessment
7. Evidence
8. Recommendations
9. Conclusion
10. Appendix: Evidence Inventory

1. Executive Summary

This report records practical penetration-testing learning completed in the supplied HTB Academy evidence set for Week 5. The work follows a controlled-lab approach: identify the

authorized target, enumerate the exposed services, review the available application or host information, validate observations with limited lab actions, and record the result.

The supplied screenshots show evidence of network and service enumeration, web-server and TLS identification, FTP/service review, Linux configuration checks, terminal-based security exercises, and Windows/PowerShell-based lab work. The strongest recurring lesson is that a tester should connect every technical observation to a defensive action. A service version, certificate detail, exposed file, or permissive host setting can become useful attack context when it is combined with other weaknesses.

The evidence supplied supports a professional learning record. It does not support claiming access to any real-world system, and this report therefore keeps the conclusions limited to the authorized training environment and the screenshots provided.

2. Scope and Rules of Engagement

Testing was limited to the targets and workstations explicitly provided by Hack The Box Academy and the instructor for the Week 5 assignment. No public website, personal account, production server, or third-party device was tested. Activities were performed for learning and validation in the authorized lab environment only.

The report intentionally omits passwords, tokens, flags, and other sensitive lab data. Any screenshot that contains lab-only account or target information should remain in the private submission copy and should not be uploaded to a public repository or social-media post without redaction.

3. Methodology

The practical workflow used in the evidence set was:

1. Confirm the lab target and exercise objective.
2. Identify reachable services and collect basic version information.
3. Review web, TLS, FTP, Linux, or Windows evidence relevant to the exercise.
4. Validate the observation with a focused command or lab interaction.
5. Record what the observation means from a defensive perspective.
6. Preserve screenshots as evidence and avoid unnecessary impact.

This is a high-level description rather than a step-by-step exploit walkthrough. It is sufficient to explain the reasoning without publishing reusable attack instructions or sensitive lab answers.

4. Tools and Techniques Observed

The supplied evidence shows use of or interaction with the following tools and techniques:

- **Nmap/service enumeration:** identifying reachable ports, service names, and versions.
- **Web and HTTP review:** inspecting application responses and server behavior in the lab.
- **TLS certificate review:** checking certificate subject, validity, and related service details.
- **FTP/service review:** examining an exposed file-transfer service in the controlled target.
- **Linux command line:** checking host settings and security-relevant configuration.
- **PowerShell/Windows command line:** reviewing Windows-side lab information and outputs.
- **Sysctl configuration check:** observing the value of `kernel.unprivileged_usersns_clone` as a host-hardening signal.

5. Module Summaries

Module 296 — service enumeration and initial assessment evidence

The evidence explicitly named for Module 296 shows Nmap output, an identified HTTP service, an Nginx/server-version observation, and a TLS certificate review. The work demonstrates how a tester builds an initial picture of a target before attempting any deeper validation. The key concepts are attack-surface discovery, service fingerprinting, and certificate/configuration review.

A useful command pattern learned was focused Nmap service detection rather than broad, unnecessary testing. The security lesson is that exposed services and version information should be minimized, maintained, and monitored because they help an attacker select the next step.

Evidence references: `mod296_ss2_nginx_version.png` , `mod296_ss3_ssl_cert.png` , and `ftp 1.png` .

Module 77 — host and Linux security checks

The second evidence group contains terminal-based work involving Linux host inspection and security-relevant configuration. The supplied screenshot for

`kernel.unprivileged_usersns_clone` shows a direct configuration check, while the other terminal captures show additional command-line exercise work. These observations are useful for understanding how local configuration can affect privilege boundaries and exploitability.

The main concepts recorded here are local enumeration, security-sensitive system settings, and the need to verify whether a weakness is actually reachable in the given context. The defensive

lesson is to harden host configuration deliberately, monitor changes, and retest after applying a control.

Evidence references: `sysctl kernel.unprivileged_usersns_clone.png` and `1 g.png` .

Module 90 — Windows/web lab evidence and validation

The third evidence group contains Windows/PowerShell and web-lab terminal captures. The screenshots show command-line validation and application-side work in the supplied lab environment. Because the archive does not include a completion export or a readable module-title page, this section records the demonstrated activities without inventing a module title or claiming results not visible in the evidence.

The useful concepts are evidence collection, command-line validation, and separating an observed technical condition from its possible impact. The defensive lesson is to reduce unnecessary exposure, keep application and host components updated, and validate security controls through repeatable testing.

Evidence references: `1.a.png` and `2c.png` .

6. Findings and Risk Assessment

The following observations are written as lab findings. Their severity is intentionally conservative because the supplied screenshots do not establish a production impact or a complete exploit chain.

PT-01 — Service and version information exposed during enumeration

Severity: Low

Affected lab: Module 296 evidence set

Description: The evidence shows reachable services and identifiable server/version information, including an HTTP service and an Nginx-related observation.

Impact: In a real environment, unnecessary service exposure and version disclosure could help an attacker prioritize known weaknesses. The screenshot alone does not prove exploitation.

Recommendation: Disable unused services, restrict management interfaces, keep exposed software patched, and avoid unnecessary version banners. Confirm the change with an authorized rescan.

PT-02 — TLS certificate/configuration requires periodic review

Severity: Low

Affected lab: Module 296 evidence set

Description: A screenshot records TLS certificate and service details for the lab target.

Impact: Weak, expired, mismatched, or unnecessarily revealing certificate configuration can

reduce trust and provide useful reconnaissance information. The supplied evidence is a review point, not proof of a certificate vulnerability.

Recommendation: Use a valid certificate for the intended hostname, maintain current validity and strong protocol settings, and review certificate exposure during routine assessments.

PT-03 — Security-sensitive Linux configuration observed

Severity: Informational / Low

Affected lab: Module 77 evidence set

Description: The supplied evidence checks the value of `kernel.unprivileged_userns_clone`, a host setting that can affect the availability of unprivileged user namespaces.

Impact: A permissive setting can increase the attack surface for local users when combined with another local vulnerability. The screenshot alone does not demonstrate privilege escalation.

Recommendation: Apply a documented hardening baseline, set the value according to the system's operational needs, and test applications after changing it.

PT-04 — Multiple exposed services increase attack surface

Severity: Informational

Affected lab: Supplied service and web evidence

Description: The evidence includes web, FTP, and command-line/service review activity in the authorized lab.

Impact: Every reachable service creates another surface that must be patched, authenticated, logged, and restricted. The evidence does not establish that any service was compromised.

Recommendation: Maintain an approved service inventory, remove unnecessary services, restrict access by network policy, and monitor authentication and administrative activity.

7. Evidence

Figure 1 — Module 296: Nginx/service version observation

```
Nmap done: 1 IP address (1 host up) scanned in 48.14 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > nmap -sV -p80 10.129.233.210
Starting Nmap 7.95 ( https://nmap.org ) at 2026-09-10 07:41 EDT
Nmap scan report for 10.129.233.210
Host is up (0.17s latency).

PORT      STATE SERVICE VERSION
80/tcp    open  http    nginx 1.18.0 (Ubuntu)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.79 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > █
```

Figure 1 — Supplied screenshot showing service enumeration and an Nginx/server-version observation in the authorized lab.

Figure 2 — Module 296: TLS certificate review

```
Nmap scan report for 10.129.233.210
Host is up (0.051s latency).

PORT      STATE SERVICE VERSION
443/tcp    open  ssl/http Apache httpd 2.4.52 ((Ubuntu))
|_http-server-header: Apache/2.4.52 (Ubuntu)
|_ssl-cert: Subject: commonName=cube-case.htb/organizationName=Organization/stateOrProvinceName=State/countryName=US
| Issuer: commonName=cube-case.htb/organizationName=Organization/stateOrProvinceName=State/countryName=US
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha256WithRSAEncryption
| Not valid before: 2025-02-15T18:00:13
| Not valid after: 2026-02-15T18:00:13
| MD5: d560:c26e:b6c6:536c:88ad:dae2:3e63:af95
|_SHA-1: e565:6531:42e5:b061:e3f1:f21a:b3f5:f774:852e:d2de

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 21.13 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > █
```

Figure 2 — Supplied screenshot showing TLS certificate and service details for the authorized lab target.


Figure 3 — Module 77: Linux security configuration check

A terminal window with a dark background and light blue text. The window has a menu bar with 'File', 'Edit', 'View', 'Search', 'Terminal', and 'Help'. The terminal output shows several configuration checks: setting environment variables for support, bug report, and privacy policy URLs; checking the Ubuntu codename (jammy); running 'sudo --version' which outputs 'Sudo version 1.9.9' and details about policy, grammar, I/O, and audit plugins; running 'lsb_release -r' which outputs 'Release: 22.04'; running 'which passwd' which outputs '/usr/bin/passwd'; and running 'sysctl kernel.unprivileged_userns_clone' three times, each outputting '/bin/sh: 5: sysctl: not found' or '/bin/sh: 6: sysctl: not found'. The final line shows 'sysctl kernel.unprivileged_userns_clone' followed by 'kernel.unprivileged_userns_clone = 0' on a new line.

```
File Edit View Search Terminal Help
SUPPORT_URL="https://help.ubuntu.com/"
BUG_REPORT_URL="https://bugs.launchpad.net/ubuntu/"
PRIVACY_POLICY_URL="https://www.ubuntu.com/legal/terms-and-policies/privacy-policy"
UBUNTU_CODENAME=jammy
sudo --version
Sudo version 1.9.9
Sudoers policy plugin version 1.9.9
Sudoers file grammar version 48
Sudoers I/O plugin version 1.9.9
Sudoers audit plugin version 1.9.9
lsb_release -r
Release:      22.04
which passwd
/usr/bin/passwd
sysctl kernel.unprivileged_userns_clone
/bin/sh: 5: sysctl: not found
sysctl kernel.unprivileged_userns_clone
/bin/sh: 6: sysctl: not found
sysctl kernel.unprivileged_userns_clone
kernel.unprivileged_userns_clone = 0
```

Figure 3 — Supplied screenshot showing a check of the Linux `kernel.unprivileged_userns_clone` setting.

Figure 4 — Module 77: terminal exercise evidence

A terminal window with a dark background and light blue text. The terminal output shows the same sequence of commands as Figure 3, but with some additional lines at the bottom: 'which lxc' and '/snap/bin/lxc'. The output for 'sysctl kernel.unprivileged_userns_clone' is repeated three times, each outputting '/bin/sh: 5: sysctl: not found' or '/bin/sh: 6: sysctl: not found'. The final line shows 'sysctl kernel.unprivileged_userns_clone' followed by 'kernel.unprivileged_userns_clone = 0' on a new line.

```
Sudoers audit plugin version 1.9.9
lsb_release -r
Release:      22.04
which passwd
/usr/bin/passwd
sysctl kernel.unprivileged_userns_clone
/bin/sh: 5: sysctl: not found
sysctl kernel.unprivileged_userns_clone
/bin/sh: 6: sysctl: not found
sysctl kernel.unprivileged_userns_clone
kernel.unprivileged_userns_clone = 0
which lxc
/snap/bin/lxc
```

Figure 4 — Supplied screenshot showing command-line work from the Linux security exercise.

Figure 5 — Module 90: Windows/web lab command-line evidence




Figure 5 — Supplied screenshot showing Windows/web lab validation activity.

Figure 6 — Module 90: additional validation output




Figure 6 — Supplied screenshot showing additional command-line evidence from the supplied lab set.

8. Recommendations

The immediate priority is to maintain an accurate service inventory and remove anything that is not required. Exposed services should be restricted to the necessary network segments, patched on a defined schedule, and monitored for unexpected access.

For web and TLS services, hide unnecessary version details, use current server releases, maintain correctly scoped certificates, and verify protocol settings with an authorized security check. For Linux hosts, apply a documented baseline for sensitive kernel and system settings rather than changing values without considering application compatibility.

Finally, every lab observation should be retested after remediation. A finding is not closed because a configuration was changed; it is closed after the change is confirmed and no longer creates the same condition.

9. Conclusion

The supplied evidence demonstrates the value of a disciplined penetration-testing workflow. Enumeration provides context, focused validation prevents unnecessary impact, and clear evidence makes the result reviewable. The most important defensive takeaway is that small exposures—such as a reachable service, a version banner, or a permissive local setting—should be assessed together with patching, access control, monitoring, and retesting.

This report is limited to the authorized HTB Academy learning environment and the evidence supplied with the assignment.

10. Appendix: Evidence Inventory

Evidence file	Report use
mod296_ss2_nginx_version.png	Module 296 service/version observation
mod296_ss3_ssl_cert.png	Module 296 TLS certificate review
ftp 1.png	Supporting service-review evidence
sysctl kernel.unprivileged_userns_clone.png	Module 77 Linux configuration check
1 g.png	Module 77 terminal exercise evidence
1.a.png	Module 90 Windows/web lab evidence
2c.png	Module 90 additional validation evidence

Submission note: Confirm the exact completion status and the module-title mapping in HTB Academy before submitting. Do not claim completion of a module unless the corresponding practical work was actually completed.

Appendix B — Complete Supplied Screenshot Evidence

The following appendix preserves all screenshots supplied in the assignment archive. Each image is included as received and labeled by its original filename. These images are retained for the private academic submission; only redacted copies should be shared publicly.

Figure B-1 — 1;l.png




Figure B-1 — Supplied screenshot: 1;l.png.

Figure B-2 — 1 f.png




Figure B-2 — Supplied screenshot: 1 f.png.

Figure B-3 — 1 final.png




Figure B-3 — Supplied screenshot: 1 final.png .

Figure B-4 — 1 g.png




Figure B-4 — Supplied screenshot: 1 g.png .

Figure B-5 — 1 h.png




Figure B-5 — Supplied screenshot: 1 h.png .

Figure B-6 — 1 i.png




Figure B-6 — Supplied screenshot: 1 i.png .

Figure B-7 — 1 j.png




Figure B-7 — Supplied screenshot: 1 j.png .

Figure B-8 — 1 k.png




Figure B-8 — Supplied screenshot: 1 k.png .

Figure B-9 — 1 last.png




Figure B-9 — Supplied screenshot: 1 last.png .

Figure B-10 — 1.a.png





Figure B-10 — Supplied screenshot: 1.a.png .

Figure B-11 — 1.e.png




```
File Edit View Search Terminal Help
PowerShell 7.6.0
Welcome to Parrot OS

Welcome to Pwnbox, Powered by Parrot OS
PS [10.10.14.99] /home/htb-ac-2831047 > curl -sk https://10.129.85.255/feed/ | g
rep -i generator

<generator>https://wordpress.org/?v=6.7.2</generator>
PS [10.10.14.99] /home/htb-ac-2831047 >
```

Figure B-11 — Supplied screenshot: 1.e.png.


Figure B-12 — 1d.png



```
<generator>https://wordpress.org/?v=6.7.2</generator>
PS [10.10.14.99] /home/htb-ac-2831047 > curl -sk https://10.129.85.255/feed/ | g
rep -i "wp-content/themes"
PS [10.10.14.99] /home/htb-ac-2831047 > curl -sk https://10.129.85.255/ | grep -
i "wp-content/themes"
<link rel='stylesheet' id='twentytwentyfive-style-css' href='https://cube-case.h
tb/wp-content/themes/twentytwentyfive/style.css?ver=1.0' media='all' />
@font-face{font-family:Beiruti;font-style:normal;font-weight:200 900;font-displa
y:fallback;src:url('https://cube-case.htb/wp-content/themes/twentytwentyfive/ass
ets/fonts/beiruti/Beiruti-VariableFont_wght.woff2') format('woff2');}
@font-face{font-family:Literata;font-style:normal;font-weight:200;font-display:f
allback;src:url('https://cube-case.htb/wp-content/themes/twentytwentyfive/assets
/fonts/literata/Literata72pt-ExtraLight.woff2') format('woff2');}
@font-face{font-family:Literata;font-style:italic;font-weight:200;font-display:f
allback;src:url('https://cube-case.htb/wp-content/themes/twentytwentyfive/assets
/fonts/literata/Literata72pt-ExtraLightItalic.woff2') format('woff2');}
@font-face{font-family:Literata;font-style:normal;font-weight:300;font-display:f
allback;src:url('https://cube-case.htb/wp-content/themes/twentytwentyfive/assets
/fonts/literata/Literata72pt-Light.woff2') format('woff2');}
@font-face{font-family:Literata;font-style:italic;font-weight:300;font-display:f
```

Figure B-12 — Supplied screenshot: 1d.png.

Figure B-13 — 1m.png



```
File Edit View Search Terminal Help
+ Select-String -Path 'C:\Users\Administrator\customer_database.csv' -Pa ...
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (C:\Users\Ammini...mer_database.csv
+ FullyQualifiedErrorId : PathNotFound,Microsoft.PowerShell.Commands.SelectS
tringCommand


C:\Users\Administrator\gitea-repositories\john\lotlux_flowdesk.git>powershell -c
"Select-String -Path 'C:\Users\Administrator\customer_database.csv' -Pattern 'N
icholas,Taylor'"
powershell -c "Select-String -Path 'C:\Users\Administrator\customer_database.csv
' -Pattern 'Nicholas,Taylor'"

C:\Users\Administrator\customer_database.csv:400:7d660ce6-fb54-4006-8446-5ae1b3a
e1064,Nicholas,Taylor,amandalewis@yahoo
.com,(157)922-3156,"8849 Brandon Roads Apt. 930

PowerShell
```

Figure B-13 — Supplied screenshot: 1m.png.

Figure B-14 — 2 d.png



```
user1@ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:~$ sudo su
-
[sudo] password for user1:
Sorry, user user1 is not allowed to execute '/usr/bin/su -' as root on n
g-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk.
user1@ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:~$ sudo -l
Matching Defaults entries for user1 on
    ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/s
bin\:/bin\:/snap/bin

User user1 may run the following commands on
    ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:
    (user2 : user2) NOPASSWD: /bin/bash
user1@ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:~$ sudo -u
user2 /bin/bash
user2@ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:/home/user
1$ cat /home/user2/flag.txt
HTB{l473r4l_m0v3m3n7_70_4n07h3r_u53r}
user2@ng-2831047-gettingstartedprivesc-uh9hw-7cfb79577b-6vhlk:/home/user
1$
```

Figure B-14 — Supplied screenshot: 2 d.png.

Figure B-15 — 2a.png




Figure B-15 — Supplied screenshot: 2a.png .

Figure B-16 — 2b.png




Figure B-16 — Supplied screenshot: 2b.png .

Figure B-17 — 2c.png




Figure B-17 — Supplied screenshot: 2c.png .

Figure B-18 — ftp 1.png




Figure B-18 — Supplied screenshot: ftp 1.png .

Figure B-19 — mod296_ss2_nginx_version.png

```
Nmap done: 1 IP address (1 host up) scanned in 48.14 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > nmap -sV -p80 10.129.233.210
Starting Nmap 7.95 ( https://nmap.org ) at 2026-09-10 07:41 EDT
Nmap scan report for 10.129.233.210
Host is up (0.17s latency).

PORT      STATE SERVICE VERSION
80/tcp    open  http      nginx 1.18.0 (Ubuntu)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap
.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.79 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > █
```

Figure B-19 — Supplied screenshot: `mod296_ss2_nginx_version.png`.

Figure B-20 — mod296_ss3_ssl_cert.png

```
Nmap scan report for 10.129.233.210
Host is up (0.051s latency).

PORT      STATE SERVICE VERSION
443/tcp    open  ssl/http Apache httpd 2.4.52 ((Ubuntu))
|_http-server-header: Apache/2.4.52 (Ubuntu)
|_ssl-cert: Subject: commonName=cube-case.htb/organizationName=Organization/stat
eOrProvinceName=State/countryName=US
| Issuer: commonName=cube-case.htb/organizationName=Organization/stateOrProvince
Name=State/countryName=US
| Public Key type: rsa
| Public Key bits: 2048
| Signature Algorithm: sha256WithRSAEncryption
| Not valid before: 2025-02-15T18:00:13
| Not valid after: 2026-02-15T18:00:13
| MD5: d560:c26e:b6c6:536c:88ad:dae2:3e63:af95
|_SHA-1: e565:6531:42e5:b061:e3f1:f21a:b3f5:f774:852e:d2de

Service detection performed. Please report any incorrect results at https://nmap
.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 21.13 seconds
PS [10.10.15.215] /home/htb-ac-2831047 > █
```

Figure B-20 — Supplied screenshot: `mod296_ss3_ssl_cert.png`.

Figure B-21 — sysctl kernel.unprivileged_userns_clone.png

A terminal window with a dark background and light blue text. The window has a menu bar at the top with 'File', 'Edit', 'View', 'Search', 'Terminal', and 'Help'. The terminal shows the following commands and output:

```
SUPPORT_URL="https://help.ubuntu.com/"
BUG_REPORT_URL="https://bugs.launchpad.net/ubuntu/"
PRIVACY_POLICY_URL="https://www.ubuntu.com/legal/terms-and-policies/privacy-policy"
UBUNTU_CODENAME=jammy
sudo --version
Sudo version 1.9.9
Sudoers policy plugin version 1.9.9
Sudoers file grammar version 48
Sudoers I/O plugin version 1.9.9
Sudoers audit plugin version 1.9.9
lsb_release -r
Release: 22.04
which passwd
/usr/bin/passwd
sysctl kernel.unprivileged_userns_clone
/bin/sh: 5: sysctl: not found
sysctl kernel.unprivileged_userns_clone
/bin/sh: 6: sysctl: not found
sysctl kernel.unprivileged_userns_clone
kernel.unprivileged_userns_clone = 0
```

The last line of output is highlighted with a light blue background.

Figure B-21 — Supplied screenshot: `sysctl kernel.unprivileged_userns_clone.png`.