

CDM-Telematics Wiki Documentation

Contents

1	CDM-Telematics compiled wiki pages	2
1.1	Version	2
2	Entity details	19
2.1	Purpose	19
2.2	Diagram	19
2.3	Comments	19
3	Operational Location	20
3.1	Purpose	20
3.2	Diagram	20
3.3	Comments	20
3.3.1	Property “at operational location”	20
3.3.2	So where are moving things located at time t ?	21
4	Intermodal Transport Unit	22
4.1	Purpose	22
4.2	Diagram	22
4.3	Comments	22
5	Facility	23
5.1	Purpose	23
5.2	Diagram	23
5.3	Comments	23
6	Operational roles	24
6.1	Purpose	24
6.2	Diagram	24
6.3	Comments	25
6.3.1	No dedicated class for organizations - just a blank node	25
7	Journey Schedule	27
7.1	Purpose	27
7.2	Diagram	27
7.3	Comments	27
7.3.1	Nested Lists	27
7.3.2	Not a speed profile	27

7.3.3	Data consistency	27
7.3.4	List ontology	29
8	Train run state	38
8.1	Purpose	38
8.2	Diagram	38
8.3	Comments	38
9	Message	39
9.1	Purpose	39
9.2	Diagram	39
9.3	Comments	39
10	Time	44
10.1	Purpose	44
10.2	Diagram	44
10.3	Comments	48
10.3.1	Real Time applications	48
10.3.2	Against open-ended intervals	48
11	References	50

1 CDM-Telematics compiled wiki pages

Self-contained version with local images

1.1 Version

This document was generated on 2025-11-07 16:09:50 UTC

Con-
tents

Oper-
a-
tional
enti-
ties

Pur-
pose

##

Con-
tents

This
dia-
gram
con-
tains
the
main
classes
used
for
de-
scrib-
ing
oper-
a-
tions.
Their
scope
is not
nec-
essar-
ily
re-
stricted
to
the
TAF
TSI
scope:
for
in-
stance,
con-
tain-
ers
(as-
sets)
and
their
“freight
load”

Con-
tents

Pre-
sen-
ta-
tion

##

Con-
tents

The
left
part
(col-
ored
classes)
shows
the
DUL
(DOLCE+DnS

Ul-
tra-
lite)
con-
cepts
un-
der-
pin-
ning
the
model.

The
rest
rep-
re-
sents
the
tax-
on-
omy
that
is

spe-
cific

to
the
CDM-

TAF

on-⁵

tol-

ogy

Con- tents

Next
to
the
right
of
the
DUL
classes
are
the
classes
de-
scrib-
ing
our
do-
main
(oper-
a-
tions).
Their
names
should
sound
famil-
iar.

Con- tents

Then,
fur-
ther
right,
are
the
su-
per-
classes
(group-
ing
our
do-
main
classes).
They
will
mostly
be ig-
nored
by
users.
Details
are
pro-
vided
in
sub-
se-
quent
pages.

##

Con-
tents

##

About
“DOLCE

+

DnS

Ul-

tra-

lite”

(DUL)

##

Con-
tents

[DUL](#)

is an

“up-

per

on-

tol-

ogy”

defin-

ing

very

gen-

eral

con-

cepts

(phys-

ical

ob-

ject,

role,

de-

scrip-

tion...).

It is

suit-

able

for

de-

scrib-

ing

do-

mains

mix-

ing

as-

sets,

pro-

cesses,

and

all⁹

sorts

of

##

Con-
tents

End

users

can

safely

ig-

nore

this

up-

per

on-

tol-

ogy.

It is

how-

ever

use-

ful

for

those

who

wish

to

un-

der-

stand,

main-

tain,

or ex-

tend

the

CDM-

TAF

on-

tol-

ogy,

since

it

con-

tributes

to

sepa-

##

Con-
tents



##

Com-
ments

on

the

dia-

gram

###

GRAPHOL

con-

ven-

tions

##

Con-
tents

GRAPHOL

is
able
to
rep-
re-
sent
all
OWL2
ele-
ments
and
rela-
tion-
ships
graph-
i-
cally.
The
graphs
may
evoke
E/R
or
UML
dia-
grams,
but
there
are
sig-
nifi-
cant
dif-
fer-
ences
re-
sult-
ing¹²
from
the

##

Con-
tents

####

Classes

and

sub-

classes

Square

boxes

rep-

re-

sent

classes

(sets

of

indi-

vidu-

als).

Con-
tents

The
graph
 $A \rightarrow$
 B
means
“ A is
in-
cluded
in B ”.
When
 A
and
 B are
classes
(which
is the
case
here),
this
means
“ A is
a
sub-
class
of
 B ”.

##

Con- tents

Keep
in
mind
that
on-
tol-
ogy
classes
are
sets,
rather
than
types
(as
would
gen-
erally
be
the
case
in
object-
oriented
pro-
gram-
ming).
All
set
oper-
a-
tions,
such
as
inter-
sec-
tion,
union,
or
com-
ple-
ment,

##

Con-
tents

####

Dis-
joint
unions

A
black,
flat-
tened
hexagon
means

“dis-
joint
union
of”

what-
ever
classes

are
at-
tached

to
the
hexagon

by
dashed
lines.

##

Con-
tents

For
in-
stance,
Train,
Wagon,
Inter-
modal
Trans-
port
Unit,
Track,
and
Facil-
ity,
are
bun-
dled
into
an
anony-
mous
“dis-
joint
union”.
This
im-
plies
that
e.g. a
Train
can-
not
at
the
same
time
be a
Wagon,
etc.

##

Con- tents

This
anony-
mous,
dis-
joint
union
is a
sub-
class
of
“Op-
era-
tional
arti-
fact”
(did
you
no-
tice
the
direc-
tion
of
the
ar-
row?).
This
means
that
“op-
era-
tional
arti-
fact”
con-
tains
(or
in-
cludes)
the
mu-

2 Entity details

2.1 Purpose

Operational entities may all share time-independent properties (attributes), which are described here.

2.2 Diagram

For the time being, a user-defined “name” is proposed. It is not unique (one entity may have several names; different entities can have the same name as the “name” is a vernacular, not an identifier.



Figure 1: Operational entity details

2.3 Comments

The universally unique identifier is expected to be the entity IRI. IRIs are the foundations of the Semantic Web.


Note: one reason for introducing the “name” property is that annotation properties (such as `rdfs:label`) that would play this role are left out of OWL to JSON transformers (CIM or PIM to PSM).

Original page: [01a---Entity-details.md](#)

Train
run

Train
ser-
vic-
ing

Pur-
pose

Dia-
gram


Com-
ments
Original
page:
[02a---
Train-
servicing.md](#)

3 Operational Location

3.1 Purpose

Defining primary and subsidiary location codes. Locating fixed assets (tracks, facilities) at the places designated by these codes.

3.2 Diagram

3.3 Comments

3.3.1 Property “at operational location”

This property only applies to (= has range) spatially fixed assets such as station tracks, facilities (yards, depots, stations, terminals). There is no time information attached to it.

Please note that a yard *has* a location; a yard *is not* a location. This confusion often occurs because a yard happens to be a fixed thing. The confusion never occurs with moving things. In the present




Figure 2: operational location

ontology, fixed and moving things are treated homogeneously, so fixed things are not assimilated to their location.

3.3.2 So where are moving things located at time t ?

The answer lies in the `dul:Situation` class and its subclasses (generally called “... status” in the present ontology). `dul:Situation` is the class where time-dependent information is asserted.




Original page: [03---Operational-Location.md](#)

Train

Wagon

Pur-
pose

Dia-
gram

Com-
ments

4 Intermodal Transport Unit

4.1 Purpose

4.2 Diagram




Figure 3: ITU

4.3 Comments

Original page: 06---Intermodal-Transport-Unit.md

Cargo

Track

Pur-
pose

Dia-
gram



Com-
ments
Original
page:
[07---
Track.md](#)

5 Facility

5.1 Purpose

5.2 Diagram

5.3 Comments

Original page: [08---Facility.md](#)


Trac-
tion
role

Load
Role

Pur-
pose

Trac-
tion
role

Dia-
gram



Com-
ments
Original
page:
[10---](#)
[Load-](#)
[Role.md](#)

6 Operational roles

6.1 Purpose

Companies may play different operational roles at different times. Examples of operational roles are: Train operator, Cargo carrier, Lead RU, Lead carrier (the latter is encountered in the TAF TSI).

6.2 Diagram

Operational roles are currently listed as members of class `OperationalRole`. In the future, these may be replaced by a SKOS concept scheme provided by ERA.

The answer to “who plays the role” is outside this ontology. Such companies are by definition subclasses of `dul:Organization` and `regorg:RegisteredOrganization`.

`dul:Organization` tells that its members are able to play a role. `regorg:Organization` provides lots of useful attributes (legal name, jurisdiction, registration authority, etc.). The W3C [REGORG ontology](#) is based on the W3C ORG ontology and is recommended for use by the EC (see [this ontology collection item](#) and [this announcement page](#) from the Interoperable Europe Portal).




Figure 4: Facility

6.3 Comments

6.3.1 No dedicated class for organizations - just a blank node

We simply use a “blank node” (a class without a name) that is the intersection (“and”) of `dul:Organization` and `rerorg:RegisteredOrganization`.

What the diagram expresses (and what OWL2 says) is that anything that plays an operational role in the context of telematics is, by definition, both a `dul:Organization` (hence not a person) and a `rerorg:Organization` (with some or all of the foreseen properties provided by RERORG).

Original page: [11---Operational-roles.md](#)




Figure 5: operational roles

 Ver-
 sioned
 de-
 scrip-
 tion
 #
 Jour-
 ney
 ##
 Pur-
 pose
 ##
 Dia-
 gram

Ver-
sioned
de-
scrip-
tion

Com-
ments
Original
page:
[12a--
Journey.md](#)

7 Journey Schedule

7.1 Purpose

Represent the train journey (planned or executed) and possibly the train path in one uniform way.

The Journey may be composed of a sequence of journey sections, each having an origin and a destination (operational locations). Obviously, the destination of section N is expected to also be the origin of section N+1, and times must be increasing (except when midnight is passed).

7.2 Diagram

7.3 Comments

7.3.1 Nested Lists

Since any Journey section is a Journey schedule, it can be in turn broken down. This is convenient, as it allows to insert pass-through locations at a later stage when deemed convenient.

7.3.2 Not a speed profile

Locations documented by Journey Schedule are, for the time being, only Operational Locations. The Journey Schedule is not suitable for representing a speed profile with temporary speed restrictions for instance.

7.3.3 Data consistency

It is a user responsibility to check the order and consistency of journey sections. The ontology will preserve the sequence (using a List ontology, because OWL2 has no primitive concepts for order),




Figure 6: Journey Schedule

but whether the sequence *makes sense* must be checked by other means, such as SWRL rules, or queries (possibly embedded in SHACL), etc.

7.3.4 List ontology

The List ontology used here is different from the one used in IfcOwl (the ontology version of Industry Foundation Classes). Later on, one of the two ontologies may be eliminated in favor of the other.

Original page: [12b---Journey-Schedule.md](#)

Jour-
ney
Sched-
ule
prop-
erties

Oper-
a-
tional
State

Pur-
pose

#

Jour-
ney
Sched-
ule
prop-
erties

Describe
time-
dependent

at-
tributes
(prop-
er-
ties)

that
are
rele-
vant
to

oper-
a-
tions:

train
run
state

(“where
is my
train?”),

train
state

(“what
is the
train

com-
posi-
tion?”),

load
state

(“on
which

³⁰
wagon

is my
con-

Jour-
ney
Sched-
ule
prop-
erties

Dia-
gram
“Operational
state”
is the
top-
most
class,
on
which
the
time-
dependency
hinges.
Time
can
be
ex-
pressed
as an
in-
stant
or as
an
inter-
val.

Jour-
ney
Sched-
ule
prop-
erties

Time
in-
stant
sug-
gests
that
the
state
is
actu-
ally a
state
change,
valid
until
the
next,
or a
spot
mea-
sure-
ment
(“is
my
train
at
rest?”).

Jour-
ney
Sched-
ule
prop-
erties

Time
inter-
val
sug-
gests
that
the
state
ex-
tends
over
the
inter-
val,
or
maybe
the
state
change.



Com-
ments

Re-
stric-
tion
on
prop-
erty
dul:hasTimeInterval

Jour-
ney
Sched-
ule
prop-
erties

In
our
con-
text
we
use
the
pre-
de-
fined
prop-
erty
dul:hasTimeInterval
but
re-
strict
its
range
to
time:Interval
(im-
proper
time
inter-
val in
the
W3C
Time
on-
tol-
ogy)
when
it ap-
plies
to an³⁴
Oper-
a-

Jour-
ney
Sched-
ule
prop-
erties

Am-
bigu-
ity to
be
lifted
The
ambi-
guity
state

/
state
change
should
be re-
moved
at a
later
stage.

Proper
vs. de-
gen-
erate
inter-
vals

Jour-
ney
Sched-
ule
prop-
erties

All
time-
related
classes
are
bor-
rowed
from
the
W3C
Time
on-
tol-
ogy.

#

Jour-
ney
Sched-
ule
prop-
erties

Time
inter-
vals
can
be
bounded,

or
open-
ended,
or de-
gen-
erate

(start
in-
stant
=

end
in-
stant).

Again,
it

would
be

use-
ful to

clar-
ify

when

to

use

an in-
stant

and

when

to³⁷

use a

de-

Jour-
ney
Sched-
ule
prop-
erties

Original
page:
[13---
Operational-
State.md](#)

8 Train run state

8.1 Purpose

8.2 Diagram

8.3 Comments


Original page: [13a---Train-run-state.md](#)

Train
state

Load
State

Pur-
pose

Dia-
gram



Com-
ments

Train
state

Original
page:
[13c---](#)
[Load-](#)
[State.md](#)

9 Message

9.1 Purpose

9.2 Diagram

9.3 Comments

Original page: [14--Message.md](#)

Im-
age

RID
codes

Pur-
pose

Im-
age

Add
the
infor-
ma-
tion
about
dan-
ger-
ous
goods
and
the
re-
sult-
ing
haz-
ard
classes,
as
per
RID.

 Im-
 age

 Information
 is de-
 fined
 in
 chap-
 ter
 3.2 of
 the
 RID,
 Table
 A,
 columns
 1 and
 3a,
 re-
 spec-
 tively.
 ##
 Dia-
 gram

Im-
age

The
infor-
ma-
tion
re-
lates
to
the
dan-
ger-
ous
sub-
stance,
but
shall
be af-
fixed
on
the
ITU
or
the
wagon,
as
per
chap-
ter 5
of
RID.

Im-
age

Accordingly,

two
prop-
erties
are
pro-
vided,
the
do-
main
of
which
is the
union
of
Wagon
and
ITU.

This
union
is a
dis-
joint
one,
since
classes
Wagon
and
ITU
were
de-
clared
dis-
joint
(no
wagon
is an
ITU,
no
ITU
is a

10 Time

10.1 Purpose

Propose “time entities” to be consumed by time-dependent entities (such as “train speed” or “custom clearance status”).

The time entities are derived from the [W3C time ontology](#) and aligned with the DUL TimeInterval concept.

10.2 Diagram

An operational time is either an instant or an interval: these are disjoint classes, as the black flattened hexagon indicates in the diagram. The distinction between instant and interval rests on semantics, not on timestamp values: an interval has a beginning and an end (whether or not the values are known), while an instant has a beginning (instant) and an end (instant). These may happen to coincide, i.e. have equal timestamp values.

The GRAPHOL diagram expresses that each interval is expected to have exactly one beginning and one end, by means of OWL universal restrictions (“forAll”), and that the beginning or end are of type “Operational instant”.

Note: if the data provide two beginnings for an interval, the logical consequence is that the beginnings B1 and B2 are the same individual (:B1 owl:sameAs :B2) and any OWL reasoner will infer that and inform the user accordingly. Then the user software may want to compare the respective timestamp values (OWL2 ignores them, so use SPARQL or code). If timestamps of B1 and B2 fail the test for equality (say, difference is more than one millisecond? which is context-dependent), then the user has detected an inconsistency and should consider resolving it. In a world of imperfect data, wrong data should not break the database. Ontologies, being robust against such data errors, are a




Figure 7: Train run state





Figure 8: Message

suitable tool to represent them, but the onus of error detection is partly on the user: OWL2 has no numeric operators.



The bottom part (Temporal role class and individuals) add meaning to time-dependent situations, i.e. whether they relate to a planned, revised, forecast, actual, etc. situation (the DUL term) or state (our used term).

10.3 Comments

10.3.1 Real Time applications

The time representation is conceptually compatible with the [UML MARTE profile](#), so it can serve as a basis for a demanding real-time application. The main missing concept is that of Clock: we currently assume all clocks to be synchronized, so we ignore them altogether (there is no need for a Clock class).

We do not distinguish intervals from “proper intervals” (length > 0) in the sense of the W3C Time ontology: as no assumptions are made regarding the timestamps, it may well happen that the beginning and the end of an interval are distinct (in actual time), but have the same timestamp value. Calling it a “proper interval” would then be a semantic error.

10.3.2 Against open-ended intervals

Leaving out the beginning or end of an interval *may* be interpreted as the interval being “open-ended”. We would like to sternly warn against such convention, since it breaks the monotonicity of time reasoning. Example: if a fire extinguisher has a usability interval but the end is missing from the available data, it shall not be understood as “usable forever”, as this conclusion would immediately be falsified by the provision, at some stage, of the missing information.

In the context of railway applications, nothing is actually open-ended in time, and most data may be made available with some delay, so the “open ended” interpretation of any interval with missing data would be a gross mistake.

Original page: [90---Time.md](#)

Varia

De-
pen-
den-
cies

#

Varia

##

Gen-

eral

and

up-

per

on-

tolo-

gies

###

W3C

Time

on-

tol-

ogy

###

SOSA/SSN

###

QUDT

###

DOLCE+DnS

Ul-

tra-

lite

###

RE-

GORG,

ORG

##

Se-

man-

tic

RSM

on-

tolo-

gies

Varia

Rolling
stock
on-
tolo-
gies

Con-
sist

Ty-
pol-
ogy

ERA
Con-
cept
Schemes
Original
page:
[97---
Dependencies.md](#)

11 References

...

Original page: [99---References.md](#)