ptz_camera_PT30XNDI_GY_WH _v1_0_0_0.py

Global Scripter Module Communication Sheet

Revision: 10/14/2019

This document provides additional assistance with wiring your Extron IP Link Pro Control Processor to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific IP Link Pro Control Processor or the documentation supplied by the manufacturer of the controlled device.

For more information on using Global Scripter Modules, refer to the "Guide to Using Scripter Modules" document.

Device Specifications

Device Type: Camera
Manufacturer: PTZ Optics
Firmware Version: N/A

Model(s): PT30X-NDI-GY, PT30X-NDI-WH

Tested on the Following Software and Firmware Versions

IP Link Pro Control Processor Firmware	Global Scripter Version
3.04.0001-b002	2.3.1

Version History

Module Version	Date	Notes
1_0_0_0	10/14/2019	Initial Version

Revision: 10/14/2019

Module Notes

- Unidirectional variable must be set to 'True' if status is not required. Default value is 'False'. Example: InterfaceName.Unidirectional = 'True'
- connectionCounter variable must be set to the number of queries that will be sent to the device before displaying 'Disconnected' if no response is received. Default value is 15.

 Example: InterfaceName.connectionCounter = 5
- DeviceID variable must be set accordingly. Default value is '1'. DeviceID ranges from 1' to '7, and Broadcast. If Device ID is set to 'Broadcast', status is unavailable.
 Example: InterfaceName.DeviceID = '1'

Supported Classes and Examples

Revision: 10/14/2019

Control Commands

Format with Qualifier:

InterfaceName.Set(Command, Value, {'Qualifier Key': 'Qualifier Value'})

Format with Qualifier:

InterfaceName.Set(Command, Value)

Command	Value	Value	Value
AutoExposure	'Full Auto'	'Manual'	'Shutter Priority'
·	'Iris Priority'	'Bright'	•
# AutoExposure exampl InterfaceName.Set('Au	e ·		•
Command	Value	Value	
AutoFocus	'On'	'Off'	
<pre># AutoFocus example InterfaceName.Set('Au</pre>	toFocus'. 'On')		
Command	Value	Value	
Backlight	'On'	'Off'	
<pre># Backlight example InterfaceName.Set('Ba</pre>	cklight', 'On')		
Command	Value	Value	Value
Focus	'Far'	'Near'	'Stop'
Qualifier Key	Qualifier Value		
'Focus Speed'	'0' – '7'		
# Focus example		- 11 12122	
InterfaceName.Set('Fo		Speed': '0'})	
Command	Value		
Home	None		
# Home example InterfaceName.Set('Ho			
Command	Value	Value	Value
Iris	'Up'	'Down'	'Reset'
<pre># Iris example InterfaceName.Set('Ir</pre>	is', 'Up')		
Command	Value	Value	Value
PanTilt	'Up'	'Down'	'Left'
	'Right'	'Up Left'	'Up Right'
	'Down Left'	'Down Right'	'Stop'
Qualifier Key	Qualifier Value		
'Pan Speed'	'0' – '24'		
Qualifier Key	Qualifier Value		
'Tilt Speed'	'0' – '20'		
<pre># PanTilt example InterfaceName.Set('Pa</pre>		Speed': '0', 'Tilt Speed	': '0'})
Command	Value		
PanTiltReset	None		
<pre># PanTiltReset exampl InterfaceName.Set('Pa</pre>			
Command	Value	Value	
Power	'On'	'Off'	
<pre># Power example InterfaceName.Set('Po</pre>	wer', 'On')		

Revision: 10/14/2019

Command	Value			
PresetRecall	'0' – '127'			
	<pre># PresetRecall example InterfaceName.Set('PresetRecall', '0')</pre>			
Command	Value			
PresetReset	'0' – '127'			
# PresetReset example InterfaceName.Set('PresetReset', '0')				
Command	Value			
PresetSave	'0' – '127'			
<pre># PresetSave example InterfaceName.Set('PresetSave', '0')</pre>				
Command	Value	Value	Value	
Zoom	'Tele'	'Wide'	'Stop'	
Qualifier Key	Qualifier Value			
'Zoom Speed'	'0' – '7'			
<pre># Zoom example InterfaceName.Set('Zoom', 'Tele', {'Zoom Speed': '0'})</pre>				

Revision: 10/14/2019

Status Available

For all commands, call Update to receive the latest status. ConnectionStatus does not support the Update function and is triggered by the device providing a successful response to other Update function calls.

Format with Qualifier:

InterfaceName.Update(Command, {'Qualifier Key': 'Qualifier Value'})
 Value = InterfaceName.ReadStatus(Command, {'Qualifier Key': 'Qualifier Value'})
 InterfaceName.SubscribeStatus(Command, {'Qualifier Key': 'Qualifier Value'},
FeedbackHandler)

FeedbackHandler will be called only when the specified qualifier gets a new status.

Format without Qualifier:

InterfaceName.Update(Command)
Value = InterfaceName.ReadStatus(Command)
InterfaceName.SubscribeStatus(Command, None, FeedbackHandler)
FeedbackHandler will be called when any qualifier gets a new status.

Command	Value	Value	Value
AutoExposure	'Full Auto'	'Manual'	'Shutter Priority'
	'Iris Priority'	'Bright'	
# AutoExposure example InterfaceName.Update('AutoExposure') Value = InterfaceName.ReadStatus('AutoExposure') InterfaceName.SubscribeStatus('AutoExposure', None, FeedbackHandler)			
Command	Value	Value	
AutoFocus	'On'	'Off'	
# AutoFocus example InterfaceName.Update('AutoFocus') Value = InterfaceName.ReadStatus('AutoFocus') InterfaceName.SubscribeStatus('AutoFocus', None, FeedbackHandler)			
Command	Value	Value	
Backlight	'On'	'Off'	
# Backlight example InterfaceName.Update('Backlight') Value = InterfaceName.ReadStatus('Backlight') InterfaceName.SubscribeStatus('Backlight', None, FeedbackHandler)			
Command	Value	Value	
ConnectionStatus	'Connected'	'Disconnected'	
# ConnectionStatus example Value = InterfaceName.ReadStatus('ConnectionStatus') InterfaceName.SubscribeStatus('ConnectionStatus', None, FeedbackHandler)			
Command	Value	Value	Value
Power	'On'	'Off'	'Internal Power Circuit Error'
# Power example InterfaceName.Update('Power') Value = InterfaceName.ReadStatus('Power') InterfaceName.SubscribeStatus('Power', None, FeedbackHandler)			

Revision: 10/14/2019

Cable and Adapter Requirements


Captive Screw to DIN-8 VISCA Serial Cable

Notes for the Device


Serial communication

Port Type:RS-232, RS-485Parity:NoneBaud Rate:9600Stop Bits:OneData Bits:8Flow Control:None

Pin Assignments Diagram



Signal	Main Cable	Pin	Signal
TxD		5	RxD
RxD		3	TxD
GND		4	GND



ptz_camera_PT30XNDI_GY_WH _v1_0_0_0.py

Global Scripter Module Communication Sheet

Revision: 10/14/2019

Network communication

When configuring the Ethernet module, be sure device settings match those of the Global Scripter ethernet interface.

Port Type: Ethernet

Default Port: 5678

Logon Credentials

Supported:

Multi-Connection Undetermined

Capabilities:

Port Changeability: Yes

Ethernet Module Configuration Description

No

Please refer to user manual for settings and changes to the network communication

Notes for the Device

Page 7 of 9 Rev. B1

Revision: 10/14/2019

Appendix A. Set Commands

Auto Exposure Bright	\x81\x01\x049\x0D\xFF
Auto Exposure Full Auto	\x81\x01\x049\x00\xFF
Auto Exposure Iris Priority	\x81\x01\x049\x0B\xFF
Auto Exposure Manual	\x81\x01\x049\x03\xFF
Auto Exposure Shutter Priority	\x81\x01\x049\x0A\xFF
Auto Focus Off	\x81\x01\x048\x03\xFF
Auto Focus On	\x81\x01\x048\x02\xFF
Backlight Off	\x81\x01\x043\x03\xFF
Backlight On	\x81\x01\x043\x02\xFF
Focus Far Focus Speed 0	\x81\x01\x04\x08 \xFF
Focus Far Focus Speed 7	\x81\x01\x04\x08'\xFF
Focus Near Focus Speed 0	\x81\x01\x04\x080\xFF
Focus Near Focus Speed 7	\x81\x01\x04\x087\xFF
Focus Stop Focus Speed 0	\x81\x01\x04\x08\x00\xFF
Focus Stop Focus Speed 7	\x81\x01\x04\x08\x00\xFF
Home None	\x81\x01\x06\x04\xFF
Iris Down	\x81\x01\x04\x0B\x03\xFF
Iris Reset	\x81\x01\x04\x0B\x00\xFF
Iris Up	\x81\x01\x04\x0B\x02\xFF
Pan Tilt Down Left Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x01\x02\xFF
Pan Tilt Down Left Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x01\x02\xFF
Pan Tilt Down Left Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x01\x02\xFF
Pan Tilt Down Left Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x01\x02\xFF
Pan Tilt Down Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x03\x02\xFF
Pan Tilt Down Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x03\x02\xFF
Pan Tilt Down Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x03\x02\xFF
Pan Tilt Down Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x03\x02\xFF
Pan Tilt Down Right Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x02\x02\xFF
Pan Tilt Down Right Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x02\x02\xFF
Pan Tilt Down Right Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x02\x02\xFF
Pan Tilt Down Right Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x02\x02\xFF
Pan Tilt Left Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x01\x03\xFF
Pan Tilt Left Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x01\x03\xFF
Pan Tilt Left Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x01\x03\xFF
Pan Tilt Left Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x01\x03\xFF
Pan Tilt Reset None	\x81\x01\x06\x05\xFF
Pan Tilt Right Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x02\x03\xFF
Pan Tilt Right Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x02\x03\xFF
Pan Tilt Right Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x02\x03\xFF
Pan Tilt Right Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x02\x03\xFF
Pan Tilt Stop Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x03\x03\xFF
Pan Tilt Stop Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x03\x03\xFF

Revision: 10/14/2019

	1
Pan Tilt Stop Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x03\x0F
Pan Tilt Stop Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x03\x03\xFF
Pan Tilt Up Left Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x01\x01\xFF
Pan Tilt Up Left Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x01\x01\xFF
Pan Tilt Up Left Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x01\x01\xFF
Pan Tilt Up Left Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x01\x01\xFF
Pan Tilt Up Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x03\x01\xFF
Pan Tilt Up Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x03\x01\xFF
Pan Tilt Up Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x03\x01\xFF
Pan Tilt Up Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x03\x01\xFF
Pan Tilt Up Right Pan Speed 0 Tilt Speed 0	\x81\x01\x06\x01\x00\x00\x02\x01\xFF
Pan Tilt Up Right Pan Speed 0 Tilt Speed 20	\x81\x01\x06\x01\x00\x14\x02\x01\xFF
Pan Tilt Up Right Pan Speed 24 Tilt Speed 0	\x81\x01\x06\x01\x18\x00\x02\x01\xFF
Pan Tilt Up Right Pan Speed 24 Tilt Speed 20	\x81\x01\x06\x01\x18\x14\x02\x01\xFF
Power Off	\x81\x01\x04\x00\x03\xFF
Power On	\x81\x01\x04\x00\x02\xFF
Preset Recall 0	\x81\x01\x04?\x02\x00\xFF
Preset Recall 127	\x81\x01\x04?\x02\x7F\xFF
Preset Reset 0	\x81\x01\x04?\x00\x00\xFF
Preset Reset 127	\x81\x01\x04?\x00\x7F\xFF
Preset Save 0	\x81\x01\x04?\x01\x00\xFF
Preset Save 127	\x81\x01\x04?\x01\x7F\xFF
Zoom Stop Zoom Speed 0	\x81\x01\x04\x07\x00\xFF
Zoom Stop Zoom Speed 7	\x81\x01\x04\x07\x00\xFF
Zoom Tele Zoom Speed 0	\x81\x01\x04\x07 \xFF
Zoom Tele Zoom Speed 7	\x81\x01\x04\x07'\xFF
Zoom Wide Zoom Speed 0	\x81\x01\x04\x070\xFF
Zoom Wide Zoom Speed 7	\x81\x01\x04\x077\xFF

Appendix B. Update Commands

Auto Exposure	\x81\x09\x049\xFF
Auto Focus	\x81\x09\x048\xFF
Backlight	\x81\x09\x043\xFF
Power	\x81\x09\x04\x00\xFF