The “Optional: Try it with the data” activity

Syntax

Author: Rihab Dahab



[11/11/26]
Copyright © 2026 University of Manchester. Cathie Marsh Institute, UK Data Service.
Version No. 1
CC BY-NC-SA

Table of contents

The syntaxes in SPSS, R and Stata of how to: 3
The syntaxes in SPSS, R and Stata of how to: 4

The syntaxes in SPSS, R and Stata of how to:

1. Create a variable identifying individuals aged 11–15.
2. Use this to calculate the number of children aged 11–15 in each household.

SPSS

```
#Use the individual-level data file to identify individuals aged 11–15.

COMPUTE number_child_11_15 = (AGE_CAT = 3).



#Group individuals by HHID and create the number of children aged 11–15 in each household.

AGGREGATE

 /OUTFILE=* MODE=ADDVARIABLES

 /BREAK=HHID

 /total_number_child_11_15 = SUM(number_child_11_15).
```

R

```
#Load the dplyr package from R library for data manipulation.

library(dplyr)



#Group by HHID to count children, attach the new variable to all individuals in the household, and ungroup data.

Individual_level <- Individual_level %>%

 group_by(HHID) %>%
```

```
 mutate(total_number_child_11_15 =
sum(AGE_CAT == 3)) %>%

 ungroup()
```

Stata

```
# Create the variable number_child_11_15.

gen number_child_11_15 = (AGE_CAT ==
3)



# calculate the number of children aged 11–
15 in each household.

bysort HHID: egen
total_number_child_11_15 =
total(number_child_11_15)
```

The syntaxes in SPSS, R and Stata of how to:

3. Add this new household-level variable to the household-level dataset.
4. Merge the household-level dataset with the individual-level dataset using household ID, so that each individual record includes the household-level information.

SPSS

```
# Sort both files by HHID first.

SORT CASES BY HHID.

DATASET ACTIVATE Household_level.

SORT CASES BY HHID.



# Merge household variables into individual
file.

MATCH FILES
```

```
/FILE=Individual_level

/TABLE=Household_level

/BY HHID.

EXECUTE.
```

R

```
#Load the dplyr package from R library for data manipulation.

library(dplyr)



# Merge the two datafiles using the key variable HHID.

merged_file <- Individual_level %>%

 left_join(Household_level, by = "HHID")
```

Stata

```
# Load individual data.

use Individual_level, clear



# Merge household data (one household to many individuals).

merge 1:m HHID using Household_level
```

www.ukdataservice.ac.uk

help@ukdataservice.ac.uk

+44 (0) 1206 872143

We are supported by the Universities of Essex, Manchester, Edinburgh, University College London and Jisc. We are funded by UKRI through the Economic and Social Research Council.