

# Fuzix for the Pico Computer

Unix and BBC BASIC on the Pico Computer 2 and 3

Release v0.17 — August 2026

## Contents

|          |                                                          |           |
|----------|----------------------------------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>                                      | <b>4</b>  |
| 1.1      | New in v0.16 . . . . .                                   | 4         |
| 1.2      | New in v0.15 . . . . .                                   | 5         |
| 1.3      | New in v0.14 . . . . .                                   | 6         |
| 1.4      | New in v0.13 . . . . .                                   | 7         |
| 1.5      | New in v0.12 . . . . .                                   | 7         |
| 1.6      | New in v0.11 . . . . .                                   | 8         |
| 1.7      | New in v0.10 . . . . .                                   | 9         |
| 1.8      | New in v0.9 . . . . .                                    | 11        |
| 1.9      | New in v0.8 . . . . .                                    | 12        |
| 1.10     | New in v0.7 . . . . .                                    | 12        |
| 1.11     | New in v0.6 . . . . .                                    | 13        |
| 1.12     | New in v0.5 . . . . .                                    | 13        |
| <b>2</b> | <b>Installing Fuzix</b>                                  | <b>15</b> |
| 2.1      | Flashing the kernel . . . . .                            | 15        |
| 2.2      | Writing the SD card . . . . .                            | 15        |
| 2.3      | First boot . . . . .                                     | 16        |
| 2.4      | Setting the clock . . . . .                              | 16        |
| 2.5      | Command history and line editing . . . . .               | 17        |
| 2.6      | Escape routes . . . . .                                  | 17        |
| <b>3</b> | <b>The consoles</b>                                      | <b>18</b> |
| <b>4</b> | <b>BBC BASIC</b>                                         | <b>19</b> |
| 4.1      | Loading programs, including plain text . . . . .         | 19        |
| 4.2      | Graphics . . . . .                                       | 19        |
| 4.3      | Sound . . . . .                                          | 20        |
| 4.4      | ADVAL: joystick, analogue inputs, sound queues . . . . . | 20        |
| 4.5      | Serial port . . . . .                                    | 21        |
| 4.6      | Star commands and the shell . . . . .                    | 21        |
| 4.7      | The inline assembler . . . . .                           | 21        |
| 4.8      | Differences from the original BBC Micro . . . . .        | 21        |

|           |                                                                                       |           |
|-----------|---------------------------------------------------------------------------------------|-----------|
| <b>5</b>  | <b>The C compiler</b>                                                                 | <b>23</b> |
| 5.1       | What it compiles . . . . .                                                            | 23        |
| 5.2       | Headers and the runtime library . . . . .                                             | 23        |
| 5.3       | Limitations . . . . .                                                                 | 24        |
| 5.4       | Speed . . . . .                                                                       | 24        |
| <b>6</b>  | <b>MMBasic: the mmbc translator</b>                                                   | <b>26</b> |
| 6.1       | The three commands . . . . .                                                          | 26        |
| 6.2       | A first program . . . . .                                                             | 26        |
| 6.3       | A worked example: the KnivD benchmark . . . . .                                       | 27        |
| 6.4       | A worked example: something numerical . . . . .                                       | 28        |
| 6.5       | What the translation looks like . . . . .                                             | 28        |
| 6.6       | Strings, arrays and functions . . . . .                                               | 28        |
| 6.7       | Errors . . . . .                                                                      | 29        |
| 6.8       | Graphics . . . . .                                                                    | 29        |
| 6.9       | The sixteen colours: MAP . . . . .                                                    | 30        |
| 6.10      | Text on the picture: TEXT and FONT . . . . .                                          | 31        |
| 6.11      | Your own font: DefineFont . . . . .                                                   | 33        |
| 6.12      | The glyphs themselves: MM.INFO(FONT ADDRESS) and PEEK . . . . .                       | 33        |
| 6.13      | Animation: FRAMEBUFFER . . . . .                                                      | 35        |
| 6.14      | Running another program: SYSTEM, SAVE IMAGE, LOAD IMAGE, LOAD JPG, LOAD PNG . . . . . | 37        |
| 6.15      | Music: PLAY MP3, PLAY WAV, PLAY FLAC, PLAY SOUND, PLAY TONE, PLAY MODFILE . . . . .   | 38        |
| 6.16      | Pins: SETPIN and PIN . . . . .                                                        | 40        |
| 6.17      | Pin interrupts . . . . .                                                              | 43        |
| 6.18      | PWM . . . . .                                                                         | 44        |
| 6.19      | SERVO . . . . .                                                                       | 44        |
| 6.20      | SETTICK — periodic timers . . . . .                                                   | 45        |
| 6.21      | ON KEY — the console . . . . .                                                        | 45        |
| 6.22      | KEYDOWN — which keys are <i>held</i> . . . . .                                        | 46        |
| 6.23      | Asking the machine about itself: MM.INFO . . . . .                                    | 47        |
| 6.24      | Pin names: GP8 . . . . .                                                              | 48        |
| 6.25      | Timers and the deliberate divergence . . . . .                                        | 48        |
| 6.26      | Practical notes . . . . .                                                             | 49        |
| 6.27      | A worked example: a barometric station . . . . .                                      | 49        |
| 6.28      | Making a big program fit — and run fast . . . . .                                     | 52        |
| <b>7</b>  | <b>mmedit: MMBasic's editor</b>                                                       | <b>54</b> |
| 7.1       | The other editor: vi . . . . .                                                        | 54        |
| <b>8</b>  | <b>The FAT partition and the fat command</b>                                          | <b>56</b> |
| <b>9</b>  | <b>Moving files over the serial port</b>                                              | <b>57</b> |
| 9.1       | Sending a file to the board . . . . .                                                 | 57        |
| 9.2       | Fetching a file from the board . . . . .                                              | 57        |
| 9.3       | Programs to use . . . . .                                                             | 57        |
| <b>10</b> | <b>Commands at the # prompt</b>                                                       | <b>59</b> |
| 10.1      | The machine itself: picoct1 . . . . .                                                 | 59        |
| 10.2      | Pictures . . . . .                                                                    | 59        |

|           |                                             |           |
|-----------|---------------------------------------------|-----------|
| 10.3      | Sound . . . . .                             | 60        |
| 10.4      | Languages and the toolchain . . . . .       | 61        |
| 10.5      | Editors . . . . .                           | 61        |
| 10.6      | Getting files on and off . . . . .          | 61        |
| 10.7      | The clock, and housekeeping . . . . .       | 61        |
| 10.8      | Where this is not 1979 . . . . .            | 62        |
| 10.9      | What is not here . . . . .                  | 63        |
| <b>11</b> | <b>The filesystem and included software</b> | <b>63</b> |
| 11.1      | Layout . . . . .                            | 63        |
| 11.2      | Applications . . . . .                      | 63        |
| 11.3      | Text processing . . . . .                   | 64        |
| <b>12</b> | <b>Appendix A: pin usage</b>                | <b>65</b> |
| <b>13</b> | <b>Appendix B: boot options</b>             | <b>66</b> |
| <b>14</b> | <b>Appendix C: MMBasic coverage</b>         | <b>67</b> |
| 14.1      | Statements . . . . .                        | 67        |
| 14.2      | Functions . . . . .                         | 67        |
| 14.3      | MATH() sub-functions . . . . .              | 68        |
| 14.4      | MATH sub-commands . . . . .                 | 68        |
| 14.5      | Types and structure . . . . .               | 69        |
| 14.6      | Errors, and surviving them . . . . .        | 70        |
| 14.7      | Not covered . . . . .                       | 73        |

# 1 Introduction

Fuzix is Alan Cox’s compact V7-style Unix. This port makes it a third first-class environment for the Pico Computer, beside MMBasic and MicroPython: a genuine multi-tasking Unix booting from SD card, with a full set of classic utilities — and R. T. Russell’s BBC BASIC as its flagship application, complete with BBC graphics modes on the HDMI display, the four-channel BBC sound system on the audio DAC, joystick and analogue inputs, and a spare serial port.

It also compiles on its own. `cc` is a complete C89 toolchain running on the hardware — not a cross-compiler — and it generates native ARM code, so the machine builds its own programs, at its own speed, with no PC involved. `mmbc` puts MMBasic in front of it: an MMBasic program translates to C, compiles, and runs as a native program several times faster than the interpreter it was written for.

One kernel image serves both machines. At boot it probes GP27 for the DS3231’s 32 kHz clock (the same test MMBasic and MicroPython use): present means Pico Computer 3, absent means Pico Computer 2. The practical difference is the SD card wiring, handled automatically; the boot banner names the detected board.

Headline specification as configured here:

- CPU at 375 MHz (the XGA-capable clock, as MMBasic uses)
- 340 KB of program RAM managed as 4 KB pages, with the 8 MB PSRAM behind it — up to 64 concurrent processes, and a single process may have about 292 KB of it. A swapped-out process is a PSRAM allocation the size of the process, not a slot on a device, so nothing is reserved for one that does not exist
- Programs get their heap from the PSRAM too, so a BASIC array or a C `malloc` is limited by the 8 MB rather than by the process
- Root filesystem on SD card; the on-board NAND flash holds a recovery system
- 80×40 colour ANSI console on HDMI, mirrored to the USB-C serial port, with USB keyboard support (six layouts)
- Pre-emptive multitasking: a runaway program can always be stopped from the keyboard
- A self-hosted C89 compiler generating native ARM code, and an MMBasic translator in front of it — both run on the machine itself
- MMBasic’s own full-screen editor, `mmedit`, so BASIC is written, translated, compiled and run without leaving the machine

## 1.1 New in v0.16

Porting other people’s MMBasic programs, and the things that stopped it.

**PLAY WAV and PLAY FLAC**, beside **PLAY MP3**. One statement each with a different decoder behind it, and **PLAY STOP** reaches all three the same way. See [Music](#).

**KEYDOWN()** — which keys are *held*, up to six at once, rather than which key was typed. A game needs this and **INKEY\$** structurally cannot give it: a character stream has no way to say “up and fire together”. The USB boot report already carried exactly the six codes MMBasic exposes; nothing outside the kernel could ask for them. See [KEYDOWN](#).

**Pin names.** **SETPIN GP4**, **DIN** and **PIN(GP4)** now mean what they say. This closes a trap as much as it adds a convenience: without it, **GP4** in a program that had not declared it became an implied variable worth zero, so **PIN(GP4)** quietly read **GP0**. See [Pin names](#).

**MM.INFO()** answers seventeen things rather than three — the program's own path, whether a file or directory exists and how big it is, the current font's cell, the text cursor, **OPTION BASE**, and what machine this is. **MM.INFO\$()** is the same function, as in MMBasic. See [Asking the machine about itself](#).

**MM.DEVICE\$** is now "Fuzix" and not "Fuzix on PC3". It names the firmware; the board moved to **MM.INFO(PLATFORM)**, which is MMBasic's own division of the two. A program testing **INSTR(MM.DEVICE\$, "PicoMite")** gets a clean no either way.

**CONST inside a SUB is local to it**, as MMBasic has always had it (**cmd\_const** sets **V\_LOCAL** when it is not at the top level). Every **CONST** used to go into the globals whatever scope it was written in, so two routines that each declared their own collided — and the error surfaced somewhere else entirely, as an unrelated variable of the same name "already declared as **STRING**". Shared library code declares constants inside routines constantly, so this blocked whole programs rather than single lines.

Two smaller things found while fixing that one, both of which had never been exercised by any test: a global **CONST** and a **LOCAL** of the same name generated the same C name, and a program using **MM.CMDLINE\$** crashed on the board before its first statement.

## 1.2 New in v0.15

The machine can play a game, and everything in this release is something that had to be true before it could.

**BLIT, SPRITE and the flash slots.** **BLIT** copies a rectangle of screen anywhere, reads and writes the flash slots MMBasic keeps images in, and works against the off-screen framebuffer as well as the display. On top of it sits the **SPRITE** family — load, show, move, hide, collision detection, transparency, and a two-axis **SPRITE SCROLL**. A rectangle now crosses into the kernel once rather than once per row, which is what makes a screenful of sprites affordable.

**SPRITE LOADPNG** builds a sprite straight from a PNG:

```
SPRITE LOADPNG [#]n, fname$ [,transparent] [,cutoff]
```

The decoding happens in another process and the sprite arrives down a pipe, so a program that loads twenty sprites still carries no decoder. **transparent** defaults to **0** and **cutoff** to **30**, both as in the reference, and the default is the point: **SPRITE SHOW** skips colour 0 because that is the sprite transparent colour's own default, so a PNG's see-through pixels become see-through sprite pixels with no arguments at all. Pass a different index to paint them instead, or a *negative* value to substitute that index for opaque black — which is how artwork whose black would vanish against a black background is kept visible.

**The synthesiser moved into the kernel.** **PLAY SOUND** and **PLAY TONE** used to be rendered by a separate program keeping a fifth of a second of audio queued ahead. That is fine for music and impossible for a game: a program changing pitch every 20 ms was heard a tenth of a second late, and the renderer and the game could not both fit in memory at once, so the machine spent its time swapping them past each other. The four voices are now rendered in the interrupt that feeds the DAC, exactly where MMBasic renders them, and a **PLAY SOUND** is heard in the next buffer the hardware asks for. **PLAY MODFILE** and **PLAY MODSAMPLE** play tracker modules.

**A program's own font.** **DefineFont** takes MMBasic's hex block and gives the program fonts 10 to 16, usable everywhere a built-in font is. The data is byte-compatible with MMBasic's, so a font

written for a PicoMite is pasted in and works.

**The compiler bug that made all of it fail.** picofrog froze the machine with no crash message, in native code and in bytecode alike. The compiler was emitting a stack frame of whatever size the locals added up to — 261 bytes in the function that moved the frog — and an odd frame leaves the interpreter’s stack pointer odd, so the next 64-bit store through a by-reference local wrote across an alignment boundary and took a fault the display mode hid. Frames are rounded now. It would have reached any program with enough locals and a `FLOAT` passed by reference, so it is worth knowing it was there.

**The keyboard.** AltGr types the third character on a key at last, the console and the BASIC `INKEY$` path share one decoder rather than two that had drifted, and the USB stack survives a keyboard being unplugged, replugged or reset mid-session instead of taking the machine down with it.

**Smaller things.** `cc prog.bas` translates and compiles in one command. `ELSE IF` written as two words translates, which is how MMBasic spells it. Stopping a program with `Ctrl-C` no longer leaves the terminal in the state the program set it to — which had been logging people out, because a shell reading a raw terminal sees an instant end of input and takes it for a hangup. `mmedit` colours `DefineFont`, `SPRITE`, `BLIT` and `FLASH` as the translatable keywords they became. Forty-six MMBasic example programs live in `/root/MMBasic` with a `README` saying what each one shows.

### 1.3 New in v0.14

The buses stopped being three different programs, and the display gained a layer.

**One implementation of the data arguments.** `I2C`, `SPI` and `ONEWIRE` all take their data the same way in MMBasic — a list of values, a string, a whole array, or a long string — because MMBasic writes that handling once and calls it from three places. Here it had been written twice, and the two copies had drifted apart: a write list never checked that its count matched, so `I2C2 WRITE a, 0, 3, 1, 2` sent a third byte off the stack; reading into a list of variables did not exist at all; neither array form was bounds checked; `SPI` reported `I2C2`’s error messages because it called `I2C2`’s helper; and the buffers held bytes, so `SPI OPEN speed, mode, 16` sent the low half of each word — and read twice as far as the buffer went, because the transfer counts units and not bytes. There is one implementation now and one set of rules, and `ONEWIRE` needed no argument handling of its own when it arrived, which is the point of doing it this way.

**LONGSTRING as bus data.** `SPI WRITE n, LONGSTRING a()` and the matching `READ`, on every bus. A BASIC string stops at 255 bytes and a 240-pixel RGB565 row is 480, so a panel row used to take two writes. It has to be spelled out, because a long string *is* an integer array: written `a()` it is a numeric array and sends one byte per eight-byte cell. That is MMBasic’s behaviour and it stays.

**ONEWIRE and TEMPR.** `ONEWIRE RESET`, `WRITE` and `READ`, with `MM.ONEWIRE`, and `TEMPR(pin)` and `TEMPR START` for a DS18B20. Bit banged in your own program’s time, which this machine can do because a pin is a register access rather than a system call. **TEMPR sleeps through the conversion** where MMBasic spins: three quarters of a second is a long time on a machine with other processes in it.

**FRAMEBUFFER LAYER and FRAMEBUFFER MERGE.** A second off-screen buffer that goes *over* the first, with one colour transparent, so the background is drawn once and only the thing on top is redrawn. This is MMBasic’s TFT model, so a program written for a PicoMite with a panel on it runs here

unchanged. In `MODE 2` the whole loop — clear the layer, draw, merge, wait for the frame — runs at 60 frames a second.

**MM.VER answers the release you are running.** It had said 0.10 since v0.10, through three releases that were not v0.10, because the number lived in a second place and only a comment asked for it to be kept in step. `relcheck.sh` compares the three places it is written down and the release cannot go out with them disagreeing.

The editor colours six more keywords correctly, `TEMPR START` and `LINE INPUT` among them: it could not see a command `MMBasic` spells as two words.

## 1.4 New in v0.13

Two releases in one. The machine gains the Unix tools you would expect to find on it, the C library gained something it turns out never to have had — and BASIC finished a category of `MMBasic` statements that had been half-done for several releases.

**BASIC.** The drawing statements are complete: `POLYGON` (convex or concave, with the even-odd rule `MMBasic` uses), `BEZIER`, and `FILL` for flood-filling a region. The pins gained `PORT` in both directions and `PULSE`. And the statements that reach *into* a value rather than replacing it are all there now: `LMID`, `BIT`, `BYTE`, `FLAG`, `FLAGS`, along with `POS` and `FLUSH`.

Two of those are worth a sentence each. **`PORT` changes every pin in a bank on the same clock edge** — the bits that differ are worked out first and posted as one masked store — which is the whole reason to use it for a bus rather than writing the pins one at a time. And **`PAUSE` now services interrupts while it waits**, as `MMBasic`'s does. It never did before, and a program that arms a `SETTICK` usually has a main loop of little but `PAUSE`, so the handler could go its whole life without running once.

**Unix.**

- **`awk`** — Lucent's one true `awk`, the maintained descendant of the V7 original. Associative arrays, user-defined functions, regular expressions, `getline`, pipes and `printf`, all of it. See [Text processing](#).
- **`sed`, `find`, `expr`, `seq`, `uname`, and `[`** — every one of these was **already being compiled** and simply never installed. `[` is the one that matters: `/bin/test` existed and `/bin/[` did not, so every bracket test in every shell script failed with `[: not found`.
- **`grep -q`, and `ls -t` and `ls -1`.**
- **The C library can print a fraction.** `printf("%f", x)` used to print the letter `f` — the conversion was behind a build option no target defined, and the function it called did not exist anywhere in the tree. `%e`, `%f` and `%g` now work, in `printf` and in `scanf`, and so do `%j` and `%z`. A bytecode program's `printf` gained `%e` and `%g` too, where before they printed themselves *and* misaligned every argument after them.
- **The flash disk is fifteen megabytes**, up from two. The kernel gets 1 MB of the chip and the disk takes the rest — and the chip is 16 MB, which the build had never been told. See [Appendix B](#).

## 1.5 New in v0.12

The theme is the outside world again, but reaching further out. v0.11 gave the machine pins it could drive; this one gives it buses, and a way to put its own text on something at the far end of one.

- **I2C2** works from BASIC, with MMBasic's option word and its OPEN timeout — see the I2C2 section for the two deliberate differences from a PicoMite. A BMP180 on GP38/GP39 reads through MMBasic's own reference program unchanged apart from the bus.
- **The RTC alarm** is armable and was re-tested properly. The v0.11 note that it worked was taken from a test that could not tell an alarm from the DS3231's 1 Hz square wave, and had in fact been measuring the square wave.
- **printf understands %lld and %llx.** It did not, silently, which made every &H constant zero in a program translated *on the board*.
- **SPI** on the header pins — see the SPI section. An ILI9341 driven from BASIC fills its 240×320 screen in 26 ms.
- **Every peripheral got faster.** `clk_peri` had been left on the USB PLL at 48 MHz whatever the system clock was doing, so SPI could not exceed 24 MHz, and the UART and SD card were on the same 48 MHz. It now follows `clk_sys`.
- **The built-in fonts can be read.** `MM.INFO(FONT ADDRESS n)` gives the address of a font's glyph data, and `PEEK` — which did not exist at all before — reads it. Together they let a program draw MMBasic's own text onto a display the firmware knows nothing about. Both spellings are MMBasic's. See the section on the glyphs, and the worked barometric station that uses them.

## 1.6 New in v0.11

This release is about the **outside world**. The machine could already draw, make a noise and compile its own BASIC; what it could not do was control anything. It can now — and the pin work is between one and two orders of magnitude faster than the way it used to be done, because it stopped being a system call.

- **Pins are owned, and come back.** `SETPIN` claims a pin from the kernel, and the claim is released — with the pin **reset to an input** — when your program ends, however it ends, including being killed or crashing. A program that dies driving a relay no longer leaves it driven. Claiming a pin another program holds is refused rather than quietly fought over, and only the I/O header can be claimed at all, so a BASIC program can no longer take a pin the SD card or the display is using.
- **A pin is now a register access, not a system call** — about ten nanoseconds against 1.5  $\mu$ s. That is what makes bit-banging a protocol from BASIC possible at all, and it is why the rest of this list could be built without adding kernel drivers for any of it.
- **Analogue in:** `SETPIN n`, `AIN` reads volts, `ARAW` the raw count, using MMBasic's own ten-sample sort-and-discard filter.
- **Pin interrupts:** `SETPIN n`, `INTH|INTL|INTB`, `handler`, with the handler an ordinary SUB.
- **SETTICK** — four periodic timers, with `PAUSE`, `RESUME` and catch-up that drops missed ticks rather than queueing them. Measured at 1999.98 ms for twenty 100 ms ticks.
- **ON KEY**, both forms — one that fires on any key and leaves it for `INKEY$`, one that claims a single key and eats it.
- **INKEY\$ works.** It never had, on this machine: the console's line editor was taking every keystroke before a program could see it, and nothing had exercised it hard enough to notice. A program reading keys now holds the terminal, and gives it back for `INPUT` and at exit.
- **PWM** and **SERVO**, with MMBasic's arithmetic and its frequency range — 50 Hz to 100 kHz verified on a scope, and servo positions from 0.8 ms to 2.2 ms.
- **PULLUP** and **PULLDOWN** on the input modes, and hysteresis on every input, as MMBasic does.
- **GP32**, the DS3231's alarm line, is readable. (Setting an alarm is not yet possible — see the



pin section.)

- `/dev/i2c` for C programs, sharing the QWIIC bus with the kernel's own clock.

Two things this exposed and fixed along the way: the compiler could be run twice at once and corrupt its own output, and its progress dots ignored redirection. Both are gone.

## 1.7 New in v0.10

This release fills in the MMBasic translator's two largest gaps — the rest of the drawing statements, and structures — and makes the whole machine faster.

- **BOX, RBOX, TRIANGLE and ARC translate.** With `CIRCLE`, `TEXT` and `MAP` already in, the PicoMite drawing set is now covered. Each primitive is a header of static C functions, one header per primitive, so a compiled program carries only the primitives it actually uses — the compiler discards the rest. The same headers are callable from plain C; the C manual documents them.
- **TYPE ... END TYPE — MMBasic structures.** Nested types, member arrays, structure arrays, `LOCALs`, by-reference parameters, whole-structure assignment, `STRUCT COPY/CLEAR/SWAP`, and `STRUCT(SIZEOF/OFFSET/TYPE)` folded to compile-time constants. The firmware's byte layout is reproduced exactly — sizes, offsets, padding and the length-byte string format — so `STRUCT(SIZEOF "t")` answers the same number here and on a PicoMite, and assigning an over-length string to a `LENGTH n` member raises `String too long` just as the firmware does. Verified side by side against a real PicoMite running the firmware's own structure test suite: every feature implemented here passes identically there. What does not translate is refused by name rather than mistranslated; the translator chapter lists it.
- **A class of board-only crashes in compiled programs is fixed.** `bcrun` could size a program's memory arena so that the stack ended up misaligned for the ARM's paired-register stores, and the Cortex-M33 faults on those regardless of its unaligned-access support. Neither the host runner nor `qemu` enforces that, so the crash existed only on real hardware. The arena is now rounded so the stack is always 8-byte aligned.
- **ON ERROR SKIP/IGNORE, with `MM.ERRNO` and `MM.ERRMSG$`.** A program can survive an error instead of stopping at it, exactly as it can on a PicoMite — and the errors themselves now fire where the interpreter fires them. That was the larger half of the work: float division by zero used to answer `inf` rather than stopping, `SQR(-1)` and `LOG(0)` answered `nan` and `-inf`, string concatenation past 255 characters truncated instead of erroring, and `ASC("")` errored where a PicoMite returns 0. Each of those was a program that behaved differently here and said nothing about it. There is a section on all of this below.
- **The arithmetic checks are paid for only by programs that can use them.** A program with no `ON ERROR` cannot trap an error, so `mmbc` compiles its float divisions to the machine's own divide and its `SQR/LOG/ASIN/ACOS` to direct `libm` calls — full speed, C answers (`inf/nan`) if the argument was bad. The moment `ON ERROR` appears, every one of those becomes the checked, trappable statement the interpreter has. “What `ON ERROR` costs”, below, has the numbers.
- **The machine can say what it is.** `MM.VER` gives the release as a number (0.10 reads higher than 0.09), `MM.DEVICE$` names the firmware and `MM.CMDLINE$` gives the arguments the program was started with, so a translated program can be used as a proper command. Naming the machine needed a new kernel call: which board this is was something the kernel knew and only the boot banner ever said. *(In this release `MM.DEVICE$` answered `Fuzix on PC2` / `Fuzix on PC3`. Since v0.16 it is `Fuzix` alone and the board is `MM.INFO(PLATFORM)` — see [Asking the machine about itself](#).)*

- **mmedit's Find works from the machine's own keyboard.** F3 opened the prompt and then ignored Enter, because a serial terminal sends CR where the USB keyboard sends LF and the prompt only accepted the first. Every prompt now takes either, so F3, F10 and the rest behave the same on the HDMI console as over a serial line.
- **mmedit takes the screen back from a graphics mode.** Editing after a program that ended in MODE 2 meant typing into a console the monitor was not showing. The editor now switches to MODE 1 while it runs and restores the mode when it leaves, so the program's screen comes back as it was.
- **mmedit colours the new statements correctly.** Box, RBox, Triangle, Arc, Type, End Type, Struct and Struct( now show as translatable (cyan) rather than interpreter-only (blue), and so do the MM. functions mmhc understands — while MM.WATCHDOG, MM.INFO and the rest it does not are honestly blue, where the editor used to call everything translatable.
- **The kernel's crash report leads with r4–r7** — the registers that actually locate the fault in compiled code — so a report copied from the screen is useful even when cut short.

And a group of changes that make everything on the machine faster, without any program being written differently:

- **The C library's string routines are newlib's.** Every program in the userland — the compiler, the translator, bcrun, the editor, your own C — was using the generic byte-at-a-time memcpy, memset, memmove, strlen, strcmp and their relatives: about nine cycles a byte on this processor. Twenty-one objects are now taken from the ARM toolchain's own libc.a at build time, so the machine runs the routines that were written and tuned for it. On identical bytecode: the grains benchmark 52,052 → **55,163**, the solar eclipse predictor 2.022 → **1.953 s**, a graphics frame 78.81 → **74.03 ms**. The compiler is a program in that userland too, so compiling the eclipse went from 7 seconds to 6.
- **Integer division uses the divide instruction.** MMBasic integers are 64 bits wide and this processor's SDIV is 32, so every \ and MOD went through a software routine that is roughly twenty times the cost of the instruction — even when both numbers were small. When they both fit in 32 bits, which in practice is nearly always, the instruction is used directly. The grains benchmark gains about 1%, the eclipse predictor 2%.
- **PIXEL no longer pays a system call per point.** Plotting a point cost about 1.3 µs of crossing into the kernel to store 15 ns of pixel — 96% overhead. Points now queue and go across in one call, up to 512 at a time or every 10 ms, whichever comes first, and any other drawing statement flushes the queue first so the order on screen is exactly the order in the program. A pure-PIXEL demo (ripple.bas) went from 217 ms a frame at v0.9 to **171** — 21%. A program that already builds its points into an array and plots them with the array form of PIXEL is unaffected: that was, and remains, the fastest way to plot a lot of points. One deliberate behaviour change comes with this: a PIXEL outside the screen is now **dropped**, as the interpreter drops it, where before the coordinates wrapped and the point appeared somewhere else. A program that relied on the wrapping will look different.
- **Recursion goes 255 levels deep, not 15.** The old limit was nothing to do with the stack. A by-reference argument occupies a slot that cannot be released until the call returns, there were sixteen slots, and so a routine that passed an argument by reference to itself stopped at fifteen. There are now 256, which costs 2 KB and is measured at 255 levels for every shape of recursive routine — with locals, with local strings, with a string expression built at each level. Beyond that a program stops with **Expression too complex** rather than misbehaving. For scale: a recursive walk over a million-node balanced tree is twenty levels deep. A program that recurses without any terminating condition is still a program that crashes the machine; the

depth guard does not cover compiled routines that the translator has turned into native code.

- **Four C89 gaps in the preprocessor.** `?:` in an `#if`, the `#line` directive, `__LINE__` inside an `#if`, and macro arguments being expanded before `##` pastes them. The host build of the compiler uses `gcc -E`, so the machine's own preprocessor had never been tested by anything; it has its own test suite now. C conformance measured on the machine goes from 156 to **160 of 175**.
- **cc1 folded signed constant division as unsigned.** `-7/2` in a constant expression came out as an enormous positive number. Both operands are now cast to a signed type before folding.

## 1.8 New in v0.9

This release takes the 32 MB limit off the filesystem and makes compiled code substantially faster.

- **A 2 TB disk format.** Block numbers are 32-bit and inodes 256 bytes, in place of the 16-bit block number that capped a filesystem at 32 MB. The shipped card now has an 800 MB root rather than 32 MB, a single file can reach 1 GB, and the format itself goes to 2 TB. **Old cards and new kernels do not mix:** each refuses the other by name rather than misreading it, so flash the kernel and write the card in the same sitting.
- **Compiled code is over 60% faster.** Dhrystone 2.1, compiled on the machine, went from 102,842 to 166,834 per second — 44% of the same benchmark cross-compiled by `gcc -O2` for this chip. Almost none of that came from generating cleverer instructions; it came from *keeping hot code native*. Library symbols are bound once at load instead of being looked up on every call, the hottest local in a function is held in a register, and compound assignment on 64-bit and double values is inlined rather than calling out to the runtime — that last one had been costing every MMBasic `FOR` loop a crossing out of native code on every single iteration.
- **The console survives a lost UART interrupt.** Three console wedges during large serial transfers shared one state: the interrupt enabled and pending, but never delivered. Why delivery is lost is still not understood, but it is no longer fatal — the handler now drains both directions and the 5 ms tick is a full polled rescue, so the console degrades to polled instead of dying.
- **vi.** The editor has always been on the card, but only under its own name, `levee`. It now answers to `vi` as well: one file, two names, no extra space.
- **mmedit's function keys work from a serial terminal.** They always worked from a USB keyboard on the HDMI console, but a terminal such as TeraTerm spells F1–F4 differently — `ESC [ 11 ~` where the console sends `ESC O P` — and the editor silently ignored the spelling it did not know. Since the editor is driven almost entirely by function keys, that made it close to unusable over the serial port. It now accepts every sequence MMBasic's own `MMInkey` accepts, including the shifted forms.
- **INKEY\$ returns MMBasic's key codes.** A terminal sends an arrow or a function key as a several-byte escape sequence; MMBasic hands back one code for it, and until now a translated program here saw the raw bytes one at a time instead. So `IF INKEY$ = CHR$(&H80)` — the way every PicoMite program tests for cursor-up — quietly never matched. `INKEY$` now reassembles the sequence and returns the same single code the PicoMite does: `&H80–&H83` for the cursor keys, `&H91–&H9C` for F1–F12, and the editing cluster besides. Anything it does not recognise is handed back byte by byte, as before, so nothing is swallowed.
- **vi can edit a real file.** Levee shipped with a 4 KB buffer — a fair share of an 8-bit micro, and not of this machine. It is now 64 KB.

## 1.9 New in v0.8

This release gives the machine music, pins, and MMBasic's own text.

- **MP3 playback.** `PLAY MP3 f$` plays a file *while your program carries on running* — the decoder is a separate process feeding a deep buffer in the kernel, so nothing has to be refilled from a main loop. `PLAY VOLUME n` sets the level and is remembered; `PLAY STOP` stops whatever is playing, including a player left behind by a program you interrupted. A translated BASIC benchmark still runs at **89% of full speed** with music playing.
- **SETPIN and PIN** — all forty-eight GPIOs of the RP2350B, not the 28 an RP2040 has. `SETPIN n, DIN|DOUT|AIN|ARAW|OFF, PIN(n) = v` and the `PIN(n)` function, with analogue in volts or raw counts. Pins are owned, and come back reset when your program ends; and a pin read or write is a register access, not a system call.
- **TEXT, FONT and all nine of MMBasic's fonts**, held in flash so they cost no RAM at all. `TEXT` takes the full alignment and scale arguments.
- **MAP, statement and function**, with `CLS [colour]:` the sixteen colours can be remapped exactly as in MMBasic, and the defaults are now MMBasic's own HDMI values rather than an approximation.
- **PAUSE gives the CPU up** instead of spinning, so a program that waits no longer holds the machine — and the fraction of a second it cannot sleep is bounded at 99 ms however long the pause.
- **Programs are much smaller.** MMBasic's scratch memory is now sized per program rather than fixed, taking a translated program's static data from 61,904 bytes to 12,748.
- **Maths runs on the DCP.** `SIN`, `COS`, `EXP` and the rest are shared out of kernel flash and use the RP2350's double-precision co-processor: about **2.7× faster** than the copy that used to be linked into every program, and it costs no program memory.
- **A C library fix that reaches everything.** `<limits.h>` declared `INT_MAX` as 32767 on a machine whose `int` is 32 bits. Any program that compared against it — or sized a buffer with it — was working from a number two thousand times too small. Every binary on the card has been rebuilt.

The kernel and the card are a matched pair, as always: the card's programs are statically linked, so a new kernel with an old card runs the old C library.

## 1.10 New in v0.7

Most of the kernel now executes from flash instead of being copied into RAM at boot, and the memory that frees goes to programs.

- **340 KB of program RAM**, up from 312, and a single process can have about **292 KB**. 90,676 bytes of kernel code used to be copied into RAM at boot; 45,000 of them are gone, and what is left has room to grow. Costs nothing measurable: the display DMAs out of RAM continuously, so RAM bandwidth is contended while the flash cache is a separate path.
- **64 processes**, up from 30, with the open-file and inode tables sized to match — the shell gives every background job its own `/dev/null`, so the file table ran dry before the process table did.
- **FRAMEBUFFER** — `CREATE, WRITE N|F, COPY s,d[,B], CLOSE, WAIT`. Draw off-screen and show the frame in one go. A redraw-and-show frame costs about 4.4 ms against the 17 ms the display gives you, and `COPY ... ,B` holds a loop to the refresh rate.
- **PRINT @(x, y [, mode])** puts text at a pixel position. In a graphics mode `PRINT` now *draws* the characters, as MMBasic does, rather than sending them to the console — so text follows

the drawing into the framebuffer instead of the console scrolling the display out from under it. mode 1 draws over what is there, 2 swaps ink and paper.

- **INKEY\$** — which was not implemented at all, and because it ends in \$ was quietly being treated as an ordinary empty string variable, so `LOOP UNTIL INKEY$ <> ""` could never exit.
- **PIXEL x(), y(), c()** — the array form, one call for a whole run of points instead of one syscall each.
- **Text scrolls the same way everywhere.** A `PRINT` on the last line scrolls in a graphics mode exactly as it does on the console, because it is now literally the same code.
- **A stretched ellipse outline is no longer dotted** — the fix from MMBasic's own `DrawCircle`.
- **PRINT "x"; reaches the screen.** A partial line used to sit in a buffer until the next newline, so a program printing "Calculating..." and then working for half a minute showed nothing until it finished.
- **BBC BASIC works again.** It sizes its workspace by asking for memory until the kernel refuses; v0.6 let it take every last block, leaving the shell nowhere to return to. A process may now grow only as far as leaves room for the largest other one.
- **The boot banner names the PC3 release**, alongside Fuzix's own version — they are different numbers, and only one of them used to be on screen.

### 1.11 New in v0.6

This release is about memory. A translated BASIC program could not hold a framebuffer-sized array, and a large one could not be loaded at all; both are fixed, and the same work made everything faster.

- **BASIC arrays and strings live in the PSRAM heap.** They used to sit in the 48 KB the interpreter gave a program, so a 38,400 byte array — one MODE 1 framebuffer — did not fit at all. Globals go in one block taken once; `LOCAL` arrays and strings get a block per invocation, freed on the way out, which is what makes recursion correct. Simple variables stay where they are: they are the hot ones, and SRAM is 3.7× faster to reach than PSRAM.
- **Programs are 15% faster.** A program address is now a machine address rather than an offset into a 48 KB window, so every access stops paying for the conversion. The solar eclipse went from 3.31 to 2.80 seconds, and the heap change above costs about half a percent on top.
- **A process may use all of program RAM.** The old 256 KB ceiling was the size of a fixed swap slot, and swap has not worked that way for a while.
- **SYSTEM, SAVE IMAGE and LOAD IMAGE work from large programs again.** `fork` needed the process resident twice over, so anything past half of memory could not do it. The parent is now staged into PSRAM instead.
- **A memory leak fixed** that cost 132 KB — of 312 KB — every time a program failed to start, for the rest of that boot.
- **A C library bug fixed** that made `fread` and `fseek` disagree about a file's position and quietly return the wrong bytes. It needed a file small enough to fit one buffer, which is why it went unnoticed: it took down the compiler on a 305-byte object while 100 KB ones were fine. It is not specific to this machine and has been reported upstream.

### 1.12 New in v0.5

- **MMBasic draws.** `MODE`, `COLOUR`, `PIXEL`, `LINE`, `CIRCLE` and `RGB()` are translated and run on the HDMI display — a whole shape crosses into the kernel in one call, so a 640-point line costs

one syscall rather than 640.

- **SAVE IMAGE and LOAD IMAGE**, with MMBasic's BMP decoder: 1/4/8/16/24/32-bit files, RLE4 and RLE8, and its dithering modes.
- **SYSTEM** — a BASIC program can run another program and wait for it, which is how **SAVE IMAGE** and **LOAD IMAGE** are built.
- **mmedit**, MMBasic's editor, ported.
- **TIMER is a float** off a 64-bit microsecond clock, and **RND returns 53 bits** from splitmix64 rather than 15 from the C library.
- The SD root filesystem is now **built from source** by **mksdimage.sh** — it had no build recipe before — and is **64000 blocks** rather than the 65535 that sat on **blkno\_t**'s ceiling.
- A **filesystem corruption fixed** that had been destroying cards under repeated large-file rewrites: **f\_trunc** freed a file's double indirect block and left the inode still pointing at it. It bit any file over 273 blocks. See the release notes.
- **Panic messages now reach the serial port.** They were being truncated to about eleven characters by an interrupt-driven UART that stopped with the machine.

## 2 Installing Fuzix

### 2.1 Flashing the kernel

The kernel is a standard UF2 file, `fuzix.uf2`, flashed exactly like any other Pico Computer firmware:

1. Set the USB HUB switch to **DISABLE** and connect the **Prog** port to your PC.
2. Hold **BOOT**, click **RESET**, release **BOOT**. A USB drive appears.
3. Drag `fuzix.uf2` onto the drive. The board reboots when the copy completes.
4. Set the HUB switch back to **ENABLE**.

Flashing does not touch the SD card.

### 2.2 Writing the SD card

Fuzix boots from a ready-made card image, `pc3-sd.img` (978 MB, about 4.9 MB compressed for download). Write it to a card of **1 GB or larger** with any raw-image tool — Raspberry Pi Imager (“use custom image”), Win32DiskImager, balenaEtcher, or `dd` on Linux/macOS. **The whole card is overwritten.**

The image lays the card out as three partitions:

| Partition | Size   | Type       | Purpose                                              |
|-----------|--------|------------|------------------------------------------------------|
| 1         | 128 MB | FAT        | File interchange with Windows/macOS/Linux            |
| 2         | 800 MB | Fuzix root | The Unix filesystem (boot device <code>hdb2</code> ) |
| 3         | 4 MB   | 0x7F       | Reserved                                             |

The root filesystem is 1,638,400 blocks of 512 bytes with 25,600 inodes, and it fills its partition exactly.

It did not always. Before v0.9 a block number was 16 bits, so 65535 was at once the highest block a filesystem could have and the marker meaning “no such block” — and the filesystem was deliberately held to 64000 blocks, short of its own partition, so that a stray value could be recognised as wrong instead of pointing at a real sector. That is what limited the root to 32 MB. From v0.9 the format is **FS32**: 32-bit block numbers and 256-byte inodes, with a “no such block” marker that cannot be a real block at all. The margin is gone, and with it the ceiling — a filesystem can now be up to 2 TB and a single file up to 1 GB.

**A v0.9 kernel and a v0.9 card go together.** The two formats are not interchangeable and neither pretends otherwise: a v0.9 kernel refuses an older card by name at the `bootdev:` prompt, and an older kernel refuses a v0.9 one. Flash `fuzix.uf2` and write the card in the same sitting.

Since v0.5 the filesystem has been built from source by `mkimage.sh`, so the card can be reproduced rather than merely copied. `mkcard.sh` decides the layout, and its `FAT_MB` and `ROOT_MB` settings are the only place the partition sizes are written down.

Partition 1 ships unformatted: format it as **FAT or FAT32 (not exFAT)** in Windows before first use — see section 6. Partition 2 is Fuzix’s own filesystem format; no desktop OS can mount it, which is why the FAT partition and the `fat` command exist.

## 2.3 First boot

Connect a monitor to the HDMI port and/or a terminal program (for example TeraTerm at 115200) to the USB-C console port. Switch on: the kernel banner, board identification and device probe appear on both, then:

```
login: root
```

There is no password. The system arrives at a Bourne shell; the console is an 80×40 colour terminal (termcap type `pc3`) and the USB keyboard and serial input feed the same session interchangeably. Set the keyboard layout in `/etc/rc` (`picocctl keymap uk` by default).

**Auto-repeat** waits 250 ms and then repeats every 50 ms — twenty a second. HID keyboards only report a change of state, so the repeat is synthesised from the held key. These were MMBasic’s 600/150, which is a typewriter’s rate and fine for typing, but anything *held* suffers: a game played from the keyboard crawled beside the same game played from a switch array, which is read fresh every pass of its loop with no typematic delay at all. The standard `KBRATE` tty ioctl adjusts them at run time, but note that its units are TENTHS of a second and so cannot express the 50 ms default.

### 2.3.1 Num lock, and keyboards with no keypad

A keyboard with no numeric keypad — a Raspberry Pi keyboard, and most laptop-style boards — usually overlays one onto `7890/uiop/jkl;/m` whenever num lock is on, so those letters type digits. The keyboard’s own firmware does that, in response to the num lock light the machine asks it to show.

Two things handle it. A keyboard that reports **no num lock light** is taken to have no keypad and starts with num lock off (it says so at boot). That does not catch every such keyboard — one that reports a num lock light while having no keypad is indistinguishable from a full-size keyboard — so **pressing Num Lock is also remembered**, per keyboard, for as long as the machine stays on.

To ask what is going on:

```
# picocctl numlock
num lock on
keyboard 04d9:0006, num lock LED declared
```

and to change it: `picocctl numlock off`. The kernel does not write files, so a setting is only permanent if it is named in `/etc/rc`, where each keyboard can have its own line:

```
picocctl numlock off 04d9:0006
```

To power off, type `shutdown` (or at minimum `sync`, then wait a moment). After an unclean power-off the next boot repairs the filesystem automatically (`fsck -a -y`).

## 2.4 Setting the clock

The board’s DS3231 battery-backed clock supplies the date and time: at every boot `/etc/rc` runs `setdate`, which reads the chip and sets system time silently. If the chip cannot supply a valid time (fresh battery, or the battery was removed) the same command falls back to prompting on the console:

```
Current date is Mon 2026-07-27
Enter new date:
```



Press Enter to keep a value, or type a new one (2026-07-28, then 16:30:00). To set the clock at any other time run `setdate -u`, which always prompts.

Setting the system time does not touch the chip. To make the time permanent, write it back:

```
# setdate -w
writing
```

That also restarts a stopped oscillator, so the sequence for a new battery is: `setdate -u` (enter the time), then `setdate -w`. The kernel message `oscillator was stopped, time needs setting` at boot means exactly that sequence is wanted.

While running, system time is kept by the crystal-driven timer tick and gently re-synchronised from the DS3231 about once an hour, the same policy as MMBasic. `date` prints the current time.

If a transaction to the chip is ever interrupted at the wrong moment (a reset mid-read), the battery-backed DS3231 can be left jamming the I2C bus - even across power cycles. The kernel detects this at boot (`ds3231: SDA held low, clocking bus free`) and clears it automatically.

## 2.5 Command history and line editing

At any cooked-mode prompt - the shell, login, most line-oriented programs - the console provides in-line editing and command history:

| Key                             | Action                                        |
|---------------------------------|-----------------------------------------------|
| Up / Down                       | walk back / forward through previous commands |
| Left / Right                    | move within the line                          |
| Home / End (or Ctrl-A / Ctrl-E) | start / end of line                           |
| Backspace / Delete              | delete left / at the cursor                   |
| Ctrl-U                          | discard the line                              |

The history (about 500 commands) lives in a small region reserved at the top of the PSRAM, so it costs no program memory; like the RAM disc it survives a reset but not a power cycle. Programs that take the terminal raw (BBC BASIC, the editor) see every keystroke themselves as usual - BBC BASIC has its own line editor and `*EDIT`.

## 2.6 Escape routes

- **Esc** — inside BBC BASIC, stops the running program.
- **Ctrl-\** — kernel emergency break: kills the foreground program even if it has the terminal in raw mode, and restores a sane terminal. Use it instead of the RESET button when something wedges.
- **kill** from the shell works on anything; Fuzix pre-emption guarantees a spinning process can't lock you out.

### 3 The consoles

Everything is mirrored: kernel and program output appear on the HDMI display and the serial console simultaneously, and input is merged from the USB keyboard and the serial line. TeraTerm is resized to 80×40 automatically at boot.

While BBC BASIC has a graphics MODE on screen, the HDMI display belongs to the graphics; text output continues to the serial side as a plain stream, so a transcript survives even a full-screen game.

## 4 BBC BASIC

Start it by name; leave with QUIT:

```
# bbcbasic
BBC BASIC for Fuzix Console v0.50
(C) Copyright R. T. Russell, 2025
>
```

This is R. T. Russell's BBC BASIC (the BBCSDL console edition), so the language is the full modern dialect: 64-bit integers, IEEE double floats, long variable names, **WHILE/ENDWHILE**, multi-line **IF/ELSE/ENDIF**, structures, and the inline assembler. Keywords must be typed in **capitals** (**PRINT**, not **print**); **\*LOWERCASE ON** relaxes this. Star commands are case-insensitive.

### 4.1 Loading programs, including plain text

**LOAD** and **CHAIN** accept **both** program formats:

- the tokenised internal format written by **SAVE** (fast, exact), and
- **plain ASCII listings**, detected automatically. An unnumbered modern-style listing is given line numbers 10, 20, 30...; a listing with its own numbers keeps them. Windows line endings are fine, and typographic characters that desktop editors introduce (curly quotes, non-breaking spaces, tabs) are silently converted to their ASCII equivalents — an invisible “smart” character can otherwise produce a baffling **Syntax error** on a line that looks perfect.

The comfortable round trip: edit `myprog.bas` on your PC, copy it to the FAT partition, then:

```
# fat get myprog.bas
# bbcbasic
>LOAD "myprog.bas"
>RUN
>SAVE "MYPROG"           save tokenised for fast loading next time
```

### 4.2 Graphics

**MODE 0–5** switch the display to 1024×768 and provide the classic screens; **MODE** with any higher number (e.g. **MODE 6**) returns to the text console. Errors leave you at the prompt *in* the current mode, exactly like the original machine.

| MODE | Resolution | Colours | Presentation on the monitor                  |
|------|------------|---------|----------------------------------------------|
| 0, 3 | 640×256    | 2       | Full width (5:8 smooth upscale), full height |
| 1, 4 | 320×256    | 4       | 960×768 — every pixel a crisp 3×3 block      |
| 2, 5 | 160×256    | 16      | 960×768 — every pixel a crisp 6×3 block      |

Coordinates are the authentic 1280×1024 graphics units, origin bottom-left, movable with **VDU 29**. Implemented: **MOVE**, **DRAW**, **PLOT** (move/line families 0–15, points 64–71, filled triangles 80–87 — so **PLOT 85** works), **CLG**, **GCOL**, **COLOUR**, **POINT(x,y)**, **VDU 19** palette changes (instant, no redraw), **TAB(x,y)**, and text printed with the built-in 8×8 font (40 or 80 columns × 32 rows, with scrolling). **MODE 1/4** store 4 bits per pixel, so all 16 logical colours are available there via **VDU 19** even though the default palette is the authentic four.

### 4.3 Sound

The full BBC sound system plays through the PCM5102 DAC and the 3.5 mm jack:

```
SOUND 1,-15,89,20                                A4 (440 Hz) for one second
ENVELOPE 1,1,4,-4,4,10,10,10,126,-2,0,-10,120,100
SOUND 1,1,100,30                                  envelope-shaped note
SOUND &201,-15,53,20:SOUND &202,-15,69,20:SOUND &203,-15,81,20
                                                a synchronised C-E-G chord
```

Channels 1–3 are square-wave tones, channel 0 is noise. Each channel queues up to 8 notes; `&1x` in the channel number flushes the queue. `&Sxx` holds the note until *S* other channels carry the same sync mark, so a three-note chord wants `&2xx` on each channel — `&1xx` releases in pairs, playing two notes and leaving the third waiting for a partner that never comes. `ENVELOPE` implements the three-section pitch envelope and ADSR amplitude, stepped at the authentic 100 Hz. Pitch follows the BBC scale: 4 units per semitone,  $89 = A4 = 440$  Hz. Durations are in 20ths of a second; 255 means “until further notice”. `SOUND` blocks BBC-style when a queue is full (Esc still works).

A note on character. The output is hot: one full-amplitude (–15) square is a quarter of DAC full scale and three sum to nearly three-quarters, which can clip a sensitive line input that handles MP3 playback happily — drop to –7 if the input distorts. The squares themselves are band-limited (polyBLEP), so sustained notes hold a pure pitch right to the top of the range instead of carrying the aliasing shimmer a naive digital square picks up.

There is one audio output, so the synthesiser and MP3 playback are mutually exclusive — as they are in MMBasic. While a track is playing, notes are queued and heard when it ends; `PLAY STOP`, or `killing playmp3`, gives the synthesiser the hardware back at once.

### 4.4 ADVAL: joystick, analogue inputs, sound queues

| Call                             | Returns                                                                                                                |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <code>ADVAL(0)</code>            | Joystick switches on GP34–37 as a mask: bit 0 = GP34, bit 1 = GP35, bit 2 = GP36, bit 3 = GP37; pressed (grounded) = 1 |
| <code>ADVAL(1)–ADVAL(4)</code>   | Analogue readings of GP41–GP44, 0–65520 (12-bit ADC ×16)                                                               |
| <code>ADVAL(-1)</code>           | Characters waiting in the keyboard buffer                                                                              |
| <code>ADVAL(-5)–ADVAL(-8)</code> | Free queue slots on sound channels 0–3                                                                                 |
| <code>ADVAL(-9)</code>           | Hardware microsecond counter (64-bit)                                                                                  |

The joystick inputs have pull-ups and Schmitt-trigger inputs enabled; wire switches directly to ground. The analogue inputs are 3.3 V full-scale.

`ADVAL(-9)` is the benchmarking clock — the RP2350’s free-running microsecond timer, far finer than `TIME`’s centiseconds (which tick in tenths of a second on this kernel). MMBasic-style usage:

```
DEF FNtimer = ADVAL(-9)
T% = FNtimer
REM ... code under test ...
PRINT (FNtimer - T%) / 1000; " ms"
```

Each reading costs one system call (a few tens of microseconds) - negligible over millisecond-scale measurements. The value is the full 64-bit hardware counter (BBC BASIC integers are 64-bit), counting microseconds since power-on: it never wraps in practice.

## 4.5 Serial port

A second serial port lives on the I/O header: **TX = GP0, RX = GP1** (3.3 V logic, no flow control), visible as `/dev/tty2`. BBC BASIC reaches it as a *port channel* — raw and unbuffered:

```
*stty 9600 </dev/tty2
ch% = OPENUP("/dev/tty2")
BPUT#ch%,65          send a byte
X% = BGET#ch%        receive a byte (waits for one)
CLOSE#ch%
```

Any `stty` setting applies (baud rate, parity, size). The same `OPENIN/OPENUP/BGET#/BPUT#` mechanism works on any `/dev` device; ordinary file names get the buffered 256-byte file channels instead, exactly as on the original machine.

## 4.6 Star commands and the shell

The built-in set includes `*DIR/*. , *CD, *TYPE, *COPY, *DELETE/*ERA, *MKDIR, *RMDIR, *KEY, *SPOOL, *EXEC, *LOWERCASE, *TEMPO, *QUIT`. Anything unrecognised is passed to the Unix shell, so `*ls -l, *stty 9600 </dev/tty2` and even `*fat get demo.bas` work from inside BASIC.

## 4.7 The inline assembler

The assembler between `[` and `]` targets the machine it runs on: **ARM Thumb (v6-M subset)**, not 6502. `CALL` and `USR` work as documented for BBCSDL's ARM editions. Machine code written for a BBC Micro will not run; this is the same situation as every modern BBC BASIC.

## 4.8 Differences from the original BBC Micro

Better than the original:

- ~110 KB of program workspace (about 80 KB when graphics are in use) against the Model B's 32 KB shared with the screen
- 64-bit integers, double-precision floats, the modern language
- Long file names on a hierarchical filesystem
- The machine multitasks underneath — BASIC is just a process

Not (yet) present, compared with an original machine or full BBCSDL:

- **MODE 7** teletext (MODE 6 and 7 return to the console)
- VDU 5 text-at-the-graphics-cursor; user-defined characters (VDU 23) are accepted but not rendered
- PLOT families beyond points/lines/triangles: no circles, arcs, ellipses, flood fill or rectangle/parallelogram fills yet
- GCOL action modes 1–4 (OR/AND/EOR/invert) plot as mode 0 (set)
- Flashing colours (8–15 map to their steady equivalents)
- `*FX` calls, `INKEY` with negative arguments (keyboard scanning), and the 6502 `CALL` interface
- `TIME` advances in 0.1 s steps (the kernel clock granularity)

- Cassette/Econet/ROM filing systems, for obvious reasons

## 5 The C compiler

The machine compiles C on its own, with no PC involved. `cc` is Alan Cox's Fuzix Compiler Kit, retargeted here to a bytecode machine.

```
# cat > hello.c
#include <stdio.h>
```

```
int main(void)
{
    printf("hello from Fuzix\n");
    return 0;
}
```

```
^D
```

```
# cc hello.c
# ./hello.bc
hello from Fuzix
```

`cc prog.c` writes `prog.bc` and makes it executable, so `./prog.bc` runs it directly — the object starts with `#!/usr/bin/bcrun`, and the kernel does the rest. `bcrun prog.bc` still works and is the way to run an object that has lost its execute bit. Options are `-o name`, `-v` to show each pass as it runs, and `-k` to keep the intermediates. `bcdump prog.bc` disassembles.

`cc` is a driver: it runs `cpp`, then the three compiler passes from `/usr/lib/cc`. The passes cannot be driven from the shell by hand — two of them read back from their own standard output, which needs a redirection the Bourne shell here does not have. Like BBC BASIC, the compiler lives on the SD card root and is not in the NAND recovery system.

A small program takes about a second to compile. The dots `cc` prints are progress, one per top-level declaration.

### 5.1 What it compiles

**C89, plus declarations after statements** — the one C99 borrowing, because refusing it is a nuisance out of proportion to the standard it comes from. Everything else is ANSI C as of 1989: the full type system, `struct` and `union` including passing and returning them by value, `enum`, `typedef`, function pointers, `switch`, `goto`, all the usual operators, 64-bit `long long`, and double-precision floating point.

The compiler is checked against `gcc` as an oracle: 165 of the 175 applicable tests in the public `c-testsuite` conformance suite pass with byte-identical output, and a set of samples in the source tree is diffed against `gcc` on every change — on the board as well as on the host.

### 5.2 Headers and the runtime library

`/usr/lib/cc/include` holds `stdio.h`, `stdlib.h`, `string.h`, `math.h`, `assert.h`, `limits.h` and `stddef.h`. These describe what `bcrun` actually provides, and they are deliberately **not** `/usr/include`, which describes the Fuzix C library used by native binaries.

Available: `printf sprintf puts putchar; fopen fclose fread fwrite fgetcgetc fputcputc fgets fputs fprintf feof fseek ftell rewind fflush remove; malloc calloc realloc free exit atoi abs; strlen strcpy strncpy strcat strcmp strncmp strchr strrchr memset memcpy`

`memmove memcmp`; and from `math.h`, in double precision, `sin cos tan asin acos atan atan2 sinh cosh tanh sqrt exp log log10 pow floor ceil fabs fmod`. Each of those is a native function inside `bcrun`, so it runs at machine speed whatever the calling code is.

`malloc` takes its memory from the PSRAM, not from the program's own 340 KB, so a C program can allocate far more than it could hold itself. It is asked for once when the program loads; set `BCRUN_HEAP` to a size in KB in the environment to change how much.

The raw system calls `open creat close read write lseek unlink` are also linked in, but no header declares them — declare them yourself if you want them. Two extras reach the hardware: `time_us()` returns the microsecond counter, and `adval(n)` is the BASIC ADVAL function (joystick, analogue inputs, sound queues).

### 5.3 Limitations

These are worth knowing before you start a large program.

- **One source file per program.** There is no assembler and no linker: `cc2` writes a loadable object directly, so nothing can be linked together. `cc` rejects a second source file rather than pretending.
- **Bitfields are not implemented.** `unsigned flags : 3;` is refused with a diagnostic. This is the only part of C89 missing.
- **& on a library function does not work.** A runtime function is resolved by index and has no address, so `&printf` cannot be represented. `bcrun` refuses such a program by name when it loads it, rather than running it with something wrong in place of an address. Pointers to *your own* functions are entirely fine.
- **No wide strings.** `L'x'` is accepted (and equals `'x'` here); `L"..."` is refused rather than quietly returned as a narrow array.
- **printf rounds halves up.** `%.2f` of 0.125 gives 0.13 where a full C library gives 0.12. A deliberate, documented difference: matching the round-half-to-even rule needs exact decimal expansion.

### 5.4 Speed

`cc2` translates each function it compiles into native Thumb-2 for the Cortex-M33 and stores that in the object beside the bytecode; `bcrun` runs the native code and keeps the interpreter for whatever did not translate. Nothing needs to be asked for — it is simply what the compiler does.

Dhrystone 2.1, compiled on the machine, runs at about **167,000 Dhrystones/second** — 44% of the same benchmark cross-compiled by `gcc -O2` for the same chip (379,000). Individual loops do better: a sieve, a shell sort and an xorshift generator all land within a factor of two or three of gcc, and double-precision arithmetic uses the RP2350's hardware co-processor through the same routines the rest of the system uses.

That figure has moved a long way and is still moving: the same benchmark ran at 3,808/second on the original pure interpreter and 90,000 as recently as v0.8. Most of the recent ground came from keeping the hot code in native form rather than from generating better instructions — binding every library symbol once at load, caching the hottest local in a register, and inlining the compound assignments (`i += n`) on the 64-bit and double types that every MMBasic loop counter uses. Each of those had been quietly leaving native code and crossing back into the C runtime once per iteration.



A program can be forced to interpret with `BCRUN_BYTECODE=1` in the environment, which is how the native code is checked against the interpreter — the two must agree exactly.

What the compiler is *for* is being able to write and build real programs on the machine itself — utilities, file handling, glue, and now whole applications where the speed matters. Nothing else on the Pico Computer can do it: this is a complete toolchain that runs on the hardware, not a cross-compiler.

The bytecode is also a deliberately language-neutral intermediate form, so front ends for other languages can share the same back end and runtime. `mmbc`, the MMBasic translator described next, is the first.

## 6 MMBasic: the mmbc translator

mmbc translates an MMBasic program into C. cc compiles that C into native ARM code. The result runs as an ordinary program, several times faster than the same source under the MMBasic interpreter, on the same machine at the same clock.

Nothing about it is a cross-development trick: both programs live on the SD card and run on the Pico Computer.

### 6.1 The three commands

```
# mmbc prog.bas      -> prog.c
# cc prog.c          -> prog.bc
# ./prog.bc          runs it
```

mmbc writes prog.c next to the source and says so. -o name.c puts it somewhere else. Every line it cannot translate is reported with its line number and left as a comment in the C, so a program that uses something unsupported still produces a translation you can read, and tells you exactly where it gave up.

On the machine, mmbc writes C for the machine's own compiler. On a host it writes the slightly different C that gcc prefers; --fcc and --gcc force either form, which only matters if you are moving the generated C between the two.

### 6.2 A first program

```
# cat > hello.bas
Print "Hello from MMBasic"
For i = 1 To 5
  Print i, i * i
Next i
^D
# mmbc hello.bas
wrote hello.c
# cc hello.c
....
# ./hello.bc
Hello from MMBasic
1      1
2      4
3      9
4     16
5     25
```

The dots from cc are one per top-level declaration — a translated program carries the MMBasic runtime's declarations with it, so there are a couple of hundred of them even for four lines of BASIC. That is also why the first compile takes longer than the size of your program suggests: about half a minute here, and much the same for anything small.

Print with a comma gives MMBasic's tabbed columns, as above.

### 6.3 A worked example: the KnivD benchmark

This is a published MMBasic benchmark, unmodified. It runs four thirty-second rounds and reports a score.

```
# cat bench.bas
Print "MMBASIC benchmark (C) KnivD 2016"
Dim integer t, i=0
Dim float x(1000), f=0.0
Dim string s=""
Print "Calculating... ";
count%=0
Do
  s=""
  f=0.0
  i=0
  Timer =0
  Do While Timer<30000
    i=i+2 : f=f+2.0002
    If (i Mod 2)=0 Then
      i=i*2 : i=i\2
      f=f*2.0002 : f=f/2.0002
    End If
    i=i-1
    For t=1 To 100
      f=f-1.0001
      If (f-Int(f))>=0.5 Then
        f=Sin(f*Log(i))
        s=Str$(f,6,6)
      End If
      f=(f-Tan(i))*(Rnd(0)/i)
      If Instr(s,LEFT$(Str$(i),2))>0 Then s=s+"0"
    Next
    x(1+(i Mod 1000))=f
  Loop
  Print Chr$(13)+"Performance: "+Str$((i*1024)\286,8,0)+" grains"
  Inc count%
Loop Until count%=4
End

# cc bench.bas
wrote bench.mb.c
.....
# ./bench.bc
MMBASIC benchmark (C) KnivD 2016
Performance:    55353 grains
Performance:    55360 grains
Performance:    55353 grains
Performance:    55356 grains
```

MMBasic itself scores about 12,000 grains on the same board at the same clock. Note what the program exercises: 64-bit integers, doubles, string building, `Str$`, `Instr`, `Sin`, `Log`, `Tan`, `Rnd`, a thousand-element array and a timer — all of it translated, compiled and running natively.

Read the timings in this chapter as figures to compare against rather than constants. They are wall-clock measurements on a machine with other processes in it, they move a percent or two between runs, and they drift as the language grows — this one has roughly doubled since it was first printed here, and the eclipse below has slowed a little as more of MMBasic went in.

## 6.4 A worked example: something numerical

A longer one. It is a 3,200-line astronomical calculation (Bessel elements, lunar and solar series) that reads a date and prints the circumstances of an eclipse, and it is a good test because every digit of its output can be checked against other machines. It is among the examples as `eclipse.bas`, and in `/root/cc` as `solar_eclipse.bas` with a `solar_eclipse.in` holding a date to feed it:

```
# cd /root/cc
# cc solar_eclipse.bas
wrote solar_eclipse.mb.c
.....
# ./solar_eclipse.bc < solar_eclipse.in
...
event duration          2.61100904 hours
Time taken :           2.168458 Seconds
```

The same program takes 12.5 seconds under MMBasic and 8.8 seconds under MicroPython on this hardware; every digit printed is identical in all three. Translating and compiling it together takes about twenty seconds — it is a hundred and forty kilobytes of C, so it is much the longest build in this manual.

This one was 1.95 seconds at v0.13, with rather less of MMBasic implemented; the digits of the answer have not moved.

## 6.5 What the translation looks like

The C is meant to be read. Variables keep their names, control flow keeps its shape, and the MMBasic semantics that C does not share — integer division, `Mod` on negative numbers, string handling, the 64-bit integer/double type rules — are handled by a small runtime inside `bcrun` rather than by rewriting your program into something unrecognisable.

```
# mmbc hello.bas
# head -20 hello.c
```

is worth doing once, to see what your program became.

## 6.6 Strings, arrays and functions

Strings are MMBasic strings: `Dim string s` gives the usual 255 characters, and `Dim string s length 40` the shorter form. Arrays index from `OPTION BASE` as they should, and `Bound()` reports their limits. `Sub` and `Function` work, including arrays passed by reference and modified in place.

Arrays and strings live in the PSRAM heap, so what limits them is the 8 MB rather than the size of a process. A framebuffer-sized array — `Dim Integer fb(4800)`, 38,408 bytes — is unremarkable now; before v0.6 it would not fit at all. Simple variables stay in the program’s own memory, where they are quicker to reach, which is the same split MMBasic itself makes and for the same reason.

LOCAL arrays and strings get their own block for each call, released when the routine returns, so a recursive routine sees its own copy at every level. STATIC locals are unaffected — they are meant to outlive the call, so they stay where they were.

The one thing to remember is that a translated program is a *program*, not an interactive session: there is no editor, no RUN, no immediate mode. You edit the `.bas` file, translate, compile and run — which is also why a translated program can be put in `/usr/bin` and used like any other command.

## 6.7 Errors

mmbc reports what it could not translate, by line, and carries on:

```
# mmbc gpio.bas
2 line(s) could not be translated and were commented out:
  line 2: expected '='
  line 3: 'pin' is not an array
wrote gpio.c
```

The reasons are the translator’s own — it reads `SetPin GP1, DOUT` as far as it can and then says what it wanted to see — so they name the symptom rather than the statement. The lines themselves appear in the C as comments, with the original text, which is the quickest way to see what was dropped:

```
/*      SetPin GP1 , DOUT */
```

The translation still happens and everything else works. `--strict` stops on the first such line instead, and `--report` lists them again at the end along with any implied global variables.

Appendix C lists what is covered.

## 6.8 Graphics

A translated program draws on the HDMI display with MMBasic’s own statements:

```
MODE 2
COLOUR RGB(YELLOW)
LINE 0, 0, 319, 239
CIRCLE 160, 120, 60, , , RGB(WHITE), RGB(BLUE)
PIXEL 10, 10, RGB(RED)
```

Two modes are available, chosen to match the VGA builds of MMBasic and the first two HDMI modes:

| MODE   | Resolution | Colours                       |
|--------|------------|-------------------------------|
| MODE 1 | 640×480    | monochrome                    |
| MODE 2 | 320×240    | 16, from MMBasic’s RGB121 set |

RGB() takes the usual named colours and RGB(r,g,b). COLOUR sets the current drawing colour, which every statement uses when no colour is given. LINE, CIRCLE and the rest take MMBasic's argument order, including the blank arguments — CIRCLE x, y, r, , , fill is written exactly as MMBasic writes it.

### 6.8.1 Shapes from arrays, and filling

```
DIM x(5), y(5)
POLYGON 6, x(), y(), RGB(WHITE), RGB(RED)    ' outline, then fill
POLYGON 0, x(), y()                          ' 0 = as many as the array holds
BEZIER cx(), cy(), , RGB(CYAN)                ' n control points
FILL 100, 80, RGB(GREEN)                      ' flood from a point
FILL 100, 80, RGB(GREEN), RGB(WHITE)          ' ...up to a boundary colour
```

POLYGON is always closed — the edge from the last vertex back to the first is drawn, and the fill assumes it. Coordinates may be integer or float arrays. **Concave outlines fill correctly**: the fill collects every edge crossing on each row and fills between alternate pairs, so an arrowhead's notch stays empty. The multi-polygon form, where the first argument is an array of vertex counts, is not translated.

BEZIER takes **integer** control-point arrays, which is MMBasic's own restriction, and at most sixteen of them.

FILL has MMBasic's two modes: given a boundary colour it fills everything reachable that is not that colour; without one it replaces the colour it finds under the starting point. Note that boundary mode fills *over* other colours — it stops only at the boundary. A circle interior takes about 6 ms and a whole 320×240 screen about 75 ms.

The drawing primitives live in headers as static functions, one header per primitive — mmb\_gfx\_circle.h, mmb\_gfx\_box.h, mmb\_gfx\_rbox.h, mmb\_gfx\_triangle.h, mmb\_gfx\_arc.h, mmb\_gfx\_text.h, mmb\_gfx\_map.h, over the shared batch helpers in mmb\_gfx\_pts.h — and the translator includes exactly the ones the program uses, so a program that never draws a circle does not carry the circle code. (cc discards a file-scope static nothing calls, but that rule counts names rather than reachability, so a recursive primitive survives inside any header that carries it — which is why the include, not the static, is the unit that matters.) And a whole shape crosses into the kernel in a single call, so a 640-point line is one syscall, not 640 — measured at 71 µs against 433 µs for the naive version.

The geometry is MMBasic's, copied rather than re-derived, down to the dotted appearance of a stretched ellipse. If a picture differs from MMBasic's, that is a bug worth reporting.

**One caution.** In MODE 1 the console and the graphics share a single framebuffer, so anything printed — including the cursor — appears on the picture. It is visible in a SAVE IMAGE of the whole screen as a difference in the top text line. Restricting the saved region avoids it; directing program output elsewhere is planned.

## 6.9 The sixteen colours: MAP

MODE 2 stores a colour *number* per pixel, 0 to 15, and MAP says what colour each number actually is. Change entry 8 and everything already drawn in colour 8 changes with it — without redrawing a single pixel. That is what makes fades, flashes and colour cycling free.

|                           |                                                        |
|---------------------------|--------------------------------------------------------|
| MAP(4) = RGB(255, 128, 0) | ' collect                                              |
| MAP SET                   | ' ... and apply, all at once                           |
| MAP(n) = colour           | set entry n, 0 to 15. <b>Nothing changes yet</b>       |
| MAP SET                   | apply the collected palette, during the frame blanking |
| MAP RESET                 | back to the mode's own sixteen                         |
| MAP MAXIMATE              | the original Colour Maximize's sixteen                 |
| MAP GRAYSCALE             | sixteen greys, 0 to 255 in steps of 17 (GRAYSCALE too) |

The two-step is the point, and it is MMBasic's own: applying a new palette one entry at a time shows the picture half recoloured, and MAP SET waits for the blanking so the change lands between frames.

MAP(n) is also a **function**, giving the colour entry n stands for by default — which is the colour a program must ask for to land on that entry:

```
FOR i = 0 TO 15
  LINE i * 20, 0, i * 20, 199, , MAP(i)      ' one line per entry
NEXT i
```

It reports the default and takes no notice of any remapping, exactly as MMBasic does; it is the inverse of the fixed rule that turns a colour into an entry number. That rule is bit extraction — one bit of red, two of green, one of blue — and it does **not** depend on the palette, so remapping never moves where new drawing lands.

MAP needs a 16-colour mode; in MODE 1 it is an error.

### 6.9.1 COLOUR MAP — a whole array at once

COLOUR MAP in%(), out%() is the array form of the MAP() function: it turns a whole array of colour codes 0-15 into RGB888 colours in one statement, which is what an image or a tile table wants.

```
DIM INTEGER code(255), col(255)
COLOUR MAP code(), col()          ' the default palette
```

A third array replaces the palette for that call — it must be exactly sixteen entries, and each must be a valid 24-bit colour:

```
DIM INTEGER pal(15)
FOR i = 0 TO 15 : pal(i) = RGB(i * 17, i * 17, i * 17) : NEXT i
COLOUR MAP code(), col(), pal()    ' sixteen greys instead
```

The two arrays must be the same size, and in and out may be the same array — each element is read before it is written. The arrays are integer; MMBasic accepts float ones as well, and here that is an error rather than a silent conversion.

## 6.10 Text on the picture: TEXT and FONT

TEXT puts a string at a pixel position, justified how you ask, in any of nine fonts:

```
TEXT 160, 120, "Centred", "CM"
TEXT 319, 0, "top right", "RT", 3
TEXT 0, 100, "big and red", "LT", 5, 2, RGB(RED)
TEXT 0, 200, "over the picture", "LT", 1, 1, RGB(WHITE), -1

TEXT x, y, string$ [, alignment$] [, font] [, scale] [, colour] [, background]
```

Everything after the string may be left out, and a blank argument takes the default, as everywhere in MMBasic. **background** of -1 is transparent, which is how you write over a picture without a box of paper around the letters. With no colours given, **COLOUR**'s are used.

**alignment\$** is up to three letters and any of them may be omitted:

|             | letters | meaning                                     |
|-------------|---------|---------------------------------------------|
| horizontal  | L C R   | x is the left, the centre, the right        |
| vertical    | T M B   | y is the top, the middle, the bottom        |
| orientation | N V     | normal, or one character per line downwards |

The other three orientations MMBasic offers — I inverted, U and D rotated — are **not yet drawn**; they are accepted and come out normal.

The nine fonts are MMBasic's own, so a character looks the same here as it does there. They live in the PC3's flash, which is why there is no cost to having all of them:

| font | cell  | what it is                                 |
|------|-------|--------------------------------------------|
| 1    | 8×12  | the console's own — the default            |
| 2    | 12×20 |                                            |
| 3    | 16×24 |                                            |
| 4    | 10×16 |                                            |
| 5    | 24×32 |                                            |
| 6    | 32×50 | <b>digits only</b> — a clock face, a score |
| 7    | 6×8   | the smallest                               |
| 8    | 4×6   |                                            |
| 9    | 8×10  |                                            |

**scale** is 1 to 15 and multiplies the cell, so font 1 at scale 2 is a 16×24 character built from the 8×12 one.

A character a font does not have prints as a blank cell. With font 6 that is everything except 0 to 9.

**FONT** sets the font **PRINT** itself uses, in a graphics mode:

```
FONT 3, 1
PRINT "large"
```

```
FONT [#]n [, scale]
```

This changes where the next line goes as well as how the letters look — a 24×32 font fills the screen in seven lines where font 1 takes nineteen — and scrolling follows it.



## 6.11 Your own font: DefineFont

A program can carry a font of its own and use it exactly like the nine built-in ones:

```
FONT 10
TEXT 8, 8, "SCORE 1000", "LT", 10
```

```
DefineFont 10
    03300808
    FFFFFFFF FFFFFFFF
    55AA55AA 55AA55AA
End DefineFont
```

The block may sit anywhere in the file — the bottom is the usual place, as it is in MMBasic, and the font is in force from the first line of the program whatever line it is written on.

**Numbers 10 to 16.** Fonts 1 to 9 are the built-in ones, shared with the shell and every other program, so they cannot be replaced; **DefineFont 9** is an error naming the range rather than a definition that quietly does not happen. Ports of PicoMite programs that define a low-numbered font need that one number changed.

The first word is the font describing itself and the rest are the glyphs, in MMBasic's format, so a **DefineFont** block from a PicoMite program can be pasted in unaltered:

|                              |                     |
|------------------------------|---------------------|
| the first word, byte by byte |                     |
| width in pixels              | height in pixels    |
| code of the first character  | how many characters |

Each group of eight hex digits is one 32-bit word, **least significant byte first** — so 03300808 is width 8, height 8, first character 0x30 (0), three characters. Each glyph follows as width × height bits, most significant bit leftmost, with no padding; width × height must be a multiple of 8. A font is checked when the program is translated, so a header that disagrees with the data it carries is a translation error rather than a screen full of rubbish.

The glyphs live in the program and cost nothing else — the firmware is handed their address, not a copy — and they go away with it. Another program asking for font 10 gets its own, or nothing.

## 6.12 The glyphs themselves: MM.INFO(FONT ADDRESS) and PEEK

TEXT draws on the PC3's own screen. If you have hung a display off the I/O header — an ILI9341 on SPI, say — the firmware knows nothing about it, and you are drawing every pixel yourself. You would rather not also carry your own copy of a font to do it.

You do not have to. Ask where the built-in ones are:

```
a = MM.INFO(FONT ADDRESS 3)
```

That is a machine address, and on this computer a machine address is something a program can simply read. There is no MMU and no memory protection: the fonts are **const**, so they live in flash where nothing can move them, and PEEK reaches them where they lie.

The first four bytes at that address are the font describing itself:

| offset |                                    |
|--------|------------------------------------|
| 0      | width in pixels                    |
| 1      | height in pixels                   |
| 2      | code of the first character it has |
| 3      | how many characters                |

so having the address you need nothing else — no table of sizes, no constants of your own to get wrong:

```
w      = PEEK(BYTE a)
h      = PEEK(BYTE a + 1)
first  = PEEK(BYTE a + 2)
count  = PEEK(BYTE a + 3)
```

The glyphs follow, each `width × height` bits, packed continuously with no padding between rows and no padding between characters, most significant bit first. The one for character *c* starts at

`a + 4 + (c - first) * width * height / 8`

and bit  $y \times \text{width} + x$  of it is the pixel at  $(x, y)$ . This is MMBasic's own layout, unchanged, because these are MMBasic's own nine fonts — the ones the console draws from.

Reading one back is the clearest way to see it. `fontaddr.bas` in `/root/MMBasic` does exactly this, and prints:

| font | address  | cell  | first | count |
|------|----------|-------|-------|-------|
| 1    | 1000EF10 | 8x12  | 32    | 224   |
| 2    | 1000F994 | 12x20 | 32    | 95    |
| 3    | 100104BC | 16x24 | 32    | 95    |
| 5    | 10012814 | 24x32 | 32    | 95    |
| 6    | 10014BB8 | 32x50 | 48    | 11    |

Font 6 saying `first 48`, `count 11` is the digits-only font describing itself: 48 is "0", and eleven characters is 0 to 9 and one more. Nothing in the program was told that.

|                                      |                                                      |
|--------------------------------------|------------------------------------------------------|
| <code>MM.INFO(FONT ADDRESS n)</code> | <code>n</code> is 1 to 9; 0 if there is no such font |
| <code>PEEK(BYTE addr)</code>         | one unsigned byte                                    |
| <code>PEEK(SHORT addr)</code>        | sixteen bits, signed                                 |
| <code>PEEK(WORD addr)</code>         | thirty-two bits, unsigned                            |
| <code>PEEK(INTEGER addr)</code>      | sixty-four bits, signed                              |
| <code>PEEK(FLOAT addr)</code>        | a double                                             |

Both spellings are MMBasic's, so a program written this way runs on a PicoMite unchanged.

**These are sharp.** A `PEEK` of a wrong address is not an error message — there is nothing on this machine to catch it. It reads whatever is there, or the program dies. Check the address you were given before you use it:

```
a = MM.INFO(FONT ADDRESS 3)
IF a = 0 THEN ERROR "no font 3"
```

The wider forms insist the address is a multiple of their width, as MMBasic does, and say **Address not divisible by 4** if it is not. That is a real check and not a formality: an unaligned load faults on this processor.

MMBasic's `PEEK(VAR ...)`, `PEEK(VARADDR ...)` and `PEEK(CFUNADDR ...)` are not translated — those ask about a *variable* rather than an address, which needs the symbol table. Neither is `POKE`, in any form. What else `MM.INFO` answers is listed under [Asking the machine about itself](#).

There is a worked example of all of this driving a real panel under [A worked example: a barometric station](#).

### 6.13 Animation: FRAMEBUFFER

Drawing straight to the screen means the monitor shows the picture half-finished — the erase, then each shape appearing in turn. MMBasic's answer is to build the frame off-screen and show it in one go, and it is here:

```
MODE 2
FRAMEBUFFER CREATE
FRAMEBUFFER WRITE F
DO
  CLS
  CIRCLE x, y, 20, , , 0, RGB(YELLOW)
  FRAMEBUFFER COPY F, N, B
LOOP WHILE INKEY$ = ""
```

---

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| FRAMEBUFFER CREATE          | make the off-screen buffer, blank                        |
| FRAMEBUFFER LAYER           | make the layer, blank                                    |
| FRAMEBUFFER WRITE N   F   L | send drawing to the screen, the buffer, or the layer     |
| FRAMEBUFFER COPY s, d [, B] | s and d each N, F or L; B starts at the top of the frame |
| FRAMEBUFFER MERGE [colour]  | the layer over the buffer, onto the screen               |
| FRAMEBUFFER CLOSE [F   L]   | give one back                                            |
| FRAMEBUFFER WAIT            | wait for the top of the frame                            |

---

Everything that draws follows `WRITE`, `CLS` included — so `CLS` while writing to `F` clears the buffer and leaves the picture on the screen alone.

`CLS [colour]`

fills whatever is being drawn on. With no colour it uses the background from `COLOUR`, so `COLOUR RGB(WHITE)`, `RGB(BLUE)` then `CLS` gives a blue screen; `CLS RGB(GREEN)` fills with green without changing what `COLOUR` set. Either way the text cursor goes back to the top left, as MMBasic's does.

`CREATE` belongs **after** `MODE`. A mode change throws the buffer away, because what is in it is in the geometry of the mode being left and nothing converts it. That is MMBasic's rule too. You do not have to `CLOSE`: the buffer comes back automatically when the program ends.

Only one program can hold the buffer at a time — a second one is told so rather than quietly sharing it — and only the program holding it draws into it. Anything else that draws while your program is

between frames, a shell prompt included, still goes to the screen.

**What it costs.** The buffer is in PSRAM, so drawing into it is about  $2.4\times$  the cost of drawing on the screen — a full-screen fill measured 1.49 ms direct against 3.63 ms buffered. The copy back is 38,400 bytes at about 53 MB/s, or **0.73 ms**. So a redraw-and-show frame costs somewhere near 4.4 ms against the 17 ms the display gives you, and `COPY . . . ,B` holds the loop to the refresh rate: 59 frames a second, with room for roughly three times as much drawing before one is dropped.

### 6.13.1 The layer

`FRAMEBUFFER LAYER` makes a second off-screen buffer. It is the same size and shape as `F` and you draw into it the same way, with `FRAMEBUFFER WRITE L`; what makes it a *layer* is `MERGE`, which puts it **on top**:

```
FRAMEBUFFER MERGE [colour]
```

lays the layer over `F` and shows the result, treating `colour` as transparent — wherever the layer holds it, `F` shows through. Left out, it is 0.

**Neither source is changed by a merge.** That is the whole point of having one: the background goes into `F` once, the thing that moves goes into the layer, and a frame is one `CLS` of the layer, one shape, and one `MERGE` — no repainting of everything underneath:

```
MODE 2
FRAMEBUFFER CREATE
FRAMEBUFFER LAYER

FRAMEBUFFER WRITE F           ' the background, drawn once
CLS RGB(BLUE)
BOX 20, 20, 120, 80, 2, RGB(WHITE), RGB(RED)

FRAMEBUFFER WRITE N
DO
  FRAMEBUFFER WRITE L
  CLS 0                        ' 0 is the transparent index
  CIRCLE x, 120, 30, 2, 1, RGB(YELLOW), RGB(YELLOW)
  FRAMEBUFFER WRITE N
  FRAMEBUFFER MERGE 0
  x = x + 4
LOOP WHILE INKEY$ = ""
```

`COPY` takes `L` at either end, so `COPY F, L` puts the background into the layer to draw over, and `COPY L, N` shows the layer on its own. `CLOSE L` gives it back; so does the end of the program.

**The transparent colour means what it means in the mode you are in.** In `MODE 2` a pixel is four bits, so it is a colour index from 0 to 15 and the merge keys on it per pixel. In `MODE 1` a pixel is one bit: transparent 0 means the layer's set pixels paint and its clear ones let `F` through, and transparent 1 is the other way round. Same command, same program, and `MODE 1` is the faster of the two.

**What it costs.** A merge waits for the top of the frame first, always — it writes into the buffer being scanned out, and starting part way down tears the picture once per merge. In `MODE 2` the

loop above runs at **16.62 ms a frame, 60 frames a second**, of which the drawing is 2.57 ms; the rest is the composite and the wait it is hidden behind. It is quantised by that wait, so a little more drawing costs nothing at all and too much costs a whole frame.

MERGE needs both buffers and says so — “Layer not created” if there is no layer, “Frame buffer not created” if there is no F — rather than doing half of it.

This is MMBasic’s TFT model, the one its ILI9341 builds use, so a program written for a PicoMite with a panel on it runs here unchanged. Its VGA and HDMI builds do the same compositing inside the scanline builder instead, continuously and without a command; that needs every buffer in the RAM the display DMAs from, which on this machine is 40K taken off every program forever, whether it uses a layer or not. The reasoning is written out in `PC3-LAYER-MERGE.md` in the source tree.

INKEY\$ returns the key that has been pressed, or "" if none has, without waiting — which is how the loop above ends. It leaves the terminal as it found it, so INPUT still works afterwards and a program stopped with Ctrl-C does not take the shell’s echo with it.

A cursor or function key reaches a terminal as an escape sequence of several bytes, and INKEY\$ reassembles it and gives back the single code MMBasic gives, so the PicoMite idiom works unchanged:

```
DO
  k$ = INKEY$
  IF k$ = CHR$(&H80) THEN PRINT "up"
  IF k$ = CHR$(&H91) THEN PRINT "F1"
LOOP UNTIL k$ = "q"
```

The codes are MMBasic’s: &H80–&H83 for up, down, left and right, &H84 insert, &H86 home, &H87 end, &H88/&H89 page up and down, &H7F delete, and &H91–&H9C for F1 to F12. A sequence it does not recognise comes back byte by byte behind its escape, so nothing is lost — and a bare ESC is still CHR\$(27).

## 6.14 Running another program: SYSTEM, SAVE IMAGE, LOAD IMAGE, LOAD JPG, LOAD PNG

SYSTEM runs a program and waits for it:

```
SYSTEM "sum", "a.bmp", "b.bmp"
```

Each argument is passed separately, so no shell quoting is involved and a filename with a space in it needs no special care.

SAVE IMAGE and LOAD IMAGE are built on it — they run the `saveimage` and `loadimage` programs described in the applications list, which means a BASIC program that never touches an image pays nothing for them:

```
SAVE IMAGE "shot.bmp"           ' the whole screen
SAVE IMAGE "part.bmp", 160, 120, 320, 240 ' x, y, w, h
LOAD IMAGE "shot.bmp"           ' at 0,0
LOAD IMAGE "shot.bmp", 160, 120  ' at x,y
```

LOAD IMAGE takes MMBasic’s full syntax including the dither mode and the source rectangle:

```
LOAD IMAGE fname$ [,x] [,y] [,mode] [,ximage] [,yimage] [,wimage] [,himage]
```

The decoder is MMBasic's, so it reads 1, 4, 8, 16, 24 and 32-bit BMPs, BI\_BITFIELDS, and RLE4/RLE8 compression. Dithering is *optional*, as in MMBasic — omit the mode and the image is mapped without it.

LOAD BMP is accepted as a synonym for LOAD IMAGE, as in the reference.

#### 6.14.1 LOAD JPG

```
LOAD JPG fname$ [,x] [,y] [,mode] [,ximage] [,yimage] [,scale]
```

MMBasic's own picojpeg, as the `loadjpg` program. `scale` is 1, 2, 4 or 8 and bins that many source pixels into one on screen, so a photograph larger than the display can be fitted to it. `ximage/yimage` take a region out of the middle of a larger picture.

Binning costs nothing extra: every MCU still has to be decoded, because a JPEG stream cannot be seeked into — only the drawing is reduced. A 320×240 photograph draws in about 0.45 s either way.

`mode` is the dither argument. It is *parsed and ignored*, for the reason given under LOAD IMAGE: error diffusion wants rows of signed error per channel, and this program runs while your BASIC program is still resident in memory.

#### 6.14.2 LOAD PNG

```
LOAD PNG fname$ [,x] [,y] [,transparent] [,cutoff]
```

MMBasic's own upng, as the `loadpng` program.

**transparent decides what happens to see-through pixels, and its default will surprise you the first time.** As in the reference it defaults to 0, which is the palette's black — so a PNG with a transparent surround lands on screen inside a black box. That is what a PicoMite does, and it is deliberate: the same default is what makes SPRITE LOADPNG work (see below). To let the screen show through instead, pass -1:

```
CLS RGB(255,255,255)
LOAD PNG "apple.png", 0, 0, -1      ' the white shows through
LOAD PNG "apple.png"               ' a black box around it
```

`cutoff` is the alpha value above which a pixel counts as opaque, 1 to 254, default 20.

Note that an *opaque* black pixel is drawn black whichever you choose — nothing can tell “background” from “black” once the alpha channel says opaque. If a picture has an unwanted dark surround even with -1, the file has an opaque background rather than an alpha one.

LOAD PNG needs the PSRAM arena and says so if a kernel cannot provide one. PNG cannot be decoded a piece at a time — its filters refer to the row above and its compressed stream is one window over the whole image — so the entire picture is inflated before any of it can be drawn: about 300 KB for a full screen, twice the whole process pool. The reference has the same constraint and offers LOAD PNG only on RP2350 for it.

### 6.15 Music: PLAY MP3, PLAY WAV, PLAY FLAC, PLAY SOUND, PLAY TONE, PLAY MODFILE

```
PLAY VOLUME 70
PLAY MP3 "/root/mp3/whiter.mp3"
' the program carries straight on, and the music plays
```

```

FOR i% = 1 TO 20
  PRINT "still working"; i%
  PAUSE 500
NEXT i%
PLAY STOP

```

PLAY MP3 does **not** wait. The decoder is a separate program feeding a 1.5-second buffer in the kernel, and the sound hardware empties that buffer by DMA, so playback needs nothing from your program once it has started. MMBasic has to refill its audio from the interpreter's idle loop; here there is no idle loop to do it in, and no cost when there is nothing to play. A translated benchmark measured **89% of its full speed** with a track playing.

PLAY WAV and PLAY FLAC are the same statement with a different decoder behind it, and behave the same way in every respect — they do not wait, PLAY STOP stops them, and PLAY VOLUME sets their level. WAV covers 8, 16, 24 and 32-bit PCM, IEEE float, A-law and mu-law, all converted to the 16 bits the hardware takes. FLAC is read at its own rate and bit depth; a 44.1 kHz 16-bit stereo file plays with no underruns while the machine is otherwise idle.

One thing to know about FLAC in particular: its decoder is sized from the file, at roughly `maxBlockSize x 4 x channels`, so a file written with 4096-sample blocks wants about 32K and one written with 16384 wants about 132K — out of a pool of 336K shared with everything else running. A file that will not open says so, and says how much it wanted, rather than failing silently.

PLAY VOLUME *n* takes 0 to 100 and is remembered, so every later PLAY MP3, PLAY WAV or PLAY FLAC uses it until it is changed again. Out-of-range values are clamped rather than refused. The default is 80. The scale is logarithmic, so 50 is a comfortable half rather than a whisper.

PLAY STOP stops whatever is playing. It asks the kernel which process holds the sound output rather than remembering what it started, so it also stops a player left running by a program that was stopped with Ctrl-C — which is the situation it is most often wanted for. Stopping when nothing is playing is not an error, as in MMBasic.

There is one sound output, so there is one player:

**Error: sound output in use**

is what PLAY MP3 gives if something is already playing. Use PLAY STOP first. (This is MMBasic's "Sound output in use for ..." under a shorter name.) The rule is enforced by the kernel rather than by convention: two decoders writing into the same buffer interleave their samples, and it sounds like it.

Files play at their own sample rate — 8 kHz to 48 kHz, mono or stereo, and a mono file costs nothing extra because the driver duplicates the channels itself. Copy MP3s onto the FAT partition from a PC and bring them over with `fat get`, as with any other file.

PLAY and BBC BASIC's SOUND share one piece of hardware and are mutually exclusive, exactly as they are in MMBasic. Starting a track silences the synthesiser; stopping it hands the hardware back.

### 6.15.1 The synthesiser: PLAY SOUND and PLAY TONE

```

PLAY SOUND 1, B, S, 440, 15      ' voice 1, both sides, sine, 440 Hz
PLAY SOUND 2, B, Q, 220, 10      ' a square underneath it
PAUSE 1000

```

```
PLAY SOUND 1, B, 0           ' voice 1 off
PLAY TONE 440, 554, 600      ' left/right pair for 600 ms
```

MMBasic's four-voice synthesiser, rendered by the kernel itself in the audio interrupt that drives the DAC — the same place MMBasic renders it. Four voices, each with an independent left and right side; channels are L, R, B or M, and the types are Sine, Q (square), Triangle, W (sawtooth), Periodic noise, N (white noise) and Off. Frequency is 1 Hz to 20 kHz, volume 0 to 25. `PLAY TONE` takes left and right frequencies and an optional duration in milliseconds, rounded down to whole cycles as MMBasic rounds it; no duration means until further notice. The square and sawtooth are band-limited (polyBLEP), so they hold a pure pitch at the top of the range instead of shimmering.

Channel and type may be written as a bare letter, a quoted letter or a string worked out at run time, as MMBasic writes them: `PLAY SOUND 1, B, S, 440`, `PLAY SOUND 1, "B", "S", 440` and `PLAY SOUND 1, c$, t$, 440` are the same statement.

**A change of note is heard at once.** Until v0.15 the synthesiser was a separate program rendering ahead into a queue, which put a fifth of a second between the statement and the sound — audible as lag in a game, and the reason a program changing pitch every 20 ms could not work at all. It now runs where MMBasic runs it, in the interrupt that feeds the DAC, so a `PLAY SOUND` is in the next buffer the hardware asks for: under two milliseconds. The voices go quiet by themselves after five seconds with every voice off, or on `PLAY STOP`, and a program that ends — including one stopped with `Ctrl-C` — takes its sound with it.

### 6.15.2 Modules: `PLAY MODFILE` and `PLAY MODSAMPLE`

```
PLAY MODFILE "/root/ptetris.mod"
PAUSE 5000
PLAY MODSAMPLE 3, 4           ' fire sample 3 on channel 4, over the music
PLAY STOP
```

`PLAY MODFILE` plays ProTracker modules at 22 kHz through the `hxcmod` tracker, the whole file staged in PSRAM. Like MP3 it runs as its own program and does not wait. `PLAY MODSAMPLE n, ch [, vol]` asks the *running* player to mix one of the module's own samples over the music - MMBasic's game sound-effect trick - with nothing loaded and nothing interrupted. With a completion interrupt the module plays once; otherwise it loops until `PLAY STOP`.

### 6.16 Pins: `SETPIN` and `PIN`

```
SETPIN 2, DOUT
SETPIN 3, DIN
PIN(2) = 1
IF PIN(3) = 1 THEN PRINT "high"

SETPIN 41, AIN           ' analogue, in volts
PRINT PIN(41)            ' 1.677936508
SETPIN 41, ARAW           ' analogue, raw
PRINT PIN(41)            ' 2090
```

All **forty-eight** GPIOs of the RP2350B are available — the wider part is why the PC3 can put the real-time clock's alarm on GP32, which a 28-pin RP2040 could not reach.



`n` is the **GPIO number**, not MMBasic's connector-pin numbering. The GPIO number is what the schematic, the kernel, and every other tool on this machine use, and inventing a second numbering for one statement would cause more confusion than the incompatibility does.

SETPIN takes:

| mode | what the pin becomes                                          |
|------|---------------------------------------------------------------|
| DIN  | a digital input                                               |
| DOUT | a digital output, driven by <code>PIN(n) = v</code>           |
| AIN  | an analogue input read as <b>volts</b>                        |
| ARAW | an analogue input read as the <b>raw 0–4095 count</b>         |
| INTH | a digital input that calls a SUB on a <b>low-to-high</b> edge |
| INTL | ... on a <b>high-to-low</b> edge                              |
| INTB | ... on <b>either</b> edge                                     |
| PWM  | a PWM output, driven by the PWM statement                     |
| OFF  | not configured                                                |

MMBasic's remaining modes — frequency and counting — are not translated, and are reported by name.

Input modes take MMBasic's optional pull:

```
SETPIN 2, DIN, PULLUP
SETPIN 3, DIN, PULLDOWN
SETPIN 35, INTL, Pressed, PULLUP      ' after the handler
```

Absent means neither, which is MMBasic's default — a floating input then reads whatever the wire is doing, and with nothing connected that is noise. A switch to ground wants PULLUP.

**Hysteresis is always on for inputs.** It is not an option in MMBasic either: every digital input it configures gets the Schmitt trigger, and so does every one here. On a board with header pins and flying leads a slow or noisy edge is the normal case.

AIN and ARAW need an ADC pin: on the RP2350B channel `n` is `GP40+n`, so **GP40–GP46** on the I/O header. Anything else gives `Pin cannot do that`.

The two analogue modes differ only in what `PIN()` gives back. ARAW is a single conversion, which is what you want when you are going to do your own filtering or you care about speed. AIN is MMBasic's filter, step for step: ten readings, sorted, the top two and bottom two thrown away, and the remaining six averaged and scaled by 3.3 V. The point of it is the *discard* — one wild sample is dropped rather than smeared across the answer, which plain averaging would do. (MMBasic's `OPTION VCC` is not supported, so the scale is always 3.3 V.)

`PIN()` returns a **float in every mode**, where MMBasic returns an integer for digital pins and ARAW. Nothing observable changes — `PRINT PIN(2)` still prints 1, and comparisons and array indices behave the same — because a double holds 0, 1 and every 12-bit count exactly. The reason is that translated C has to know the type when it is generated, and nothing at that point knows what mode a pin will be in.

**Pins are now owned.** SETPIN claims the pin from the kernel, and claiming one that another program holds gives `Pin cannot do that` rather than quietly fighting over it. The claim is released

— and the pin **reset to an input** — when your program ends, however it ends, including being killed or crashing. So a program that dies driving a relay does not leave it driven.

Only the I/O header can be claimed: **GP0–GP7, GP26 and GP34–GP46**, plus **GP32**. The rest belong to the board (display, SD card, PSRAM, sound, console, the DS3231's I2C), and asking for one gives `Pin cannot do that` instead of taking a pin the audio hardware is driving. Appendix A lists what the board uses. A pin number outside 0–47 gives `Invalid pin`.

GP32 is not on the header — it is the **DS3231's alarm output**, and an alarm nothing can read is not an alarm. It is open-drain and active low, so with a pull-up it reads 1 until the alarm asserts:

```
SETPIN 32, DIN, PULLUP
PRINT PIN(32)                ' 1 = not asserted

SETPIN 32, INTL, WakeUp, PULLUP ' fires when it does assert
```

### 6.16.1 Arming the alarm

MMBasic has no alarm command — a program writes the chip's registers, and so does this:

```
SUB Alarm
  hits = hits + 1
  RTC SETREG 15, 0          ' clear the flag, or it never fires again
END SUB

RTC SETREG 7, 128          ' alarm 1 masks: match nothing = every second
RTC SETREG 8, 128
RTC SETREG 9, 128
RTC SETREG 10, 128
RTC SETREG 15, 0           ' clear any stale flag
RTC SETREG 14, 5           ' INTCN | A1IE - drive INT, enable alarm 1

SETPIN 32, INTL, Alarm, PULLUP
```

`RTC GETREG reg, var` and `RTC SETREG reg, value` reach any of the DS3231's registers, which is MMBasic's own interface (it has `GETREG` and `SETREG` and no alarm command). Register 7–10 are alarm 1, 0x0E is control, 0x0F is status. The chip's data sheet is the reference.

**Your handler must clear the alarm flag.** The INT line stays low until it is, so an alarm that does not clear it fires once and then looks broken.

Two things this cannot do. It will not stop the oscillator — a write to the control register comes back with `EOSC` masked out, because on a battery-backed part a stopped clock outlives the power cycle and the machine boots not knowing the time. And it is not `/dev/i2c:` that driver refuses address 0x68 outright, so this goes through the kernel's own path to the chip, sharing the retry and recovery the system clock already relies on.

On a **Pico Computer 2** GP32 is the SD card's MISO instead, so the same kernel refuses to hand it out there — the board tells itself apart at boot. This is the one pin whose availability depends on which machine you are running on.

`PIN(n) = v` on a pin that is not a `DOUT` gives `Pin is not an output`, and reading a pin that has never been `SETPINed` gives `Pin is not an input` — both as MMBasic does.

Pin work no longer costs a system call. `SETPIN` makes one, once, to claim; after that `PIN(n)` and `PIN(n) = v` are single register accesses, about ten nanoseconds against the 1.5  $\mu$ s an `ioctl` costs. That is what makes bit-banging a protocol in BASIC possible at all — and it is not a theoretical claim: `ONEWIRE` is bit-banged that way, in slots of 60  $\mu$ s with a 10  $\mu$ s sample point inside them, which an `ioctl` per edge could not have fitted twice over.

## 6.17 Pin interrupts

```
SUB Pressed
```

```
    PRINT "GP35 went ";PIN(35)
END SUB
```

```
SETPIN 35, INTB, Pressed      ' either edge
DO
    ' ... ordinary work; the handler runs between statements
LOOP
```

The handler is an ordinary `SUB` taking no parameters, and it ends with `END SUB`. **There is no `IRETURN to write`** — that is MMBasic’s behaviour too, not a simplification: for a `SUB` target MMBasic builds an `IRETURN` of its own and uses it as the return address of the `GOSUB` it fakes, so `END SUB` performs the interrupt return. Written `IRETURN` only ever existed for targets given as a label or a line number, and those are not translated: compiled code cannot jump into the middle of a function, so a label or line number is refused with a clear message rather than half-working.

**These are not hardware interrupts, and they are not in MMBasic either.** The whole facility is a poll. MMBasic’s interpreter checks after every statement, and pin “interrupts” there are a comparison of the pin’s level against its level at the previous check — there is no GPIO IRQ anywhere in it. This does the same thing at the same place, so the behaviour you get is the behaviour a PicoMite gives:

- **Latency is one statement**, and a statement is atomic. Nothing ever runs half a statement of your program.
- **A pulse shorter than a statement is missed.** That is MMBasic’s documented limitation, replicated rather than “fixed”.
- **Interrupts never nest.** A handler’s own statements are polled, but the poll does nothing while a handler is running.
- **One handler runs per statement boundary.** If two pins change at once, the second fires at the next statement.
- `MM.ERRNO` and `MM.ERRMSG$` are **saved, cleared and restored** around a handler, so a handler starts clean and cannot leave an error behind for the interrupted code to trip over.

Up to ten pins may have interrupts, which is MMBasic’s own limit. The level a handler reads with `PIN(n)` is the level *now*, not the level that triggered it — with a mechanical switch the two often differ, because contacts bounce faster than the handler starts. MMBasic reads it the same way.

A program that arms no interrupt pays nothing at all: the per-statement poll is emitted only for programs that use the feature, exactly as the `ON ERROR` checks are.

## 6.18 PWM

```
SETPIN 0, PWM          ' GP0 is slice 0, channel A
PWM 0, 1000, 25         ' slice 0: 1 kHz, 25% on channel A
PWM 0, 1000, 25, 75     ' ...and 75% on channel B
PWM 0, 1000, -25        ' negative duty = inverted output
PWM 0, OFF
```

SETPIN pin, PWM attaches a pin to its PWM output; the PWM statement then drives the **slice**, not the pin. One slice has two channels and drives two pins, which is why the two commands are separate — the same split MMBasic uses.

Which slice a pin belongs to is arithmetic: pins below GP32 use slice  $(\text{pin} \div 2) \bmod 8$ , and GP32 upward use  $8 + ((\text{pin} \div 2) \bmod 4)$ . Even pins are channel A, odd pins channel B. **Twelve slices cover forty-eight pins, so pins alias:** GP34 and GP42 are the same slice and channel, and setting one sets the other. SETPIN pin, PWM claims the slice as well as the pin, so a second program asking for a pin that lands on a slice you hold is told **Pin cannot do that** rather than quietly changing your frequency.

Frequency is in Hz and duty in percent, and the range is wide: 100 kHz and 50 Hz both work. Below about 5.7 kHz the 16-bit counter cannot hold a whole period at 375 MHz, so the clock divider takes up the slack — that happens automatically, and the only sign of it is that very low frequencies have coarser duty resolution. Asking for something the divider cannot reach either gives **Invalid frequency**.

A **negative duty** inverts that channel's output: -25 is 25% inverted, so the pin reads high 75% of the time. It is the channel's polarity bit, not a recomputed duty.

PIN() will not read a PWM pin — it is an output, and MMBasic refuses it too.

**Giving only one duty leaves the other channel alone.** That is not a detail: two outputs share a slice, so PWM 0, 1000, 25 must not stop whatever is running on channel B.

## 6.19 SERVO

```
SETPIN 0, PWM
SERVO 0, 50          ' centre
SERVO 0, 0, 100      ' two servos on one slice, opposite ends
SERVO 0, OFF
```

A servo is PWM at a fixed 50 Hz frame with the position expressed as a pulse width, so SERVO is PWM with one line of arithmetic in front of it — MMBasic's:

| position | pulse  |               |
|----------|--------|---------------|
| 0        | 1.0 ms | one end       |
| 50       | 1.5 ms | centre        |
| 100      | 2.0 ms | the other end |
| -20      | 0.8 ms | over-travel   |
| 120      | 2.2 ms | over-travel   |

The range is -20 to 120, which is the over-travel most servos will accept; outside it you get **Invalid**

`servo position`. Everything else is the PWM statement, including the rule that omitting the second position leaves that channel alone — which is what lets two servos share a slice.

Scope-verified on GP0 at all five positions.

## 6.20 SETTICK — periodic timers

```
SUB Every100
  INC count
END SUB
```

```
SETTICK 100, Every100      ' every 100 ms
SETTICK 100, Every100, 2   ' timer 2 of 4
SETTICK PAUSE, 2           ' freeze it where it stands
SETTICK RESUME, 2
SETTICK 0, 0, 2            ' off
```

Four timers, numbered 1 to 4, period in milliseconds — MMBasic’s `NBRSETTICKS`. The number is optional and defaults to 1. The handler is a parameterless SUB, as for pin interrupts, and everything said above about them applies here too: it runs between statements, it does not nest, and one interrupt is dispatched per statement boundary. A pin edge and a tick falling due at the same moment dispatch the pin first, which is MMBasic’s scan order.

**Missed ticks are dropped, not queued.** If a handler takes longer than its own period, the timer catches up by whole periods and fires once — so a slow handler cannot spiral into a backlog it never clears. The phase is kept, so the cadence does not drift.

Measured on the board: twenty ticks of 100 ms took **1999.98 ms**, and a 10 ms timer running beside a 50 ms one fired exactly 100 times in the second the slow one took to reach twenty.

## 6.21 ON KEY — the console

```
SUB AnyKey
  k$ = INKEY$              ' the key is still there for you
END SUB
```

```
SUB QuitKey                ' fires on "q" only, and eats it
  finished = 1
END SUB
```

```
ON KEY AnyKey              ' any key
ON KEY 113, QuitKey        ' just this one
ON KEY 113, 0              ' that one off
ON KEY 0                   ' the any-key one off
```

Two forms, and **what happens to the key is the difference between them** — this is MMBasic’s design, not an accident of ours:

- **ON KEY handler** fires while a key is *waiting*, and the key stays waiting. Your handler reads it with `INKEY$`. If it doesn’t, the handler fires again at the next statement, because the key is still there.

- **ON KEY code, handler** fires only on that character code, and **consumes** it. It never reaches **INKEY\$**, so a key reserved for a hot-key handler cannot also turn up in the program's ordinary input.

The specific form is checked first, so with both armed the reserved key goes to its own handler and everything else goes to the general one.

Two things to know before relying on it:

**The console is checked at most every 5 ms**, not after every statement. Looking is a system call, and a poll site runs after every statement; checking each time would cost far more than most statements do. Five milliseconds is the kernel's own tick and far below what anyone can type or perceive, but it is a divergence from MMBasic, which looks every time.

**A program reading keys holds the terminal**, and that has visible consequences worth knowing.

The console has a line editor in front of it — the thing that gives you history and cursor keys at the shell prompt. It takes every keystroke while the terminal is in cooked mode with echo, and hands over a finished line only when you press Enter. A program that wants *keystrokes* has to stand it down, so the first **INKEY\$** or armed **ON KEY** puts the terminal into raw mode and **keeps it there** for the rest of the program.

While it is held:

- **keys are not echoed** — nothing appears on screen unless your program prints it. This is MMBasic's behaviour for **INKEY\$** too.
- **there is no line editing** — no backspace, no history, no cursor keys. Each keystroke goes straight to the program.
- **INPUT still works normally**. It gives the terminal back for the duration of the question and takes it again afterwards, so a program can mix **INKEY\$** with **INPUT** and the typed answer is edited and echoed as usual.
- the terminal is **restored when the program ends**, however it ends.

This is what BBC BASIC and the editors on this machine already do.

## 6.22 KEYDOWN — which keys are *held*

**INKEY\$** tells you what was **typed**. **KEYDOWN** tells you what is **down right now**, and for a game that is a different question: a character stream has no way to say “up and fire together”.

DO

```

IF KEYDOWN(0) THEN                                ' anything at all held?
  FOR i = 1 TO KEYDOWN(0)
    k = KEYDOWN(i)                                ' 1 is the most recent
    IF k = 128 THEN y = y - 1                       ' up
    IF k = 129 THEN y = y + 1                       ' down
    IF k = 130 THEN x = x - 1                       ' left
    IF k = 131 THEN x = x + 1                       ' right
    IF k = 32 THEN Fire                             ' ... at the same time
  NEXT i
ENDIF
LOOP
```

| argument                  | answer                                                                                                       |
|---------------------------|--------------------------------------------------------------------------------------------------------------|
| KEYDOWN(0)                | how many keys are held, 0 to 6                                                                               |
| KEYDOWN(1) ... KEYDOWN(6) | the code of the <i>n</i> th, 1 being the most recent                                                         |
| KEYDOWN(7)                | modifier bitmap: 1 left Alt, 2 left Ctrl, 4 left GUI, 8 left Shift, and 16/32/64/128 for the right-hand four |
| KEYDOWN(8)                | locks: 1 caps, 2 num, 4 scroll                                                                               |

**Six is the hardware's limit, not ours.** A USB keyboard's boot report carries six concurrent key codes, which is exactly the six MMBasic exposes, so this is the report itself rather than anything reconstructed. Most keyboards also refuse certain three-key combinations for reasons of their own wiring; that is the keyboard, and no software can see past it.

**KEYDOWN empties the type-ahead buffer**, exactly as MMBasic does. That is not tidiness: a held key still sends characters, and a game that read only KEYDOWN would otherwise pile up minutes of them behind the terminal, to be delivered to the shell the moment it exited. The consequence is that KEYDOWN and INKEY\$ are **alternatives, not layers** — whichever asks first gets the keystroke. Pick one per program.

Like INKEY\$, the first KEYDOWN puts the terminal in raw mode and holds it, with everything the section above says about that.

## 6.23 Asking the machine about itself: MM.INFO

```
PRINT MM.DEVICE$           ' Fuzix
PRINT MM.INFO(PLATFORM)    ' PC3   (or PC2)
PRINT MM.INFO(VERSION)     ' same number as MM.VER
```

MM.DEVICE\$ is "Fuzix" — **the firmware, and nothing else**. MMBasic answers with its build (PicoMiteVGA, PicoMiteHDMIUSB), and a program's whole use of it is to pick a path: IF INSTR(MM.DEVICE\$, "PicoMite"), IF INSTR(MM.DEVICE\$, "VGA"). Every one of those questions has the answer "no" here, and one word says so cleanly enough to test with a plain comparison. **Which machine** it is has moved to MM.INFO(PLATFORM), which is where MMBasic keeps it too — DEVICE is the firmware, PLATFORM is the board.

MM.INFO(...) and MM.INFO\$(...) are the same function, as in MMBasic: the sub-keyword decides the type, not the \$.

| sub-keyword     | answer                                                          |
|-----------------|-----------------------------------------------------------------|
| DEVICE          | "Fuzix"                                                         |
| PLATFORM        | "PC3" or "PC2"                                                  |
| VERSION         | the release, as MM.VER                                          |
| PATH            | the directory the running program was started from, ending in / |
| CURRENT         | the program's own file name                                     |
| DRIVE           | always "A:" — see below                                         |
| EXISTS FILE f\$ | 1 a file, <b>-1 a directory</b> , 0 nothing there               |
| EXISTS DIR d\$  | 1 if it is a directory                                          |

| sub-keyword                     | answer                                                 |
|---------------------------------|--------------------------------------------------------|
| FILESIZE f\$                    | bytes; -1 nothing there, -2 a directory                |
| OPTION BASE                     | 0 or 1                                                 |
| PINNO "GP8"                     | the pin a name stands for                              |
| FONTHEIGHT, FONTWIDTH           | the current font's cell <b>times the current scale</b> |
| HPOS, VPOS                      | the graphics text cursor                               |
| ERRNO, ERRMSG                   | as MM.ERRNO and MM.ERRMSG\$                            |
| FLAGS                           | all sixty-four scratch bits                            |
| FONT ADDRESS n, FLASH ADDRESS n | as before                                              |

MM.FONTHEIGHT, MM.FONTWIDTH, MM.HPOS and MM.VPOS are the flat spellings of four of those, and MMBasic has both — a program may write either.

**DRIVE is always "A:", and that is not a pretence.** This machine has one filesystem and no drive letters. Programs that ask save the drive, do a file operation and put it back; a constant answer makes that round trip *correct* rather than merely harmless.

**The -1 from EXISTS FILE is MMBasic's own**, and it earns its keep: it is how a program tells “that name is a directory” from “there is nothing there” without a second call.

FONTHEIGHT and FONTWIDTH follow FONT, and include the scale — so INC y, MM.INFO(FONTHEIGHT) + 1 moves down one line whatever font is selected, which is what the shape is for.

Everything else MMBasic's MM.INFO reports is about hardware, a flash program store or a network that is not here.

## 6.24 Pin names: GP8

Wherever a pin is expected you may write its **name** instead of its number:

```
SETPIN GP4, DIN, PULLUP
IF PIN(GP4) = 0 THEN PRINT "pressed"
x = PORT(GP0, 8) ' GP0..GP7 as one number
n = MM.INFO(PINNO "GP" + STR$(i)) ' ... or build the name at run time
```

On this machine a pin **is** its GPIO number, so GP8 is simply 8 — MMBasic needs a lookup table here because its pin numbers are connector pins. A variable you have declared with that name still wins.

This closes a trap rather than only adding convenience. Before it, GP8 in a program without OPTION EXPLICIT became an implied variable worth zero, so PIN(GP8) quietly read GP0 — a wrong pin, with nothing said. A silent divergence outranks a missing feature, and this one is now neither.

## 6.25 Timers and the deliberate divergence

The 100 ms figure above is the one **deliberate divergence** from MMBasic, and it is in your favour. MMBasic counts milliseconds in an interrupt and fires when the count is *greater than* the period, so a SETTICK 100 there actually runs at 101 ms and a 16 ms game timer at 17 ms — about 6% slow. This keeps a microsecond deadline instead of a millisecond counter and fires at the period you asked for. Nothing else about the behaviour differs; if you are porting a program whose timing was tuned against a PicoMite, it will run very slightly faster here.



Every read and write is a call into the kernel — comparable to drawing one pixel, which is over a microsecond. That is ample for a switch or an LED and nowhere near enough to bit-bang a protocol; write that in C, or use the hardware that already exists for it.

## 6.26 Practical notes

- One `.bas` file per program, because `cc` compiles one file per program. `Subs` and `Functions` all live in that file.
- The C file is a normal file — you can keep it, edit it, or hand it to `cc` on another day.
- `mmbc` and `cc` each need a little room. On a machine with other things running, a large program is happier if you are not also holding a big file open in an editor.
- Programs built this way are the same objects `cc` produces from hand written C, so `bcdump` disassembles them and `BCRUN_BYTECODE=1` forces interpretation for comparison.

## 6.27 A worked example: a barometric station

Everything in this chapter, on one screen. The program is `qnh.bas` in `/root/MMBasic`; what follows is how it is built rather than a listing of it.

It reads a BMP180 barometer, a potentiometer and the clock, and puts the results on an ILI9341 panel that the firmware has never heard of — including the text, drawn from the built-in fonts:

|      |      |      |       |     |      |                          |
|------|------|------|-------|-----|------|--------------------------|
| GP2  | SCLK | GP3  | MOSI  | GP4 | MISO | the panel                |
| GP5  | DC   | GP6  | RESET | GP7 | CS   | its control lines        |
| GP0  | LED  |      |       |     |      | backlight, PWM slice 0   |
| GP38 | SDA  | GP39 | SCL   |     |      | I2C2, the BMP180 at &H77 |
| GP41 |      |      |       |     |      | the potentiometer wiper  |

Build and run it the usual way:

```
# mmbc qnh.bas
# cc qnh.c
# ./qnh.bc
```

### 6.27.1 What it is for

A barometer reads the pressure where it is standing. Weather reports quote pressure **reduced to sea level**, because otherwise a reading would say more about your altitude than about the weather — the difference is about 12 hPa per hundred metres, which is the gap between a settled day and a gale.

The reduction needs to know how high you are, and that is what the potentiometer sets. The formula is the one in the BMP180's own datasheet, inverted:

$$\text{qnh} = \text{pHPa} / (1 - \text{alt} / 44330.0) ^ 5.255$$

The result is QNH: what an altimeter should be set to so it reads height above sea level.

### 6.27.2 Reading the sensor

The BMP180 arithmetic is Bosch's, out of the datasheet, and the program uses MMBasic's own BMP180 listing unchanged apart from the bus — the part is on the I/O header rather than the QWIIC socket, so `SETPIN` names the pins and `I2C2` opens the second controller:

```

SETPIN 38, 39, I2C2
I2C2 OPEN 400, 1000
I2C2 WRITE &H77, 1, 1, &HAA      ' the calibration block
I2C2 READ  &H77, 0, 22, i2cin$
ac1 = STR2BIN(int16, MID$(i2cin$, 1, 2), big)

```

Twenty-two bytes of calibration come back as a string and STR2BIN picks signed and unsigned, big-endian words out of it.

### 6.27.3 Reading the potentiometer

One line of setup, because AIN is MMBasic's:

```

SETPIN 41, AIN
alt = INT(PIN(41) / 3.3 * 1000 + 0.5)

```

PIN on an AIN pin gives volts: ten readings, sorted, the top two and bottom two discarded and the remaining six averaged, scaled 3.3 V over 4095 — MMBasic's filter, constant for constant. On the RP2350B channel  $n$  is GP40 +  $n$ , so GP41 is channel 1.

One ADC count is about a quarter of a metre over a 1000 m range, so the program ignores movements below two metres. A display that flickers between 141 and 142 is worse than one that is a metre out.

### 6.27.4 Drawing text on a panel the firmware does not know

This is the part that needs **MM.INFO(FONT ADDRESS)**. The fonts are cached once — address, cell and range, every value read out of the font's own header:

```

FOR f = 1 TO 9
  a = MM.INFO(FONT ADDRESS f)
  fadr(f) = a
  IF a <> 0 THEN
    fwid(f) = PEEK(BYTE a)
    fhgt(f) = PEEK(BYTE a + 1)
    ffst(f) = PEEK(BYTE a + 2)
    fcnt(f) = PEEK(BYTE a + 3)
  ENDIF
NEXT f

```

Drawing one character is then: find its glyph, set the panel's window to exactly one cell, and write the rows. The window is set once and the panel advances by itself, so a glyph costs one address round trip and one write per row rather than one per pixel:

```

g = fadr(f) + 4 + (c - ffst(f)) * w * h \ 8
setwin(x, y, x + w - 1, y + h - 1)
FOR row = 0 TO h - 1
  px$ = ""
  FOR col = 0 TO w - 1
    bidx = row * w + col
    bval = PEEK(BYTE g + bidx \ 8)
    IF (bval >> (7 - (bidx AND 7))) AND 1 THEN
      px$ = px$ + ink$
    ENDIF
  NEXT col
NEXT row

```

```

        ELSE
            px$ = px$ + paper$
        ENDIF
    NEXT col
    SPI WRITE w * 2, px$
NEXT row

```

ink\$ and paper\$ are two-byte RGB565 pixels built once per call, so the inner loop appends rather than converting.

A row is `width × 2` bytes, which is why this works within the 255-byte string limit: 32 bytes for the 16×24 font, 48 for the 24×32. A whole glyph would not fit — the 16×24 one is 768 bytes — but a row always does.

### 6.27.5 Two traps this example exists to show

**The panel does not refuse a window wider than itself.** It clamps the window and still accepts every pixel you write into it, so the surplus wraps onto the next row and the character comes out as noise. Fifteen characters of the 16-pixel font is 240 pixels — the whole panel — so a title starting at `x=8` loses its last letter into the row below. The program therefore drops a glyph that would overhang rather than drawing it:

```

gx = x + (i - 1) * w
IF gx + w > SW THEN EXIT FOR

```

Silently short is a layout mistake you can see. Silently wrapped looks like a bug in the font reader, and will cost you an evening.

**Mid grey is not visible.** RGB565 &H8410 is a perfectly reasonable grey and reads as almost nothing on this panel at 70 % backlight. &HBDF7 — about three quarters — is legible. Colours that look fine in a table do not always survive a real display, and there is no substitute for looking at it.

### 6.27.6 What the translation looks like

`MM.INFO(FONT ADDRESS f)` becomes a runtime call and `PEEK` becomes a load, which is the whole point of the exercise — the address is not marshalled anywhere, it is used:

```

v_a = mm_fontaddr(v_f);
H->v_fadr[(int)(v_f)] = v_a;
if (((v_a) != (0LL))) {
    H->v_fwid[(int)(v_f)] = mmpk_byte(v_a);
    H->v_fhgt[(int)(v_f)] = mmpk_byte(((v_a) + (1LL)));
    H->v_ffst[(int)(v_f)] = mmpk_byte(((v_a) + (2LL)));
    H->v_fcnt[(int)(v_f)] = mmpk_byte(((v_a) + (3LL)));
}

```

(`H->` is where arrays and strings live — one allocation the program owns, rather than globals.)

and `mmpk_byte` is one line in `mmb_peek.h`:

```

MMG_FN MMINTEGER mmpk_byte(MMINTEGER addr)
{

```

```

    return (MMINTEGER)*MMPK_PTR(unsigned char, addr);
}

```

Reading font data compiles to a `ldrb`. There is no MMU to go through, no copy, and no system call — the flash the kernel keeps its fonts in is simply memory that this program can read.

The whole program is 15 KB of BASIC and compiles to about 63 KB of bytecode.

## 6.28 Making a big program fit — and run fast

A compiled program pays for its size twice. First there is the obvious budget: a process gets about 330 KB, `bcrun` and its working space take about 170 KB of that, and what remains holds your code (which expands about  $1.8\times$  when it is translated to native ARM), your variables and your stack. Second, and less obvious: any single `Sub`, `Function` or main line whose bytecode exceeds the translator's buffers stays **interpreted**, which runs about  $2.7\times$  slower — and the main line, the part between the top of the file and the first `Sub`, is compiled as one function. A game whose whole loop lives in the main line can grow that one function past the cap and end up with its hottest code being its slowest.

The rules below come from porting PicoMan (Geoff Graham's PacMan, 1,250 lines, graphics-heavy). As it arrived it compiled to 101 KB of bytecode with a 63 KB main line — too big to translate, too big to load fully native. With the compiler taught the rule below it is 38 KB, every function translates, and the whole game images at 134 KB — unmodified. Numbers below are from that exercise. Compute-heavy programs rarely hit any of this — the solar eclipse benchmark has never been near a limit — because number crunching lives naturally in functions over a few variables. Games are different: they draw, and they grow main lines.

**1. ON ERROR IGNORE is the most expensive statement in the language.** For an error to be *survivable*, the compiler must emit checked arithmetic — every array index, every division — so the error is reported rather than corrupting memory. `ON ERROR IGNORE` arms that for an unbounded stretch of the program, so its presence anywhere makes the **whole program** pay: about  $2.6\times$  on code size (it was 62 of PicoMan's 101 KB while the compiler still treated every `ON ERROR` this way). `ON ERROR SKIP [nn]`, by contrast, covers only the next `nn` statements, and the compiler emits the checked forms for exactly that window — PicoMan's one `On Error Skip` over a first-time `Blit Close` costs a few dozen bytes, not sixty thousand. So: prefer `SKIP` with a literal count, tightly around the fallible statement, and keep `IGNORE` for short probe programs. Two prints of `MM.ERRNO` cost less than one `IGNORE`. One care with `SKIP` in a compiled program: the interpreter's count follows execution into a called `SUB`, statement by statement, while the compiled window covers the statements *written* after the `ON ERROR SKIP` (plus one for each routine entered) — a skip that relies on being consumed deep inside a callee's arithmetic behaves like the interpreter only under `IGNORE`. Runtime command errors — a `Blit Close` on nothing, a missing file, an I2C device that does not answer — are trapped anywhere the count is armed, in either world.

**2. Keep the main line thin.** The main line is one function, and a function only runs at full speed if it translates. Put the work in `Subs` and `Functions` and keep the main line to setup and a loop that calls them. A web of `GOTO`s pins code into the main line; `GOTO` is fine within a routine, but reaching a block only by `GOTO` keeps it — and everything it drags in — in the one function that must stay small.

**3. Locals are cheaper than globals.** Every reference to a global variable costs a 5-byte address in bytecode and 8-10 bytes translated; a `Local` or a parameter costs 2-3 and often 2-4. Before its

rework, 36% of PicoMan’s main line was global addressing. In a **Sub**, declare scratch variables **Local**; pass coordinates as parameters rather than parking them in globals.

**4. Fold repetition into a Sub.** Drawing statements are the widest statements in the language — every argument is a 64-bit expression that must be built and pushed, so one seven-argument **Circle** costs 120-140 bytes *each time it appears*. Four near-identical **Triangle** statements for four directions are one **Sub** with parameters. This is ordinary factoring, but on this machine it is also how the code stays under the translation caps.

**5. DATA is nearly free; code is dear.** DATA values go to the data segment byte-for-byte (unused columns are pruned), and reading them is cheap. A table beats a computed unroll: PicoMan’s 42 KB shortest-path database costs almost nothing in code, while the same information as **If** chains would be enormous.

**Seeing where you stand.** `ls -l prog.bc` gives the object size. `THUMB_VERBOSE=1 cc prog.c` prints one line per function — **native: name (bytecode -> native bytes)** — and, for any function that stayed bytecode, the reason: **size policy** means it was too big to translate, and that function will run interpreted. A program that is still too big to load can be built `BCODE_ONLY=1 cc prog.c`: about 2.7× slower, but roughly a third the code.

## 7 mmedit: MMBasic's editor

MMBasic's full-screen editor is ported and runs as an ordinary Fuzix program, so BASIC is written, translated, compiled and run without leaving the machine:

```
# mmedit prog.bas
```

It is the editor from the firmware, with the same keys:

| Key           |                                                  |
|---------------|--------------------------------------------------|
| ESC           | leave the editor                                 |
| F1            | save                                             |
| F2            | save and exit (so a wrapper can run the program) |
| F3 / F6       | find / find again                                |
| F4            | mark — then the cursor keys extend the selection |
| F5            | paste                                            |
| F7 / F8       | replace / replace again                          |
| F9 / F10      | read a file in / write the selection out         |
| F12 or Ctrl-A | beautify: re-indent and case the keywords        |

In mark mode the legend changes: DEL deletes, F4 cuts, F5 copies, F10 exports the selection to a file. The status line shows line, column and INS/OVR, and the function key legend shortens itself to fit the terminal width.

**The colour coding answers “will this compile?”** A keyword `mmbc` can translate is cyan; one only the interpreter knows is blue. That second colour is the useful one here, because a program is compiled rather than run as you type it, and it is worth seeing `MM.WATCHDOG` or `REDIM` in blue before you build rather than after. The lists come from the translator's own tables, so they cannot drift from what it does.

The editor works over the serial port as well as on the HDMI console — it drives a VT100, and the console emits VT100 function key sequences. Files with CRLF line endings are accepted; the CRs are stripped on load, which matters because most files arrive from a PC.

**It takes the screen back if a program left it in a graphics mode.** The editor draws on the text console, which is what `MODE 1` selects. A program that finished in `MODE 2` leaves the screen 320×240 in sixteen colours, and the console is then not what the monitor is showing — so the editor would be painting where nothing can be seen. `mmedit` switches to `MODE 1` on the way in and puts the old mode back on the way out, including when it is killed, so a program's screen survives a trip through the editor and comes back as it was.

### 7.1 The other editor: vi

`mmedit` is for BASIC. For small text files — a shell script, `/etc/motd`, a short C file — there is a `vi`:

```
# vi hello.c
```

It is Levee, David Parsons' small `vi` clone, with modal editing, the `:` commands and the usual movement keys. It has been on the card since the beginning under its own name, `levee`, which still works: `vi` and `levee` are two names for one file.

**Its edit buffer is 64 KB**, which is enough for any source file you are likely to write on the machine. Levee’s own default is 4 KB — it was written for 8-bit micros, where that was a fair share of the machine — and this port raises it, since a process here may have most of a 340 KB pool to itself.

Open something larger than the buffer and Levee says **[overflow]** on the status line and holds the file **read-only**: you can look and move around, but **:w** answers “File is readonly” rather than writing a truncated file back. That is the safe way round, and worth knowing as the signal that a file is too big rather than that something is wrong.

One difference from a full **vi** to watch: **cw** on the last word of a line joins the following line onto it.

## 8 The FAT partition and the `fat` command

Partition 1 of the SD card is ordinary FAT, readable and writable by any PC — this is how files travel to Fuzix, because nothing else can mount the Unix partition. Format it once in Windows (FAT or FAT32, **not** exFAT), then simply copy files onto it.

On the Fuzix side, the `fat` command reads it (long filenames and subdirectories included):

```
# fat info
/dev/hdb1: FAT16, 32695 clusters of 2048 bytes (62 MB)
# fat ls
    4523  My Program.bas
    <dir> BASIC
# fat ls basic
# fat get "my program.bas" /root/prog.bas
# fat get demo.bin                (lowercased name in current dir)
```

`fat` is read-only by design — the desktop does the writing. To move a file *out* of Fuzix, use the serial port, or write it with `doswrite` (the venerable Minix FAT12/16 tool, also included) if the partition is FAT16.



## 9 Moving files over the serial port

The FAT partition carries files *in*, but **fat** is read-only, so it cannot carry anything back *out*. The serial console can do both, in either direction, with nothing on the board but **uue** and **uud** — and it is the only route that needs no card swapping.

The idea is older than the machine: **uencode** turns any file into printable text, and printable text survives a terminal. Both tools are in `/bin`:

```
# uue FILE                writes FILE.uue - the encoded text
# uud FILE.uue            decodes it back, recreating the original name
```

### 9.1 Sending a file to the board

On the PC, encode the file, then have the board read the text into a file and decode it:

```
# cat > prog.uue          (now paste or send the encoded text)
^D
# uud prog.uue
# ls -l prog.bas
```

**The one thing that will bite you is flow control.** The terminal input queue is 132 bytes. Sending encoded text as fast as the port will take it overruns that queue and loses characters silently — a 62-character line sent every 25 ms still loses roughly 60% of the text, and the damage only shows up as a corrupt file at the end. Two ways to avoid it:

- **Let the terminal pace it.** Any sender with a per-line delay *and* a wait for the echo will do. The delay alone is not enough.
- **Use the supplied script.** `devtools/uusend.py` in the source tree does exactly this: it types the text one line at a time and waits for each line to echo before sending the next, so at most one line is ever in flight. It then runs **uud** for you.

```
python uusend.py local.bas prog.bas --port=COM11
```

Note that **uusend.py** takes a **bare** remote filename — it drives one **ucp**-style session with **cd** and plain names, so **mv** the file afterwards if it belongs somewhere else.

### 9.2 Fetching a file from the board

The other direction is easier, because the board is the slow end:

```
# uue report.txt
# cat report.uue
```

Capture the session to a file in your terminal program, cut away anything before **begin** and after **end**, and decode it on the PC.

### 9.3 Programs to use

**Linux (and macOS, and WSL):**

- **uencode** / **udecode** come from the **sharutils** package (`apt install sharutils`). macOS has **uencode** built in.

- For the terminal, **picocom** (simplest), **minicom** (its `Ctrl-A S` menu includes an `ascii-xfer` that paces lines), or **screen** `/dev/ttyUSB0 115200`.
- If `sharutils` is awkward, Python needs no install: `python3 -c "import binascii,sys; ..."` — or just use `devtools/uusend.py`, which does the encoding itself.

#### Windows:

- **Tera Term** is the pick — free, and its *File* → *Send file* has a per-line delay setting under *Setup* → *Serial port* (set a transmit delay of a few ms per character or 30–50 ms per line). This is the easiest reliable route without scripting.
- **PuTTY** works for capture (*Session* → *Logging*) but has no paced file send; pasting a large file into it will lose characters.
- **RealTerm** can send a file with a configurable delay, and is good at capturing binary.
- For the encode/decode step, Windows has no built-in `uuencode`. Use **WSL** (then it is the Linux instructions), **Python** for Windows, or **UUDevview**, which still builds and runs.

Whatever you use, the check at the end is the same: `sum` the file on both machines and compare. On the board, `sum FILE`.

## 10 Commands at the # prompt

The shell is the Bourne shell and the machine underneath it is a V7-style Unix, so most of what you know already works. This chapter is about the rest: the programs that exist because this is a Pico Computer rather than a PDP-11, and the handful of places where the tools have been brought forward from 1979.

Everything named here is on the card. That is checked rather than promised — `mancheck.sh` extracts every command name from this chapter and the next and looks for it in the built image, and the release will not go out if one is missing. The list used to be maintained by hand and had drifted badly: it offered a games collection of some thirty titles, an editor called `ue`, and an assembler, none of which were ever installed.

### 10.1 The machine itself: `picctl`

Everything the kernel will do on request that has no better home.

```
# picctl flash           reboot into the UF2 bootloader
# picctl keymap uk       us uk de fr es be
# picctl mode 2          set the display mode
# picctl mode            ... and back to the 80x40 text console
# picctl usbreset        re-enumerate after the DPDT switch
# picctl numlock         report
# picctl numlock off     for the keyboard plugged in now
# picctl numlock on 04b3:3025 for one that is not
# picctl numlock off --once do not save it
```

`picctl flash` is the polite way to reach the bootloader: `sync`, `remount -n / ro`, `sync`, then `picctl flash`, and the drive appears without anyone touching the board.

**Num lock is a property of the keyboard, not of the machine.** A keyboard with no numeric keypad usually overlays one onto 7890/uiop/jkl;/m while num lock is on, and its own firmware does that from the LED report the host sends. Nothing in the USB descriptors distinguishes such a keyboard — a Raspberry Pi keyboard and a full-size Lenovo return byte-identical HID report descriptors — so the setting is remembered per keyboard in `/etc/numlock`, written when you change it and replayed by `/etc/rc`. That is why it survives a reboot and why each of your keyboards keeps its own answer.

### 10.2 Pictures

These four are the programs `SAVE IMAGE`, `LOAD IMAGE`, `LOAD JPG` and `LOAD PNG` run, and they are just as useful typed at the prompt. All of them want a graphics mode — `picctl mode 2` if you are at the text console.

```
# saveimage shot.bmp           the whole screen
# saveimage part.bmp 160 120 320 240 x y w h
# loadimage shot.bmp          at 0,0
# loadimage tiger.bmp 0 0 4    dither mode 4
# loadjpg photo.jpg          at 0,0
# loadjpg photo.jpg 0 0 0 0 0 2 binned 2:1, so 640x480 fits
# loadpng logo.png 40 20     at x,y
```

```
# loadpng logo.png 0 0 -1           let the screen show through
# loadpng -s logo.png > logo.spr    decode to a SPRITE, on stdout
```

The full argument lists, which are MMBasic's:

---

```
saveimage  file.bmp [x y w h]
loadimage  file.bmp [x [y [mode [ximage [yimage]]]]]
loadjpg    file.jpg [x [y [mode [ximage [yimage [scale]]]]]]
loadpng    file.png [x [y [transparent [cutoff]]]]
```

---

**ximage/yimage** are the offset **into the picture**, so a large image can be cropped rather than scaled. **saveimage** writes a 24-bit BMP of any rectangle. **loadimage** is MMBasic's own BMP decoder and reads 1/4/8/16/24/32-bit files, BI\_BITFIELDS and RLE4/RLE8, dithering only when asked.

**transparent defaults to 0, which is palette black**, so a PNG with a transparent surround draws a black box on a white screen. That looks like a bug and is not — a real PicoMite does the same, and the default is chosen so that **SPRITE LOADPNG** and **SPRITE SHOW**, which both treat index 0 as see-through, meet in the middle. Pass **-1** to let the screen show through instead. **cutoff** is the alpha above which a pixel counts as opaque.

**loadjpg** decodes a block at a time, so its memory does not grow with the picture. **loadpng** cannot work that way — PNG filters refer to the row above and the whole image must be inflated first — so it takes the big buffers from the PSRAM arena and costs the process pool nothing.

The **-s** form needs no graphics mode at all: it writes the decoded sprite to standard output as two 16-bit sizes followed by one colour index per byte. That is how **SPRITE LOADPNG** works, and it is also the way to convert artwork from the shell.

### 10.3 Sound

```
# playmp3 track.mp3           volume 80 by default
# playmp3 track.mp3 40        0 to 100
# playmp3 track.mp3 &         in the background, and carry on working
# playwav clip.wav 60
# playflac album.flac
# playmod tune.mod 70         MOD, and it loops
# playmod tune.mod 70 noloop  ... or plays once
```

---

```
playmp3,playwav,playflac  file [volume 0-100]
playmod                   file.mod [volume] [noloop]
```

---

These are what **PLAY MP3**, **PLAY WAV**, **PLAY FLAC** and **PLAY MODFILE** run. **One plays at a time**: a second is refused by name and pid rather than allowed to talk over the first. Stop one with **kill -2**, or **PLAY STOP** from BASIC. **playmp3** decodes at about six times real time and leaves most of the machine to whatever else is running.

**PLAY SOUND** and **PLAY TONE** have no command-line equivalent — the synthesiser lives in the kernel's DAC interrupt and is reached through **/dev/sys**.

## 10.4 Languages and the toolchain

Each of these has a chapter of its own; this is the summary.

|                  |                                       |
|------------------|---------------------------------------|
| # cc prog.c      | -> prog.bc, and run it with ./prog.bc |
| # cc prog.bas    | BASIC in one step, via mmhc           |
| # mmhc prog.bas  | -> prog.c, and stop there             |
| # bcdump prog.bc | disassemble the bytecode              |
| # bbcbasic       | BBC BASIC, with its own editor        |
| # fforth         | a complete ANS Forth                  |
| # dc             | the V7 desk calculator                |

---

|        |                                                     |
|--------|-----------------------------------------------------|
| cc     | [-o out] [-v] [-k] [-Ldir] file.c \ file.bas        |
| mmhc   | source.bas [-o out.c] [--report] [--strict] [--fcc] |
| bcdump | file.bc                                             |

---

cc prog.bas is the whole build in one command: it runs mmhc first and writes prog.mb.c, a deliberately different name from prog.c so that compiling prog.bas can never overwrite C you wrote yourself. mmhc --report lists implied globals and any line it could not translate; --strict stops on the first of them instead of commenting it out and carrying on.

bcrun executes a .bc file, and is what the #!-less ./prog.bc actually invokes.

## 10.5 Editors

|                   |                                       |
|-------------------|---------------------------------------|
| # mmedit prog.bas | MMBasic's own, with its function keys |
| # vi hello.c      | levee, a compact vi                   |
| # ed              | the V7 line editor, still here        |

mmedit is described in its own chapter. vi and levee are two names for one program.

## 10.6 Getting files on and off

|                                           |                                         |
|-------------------------------------------|-----------------------------------------|
| # fat ls                                  | list the FAT partition                  |
| # fat ls basic                            | ... a directory of it                   |
| # fat get "my program.bas" /root/prog.bas |                                         |
| # fat info                                |                                         |
| # uue report.txt                          | -> report.uue, to paste into a terminal |
| # uud prog.uue                            | decode, recreating the original name    |
| # rx file                                 | XMODEM in, over /dev/tty2               |
| # sx file                                 | ... and out                             |
| # dosread                                 | FAT12/16 floppy-era transfers           |
| # tar                                     | the classic archiver                    |

fat takes [-d device] before its subcommand. The FAT partition is the one Windows can see, so it is the easy way to move a file from a PC; uue/uud need nothing but the console, and have a chapter of their own.

## 10.7 The clock, and housekeeping

|           |               |
|-----------|---------------|
| # setdate | show the time |
|-----------|---------------|

|                    |                                     |
|--------------------|-------------------------------------|
| # setdate -w       | write the system time to the DS3231 |
| # setdate -a       | ask for a new one                   |
| # df               | space                               |
| # free             | memory, and what the swapper took   |
| # ps               | processes                           |
| # uptime           | how long since the last boot        |
| # mount            | what is mounted                     |
| # umount /dev/hdb3 | ... and unmount it                  |
| # remount -n / ro  | read-only, before flashing          |
| # fsck /dev/hdb2   | check a filesystem                  |
| # sync             | flush the buffers                   |
| # shutdown         | the tidy way to stop                |
| # halt             | ... and the blunt one               |
| # reboot           | start again                         |

setdate also takes -u for UTC and -0 to zero the clock. swapon exists but has nothing to do: there is no swap device any more, because the kernel takes an allocation the size of the process out of PSRAM when it needs to swap one out. free reports that.

setboot, prtroot and substroot choose and report which partition the kernel boots from — see Appendix B.

## 10.8 Where this is not 1979

Fuzix is a V7-style Unix and most of the userland is period-correct. These are the places it is deliberately not, and they are worth knowing because they are what makes shell work on the machine bearable.

- **awk is Lucent's one true awk** — the maintained descendant of the V7 original, by one of its authors, not a subset. Associative arrays, user-defined functions, `getline` in each of its forms, output pipes, dynamic regular expressions, `printf` and the maths library. See [Text processing](#).
- **The C library can print a fraction.** `printf("%f", x)` used to print the letter f. %e, %f and %g work now, in `printf` and `scanf`, and so do %j and %z. A bytecode program's `printf` gained %e and %g too, where before they printed themselves *and* misaligned every argument after them.
- **[ exists.** `/bin/test` was there and `/bin/[` was not, so every bracket test in every shell script failed with `[: not found`.
- **sed, find, expr, seq and uname** were all being compiled and simply never installed. They are installed.
- **grep -q, ls -t and ls -1** — small additions, and the ones a script reaches for first.
- **mmedit** is not a Unix tool at all: it is MMBasic's own full-screen editor, keyword colouring and function keys included.

**What is still period-correct**, so that a script does not surprise you: `grep` has basic regular expressions only and no -E; `sed` is MINIX's, with no -E; `sort` uses the V7 key syntax `+beg -end` rather than -k; `diff` has no -u. The table in [Text processing](#) has the detail.

## 10.9 What is not here

A short list, because a manual that names a command the card does not have wastes more of your time than one that stays quiet.

There is no `less`, `make`, `m4`, `factor`, `units` or `mail`, and no assembler. `/usr/games` holds `advent` — the original Colossal Cave — and `cowsay`, and that is all: the Scott Adams, Mysterious Adventures and Z-machine collections are not installed. There is no network, so `ssh` cannot do anything useful. `man` is present and so are its pages, in `/usr/man/man1`.

ewpage

## 11 The filesystem and included software

### 11.1 Layout

|                          |                                                                                                           |
|--------------------------|-----------------------------------------------------------------------------------------------------------|
| <code>/bin</code>        | core utilities, and <code>picotcl</code> , <code>fat</code> , <code>uue/uud</code> , <code>setdate</code> |
| <code>/usr/bin</code>    | the toolchain, BBC BASIC, the editors, the media tools                                                    |
| <code>/usr/games</code>  | <code>advent</code> and <code>cowsay</code>                                                               |
| <code>/usr/lib/cc</code> | the C compiler passes, and its headers in <code>include/</code>                                           |
| <code>/usr/man</code>    | manual pages ( <code>man &lt;name&gt;</code> )                                                            |
| <code>/dev</code>        | devices – see below                                                                                       |
| <code>/etc</code>        | <code>rc</code> (boot script), <code>inittab</code> , <code>passwd</code> , <code>termcap</code>          |
| <code>/tmp</code>        | scratch space                                                                                             |
| <code>/root</code>       | root's home directory                                                                                     |

Key devices:

| Device                      | What it is                                                 |
|-----------------------------|------------------------------------------------------------|
| <code>/dev/tty1</code>      | The console (HDMI + USB keyboard + serial mirror)          |
| <code>/dev/tty2</code>      | The GP0/GP1 serial port                                    |
| <code>/dev/hda</code>       | On-board NAND flash filesystem                             |
| <code>/dev/hdb1–hdb3</code> | SD card partitions (root is <code>hdb2</code> )            |
| <code>/dev/rtc</code>       | The DS3231 clock ( <code>setdate</code> reads and sets it) |
| <code>/dev/sys</code>       | Platform control (graphics, sound, ADVAL iocls)            |

`/etc/rc` runs at boot: filesystem check, clock from the DS3231, keyboard layout. Edit it with any of the editors below.

There is no swap device to enable. The PSRAM is not a block device any more: the kernel takes an allocation the size of the process when it needs to swap one out, and programs take their heap from the same place. `free` reports both.

### 11.2 Applications

The programs that make this machine what it is have a chapter of their own: [Commands at the # prompt](#) covers `picotcl`, the image and sound players, the toolchain, the editors and the file-transfer tools, with their arguments.

**Shell and core:** Bourne `sh` and the classic set — `ls ll cp mv ln rm mkdir rmdir cat more head tail grep fgrep sed awk tr cut sort uniq wc find xargs diff diff3 cmp comm join split rev tar dd df du free ps kill killall uptime date cal banner echo sleep tee touch which who su passwd stty mount umount sync fsck mkfs fdisk chmod chown chgrp od seq dc expr test uname cron at write wall` — and more, so `ls /bin /usr/bin` is the authority rather than this paragraph.

**Games** (`/usr/games`): `advent`, the original Colossal Cave, and `cowsay`.

### 11.3 Text processing

`awk` is Lucent's — the one true `awk`, the maintained descendant of the V7 original by one of its authors. It is the real thing rather than a subset: associative arrays, user-defined functions, `getline` in each of its forms, output pipes, dynamic regular expressions, `printf`, and the maths library.

```
# awk '{ s[$1] += $2 } END { for (k in s) printf "%-10s %6.2f\n", k, s[k] }' log
# ps | awk 'NR > 1 { n++ } END { print n " processes" }'
```

With `sed`, `grep` and `find` alongside it the usual pipelines work:

```
# find /bin -name 'a*' | sed 's|/bin/||' | awk '{ print NR, $1 }'
```

**What these are not.** They are period tools and they show it in places, so it is worth knowing where before a script surprises you:

---

|                   |                                                                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>grep</code> | basic regular expressions only. <code>-c -e -i -l -n -q -s -v</code> , and no <code>-E</code> ; use <code>awk</code> for an extended regex, or <code>fgrep</code> for a fixed string. |
| <code>sed</code>  | MINIX's. Substitution, <code>-n</code> , several <code>-e</code> , and back-references all work; no <code>-E</code> .                                                                 |
| <code>sort</code> | the V7 key syntax, <code>+beg_pos -end_pos</code> , not <code>-k</code> .                                                                                                             |
| <code>diff</code> | V7 — no <code>-u</code> , so no unified diffs.                                                                                                                                        |
| <code>ls</code>   | <code>-t</code> sorts a <i>directory</i> by time, newest first; command-line arguments are listed in the order you gave them, as they always have been.                               |
| <code>test</code> | and <code>[</code> , which are one program under two names. <code>-a -b -c -d -e -f -g -n -o -p -r -s -t -u -w -x -z</code> .                                                         |

---



## 12 Appendix A: pin usage

| GPIO          | Function                                                        |
|---------------|-----------------------------------------------------------------|
| GP0 / GP1     | Serial port <code>/dev/tty2</code> (TX / RX)                    |
| GP8 / GP9     | System console UART (USB-C CH340)                               |
| GP10/11/22    | Audio I2S: BCLK / LRCLK / DATA (PCM5102 DAC)                    |
| GP12–GP19     | HDMI (HSTX)                                                     |
| GP20 / GP21   | I2C0: DS3231 RTC and QWIIC connector (SDA / SCL)                |
| GP27          | DS3231 32 kHz — board identification (PC3 only)                 |
| GP28/30/31/33 | SD card, Pico Computer 3 (MISO/SCK/MOSI/CS, SPI1)               |
| GP29/30/31/32 | SD card, Pico Computer 2 (CS/SCK/MOSI/MISO, bit-banged)         |
| GP32          | DS3231 alarm interrupt (PC3; unused by Fuzix)                   |
| GP34–GP37     | Joystick switches — <code>ADVAL(0)</code> bits 0–3              |
| GP40          | Analogue input (reserved; not read by <code>ADVAL</code> )      |
| GP41–GP44     | Analogue inputs — <code>ADVAL(1)</code> – <code>ADVAL(4)</code> |
| GP45/GP46     | Analogue-capable, free                                          |
| GP23/24/25/29 | CYW43 wireless (PC3; unused by Fuzix)                           |
| GP47          | PSRAM chip select                                               |

All spare header pins remain ordinary 3.3 V GPIO. Do not apply 5 V to any GPIO.

## 13 Appendix B: boot options

The kernel command line (held by the bootloader) accepts:

- `hda / hdb2 ...` — root device override
- `kbd=us|uk|de|fr|es|be` — early keyboard layout override (the layout in `/etc/rc` then applies for the session)

The build, source and development notes live in the `pc3` branch of [github.com/UKTailwind/FUZIX](https://github.com/UKTailwind/FUZIX) under `Kernel/platform/platform-rpipico/` — see `PC3-DEVNOTES.md` for the engineering history and `PC3-GFX-DESIGN.md` for the display design.

## 14 Appendix C: MMBasic coverage

This is what `mmbc` translates today. It is generated from the translator's own tables (`fcc/coverage.py` in the `mmb2c` repository), so it says what the program does rather than what anyone remembers it doing.

Coverage grows with each release, and it will never be complete. MMBasic is a large language whose statements reach deep into one particular firmware, and a translator that emits portable C cannot follow all of it. Anything not listed here is reported by name, with its line number, and the translation continues - so you find out at translate time, not at run time.

### 14.1 Statements

|          |             |           |            |
|----------|-------------|-----------|------------|
| ?        | ARC         | ARRAY     | BEZIER     |
| BIT      | BLIT        | BOX       | BYTE       |
| CALL     | CASE        | CAT       | CHDIR      |
| CIRCLE   | CLEAR       | CLOSE     | CLS        |
| COLOR    | COLOUR      | CONST     | CONTINUE   |
| COPY     | DATA        | DATE\$    | DEFINEFONT |
| DIM      | DO          | ELSE      | ELSEIF     |
| END      | ENDIF       | ERASE     | ERROR      |
| EXIT     | FILES       | FILL      | FLAG       |
| FLAGS    | FLASH       | FLUSH     | FONT       |
| FOR      | FRAMEBUFFER | FUNCTION  | GOSUB      |
| GOTO     | GUI         | I2C       | I2C2       |
| IF       | INC         | INPUT     | KILL       |
| LET      | LINE        | LMID      | LOAD       |
| LOCAL    | LONGSTRING  | LOOP      | MAP        |
| MATH     | MKDIR       | MODE      | NEXT       |
| ON       | ONEWIRE     | OPEN      | OPTION     |
| PAUSE    | PIN         | PIXEL     | PLAY       |
| POKE     | POLYGON     | PORT      | PRINT      |
| PULSE    | PWM         | RANDOMIZE | RBOX       |
| READ     | REDIM       | RENAME    | RESTORE    |
| RETURN   | RMDIR       | RTC       | SAVE       |
| SEEK     | SELECT      | SERVO     | SETPIN     |
| SETTICK  | SORT        | SPI       | SPRITE     |
| STATIC   | STRUCT      | SUB       | SYSTEM     |
| TEMPR    | TEXT        | TIME\$    | TIMER      |
| TRIANGLE | TYPE        | WEND      | WHILE      |

Assignment needs no keyword (`LET` is accepted). Statement separators, line numbers and labels, `REM` and `'` comments all work as expected.

### 14.2 Functions

|     |      |     |      |
|-----|------|-----|------|
| ABS | ACOS | ASC | ASIN |
|-----|------|-----|------|

---

|               |              |             |            |
|---------------|--------------|-------------|------------|
| ATAN2         | ATN          | BIN\$       | BIN2STR\$  |
| BIT           | BOUND        | BYTE        | CHOICE     |
| CHR\$         | CINT         | COS         | CWD\$      |
| DATE\$        | DATETIME\$   | DAY\$       | DEG        |
| DIR\$         | EOF          | EPOCH       | EXP        |
| FIELD\$       | FIX          | FLAG        | FORMAT\$   |
| HEX\$         | INKEY\$      | INPUT\$     | INSTR      |
| INT           | KEYDOWN      | LCASE\$     | LCOMPARE   |
| LEFT\$        | LEN          | LGETBYTE    | LGETSTR\$  |
| LINPUT        | LINSTR       | LLEN        | LOC        |
| LOF           | LOG          | LTRIM\$     | MAP        |
| MATH          | MAX          | MID\$       | MIN        |
| MM.CMDLINE\$  | MM.DEVICE\$  | MM.ERRMSG\$ | MM.ERRNO   |
| MM.FONTHEIGHT | MM.FONTWIDTH | MM.HPOS     | MM.HRES    |
| MM.I2C        | MM.INFO      | MM.INFO\$   | MM.ONEWIRE |
| MM.SPISPEED   | MM.VER       | MM.VPOS     | MM.VRES    |
| OCT\$         | PEEK         | PI          | PIN        |
| PIXEL         | PORT         | POS         | RAD        |
| RGB           | RIGHT\$      | RND         | RTRIM\$    |
| SGN           | SIN          | SPACE\$     | SPI        |
| SPRITE        | SQR          | STR\$       | STR2BIN    |
| STRING\$      | STRUCT       | TAB         | TAN        |
| TEMPR         | TIME\$       | TIMER       | TRIM\$     |
| UCASE\$       | VAL          |             |            |

---

### 14.3 MATH() sub-functions

Scalar: ATAN3, COSH, LOG10, SINH, TANH

Whole-array (one number out of an array): MAX, MEAN, MEDIAN, MIN, SD, SUM

### 14.4 MATH sub-commands

MATH is also a statement, and that is a different and much longer list in the interpreter. Six of it are translated — the ones that walk an array element by element, which is what most programs use it for:

---

|                              |                                            |
|------------------------------|--------------------------------------------|
| MATH SET v, a()              | every element of a() becomes v             |
| MATH ADD a(), v, b()         | b() = a() + v, element by element          |
| MATH SCALE a(), v, b()       | b() = a() * v, element by element          |
| MATH RANDOMIZE [seed]        | seed the generator; no seed uses the clock |
| MATH SLICE a(), i, , k, b()  | copy one line of a() into b()              |
| MATH INSERT a(), i, , k, b() | copy b() back into that line               |

---

SET, ADD, SLICE and INSERT take integer, float or string arrays; SCALE is numeric only, as it is there. ARRAY is accepted as a spelling of MATH for all of them, and ARRAY SLICE and ARRAY INSERT are the spellings the manual uses — the interpreter runs both through the same two functions.

### 14.4.1 Slicing an array

A **slice** is one line through an array of two or more dimensions. Give every index but one; the line runs along the one left blank, and the array it is copied to or from is one-dimensional and the same length.

```
DIM a(3, 4, 5), b(4)
ARRAY SLICE a(), 2, , 3, b()      ' b() = a(2,0,3), a(2,1,3), ... a(2,4,3)
b(0) = 99
ARRAY INSERT a(), 2, , 3, b()      ' and back again
```

It is far quicker than the equivalent FOR loop, and that is the reason it exists: the elements of the line are a fixed distance apart, so the copy is a single stride and the index arithmetic is done once at translate time rather than once per element. **OPTION BASE** is respected on both sides. A length that does not match is **Size mismatch between slice and target array**, as in the interpreter.

One difference to know about: MMBasic converts between integer and float arrays here, and this does not — both arrays must be the same type, the same rule **ARRAY ADD** already follows.

The rest are not translated, and each says so by name rather than being mistaken for something else: the matrix operations (**M\_MULT**, **M\_INVERSE**, **M\_TRANSPOSE**, **M\_PRINT**), the vector ones (**V\_MULT**, **V\_CROSS**, **V\_NORMALISE**, **V\_ROTATE**, **V\_PRINT**), the quaternions (**Q\_CREATE**, **Q\_EULER**, **Q\_INVERT**, **Q\_MULT**, **Q\_ROTATE**, **Q\_VECTOR**), the complex arithmetic (**C\_ADD**, **C\_SUB**, **C\_MUL**, **C\_DIV**, **C\_AND**, **C\_OR**, **C\_XOR**), **FFT**, **WINDOW**, **SINC**, **INTERPOLATE**, **POWER**, **SHIFT**, **PID**, **SENSORFUSION** and **AES128**.

They are a coherent block of work rather than a scattering of gaps — most are pure arithmetic over arrays with no hardware in them, so they would go in as a header of static functions and cost nothing to a program that does not use them.

## 14.5 Types and structure

**INTEGER** (64-bit), **FLOAT** (double), **STRING**, and arrays of each, up to the dimensions MMBasic allows. **DIM**, **LOCAL**, **STATIC**, **CONST**, **OPTION BASE**, **SUB** and **FUNCTION** with by-reference arguments, and the usual control flow.

**DIM s\$(n) LENGTH m** sets the **SPACING of the elements**, not just a cap on each. The firmware places element *k* at **base + k \* (m + 1)**, and a program is entitled to that: PETSCII Robots keeps its 128x64 world map as **DIM LV\$(63) LENGTH 128** and reads tiles straight out of it with **PEEK(BYTE (y) \* 129 + x + 1va)**, where the 129 *is* the **LENGTH**. So an array honours it, and an element is then the firmware's own layout — a length byte and **LENGTH** characters, with no room for the trailing **NUL** the runtime normally keeps. That is handled for you; the one visible consequence is that such an array cannot be passed whole to a **SUB** or to **SORT**, because the runtime's array helpers step at the full string size. Index it instead, or leave the **LENGTH** off. On a *scalar* **LENGTH** is still only a cap, since a scalar's layout cannot differ.

**Structures** (MMBasic's **TYPE ... END TYPE**, documented in full in the PicoMite structures manual) are translated with the firmware's byte layout reproduced exactly — **STRUCT(SIZEOF "t")** answers the same number here and on a PicoMite. Members may be **INTEGER**, **INT**, **FLOAT**, **STRING [LENGTH n]**, arrays of those, or an earlier **TYPE**; member access works to the full nesting depth (**data(2).items(1).values(4)** included), structure variables, arrays, **LOCALs** and by-reference parameters all work, whole structures assign with **=**, and **STRUCT COPY**, **STRUCT CLEAR** and **STRUCT SWAP** are in. **STRUCT(SIZEOF/OFFSET/TYPE)** fold to constants when the names are literal strings.

Not translated (each says so rather than mistranslating): `STRUCT SORT/SAVE/LOAD/PRINT/EXTRACT/INSERT, STRUCT(FIND)`, a `FUNCTION` returning a structure, whole structure arrays as parameters, and initialisers on structure arrays. Assigning a whole structure into or out of a *nested* member is refused deliberately: the interpreter copies the outer type's size there and overruns memory, and a clean error beats reproducing that.

## 14.6 Errors, and surviving them

In a program that uses `ON ERROR`, every error it can hit is a check the runtime makes *before* it does the thing — the same order the interpreter uses. Nothing is left to the hardware to notice: dividing by zero as a float would otherwise answer `inf` rather than stopping, and this processor does not trap integer division by zero at all.

A program with no `ON ERROR` anywhere is compiled without the arithmetic checks — see “What `ON ERROR` costs” below. Its float divisions and `SQR/LOG/ASIN/ACOS` take what C gives: `inf` or `nan`, flowing onward through the sums. There is no sensible recovery from arithmetic like that — the program has a bug to fix either way — so the choice is between stopping with a message (a trapping program) and full speed (everything else). Integer division and `MOD` are the exception, checked in every program: C leaves integer division by zero undefined, and the silent zero this processor answers is not a number to limp onward with.

`ON ERROR SKIP [n]`, `ON ERROR IGNORE`, `ON ERROR CLEAR` and `ON ERROR ABORT` work as they do on a PicoMite, with `MM.ERRNO` and `MM.ERRMSG$` reporting what happened. A statement that fails while an error is being skipped is abandoned where it failed: the assignment does not happen, the rest of the `PRINT` does not print, and execution resumes at the next statement — in the `SUB` it happened in, if that is where it was. The count works as it does there too, `SKIP n` covering the next `n` statements.

Two details that surprise people, both matching the interpreter. A `PRINT` that fails part way through prints **nothing at all** — not even the items before the failure — because the line is built whole and the error discards it. And calling a `SUB` spends skip count: the `SUB` line and any `LOCAL` are statements too, so `ON ERROR SKIP 2` before a call does not reach the third statement inside it.

Two limits worth knowing. A statement that jumps away (`GOTO`, `EXIT`) does not count against `SKIP n`, so a count that spans one runs one statement further than it would on a PicoMite. And running out of memory ends the program whatever `ON ERROR` says — there is nothing sensible to carry on with, and a program limping along on a failed allocation would fail somewhere far less obvious.

`ON ERROR RESTART` reboots the machine on a PicoMite; a compiled program has no equivalent, so `mmbc` refuses it by name rather than guessing.

### 14.6.1 What `ON ERROR` costs

The checks are real work in real loops. With `ON ERROR` present, every float division whose divisor is not a nonzero literal becomes a runtime call that tests the divisor first, and `SQR`, `LOG`, `ASIN` and `ACOS` go through checked wrappers instead of straight to `libm` — that is what makes their errors trappable statements. Measured on the machine from a fresh boot: the grains benchmark, whose inner loop divides by a variable and takes a logarithm every pass, pays about 12%; the solar eclipse predictor, dominated by plain arithmetic, about 2%. The string checks (concatenation past 255 characters, `ASC` of an empty string) are part of string calls that happen anyway and stay on in every program; they cost a comparison, not a call.

ON ERROR earns its keep trapping things that genuinely can fail at run time — an I2C transfer that may not be acknowledged, a file that may not exist — not arithmetic. If a program traps errors out of habit, leaving ON ERROR out buys the checks back.

### 14.6.2 I2C2 — the second controller

I2C2 is MMBasic’s second bus, and on this machine it is the one a program may have. The fixed bus (I2C, GP20/GP21) is the QWIIC socket *and* the DS3231 the system clock runs on, which the kernel polls from interrupt context, so it stays the kernel’s.

```
SETPIN 38, 39, I2C2          ' GP38/GP39 or GP42/GP43 - see below
I2C2 OPEN 400, 1000          ' speed kHz, timeout ms
I2C2 WRITE &H77, 1, 1, &HDO  ' option 1 = HOLD: no STOP
I2C2 READ  &H77, 0, 1, r$    ' ...so this is a repeated START
I2C2 CLOSE
```

The pins are not free to choose: the RP2350 muxes I2C1’s SDA only onto pins where pin AND 3 = 2 and SCL only where pin AND 3 = 3, so on this board the pairs are **GP38/GP39** and **GP42/GP43**. Anything else is refused at OPEN rather than producing a bus that never answers.

**The data arguments are the same on all three buses**, which is worth learning once. WRITE takes a list of byte expressions, a whole numeric array written a(), a string, or a long string written LONGSTRING a(). READ takes any of those, and also **a list of variables, one per byte received**:

```
I2C2 READ &H77, 0, 3, hi, mid, lo
```

MMBasic reaches one implementation of these from I2C, SPI and ONEWIRE alike, and so does this — learn them here and they work there. The string forms are what MMBasic’s own sensor examples use, because STR2BIN() then lifts the 16- and 32-bit fields straight out of what was read.

Two rules the shared code enforces, both MMBasic’s. A list must have as many values as the count says, or you get **Argument count** — the count is not a way to send fewer. And a destination is checked *before* the transfer, so asking for forty bytes into an array of sixteen is refused without the bus moving: a read addresses a device and can advance a register pointer inside it, so it must not happen and then fail.

Option bit 0 **holds** the bus: the transfer ends without a STOP so the next one is a repeated START on the same device. Most register-file devices do not need it — they keep their address pointer across a STOP — but the ones that do would otherwise read plausible nonsense.

Two differences from a PicoMite, both deliberate:

- **timeout** is milliseconds, 0 or 100 and up as MMBasic requires, but **0 means a five-second cap, not “no timeout”**. This kernel is non-preemptive: a transfer that waited for ever would not hang the program that asked for it, it would hang the machine, console and display included.
- A held bus that is never finished — the program errors, or is killed between the write and the read — is finished by the kernel, which clocks SCL until the device releases SDA and then issues a STOP. Nothing else on the board would free it.

The pins and the controller are claimed through the pin lock, so they come back if the program dies, and a second program asking for the bus gets a clear “already in use” rather than a collision.

### 14.6.3 SPI — the first controller

```
SETPIN 2, 3, 4, SPI      ' any order: the pin decides its own role
SPI OPEN 62500000, 0, 8   ' speed, mode, bits
SPI WRITE 4, &H2A, 0, 0, 0 ' a list, an array a(), or a string
SPI READ 3, r$            ' into a string or a numeric array
v = SPI(&H55)              ' write one unit, read one back
PRINT MM.SPISPEED         ' the clock it ACTUALLY got
SPI CLOSE
```

**The order of the three pins does not matter.** The RP2350 decides which signal each one carries: the controller is (pin AND 8) = 0 for SPI0, and the role is pin AND 3 — 0 MISO, 1 CS, 2 SCLK, 3 MOSI. So GP2/GP3/GP4 are SCLK/MOSI/MISO however you write them. On the header SPI0 is **GP0–GP7 and GP34–GP39**; the rest (GP26, GP40, GP42–GP46) are SPI1, which is **the SD card** and is not offered — a program that could take it could take the filesystem out from under itself. This is MMBasic’s behaviour too: it asks each pin what it can be rather than fixing an order.

**Chip select is yours**, exactly as on a PicoMite. A display needs CS held across a whole command-and-data sequence rather than per transfer, so only the program knows when to move it — and a pin is a register write now, not a system call.

MM.SPISPEED is worth using. The divisor is  $\text{clk\_peri} / (\text{CPSDVSR} \times (1 + \text{SCR}))$  with CPSDVSR even, so a request nearly always lands on a neighbouring value: asking for 50 MHz gives 46.875, and anything above  $\text{clk\_peri} / 2$  quietly becomes  $\text{clk\_peri} / 2$ . The usable steps here are 62.5, 46.875, 37.5, 31.25 MHz and down.

A whole transfer is **one system call whatever its length** — the controller reads your buffer where it lies rather than copying it through the kernel, which is sound here because there is no MMU and the kernel cannot be preempted. A 240×320 screen of 16-bit pixels is 153,600 bytes and goes out in 26 ms at 62.5 MHz.

A string holds at most 255 bytes, so a 240-pixel row of RGB565 is 480 and will not fit in one. **A long string will**, and that is what the extra word is for:

```
DIM INTEGER row(70)      ' 560 bytes of payload
' ... fill it with LONGSTRING APPEND ...
SPI WRITE 480, LONGSTRING row() ' the whole row, one call
SPI READ 480, LONGSTRING row() ' and back
```

**Say LONGSTRING and mean it**, because a long string *is* an integer array: written row() it is a numeric array and sends one byte per eight-byte cell, quietly and wrongly. That is MMBasic’s behaviour, and the extra word is how you say which of the two you meant.

It is not a speed feature. Filling 240×150 one call per row against 100 pixels a call measures 30 ms against 32 at 24 MHz, and 12 against 13 at 62.5 — the bus dominates. What changes is that the row can be assembled at all, and with it a whole frame.

### 14.6.4 One-wire and TEMPR

```
ONEWIRE RESET 26          ' MM.ONEWIRE = 1 if something answered
ONEWIRE WRITE 26, 1, 1, &H33 ' reset first, then READ ROM
ONEWIRE READ 26, 0, 8, id() ' the eight ROM bytes
PRINT TEMPR(26)           ' a DS18B20, degrees C
```



Any header pin will do; the slots are timed in the program itself. The flag is MMBasic's: **1** reset first, **2** reset afterwards, **4** send or read single bits rather than bytes, **8** hold a strong pull-up when finished, for a parasite-powered device.

The data and destination arguments are **the same ones I2C2 and SPI take** — a list, a string, a whole numeric array, a long string, or (on a read) a list of variables one per byte. That is not a coincidence: MMBasic reaches the same two functions from all three buses, and so does this.

TEMPR(pin) starts a conversion and waits for it. TEMPR START pin[, precision[, timeout]] starts one and returns immediately — 6 ms measured — so the program can do something useful during the 750 ms a 12-bit conversion takes, and collect the reading later:

```
TEMPR START 26, 3          ' 12 bits
' ... do something else ...
t = TEMPR(26)
```

**The wait sleeps rather than spins**, which is the one place this differs from MMBasic on purpose. MMBasic has one program to run and can afford to spin out three quarters of a second; this machine has others. A SETTICK handler keeps firing throughout — eight ticks of a 100 ms timer during one 12-bit conversion, measured.

One honest limitation: a program here **cannot mask interrupts** the way MMBasic does around a byte, and should not be able to. Nothing takes the processor away mid-slot — the kernel cannot be preempted — but a timer interrupt can still stretch one. One-wire tolerates a slot being long rather than short, so a stretched write still reads correctly; if a transfer matters, check the CRC the device gives you.

## 14.7 Not covered

The editor, RUN, LIST, EDIT and the rest of the immediate-mode environment, which will never apply: a translated program is compiled and run rather than typed at a prompt. (mmedit provides the editing they existed for.) The remaining hardware statements are the subject of current work.

Of the graphics, MODE, COLOUR, PIXEL (including the array form), LINE, CIRCLE, BOX, RBOX, TRIANGLE (its drawing form — SAVE/RESTORE need the interpreter's blit buffers), ARC, RGB(), FRAMEBUFFER (including LAYER and MERGE), PRINT @, TEXT, FONT, CLS [colour] and MAP (statement and function) are done, and since v0.15 so are BLIT — including the flash slots it reads and writes — and the SPRITE family with its two-axis SCROLL. TEXT draws in any of MMBasic's nine built-in fonts, and in a font the program defines for itself with DefineFont (numbers 10 to 16), but only in its normal and vertical orientations — the three that rotate the character itself are accepted and drawn normally.

Of the pins, SETPIN n, DIN|DOUT|AIN|ARAW|INTH|INTL|INTB|PWM|OFF, PIN(n) = and PIN(n) are done, and so are PORT in both directions and PULSE. PORT(pin, nbits [, pin, nbits]...) reads or writes several pins as one number, and **the first pin of a group is the least significant bit** — PORT(0,8) = 1 lights GP0, not GP7. Every pin in a bank changes on the same clock edge, which is the whole reason to use it rather than eight PIN() writes: written one at a time, eight lines carry seven wrong values first, and anything clocked off them sees all seven. A port spanning GP31/GP32 takes one store per bank, as it must.

PULSE pin, width **inverts** the pin for the width rather than driving it high, which is MMBasic's behaviour. Under 3 ms it blocks and the width is exact; at 3 ms and above it returns at once and the pin flips back later — at the next PAUSE, the next PULSE, or the next statement in a program

that also uses interrupts. MMBasic ends the long ones from a hardware timer, and this machine has no sub-second interval timer to hang one on.

ONEWIRE RESET, WRITE and READ are done, with MM.ONEWIRE and MMBasic's four flag bits, and so are TEMPR and TEMPR START for a DS18B20. ONEWIRE SEARCH is not — one device to a pin is what the statements above assume.

Also PWM slice, freq, duty [, duty2] with PWM slice, OFF, and SERVO slice, position [, position2] with SERVO slice, OFF; the frequency and counting modes of SETPIN, and PWM SYNC, are not. Interrupt handlers must be SUBs — MMBasic's label and line-number targets are refused, and with them IRETURN, which a SUB handler never needs.

Of the interrupts, SETPIN INTH|INTL|INTB, SETTICK (all four timers, PAUSE, RESUME, off) and ON KEY (both forms) are done. They are MMBasic's poll, checked between statements, with its priority order and its no-nesting rule. **A PAUSE services them while it waits**, as MMBasic's does — which matters because a program that arms a SETTICK usually has a main loop of little else, so a PAUSE that ignored it would mean the handler never ran at all. The wait is cut into slices with the poll between them, and the slice is sized from the shortest armed period: a slow tick still sleeps and costs nothing, a fast one spins as MMBasic does, and only while the program is pausing.

Three divergences, all named where they are described: SETTICK fires at the period asked for rather than MMBasic's period-plus-a-millisecond; the console is checked at most every 5 ms; and keys reach a program only when a line is complete, which is the tty driver's doing and limits ON KEY to command-at-a-time input. ON PS2, INTERRUPT, PID and SENSORFUSION have nothing to notify on this machine. The analogue pair need an ADC pin (GP40–GP46 here), and AIN uses MMBasic's own ten-sample sort-and-discard filter. PIN() returns a float in every mode rather than MMBasic's integer for digital and ARAW, and pins are *owned*: SETPIN claims from the kernel, only the I/O header may be claimed, and the pin is released and reset when the program ends however it ends. OPTION VCC is not supported, so AIN always scales by 3.3 V.

Of the sound, PLAY MP3, PLAY WAV, PLAY FLAC, PLAY VOLUME, PLAY STOP, PLAY SOUND, PLAY TONE, PLAY MODFILE and PLAY MODSAMPLE are done — MIDI, LOAD SOUND and the user-defined U waveform are not. PLAY VOLUME takes one level rather than one per channel. None of the file players takes the completion interrupt MMBasic allows on them.

Of the statements that reach *into* something rather than replacing it, MID\$(s\$,n,m) =, LMID(a(),start[,num]) =, BIT(v,n) =, BYTE(s\$,n) =, FLAG(n) = and FLAGS = are all done, with BIT(), BYTE(), FLAG() and MM.INFO(FLAGS) reading them back. FLAGS is sixty-four bits of scratch for the program's own use, cleared at start — and one set *per program* here, where MMBasic has a single firmware global. LMID is a **splice, not an overwrite**: num bytes come out and the string goes in, so the long string grows or shrinks unless the two lengths match, and leaving num out means “as long as the replacement”. Where MMBasic checks the target's type when the statement runs, the translator knows an lvalue's type as it generates the call, so a BIT on a string is refused at translation with the line named.

POS gives the column the next character will go in, 1 at the start of a line. FLUSH #n pushes a file out — *fflush and fsync*, since a program that says FLUSH means the version that survives the power going off. Note that this machine's fsync syncs the whole filesystem, so it costs more than MMBasic's per-file version; channel 0 is the console and does nothing, as MMBasic's does.

In a graphics mode a program's PRINT now draws the characters into whatever is being drawn on, as MMBasic does, so text goes into the framebuffer with everything else. What is still missing is

OPTION CONSOLE, to say whether a program's output should go to the screen, the serial port, or both.