

Algorithmic Verification of the SuperSury Identity

Johar M. Ashfaque

July 2, 2026

Abstract

This note documents the generalized “SuperSury” identity, a recent advancement in the theory of linear recurrence convolutions. We provide the formal statement of the identity, analyze its structural departure from classical generalizations of Sury’s identity, and present exhaustive computational verification against both standard sequences and randomized high-order recurrences to demonstrate the framework’s robustness.

1 Introduction and Historical Context

The classical identity established by Sury connected the Fibonacci numbers F_n , Lucas numbers L_n , and powers of two via the elegant formulation:

$$2^{n+1}F_{n+1} = \sum_{i=0}^n 2^i L_i. \quad (1)$$

Over the years, numerous authors extended this relation by replacing the base 2^i with an arbitrary parameter t . Notable extensions include Edgar’s formulation:

$$t^{n+1}F_{n+1} = \sum_{i=0}^n t^i (L_i + (t-2)F_{i+1}), \quad (2)$$

and the subsequent broad generalization by Abd-Elhameed and Zeyada, which extended the relation to generalized Fibonacci sequences $U_n^{a,b}$ and Lucas sequences $V_n^{a,b}$ governed by $W_n = aW_{n-1} + bW_{n-2}$:

$$t^{n+1}U_{n+1}^{a,b} = \frac{1}{a} \sum_{i=0}^n t^i (V_i^{a,b} + (at-2)U_{i+1}^{a,b}). \quad (3)$$

2 The Paradigm Shift: Generalized Sury vs. SuperSury

The “SuperSury” identity proposed by Dresden and Gao represents a fundamental inversion of the mathematical degrees of freedom used in all prior historical approaches. The distinct differences can be categorized across three structural dimensions:

2.1 Summand Complexity and Compounding Terms

In classical generalizations (such as those by Marques, Edgar, and Abd-Elhameed & Zeyada), the choice of an arbitrary geometric parameter t forces a correction term inside the summation. As seen in Eq. (3), this results in a complicated, hybrid summand consisting of a linear combination of both the primary and secondary recurrence sequences (V_i and U_{i+1}), scaled by a t -dependent factor ($at - 2$).

Conversely, the SuperSury identity completely eliminates hybrid terms. The summand contains only a singular, unmixed element of the target sequence (X_{i+k}). It avoids introducing external scaling adjustments or combining distinct companion sequences within the summation loop.

2.2 Directionality of Parameter Assignment

- **Classical Generalized Sury:** The user fixes the underlying sequence family, chooses an arbitrary exponential base t , and allows the internal algebra of the summand to distort to preserve equality.
- **SuperSury Framework:** The user selects *any* arbitrary second-order recurrence sequence X_n and an arbitrary initial structural index offset k first. The framework then dynamically dictates what the unique, matching geometric base t must be to satisfy the closure of the identity.

2.3 Sequence Autonomy and Shift Indexing

Historical adaptations are rigidly bound to specific complementary sequence pairs (F_n and L_n , or U_n and V_n) evaluated strictly from their initial boundary conditions ($i = 0$). SuperSury detaches itself from these restrictions by operating on any isolated sequence satisfying $X_n = c_1X_{n-1} + c_2X_{n-2}$, allowing the summation to initiate from any arbitrary offset position k (including negative index boundaries).

3 The SuperSury Identity Formulation

Dresden and Gao formalized this behavior through a master second-order recurrence relation framework.

Theorem 1 (The SuperSury Identity). *Let X_n be an arbitrary second-order linear recurrence sequence defined by $X_n = c_1X_{n-1} + c_2X_{n-2}$ with arbitrary initial values X_0 and X_1 . For any fixed integer index shift k such that X_k and X_{k-1} are non-zero, the geometric base is structurally locked to $t = -\frac{c_2X_{k-1}}{X_k}$, yielding the identity:*

$$X_0X_{n+2} - X_1X_{n+1} = \frac{X_0X_2 - X_1^2}{X_k} \sum_{i=0}^n \left(-\frac{c_2X_{k-1}}{X_k} \right)^{n-i} X_{i+k}. \quad (4)$$

Proof Sketch. The identity is established inductively by applying the difference operator $(E - t)$ to telescope the summation. Multiplying the formulation at step $n - 1$ by the structural base $t = -c_2X_{k-1}/X_k$ and subtracting it from the identity at step n isolates the single terminal summand $\frac{X_0X_2 - X_1^2}{X_k}X_{n+k}$ on the right-hand side. The assertion then follows via expansion of the left-hand side utilizing the primary recurrence definition $X_n = c_1X_{n-1} + c_2X_{n-2}$. $\square$

4 Special Case Corollaries: Fibonacci and Lucas

To further demonstrate the structural flexibility of Theorem 1, we evaluate the framework directly against classical sequences under specific shift parameters.

4.1 The Fibonacci Sequence Instance

Let $X_n = F_n$ be the standard Fibonacci sequence where $F_0 = 0, F_1 = 1$, and $c_1 = c_2 = 1$. Selecting an arbitrary shift index of $k = 3$ yields the boundary parameters $F_2 = 1$ and $F_3 = 2$. Under these constraints, the geometric base dynamically locks to $t = -1/2$. Substituting these variables into Eq. (4) simplifies the system to the following clean arithmetic framework:

$$-F_{n+1} = -\frac{1}{2} \sum_{i=0}^n \left(-\frac{1}{2}\right)^{n-i} F_{i+3}. \quad (5)$$

The matching computation data for this specialization is tracked in Table 1.

4.2 The Lucas Sequence Instance

Let $X_n = L_n$ be the standard Lucas sequence where $L_0 = 2, L_1 = 1$, and $c_1 = c_2 = 1$. Selecting an arbitrary shift index of $k = 1$ yields the parameters $L_0 = 2$ and $L_1 = 1$. This configuration forces the geometric base to lock into a clean negative integer value, $t = -2$. Substituting these properties into Eq. (4) yields:

$$2L_{n+2} - L_{n+1} = 5 \sum_{i=0}^n (-2)^{n-i} L_{i+1}. \quad (6)$$

Corollary 2. *Because the left-hand side expansion elements satisfy the baseline sequence relation, the structural parameters of the Lucas sequence instance collapse into a direct, cross-sequence identity mapping to the classical Fibonacci sequence:*

$$2L_{n+2} - L_{n+1} = 5F_{n+1}. \quad (7)$$

This specialization uncovers an elegant, alternating weighted identity mapping Lucas summations directly to scalable Fibonacci outputs, as verified in Table 2.

5 Computational Verification Data

To establish absolute algebraic rigor, all configurations were verified using exact rational arithmetic to completely bypass floating-point roundoff issues.

To demonstrate the generalized performance of the SuperSury framework beyond standard classical pairs, the computational testing suite evaluates two distinct baseline verification profiles alongside the newly derived corollaries:

- **Identity 1 (Lucas 3-step):** Evaluated using a higher-order sequence transformation ($Y_n = -7Y_{n-1} + 12Y_{n-2} - 4Y_{n-3}$) to validate framework behavior under an artificial extension of the recurrence order boundaries.
- **Identity 2 (A015530):** Instantiated using the classic OEIS sequence defined by structural parameters $c_1 = 4, c_2 = 3$ and initial conditions $X_0 = 1, X_1 = 4$ to confirm absolute alignment under sharp geometric growth trajectories.

5.1 Classical Sequence Testing Traces

Tables 1 through 4 showcase the numerical consistency between the structural Left-Hand Side (LHS) and Right-Hand Side (RHS) formulations across both the newly derived classical corollaries and the baseline verification benchmarks.

Table 1: SuperSury Verification for Fibonacci Sequence ($k = 3, t = -1/2$)

n	Fibonacci Formula LHS	Fibonacci Formula RHS	Match
0	-1	-1	True
1	-1	-1	True
2	-2	-2	True
3	-3	-3	True
4	-5	-5	True
5	-8	-8	True
6	-13	-13	True
7	-21	-21	True

Table 2: SuperSury Verification for Lucas Sequence ($k = 1, t = -2$)

n	Lucas Formula LHS	Lucas Formula RHS	Match
0	5	5	True
1	5	5	True
2	10	10	True
3	15	15	True
4	25	25	True
5	40	40	True
6	65	65	True
7	105	105	True

5.2 General Case Validation

Validation of the general identity was executed using a randomized recurrence pattern defined by the configurations: $X_0 = 3, X_1 = 7, c_1 = 5, c_2 = -2, k = 2$. This parameter block structurally locks the weight parameter to $t = 14/29$ and yields an exact global scale factor of $38/29$. The resulting verification trace is preserved in Table 5.

6 Conclusion

The computational evidence confirms that the Dresden-Gao approach provides a universal mechanism for generating weighted sum identities for second-order recurrences. By shifting the mathematical focus from parameter tuning to sequence autonomy, the SuperSury Identity uncovers hidden symmetrical structures within classical number theory and provides a clear blueprint for higher-order sequence extensions.

Table 3: Computational Verification for Identity 1 (Lucas 3-step)

n	Identity 1 LHS	Identity 1 RHS	Match
0	2	2	True
1	-6	-6	True
2	66	66	True
3	-542	-542	True
4	4610	4610	True
5	-39038	-39038	True
6	330754	330754	True
7	-2802174	-2802174	True

Table 4: Computational Verification for Identity 2 (A015530)

n	Identity 2 LHS	Identity 2 RHS	Match
0	1	1	True
1	4	4	True
2	19	19	True
3	88	88	True
4	409	409	True
5	1900	1900	True
6	8827	8827	True
7	41008	41008	True

Table 5: General SuperSury Validation ($t = 14/29$, Scale Factor = $38/29$)

n	SuperSury LHS	SuperSury RHS	Match
0	38	38	True
1	190	190	True
2	874	874	True
3	3990	3990	True
4	18202	18202	True
5	83030	83030	True
6	378746	378746	True
7	1727670	1727670	True