Slovenian Language Assistance Bot (SLAB)

Luka Škodnik, Robert Jutreša, Valter Hudovernik

Abstract

Slavko je car!

Keywords

Large Language Models, Machine Translation, Conversational AI, Slovene, Question Answering

Introduction

Natural Language Processing (NLP) is an exciting field of Artificial Intelligence that focuses on teaching machines how to understand and respond to human language. In this report, we will discuss our project for the Natural Language Processing course 2022/23, where we aim to develop a Slovenian Language Assistance Bot (SLAB) using NLP techniques. We will provide an overview of our preliminary research, discuss our idea to use a GPT-based model, and explore various data sources that we plan to use to train our model. Finally, we will discuss the importance of estimating the amount of data required to train a model effectively.

Initial Plan

Due to large amounts of conversational datasets being available in other languages. We focus on translating the most widely used and well-composed datasets into Slovenian. For this reason, one of our main tasks is developing a framework for robust translation from English to Slovene.

Our initial idea for doing this is to use multiple methods of translation and aggregate the results in a meaningful way. To this aim we consider the Slovene NMT [1], NLLB-200 [2], DeeplTranslator [3], GoogleTranslate [4], or other open-source translator supported by the deep translator python library [5]. The initial idea is to produce a metric of agreement on the individual translations and in this way filter the translated data. This should reduce the individual mistakes of each of the used methods and yield at least some usable data for further use.

For evaluating the quality of translations and generating new data examples we look at adapting the Self-Instruct [6] pipeline for self supervised data filtering.

An interesting remark in the recent GPT-4 report by Openai claims that pre-training had much more of an effect on the performance of the model as opposed to fine-tuning. However, we disclaim that this is a statement we are not able to verify as thier results are not reporoducible. Still, they have been in the foreground of the recent LLM developments so, we also put an emphasis on using and looking into additional resources for unsupervised pre-training for the Slovenian language.

To this purpose we examine the following resources; the NLP projects of other groups and large Slovenian language corpuses such as Gigafida [7] and ccKRES [8] , we also consider the Šolar corpus [9], with considerations that the written language of primary and high school students could potentially have an impact on the models performance, and GOS [10] with similar considerations about spoken language.

Related Work

Transformers & Large Language Models

Attention [11] is a key component of transformer models, which are widely used in natural language processing tasks such as language translation and text summarization. It is also a part of many modern large language models (LLM) that we will use during this project. In transformer models, attention mechanisms allow the model to focus on the most relevant parts of the input sequence at each step of processing. This is achieved by assigning weights to each element in the input sequence based on its relevance to the current step. By doing so, the transformer can capture long-range dependencies between different parts of the input sequence, which is particularly important for language processing.

SloBERTa [12] is a Slovene large language model. It is a large pre-trained masked language model based on the BERT architecture. The authors trained the model on a large

corpus of Slovene text and evaluated it on various downstream tasks such as text classification, named entity recognition, and part-of-speech tagging. The results show that SloBERTa outperforms existing Slovene language models and achieves competitive performance with state-of-the-art multilingual language models.

Datasets

The P3 dataset is a collection of prompted English datasets covering a diverse set of NLP tasks. The use of prompts allows for the creation of consistent and standardized data examples across different datasets, which can facilitate the development of new models and the comparison of results across different tasks [13].

A corpus of automatically annotated TV series subtitles for dialogue construction was developed in [14]. The authors used a combination of rule-based and machine-learning techniques to identify speaker turns and assign speaker identities. They evaluated their method on a corpus of subtitled TV series episodes and achieved high accuracy in speaker identification and turn-taking recognition. The resulting corpus was used for various downstream tasks such as emotion recognition and dialogue act classification.

GOS [10] is a reference corpus of spoken Slovene language. The methodology used to collect the corpus involved recording conversations of native Slovene speakers in various domains such as business, education, and social interactions. The transcription process involved annotating the recordings with orthographic, phonetic, and prosodic information. The resulting corpus was used for various research tasks such as acoustic modeling, speaker recognition, and speech synthesis.

Alpaca [15] by Standford University is a set consisting of a data generation procedure, dataset, and training recipe. It is a fine tuned model from 7B LLaMA [16] on 52K instruction-following data generated by the techniques in the Self-Instruct [6] paper, with some modifications. In a preliminary human evaluation, it was found that the Alpaca 7B model behaves similarly to the GPT-3 model on the Self-Instruct instruction-following evaluation suite.

BLOOM [17] a multilingual LLM was trained on the ROOTS corpus [18], amounting to 1.61 terabytes of text that span 46 natural languages and 13 programming languages. Unfortunately Slovenian is not one of the available languages. However, due to vast collections of datasets available such as Hugging Face datasets [19], we focus on developing tools for robust translation in order to translate the large amounts of available data to Slovenian in order to facilitate the development of a conversational LLM.

SuperGLUE [20] is a benchmark for evaluating the performance of natural language understanding models. It consists of eight challenging natural language understanding tasks, including both textual entailment and commonsense reasoning tasks. The benchmark is designed to test the ability of models to handle more complex linguistic phenomena and to generalize to new examples. The authors compare the performance of several state-of-the-art models on SuperGLUE and find that there is still a significant gap between the best models and human performance.

The paper [21] discusses the challenges of question answering for less-resourced languages and presents an adaptation of the English UnifiedQA approach to the Slovene language. The adaptation uses encoder-decoder transformer models (SloT5 and mT5) to handle different question-answering formats, and existing Slovene adaptations of four datasets, as well as machine translation of the MCTest dataset. The study shows that a general model can perform at least as well as specialized models for answering questions in different formats. However, the performance of the Slovene model still lags behind that of English, and cross-lingual transfer from English is used to improve the results.

Methods
Results
Discussion
Acknowledgments
References

[1] Iztok Lebar Bajec, Andraž Repar, Jure Demšar, Žan Bajec, Mitja Rizvič, Borut Kumperščak, and Marko Bajec. Neural machine translation model for slovene-english language pair RSDO-DS4-NMT 1.2.6, 2022. Slovenian language resource repository CLARIN.SI.

[2] NLLB Team, Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia-Gonzalez, Prangthip Hansanti, John Hoffman, Semarley Jarrett, Kaushik Ram Sadagopan, Dirk Rowe, Shannon Spruit, Chau Tran, Pierre Andrews, Necip Fazil Ayan, Shruti Bhosale, Sergey Edunov, Angela Fan, Cynthia Gao, Vedanuj Goswami, Francisco Guzmán, Philipp Koehn, Alexandre Mourachko, Christophe Ropers, Safiyyah Saleem, Holger Schwenk, and Jeff Wang. No language left behind: Scaling human-centered machine translation. 2022.

[3] DeepL GmbH. DeepL Translator. https://www.deepl.com/translator, Accessed 2023, March 21.

[4] Google LLC. Google Translate. https://translate.google.com/?hl=sl, Accessed 2023, March 21.

[5] deep-translator 1.10.1.

[6] Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language model with self generated instructions, 2022.

[7] Simon Krek, Tomaž Erjavec, Andraž Repar, Jaka Čibej, Špela Arhar Holdt, Polona Gantar, Iztok Kosem, Marko Robnik-Šikonja, Nikola Ljubešić, Kaja Dobrovoljc, Cyprian Laskowski, Miha Grčar, Peter Holozan, Simon Šuster, Vojko Gorjanc, Marko Stabej, and Nataša Logar. Corpus of written standard slovene gigafida 2.0, 2019. Slovenian language resource repository CLARIN.SI.

[8] N Logar Berginc, M Grčar, M Brakus, T Erjavec, Š Arhar Holdt, and S Krek. *Korpusi slovenskega jezika Gigafida, KRES, ccGigafida in ccKRES: gradnja, vsebina, uporaba.* Institut za slovenski jezik Frana Ramovša ZRC SAZU, Ljubljana, 2012.

[9] Iztok Kosem, Tomaž Rozman, and Mateja Stritar. How do slovenian primary and secondary school students write and what their teachers correct: A corpus of student writing. In *Proceedings of Corpus Linguistics Conference*, pages 20–22, July 2011.

[10] Darinka Verdonik, Iztok Kosem, Ana Zwitter Vitez, Simon Krek, and Marko Stabej. Compilation, transcription and usage of a reference speech corpus: the case of the slovene corpus GOS. *Language Resources and Evaluation*, 47(4):1031–1048, January 2013.

[11] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[12] Matej Ulčar and Marko Robnik-Šikonja. Sloberta: Slovene monolingual large pretrained masked language model. *Proceedings of SI-KDD within the Information Society 2021*, pages 17–20, 2021.

[13] Stephen H Bach, Victor Sanh, Zheng-Xin Yong, Albert Webson, Colin Raffel, Nihal V Nayak, Abheesht Sharma, Taewoon Kim, M Saiful Bari, Thibault Fevry, et al. Promptsource: An integrated development environment and repository for natural language prompts. *arXiv preprint arXiv:2202.01279*, 2022.

[14] Leilan Zhang and Qiang Zhou. Automatically annotate tv series subtitles for dialogue corpus construction. In *2019 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC)*, pages 1029–1035, 2019.

[15] Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Stanford alpaca: An instruction-following llama model. https://github.com/tatsu-lab/stanford_alpaca, 2023.

[16] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. Llama: Open and efficient foundation language models, 2023.

[17] Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, Matthias Gallé, et al. Bloom: A 176b-parameter open-access multilingual language model. *arXiv preprint arXiv:2211.05100*, 2022.

[18] Hugo Laurençon, Lucile Saulnier, Thomas Wang, Christopher Akiki, Albert Moral, Teven Scao, Leandro Werra, Chenghao Mou, Eduardo Ponferrada, Huu Nguyen, Jörg Frohberg, Mario Šaško, Quentin Lhoest, Angelina McMillan-Major, Gerard Dupont, Stella Biderman, Anna Rogers, Loubna allal, Francesco Toni, and Yacine Jernite. The bigscience roots corpus: A 1.6tb composite multilingual dataset. 03 2023.

[19] Quentin Lhoest, Albert Villanova del Moral, Yacine Jernite, Abhishek Thakur, Patrick von Platen, Suraj Patil, Julien Chaumond, Mariama Drame, Julien Plu, Lewis Tunstall, et al. Datasets: A community library for natural language processing. *arXiv preprint arXiv:2109.02846*, 2021.

[20] Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. *Advances in neural information processing systems*, 32, 2019.

[21] Katja Logar and Marko Robnik-Šikonja. Unified question answering in slovene, 2022.