



LUXEMBOURG
LET'S MAKE IT HAPPEN

Uni.lu HPC School 2021

PS2: Preliminaries (SSH - Open OnDemand)

Uni.lu High Performance Computing (HPC) Team

T. Valette and A. Olloh

University of Luxembourg (UL), Luxembourg

<http://hpc.uni.lu>



Latest versions available on Github:



UL HPC tutorials:

<https://github.com/ULHPC/tutorials>

UL HPC School:

hpc.uni.lu/education/hpcschool

PS2 tutorial sources:

ulhpc-tutorials.rtfd.io/en/latest/preliminaries



Summary

1 Introduction

2 Preliminaries Setup on your Laptop/Workstation

System Environment Adaptation

Distributed Version Control with Git

3 SSH Secure Shell

Installation

Usage

Data transfer using SSH

Prepare your laptop for next Practical Sessions

4 Discover Open OnDemand

Main Objectives of this Session



- Review **recommended setup for your personnal Laptop**
 - ↪ Windows, Mac OS or Linux
- Understand **SSH** (Secure SHell)
- **Review SSH configuration** allowing to connect to the **UL HPC Platform**
 - ↪ SSH configuration
 - ↪ Generate your SSH key pair
 - ↪ Upload your SSH key on ULHPC Identity Management Portal
- **Discover ULHPC Open OnDemand**
 - ↪ HPC Web portal
 - ↪ Job composer

OPEN  **OnDemand**

Vocabulary related to HPC (1/2)

Compute node physical server on which we run the computation (your code)

Cluster group of compute nodes interconnected to each others

Processor/CPU Central Processing Unit usually refers to a processor, chip of the server that process the instructions of the program

Core 1 processor chip usually contains several CPUs named cores

GPU Graphics Processing Unit, chip designed for image processing and computer graphics

Vocabulary related to HPC (2/2)

Resources Every component of the cluster that you have access. Can refer to CPU, core, memory, network switch...

Job Scheduler Software that schedule all the jobs according to their priority.

Job Allocation resources for a specific user and a specific amount of time

Reservation Allocate a job in the future, in advance in respect with rules (priority, job type...)

Walltime Maximum time allocated for a specific job

Job queue Before being scheduled, jobs are waiting in a queue for being processed by the scheduler

Partition Set of resources (nodes) with the same policies applied to it

Summary

1 Introduction

2 Preliminaries Setup on your Laptop/Workstation

System Environment Adaptation

Distributed Version Control with Git

3 SSH Secure Shell

Installation

Usage

Data transfer using SSH

Prepare your laptop for next Practical Sessions

4 Discover Open OnDemand

Preliminaries

ULHPC Tutorials: Setup Preliminaries

ulhpc-tutorials.rtfd.io/en/latest/setup/preliminaries

- **Pre-configuration expected on your laptop**
- **Online Accounts**, at least:
 - Uni.lu HPC - read and accept the [Acceptable Use Policy \(AUP\) 2.0](#)
 - Github - recommended professional login: <letter><name> (Ex: svarrette)
 - Vagrant Cloud
 - Docker Hub

- All instructions/practical sessions guided against a Unix/Linux system
 - Native OS within **all** HPC facilities
 - interaction from any OS (Windows, Mac OS or Linux) is possible for **all** operations
 - ✓ ... unlike WebEx Training/Event

Recommended Software List

Platform	Software	Description	Usage
Mac OS	Homebrew	The missing package manager for macOS	<code>brew install ...</code>
Mac OS	iTerm2	enhanced Terminal	
Windows	Chocolatey	Package Manager for Windows	<code>choco install ...</code>
Windows	Windows Subsystem for Linux (WSL)	Emulation-like translation of Linux kernel system calls	
Windows	Ubuntu over WSL	Linux Ubuntu on Windows	
Windows	Windows Terminal		
Windows	MobaXTERM	Terminal with tabbed SSH client	
Windows	SourceTree	enhanced git GUI	
Windows/Linux	Virtual Box	Free hypervisor provider for Vagrant	
Windows/Linux	Vagrant	Reproducible environments made easy.	
Windows	Docker for Windows	Lightweight Reproducible Containers	
Linux	Docker for Ubuntu	Lightweight Reproducible Containers	

Preliminaries Setup for Windows

≥ Windows 10 release 1607

- New “Windows Subsystem for Linux” Ubuntu Linux binaries
 - can run directly on Windows without the need for the Linux Kernel running in a VM.
 - ✓ provides emulation-like translation of Linux kernel system calls to the Windows kernel
 - Windows *feature, requires to turn on Developer mode*
- Install Ubuntu within the Microsoft Store
 - You now have an Ubuntu terminal by running bash command
 - ✓ (*optional*) consider installing oh-my-zsh and the Powerlevel10k prompt - [guide](#)
- Install Windows Terminal
 - Setup prompt in Windows Terminal & PowerShell
 - Now open Ubuntu profile
 - ✓ enjoy an *fully-featured Linux terminal*
 - ... incl. native SSH
- (*also for OLD systems*) install MobaXterm



Preliminaries Setup for Linux (incl. WSL Ubuntu) & Mac OS

- Native SSH client available, accessible with your terminal
 - Make sure you can open and interact with a terminal on your computer
 - There exists **better** terminal applications than the default ones proposed on your system
 - ✓ Mac OS: iTerm2
 - ✓ Windows Terminal
 - ✓ Linux: Guake Terminal, Terminator
- If you already have an SSH Client, you should have this following output:

```
$(laptop)> ssh -V
OpenSSH_8.8p1, OpenSSL 1.1.11 24 Aug 2021
```

- **(optional)** If you want a fancy et nice terminal layout, consider using zsh and oh-my-zsh
 - [guide](#) for Linux
 - [guide](#) for Mac OS

Git in a Nutshell

- **Distributed Version Control System**
 - ↪ Manage changes in documents and Keep the history
- **Synchronization with a server (optional)**
 - ↪ Collaborative work
 - ↪ Backup of your documents/code
- Well suited for **text** files (source code, LaTeX article etc.)
 - ↪ can also be used for binary files (images, HDF5, Office docs...)
 - ✓ if the size is reasonable
 - ↪ typically avoid to version temporary (scratch) files
 - ↪ extension exists to support large files (Git-LFS)



Installation Notes

```
### Mac OS X, using Homebrew - https://brew.sh
brew install git git-gui git-flow gitk tig kdiff3
### Ubuntu / WSL / RedHat
{ sudo apt-get | yum } install git-core git-flow tig gitk kdiff3
### Windows, using Chocolatey - https://chocolatey.org/
$> choco.exe install gitflow-avh
```

- **Windows:** Git for Windows: incl. Git Bash/GUI & Shell Integration
 - ↪ (better) Windows Subsystem for Linux (WSL)
 - ✓ Ubuntu for Windows within the Microsoft Store



Installation Notes

```
### Mac OS X, using Homebrew - https://brew.sh
brew install git git-gui git-flow gitk tig kdiff3
### Ubuntu / WSL / RedHat
{ sudo apt-get | yum } install git-core git-flow tig gitk kdiff3
### Windows, using Chocolatey - https://chocolatey.org/
$> choco.exe install gitflow-avh
```

- **Windows:** Git for Windows: incl. Git Bash/GUI & Shell Integration
 - ↪ (better) Windows Subsystem for Linux (WSL)
 - ✓ Ubuntu for Windows within the Microsoft Store


Your Turn!

- Ensure you have git installed on your system

git --version

Other related tools


- Git GUI (default): **GitK**



Other related tools


- Git GUI (Mac OS): [GitX-dev](#)

<http://rowanj.github.io/gitx/>



Other related tools

- Git GUI (Windows/Mac OS): **SourceTree**
→ Alternatives: <https://git-scm.com/downloads/guis/>



Preliminary Configurations

- You **SHOULD** at least configure your name and email to commit
 - ↪ (optional but useful) inform Git of your GPG signing key

```
### Basic Git defaults - open a Terminal
git config --global user.name "Firstname LastName"
git config --global user.email "<email>@<domain>"
git config --global user.signingkey <gpg-keyID> # <-- Leave this part if you don't
                                                # have a gpg-keyID
git config --global color.ui true
# Check that the changes are effective (see also ~/.gitconfig or ~/.config/git/config)
git config -l | grep user
```

Preliminary Configurations

- You **SHOULD** at least configure your name and email to commit
 - ↪ (optional but useful) inform Git of your GPG signing key

```
### Basic Git defaults - open a Terminal
git config --global user.name "Firstname LastName"
git config --global user.email "<email>@<domain>"
git config --global user.signingkey <gpg-keyID> # <-- Leave this part if you don't
                                                # have a gpg-keyID
git config --global color.ui true
# Check that the changes are effective (see also ~/.gitconfig or ~/.config/git/config)
git config -l | grep user
```

Hands-on Git Config

▶ url ◀ | [github](#) | [src](#)

- [Git](#) Installation and useful derived tools
- [Git Initial Setup](#)

[git-flow](#), [tig](#), [kdiff3](#), [meld](#)...
[git config --global \[...\]](#)
Uni.lu HPC School 2021/ PS2

Shell Integration: Bash prompt

For experienced users only!

- Bash Prompt integration: `__git_ps1()` in your PS1 variable
→ See [contrib/completion/git-prompt.sh](#) (Git Sources)

```
~/src/libgit2 (development *)$ █
```

Shell Integration: Bash prompt

For experienced users only!

- Bash Prompt integration:
→ See [contrib/completion/git-prompt.sh](#) (Git Sources)
- OR **Agnoster Theme for Bash**
→ requires a Powerline-patched font


```
~ > cd testproject
~/testproject > master > gco detached-head-state -q
~/testproject > - fdffaf6 touch dirty-working-directory
~/testproject > - fdffaf6± cd
~ > ssh milly
Welcome to Ubuntu 11.04 (GNU/Linux 2.6.18-308.8.2.el5.028stab101.1 x86_64)
Last login: Wed Sep 26 03:42:49 2012 from 71-215-222-90.mpls.qwest.net
agnoster@milly ~
Connection to milly.agnoster.net closed.
~ > sudo -s
Password:
$ root@Arya ~ > top &
[1] 34523
[1] + 34523 suspended (tty output) top
$ root@Arya ~ > rm no-such-file
rm: no such file: No such file or directory
x $ root@Arya ~ > kill %
[1] + 34523 terminated top
$ root@Arya ~
```

Shell Integration: ZSH



For experienced users only!

- Oh my ZSH!:
 - community-driven framework
 - manages your Zsh configuration
 - multiple **plugins**, (super nice) **themes**
 - ✓ Ex: agnoster theme / powerline
 - Install: <https://ohmyz.sh/#install>
- Consider Powerlevel10k theme for ZSH



The terminal window displays three different ZSH themes:

- Lean Style
- Classic Style
- Rainbow Style

In each theme, the terminal shows the command `git status` output:

```
q ~ ~/src on master
> [red bar]
```

Time taken for the command:

- Lean Style: 5s
- Classic Style: took 5s at 16:23:42
- Rainbow Style: took 5s at 16:23:42

Shell Integration: Powershell

- You probably want to install Windows Terminal
 - Install the Windows Terminal from the Microsoft Store.
 - Install the Cascadia Code PL font



Shell Integration: Powershell

- You probably want to install Windows Terminal
 - Install the Windows Terminal from the Microsoft Store.
 - Install the Cascadia Code PL font

For experienced users only!

- Install posh-git and oh-my-posh:

```
# Install posh-git and oh-my-posh in (administrator) powershell
# If Error: "Running scripts is disabled on this system"
Get-ExecutionPolicy -List
Set-ExecutionPolicy RemoteSigned -Scope CurrentUser
# Install
Install-Module posh-git -Scope CurrentUser
Install-Module oh-my-posh -Scope CurrentUser
Set-Theme Paradox
```



Summary

1 Introduction

2 Preliminaries Setup on your Laptop/Workstation

System Environment Adaptation

Distributed Version Control with Git

3 SSH Secure Shell

Installation

Usage

Data transfer using SSH

Prepare your laptop for next Practical Sessions

4 Discover Open OnDemand

SSH: Secure Shell

- Ensure **secure** connection to remote (UL) server
 - ↪ establish **encrypted** tunnel using **asymmetric keys**
 - ✓ **Public** id_rsa.pub vs. **Private** id_rsa (**without** .pub)
 - ✓ typically on a non-standard port (**Ex:** 8022)
 - ✓ Basic rule: 1 machine = 1 key pair
 - ↪ the private key is **SECRET**: **never** send it to anybody
 - ✓ Can be protected with a passphrase

limits kiddie script

SSH: Secure Shell


- Ensure **secure** connection to remote (UL) server
 - ↪ establish **encrypted** tunnel using **asymmetric keys**
 - ✓ **Public** id_rsa.pub vs. **Private** id_rsa (**without** .pub)
 - ✓ typically on a non-standard port (**Ex:** 8022)
 - ✓ Basic rule: 1 machine = 1 key pair
 - ↪ the private key is **SECRET**: **never** send it to anybody
 - ✓ Can be protected with a passphrase
- SSH is used as a secure backbone channel for **many** tools
 - ↪ Remote shell **i.e** remote command line
 - ↪ File transfer: **rsync**, **scp**, **sftp**
 - ↪ versioning synchronization (**svn**, **git**), **github**, **gitlab** etc.

limits kiddie script


SSH: Secure Shell

- Ensure **secure** connection to remote (UL) server
 - ↪ establish **encrypted** tunnel using **asymmetric keys**
 - ✓ **Public** id_rsa.pub vs. **Private** id_rsa (**without** .pub)
 - ✓ typically on a non-standard port (**Ex:** 8022)
 - ✓ Basic rule: 1 machine = 1 key pair
 - ↪ the private key is **SECRET**: **never** send it to anybody
 - ✓ Can be protected with a passphrase
- SSH is used as a secure backbone channel for **many** tools
 - ↪ Remote shell **i.e** remote command line
 - ↪ File transfer: **rsync**, **scp**, **sftp**
 - ↪ versioning synchronization (**svn**, **git**), **github**, **gitlab** etc.
- Authentication:
 - ↪ **password** (disable if possible)
 - ↪ (**better**) **public key authentication**


SSH: Public Key Authentication




SSH: Public Key Authentication




SSH: Public Key Authentication



SSH: Public Key Authentication



SSH: Public Key Authentication



SSH: Public Key Authentication

- **Restrict to public key authentication:** /etc/ssh/sshd_config:

```
PermitRootLogin no
# Disable Passwords
PasswordAuthentication no
ChallengeResponseAuthentication no
```

```
# Enable Public key auth.
RSAAuthentication yes
PubkeyAuthentication yes
```

SSH Setup on Linux / Mac OS

- OpenSSH natively supported; configuration directory : `~/.ssh/`
 - ↪ package `openssh-client` (Debian-like) or `ssh` (Redhat-like)
- SSH Key Pairs (public vs private) generation:
 - ↪ specify a **strong passphrase**
 - ✓ protect your **private** key from being stolen **i.e.** impersonation
 - ✓ **drawback:** passphrase must be typed to use your key

ssh-keygen

SSH Setup on Linux / Mac OS

- OpenSSH natively supported; configuration directory : `~/.ssh/`
 - ↪ package `openssh-client` (Debian-like) or `ssh` (Redhat-like)
 - SSH Key Pairs (public vs private) generation:
 - ↪ specify a **strong passphrase**
 - ✓ protect your **private** key from being stolen **i.e.** impersonation
 - ✓ ~~drawback: passphrase must be typed to use your key~~
- ssh-keygen**
- ssh-agent**

SSH Setup on Linux / Mac OS

- OpenSSH natively supported; configuration directory : `~/.ssh/`
 - ↪ package `openssh-client` (Debian-like) or `ssh` (Redhat-like)
- SSH Key Pairs (public vs private) generation:
 - ↪ specify a **strong passphrase**
 - ✓ protect your **private** key from being stolen **i.e.** impersonation
 - ✓ ~~drawback:~~ ~~passphrase must be typed to use your key~~

`ssh-keygen`

`ssh-agent`

DSA Keys + RSA 1024/2048 bits Dare deprecated now!

SSH Setup on Linux / Mac OS

- OpenSSH natively supported; configuration directory : `~/.ssh/`
 - ↪ package `openssh-client` (Debian-like) or `ssh` (Redhat-like)
 - SSH Key Pairs (public vs private) generation:
 - ↪ specify a **strong passphrase**
 - ✓ protect your **private** key from being stolen i.e. impersonation
 - ✓ ~~drawback: passphrase must be typed to use your key~~
- `ssh-keygen`
- `ssh-agent`

DSA Keys + RSA 1024/2048 bits Dare deprecated now!

```
$> ssh-keygen -t rsa -b 4096 -o -a 100          # 4096 bits RSA
(better) $> ssh-keygen -t ed25519 -o -a 100      # new sexy Ed25519
```

Private (identity) key

`~/.ssh/id_{rsa,ed25519}`

Public Key

`~/.ssh/id_{rsa,ed25519}.pub`

SSH Setup on Windows: the OLD way

- Putty Suite, includes:
 - PuTTY, the free SSH client
 - Pageant, an SSH authentication agent for PuTTY tools
 - PLink, th PuTTy CLI and PuTTYgen, an RSA and DSA key generation utility

SSH Setup on Windows: the OLD way

- Putty Suite, includes:
 - PuTTY, the free SSH client
 - Pageant, an SSH authentication agent for PuTTY tools
 - PLink, the PuTTY CLI and PuTTYgen, an RSA and DSA key generation utility

PuTTY ≠ OpenSSH

SSH Setup on Windows: the OLD way

- Putty Suite, includes:
 - PuTTY, the free SSH client
 - Pageant, an SSH authentication agent for PuTTY tools
 - PLink, th PuTTy CLI and PuTTYgen, an RSA and DSA key generation utility


PuTTY ≠ OpenSSH

- Putty keys are **NOT** supported by OpenSSH (yet can be exported)
- Binding Pageant with OpenSSH agent is **NOT** natively supported
 - Third-party tools like `ssh-pageant` are made for that
 - Combine nicely with `Git bash`
- with PLink, hostnames eventually refer to **PuTTY Sessions**
 - **NEVER** to SSH entries in `~/.ssh/config`
 - This usage might be hidden... Ex: `$GIT_SSH` etc.


<https://git-for-windows.github.io/>

SSH Setup on Windows



- New “**Windows Subsystem for Linux**” Ubuntu Linux binaries
 - ↪ Windows feature, requires to turn on Developer mode
 - ↪ Install Ubuntu within the [Microsoft Store](#)
 - ↪ You now have an Ubuntu terminal by running bash command
 - ✓ ([optional](#)) consider installing [oh-my-zsh](#) and the [Powerlevel10k](#) prompt - [guide](#)
- Install [Windows Terminal](#)
 - ↪ Setup prompt in Windows Terminal and PowerShell - [guide](#)
 - ↪ Now open Ubuntu profile to enjoy an fully-featured Linux terminal, incl. native SSH




SSH Setup on Windows with X11 support



- Use **MobaXterm** to Run Graphical Linux App
 - [tabbed] Sessions management
 - X11 server w. enhanced X extensions
 - SSH gateway / tunnels wizards
 - **Run your WSL Ubuntu profile by default**
 - ✓ share Ubuntu home (and SSH setup)




Send your public key to ULHPC



- Connect to **ULHPC IPA portal** (the url is in your registration email)
 - ↪ Go to **your profile** page (step 1 & 2)
 - ↪ Add your **PUBLIC** SSH key (step 3)
 - ↪ **Save** your profile (step 4)

Send your public key to ULHPC



The screenshot shows the Red Hat Identity Management interface for managing user profiles. The top navigation bar includes tabs for Identity, Policy, Authentication, Network Services, and IPA Server. The main menu has options for Users, Hosts, Services, Groups, ID Views, Automember, and Active users (with a selected entry for 'tvallette'). A sub-menu for 'tvallette' is open, showing options: Profile (highlighted with red circle 1), Change password, Customization, About, and Logout.

User Profile Fields:

- Identity Settings:** Includes fields for Job role (Infrastructure and architecture engineer), First name (Teddy), Last name (Valette), Full name (Teddy Valette), Display name (Teddy Valette), Initial (TV), GECOS (Teddy Valette), and Class.
- Account Settings:** Includes fields for User login (tvallette), Password (*****), Password expiration (disabled), UID (disabled), GID (disabled), Principal alias (tvallette@HPC.UNILUX), Kerberos principal expiration (disabled), Login shell (/bin/bash), Home directory (disabled), SSH public keys (disabled), and Certificates (disabled).

Annotations:

- A red circle labeled '1' points to the 'Profile' option in the user context menu.
- A red circle labeled '2' points to the 'Logout' option in the user context menu.
- A red circle labeled '3' points to the 'Add' button under the 'Certificates' section.
- A red circle labeled '4' points to the 'Actions' dropdown menu at the top of the page.

SSH in Practice

~/.ssh/config

```
$> ssh [-X] [-p <port>] <login>@<hostname>  
# Example: ssh -p 8022 svarrette@access-iris.uni.lu
```

```
Host <shortname>  
  Port <port>  
  User <login>  
  Hostname <hostname>
```

- `~/.ssh/config:`
 - Simpler commands
 - Bash completion \$> ssh iri<TAB>

SSH in Practice

~/.ssh/config

```
$> ssh [-X] [-p <port>] <login>@<hostname>  
# Example: ssh -p 8022 svarrette@access-iris.uni.lu
```

```
Host *.ext_ul  
    ProxyCommand ssh -q iris-cluster \  
        -W `basename %h .ext_ul`:%p  
# UL HPC Platform -- http://hpc.uni.lu  
Host iris-cluster  
    Hostname access-iris.uni.lu  
Host aion-cluster  
    Hostname access-aion.uni.lu  
Host *-cluster  
    User login #ADAPT accordingly  
    Port 8022  
    ForwardAgent no
```

```
Host <shortname>  
    Port <port>  
    User <login>  
    Hostname <hostname>
```

- ~/.ssh/config:
 - Simpler commands
 - Bash completion \$> ssh iri<TAB>

SSH in Practice

~/.ssh/config

```
$> ssh [-X] [-p <port>] <login>@<hostname>  
# Example: ssh -p 8022 svarrette@access-iris.uni.lu
```

```
Host *.ext_ul  
    ProxyCommand ssh -q iris-cluster \  
        -W `basename %h .ext_ul`:%p  
# UL HPC Platform -- http://hpc.uni.lu  
Host iris-cluster  
    Hostname access-iris.uni.lu  
Host aion-cluster  
    Hostname access-aion.uni.lu  
Host *-cluster  
    User login #ADAPT accordingly  
    Port 8022  
    ForwardAgent no
```

```
Host <shortname>  
    Port <port>  
    User <login>  
    Hostname <hostname>
```

- ~/.ssh/config:
 - Simpler commands
 - Bash completion \$> ssh iri<TAB>

```
$> ssh iris-cluster  
$> ssh work  
$> ssh work.ext_ul
```

SSH Training - Application to Uni.lu HPC Access

Your Turn!

Hands-on SSH

▶ url ◀ | [github](#) | [src](#)

- **SSH Key Management**

↪ Generate strong RSA (4096 bits) & [reference] ED25519 Key pairs

- **Upload the keys on the ULHPC Identity Management Portal**

- **Custom SSH Configuration**

`~/.ssh/config`

↪ (advanced users only) SSH Agent, SOCKS Proxy

SSH Training - Application to Uni.lu HPC Access

Your Turn!

Hands-on SSH

▶ url ◀ | [github](#) | [src](#)

- **SSH Key Management**

↪ Generate strong RSA (4096 bits) & [reference] ED25519 Key pairs

- **Upload the keys on the ULHPC Identity Management Portal**

- **Custom SSH Configuration**

`~/.ssh/config`

↪ (advanced users only) SSH Agent, SOCKS Proxy

Hands-on Access to Uni.lu HPC Facility

▶ url ◀ | [github](#) | [src](#)

- **Connect** to UL HPC (Linux / Mac OS / Unix)

(Step 1)

Data transfer using SSH - SCP

- SCP (Secure CoPy):
 - from your local terminal
 - plain linear copy

```
$> scp [-P <port>] [remote:]src/ [remote:]dst/
```

```
# If you have configured your SSH client as explained before
scp /tmp/test_file aion-cluster:~
# If you haven't
scp -P 8022 /tmp/test_file tvallette@access-aion.uni.lu:~/
```

Data transfer using SSH - RSync

- RSync (Remote SYNChronization):
 - ↪ from your local terminal
 - ↪ algorithm to optimize the transfer of files
 - ✓ based on differences between local files and remote ones

```
$> rsync [-e '<ssh options>'] [remote:]src/ [remote:]dst/
```


```
# If you have configured your SSH client as explained before
rsync /tmp/test_file aion-cluster:~
# If you haven't
rsync -e 'ssh -p 8022' /tmp/test_file tvallette@access-aion.uni.lu:~/
```

Data transfer using SSH - FileZilla

- FileZilla:

- ↪ Well known GUI (with a big community) compatible with Windows, Linux and MacOS
- ↪ Open "Site Manager" (step 1)
- ↪ Create a new site (step 2)
- ↪ Fill the following fields (step 3)
 - ✓ Protocol: SFTP - SSH File Transfer Protocol
 - ✓ Host: access-iris.uni.lu (**or access-aion.uni.lu**)
 - ✓ Port: 8022
 - ✓ Logon Type: Key file
 - ✓ User:
 - ✓ Key file:
- ↪ Connect and drag and drop files from your local to your remote site and vice versa

Data transfer using SSH - FileZilla



Data transfer Training

Your Turn!

Hands-on Data transfer using SSH

▶ url ◀ | [github](#) | [src](#)

- **Install your favorite tool**

- ↪ Mac OS/Linux : scp, rsync, Filezilla
- ↪ Windows : WSL (scp, rsync), Filezilla
- ✓ You can also use the MobaXTerm's data transfer feature

- Start transferring your files

wget, scp, rsync, MobaXterm(SFTP)

ULHPC School Tutorials

- You **need to use git to get training materials** required for Practical Sessions
 - ↪ Training materials are stored on Github: [ULHPC/tutorials](#) repository
 - ↪ You should **clone** this repository:
 - ✓ **locally** on your laptop to have quick access to the material offline
 - ✓ **remotely** within your ULHPC homedir to be able to practice and follow the PS
 - ↪ At any point of time, you can **pull** the latest updates `git pull (or better) make up)`
- **Pre-requisite:** make sure you have a working SSH and git environment!

ULHPC School Tutorials

- You **need to use git to get training materials** required for Practical Sessions
 - ↪ Training materials are stored on Github: [ULHPC/tutorials](#) repository
 - ↪ You should **clone** this repository:
 - ✓ **locally** on your laptop to have quick access to the material offline
 - ✓ **remotely** within your ULHPC homedir to be able to practice and follow the PS
 - ↪ At any point of time, you can **pull** the latest updates `git pull (or better) make up)`

- **Pre-requisite:** make sure you have a working SSH and git environment!

Your Turn!

- Open your terminal (iTerm2, Terminator, MobaXTerm, ...) & follow next instructions

Keep Sync with Uni.lu HPC Training Material

```
### First time: clone the repo under a meaningful path
$> mkdir -p ~/git/github.com/ULHPC
$> cd ~/git/github.com/ULHPC
$> git clone https://github.com/ULHPC/tutorials.git
$> cd tutorials
$> make setup
### Next times: pull latest changes
$> cd ~/git/github.com/ULHPC/tutorials
$> make up      # update both branches (production and devel)

# Prepare a dedicated (separated) working directory
$> mkdir -p ~/tutorials/ULHPC-School-2021
$> cd ~/tutorials/ULHPC-School-2021
# create a symbolic link pointing to the tutorial reference material
$> ln -s ~/git/github.com/ULHPC/tutorials ref.d
# Now $HOME/tutorials/ULHPC-School-2021/ref.d/ points to reference training material
```

Summary

1 Introduction

2 Preliminaries Setup on your Laptop/Workstation

System Environment Adaptation

Distributed Version Control with Git

3 SSH Secure Shell

Installation

Usage

Data transfer using SSH

Prepare your laptop for next Practical Sessions

4 Discover Open OnDemand

ULHPC Open OnDemand (OOD) Portal



• Open OnDemand (OOD)

- ↪ Web portal
 - ✓ compatible with Windows, Linux and MacOS (thanks to browsers)
 - ✓ use your ULHPC credential to login
- ↪ Provides a web access to the HPC resources and integrates
 - ✓ a file management system
 - ✓ a job management system (job composer, monitoring your submitted jobs, . . .)
 - ✓ an interactive command-line shell access
 - ✓ interactive apps with graphical desktop environments

ULHPC Open OnDemand (OOD) Portal



- **Open OnDemand (OOD)**

- ↪ Web portal
 - ✓ compatible with Windows, Linux and MacOS (thanks to browsers)
 - ✓ use your ULHPC credential to login
- ↪ Provides a web access to the HPC resources and integrates
 - ✓ a file management system
 - ✓ a job management system (job composer, monitoring your submitted jobs, . . .)
 - ✓ an interactive command-line shell access
 - ✓ interactive apps with graphical desktop environments

Warning!

- The **ULHPC OOD portal** is **NOT** accessible outside the UniLu network
 - ↪ If you want to use it, you will need to setup a VPN to access the [UniLu network](http://vpn.uni.lu) `vpn.uni.lu`

ULHPC Open OnDemand (OOD) Portal




- **Open OnDemand (OOD)**

- ↪ Web portal
 - ✓ compatible with Windows, Linux and MacOS (thanks to browsers)
 - ✓ use your ULHPC credential to login
- ↪ Provides a web access to the HPC resources and integrates
 - ✓ a file management system
 - ✓ a job management system (job composer, monitoring your submitted jobs, . . .)
 - ✓ an interactive command-line shell access
 - ✓ interactive apps with graphical desktop environments

Warning!

- The **ULHPC OOD portal** is **NOT** accessible outside the UniLu network
 - ↪ If you want to use it, you will need to setup a VPN to access the [UniLu network](http://vpn.uni.lu) `vpn.uni.lu`
 - ↪ The portal doesn't integrate (*yet*) Aion cluster and is under active development state.
 - ✓ Missing features and bugs can be reported to the ULHPC team via the [support portal](#)

Open OnDemand - File management



The screenshot shows a file manager interface with a sidebar on the left and a main content area on the right.

Left Sidebar: Labeled "Home Directory", it lists several sub-directories: 2019-04, __pycache__, bin, git, include, lib, man, openfoam, qualif, share, and stow.

Main Content Area: The path is displayed as "/home/users/tvallette/". Below the path are several toolbar buttons: View, Edit, Alt Rename/Move, Download, Copy, Paste, and (Un)Select All. To the right of these buttons is a red "Delete" button.

File Listing: A table displays the contents of the directory. The columns are "name", "size", and "modified date". The table includes the following entries:

name	size	modified date
2019-04	dir	11/05/2021
__pycache__	dir	10/03/2021
bin	dir	10/15/2021
git	dir	07/30/2021
include	dir	10/15/2021
lib	dir	10/15/2021
man	dir	10/14/2021
openfoam	dir	10/03/2021
qualif	dir	10/03/2021
share	dir	10/14/2021
stow	dir	10/14/2021
bootstrap_elb.py	50.39kb	05/12/2021

Open OnDemand - Job composer

Jobs

+ New Job ▾

★ Create Template

Edit Files Job Options Open Terminal Submit Stop Delete

Show 25 entries Search:

Created	Name	ID	Cluster	Status
November 9, 2021 7:08pm	(default) Simple Slurm Job	Iris		Not Submitted

Showing 1 to 1 of 1 entries Previous | Next

Job Details

Job Name:
(default) Simple Slurm Job

Submit to:
Iris

Account:
Not specified

Script location:
/home/users/tvallette/ondemand/data/sys/myjobs/projects/default/1

Script name:
launcher.sh

Folder Contents:
launcher.sh

Open OnDemand - Jobs list

All Jobs

Active Jobs

Show 25 entries Filter:

ID	Name	User	Account	Time Used	Queue	Status	Cluster	Actions
>	COINF_PROFILING.human3_profiling	[REDACTED]	[REDACTED]	02:20:34	batch	Completed	Iris	<input type="button" value="View"/>
>	SCP259	[REDACTED]	[REDACTED]	00:15:47	batch	Completed	Iris	<input type="button" value="View"/>
>	start0_2.sh	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	start10_1.sh	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	start10_2.sh	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	start11_1.sh	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	start11_2.sh	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	AEL_deeplog_HDFS	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-148	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-149	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-150	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-146	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-147	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-143	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-144	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>
>	r-145	[REDACTED]	[REDACTED]	00:00:00	batch	Submitted	Iris	<input type="button" value="View"/>

Open OnDemand - Shell access

Open OnDemand - Interactive sessions

Iris Desktop (advanced allocation) (2534226) Queued

Created at: 2021-11-09 19:14:04 CET 

Time Requested: 1 hour

Session ID: [e630ef12-0a78-4e3e-9d5b-d96c1575d3c4](#)

Please be patient as your job currently sits in queue. The wait time depends on the number of cores as well as time requested.

Iris Desktop (advanced allocation) (2534226) 1 node | 1 core | Running

Host: [Iris-180](#) 

Created at: 2021-11-09 19:14:04 CET

Time Remaining: 59 minutes


Session ID: [e630ef12-0a78-4e3e-9d5b-d96c1575d3c4](#)

Compression Image Quality

0 (low) to 9 (high) 0 (low) to 9 (high)

[Launch Iris Desktop \(advanced allocation\)](#) [View Only \(Share-able Link\)](#)

Open OnDemand - Graphical Desktop Environment



Thank you for your attention...

Questions?

ulhpc-tutorials.rtfd.io/en/latest/preliminaries



High Performance Computing @ Uni.lu

University of Luxembourg, Belval Campus
Maison du Nombre, 4th floor
2, avenue de l'Université
L-4365 Esch-sur-Alzette
mail: hpc@uni.lu

1 Introduction

2 Preliminaries Setup on your Laptop/Workstation

System Environment Adaptation
Distributed Version Control with Git

3 SSH Secure Shell

Installation
Usage
Data transfer using SSH
Prepare your laptop for next Practical Sessions

4 Discover Open OnDemand

Uni.lu HPC School 2021 Contributors

	Dr. Xavier Besseron Research Scientist		Hyacinthe Cartiaux Infra. & HPC Arch. Engineer		Dr. Tiago C. Pessoa Postdoctoral Researcher
	Dr. Aurelien Ginohac Research Scientist		Dr. Emmanuel Kieffer Research Scientist		Sarah Peter Infra. & Arch. Engineer
	Dr. Loizos Koutsantonis Postdoctoral Researcher		Dr. Teddy Valette Infra. & HPC Arch. Engineer		Dr. Sébastien Varrette Research Scientist
	Dr. Ezhilmathi Krishnasamy Postdoctoral Researcher				... and additional help (Survey, session tests)
					Arlyne Vandevenne Project Manager

hpc.uni.lu