Overview → Collect → Structure → Query → Report → Automate

Query the database

Select a connection

moonstone ▼

Query editor

Use **Ctrl + Enter** to execute the query. (**Cmd + Enter** for the unfortunate MacOS users.)

```
1  SELECT ?s ?p ?o FROM <https://manual.sparqling-genomics.org> { ?s ?p ?o }
2  LIMIT 100
3
```

Execute query

Query results

Note: Query results are limited to a maximum of 5000 rows. Programmatic access does not have this limitation.

Show 10 ▼ entries

s	p	o
https://manual.sparqling-genomics.org/1	http://www.w3.org/1999/02/22-rdf-syntax-ns#type	http://www.w3.org/2000/01/rdf-schema#Class
https://manual.sparqling-genomics.org/1	http://www.w3.org/2000/01/rdf-schema#label	First

Showing 1 to 2 of 2 entries

Previous | 1 | Next

History

The table below contains queries that were previously executed. For compactness, all `PREFIX` declarations and empty lines are not shown.

Query	Connection	Executed by	Duration (in seconds)	Actions (Remove unselected)
SELECT ?s ?p ?o FROM <https://manual.sparqling-genomics.org> { ?s ?p ?o } LIMIT 100	moonstone	roel	0	☐ ✗ ↰