

---

# **Cortix Documentation**

***Release 0.1.0***

**Valmor F. de Almeida, Taha Azzaoui, Gilberto E. Alas**

**Aug 08, 2019**

# CONTENTS

<b>1</b>	<b>src</b>	<b>1</b>
1.1	cortex_main . . . . .	1
1.2	module module . . . . .	1
1.3	port module . . . . .	3
<b>2</b>	<b>examples</b>	<b>4</b>
2.1	adjudication module . . . . .	4
2.2	arrested module . . . . .	5
2.3	community module . . . . .	6
2.4	dataplot module . . . . .	7
2.5	droplet module . . . . .	7
2.6	dummy_module module . . . . .	8
2.7	jail module . . . . .	9
2.8	parole module . . . . .	10
2.9	plot_data module . . . . .	11
2.10	prison module . . . . .	11
2.11	probation module . . . . .	12
2.12	run_justice module . . . . .	13
2.13	vortex module . . . . .	13
<b>3</b>	<b>support</b>	<b>15</b>
3.1	actor . . . . .	15
3.2	fuel_bucket . . . . .	15
3.3	fuel_bundle . . . . .	23
3.4	fuel_segment . . . . .	29
3.5	fuelsegmentsgroups . . . . .	31
3.6	fuelslug . . . . .	32
3.7	nuclides . . . . .	34
3.8	periodictable . . . . .	34
3.9	phase . . . . .	35
3.10	quantity . . . . .	40
3.11	specie . . . . .	42
3.12	stream . . . . .	51
	<b>Python Module Index</b>	<b>53</b>
	<b>Index</b>	<b>54</b>

## 1.1 cortix\_main

**class** cortix\_main.Cortix (use\_mpi=False, splash=False)

Bases: object

The main Cortix class definition: 1. Create the object 2. Add modules 3. Run the simulation

**\_\_del\_\_** ()

Note: by the time the body of this function is executed, the machinery of variables may have been deleted already. For example, *logging* is no longer there; do the least amount of work here.

**add\_module** (m)

Add a module to the Cortix object

*m*: An instance of a class that inherits from the Module base class

**draw\_network** (file\_name='network.png', dpi=220)

Draws the networkx Module network graph using matplotlib

*file\_name*: The resulting network diagram output file name *dpi*: dpi used for generating the network image

**get\_modules** ()

Return the list of modules in the root (master) process. If the *run()* method has completed, the list is updated with data from the other processes.

**get\_network** ()

Constructs and returns a networkx graph representation of the module network.

**run** ()

Run the Cortix simulation with either MPI or Python multiprocessing.

## 1.2 module module

**class** module.Module

Bases: object

The representation of a Cortix module. This class is to be inherited by every Cortix module. It provides facilities for creating modules within the Cortix network. In addition Cortix will map one object of this class to a Python multiprocessing child process, or one executable object of this class to one MPI process.

**\_\_init\_\_** ()

**name**

*str* – A name given to the instance. Default is *None*.

**port\_names\_expected**

*list(str)* or *None* – A list of names of ports expected in the module. This will be compared to port names during runtime to check against the intended use of the module.

**state**

*any* – Any *pickle-able* data structure to be passed in a *multiprocessing.Queue* to the parent process or to be gathered in the root MPI process. Default is *None*.

**connect** (*port\_name\_or\_module*, *to\_other\_port=None*)

A simpler interface (as compared to direct *port* connection) to create module connectivity. Connect the module *port* (or *module*) to a given *to\_other\_port* port.

**Parameters**

- **port\_name\_or\_module** (*str* or *Module*) – Either a *port* name or a *Module* can be given. In the latter case the *name* attribute of the module will be used to get the *port* of the module passed. This port will be connected to the port of the calling object.
- **to\_other\_port** (*Port*) – A *port* object to connect to. This must be *None* or absent if the first argument is a *Module*.

**get\_port** (*name*)

Get port by name; if it does not exist, create one.

**recv** (*port*)

Receive data from a given port

**run** (*\*args*)

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

**Notes**

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

**if not self.use\_mpi:**

**try:** pickle.dumps(self.state)

**except pickle.PicklingError:** args[1].put((arg[0],None))

**else:** args[1].put((arg[0],self.state))

at the bottom of the user defined run() function.

**Parameters**

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

**send** (*data*, *port*)

Send data through a given port.

## 1.3 port module

**class** `port.Port` (*name=None*, *use\_mpi=False*)

Bases: `object`

The Port class provides an interface for creating ports and connecting them to other ports for the purpose of data transfer. Data exchange takes place by send and/or receive calls on a given port. The concept of a port is that of a data transfer “interaction.” This can be one- or two-way with sends and receives. A port is connected to only one other port; as two ends of a pipe are connected.

`__eq__` (*other*)

Ports are the same if their names are the same

`__repr__` ()

Port name representation

**connect** (*port*)

Connect the port to another port

*port*: A Port object that represents the port to connect to.

**recv** ()

Returns the data received from the connected port.

**send** (*data*, *tag=None*)

Send data to the connected port. If the sending port is not connected do nothing.

**Parameters** **data** (*any pickle-able data*) –

**Returns**

**Return type** None

## EXAMPLES

## 2.1 adjudication module

**class** adjudication.**Adjudication** (*n\_groups=1, pool\_size=0.0*)

Bases: cortix.src.module.Module

Adjudication Cortix module used to model criminal group population in an adjudication system.

### Notes

These are the *port* names available in this module to connect to respective modules: *probation*, *jail*, *arrested*, *prison*, and *community*. See instance attribute *port\_names\_expected*.

**\_\_init\_\_** (*n\_groups=1, pool\_size=0.0*)

### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

**run** (*\*args*)

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *\*run(self, \*args)*.

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

**if not self.use\_mpi:**

**try:** pickle.dumps(self.state)

**except pickle.PicklingError:** args[1].put((arg[0],None))

**else:** args[1].put((arg[0],self.state))

at the bottom of the user defined run() function.

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.2 arrested module

**class** arrested.**Arrested** (*n\_groups=1, pool\_size=0.0*)

Bases: *cortex.src.module.Module*

Arrested Cortex module used to model criminal group population in an arrested system.

---

### Notes

These are the *port* names available in this module to connect to respective modules: *probation*, *adjudication*, *jail*, and *community*. See instance attribute *port\_names\_expected*.

---

**\_\_init\_\_** (*n\_groups=1, pool\_size=0.0*)

### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

**run** (*\*args*)

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.3 community module

```
class community.Community(n_groups=1, maturity_rate=0.00011574074074074075, of-  
                           fender_pool_size=0.0)  
    Bases: cortex.src.module.Module
```

Community Cortex module used to model criminal group population in a community system. Community here is the system at large with all possible adult individuals included in a society.

---

### Notes

These are the *port* names available in this module to connect to respective modules: *probation*, *adjudication*, *jail*, *prison*, *arrested*, and *parole*. See instance attribute *port\_names\_expected*.

---

```
__init__(n_groups=1, maturity_rate=0.00011574074074074075, offender_pool_size=0.0)
```

### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **maturity\_rate** (*float*) – Rate of individuals reaching the adult age (SI) unit. Default: 10 per day.
- **offender\_pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

```
run(*args)
```

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
```

```
    try: pickle.dumps(self.state)
```

```
    except pickle.PicklingError: args[1].put((arg[0],None))
```

```
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.



## 2.4 dataplot module

```
class dataplot.DataPlot
    Bases: cortix.src.module.Module

    plot_data()

    recv_data(port)
        Keep listening on the port and receiving data.

    run(state_comm=None, idx_comm=None)
        Spawn a thread to handle each port connection.
```

## 2.5 droplet module

```
class droplet.Droplet
    Bases: cortix.src.module.Module

    Droplet Cortex module used to model very simple fluid-particle interactions.
```

---

### Notes

Port names used in this module: *external-flow* exchanges data with any other module that provides information about the flow outside the droplet, *visualization* sends data to a visualization module.

---

```
rhs_fn(u_vec, t, params)
```

```
run(*args)
```

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

**step** (*time=0.0*)

ODE IVP problem: Given the initial data at  $t = 0$ ,  $(u_1(0), u_2(0), u_3(0)) = (x_0, x_1, x_2)$ ,  $(u_4(0), u_5(0), u_6(0)) = (v_0, v_1, v_2) = (\dot{u}_1(0), \dot{u}_2(0), \dot{u}_3(0))$ , solve  $\frac{du}{dt} = f(u)$  in the interval  $0 \leq t \leq t_f$ . When  $u_3(t)$  is negative, bounce the droplet to a random height between 0 and  $1.0 x_0$  with no velocity, and continue the time integration until  $t = t_f$ .

**Parameters** **time** (*float*) – Time in the droplet unit of time (seconds).

**Returns**

**Return type** None

## 2.6 dummy\_module module

**class** dummy\_module.DummyModule

Bases: cortix.src.module.Module

**run** ()

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

**if not self.use\_mpi:**

**try:** pickle.dumps(self.state)

**except pickle.PicklingError:** args[1].put((arg[0],None))

**else:** args[1].put((arg[0],self.state))

at the bottom of the user defined run() function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

**class** dummy\_module.DummyModule2

Bases: cortix.src.module.Module

**run** ()

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

#### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.7 jail module

```
class jail.Jail (n_groups=1, pool_size=0.0)
```

Bases: *cortix.src.module.Module*

Jail Cortix module used to model criminal group population in a jail.

---

#### Notes

These are the *port* names available in this module to connect to respective modules: *probation*, *adjudication*, *arrested*, *prison*, and *community*. See instance attribute *port\_names\_expected*.

---

```
__init__ (n_groups=1, pool_size=0.0)
```

#### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

```
run (*args)
```

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

#### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
```

---

```
except pickle.PicklingError: args[1].put((arg[0],None))
```

```
else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined run() function.

---

#### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.8 parole module

```
class parole.Parole (n_groups=1, pool_size=0.0)
```

```
Bases: cortex.src.module.Module
```

Parole Cortex module used to model criminal group population in a parole system.

---

#### Notes

These are the *port* names available in this module to connect to respective modules: *prison* and *community*. See instance attribute *port\_names\_expected*.

---

```
run (*args)
```

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

#### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
```

```
    try: pickle.dumps(self.state)
```

```
    except pickle.PicklingError: args[1].put((arg[0],None))
```

```
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined run() function.

---

#### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.9 plot\_data module

**class** `plot_data.PlotData`

Bases: `cortix.src.module.Module`

**run()**

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with `run(self)` or `run(self, *args)` as long as `self.state = None`. If `self.state` points to anything but `None`, the user must use `run(self, *args)`.

---

### Notes

When in multiprocessing, `*args` has two elements: `comm_idx` and `comm_state`. To pass back the state of the module, the user should insert the provided index `comm_idx` and the `state` into the queue as follows:

**if not self.use\_mpi:**

**try:** `pickle.dumps(self.state)`

**except pickle.PicklingError:** `args[1].put((arg[0],None))`

**else:** `args[1].put((arg[0],self.state))`

at the bottom of the user defined `run()` function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library `state_comm` must have the module's `self.state` in it. That is, `state_comm.put((idx_comm,self.state))` must be the last command in the method before `return`. In addition, `self.state` must be *pickle-able*.

## 2.10 prison module

**class** `prison.Prison` (`n_groups=1, pool_size=0.0`)

Bases: `cortix.src.module.Module`

Prison Cortix module used to model criminal group population in a prison.

---

### Notes

These are the *port* names available in this module to connect to respective modules: *parole*, *adjudication*, *jail*, and *community*. See instance attribute `port_names_expected`.

---

**\_\_init\_\_** (`n_groups=1, pool_size=0.0`)

### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

**run** (\*args)

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.11 probation module

**class** `probation.Probation` (*n\_groups=1, pool\_size=0.0*)

Bases: `cortix.src.module.Module`

Probation Cortix module used to model criminal group population in a probation.

---

### Notes

These are the *port* names available in this module to connect to respective modules: *adjudication*, *jail*, *arrested*, and *community*. See instance attribute *port\_names\_expected*.

---

**\_\_init\_\_** (*n\_groups=1, pool\_size=0.0*)

### Parameters

- **n\_groups** (*int*) – Number of groups in the population.
- **pool\_size** (*float*) – Upperbound on the range of the existing population groups. A random value from 0 to the upperbound value will be assigned to each group.

**run** (\*args)

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with *run(self)* or *run(self, \*args)* as long as *self.state = None*. If *self.state* points to anything but *None*, the user must use *run(self, \*args)*.

---

### Notes

When in multiprocessing, *\*args* has two elements: *comm\_idx* and *comm\_state*. To pass back the state of the module, the user should insert the provided index *comm\_idx* and the *state* into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined *run()* function.

---

### Parameters

- **comm\_idx** (*int*) – Index of the state in the communication queue.
- **comm\_state** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library *state\_comm* must have the module's *self.state* in it. That is, *state\_comm.put((idx\_comm,self.state))* must be the last command in the method before *return*. In addition, *self.state* must be *pickle-able*.

## 2.12 run\_justice module

## 2.13 vortex module

**class** *vortex.Vortex*

Bases: *cortex.src.module.Module*

Vortex module used to model fluid flow using Cortex.

---

### Notes

Any *port* name and any number of ports are allowed.

---

**compute\_velocity** (*time, position*)

Compute the vortex velocity at the given external position using a vortex flow model

### Parameters

- **time** (*float*) – Time in SI unit.
- **position** (*numpy.ndarray(3)*) – Spatial position in SI unit.

**Returns** *vortex\_velocity*

**Return type** *numpy.ndarray(3)*

**plot\_velocity** (*time=None*)

Plot the vortex velocity as a function of height.

**run** ()

Run method with an option to pass data back to the parent process when running in Python multiprocessing mode. If the user does not want to share data with the parent process, this function can be overridden with

`run(self)` or `run(self, *args)` as long as `self.state = None`. If `self.state` points to anything but `None`, the user must use `run(self, *args)`.

---

### Notes

When in multiprocessing, `*args` has two elements: `comm_idx` and `comm_state`. To pass back the state of the module, the user should insert the provided index `comm_idx` and the `state` into the queue as follows:

```
if not self.use_mpi:
    try: pickle.dumps(self.state)
    except pickle.PicklingError: args[1].put((arg[0],None))
    else: args[1].put((arg[0],self.state))
```

at the bottom of the user defined `run()` function.

---

### Parameters

- **`comm_idx`** (*int*) – Index of the state in the communication queue.
- **`comm_state`** (*multiprocessing.Queue*) – When using the Python *multiprocessing* library `state_comm` must have the module's `self.state` in it. That is, `state_comm.put((idx_comm,self.state))` must be the last command in the method before `return`. In addition, `self.state` must be *pickle-able*.



### 3.1 actor

This is a simple way to hide the name of species of interest in a simulation. The user would modify and copy this class into the Cortex module of interest and keep it private. Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda  
Sat Aug 15 13:41:12 EDT 2015

**class** actor.**Actor** (*name*)

Bases: `object`

See atoms list in Specie.

**atoms**

Returns the specific nuclides found in the specified chemical.

**Parameters** `empty` –

**Returns** `atoms`

**Return type** `list(str)`

**formula**

Returns the formula of the chemical in question.

**Parameters** `empty` –

**Returns** `formula`

**Return type** `str`

### 3.2 fuel\_bucket

This FuelBucket class is a container for usage with other plant-level process modules. It is meant to represent a fuel bucket of a metal fuel reactor. ———- ATTENTION: ———- This container uses Phase() for phases (cladding and fuel). Therefore user is responsible to make the “history” of the phases consistent. See Phase() info.

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

**class** fuel\_bucket.**FuelBucket** (*specs=Empty DataFrame Columns: [] Index: []*)

Bases: `object`

`__repr__()`

`__str__()`

**cladding\_end\_thickness**

Gets the thickness of the hemispherical cladding end caps that are placed on the top and bottom of the fuel slug, in cm.

**Parameters** `empty` –

**Returns** `cladding_end_thickness`

**Return type** `cm`

**cladding\_mass**

Returns the total mass of cladding material in the bucket, in grams.

**Parameters** `empty` –

**Returns** `cladding_mass`

**Return type** `float`

**cladding\_phase**

Returns the phase history of the cladding.

**Parameters** `empty` –

**Returns** `cladding_phase`

**Return type** `dataFrame`

**cladding\_volume**

Returns the total volume of cladding in the bucket, in  $\text{cm}^3$ .

**Parameters** `empty` –

**Returns** `cladding_volume`

**Return type** `float`

**cladding\_wall\_thickness**

Returns the thickness of the cladding wall which is on the outside of every fuel slug, and in between both sections of fuel, in cm.

**Parameters** `empty` –

**Returns** `cladding_wall_thickness`

**Return type** `float`

**fresh\_u235\_mass**

Returns the total amount of uranium-235 in the bucket, in grams.

**Parameters** `empty` –

**Returns** `fresh_u235_mass`

**Return type** `float`

**fresh\_u238\_mass**

Returns the total amount of uranium-238 in the bucket, in grams.

**Parameters** `empty` –

**Returns** `fresh_u238_mass`

**Return type** `float`

**fresh\_u\_mass**

Returns the total amount of uranium in the bucket, in grams.

Parameters **empty** –

Returns **fresh\_u\_mass**

Return type **float**

**fuel\_enrichment**

Returns the enrichment of the fuel slugs in the bucket, in %.

Parameters **empty** –

Returns **fuel\_enrichment**

Return type **float**

**fuel\_mass**

Returns the total mass of fuel in the solid phase in the bucket.

Parameters **empty** –

Returns **fuel\_mass**

Return type **float**

**fuel\_mass\_unit**

Returns the unit that is used to measure the mass of fuel in the bucket.

Parameters **empty** –

Returns **fuel\_mass\_unit**

Return type **str**

**fuel\_phase**

Returns the phase history of the fuel.

Parameters **empty** –

Returns **fuel\_phase**

Return type **pandas.core.frame.DataFrame**

**fuel\_radioactivity**

Returns the total radioactivity of the solid phase fuel, in units of curies.

Parameters **empty** –

Returns **fuel\_radioactivity**

Return type **float**

**fuel\_volume**

Returns the total volume of fuel in the entire bucket, in cm<sup>3</sup>.

Parameters **empty** –

Returns **fuel\_volume**

Return type **float**

**gamma\_pwr**

Returns the amount of gamma radiation given off by the fuel bucket, in units of watts.

Parameters **empty** –

Returns **gamma\_pwr**

Return type **float**

**get\_cladding\_end\_thickness()**

Gets the thickness of the hemispherical cladding end caps that are placed on the top and bottom of the fuel slug, in cm.

**Parameters** `empty` –

**Returns** `cladding_end_thickness`

**Return type** `cm`

**get\_cladding\_mass()**

Returns the total mass of cladding material in the bucket, in grams.

**Parameters** `empty` –

**Returns** `cladding_mass`

**Return type** `float`

**get\_cladding\_phase()**

Returns the phase history of the cladding.

**Parameters** `empty` –

**Returns** `cladding_phase`

**Return type** `dataFrame`

**get\_cladding\_volume()**

Returns the total volume of cladding in the bucket, in  $\text{cm}^3$ .

**Parameters** `empty` –

**Returns** `cladding_volume`

**Return type** `float`

**get\_cladding\_wall\_thickness()**

Returns the thickness of the cladding wall which is on the outside of every fuel slug, and in between both sections of fuel, in cm.

**Parameters** `empty` –

**Returns** `cladding_wall_thickness`

**Return type** `float`

**get\_fresh\_u235\_mass()**

Returns the total amount of uranium-235 in the bucket, in grams.

**Parameters** `empty` –

**Returns** `fresh_u235_mass`

**Return type** `float`

**get\_fresh\_u238\_mass()**

Returns the total amount of uranium-238 in the bucket, in grams.

**Parameters** `empty` –

**Returns** `fresh_u238_mass`

**Return type** `float`

**get\_fresh\_u\_mass()**

Returns the total amount of uranium in the bucket, in grams.

Parameters **empty** –

Returns **fresh\_u\_mass**

Return type **float**

**get\_fuel\_enrichment()**

Returns the enrichment of the fuel slugs in the bucket, in %.

Parameters **empty** –

Returns **fuel\_enrichment**

Return type **float**

**get\_fuel\_mass()**

Returns the total mass of fuel in the solid phase in the bucket.

Parameters **empty** –

Returns **fuel\_mass**

Return type **float**

**get\_fuel\_mass\_unit()**

Returns the unit that is used to measure the mass of fuel in the bucket.

Parameters **empty** –

Returns **fuel\_mass\_unit**

Return type **str**

**get\_fuel\_phase()**

Returns the phase history of the fuel.

Parameters **empty** –

Returns **fuel\_phase**

Return type **pandas.core.frame.DataFrame**

**get\_fuel\_radioactivity()**

Returns the total radioactivity of the solid phase fuel, in units of curies.

Parameters **empty** –

Returns **fuel\_radioactivity**

Return type **float**

**get\_fuel\_volume()**

Returns the total volume of fuel in the entire bucket, in cm<sup>3</sup>.

Parameters **empty** –

Returns **fuel\_volume**

Return type **float**

**get\_gamma\_pwr()**

Returns the amount of gamma radiation given off by the fuel bucket, in units of watts.

Parameters **empty** –

Returns **gamma\_pwr**

Return type **float**

**get\_heat\_pwr()**

Returns the total amount of heat generated by the bucket, in units of watts.

**Parameters** `empty` –

**Returns** `heat_pwr`

**Return type** `float`

**get\_inner\_slug\_id()**

Returns the inner diameter of the inner section of fuel, in cm.

**Parameters** `empty` –

**Returns** `inner_slug_id`

**Return type** `float`

**get\_inner\_slug\_od()**

Returns the outer diameter of the inner section of fuel, in cm.

**Parameters** `empty` –

**Returns** `inner_slug_od`

**Return type** `float`

**get\_n\_slugs()**

Returns the number of fuel slugs in the bucket.

**Parameters** `empty` –

**Returns** `n_slugs`

**Return type** `int`

**get\_name()**

Returns the name of the fuel bucket.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**get\_outer\_slug\_id()**

Returns the inner diameter of the outer section of fuel, in cm.

**Parameters** `empty` –

**Returns** `outer_slug_id`

**Return type** `float`

**get\_outer\_slug\_od()**

Returns the outer diameter of the outer section of fuel, in cm. A fuel slug consists of an outer section of fuel and an inner section of fuel, with cladding on the outside of the slug and between the inner and outer sections of fuel.

**Parameters** `empty` –

**Returns** `outer_slug_od`

**Return type** `float`

**get\_radioactivity()**

Returns the radioactivity of the fuel bucket, in units of curies.

Parameters **empty** –

Returns radioactivity

Return type **float**

**get\_slug\_cladding\_volume()**

Returns the volume of cladding present in a single fuel slug, in  $\text{cm}^3$ .

Parameters **empty** –

Returns **slug\_cladding\_volume**

Return type **float**

**get\_slug\_fuel\_volume()**

Returns the volume of fuel present in a single fuel slug, in  $\text{cm}^3$ .

Parameters **empty** –

Returns **slug\_fuel\_volume**

Return type **float**

**get\_slug\_length()**

Returns the length of each slug in the fuel bucket.

Parameters **empty** –

Returns **slug\_length**

Return type **float**

**get\_slug\_type()**

Returns the type of slugs being stored in the bucket (inner slug or outer slug).

Parameters **empty** –

Returns **slug\_type**

Return type **str**

**heat\_pwr**

Returns the total amount of heat generated by the bucket, in units of watts.

Parameters **empty** –

Returns **heat\_pwr**

Return type **float**

**inner\_slug\_id**

Returns the inner diameter of the inner section of fuel, in cm.

Parameters **empty** –

Returns **inner\_slug\_id**

Return type **float**

**inner\_slug\_od**

Returns the outer diameter of the inner section of fuel, in cm.

Parameters **empty** –

Returns **inner\_slug\_od**

Return type **float**

**n\_slugs**

Returns the number of fuel slugs in the bucket.

**Parameters** `empty` –

**Returns** `n_slugs`

**Return type** `int`

**name**

Returns the name of the fuel bucket.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**outer\_slug\_id**

Returns the inner diameter of the outer section of fuel, in cm.

**Parameters** `empty` –

**Returns** `outer_slug_id`

**Return type** `float`

**outer\_slug\_od**

Returns the outer diameter of the outer section of fuel, in cm. A fuel slug consists of an outer section of fuel and an inner section of fuel, with cladding on the outside of the slug and between the inner and outer sections of fuel.

**Parameters** `empty` –

**Returns** `outer_slug_od`

**Return type** `float`

**radioactivity**

Returns the radioactivity of the fuel bucket, in units of curies.

**Parameters** `empty` –

**Returns** `radioactivity`

**Return type** `float`

**set\_cladding\_phase** (*phase*)

Set's the phase history to specific values.

**Parameters** `phase` (*dataFrame*) –

**Returns**

**Return type** `empty`

**set\_fuel\_phase** (*phase*)

Sets the current fuel phase to a specified phase value.

**Parameters** `phase` (*dataFrame*) –

**Returns**

**Return type** `empty`

**set\_slug\_length** (*x*)

Sets the length of all slugs in the bucket to x. Used for chopping.



**Parameters** `x` (*float*) –

**Returns**

**Return type** `empty`

**slug\_cladding\_volume**

Returns the volume of cladding present in a single fuel slug, in  $\text{cm}^3$ .

**Parameters** `empty` –

**Returns** `slug_cladding_volume`

**Return type** `float`

**slug\_fuel\_volume**

Returns the volume of fuel present in a single fuel slug, in  $\text{cm}^3$ .

**Parameters** `empty` –

**Returns** `slug_fuel_volume`

**Return type** `float`

**slug\_length**

Returns the length of each slug in the fuel bucket.

**Parameters** `empty` –

**Returns** `slug_length`

**Return type** `float`

**slug\_type**

Returns the type of slugs being stored in the bucket (inner slug or outer slug).

**Parameters** `empty` –

**Returns** `slug_type`

**Return type** `str`

### 3.3 fuel\_bundle

This FuelBundle class is a container for usage with other plant-level process modules. It is meant to represent a fuel bundle of an oxide fuel LWR reactor. There are three main data structures:

1. fuel bundle specs
2. solid phase
3. gas phase

The container user will have to provide all the data and from then on, this class will help access the data. The printing methods reveal the contained data.

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda Sun Dec 27 15:06:55 EST 2015

**class** `fuel_bundle.FuelBundle` (*specs=Empty DataFrame Columns: [] Index: []*)

Bases: `object`

**fresh\_u235\_mass**

Returns the amount of uranium-235 in the bucket, in grams.

**Parameters** `empty` –

Returns `fresh_u235_mass`

Return type `float`

**fresh\_u238\_mass**

Returns the amount of uranium-238 in the bucket, in grams.

Parameters `empty` –

Returns `fresh_u238_mass`

Return type `float`

**fresh\_u\_mass**

Returns the amount of uranium in the bundle, in grams.

Parameters `empty` –

Returns `fresh_u_mass`

Return type `float`

**fuel\_enrichment**

Returns the enrichment of the fuel pins in the bundle, in %.

Parameters `empty` –

Returns `fuel_enrichment`

Return type `float`

**fuel\_mass**

Returns the total numerical value for mass of fuel in the solid phase in the bundle.

Parameters `empty` –

Returns `fuel_mass`

Return type `float`

**fuel\_mass\_unit**

Returns the unit used to measure the mass of fuel in the bundle.

Parameters `empty` –

Returns `fuel_mass_unit`

Return type `str`

**fuel\_pin\_length**

Returns the length of each fuel pin in the fuel bundle. A fuel pin is a cylindrical section of uranium fuel that is surrounded by cladding.

Parameters `empty` –

Returns `fuel_pin_length`

Return type `float`

**fuel\_pin\_radius**

Returns the radius of the fuel pin, in cm.

**fuel\_pin\_volume**

Returns the volume of fuel in each fuel pin, in cm<sup>3</sup>.

Parameters `empty` –

Returns `fuel_pin_volume`

**Return type** float

#### **fuel\_radioactivity**

Returns the total radioactivity of the fuel in the solid phase in the fuel bundle.

**Parameters** empty –

**Returns** fuel\_radioactivity

**Return type** float

#### **fuel\_rod\_od**

returns the outer diameter of the fuel rod, in cm. A fuel rod consists of a fuel pin surrounded by cladding.

**Parameters** empty –

**Returns** fuel\_rod\_od

**Return type** float

#### **fuel\_volume**

Returns the total volume of fuel in the bundle, in cm<sup>3</sup>.

**Parameters** empty –

**Returns** fuel\_volume

**Return type** float

#### **gamma\_pwr**

Returns the total amount of gamma radiation given by the fuel bundle, in watts.

**Parameters** empty –

**Returns** gamma\_pwr

**Return type** float

#### **gas\_mass**

Returns the total numerical value for mass of the fuel in the gas phase.

#### **gas\_phase**

Returns the gas phase history of the fuel.

**Parameters** empty –

**Returns** gas\_phase

**Return type** dataframe

#### **gas\_radioactivity**

Returns the total radioactivity of the fuel in the gas phase in the fuel bundle, in curies.

**Parameters** empty –

**Returns** gas\_radioactivity

**Return type** float

#### **get\_fresh\_U235\_mass()**

Returns the amount of uranium-235 in the bucket, in grams.

**Parameters** empty –

**Returns** fresh\_u235\_mass

**Return type** float

**get\_fresh\_u238\_mass()**

Returns the amount of uranium-238 in the bucket, in grams.

Parameters **empty** –

Returns **fresh\_u238\_mass**

Return type **float**

**get\_fresh\_u\_mass()**

Returns the amount of uranium in the bundle, in grams.

Parameters **empty** –

Returns **fresh\_u\_mass**

Return type **float**

**get\_fuel\_enrichment()**

Returns the enrichment of the fuel pins in the bundle, in %.

Parameters **empty** –

Returns **fuel\_enrichment**

Return type **float**

**get\_fuel\_mass()**

Returns the total numerical value for mass of fuel in the solid phase in the bundle.

Parameters **empty** –

Returns **fuel\_mass**

Return type **float**

**get\_fuel\_mass\_unit()**

Returns the unit used to measure the mass of fuel in the bundle.

Parameters **empty** –

Returns **fuel\_mass\_unit**

Return type **str**

**get\_fuel\_pin\_length()**

Returns the length of each fuel pin in the fuel bundle. A fuel pin is a cylindrical section of uranium fuel that is surrounded by cladding.

Parameters **empty** –

Returns **fuel\_pin\_length**

Return type **float**

**get\_fuel\_pin\_radius()**

Returns the radius of the fuel pin, in cm.

**get\_fuel\_pin\_volume()**

Returns the volume of fuel in each fuel pin, in cm<sup>3</sup>.

Parameters **empty** –

Returns **fuel\_pin\_volume**

Return type **float**

**get\_fuel\_radioactivity()**

Returns the total radioactivity of the fuel in the solid phase in the fuel bundle.

**Parameters** `empty` –

**Returns** `fuel_radioactivity`

**Return type** `float`

**get\_fuel\_rod\_od()**

returns the outer diameter of the fuel rod, in cm. A fuel rod consists of a fuel pin surrounded by cladding.

**Parameters** `empty` –

**Returns** `fuel_rod_od`

**Return type** `float`

**get\_fuel\_volume()**

Returns the total volume of fuel in the bundle, in  $\text{cm}^3$ .

**Parameters** `empty` –

**Returns** `fuel_volume`

**Return type** `float`

**get\_gamma\_pwr()**

Returns the total amount of gamma radiation given by the fuel bundle, in watts.

**Parameters** `empty` –

**Returns** `gamma_pwr`

**Return type** `float`

**get\_gas\_mass()**

Returns the total numerical value for mass of the fuel in the gas phase.

**get\_gas\_phase()**

Returns the gas phase history of the fuel.

**Parameters** `empty` –

**Returns** `gas_phase`

**Return type** `dataFrame`

**get\_gas\_radioactivity()**

Returns the total radioactivity of the fuel in the gas phase in the fuel bundle, in curies.

**Parameters** `empty` –

**Returns** `gas_radioactivity`

**Return type** `float`

**get\_heat\_pwr()**

Returns the total amount of heat produced by the fuel bundle, in watts.

**Parameters** `empty` –

**Returns** `heat_pwr`

**Return type** `float`

**get\_n\_fuel\_rods()**

Returns the number of fuel rods in the bundle.

**Parameters** `empty` –

**Returns** `n_fuel_rods`

**Return type** `int`

**get\_name()**

Returns the name of the fuel bundle.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**get\_radioactivity()**

Returns the total radioactivity of the fuel bundle, in curies.

**Parameters** `empty` –

**Returns** `raduioactivity`

**Return type** `float`

**get\_solid\_phase()**

Returns the solid phase history associated with this fuel bundle.

**Parameters** `empty` –

**Returns** `solidPhase`

**Return type** `dataFrame`

**heat\_pwr**

Returns the total amount of heat produced by the fuel bundle, in watts.

**Parameters** `empty` –

**Returns** `heat_pwr`

**Return type** `float`

**n\_fuel\_rods**

Returns the number of fuel rods in the bundle.

**Parameters** `empty` –

**Returns** `n_fuel_rods`

**Return type** `int`

**name**

Returns the name of the fuel bundle.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**radioactivity**

Returns the total radioactivity of the fuel bundle, in curies.

**Parameters** `empty` –

**Returns** `raduioactivity`

**Return type** `float`

**set\_fuel\_pin\_length** (*x*)

Sets the length of all fuel pins in the bundle to *x*.

**Parameters** *empty* –

**Returns** *x*

**Return type** *float*

**set\_gas\_phase** (*phase*)

Sets the gas phase history of the fuel equal to *phase*.

**Parameters** *phase* (*dataFrame*) –

**Returns**

**Return type** *empty*

**set\_solid\_phase** (*phase*)

Sets the solid phase history of the fuel equal to *phase*.

**Parameters** *phase* (*dataFrame*) –

**Returns**

**Return type** *empty*

**solid\_phase**

Returns the solid phase history associated with this fuel bundle.

**Parameters** *empty* –

**Returns** *solidPhase*

**Return type** *dataFrame*

## 3.4 fuel\_segment

Fuel segment Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda Sat Jun 27 14:46:49 EDT 2015

**class** `fuel_segment.FuelSegment` (*geometry=Series([], dtype: float64), species=[]*)

Bases: *object*

**\_\_repr\_\_** ()

Used to pront the geometry of the fuel segment and the species that it consists of.

**Parameters** *empty* –

**Returns** *s*

**Return type** *str*

**\_\_str\_\_** ()

Used to print the geometry of the fuel segment and the species that it consists of.

**Parameters** *empty* –

**Returns** *s*

**Return type** *str*

**geometry**

Returns the geometry of the fuel bundle (cylindrical, hexoganol, rectangular, etc).

**Parameters** *Empty* –

**Returns geometry**

**Return type** `str`

**get\_attribute** (*name*, *nuclide=None*, *series=None*)

Used to get stored fuel segment properties, either overall (as an average), or on a nuclide basis. “name” in this case refers to the attribute in question. At this point in time, series is not implemented and passing it to this function will result in an error. Possible attributes that may be retrieved with this function, as well as the name to pass to this function to retrieve them are: number of segments in the bundle (n-segments, always equal to 1), the id of the segment that makes up the bundle (segment-id), the volume of the fuel in the bundle (fuel-volume), the total volume of the segment (segment-volume), the diameter (fuel-diameter) and length (fuel-length) of the segment, the mass or mass density of the segment (mass or mass-cc, respectively), or the total or per-volume radioactivity, gamma radiation density or heat density of the fuel segment (radioactivity and radioactivityDens, gamma and gamma-dens, and heat and heat-dens, respectively).

Finally, density or total mass of a specific nuclide can be determined by passing a specific nuclide to the function, with a name value of mass or mass-cc.

**Parameters**

- **name** (`str`) –
- **nuclide** (`str`) –

**Returns**

**Return type** many types

**get\_geometry** ()

Returns the geometry of the fuel bundle (cylindrical, hexagonal, rectangular, etc).

**Parameters** **Empty** –

**Returns geometry**

**Return type** `str`

**get\_specie** (*name*)

Returns a specie named [name] from the list of species making up the fuel bundle. If no name is specified, this function will return None.

**Parameters** **name** (`str`) –

**Returns specie**

**Return type** `obj`

**get\_species** ()

Returns the species object which describes the composition of the fuel bundle. The species encapsulates all chemical species present in the fuel bundle. :param None:

**Returns species**

**Return type** `object`

**specie**

Returns a specie named [name] from the list of species making up the fuel bundle. If no name is specified, this function will return None.

**Parameters** **name** (`str`) –

**Returns specie**

**Return type** `obj`



**species**

Returns the species object which describes the composition of the fuel bundle. The species encapsulates all chemical species present in the fuel bundle. :param None:

**Returns** species

**Return type** object

## 3.5 fuelsegmentsgroups

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

Fuel segment

VFdALib support classes

Sat Jun 27 14:46:49 EDT 2015

**class** fuelsegmentsgroups.FuelSegmentsGroups (*key=None, fuelSegments=None*)

Bases: object

Creates a dictionary of lists of fuel segment objects, with the keys typically being timestamps. Each fuel segment object has two data members, a *Pandas* Series for geometry spec and a *panda* DataFrame for property density.

**AddGroup** (*key, fuelSegments=None*)

Appends the dictionary with a new key and associated list of fuelSegments. If the specified key is already present in the dictionary, then the specified list of fuel segments will be appended to the list of fuel segments already associated with the specified key.

**Parameters**

- **key** (*str*) –
- **fuelSegments** (*list*) –

**Returns**

**Return type** empty

**GetAttribute** (*groupKey=None, attributeName=None, nuclideSymbol=None, nuclideSeries=None*)

Returns the average value of an attribute amongst all elements in a group (WARNING: keys with no values associated with them will lower this average!). If groupKey is not specified, the function will return the average attribute value of every fuel segment element in the entire dictionary. If attribute is not specified, the function call will fail. If the key value specified does not match any keys in the dictionary, the function will return a value of 0.

**Parameters**

- **groupKey** (*str*) –
- **attributeName** (*str*) –
- **nuclideSymbol** (*str*) –
- **nuclideSeries** (*str*) –

**Returns** groupAttribute

**Return type** float

**GetFuelSegments** (*groupKey=None*)

Returns a list of fuel segments associated with a specified groupkey. If no group key is specified, then all

elements in the dictionary will be returned. If the specified group key does not exist, then the function will return an empty list.

**Parameters** `groupKey` (*str*) –

**Returns** `fuelSegments`

**Return type** `list`

**HasGroup** (*key*)

Checks if the specified key has a group of fuel segments associated with it.

**Parameters** `key` (*str*) –

**Returns** `key`

**Return type** `str`

**RemoveFuelSegment** (*groupKey*, *fuelSegment*)

Removes a fuel segment from a list associated with a specified group key. If the specified group key or fuel segment do not exist, the function will fail.

**Parameters**

- `groupKey` (*str*) –
- `fuelSegment` (*str*) –

**Returns**

**Return type** `empty`

## 3.6 fuelslug

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

Fuel slug

### 3.6.1 ATTENTION:

This container requires two Phase() containers which are by definition histories. The history is not checked. Therefore any inconsistency will be propagated forward. A fuel slug has two solid phases: cladding and fuel. The user will decide how to best use the underlying history data in the Phase() container of each phase.

VFdALib support classes

Thu Dec 15 16:18:39 EST 2016

```
class fuelslug.FuelSlug(specs=Series([], dtype: float64), fuelPhase= **Phase()**: time unit:
s *quantities*: None *species*: None *history* #time_stamp=1 *his-
tory end* @0.0 Series([], Name: 0.0, dtype: float64), claddingPhase=
**Phase()**: time unit: s *quantities*: None *species*: None *history* #
time_stamp=1 *history end* @0.0 Series([], Name: 0.0, dtype: float64))
```

**Bases:** `object`

**GetAttribute** (*name*, *phase=None*, *symbol=None*, *series=None*)

Returns the value of the specified attribute. Any attribute that is specified in class construction can be retrieved using this function. The attribute may also be retrived from a speciefic phase, a specific nuclide OR a specific series.

**Parameters**

- **name** (*str*) –
- **phase** (*str*) –
- **symbol** (*str*) –
- **series** (*str*) –

**Returns** attribute

**Return type** int or float

**GetCladdingPhase** ()

Returns the phase history of the cladding.

**Parameters** empty –

**Returns** claddingPhase

**Return type** dataframe

**GetFuelPhase** ()

Returns the phase history of the solid fuel.

**Parameters** empty –

**Returns** fuelPhase

**Return type** dataframe

**GetSpecs** ()

Returns the species associated with this fuel slug.

**Parameters** empty –

**Returns** specs

**Return type** str

**ReduceCladdingVolume** (*dissolvedVolume*)

Reduces the amount of cladding in the slug by dissolvedvolume. This will also update the dimensions of the cladding walls and end caps; volume will be taken from all sections equally such that the relative dimensions stay the same.

**Parameters** dissolvedVolume (*float*) –

**Returns**

**Return type** empty

**ReduceFuelVolume** (*dissolvedVolume*)

Reduces the amount of fuel in the slug by dissolvedVolume. This will also update the dimensions of the fuel slug, mainly the thickness of each fuel layers.

**Parameters** dissolvedVolume (*float*) –

**Returns**

**Return type** empty

**claddingPhase**

Returns the phase history of the cladding.

**Parameters** empty –

**Returns** claddingPhase

**Return type** dataframe

**fuelPhase**

Returns the phase history of the solid fuel.

**Parameters** `empty` –

**Returns** `fuelPhase`

**Return type** `dataFrame`

**specs**

Returns the species associated with this fuel slug.

**Parameters** `empty` –

**Returns** `specs`

**Return type** `str`

## 3.7 nuclides

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

Nuclides container. The purpose of the this container is to store and query a table of nuclides. Typically the table is filled in with data from an ORIGEN calculation or some other fission/transmutation code.

VFdALib support classes

Sat Jun 27 14:46:49 EDT 2015

**class** `nuclides.Nuclides` (*propertyDensities=Empty DataFrame Columns: [] Index: []*)

Bases: `object`

**GetAttribute** (*name, symbol=None, series=None*)

## 3.8 periodictable

Properties of the chemical elements.

Each chemical element is represented as an object instance. Physicochemical and descriptive properties of the elements are stored as instance attributes.

**Author** [Christoph Gohlke](#)

**Version** 2015.01.29

Radiochemical data (isotopes) has been added to this table (2015-2016) Origin: <http://www.radiochemistry.org/> Valmor F. de Almeida: [dealmeidavf@gmail.com](mailto:dealmeidavf@gmail.com); [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov)

### 3.8.1 Requirements

- CPython 2.7 or 3.4

### References

1. <http://physics.nist.gov/PhysRefData/Compositions/>
2. <http://physics.nist.gov/PhysRefData/IonEnergy/tblNew.html>

3. [http://en.wikipedia.org/wiki/%\(element.name\)s](http://en.wikipedia.org/wiki/%(element.name)s)
4. <http://www.miranda.org/~jkominek/elements/elements.db>

## Examples

```
>>> from elements import ELEMENTS
>>> len(ELEMENTS)
109
>>> str(ELEMENTS[109])
'Meitnerium'
>>> ele = ELEMENTS['C']
>>> ele.number, ele.symbol, ele.name, ele.eleconfig
(6, 'C', 'Carbon', '[He] 2s2 2p2')
>>> ele.eleconfig_dict
{(1, 's'): 2, (2, 'p'): 2, (2, 's'): 2}
>>> sum(ele.mass for ele in ELEMENTS)
14659.1115599
>>> for ele in ELEMENTS:
...     ele.validate()
...     ele = eval(repr(ele))
```

## 3.9 phase

Phase *history* container. When you think of a phase value, think of that value at a specific point in time. This container holds the historic data of a phase; its species and quantities. This implementation treats access of time stamps within a tolerance. All searches for time stamped values are subjected to an approximation of the time stamp to avoid storing values too close to each other in time, and/or to return the closest value in time searched or no value if none can be found according to the tolerance.

### 3.9.1 Background

TODO: ATTENTION: The species (list of *Specie*) AND quantities (list of *Quantity*) data members have ARBITRARY density values either at an arbitrary point in the history or at no point in the history. This needs to be removed in the future to avoid confusion.

To obtain history values, associated to the phase, at a particular point in time, use the `GetValue()` method to access the history data frame (pandas) via columns and rows. ALERT: The corresponding values in species and quantities are OVERRIDEN and NOT to be used through the phase interface.

Author: Valmor F. de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda Sat Sep 5 01:26:53 EDT 2015

Cortix: a program for system-level modules coupling, execution, and analysis.

**class** `phase.Phase` (*time\_stamp=None, time\_unit=None, species=None, quantities=None*)  
 Bases: `object`

Phase *history* container. A *Phase* consists of *Species* and *Quantities* varying with time. This container is meant to reproduce the basic idea of a material phase.

**AddQuantity** (*newQuant*)

Adds a new quantity object to the dataframe. See `quantity.py` for more details on the quantity class.

**Parameters** *newQuant* (*object*) –

**Returns****Return type** empty**AddRow** (*try\_time\_stamp*, *row\_values*)

Adds a row to the dataframe, with a timestamp of *try\_time\_stamp* and row values equal to *row\_values*. Take care that the dimensions and order of the data matches up!

**Parameters**

- **try\_time\_stamp** (*float*) –
- **row\_values** (*list*) –

**Returns****Return type** empty**AddSpecie** (*new\_specie*)

Adds a new specie object to the phase history. See *species.py* for more details on the specie class.

**Parameters** **new\_specie** (*obj*) –**Returns****Return type** empty**ClearHistory** (*value=0.0*)

Set species and quantities of history to a given value (default to zero value), all time stamps are preserved.

**Parameters** **value** (*float*) –**Returns****Return type** empty**GetActors** ()

Returns a list of all the actors in the phase history.

**Parameters** **empty** –**Returns** **list(self.\_\_phase.columns)****Return type** *list***GetColumn** (*actor*)

Returns an entire column of data. A column is the entire history of data associated with a specific actor.

**Parameters** **actor** (*str*) –**Returns** **list(self.\_\_phase.loc[****Return type** , actor]): *list***GetQuantities** ()

Returns the list of *Quantities*. The values in each *Quantity* are synchronized with the *Phase* data frame.

**Parameters** **empty** –**Returns** **quantities****Return type** *list***GetQuantity** (*name*)

Returns the quantity evaluated at the last time step of the phase history. This also updates the value of the quantity object. If the quantity name does not exist the return is *None*.

**Parameters** **name** (*str*) –

**Returns****Return type** empty**GetRow** (*try\_time\_stamp=None*)

Returns an entire row of the phase dataframe. A row is a series of values that are all at the same time stamp.

**Parameters** *try\_time\_stamp* (*float*) –**Returns** *list(self.\_\_phase.loc[time\_stamp,***Return type** *]*): list**GetSpecie** (*name*)

Returns the species specified by name if it exists, or none if it doesn't.

**Parameters** *name* (*str*) –**Returns** *specie***Return type** *str***GetSpecies** ()

Returns every single species in the phase history.

**Parameters** *empty* –**Returns** *species***Return type** *list***GetTimeStamps** ()

Returns a list of all the time stamps in the phase history.

**Parameters** *empty* –**Returns** *timeStamps***Return type** *list***GetValue** (*actor, try\_time\_stamp=None*)

Deprecated: use `get_value()`

**ResetHistory** (*try\_time\_stamp=None, value=None*)

Set species and quantities of history to a given value (default to zero value) only one time stamp is preserved (default to last time stamp).

**Parameters**• *try\_time\_stamp* (*float*) –• *value* (*float*) –**Returns****Return type** empty**ScaleRow** (*try\_time\_stamp, value*)

Multiplies all of the data in a row (except time stamp) by a scalar value.

**Parameters**• *try\_time\_stamp* (*float*) –• *value* (*float*) –**Returns**

**Return type** empty

**SetSpecieId** (*name*, *val*)

Sets the flag of a specie “name” equal to val.

**Parameters**

- **name** (*str*) –
- **val** (*int*) –

**Returns**

**Return type** empty

**SetValue** (*actor*, *value*, *try\_time\_stamp=None*)

For the record: old def SetValue(self, time\_stamp, actor, value):

**Parameters**

- **actor** (*str*) –
- **value** (*float*) –
- **try\_time\_stamp** (*float*) –

**Returns**

**Return type** empty

**WriteHTML** (*fileName*)

Convert the *Phase* container into an HTML file.

**Parameters** **fileName** (*str*) –

**Returns**

**Return type** empty

**\_\_init\_\_** (*time\_stamp=None*, *time\_unit=None*, *species=None*, *quantities=None*)

Sometimes an empty Phase object is created by user code. This case needs adequate logic for None types. Note on usage: when passing quantities, do set the value argument explicitly to help define the type and avoid SetValue() errors with Pandas. This is to be investigated later. Also, the usage of a DataFrame needs to be re-evaluated. Maybe better to use a Quantity object and a Specie object with a Pandas Series history as a value to avoid the existence of a value in Quantity and a value in Phase that are not in sync.

**get\_quantity** (*name*, *try\_time\_stamp=None*)

New version. Get the quantity *name* at a point in time closest to *try\_time\_stamp* up to a tolerance. If no time stamp is passed, the whole history is returned.

**Parameters**

- **name** (*str*) –
- **try\_time\_stamp** (*float*, *int* or *None*) – Time stamp of desired quantity value.  
Default: None returns the whole quantity history.

**Returns** **quant.value**

**Return type** *float* or *int* or other

**get\_quantity\_history** (*name*)

Create a Quantity *name* history. This will create a fully qualified Quantity object and return to the caller. The function is typically needed for data output to a file through *pickle*. Since the value attribute of a quantity can be any data structure, a time-series is built on the fly and stored in the value attribute. In addition the time unit is added to the final return value as a tuple.



**Parameters** `name (str)` –

**Returns** `quant_history`

**Return type** `tuple(Quantity, str)`

**get\_value** (`actor`, `try_time_stamp=None`)

Returns the value associated with a specified actor at a specified time stamp.

**Parameters**

- **actor** (`str`) –
- **try\_time\_stamp** (`float`) –

**Returns** `self.__phase.loc[time_stamp, actor]`

**Return type** `float`

**has\_time\_stamp** (`try_time_stamp`)

Checks to see if `try_time_stamp` exists in the phase history.

**Parameters** `try_time_stamp` –

**quantities**

Returns the list of *Quantities*. The values in each *Quantity* are synchronized with the *Phase* data frame.

**Parameters** `empty` –

**Returns** `quantities`

**Return type** `list`

**set\_value** (`actor`, `value`, `try_time_stamp=None`)

New version. Discontinue using `SetValue()`

**species**

Returns every single species in the phase history.

**Parameters** `empty` –

**Returns** `species`

**Return type** `list`

**timeStamps**

Returns a list of all the time stamps in the phase history.

**Parameters** `empty` –

**Returns** `timeStamps`

**Return type** `list`

**time\_stamps**

Get all time stamps in the index of the data frame.

**Parameters** `empty` –

**Returns** `time_stamps`

**Return type** `list`

**time\_unit**

Returns the time unit of the *Phase*.

**Parameters** `empty` –

**Returns** `time_unit`

Return type `str`

## 3.10 quantity

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

This Quantity class is to be used with other classes in plant-level process modules.

**For unit testing do at the linux command prompt:** `python quantity.py`

Sat Sep 5 12:51:34 EDT 2015

```
class quantity.Quantity (name='null-quantity',      formalName='null-quantity',      value=0.0,
                          unit='null-unit')
```

Bases: `object`

**todo:** this probably should not have a “value” for the same reason as **Specie**. this needs some thinking.

well not so fast. This can be used to build a quantity with anything as a value. For instance a history of the quantity as a time series.

**GetFormalName ()**

Returns the formal name of the quantity.

**Parameters** `empty` –

**Returns** `formalName`

**Return type** `str`

**GetUnit ()**

Returns the units of the quantity.

**Parameters** `empty` –

**Returns** `unit`

**Return type** `str`

**GetValue ()**

Gets the numerical value of the quantity.

**Parameters** `empty` –

**Returns** `value`

**Return type** any type

**SetFormalName (fn)**

Sets the formal name of the property to fn.

**Parameters** `fn (str)` –

**Returns**

**Return type** `empty`

**SetName (n)**

Sets the name of the quantity in question to n.

**Parameters** `n (str)` –

**Returns**

**Return type** `empty`

**SetUnit** (*f*)

Sets the units of the quantity to *f* (for example, density would be in units of g/cc).

**Parameters** *f* (*str*) –

**Returns**

**Return type** `empty`

**SetValue** (*v*)

Sets the numerical value of the quantity to *v*.

**Parameters** *v* (*float*) –

**Returns**

**Return type** `empty`

**\_\_repr\_\_** ()

Used to print the data stored by the quantity class. Will print out name, formal name, the value of the quantity and its unit.

**Parameters** `empty` –

**Returns** `s`

**Return type** `str`

**\_\_str\_\_** ()

Used to print the data stored by the quantity class. Will print out name, formal name, the value of the quantity and its unit.

**Parameters** `empty` –

**Returns** `s`

**Return type** `str`

**formalName**

Returns the formal name of the quantity.

**Parameters** `empty` –

**Returns** `formalName`

**Return type** `str`

**formal\_name**

Returns the formal name of the quantity.

**Parameters** `empty` –

**Returns** `formalName`

**Return type** `str`

**get\_name** ()

Returns the name of the quantity.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**name**

Returns the name of the quantity.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**plot** (*x\_scaling=1, y\_scaling=1, title=None, x\_label='x', y\_label=None, file\_name=None, same\_axis=True, dpi=300*)

This will support a few possibilities for data storage in the `self.__value` member.

Pandas Series. If `self.__value` is a Pandas Series, plot against the index. However the type stored in the Series matter. Suppose it is a series of a *numpy* array. This must be of the same rank for every entry. This plot method assumes it is an iterable type of the same length for every entry in the series. A plot of all elements in the type against the index of the series will be made. The plot may have all elements in one axis or each element in its own axis.

**unit**

Returns the units of the quantity.

**Parameters** `empty` –

**Returns** `unit`

**Return type** `str`

**value**

Gets the numerical value of the quantity.

**Parameters** `empty` –

**Returns** `value`

**Return type** any type

## 3.11 specie

Author: Valmor de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

This Specie class is to be used with other classes in plant-level process modules.

**NB: Species is always used either in singular or plural cases, the class** named here reflects one species. If many species are used in an external context, the species object name can be used without conflict.

**For unit testing do at the linux command prompt:** `python specie.py`

**NB: The Specie() class encapsulates either the molecular or empirical chemical** formula of a compound. This is done as follows. Say MAO2 is either a molecular or empirical formula of a fictitious compound denoting minor actinides dioxide. The list of atoms is given as follows:

```
['0.49*Np-237', '0.42*Am-241', '0.08*Am-243', '0.01*Cm-244', '2.0*O-16']
```

note the MA forming nuclides add to 1 = 0.49 + 0.42 + 0.08 + 0.01. Therefore the number of atoms in this compound is 3. 1 MA “atom” and 2 O. Note that the total number of “atoms” is obtained by summing all multipliers: 0.49 + 0.42 + 0.08 + 0.01 + 2.0. The nuclide is indicated by the element symbol followed by a dash and the atomic mass number. Here the number of nuclide types is 5 (`self._nNuclideTypes`).

The numbers preceeding the nuclide symbol before the \* will be referred to as multipliers. The sum of the multipliers will add to the number of “atoms” in the formula. **WARNING:** a multiplier could be in the format 0.00e-00. In this case a hipen may appear twice, e.g.: 1.549e-09\*U-233

Other forms can be used for common true species

```
['Np-237', '2.0*O-16'] or ['Np-237', 'O-16', 'O-16'] or [ '2*H', 'O' ] or [ 'H', 'O', 'H' ] etc...
```

This code will calculate the molar mass of any species with a given valid atom list using a provided periodic table of chemical elements. The user can also reset the value of the molar mass with a setter method.

Sat May 9 21:40:48 EDT 2015 created; vfda

```
class specie.Specie (name='null', formula_name='null', phase='null', atoms=[], molarCC=0.0,
                    massCC=0.0, flag=None)
```

Bases: `object`

**todo:** phase should not be here; concentrations should not be here only molar quantities should be here see the Phase container

**GetAtoms** ()

**GetFlag** ()

Returns the flag associated with the species.

Parameters **empty** –

Returns **flag**

Return type `str`

**GetFormula** ()

Returns the molecular or empirical formula of the species. It is usually a list, for example, of the form ['2\*H', 'O'].

Returns **formula**

Return type `list`

**GetFormulaName** ()

Returns the formulaic name of the compound. For example, "Dihydrogen monoxide".

Parameters **empty** –

Returns **self.\_\_formula\_name**

Return type `str`

**GetMassCC** ()

Returns the numerical value of the mass density of the species (mass/volume).

Parameters **empty** –

Returns **massCC**

Return type `float`

**GetMassCCUnit** ()

Returns the unit used to measure the mass density of the species.

Parameters **empty** –

Returns **massCCUnit**

Return type `str`

**GetMolarCC** ()

Returns the numerical value for the number (molar) density of the species (moles/volume).

Parameters **empty** –

Returns **molarCC**

Return type `float`

**GetMolarCCUnit ()**

Returns the unit used to measure molar density of the species.

**Parameters** `empty` –

**Returns** `molarCCUnit`

**Return type** `str`

**GetMolarGammaPwr ()**

Returns the amount of gamma radiation produced per mole of this species (measured in units of power).

**Parameters** `empty` –

**Returns** `molarGammaPwr`

**Return type** `float`

**GetMolarGammaPwrUnit ()**

Returns the unit used to measure the amount of gamma radiation produced per mole of this species.

**Parameters** `empty` –

**Returns** `molarGammaPwrUnit`

**Return type** `str`

**GetMolarHeatPwr ()**

Returns the amount of heat generated per mole of this species.

**Parameters** `empty` –

**Returns** `molarHeatPwr`

**Return type** `float`

**GetMolarHeatPwrUnit ()**

Returns the unit used to measure the amount of heat generated per mole of this species.

**Parameters** `empty` –

**Returns** `molarHeatPwrUnit`

**Return type** `str`

**GetMolarMass ()**

Returns the numerical value for the molar mass of the species. Units are given by `molarMassUnit`.

**Parameters** `empty` –

**Returns** `molarMass`

**Return type** `float`

**GetMolarMassUnit ()**

Returns the unit used to measure the molar mass of the species.

**Parameters** `empty` –

**Returns** `molarMassUnit`

**Return type** `str`

**GetMolarRadioactivity ()**

Returns the numerical value for molar radioactivity of the species.

**Parameters** `empty` –

**Returns** `molarRadioactivity`

**Return type** `float`

**GetMolarRadioactivityFractions** ()

Returns a list of numbers that specifies the % of molar reactivity that comes from each type of atom in the species. For example, a molarRadioactivityFraction of [0.65, 0.35] for water means that 65% of the molar radioactivity comes from the hydrogen atoms and 35% comes from the oxygen atom.

**Parameters** `empty` –

**Returns** `molarRadioactivityFractions`

**Return type** `list`

**GetMolarRadioactivityUnit** ()

Returns the unit used to measure molar radioactivity.

**Parameters** `empty` –

**Returns** `molarRadioactivityUnit`

**Return type** `str`

**GetNAtoms** ()

Returns the total number of atoms comprising the species. For example, water is comprised of three atoms.

**Parameters** `empty` –

**Returns** `nAtoms`

**Return type** `int`

**GetNNuclideTypes** ()

Returns the number of different types of atoms comprising the species. For example, water is composed of two different types of atoms, hydrogen and oxygen.

**Parameters** `empty` –

**Returns** `nNuclideTypes`

**Return type** `int`

**GetName** ()

Returns the empirical name of the species. For example, “water”.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

**GetPhase** ()

Returns the phase history of the species.

**Parameters** `empty` –

**Returns** `phase`

**Return type** `dataFrame`

**SetAtoms** (*atoms*)

**SetFlag** (*f*)

Sets the flag associated with the species to *f*.

**Parameters** *f* (`str`) –

**Returns**

**Return type** empty

**SetFormula** (*atoms*)

Sets the species' formula equal to atoms. Will automatically update the molar mass of the species, and will also fail if atoms is not a list of strings.

**Parameters** *atoms* (*list*) –

**Returns**

**Return type** empty

**SetFormulaName** (*f*)

Sets the formulaic name to f.

**Parameters** *empty* –

**Returns**

- *empty*
- *self.\_\_formula\_name* (*str*)

**SetMassCC** (*v*)

Sets the numerical value of the mass density equal to v.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty

**SetMassCCUnit** (*v*)

Sets the units used to measure mass density to v.

**Parameters** *v* (*str*) –

**Returns**

**Return type** empty

**SetMolarCC** (*v*)

Sets the numerical value for the molar density of the species to v.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty

**SetMolarCCUnit** (*v*)

Sets the unit used to measure the molar density of the species to v.

**Parameters** *v* (*str*) –

**Returns**

**Return type** empty

**SetMolarGammaPwr** (*v*)

Sets the amount of gamma radiation produced per mole of this species to v.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty



**SetMolarGammaPwrUnit** (*v*)

Sets the unit used to measure the amount of gamma radiation produced per mole of this species to *v*.

**Parameters** *v* (*str*) –

**Returns**

**Return type** empty

**SetMolarHeatPwr** (*v*)

Sets the amount of heat generated per mole of this species to *v*.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty

**SetMolarHeatPwrUnit** (*v*)

Sets the unit used to measure the amount of heat generated per mole of this species to *v*.

**Parameters** *v* (*str*) –

**Returns**

**Return type** empty

**SetMolarMass** (*v*)

Sets the molar mass of the species equal to *v*.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty

**SetMolarMassUnit** (*v*)

Sets the unit used to measure the molar mass of the species to *v*.

**Parameters** *v* (*str*) –

**Returns**

**Return type** empty

**SetMolarRadioactivity** (*v*)

Sets the molar radioactivity of the species equal to *v*.

**Parameters** *v* (*float*) –

**Returns**

**Return type** empty

**SetMolarRadioactivityFractions** (*fracs*)

Sets molarRadioactivityFractions equal to *fracs*. *Fracs* must be a list of floats with the same length as there are different atoms in the species, or the function call will fail. (e.g. `self._atoms` and *fracs* must be of the same length). Take care to ensure that the elements of *fracs* match with the elements of `self._atoms`! (65% is in the same position in *fracs* as hydrogen is in `self._atoms`, following the above example).

**Parameters** *fracs* (*list*) –

**Returns**

**Return type** empty

**SetMolarRadioactivityUnit** (*v*)

Sets the unit used to measure molar radioactivity to *v*.

**Parameters** `v` (*str*) –

**Returns**

**Return type** `empty`

**SetName** (*n*)

Sets the empirical name of the species to *n*.

**Parameters** `n` (*str*) –

**Returns**

**Return type** `empty`

**SetPhase** (*p*)

Sets the phase history to *p*.

**Parameters** `p` (*dataFrame*) –

**Returns**

**Return type** `empty`

**atoms**

**flag**

Returns the flag associated with the species.

**Parameters** `empty` –

**Returns** `flag`

**Return type** `str`

**formula**

Returns the molecular or empirical formula of the species. It is usually a list, for example, of the form ['2\*H', 'O'].

**Returns** `formula`

**Return type** `list`

**formula\_name**

Returns the formulaic name of the compound. For example, "Dihydrogen monoxide".

**Parameters** `empty` –

**Returns** `self.__formula_name`

**Return type** `str`

**massCC**

Returns the numerical value of the mass density of the species (mass/volume).

**Parameters** `empty` –

**Returns** `massCC`

**Return type** `float`

**massCCUnit**

Returns the unit used to measure the mass density of the species.

**Parameters** `empty` –

**Returns** `massCCUnit`

**Return type** `str`

**molarCC**

Returns the numerical value for the number (molar) density of the species (moles/volume).

**Parameters** `empty` –

**Returns** `molarCC`

**Return type** `float`

**molarCCUnit**

Returns the unit used to measure molar density of the species.

**Parameters** `empty` –

**Returns** `molarCCUnit`

**Return type** `str`

**molarGammaPwr**

Returns the amount of gamma radiation produced per mole of this species (measured in units of power).

**Parameters** `empty` –

**Returns** `molarGammaPwr`

**Return type** `float`

**molarGammaPwrUnit**

Returns the unit used to measure the amount of gamma radiation produced per mole of this species.

**Parameters** `empty` –

**Returns** `molarGammaPwrUnit`

**Return type** `str`

**molarHeatPwr**

Returns the amount of heat generated per mole of this species.

**Parameters** `empty` –

**Returns** `molarHeatPwr`

**Return type** `float`

**molarHeatPwrUnit**

Returns the unit used to measure the amount of heat generated per mole of this species.

**Parameters** `empty` –

**Returns** `molarHeatPwrUnit`

**Return type** `str`

**molarMass**

Returns the numerical value for the molar mass of the species. Units are given by `molarMassUnit`.

**Parameters** `empty` –

**Returns** `molarMass`

**Return type** `float`

**molarMassUnit**

Returns the unit used to measure the molar mass of the species.

**Parameters** `empty` –

**Returns** `molarMassUnit`

**Return type** `str`

#### **molarRadioactivity**

Returns the numerical value for molar radioactivity of the species.

**Parameters** `empty` –

**Returns** `molarRadioactivity`

**Return type** `float`

#### **molarRadioactivityFractions**

Returns a list of numbers that specifies the % of molar reactivity that comes from each type of atom in the species. For example, a `molarRadioactivityFraction` of [0.65, 0.35] for water means that 65% of the molar radioactivity comes from the hydrogen atoms and 35% comes from the oxygen atom.

**Parameters** `empty` –

**Returns** `molarRadioactivityFractions`

**Return type** `list`

#### **molarRadioactivityUnit**

Returns the unit used to measure molar radioactivity.

**Parameters** `empty` –

**Returns** `molarRadioactivityUnit`

**Return type** `str`

#### **nAtoms**

Returns the total number of atoms comprising the species. For example, water is comprised of three atoms.

**Parameters** `empty` –

**Returns** `nAtoms`

**Return type** `int`

#### **nNuclideTypes**

Returns the number of different types of atoms comprising the species. For example, water is composed of two different types of atoms, hydrogen and oxygen.

**Parameters** `empty` –

**Returns** `nNuclideTypes`

**Return type** `int`

#### **name**

Returns the empirical name of the species. For example, “water”.

**Parameters** `empty` –

**Returns** `name`

**Return type** `str`

#### **phase**

Returns the phase history of the species.

**Parameters** `empty` –

**Returns** `phase`

**Return type** `dataFrame`

## 3.12 stream

Author: Valmor F. de Almeida [dealmeidav@ornl.gov](mailto:dealmeidav@ornl.gov); vfda

Stream container

VFdALib support classes

Sat Aug 15 17:24:02 EDT 2015

**class** `stream.Stream` (*timeStamp*, *species=None*, *quantities=None*, *values=0.0*)

Bases: `object`

**GetActors** ()

Returns the actors present in the stream of data.

Parameters **empty** –

Returns `list(self.stream.columns)`

Return type `list`

**GetQuantities** ()

Returns all the quantities given by the stream.

Parameters **empty** –

Returns `self.quantities`

Return type `list`

**GetQuantity** (*name*)

Returns the specified quantity called “name” from the stream, or none if the specified name does not exist.

Parameters **name** (*str*) –

Returns `quant`

Return type `float`

**GetRow** (*timeStamp=None*)

Returns an entire row of data from the stream. A row of data is all the data in a dataframe at a specified time stamp, given by *timeStamp*. If *timeStamp* is not specified, this function will return the entire stream dataframe.

Parameters **timeStamp** (*float*) –

Returns

- `self.stream.loc[self.timestamp, ()]` or `self.stream.loc[timeStamp, :]`
- `list`

**GetSpecie** (*name*)

Returns a specie named “name” from the stream.

Parameters **name** (*str*) –

Returns `specie`

Return type `obj`

**GetSpecies** ()

Returns a list of all species in the stream.

Parameters **empty** –

**Returns** `self.species`

**Return type** `list`

**GetTimeStamp()**

Returns the time stamp of the stream.

**Parameters** `empty` –

**Returns** `self.timeStamp`

**Return type** `float`

**GetValue** (*actor*, *timeStamp=None*)

Returns the value associated with a specified “actor” at a specified “timeStamp”. If no timeStamp is specified, then the function will return all values associated with the specified actor at all time stamps.

**Parameters**

- **actor** (*str*) –
- **timeStamp** (*float*) –

**Returns**

- `self.stream.loc[self.timeStamp, actor]` or `self.stream.loc[timeStamp,`
- `actor]` (*list or float, respectively.*)

**SetSpecieId** (*name*, *val*)

Sets the numerical id of the specie of name “name” to val.

**Parameters**

- **name** (*str*) –
- **val** (*int*) –

**Returns**

**Return type** `empty`

**SetValue** (*actor*, *value=None*, *timeStamp=None*)

Sets the value associated with a specified actor at a specified timeStamp to “value”. If no value is specified, the value will default to 0.0. If no timeStamp is specified, it will set all values associated with actor to the specified value (or 0.0 if value = None).

**Parameters**

- **actor** (*str*) –
- **value** (*float*) –
- **timeStamp** (*float*) –

**Returns**

**Return type** `empty`

## PYTHON MODULE INDEX

### a

actor, 15  
adjudication, 4  
arrested, 5

### c

community, 6  
cortex\_main, 1

### d

dataplot, 7  
droplet, 7  
dummy\_module, 8

### f

fuel\_bucket, 15  
fuel\_bundle, 23  
fuel\_segment, 29  
fuelsegmentsgroups, 31  
fuelslug, 32

### j

jail, 9

### m

module, 1

### n

nuclides, 34

### p

parole, 10  
periodictable, 34  
phase, 35  
plot\_data, 11  
port, 3  
prison, 11  
probation, 12

### q

quantity, 40

### r

run\_justice, 13

### s

specie, 42  
stream, 51

### v

vortex, 13

## Symbols

`__del__()` (cortex\_main.Cortex method), 1  
`__eq__()` (port.Port method), 3  
`__init__()` (adjudication.Adjudication method), 4  
`__init__()` (arrested.Arrested method), 5  
`__init__()` (community.Community method), 6  
`__init__()` (jail.Jail method), 9  
`__init__()` (module.Module method), 1  
`__init__()` (phase.Phase method), 38  
`__init__()` (prison.Prison method), 11  
`__init__()` (probation.Probation method), 12  
`__repr__()` (fuel\_bucket.FuelBucket method), 15  
`__repr__()` (fuel\_segment.FuelSegment method), 29  
`__repr__()` (port.Port method), 3  
`__repr__()` (quantity.Quantity method), 41  
`__str__()` (fuel\_bucket.FuelBucket method), 15  
`__str__()` (fuel\_segment.FuelSegment method), 29  
`__str__()` (quantity.Quantity method), 41

## A

Actor (class in actor), 15  
 actor (module), 15  
`add_module()` (cortex\_main.Cortex method), 1  
`AddGroup()` (fuelsegmentsgroups.FuelSegmentsGroups method), 31  
`AddQuantity()` (phase.Phase method), 35  
`AddRow()` (phase.Phase method), 36  
`AddSpecie()` (phase.Phase method), 36  
 Adjudication (class in adjudication), 4  
 adjudication (module), 4  
 Arrested (class in arrested), 5  
 arrested (module), 5  
 atoms (actor.Actor attribute), 15  
 atoms (specie.Specie attribute), 48

## C

`cladding_end_thickness` (fuel\_bucket.FuelBucket attribute), 15  
`cladding_mass` (fuel\_bucket.FuelBucket attribute), 16  
`cladding_phase` (fuel\_bucket.FuelBucket attribute), 16  
`cladding_volume` (fuel\_bucket.FuelBucket attribute), 16

`cladding_wall_thickness` (fuel\_bucket.FuelBucket attribute), 16  
`claddingPhase` (fuelslug.FuelSlug attribute), 33  
`ClearHistory()` (phase.Phase method), 36  
 Community (class in community), 6  
 community (module), 6  
`compute_velocity()` (vortex.Vortex method), 13  
`connect()` (module.Module method), 2  
`connect()` (port.Port method), 3  
 Cortex (class in cortex\_main), 1  
 cortex\_main (module), 1

## D

DataPlot (class in dataplot), 7  
 dataplot (module), 7  
`draw_network()` (cortex\_main.Cortex method), 1  
 Droplet (class in droplet), 7  
 droplet (module), 7  
 dummy\_module (module), 8  
 DummyModule (class in dummy\_module), 8  
 DummyModule2 (class in dummy\_module), 8

## F

`flag` (specie.Specie attribute), 48  
`formal_name` (quantity.Quantity attribute), 41  
`formalName` (quantity.Quantity attribute), 41  
`formula` (actor.Actor attribute), 15  
`formula` (specie.Specie attribute), 48  
`formula_name` (specie.Specie attribute), 48  
`fresh_u235_mass` (fuel\_bucket.FuelBucket attribute), 16  
`fresh_u235_mass` (fuel\_bundle.FuelBundle attribute), 23  
`fresh_u238_mass` (fuel\_bucket.FuelBucket attribute), 16  
`fresh_u238_mass` (fuel\_bundle.FuelBundle attribute), 24  
`fresh_u_mass` (fuel\_bucket.FuelBucket attribute), 16  
`fresh_u_mass` (fuel\_bundle.FuelBundle attribute), 24  
 fuel\_bucket (module), 15  
 fuel\_bundle (module), 23  
`fuel_enrichment` (fuel\_bucket.FuelBucket attribute), 17  
`fuel_enrichment` (fuel\_bundle.FuelBundle attribute), 24  
`fuel_mass` (fuel\_bucket.FuelBucket attribute), 17  
`fuel_mass` (fuel\_bundle.FuelBundle attribute), 24  
`fuel_mass_unit` (fuel\_bucket.FuelBucket attribute), 17



[fuel\\_mass\\_unit \(fuel\\_bundle.FuelBundle attribute\), 24](#)  
[fuel\\_phase \(fuel\\_bucket.FuelBucket attribute\), 17](#)  
[fuel\\_pin\\_length \(fuel\\_bundle.FuelBundle attribute\), 24](#)  
[fuel\\_pin\\_radius \(fuel\\_bundle.FuelBundle attribute\), 24](#)  
[fuel\\_pin\\_volume \(fuel\\_bundle.FuelBundle attribute\), 24](#)  
[fuel\\_radioactivity \(fuel\\_bucket.FuelBucket attribute\), 17](#)  
[fuel\\_radioactivity \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[fuel\\_rod\\_od \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[fuel\\_segment \(module\), 29](#)  
[fuel\\_volume \(fuel\\_bucket.FuelBucket attribute\), 17](#)  
[fuel\\_volume \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[FuelBucket \(class in fuel\\_bucket\), 15](#)  
[FuelBundle \(class in fuel\\_bundle\), 23](#)  
[fuelPhase \(fuelslug.FuelSlug attribute\), 33](#)  
[FuelSegment \(class in fuel\\_segment\), 29](#)  
[FuelSegmentsGroups \(class in fuelsegmentsgroups\), 31](#)  
[fuelsegmentsgroups \(module\), 31](#)  
[FuelSlug \(class in fuelslug\), 32](#)  
[fuelslug \(module\), 32](#)

## G

[gamma\\_pwr \(fuel\\_bucket.FuelBucket attribute\), 17](#)  
[gamma\\_pwr \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[gas\\_mass \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[gas\\_phase \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[gas\\_radioactivity \(fuel\\_bundle.FuelBundle attribute\), 25](#)  
[geometry \(fuel\\_segment.FuelSegment attribute\), 29](#)  
[get\\_attribute\(\) \(fuel\\_segment.FuelSegment method\), 30](#)  
[get\\_cladding\\_end\\_thickness\(\) \(fuel\\_bucket.FuelBucket method\), 17](#)  
[get\\_cladding\\_mass\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_cladding\\_phase\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_cladding\\_volume\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_cladding\\_wall\\_thickness\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_fresh\\_u235\\_mass\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_fresh\\_U235\\_mass\(\) \(fuel\\_bundle.FuelBundle method\), 25](#)  
[get\\_fresh\\_u238\\_mass\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_fresh\\_u238\\_mass\(\) \(fuel\\_bundle.FuelBundle method\), 25](#)  
[get\\_fresh\\_u\\_mass\(\) \(fuel\\_bucket.FuelBucket method\), 18](#)  
[get\\_fresh\\_u\\_mass\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_enrichment\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_fuel\\_enrichment\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_mass\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)

[get\\_fuel\\_mass\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_mass\\_unit\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_fuel\\_mass\\_unit\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_phase\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_fuel\\_pin\\_length\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_pin\\_radius\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_pin\\_volume\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_radioactivity\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_fuel\\_radioactivity\(\) \(fuel\\_bundle.FuelBundle method\), 26](#)  
[get\\_fuel\\_rod\\_od\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_fuel\\_volume\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_fuel\\_volume\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_gamma\\_pwr\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_gamma\\_pwr\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_gas\\_mass\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_gas\\_phase\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_gas\\_radioactivity\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_geometry\(\) \(fuel\\_segment.FuelSegment method\), 30](#)  
[get\\_heat\\_pwr\(\) \(fuel\\_bucket.FuelBucket method\), 19](#)  
[get\\_heat\\_pwr\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_inner\\_slug\\_id\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_inner\\_slug\\_od\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_modules\(\) \(cortex\\_main.Cortex method\), 1](#)  
[get\\_n\\_fuel\\_rods\(\) \(fuel\\_bundle.FuelBundle method\), 27](#)  
[get\\_n\\_slugs\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_name\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_name\(\) \(fuel\\_bundle.FuelBundle method\), 28](#)  
[get\\_name\(\) \(quantity.Quantity method\), 41](#)  
[get\\_network\(\) \(cortex\\_main.Cortex method\), 1](#)  
[get\\_outer\\_slug\\_id\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_outer\\_slug\\_od\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_port\(\) \(module.Module method\), 2](#)  
[get\\_quantity\(\) \(phase.Phase method\), 38](#)  
[get\\_quantity\\_history\(\) \(phase.Phase method\), 38](#)  
[get\\_radioactivity\(\) \(fuel\\_bucket.FuelBucket method\), 20](#)  
[get\\_radioactivity\(\) \(fuel\\_bundle.FuelBundle method\), 28](#)  
[get\\_slug\\_cladding\\_volume\(\) \(fuel\\_bucket.FuelBucket method\), 21](#)  
[get\\_slug\\_fuel\\_volume\(\) \(fuel\\_bucket.FuelBucket method\), 21](#)  
[get\\_slug\\_length\(\) \(fuel\\_bucket.FuelBucket method\), 21](#)  
[get\\_slug\\_type\(\) \(fuel\\_bucket.FuelBucket method\), 21](#)  
[get\\_solid\\_phase\(\) \(fuel\\_bundle.FuelBundle method\), 28](#)  
[get\\_specie\(\) \(fuel\\_segment.FuelSegment method\), 30](#)

[get\\_species\(\)](#) (fuel\_segment.FuelSegment method), 30  
[get\\_value\(\)](#) (phase.Phase method), 39  
[GetActors\(\)](#) (phase.Phase method), 36  
[GetActors\(\)](#) (stream.Stream method), 51  
[GetAtoms\(\)](#) (specie.Specie method), 43  
[GetAttribute\(\)](#) (fuelsegments-groups.FuelSegmentsGroups method), 31  
[GetAttribute\(\)](#) (fuelslug.FuelSlug method), 32  
[GetAttribute\(\)](#) (nuclides.Nuclides method), 34  
[GetCladdingPhase\(\)](#) (fuelslug.FuelSlug method), 33  
[GetColumn\(\)](#) (phase.Phase method), 36  
[GetFlag\(\)](#) (specie.Specie method), 43  
[GetFormalName\(\)](#) (quantity.Quantity method), 40  
[GetFormula\(\)](#) (specie.Specie method), 43  
[GetFormulaName\(\)](#) (specie.Specie method), 43  
[GetFuelPhase\(\)](#) (fuelslug.FuelSlug method), 33  
[GetFuelSegments\(\)](#) (fuelsegments-groups.FuelSegmentsGroups method), 31  
[GetMassCC\(\)](#) (specie.Specie method), 43  
[GetMassCCUnit\(\)](#) (specie.Specie method), 43  
[GetMolarCC\(\)](#) (specie.Specie method), 43  
[GetMolarCCUnit\(\)](#) (specie.Specie method), 43  
[GetMolarGammaPwr\(\)](#) (specie.Specie method), 44  
[GetMolarGammaPwrUnit\(\)](#) (specie.Specie method), 44  
[GetMolarHeatPwr\(\)](#) (specie.Specie method), 44  
[GetMolarHeatPwrUnit\(\)](#) (specie.Specie method), 44  
[GetMolarMass\(\)](#) (specie.Specie method), 44  
[GetMolarMassUnit\(\)](#) (specie.Specie method), 44  
[GetMolarRadioactivity\(\)](#) (specie.Specie method), 44  
[GetMolarRadioactivityFractions\(\)](#) (specie.Specie method), 45  
[GetMolarRadioactivityUnit\(\)](#) (specie.Specie method), 45  
[GetName\(\)](#) (specie.Specie method), 45  
[GetNAtoms\(\)](#) (specie.Specie method), 45  
[GetNNuclideTypes\(\)](#) (specie.Specie method), 45  
[GetPhase\(\)](#) (specie.Specie method), 45  
[GetQuantities\(\)](#) (phase.Phase method), 36  
[GetQuantities\(\)](#) (stream.Stream method), 51  
[GetQuantity\(\)](#) (phase.Phase method), 36  
[GetQuantity\(\)](#) (stream.Stream method), 51  
[GetRow\(\)](#) (phase.Phase method), 37  
[GetRow\(\)](#) (stream.Stream method), 51  
[GetSpecie\(\)](#) (phase.Phase method), 37  
[GetSpecie\(\)](#) (stream.Stream method), 51  
[GetSpecies\(\)](#) (phase.Phase method), 37  
[GetSpecies\(\)](#) (stream.Stream method), 51  
[GetSpecs\(\)](#) (fuelslug.FuelSlug method), 33  
[GetTimeStamp\(\)](#) (stream.Stream method), 52  
[GetTimeStamps\(\)](#) (phase.Phase method), 37  
[GetUnit\(\)](#) (quantity.Quantity method), 40  
[GetValue\(\)](#) (phase.Phase method), 37  
[GetValue\(\)](#) (quantity.Quantity method), 40  
[GetValue\(\)](#) (stream.Stream method), 52

## H

[has\\_time\\_stamp\(\)](#) (phase.Phase method), 39  
[HasGroup\(\)](#) (fuelsegmentsgroups.FuelSegmentsGroups method), 32  
[heat\\_pwr](#) (fuel\_bucket.FuelBucket attribute), 21  
[heat\\_pwr](#) (fuel\_bundle.FuelBundle attribute), 28

## I

[inner\\_slug\\_id](#) (fuel\_bucket.FuelBucket attribute), 21  
[inner\\_slug\\_od](#) (fuel\_bucket.FuelBucket attribute), 21

## J

[Jail](#) (class in jail), 9  
[jail](#) (module), 9

## M

[massCC](#) (specie.Specie attribute), 48  
[massCCUnit](#) (specie.Specie attribute), 48  
[Module](#) (class in module), 1  
[module](#) (module), 1  
[molarCC](#) (specie.Specie attribute), 48  
[molarCCUnit](#) (specie.Specie attribute), 49  
[molarGammaPwr](#) (specie.Specie attribute), 49  
[molarGammaPwrUnit](#) (specie.Specie attribute), 49  
[molarHeatPwr](#) (specie.Specie attribute), 49  
[molarHeatPwrUnit](#) (specie.Specie attribute), 49  
[molarMass](#) (specie.Specie attribute), 49  
[molarMassUnit](#) (specie.Specie attribute), 49  
[molarRadioactivity](#) (specie.Specie attribute), 50  
[molarRadioactivityFractions](#) (specie.Specie attribute), 50  
[molarRadioactivityUnit](#) (specie.Specie attribute), 50

## N

[n\\_fuel\\_rods](#) (fuel\_bundle.FuelBundle attribute), 28  
[n\\_slugs](#) (fuel\_bucket.FuelBucket attribute), 21  
[name](#) (fuel\_bucket.FuelBucket attribute), 22  
[name](#) (fuel\_bundle.FuelBundle attribute), 28  
[name](#) (module.Module attribute), 1  
[name](#) (quantity.Quantity attribute), 41  
[name](#) (specie.Specie attribute), 50  
[nAtoms](#) (specie.Specie attribute), 50  
[nNuclideTypes](#) (specie.Specie attribute), 50  
[Nuclides](#) (class in nuclides), 34  
[nuclides](#) (module), 34

## O

[outer\\_slug\\_id](#) (fuel\_bucket.FuelBucket attribute), 22  
[outer\\_slug\\_od](#) (fuel\_bucket.FuelBucket attribute), 22

## P

[Parole](#) (class in parole), 10  
[parole](#) (module), 10  
[periodictable](#) (module), 34

Phase (class in phase), 35  
 phase (module), 35  
 phase (specie.Specie attribute), 50  
 plot() (quantity.Quantity method), 42  
 plot\_data (module), 11  
 plot\_data() (dataplot.DataPlot method), 7  
 plot\_velocity() (vortex.Vortex method), 13  
 PlotData (class in plot\_data), 11  
 Port (class in port), 3  
 port (module), 3  
 port\_names\_expected (module.Module attribute), 2  
 Prison (class in prison), 11  
 prison (module), 11  
 Probation (class in probation), 12  
 probation (module), 12

## Q

quantities (phase.Phase attribute), 39  
 Quantity (class in quantity), 40  
 quantity (module), 40

## R

radioactivity (fuel\_bucket.FuelBucket attribute), 22  
 radioactivity (fuel\_bundle.FuelBundle attribute), 28  
 recv() (module.Module method), 2  
 recv() (port.Port method), 3  
 recv\_data() (dataplot.DataPlot method), 7  
 ReduceCladdingVolume() (fuelslug.FuelSlug method), 33  
 ReduceFuelVolume() (fuelslug.FuelSlug method), 33  
 RemoveFuelSegment() (fuelsegments-groups.FuelSegmentsGroups method), 32  
 ResetHistory() (phase.Phase method), 37  
 rhs\_fn() (droplet.Droplet method), 7  
 run() (adjudication.Adjudication method), 4  
 run() (arrested.Arrested method), 5  
 run() (community.Community method), 6  
 run() (cortex\_main.Cortex method), 1  
 run() (dataplot.DataPlot method), 7  
 run() (droplet.Droplet method), 7  
 run() (dummy\_module.DummyModule method), 8  
 run() (dummy\_module.DummyModule2 method), 8  
 run() (jail.Jail method), 9  
 run() (module.Module method), 2  
 run() (parole.Parole method), 10  
 run() (plot\_data.PlotData method), 11  
 run() (prison.Prison method), 11  
 run() (probation.Probation method), 12  
 run() (vortex.Vortex method), 13  
 run\_justice (module), 13

## S

ScaleRow() (phase.Phase method), 37

send() (module.Module method), 2  
 send() (port.Port method), 3  
 set\_cladding\_phase() (fuel\_bucket.FuelBucket method), 22  
 set\_fuel\_phase() (fuel\_bucket.FuelBucket method), 22  
 set\_fuel\_pin\_length() (fuel\_bundle.FuelBundle method), 28  
 set\_gas\_phase() (fuel\_bundle.FuelBundle method), 29  
 set\_slug\_length() (fuel\_bucket.FuelBucket method), 22  
 set\_solid\_phase() (fuel\_bundle.FuelBundle method), 29  
 set\_value() (phase.Phase method), 39  
 SetAtoms() (specie.Specie method), 45  
 SetFlag() (specie.Specie method), 45  
 SetFormalName() (quantity.Quantity method), 40  
 SetFormula() (specie.Specie method), 46  
 SetFormulaName() (specie.Specie method), 46  
 SetMassCC() (specie.Specie method), 46  
 SetMassCCUnit() (specie.Specie method), 46  
 SetMolarCC() (specie.Specie method), 46  
 SetMolarCCUnit() (specie.Specie method), 46  
 SetMolarGammaPwr() (specie.Specie method), 46  
 SetMolarGammaPwrUnit() (specie.Specie method), 46  
 SetMolarHeatPwr() (specie.Specie method), 47  
 SetMolarHeatPwrUnit() (specie.Specie method), 47  
 SetMolarMass() (specie.Specie method), 47  
 SetMolarMassUnit() (specie.Specie method), 47  
 SetMolarRadioactivity() (specie.Specie method), 47  
 SetMolarRadioactivityFractions() (specie.Specie method), 47  
 SetMolarRadioactivityUnit() (specie.Specie method), 47  
 SetName() (quantity.Quantity method), 40  
 SetName() (specie.Specie method), 48  
 SetPhase() (specie.Specie method), 48  
 SetSpecieId() (phase.Phase method), 38  
 SetSpecieId() (stream.Stream method), 52  
 SetUnit() (quantity.Quantity method), 40  
 SetValue() (phase.Phase method), 38  
 SetValue() (quantity.Quantity method), 41  
 SetValue() (stream.Stream method), 52  
 slug\_cladding\_volume (fuel\_bucket.FuelBucket attribute), 23  
 slug\_fuel\_volume (fuel\_bucket.FuelBucket attribute), 23  
 slug\_length (fuel\_bucket.FuelBucket attribute), 23  
 slug\_type (fuel\_bucket.FuelBucket attribute), 23  
 solid\_phase (fuel\_bundle.FuelBundle attribute), 29  
 Specie (class in specie), 43  
 specie (fuel\_segment.FuelSegment attribute), 30  
 specie (module), 42  
 species (fuel\_segment.FuelSegment attribute), 30  
 species (phase.Phase attribute), 39  
 specs (fuelslug.FuelSlug attribute), 34  
 state (module.Module attribute), 2  
 step() (droplet.Droplet method), 7  
 Stream (class in stream), 51

[stream \(module\)](#), [51](#)

## T

[time\\_stamps \(phase.Phase attribute\)](#), [39](#)

[time\\_unit \(phase.Phase attribute\)](#), [39](#)

[timeStamps \(phase.Phase attribute\)](#), [39](#)

## U

[unit \(quantity.Quantity attribute\)](#), [42](#)

## V

[value \(quantity.Quantity attribute\)](#), [42](#)

[Vortex \(class in vortex\)](#), [13](#)

[vortex \(module\)](#), [13](#)

## W

[WriteHTML\(\) \(phase.Phase method\)](#), [38](#)