Steady-State Architecture

Table of contents

Overview . . . 2
- Business domains . . . 2
- The four process types . . . 3
- Design rules of the steady-state model . . . 3
- Steady states at a glance . . . 4
- State lifecycle . . . 4
- How each state is described . . . 4

Boundary Position #0: Source Data . . . 5

State #1: Raw Data . . . 5
- 1. Definition and value added . . . 5
- 2. Producing and consuming domains . . . 5
- 3. Quality gate . . . 6
- 4. Data and metadata characteristics . . . 6
- 5. Security, privacy, and access . . . 7
- 6. Ownership and governance . . . 7
- 7. Versioning, retention, and lineage . . . 7
- 8. Reuse and handover . . . 7
- 9. Traceability to the framework . . . 8
- 10. Examples and anti-patterns . . . 8

State #2: Standardized Data . . . 8
- 1. Definition and value added . . . 8
- 2. Producing and consuming domains . . . 9
- 3. Quality gate . . . 9
- 4. Data and metadata characteristics . . . 10
- 5. Security, privacy, and access . . . 10
- 6. Ownership and governance . . . 11
- 7. Versioning, retention, and lineage . . . 11
- 8. Reuse and handover . . . 11
- 9. Traceability to the framework . . . 12
- 10. Examples and anti-patterns . . . 12

State #3: Processed Data . . . 13
- 1. Definition and value added . . . 13
- 2. Producing and consuming domains . . . 13
- 3. Quality gate . . . 13
- 4. Data and metadata characteristics . . . 14
- 5. Security, privacy, and access . . . 15
- 6. Ownership and governance . . . 15
- 7. Versioning, retention, and lineage . . . 16
- 8. Reuse and handover . . . 16
- 9. Traceability to the framework . . . 16
- 10. Examples and anti-patterns . . . 17

State #4: Statistics . . . 17
- 1. Definition and value added . . . 17
- 2. Producing and consuming domains . . . 18
- 3. Quality gate . . . 18

4. Data and metadata characteristics . . . 19
5. Security, privacy, and access . . . 20
6. Ownership and governance . . . 20
7. Versioning, retention, and lineage . . . 21
8. Reuse and handover . . . 21
9. Traceability to the framework . . . 21
10. Examples and anti-patterns . . . 22
State #5: Released Data . . . 22
1. Definition and value added . . . 22
2. Producing and consuming domains . . . 23
3. Quality gate . . . 23
4. Data and metadata characteristics . . . 24
5. Security, privacy, and access . . . 24
6. Ownership and governance . . . 24
7. Versioning, retention, and lineage . . . 25
8. Reuse and handover . . . 25
9. Traceability to the framework . . . 25
10. Examples and anti-patterns . . . 26
Boundary Position #6: Consumed Data . . . 26

Overview

Business domains

The statistical process is divided into three main business domains (Observation, Processing/Analysis, and Dissemination). Processing/Analysis is divided into four subdomains, which results in six business domains. Each domain adds one specific kind of statistical value and produces one steady state.

#	Business domain	Value added	Business functions (ArchiMate view)	Value stream	GSBPM	State in → out
1	Observation/Collection	Data in NSI custody, authentic and traceable	Receive Data, Extract Data, Collect Survey	VS-01	4	#0 → #1
2	Standardization without loss of content	Common structure, format, and classifications	Transform Data, Anonymize Data, Classify Data	VS-02	5.1–5.2	#1 → #2
3	Editing, derivation, and non-response correction	Reliable, complete, enriched microdata	Imputate Data, Integrate Data	VS-03	5.3–5.5, 5.8	#2 → #3
4	Estimation and balancing	Representative statistics with accuracy	Estimate Data, Aggregate Data	VS-04	5.6–5.7, 6.1–6.4	#3 → #4

#	Business domain	Value added	Business functions (ArchiMate view)	Value stream	GSBPM	State in → out
5	Statistically composed and composite products	Coherent, approved products	Compose Data	VS-05	6.5, 7.1–7.2	#4 → #4 (approved)
6	Dissemination	Disclosure-safe, accessible released data	Data Delivery, Data Publication	VS-06	6.4, 7.3–7.5	#4 → #5
—	Consumption (external)	Use of statistics by society	Data Consumption, Consumption Optimization	VS-10 (feedback)	8	#5 → (#6)

The execution processes between the business domains are loosely coupled. Each has its own design and implementation. For the mutual exchange of data, they are loosely linked via steady state interfaces. To this end, five steady state phases are recognized as handover points at the business-domain boundaries described above. This means that the business domain "Observation" produces "Raw Data", business domain "Standardization without loss of content" produces "standardized data" etc. 1. raw data, 2. standardized data, 3. processed data, 4. statistics, 5. released data, and 6. Consumable data products.

A steady state phase is therefore an environment where high-quality versions of data are brought together for exchange, but it also represents a value in the value chain of this data.

The four process types

Each business domain uses the same four process types:

1. **Design** of the execution processes, which provides metadata.
2. **Implementation** of the execution processes, which provides the execution process.
3. **Execution** of the execution processes, which provides the statistical data.
4. **Management** of the execution processes, which provides quality reports.

How an execution process adds statistical value, and therefore how it is designed and implemented, falls outside the scope of the SAF business architecture. That design follows from, among other things, the NSI's methodology.

Design rules of the steady-state model

The model rests on six design rules. They apply the SAF architecture principles to the data value chain.

1. **Loose coupling through states (SAF-P07).** Domains exchange data only through registered steady states, never through each other's internal working data. A domain can change its methods or systems without affecting its neighbours, as long as the state it produces meets its quality gate.
2. **One state, one kind of value.** Each state represents exactly one kind of added statistical value. This keeps quality gates testable and accountability unambiguous.
3. **Immutable quality versions.** Data registered in a state is never overwritten. Corrections and redeliveries create a new version, so every statistic can be traced to the exact data it was built on.
4. **No state without metadata (SAF-P09).** Registration requires the minimum metadata set of the state. Data without it does not enter the state.

5. **Progressive confidentiality (SAF-P11).** Protection increases along the chain: direct identifiers are removed or pseudonymised at #2, disclosure risk is assessed at #3, initial disclosure control is applied at #4, and final disclosure control gates #5.
6. **Reuse before reprocessing (SAF-P08).** An authorised consumer that needs data at a given level of value reuses the registered state rather than repeating the upstream processing.

Steady states at a glance

Position	Name	Produced by	Kind of value	Mandatory?
(#0)	Source Data	External provider	Outside NSI custody, boundary position	n/a
#1	Raw Data	VS-01	Authentic, traceable custody	When the product collects its own data
#2	Standardized Data	VS-02	Comparability, values unchanged	Optional
#3	Processed Data	VS-03	Reliability and completeness of microdata	Always
#4	Statistics	VS-04, VS-05	Representative, approved statistics	Always
#5	Released Data	VS-06	Disclosure-safe, accessible output	When output is released
(#6)	Consumed Data	External users	Outside NSI control, boundary position	n/a

State lifecycle

Every steady state follows the same lifecycle:

1. **Promotion.** The producing domain submits a dataset to the quality gate of the target state.
2. **Gate outcome.** The dataset is accepted, conditionally accepted with explicit quality flags, or rejected. Rejected data does not enter the state; it returns to the producing domain or, for #1, to the provider.
3. **Registration.** An accepted dataset receives a persistent identifier, its metadata is registered in the catalogue, and a registration event notifies consuming domains.
4. **Consumption.** Authorised consuming domains read the registered version. Responsibility for further processing transfers on receipt of the event; custody of the registered version stays with the producer.
5. **Revision.** A correction produces a new version that passes the same gate. Consumers are notified and decide whether to reprocess. Earlier versions remain available for as long as statistics depend on them.
6. **Retirement.** A version is disposed of according to the retention policy of the state, after its lineage obligations have been met.

How each state is described

Each state below is described with the same ten attributes. NSIs can use this template to document their own implementation; the SAF toolkit will provide it as a fill-in form.

#	Attribute	Question it answers
1	Definition and value added	What is this state and why does it exist?

#	Attribute	Question it answers
2	Producing and consuming domains	Who creates it, and who may use it?
3	Quality gate	What must data satisfy to be registered?
4	Data and metadata characteristics	What does the data look like, and which metadata must accompany it?
5	Security, privacy, and access	How is the data protected, and who may see it?
6	Ownership and governance	Who is accountable?
7	Versioning, retention, and lineage	How are versions managed, how long are they kept, and how is the trace preserved?
8	Reuse and handover	How is the state made available to consumers?
9	Traceability to the framework	Which capabilities, value-stream stages, and GSBPM sub-processes relate to it?
10	Examples and anti-patterns	What does good practice look like, and what should be avoided?

Boundary Position #0: Source Data

Description: Source data is data as it exists at the data holder, before it enters the NSI: a register at a government agency, a company's accounting system, a respondent's answers before submission, or a web page. The NSI has no custody of source data and cannot guarantee its quality. It can influence it only through agreements, questionnaire design, and cooperation with the data holder.

Why it is described: The SAF describes #0 so that the boundary of the NSIs responsibility is explicit. Everything the NSI knows about source data is captured as metadata when the data crosses into #1: who provided it, under which agreement, through which channel, and in what condition.

State #1: Raw Data

1. Definition and value added

Raw data is data received from an external data holder or respondent, placed under NSI custody in its original form, and verified for technical integrity and authenticity. It is the first point of possession. At this moment the NSI does not have access to the data at the source, so #1 is the earliest point at which the NSI can guarantee what it holds.

The value of #1 is **authentic custody**. It proves that the NSI holds exactly what the provider delivered, when it was delivered, under which legal basis, and through which channel. That proof is the foundation for all downstream traceability. If a statistic is ever questioned, the chain of evidence ends here.

2. Producing and consuming domains

Role	Domain	Note
Producer	Observation/Collection (VS-01)	Functions: Receive Data, Extract Data, Collect Survey
Primary consumer	Standardization (VS-02)	Triggered by the *Raw Data Registered* event
Secondary consumer	Editing (VS-03)	Only where #2 is skipped for this product

Role	Domain	Note
Occasional consumer	Innovation and Methodology (VS-08)	Source exploration, under specific authorisation
Assurance	Governance and Compliance (VS-07)	Audit of provenance and legal basis

3. Quality gate

The gate for #1 checks technical and legal conditions only. It does not assess content; content quality is the concern of #3.

Criterion	Check	Typical outcome on failure
Legal basis	A valid agreement or statutory basis covers this delivery	Reject; escalate to legal
Sender authenticity	Sender verified (certificate, credentials, signed delivery)	Reject
Integrity	Checksum or digital signature matches	Reject; request redelivery
Security	Malware and security scan passed	Quarantine; reject
Structural conformance	Delivery matches the agreed technical specification (file format, schema, encoding)	Reject or conditionally accept with flag
Completeness against agreement	Record counts and delivery scope within agreed tolerance	Conditionally accept with flag, or reject
Timeliness	Delivered within the agreed window	Accept with flag; report to relationship management
Metadata	Minimum metadata set captured (see attribute 4)	Hold until complete

Conditional acceptance is a deliberate option. A late or slightly incomplete delivery may still be the best available data. The flag ensures every downstream user knows this.

4. Data and metadata characteristics

Data. Raw data is stored in its original format, or in a lossless technical equivalent. Permitted technical operations are those that change representation without changing content and that can be reversed: decryption, decompression, character-encoding normalisation, and container conversion. Operations that change values, codes, or record selection are not permitted at #1. The original byte stream, or a verifiable hash of it, is retained.

Minimum metadata set.

Metadata element	Description
Persistent identifier and version	Unique identifier of this delivery version
Provider	Organisation or respondent group that supplied the data
Agreement reference and legal basis	Agreement identifier and the applicable legal ground
Channel and method	Transfer channel (file transfer, API, data space connector, survey mode) and instrument version
Receipt timestamp	Moment of receipt into NSI custody
Integrity proof	Checksum or signature value and algorithm
Volume	Record count and size
Reference period	Period the data describes, as stated by the provider
Structural description	Schema or technical specification the delivery conforms to

Metadata element	Description
Gate outcome	Accepted or conditionally accepted, with quality flags
Classification	Availability, integrity, and confidentiality rating

In GSIM terms, #1 typically instantiates a *Data Set* received from an *Information Provider* through an *Exchange Channel* under a *Provision Agreement*.

5. Security, privacy, and access

Raw data usually contains direct identifiers and therefore carries the highest confidentiality rating in the chain. Access is limited to the roles that operate the intake and the standardization process. Analysts and subject-matter staff do not work on #1.

Pseudonymisation is normally applied at the transition to #2. Some NSIs pseudonymise at the intake boundary, or receive data already pseudonymised by a trusted third party. Both variants are compatible with the model, provided the choice is documented and the key management is separated from the data. Data minimisation starts before #1: the agreement and the collection design determine that only necessary data is received.

6. Ownership and governance

Role	Responsibility for #1
Data owner	Process owner of Observation/Collection; accountable for lawful acquisition and fitness of the intake
Data steward	Maintains metadata and catalogue entries; resolves gate exceptions
Data custodian	Operates storage, access control, and retention
Relationship manager	Handles provider follow-up on rejected or flagged deliveries (with VS-10)

7. Versioning, retention, and lineage

Every delivery, including a redelivery or correction by the provider, is a new immutable version. A redelivery never overwrites an earlier version, because statistics may already be built on it.

Retention of #1 is governed by two needs that pull in opposite directions. Reproducibility and audit favour keeping raw data; data minimisation and storage cost favour disposal. A common arrangement is to keep #1 until the dependent #3 version is verified and the audit period has passed, while #3 is the state subject to long-term archival requirements. The exact period is set by national law and NSI policy.

Lineage at #1 is the provenance record: the link from the registered version to the provider, the agreement, and the delivery event. Every downstream state must be able to trace back to a #1 version or, where a product starts from another domain's data, to the state it consumed.

8. Reuse and handover

Registration of #1 publishes the *Raw Data Registered* event and a catalogue entry. Consumers discover the delivery through the catalogue and access it through the handover interface, never through direct access to the intake system.

One delivery can serve several statistical products. The register-based census and the labour market statistics may both draw on the same population register delivery. Under SAF-P08, products reuse the

registered delivery rather than requesting the same data again from the provider. This also reduces response burden.

Handover element	Content
Artefact	Registered Raw Data version
Required metadata	Minimum metadata set (attribute 4)
Trigger event	*Raw Data Registered*
Responsibility transfer	VS-01 keeps custody; the consumer takes responsibility for further processing on receipt of the event

9. Traceability to the framework

Framework element	References
Capabilities	1.2.1 Primary data collection, 1.2.2 Secondary data collection, 2.1.1 Data lifecycle management, 2.1.2 Metadata management, 3.3.4 Logical identity and access control, 3.4.3 Service agreement
Value-stream stages	VS-01.3 Collect, Receive, or Extract Data; VS-01.4 Validate and Log Data Intake; VS-01.5 Store and Register Raw Data Artefacts
GSBPM	4.3 Run collection, 4.4 Finalise collection
Principles	SAF-P07, SAF-P08, SAF-P09, SAF-P10, SAF-P11

10. Examples and anti-patterns

Examples

- *Survey.* Responses from a web questionnaire are received with paradata (mode, completion time, instrument version). The delivery is registered as one #1 version per collection batch.
- *Administrative register.* A quarterly tax file arrives by file transfer, with a manifest. Checksum, schema, and record count are checked against the agreement; 14 unknown business identifiers are not a #1 issue and pass through for handling downstream.
- *Web data.* Daily scraped price data is registered with the scraper version and page fingerprint per retailer, so a change in a website's structure can be traced to the affected deliveries.

Anti-patterns

- Correcting obvious errors "while the file is open" at intake. Any value change belongs in #3, where it is documented.
- Overwriting a delivery with the provider's corrected version. Statistics built on the first version lose their trace.
- Giving analysts direct access to raw data for convenience. This bypasses the pseudonymisation at #2.
- Keeping only a converted copy and discarding the original. The proof of authentic custody is lost.
- Registering a delivery without its agreement reference. The legal basis can no longer be demonstrated in an audit.

State #2: Standardized Data

1. Definition and value added

Standardized data is raw data that has been brought into the common structure, format, and classifications of the NSI. Its values are unchanged. Only the representation changes: fields are renamed and restructured, types are cast, source codes are mapped one-to-one to standard codes, and descriptive metadata is attached.

Direct identifiers are removed or replaced with pseudonymous keys. #2 is therefore the first state in which data from different sources can be compared and combined, and the first state without direct identifiers.

The value of #2 is **comparability without loss of content**. Data that looked different at the source now uses the same structure, the same codes, and documented definitions, units, and reference periods. Because no value has changed, the trace back to the authentic delivery in #1 stays simple and deterministic. Every interpretation, correction, or conversion is left to #3, where it is documented as an edit.

#2 is an optional state. A product can go directly from #1 to #3, for example when a source already arrives in the NSI's standard structure and coding. In that case the NSI records in the catalog that #2 was skipped, and why (see *Applying the steady states pragmatically*). [**SS1**]

2. Producing and consuming domains

Role	Domain	Note
Producer	Standardization without loss of content (VS-02)	Functions: Transform Data, Anonymize Data, Classify Data
Primary consumer	Editing (VS-03)	Triggered by the *Standardized Data Registered* event
Secondary consumer	Other statistical products	Reuse of the same standardized source under SAF-P08, with authorization
Occasional consumer	Innovation and Methodology (VS-08)	Exploration of sources and methods, under specific authorization
Assurance	Governance and Compliance (VS-07)	Audit of mapping lineage and pseudonymization

3. Quality gate

The gate for #2 checks conformance and preservation. It does not assess whether values are correct; that is the concern of #3. A value that cannot be mapped is not an error of standardization. It is a fact about the source, so it is flagged and handed to VS-03.

Criterion	Check	Typical outcome on failure
Structural conformance	Fields, types, formats, and cardinalities match the target data model	Reject; re-map
Classification conformance	Every mapped code exists in the stated classification version; no orphan codes	Reject; correct the correspondence table
Mapping coverage	Share of source codes mapped one-to-one is above the agreed threshold	Conditionally accept with flag; unmapped values listed for VS-03
Semantic metadata	Unit, currency, reference-period basis, and definition recorded for every variable	Hold until complete
No loss of content	Record counts and key measures identical to the #1 version; no value changed	Reject
Identifier protection	Direct identifiers removed or pseudonymized according to the privacy design	Reject; escalate to the privacy officer
Referential integrity	Linkage keys exist in the reference register (e.g., the statistical business register)	Conditionally accept with flag

Criterion	Check	Typical outcome on failure
Metadata and lineage	Minimum metadata set captured (see attribute 4); field-level lineage complete	Hold until complete

Conditional acceptance is the normal outcome for many sources. Unmapped codes and unmatched keys are often caused by known lags, such as newly registered businesses. The flag ensures every downstream user knows exactly which values still need work.

4. Data and metadata characteristics

Data. Standardized data is stored in the canonical target data model. Standard codes are stored next to the original source values, so the original remains visible. Permitted operations are renaming, restructuring, type casting, reformatting (for example from CSV to a standard exchange format), key alignment, one-to-one code mapping through maintained correspondence tables, removal or pseudonymization of direct identifiers, and dropping variables that are not needed for the statistical purpose. Operations that change values are not permitted at #2: unit or currency conversion, reference-period alignment, reconciliation of differing definitions, derivation, interpretive coding of free text, editing, and imputation. These belong to #3. [**SS2**]

Minimum metadata set.

Metadata element	Description
Persistent identifier and version	Unique identifier of this standardized version
Source reference	The #1 version or versions this dataset was produced from
Target model version	Version of the canonical data model applied
Mapping ruleset and engine version	Versions of the mapping rules and the tool that applied them
Classifications applied	Scheme and version per coded variable (e.g., NACE Rev. 2, ISCED 2011)
Mapping coverage and unmapped values	Coverage per variable and the list of values routed to VS-03
Units, currency, and reference-period basis	Recorded per variable as received, not converted
Concept links and definition differences	Link to the canonical concept; recorded differences with other sources
Pseudonymization record	Identifiers removed or pseudonymized, method, key reference (never the key itself)
Conformance assessment	Structural, classification, and semantic results; no-loss-of-content confirmation
Gate outcome	Accepted or conditionally accepted, with quality flags
Classification	Availability, integrity, and confidentiality rating

In GSIM terms, #2 typically instantiates a *Unit Data Set* that conforms to a *Data Structure*, whose *Represented Variables* take their values from *Statistical Classifications* and *Code Lists*.

5. Security, privacy, and access

#2 is the point where direct identifiers leave the working data. **Removal** deletes an identifier and ends the possibility to link on it. **Pseudonymization** replaces it with a key that still allows records to be linked. The privacy design decides per identifier which of the two applies, and the choice is recorded in the pseudonymization record.

Pseudonymization keys are managed by the data custodian, separately from the data and under separate access rights. Staff who work on #2 and later states never have access to the keys. Some NSIs pseudonymize

at intake, or receive data already pseudonymized by a trusted third party. In that case #2 confirms and records the protection that is already in place.

Standardized data is still detailed microdata. Indirect identifiers, such as date of birth, place of residence, or occupation, remain, and combinations of them can identify a person or business. The confidentiality rating of #2 therefore stays high. Access is limited to the roles that standardize and edit the data, and to authorized reusers with a stated purpose. The formal assessment of disclosure risk starts at #3. **[SS3]**

6. Ownership and governance

Role	Responsibility for #2
Data owner	Process owner of Standardization; accountable for conformance and for applying the privacy design
Data steward	Registers versions, maintains catalog entries, and resolves gate exceptions
Data custodian	Operates storage, access control, and retention; manages pseudonymization keys separately from the data
Classification steward	Maintains the correspondence tables and the classification versions used in mapping
Metadata and data architect	Owns the target data model and the links to canonical concepts

7. Versioning, retention, and lineage

Every standardization run produces a new immutable version. A new version also arises when the input stays the same but the rules change: a new correspondence table, a new classification version, or a revised target model. The earlier version is never overwritten, because #3 versions may already be built on it. Each #2 version records the exact #1 version and rule versions it was produced from.

Standardization is deterministic, so a #2 version can be regenerated from its #1 version and the recorded rule versions. Many NSIs therefore keep #2 only as long as the dependent #3 versions are produced and reviewed. This only works while #1 and the rule versions are themselves retained. If #1 is disposed of earlier, #2 must be kept for as long as reproducibility requires. The exact periods are set by national law and NSI policy.

Lineage at #2 is field-level. Each standardized value can be traced to the raw value it came from and to the mapping rule that was applied. The pseudonymization record shows which identifiers were replaced, without revealing the keys.

8. Reuse and handover

Registration of #2 publishes the *Standardized Data Registered* event and a catalog entry. Consumers discover the version through the catalog and access it through the handover interface, never through the standardization working environment.

One standardized source can serve many statistical products. A population register delivery is standardized once and is then used by the census, labour market statistics, and income statistics. Under SAF-P08, products reuse the registered version instead of standardizing the same source again. Repeating the work per product wastes effort and leads to inconsistent coding of the same source.

The list of unmapped values and the recorded units and periods travel with the handover. VS-03 then knows exactly which interpretive coding and conversions remain to be done.

Handover element	Content
Artifact	Registered Standardized Data version

Handover element	Content
Required metadata	Minimum metadata set (attribute 4), including unmapped values and recorded units and periods
Trigger event	*Standardized Data Registered*
Responsibility transfer	VS-02 keeps custody; the consumer takes responsibility for editing, interpretive coding, and conversion on receipt of the event

9. Traceability to the framework

Framework element	References
Capabilities	1.3.1 Data standardization, 2.1.1 Data lifecycle management, 2.1.2 Metadata management, 2.1.4 Statistical register management, 3.3.1 Privacy management, 3.3.4 Logical identity and access control
Value-stream stages	VS-02.1 Profile and Assess Data Structure; VS-02.2 Apply Standard Classifications and Formats; VS-02.3 Align Metadata and Semantics; VS-02.4 Validate Structural and Semantic Conformance; VS-02.5 Register Standardized Artifacts
SAF processes [**SS4**]	PRD-5.2 Classify and code (deterministic mapping only), PRD-5.3 Review and validate (structural checks only), DLM-2 Promote data through a quality gate, DLM-3 Register and catalog data, DLM-4 Classify and protect data, DLM-9 Manage reference and master data
GSBPM	5.1 Integrate data (key alignment only; record linkage takes place in #3), 5.2 Classify and code
Principles	SAF-P07, SAF-P08, SAF-P09, SAF-P10, SAF-P11
Medallion layer [**SS4**]	Silver, lower sub-layer; in a Medallion arrangement often merged with #3

10. Examples and anti-patterns

Examples

- *Survey.* Labour Force Survey returns are restructured into the canonical person and household model. Source education codes are mapped one-to-one to ISCED 2011, and region codes to NUTS-3. The 42,000 free-text occupation answers are not coded here; they are listed as unmapped and handed to VS-03. The personal identifier is replaced with a pseudonymous key.
- *Administrative register.* The tax authority's internal activity codes are mapped to NACE Rev. 2 through a maintained correspondence table; 0.6% of codes have no correspondence and are flagged. Turnover stays in thousands of euro on a fiscal-year basis, and this basis is recorded as metadata. Conversion to units on a calendar-year basis takes place in #3.
- *Web data.* Scraped price records are reshaped into the canonical price record. Currency, unit, and scrape timestamp are recorded as metadata, and prices are kept exactly as received. Most products only have a free-text name and are passed to VS-03 for classification to COICOP.

Anti-patterns

- Converting currencies or units at #2 "because the data is open anyway". The value changes without an edit record.
- Coding free text with a classifier at #2. Interpretive coding needs review and logging, which happens in #3.
- Silently dropping records with unknown codes. This breaks the no-loss-of-content guarantee.

- Overwriting a #2 version after a correspondence table update. Statistics built on the earlier version lose their trace.
- Storing pseudonymization keys together with the data. The protection of #2 is then only on paper.
- Skipping #2 without recording the reason. Auditors can no longer see why the state is missing.

State #3: Processed Data

1. Definition and value added

Processed data is microdata whose content has been checked, corrected, completed, and enriched. Errors, duplicates, outliers, and inconsistencies have been detected and resolved. Missing values have been imputed, free text has been coded, and units, currencies, and reference periods have been converted to a common basis. Records from different sources have been linked, and new variables have been derived. Unlike in #2, values do change here, but every change is documented, attributable, and reversible.

The value of #3 is **reliability and analytical readiness**. Every estimate, model, and publication downstream rests on this microdata. The guarantee is not that values stay the same, but that no value changes without a record of the original value, the rule or decision applied, the reason, the actor, and the time. That record makes it possible to explain, reproduce, or reverse any change.

#3 is the only steady state that is mandatory for all statistical production. It is the microdata on which everything downstream is verifiably built. It is also the state that national archival requirements usually apply to: without it, the statistics built on it cannot be re-verified. **[SS5]**

Processing is primarily driven by the individual statistical domains. Depending on the type of data, it may also be performed by a central unit for efficiency and consistency. Either way, the result is registered as #3 under the same quality gate.

2. Producing and consuming domains

Role	Domain	Note
Producer	Editing, derivation, and non-response correction (VS-03)	Functions: Impute Data, Integrate Data
Primary consumer	Estimation and Analysis (VS-04)	Triggered by the *Processed Data Registered* event
Secondary consumer	Other statistical products	Reuse of processed microdata under SAF-P08, with authorization
Secondary consumer	Microdata services (VS-06)	Research datasets are prepared from #3 and released as #5 **[SS6]**
Occasional consumer	Innovation and Methodology (VS-08)	Testing of new editing, imputation, or coding methods, under specific authorization
Assurance	Governance and Compliance (VS-07)	Audit of edit lineage, methodology compliance, and disclosure risk

3. Quality gate

The gate for #3 checks content quality and traceability. It is the first gate that judges whether values are plausible and complete. A dataset may pass with known remaining quality issues, as long as they are measured and documented.

Criterion	Check	Typical outcome on failure
Rule conformance	No record violates the validation and editing rules after correction	Reject; re-edit
Edit lineage	Every changed value has its original value, rule or decision, reason, actor, and time recorded	Hold until complete
Imputation flags	Every imputed value carries a flag and a method code; no observed value is overwritten	Reject
Coding	Free-text values are coded or explicitly left uncoded with a reason; low-confidence codes are reviewed	Conditionally accept with flag
Conversion and reconciliation	Every unit, currency, or reference-period conversion and every reconciliation has its rule and original value recorded	Hold until complete
Linkage quality	Linkage rate and match quality are measured and within agreed limits	Conditionally accept with flag, or reject
Derived variables	Every derived variable has a formula, inputs, unit, and classification	Hold until complete
Quality improvement	Completeness and accuracy measured against the #2 baseline (or #1 where #2 was skipped)	Conditionally accept with flag
Disclosure risk	Re-identification risk of the enriched and linked data assessed against the privacy design	Reject; reduce detail or restrict access
Reproducibility	The version can be regenerated from its inputs plus the recorded rules and models	Reject

Conditional acceptance is common for imputation and linkage. A linkage rate slightly below target may still give the best available data. The flag makes sure estimation in VS-04 takes the issue into account, for example in its variance estimation.

4. Data and metadata characteristics

Data. Processed data contains the processed value of every variable. The original value stays recoverable through the edit lineage, and imputed values carry a flag. Permitted operations are error detection, editing and correction, imputation, interpretive coding of free text, conversion of units, currencies, and reference periods, reconciliation of values between sources, record linkage, and derivation of new variables and units. These are the value-changing operations that #2 deliberately left open. Operations that turn microdata into statistics are not permitted at #3: weighting, calibration, estimation, and aggregation belong to #4. **[SS5]**

Minimum metadata set.

Metadata element	Description
Persistent identifier and version	Unique identifier of this quality version
Source reference	The #2 version or versions (or #1, where #2 was skipped) this dataset was produced from
Rule and model versions	Versions of the editing rules, imputation models, coding service, and derivation specifications applied
Edit lineage	Per changed value: original value, new value, rule or decision, reason code, actor, and time

Metadata element	Description
Imputation record	Per imputed value: flag, method code, and the predictors or donors used
Coding record	Per coded value: source text, assigned code, method, and confidence
Conversion and reconciliation record	Rule, factor or rate, and original value for every conversion or reconciliation
Linkage record	Keys used, matching method, linkage rate, and match quality
Derived variables	Formula, inputs, unit, and classification per derived variable
Quality assessment	Edit rate, imputation rate, coding completion, and improvement against the baseline
Disclosure-risk assessment	Outcome of the re-identification risk assessment and the resulting access conditions
Gate outcome	Accepted or conditionally accepted, with quality flags
Classification	Availability, integrity, and confidentiality rating

In GSIM terms, #3 typically instantiates a *Unit Data Set*, extended with derived *Represented Variables*. The edits are described as *Rules* applied in *Process Steps*, which gives the edit lineage its formal structure.

5. Security, privacy, and access

Processed data is pseudonymized microdata, but it is richer than #2. Linking sources and deriving variables adds detail, and more detail means a higher risk that a person or business can be recognized. #3 is therefore the point where the disclosure risk of microdata is formally assessed. The outcome sets the conditions for access and reuse.

Linkage uses the pseudonymous keys created at #2. The keys themselves remain with the data custodian, separately from the data. Access to #3 is limited to the roles that edit, estimate, and analyze the data, and to authorized reusers with a stated purpose. External researchers never access #3 directly. Their access runs through the microdata services in VS-06, which prepare a project-specific dataset with its own pseudonyms and release it as #5.

The edit audit trail is itself sensitive and must be tamper-evident. It shows who changed which value and why, which is essential evidence in an audit.

6. Ownership and governance

Role	Responsibility for #3
Data owner	Process owner of Editing; accountable for the quality version and for the correct application of approved methods
Data steward	Registers quality versions, maintains catalog entries, and resolves gate exceptions
Data custodian	Operates storage, access control, retention, and archival; keeps pseudonymization keys separate from the data
Methodologist	Owns the editing rules, imputation methodology, and derivation specifications
Subject-matter statistician	Adjudicates flagged records and signs off domain-specific corrections

7. Versioning, retention, and lineage

Every completed editing cycle produces a new immutable quality version. A new version also arises when a source is redelivered, when a correction comes in, or when a rule or model changes. The earlier version is never overwritten, because estimates may already be built on it. Many NSIs distinguish preliminary and final versions; both are registered as separate quality versions of #3.

#3 is usually the state with the longest retention. It is the microdata that must be preserved to re-verify published statistics, and archival legislation often applies to it. When #3 is archived, its edit lineage, imputation flags, and derived-variable definitions are archived with it. Without that metadata, the archived values cannot be interpreted.

Lineage at #3 is value-level. Each processed value can be traced back to its original value in #2 or #1, the rule or decision that changed it, and the inputs of any imputation, conversion, or derivation. Linked records keep a reference to the source records they were built from.

8. Reuse and handover

Registration of #3 publishes the *Processed Data Registered* event and a catalog entry. Consumers discover the version through the catalog and access it through the handover interface, never through the editing working environment.

Processed microdata is the most valuable reusable asset in the chain. An integrated person-level dataset, edited and enriched once, can serve many statistics on labor, income, education, and health. Under SAF-P08, products reuse the registered quality version rather than editing the same data again. Editing the same data twice leads to different corrections of the same record, and therefore to statistics that do not agree.

The imputation flags travel with the handover. VS-04 needs them to reflect the extra uncertainty of imputed values in its accuracy measures.

Handover element	Content
Artifact	Registered Processed Data quality version
Required metadata	Minimum metadata set (attribute 4), including edit lineage, imputation flags, and derived-variable definitions
Trigger event	*Processed Data Registered*
Responsibility transfer	VS-03 keeps custody; the consumer takes responsibility for weighting, estimation, and analysis on receipt of the event

9. Traceability to the framework

Framework element	References
Capabilities	1.3.2 Deriving variables and units, 1.3.3 Check content, 1.3.4 Adjusting and imputing, 2.1.1 Data lifecycle management, 2.1.2 Metadata management, 2.1.3 Statistical quality management, 2.1.4 Statistical register management
Value-stream stages	VS-03.1 Conduct Error Detection and Quality Diagnostics; VS-03.2 Perform Data Editing and Correction; VS-03.3 Impute Missing or Non-Response Data; VS-03.4 Derive Additional Variables and Indicators; VS-03.5 Perform Quality Evaluation and Versioning

Framework element	References
SAF processes	PRD-5.1 Integrate data, PRD-5.2 Classify and code (interpretive coding), PRD-5.3 Review and validate, PRD-5.4 Edit and impute, PRD-5.5 Derive new variables and units, PRD-5.8 Finalize data files, DLM-2, DLM-3, DLM-7 Revise data, DLM-10 Archive and preserve data
GSBPM	5.1 Integrate data, 5.2 Classify and code, 5.3 Review and validate, 5.4 Edit and impute, 5.5 Derive new variables and units, 5.8 Finalize data files
Principles	SAF-P07, SAF-P08, SAF-P09, SAF-P10, SAF-P11
Medallion layer	Silver; the main reusable microdata layer

10. Examples and anti-patterns

Examples

- *Survey.* The 42,000 free-text occupation answers handed over from #2 are coded to ISCO-08: 88% automatically, the rest computer-assisted or by experts. Item non-response on income (9%) is imputed by regression and flagged. Each coded and imputed value carries its method, so it can be reviewed or revised later.
- *Administrative register.* Turnover, received in thousands of euro on a fiscal-year basis, is converted to units on a calendar-year basis. The conversion factor and the original value are stored in the lineage. The tax data is then linked to the business survey on the statistical business register key, and a reconciliation rule resolves values where the two sources disagree.
- *Web data.* Products with only a free-text name are classified to COICOP with a machine-learning classifier; low-confidence cases are reviewed. Prices are converted to euro and standard units. Missing daily prices are filled by carry-forward and flagged with a staleness indicator.

Anti-patterns

- Overwriting the original value with the corrected one. The edit can no longer be explained or reversed.
- Imputing without a flag. Estimation then treats imputed values as observed and understates uncertainty.
- Correcting every outlier by hand. Over-editing costs effort, changes little in the results, and can introduce bias.
- Calculating weights or aggregates at #3. That work belongs to #4, where its method and accuracy are documented.
- Fixing values in a spreadsheet outside the editing pipeline. The change has no lineage and cannot be reproduced.
- Linking an extra source without reassessing disclosure risk. The richer dataset may identify people that #2 did not.
- Disposing of #3 once figures are published. The published statistics can then no longer be verified.

State #4: Statistics

1. Definition and value added

Statistics are the results produced from processed microdata: estimates, aggregates, indices, time series, and model outputs. Each result carries the method that produced it and a measure of its accuracy, such as a standard error or confidence interval. State #4 can also hold output microdata with weights, prepared for a specific internal purpose. Initial disclosure control has been applied, so the results can potentially be released. They are not yet released: #4 may still contain detail that is confidential or not suitable for publication.

The value of #4 is **statistical credibility and coherence**. Data has become information about a population, and that information is accurate, transparent, and consistent with related statistics. Any figure

in #4 can be regenerated from #3 and defended, because its method, parameters, weights, and accuracy are recorded.

#4 is produced by two domains and therefore has **two gate moments**. [**SS7**]

Gate moment	Produced by	Status of the version	What it confirms
Analytical gate	Estimation and closed-loop (VS-04)	*Analytical*	Results are methodologically sound, accurate, coherent, and initially disclosure-controlled
Approval gate	Statistically composed and composite products (VS-05)	*Approved*	Results are composed into a coherent product, explained, checked against dissemination and confidentiality standards, and signed off

Both are versions of the same state. Approval does not change an analytical version; it creates a new, immutable version with the status *approved* that refers to the analytical versions it was composed from. #4 is mandatory for all statistical production.

2. Producing and consuming domains

Role	Domain	Note
Producer (analytical)	Estimation and closed-loop (VS-04)	Functions: Estimate Data, Aggregate Data
Producer (approved)	Statistically composed and composite products (VS-05)	Function: Compose Data
Primary consumer (analytical)	Product composition (VS-05)	Triggered by the *Output Data Registered* event
Primary consumer (approved)	Dissemination (VS-06)	Triggered by the *Statistical Product Registered* event
Secondary consumer	Other statistical processes	Internal input for macro statistics and integration systems, such as the national accounts
Assurance	Governance and Compliance (VS-07)	Audit of methodology, reproducibility, and approval

3. Quality gate

The two gate moments check different things. The analytical gate tests the statistics; the approval gate tests the product.

Analytical gate (VS-04)

Criterion	Check	Typical outcome on failure
Approved method	Estimation, weighting, and model methods are approved and documented for this output	Reject; return to design
Weights	Calibration converged; weights within the agreed bounds	Reject; re-weight

Criterion	Check	Typical outcome on failure
Accuracy	Every estimate has an accuracy measure; imputation uncertainty from #3 is reflected	Hold until complete
Model diagnostics	Diagnostics of model-based results are within the agreed limits	Reject, or conditionally accept with flag
Soundness and coherence	Results are plausible and coherent with prior periods and related statistics; large movements are explained	Conditionally accept with flag, or reject
Initial disclosure control	Disclosure risk assessed and initial protection applied	Reject
Reproducibility	Results regenerate from #3 plus the recorded methodology and parameters	Reject
Metadata	Minimum metadata set captured (see attribute 4)	Hold until complete

Approval gate (VS-05)

Criterion	Check	Typical outcome on failure
Component selection	The exact analytical versions used are pinned and recorded	Hold until complete
Composition	Composite indicators, indices, and time series follow their documented specifications	Reject; re-compose
Consistency and coherence	Totals reconcile to components; the product is coherent with related and prior products	Return to VS-04, or conditionally accept with explained flag
Interpretive content	Commentary and visualizations are reviewed and consistent with the data and its accuracy	Hold until complete
Dissemination and confidentiality standards	The product meets the standards, including the disclosure risk of combining outputs	Reject
Sign-off	The designated approval authority has approved the product	Hold until approved

Coherence problems at the approval gate are never solved by adjusting a component estimate in VS-05. If a component is wrong, it goes back to VS-04 and returns as a new analytical version.

4. Data and metadata characteristics

Data. Statistics in #4 are mostly aggregated data: tables, data cubes, indicators, indices, and time series. They can also include weighted output microdata, prepared for a specific internal use. Permitted operations are weighting and calibration, estimation and aggregation, model-based analysis, seasonal adjustment, initial disclosure control, and, at the approval stage, composition of indicators, indices, and time series from analytical versions. Changing microdata values is not permitted at #4: corrections go back to #3. Final disclosure control for release is not part of #4 either; it belongs to the transition to #5. **[SS8]**

Minimum metadata set.

Metadata element	Description
Persistent identifier and version	Unique identifier of this version
Status	*Analytical* or *approved*
Source reference	The #3 versions (for analytical versions) or the analytical #4 versions (for approved versions) used
Methodology	Estimation, weighting, and model methods, with their versions and parameters
Weights and calibration totals	Calibration method, auxiliary variables, and the source and version of the totals
Accuracy	Standard error, coefficient of variation, or confidence interval per estimate; whether imputation uncertainty is included
Model diagnostics	Fit and prediction intervals for model-based results
Disclosure control	Method applied and outcome of the risk assessment
Coherence results	Outcome of the coherence checks against related and prior statistics
Composition record	For approved versions: composition method and the component versions used
Interpretive content	For approved versions: reference to commentary, key messages, and visualizations
Approval record	For approved versions: approval authority, date, and confidentiality clearance
Classification	Availability, integrity, and confidentiality rating

In GSIM terms, aggregated results in #4 typically instantiate a *Dimensional Data Set*, and weighted output microdata a *Unit Data Set*. Both conform to a *Data Structure* that SDMX can use for exchange.

5. Security, privacy, and access

Initial disclosure control is applied at the analytical gate, so the results could in principle be released. That does not make #4 public. It may still hold detailed cells, internal breakdowns, or output microdata that are only suitable for internal use. Different confidentiality thresholds can apply depending on the intended use, and the version records which threshold was applied.

Composition creates a specific risk. Two tables that are each safe on their own can together reveal a value through differencing. The approval gate therefore checks the disclosure risk of the product as a whole, not only of its components.

Approved products are usually market-sensitive or politically sensitive before their release. Access to approved versions is restricted to the people who need it to prepare the release. Every pre-release access is logged, so equal access at the moment of release can be demonstrated.

6. Ownership and governance

Role	Responsibility for #4
Data owner (analytical)	Process owner of Estimation; accountable for methodological soundness and accuracy
Data owner (approved)	Process owner of Product Composition; accountable for coherence and interpretability of the product
Approval authority	Signs off approved versions against dissemination and confidentiality standards
Data steward	Registers versions, maintains catalog entries, and resolves gate exceptions
Data custodian	Operates storage, access control, retention, and the pre-release access log
Methodologist	Owns estimation, weighting, and model methods

Role	Responsibility for #4
Disclosure control specialist	Owns the disclosure-control rules for internal and potential external use

7. Versioning, retention, and lineage

Every estimation run produces a new immutable analytical version. Every approval produces a new immutable approved version that refers to the analytical versions it was built from. Revisions follow the revision policy: a preliminary figure, a revised figure, and a final figure are three separate versions. Nothing is overwritten, because published figures and other statistics may depend on any of them.

Approved versions that were released are kept for as long as the released figures exist, because they are the direct basis of #5. Analytical versions that never led to a release can be kept for a shorter period, as long as revisions and reproducibility are covered. The exact periods are set by national law and NSI policy.

Lineage at #4 has two steps. An estimate traces back to the #3 version, the method, the parameters, and the weights that produced it. An approved product traces back to the analytical versions it was composed from, and through them to #3.

8. Reuse and handover

#4 has two handovers, one for each gate moment. The analytical version goes to VS-05 for composition; the approved version goes to VS-06 for release. Consumers access versions through the catalog and the handover interface, never through the estimation or composition working environment.

Statistics in #4 are also reused internally. Integration systems, such as the national accounts or labor accounts, use statistics from many domains as input. Under SAF-P08 they reuse the registered version instead of estimating the same figure again. This keeps internal use and later publication consistent.

Handover element	Analytical version (VS-04 → VS-05)	Approved version (VS-05 → VS-06)
Artifact	Registered analytical #4 version	Registered approved #4 version
Required metadata	Methodology, weights, accuracy, model diagnostics, disclosure control, coherence results	Composition record, propagated accuracy, coherence results, interpretive content, approval record
Trigger event	*Output Data Registered*	*Statistical Product Registered*
Responsibility transfer	VS-04 keeps custody; VS-05 takes responsibility for composition and approval	VS-05 keeps custody; VS-06 takes responsibility for final disclosure control, release, and user support

9. Traceability to the framework

Framework element	References
Capabilities	1.3.5 Estimating population parameters, 1.3.6 Integrate statistics, 1.3.7 Statistical disclosure, 1.4.1 Statistical (output) analysis, 2.1.2 Metadata management, 2.1.3 Statistical quality management
Value-stream stages	VS-04.1 to VS-04.5 (analytical gate); VS-05.1 to VS-05.5 (approval gate)

Framework element	References
SAF processes	PRD-5.6 Calculate weights, PRD-5.7 Calculate aggregates, PRD-6.1 Prepare draft outputs, PRD-6.2 Validate outputs, PRD-6.3 Interpret and explain outputs, PRD-6.4 Apply disclosure control (initial), PRD-6.5 Finalize outputs, PRD-7.2 Produce dissemination products (content), DLM-2, DLM-3, DLM-7 Revise data
GSBPM	5.6 Calculate weights, 5.7 Calculate aggregates, 6.1 to 6.5 Analyze
Principles	SAF-P07, SAF-P08, SAF-P09, SAF-P10, SAF-P11
Medallion layer	Gold, internal sub-layer; not yet released

10. Examples and anti-patterns

Examples

- *Survey.* The Labor Force Survey estimates an employment rate of 71.4%, with a 95% confidence interval of ±0.5 percentage points at national level. The variance includes the uncertainty of imputed income from #3. This analytical version is then composed with unemployment and vacancy figures into the quarterly labor market product, which is approved and registered.
- *Administrative register.* Turnover is aggregated by industry and region. For small domains where the direct aggregate is unstable, a small-area model is used, and its results are flagged as model-based. In the approval gate, one domain fails the coherence check; it goes back to VS-04 instead of being adjusted in the product.
- *Web data.* A multilateral price index is calculated from the item prices in #3. The headline index and its main divisions are composed with the period weights, checked for coherence with the prior month and year, and approved.

Anti-patterns

- Approving a product by overwriting the analytical version. The difference between the tested figure and the approved figure disappears.
- Adjusting a component estimate in VS-05 to make the coherence check pass. The estimate no longer matches its documented method.
- Publishing an estimate without an accuracy measure. Users cannot judge whether a movement is meaningful.
- Treating initial disclosure control as final. Release requires the final check of the transition to #5.
- Sharing approved figures before release without logging the access. Equal access can no longer be demonstrated.
- Re-estimating a figure for internal use instead of reusing the registered version. Internal and published figures start to differ.

State #5: Released Data

1. Definition and value added

Released data is statistical output that the NSI has made available outside its own organization. It is based on an approved #4 version that has passed final disclosure control, has been documented for correct interpretation, and has been released through a trusted channel. Released data includes published tables and datasets, open data, data available through an API, deliveries to international organizations, data offered in a data space, and de-identified microdata made available to accredited researchers. #5 is the last point at which the NSI controls the data. Once users have it, it becomes consumed data, outside the NSI's control.

The value of #5 is **accessibility and trust**. Users get accurate, documented statistics through channels they can rely on, at a moment that is the same for everyone. The final disclosure check ensures that no

respondent can be identified. The documentation ensures that users can interpret the figures correctly, including their accuracy and limitations.

#5 is mandatory whenever output is released. If nothing changes between the approved #4 version and the release, the same artifact can be marked as released instead of being registered again. The release steps still take place and are recorded: release authorization, the final disclosure check, and the release itself (see *Applying the steady states pragmatically*).

2. Producing and consuming domains

Role	Domain	Note
Producer	Dissemination (VS-06)	Functions: Data Delivery, Data Publication
Primary consumer	External users	Policy makers, researchers, media, businesses, and the public; use turns #5 into #6
Primary consumer	International organizations	Deliveries under agreed transmission programs, such as to Eurostat or the OECD
Primary consumer	Accredited researchers	Access to de-identified research datasets in a secure processing environment **[SS9]**
Secondary consumer	Customer and Stakeholder Engagement (VS-10)	Usage and feedback data for needs analysis and impact measurement
Assurance	Governance and Compliance (VS-07)	Audit of disclosure control, equal access, and release authorization

3. Quality gate

The gate for #5 is the release gate. Confidentiality is not negotiable at this boundary. Unlike the earlier gates, the disclosure criteria allow no conditional acceptance: a release that fails them is returned for further protection. **[SS10]**

Criterion	Check	Typical outcome on failure
Approved source	The release is based on an approved #4 version	Reject
Final disclosure control	Final protection applied and disclosure-risk criteria met for every table, dataset, and dashboard	Reject; apply further protection
De-identification	Released microdata meets the de-identification standard for its channel	Reject
Documentation	Methodology notes, metadata, and user guidance are complete	Hold until complete
Format and accessibility	Each channel format is valid, machine-readable where required, and meets the accessibility standard	Hold until corrected
Release authorization	The release has been signed off	Hold until authorized
Timing and equal access	Release time follows the release calendar; embargo arrangements are in place and logged	Hold until the release slot
Metadata	Minimum metadata set captured (see attribute 4)	Hold until complete

4. Data and metadata characteristics

Data. One released version can have several representations, one per channel: a published table, an SDMX dataset behind an API, a dashboard, or a research dataset. All representations come from the same released version, so a user always gets the same figure through every channel. Permitted operations are final disclosure control, de-identification of microdata, formatting per channel, packaging, and adding documentation. Changing the statistical content is not permitted at #5. A correction to a released figure goes back to #4 as a new approved version and is released again with an erratum. [**SS11**]

Minimum metadata set.

Metadata element	Description
Persistent identifier and version	Unique identifier of this release version
Source reference	The approved #4 version this release is based on
Final disclosure control	Method applied, risk assessment outcome, and sign-off
De-identification	For microdata: the standard applied and the project or channel it applies to
Channels and formats	Every channel used, with format and access conditions
Release timestamp	Moment of release and reference to the release calendar
Embargo record	Who had pre-release access, when, and under which agreement
Documentation	References to methodology notes, reference metadata, and user guidance
Accessibility	Accessibility standard met per channel
Terms of use	Licence or terms under which the data may be used
Correction history	Errata issued and the versions they replace
Classification	Availability, integrity, and confidentiality rating

In GSIM terms, #5 is the disseminated form of a *Data Set* together with its *Referential Metadata*. SDMX defines the structure in which it is exchanged with users and international organizations.

5. Security, privacy, and access

After final disclosure control, most released data is public and has a low confidentiality rating. Its integrity rating is high. Users must be able to trust that a figure on the website or in the API is exactly the figure the NSI released. Channels therefore protect released data against tampering, and the NSI can prove which version was released when.

Before the release moment, the same data is highly restricted. Embargoed copies go only to parties with a formal agreement, such as accredited media, and every pre-release access is logged. No user gets the data before the release time outside that policy.

Research microdata follows a different path. It is released only to accredited researchers and only inside a secure processing environment. Each project gets its own dataset with project-specific pseudonyms, so data cannot be linked across projects. Results leave the environment only after an output check.

6. Ownership and governance

Role	Responsibility for #5
Data owner	Process owner of Dissemination; accountable for confidentiality, equal access, and the quality of the release

Role	Responsibility for #5
Release manager	Controls release timing, embargo, and equal access across channels
Disclosure control specialist	Applies and signs off the final disclosure control
Dissemination and service manager	Manages channels, formats, service levels, and the research access service
Data steward	Registers release versions, maintains documentation, and handles errata
Data custodian	Operates channels, access control, integrity protection, and the embargo log

7. Versioning, retention, and lineage

Every release is an immutable version. A correction never silently replaces a released figure. It produces a new approved #4 version, a new release version, and a public erratum that explains what changed and why. Earlier releases remain identifiable, so users can see which figure was available at which moment.

Released statistics are usually kept permanently, as part of the public record. National archival legislation often prescribes this. Research datasets are the exception: they are disposed of when the research project closes, together with their project-specific pseudonymization keys. The approved code and outputs of the project are kept for reproducibility.

Lineage at #5 closes the chain. Each released figure traces back to its approved #4 version, and from there through the analytical versions, #3, and #2 to the authentic delivery in #1. This makes it possible to answer any question about a published figure, from source to release.

8. Reuse and handover

Release publishes the *Statistics Released* event and makes the data available through the agreed channels. #5 has no downstream production stream. Its handover is to users outside the NSI, where the data becomes consumed data (#6). Usage and feedback flow back to VS-06 and VS-10, and through them into the design of the whole chain.

Released data is the most widely reused form of NSI output. Under SAF-P08 it is offered as openly as confidentiality allows, in standard formats and with clear terms of use. Open, documented release reduces the number of individual data requests and lets users combine NSI data with other sources.

Handover element	Content
Artifact	Released data version, in its channel-specific representations
Required metadata	Minimum metadata set (attribute 4), including documentation, terms of use, and correction history
Trigger event	*Statistics Released*
Responsibility transfer	The NSI remains responsible for the correctness and documentation of the release and for issuing errata; users are responsible for how they use the data

9. Traceability to the framework

Framework element	References
Capabilities	1.3.7 Statistical disclosure, 1.5.1 Publication management, 1.5.2 Promotion to use, 1.5.3 Facilitate data access, 1.5.4 Statistical information management, 2.2.4 Data services, 3.4.1 Services management

Framework element	References
Value-stream stages	VS-06.1 Plan Dissemination and Access Strategy; VS-06.2 Prepare Data for Dissemination; VS-06.3 Publish and Provide Access Services; VS-06.4 Support and Engage Users; VS-06.5 Monitor Usage and Feedback
SAF processes	PRD-6.4 Apply disclosure control (final), PRD-7.1 to PRD-7.5 Disseminate, MDS-3 Prepare research datasets, MDS-4 Provide a secure processing environment, MDS-7 Check and release output, MDS-9 Close projects, DSP-2 Publish data offerings, DSP-4 Exchange data under usage control
GSBPM	6.4 Apply disclosure control, 7.1 to 7.5 Disseminate
Principles	SAF-P07, SAF-P08, SAF-P09, SAF-P10, SAF-P11
Medallion layer	Gold, published sub-layer

10. Examples and anti-patterns

Examples

- *Survey.* The quarterly labor market figures are released at 09:00 on the calendar date, at the same moment on the website, the API, and the dashboard. Two small regional cells are suppressed in the final disclosure check. Accredited media received an embargoed copy and publish at the same moment.
- *Administrative register.* Aggregated business statistics are published as open data. De-identified business microdata is released to accredited researchers inside a secure processing environment, with project-specific pseudonyms and output checking.
- *Web data.* The monthly price index is market-sensitive. It is released at a fixed minute with strict equal access, and the documentation explains the main contributions to the monthly change.

Anti-patterns

- Publishing directly from #4 without a recorded final disclosure check. There is no evidence that the release was safe.
- Correcting a published figure silently. Users who already used the old figure cannot see that it changed.
- Giving a ministry or partner early access outside the embargo policy. The NSI's independence and equal access are compromised.
- Releasing figures without methodology notes or accuracy. Users draw conclusions the data cannot support.
- Sending research microdata by email or file transfer to a researcher's own environment. Control over the data is lost.
- Releasing different figures through different channels. Users lose trust when the website and the API disagree.

Boundary Position #6: Consumed Data

Description: Consumed data is released data that users have taken into their own environment and use for their own purposes. Examples are a government departments using an unemployment rate in a policy note, a researcher combining released tables with other sources, a journalist quoting an inflation figure, or an application that pulls a series from the API every day. The NSI has no custody of consumed data and cannot control how it is used, combined, or presented. It can influence correct use only through the quality of its documentation, its terms of use, its user support, and its errata.

Why it is described: The SAF describes #6 so that the end of the NSI's responsibility is explicit, just as #0 marks where it begins. Everything the NSI can do for correct use has to be done at #5: documentation, accuracy measures, terms of use, and a clear correction history. What the NSI learns about consumed data

comes back as usage and feedback, through VS-06.5 and VS-10. That feedback closes the loop: it shapes new information needs and, through them, the next cycle of the value chain from #0 onward.