

VS-04.0 Estimation, Analysis, and Statistical Modeling – Business Layer

2026-06-11

Abstract This document operationalizes the **Estimation and closed-loop** business domain into the four governance process types : *Design, Implementation, Execution, and Management*. It describes how data transitions from **Steady State #3 (Processed Data)** to **Steady State #4 (Output Data / Statistics)** through a governed pipeline that produces metadata, execution processes, statistical data, and quality reports. This is the domain where the focus shifts from improving data to **extracting insight**: weighting and calibration, estimation and aggregation, and model-based analysis turn processed microdata into representative statistics – produced with full methodological transparency, reproducibility, and accuracy measures, and with initial confidentiality protection applied. The document is intended as a canvas for National Statistical Offices (NSOs) to instantiate for their own contexts.

Table of contents

1	Introduction and Strategic Context	2
1.1	Purpose and Scope	2
1.2	Position in the Statistical Value Chain	3
1.3	Steady State Transition	3
1.4	The Four-Process Governance Pattern	5
1.5	Governing Principles	5
1.6	Capability Foundations	7
1.7	Metadata Perspective	8
2	Business Roles and Actors	9
3	Design Processes – “provides metadata”	10
3.1	Design Estimation Strategy and Accuracy Approach	10
3.2	Design Weighting and Calibration Methodology	11
3.3	Design Aggregation and Model Specifications	12
3.4	Design Validation and Disclosure-Control Policy	12
3.5	Design Quality-Measurement and Versioning Framework	13
4	Implementation Processes – “provides the execution process”	14
4.1	Build Weighting and Calibration Engines	15
4.2	Build Estimation and Aggregation Pipelines	15

4.3	Build Modeling Environment, Validation, and SDC Tooling	16
4.4	Test and Validate the Pipeline	17
5	Execution Processes — “provides the statistical data”	18
5.1	Confirm Estimation and Analytical Approach	18
5.2	Apply Weighting and Calibration	19
5.3	Estimate and Aggregate Data	20
5.4	Perform Model-Based Analysis	21
5.5	Validate and Document Results	22
6	Management Processes — “provides quality reports”	23
6.1	Monitor Process Performance	24
6.2	Assess Output Quality	25
6.3	Manage Methodology and Output-Version Lifecycle	25
6.4	Audit and Compliance Reporting	26
6.5	Continuous Improvement	26
7	Business Services and Interfaces	29
7.1	Boundary Interface Specifications	29
8	Business Objects and Data Flow	31
9	Business Events	33
10	Applying This to Your NSO	33
10.1	Maturity Assessment Checklist	33
10.2	End-to-End Scenarios	34
10.2.1	Scenario A: Labour Force Survey (Design-Based Estimation)	34
10.2.2	Scenario B: Tax Register to Business Statistics (Register-Based + Small-Area Estimation)	34
10.2.3	Scenario C: Web-Scraped Price Data (Index Estimation)	35

1 Introduction and Strategic Context

1.1 Purpose and Scope

This document specifies the complete business layer for the **Estimation and closed-loop** business domain, corresponding to the *VS-04.0 Estimation, Analysis, and Statistical Modeling Value Stream*. It also covers 4 governance process types:

- **Design** — how the estimation, weighting, and analytical approach is specified and planned (produces metadata)
- **Implementation** — how the estimation and analysis pipeline is built, configured, and tested (produces the execution process)
- **Execution** — how data is operationally weighted, estimated, modeled, and validated (produces statistical data)
- **Management** — how the domain is monitored, quality-assessed, and improved (produces quality reports)

⚠ Out of Scope

Application and Technology layer specifications are out of scope for this document. Combining multiple analyses into integrated and composite statistical products is out of scope — it belongs to VS-05.0 Statistical Product Composition. Final disclosure control for publication and dissemination belongs to VS-06.0. VS-04 produces validated statistics with initial confidentiality protection; it does not compose products or publish them.

Terminology: the strategy layer models each **VS-0x.y** as a **value stream stage**; the business layer realizes each stage as a **business process**. The numbering maps one-to-one; this document uses the business-process view.

1.2 Position in the Statistical Value Chain

VS-04.0 is the fourth primary value stream — it receives Processed Data from VS-03.0 and applies statistical methods, estimation techniques, and analytical models to turn it into representative results that describe real-world phenomena. It is the “Estimate & Analyze Information” orchestration stage where data becomes statistical information.




Figure 1: Value Stream Context Map. VS-04.0 is highlighted as the estimation-and-analysis stage that turns processed microdata into representative statistics.

1.3 Steady State Transition

VS-04.0 transitions data from **Steady State #3 (Processed Data)** — edited, complete, enriched microdata — to **Steady State #4 (Output Data / Statistics)** — aggregated and analyzed statistics with estimates calculated, accuracy and quality indicators produced, lineage documented, internal

review completed, and initial confidentiality measures applied so the output can potentially be released.




Figure 2: Steady State Transition from Processed Data to Output Data through the estimation and analysis service at the domain boundary. State #4 is shared with VS-05.0 Statistical Product Composition.

💡 Output quality criteria (Examples)*

- Estimation/analytical approach selected and justified for the analytical objective
- Weighting and calibration applied to correct for sample bias, non-response, and coverage
- Estimates and aggregates calculated with accuracy measures (sampling error, confidence intervals)
- Model-based analyses conducted where applicable, with diagnostics documented
- Results validated for statistical soundness and coherence; methodology documented
- Initial statistical disclosure control applied so the output can potentially be released
- Full lineage from each statistic back to the processed source data and the method applied

! The methodological discipline — insight, transparently produced

VS-04 does not change microdata values; it **computes statistics from them**. The output is a new kind of object — estimates, weights, aggregates, model results. The guarantee here is **methodological transparency, reproducibility, and statistical soundness**: every estimate carries the methodology and parameters that produced it, an accuracy measure (sampling error, confidence interval, or model diagnostic), and lineage to its inputs, so that any published figure can be regenerated and defended. Fitness for purpose and coherence with related statistics are explicit acceptance criteria.

i Inherited from VS-03.0

VS-04 receives Processed Data **plus** the metadata VS-03 attached — edit lineage, derived-variable definitions, and **imputation flags**. The imputation flags matter here: estimation must reflect the additional uncertainty that imputed values introduce (e.g., via variance estimation that accounts for imputation), and the edit/derivation lineage is carried through so every estimate remains traceable to its original observed and imputed inputs.

1.4 The Four-Process Governance Pattern

The Statistical Architecture Framework defines that each business domain operates through four distinct process types. This is not a linear sequence but a governance cycle where each process type produces a distinct output that feeds the others:




Figure 3: The Four-Process Governance Pattern. Each process type produces a distinct artefact class. The cycle closes when Management findings feed back into Design improvements.

! Important

Key insight: Most organizations focus primarily on execution, expecting to get results faster. The Statistical Architecture Framework emphasizes that **design, implementation, and management** are equally essential — without them, execution is ad-hoc and ungoverned, eventually leading to loss of control. The governance cycle ensures continuous improvement.

1.5 Governing Principles

The following principles directly govern the VS-04.0 business domain:

Principle	Statement	Application to VS-04.0
SAF-P01	Actively participate in open source to maintain collective control over statistical processes	NSOs should contribute to open source communities for estimation, weighting, and modeling tooling (e.g., calibration and variance-estimation libraries), ensuring collective control over critical methodological capabili-

Principle	Statement	Application to VS-04.0
		ties rather than vendor dependence.
SAF-P07	Implement loosely coupled processes and systems	The estimation domain must be independent from upstream editing and downstream composition. Output Data (State #4) serves as a decoupling interface — downstream consumers access validated statistics without knowledge of the estimation internals.
SAF-P08	Data is shared property	Output statistics and output microdata, once validated, are available to all authorized consumers. Estimation should not be duplicated across products when the same validated output can serve multiple purposes.
SAF-P09	No data without metadata and classification	Every estimate carries metadata: the methodology and parameters applied, the weights used, accuracy measures (sampling error, confidence interval), the reference population, and a classification for derived statistics. This is what makes results transparent and reproducible.
SAF-P10	Security By Design	Access controls, integrity verification, and a tamper-evident record of methods and parameters are embedded in the estimation pipeline so that every published figure is attributable and reproducible, not added as an afterthought.

Principle	Statement	Application to VS-04.0
SAF-P11	Privacy By Design	Initial statistical disclosure control is applied to outputs at this stage, and the disclosure risk of estimates and any output microdata is assessed by design, so the result can potentially be released.

i Cross-cutting principle application

Several principles cut across all four process types. SAF-P09 (no data without metadata and classification) is the backbone of methodological transparency: Design defines the methodology and required output metadata, Execute captures the method, parameters, weights, and accuracy measures for every estimate, and Manage assesses output quality and coherence. SAF-P10 (Security By Design) governs the tamper-evident record of methods and the reproducibility of outputs across Execution (Sections 5.1–5.5). SAF-P11 (Privacy By Design) applies especially to validation and disclosure control (Section 5.5), where the output’s disclosure risk is assessed before handover. SAF-P07 (loosely coupled) governs both the State #3 intake interface from VS-03.0 and the State #4 handover interface to VS-05.0.

1.6 Capability Foundations

VS-04.0 draws on the following SAF capabilities:

Capability Group	Capabilities	Role in VS-04.0
1.1 Statistical design and build	1.1.2 Design statistics product, 1.1.3 Build statistics product	Design the estimation/weighting methodology and analytical models, and build the estimation pipeline
2.1 Data management	2.1.1 Data lifecycle management, 2.1.2 Metadata management, 2.1.3 Statistical quality management, 2.1.4 Statistical register management	Manage data, methodology metadata, and quality; assess accuracy and coherence; use registers for calibration totals
3.2 Computerization and automation	3.2.1 Application development, 3.2.2 Functional management	Build and maintain weighting, estimation, aggregation, and modeling engines

Capability Group	Capabilities	Role in VS-04.0
3.3 Security and Privacy	3.3.1 Privacy management, 3.3.2 Security planning	Apply statistical disclosure control and assess output disclosure risk
4.1 Governance	4.1.1 Strategy and governance, 4.1.2 Policy and planning, 4.1.4 Improve management, 4.1.5 Accountability	Govern the domain, steward estimation methodology, plan improvements, report on reproducibility and compliance

1.7 Metadata Perspective

It is considered that metadata is an essential product of the Design phase and a critical concern of every other phase. In this domain, metadata is what makes a published figure defensible: every estimate must carry the method, parameters, weights, and accuracy that produced it. The table below consolidates the metadata produced across all four process types, covering both data metadata (about the outputs) and process metadata or paradata (about how the process runs).

Process Type	Data Metadata Produced	Process Metadata (Paradata) Produced
Design	Estimation/weighting methodology, calibration totals & sources, aggregation specs, model specifications, validation & SDC policy	Design decisions log, methodology version, review and approval records
Implement	Engine configurations, weighting/estimation parameters, model parameters, variance-estimation settings, SDC parameters	Build log, test results, reproducibility-test outcomes, deployment approvals
Execute	Per-estimate methodology, weights, accuracy measures (sampling error, CI), model diagnostics, reference population, applied-SDC record	Operator identity, timing, software/version, parameter values, run identifiers
Manage	Accuracy & coherence assessments, revision analyses, lineage assessments, trend analyses	Accuracy dashboards, coherence reports, improvement decisions, audit findings

2 Business Roles and Actors

i Indicative, not prescriptive

The roles below are indicative, not a mandated organizational structure. The SAF deliberately leaves organization design to each NSO – assign these responsibilities to fit your own size, culture, and operating model.

Role	Process Orientation	Description
Upstream Data Provider (VS-03.0)	External (internal NSO)	Supplies Processed Data (State #3) with edit/imputation lineage to the estimation domain
Methodology Authority	External	Sets the estimation, weighting, and analytical methods the NSO conforms to (e.g., methodology unit, Eurostat guidance)
Estimation Methodologist	Design	Designs the estimation strategy, weighting/calibration methodology, and accuracy-measurement approach
Model Designer	Design	Specifies analytical and forecasting models, their inputs, assumptions, and diagnostics
Disclosure-Control Designer	Design	Designs the statistical disclosure control rules and disclosure-risk criteria for outputs
Data Engineer	Implementation	Builds and configures weighting, estimation, aggregation, and modeling engines and the pipeline
System Configurator	Implementation	Configures estimation services, calibration-total sources, and access controls
Test Manager	Implementation	Plans and executes testing of the estimation pipeline (technical, reproducibility, benchmark)
Process Owner	Management	Accountable for the end-to-end performance of the estimation and analysis domain
Compliance Officer	Management	Ensures reproducibility and disclosure-risk compliance, produces audit reports
Quality Manager	Management	Monitors accuracy/coherence KPIs, produces quality reports, and drives continuous improvement
Survey Statistician	Execution	Applies the designed weighting/calibration and computes estimates with accuracy measures

Role		Process Orienta- tion	Description
Analyst Modeler	/	Execution	Conducts model-based analysis, regression, and forecasting, and documents diagnostics
Subject-Mat- ter Reviewer		Execution	Reviews results for plausibility, coherence, and fitness for purpose, and signs off
Data Steward		Execution	Registers output datasets and versions, manages metadata entries, and applies access controls

3 Design Processes — “provides metadata”

Framework	Mapping
GSBPM	Phase 1 (Specify Needs), Phase 2 (Design: 2.1–2.5)
GAMSO	Production (design activities), Capability Management
CSDA	Data Governance, Metadata Management, Data Quality
SAF Capabili- ties	1.1.2 Design statistics product, 2.1.2 Metadata management, 2.1.3 Statistical quality management

The design phase produces the **metadata artefacts** that govern all subsequent phases — the estimation strategy, weighting/calibration methodology, aggregation and model specifications, and the validation and disclosure-control policy. Without well-designed methods, estimation becomes ad-hoc and indefensible, and management has no baseline to measure accuracy and coherence against.

3.1 Design Estimation Strategy and Accuracy Approach

The starting point is choosing how the statistics will be estimated. This sub-process selects the estimation strategy appropriate to the source and analytical objective — design-based estimation for sample surveys, register-based aggregation, or model-assisted/model-based estimation for small domains — and defines the **accuracy-measurement** approach: how sampling error and confidence intervals are computed, including how the uncertainty introduced by VS-03 imputation is reflected in variance estimation. The team defines the target parameters, reference populations, and domains of estimation, aligned with GSBPM 2.5 (Design processing and analysis).

Activity	Key Outputs	Framework Ref
Select estimation strategy per source and objective (design-based / register-based / model-based)	Estimation Strategy Docu- ment	GSBPM 2.5

Activity	Key Outputs	Framework Ref
Define target parameters, reference populations, and domains of estimation	Estimation Specification	GSBPM 2.5
Define accuracy-measurement approach (sampling error, CI), reflecting imputation uncertainty	Accuracy Measurement Plan	GSBPM 2.5
Define coherence criteria with related and prior statistics	Coherence Criteria	GAMSO QM

NSO Example – Labour Force Survey:

The LFS team designs a design-based estimation strategy for the employment rate, with calibration to population totals by age, sex, and region, and a variance estimator (e.g., a linearization or replication method) that accounts for the survey design and for income/non-response imputation flagged in VS-03. Target parameters and the domains of estimation (national and NUTS-2) are specified.

3.2 Design Weighting and Calibration Methodology

This sub-process designs how sample bias, non-response, and coverage errors are corrected through weighting. The team specifies the design weights, the non-response adjustment model, and the calibration method (e.g., calibration to known population totals from registers), including the auxiliary variables and calibration totals to be used and their authoritative sources. Bounds and acceptance constraints on weights are defined to prevent extreme weights, aligned with GSBPM 2.5.

Activity	Key Outputs	Framework Ref
Specify design weights and non-response adjustment	Weighting Specification	GSBPM 2.5
Specify calibration method, auxiliary variables, and calibration totals (with sources)	Calibration Specification	GSBPM 2.5
Define weight bounds and acceptance constraints	Weight Constraint Policy	GSBPM 2.5
Define the authoritative source and version for calibration totals	Calibration-Total Source Register	CSDA Reference Data

💡 NSO Example – Household Survey:

The household survey calibration is designed to population totals by age × sex × region drawn from the population register, with a generalized regression (GREG) calibration and weight bounds to cap the calibration factor, so that weighted demographic margins reproduce the register while extreme weights are avoided.

3.3 Design Aggregation and Model Specifications

This sub-process specifies what is computed. For aggregation, each output statistic is defined by its formula, the domains/breakdowns, and rounding/units conventions. For analysis, model-based methods (regression, time-series/forecasting, small-area models) are specified with their inputs, assumptions, and the diagnostics that must be produced and checked. Each output statistic is given its metadata and classification per SAF-P09, aligned with GSBPM 2.5.

Activity	Key Outputs	Framework Ref
Specify output aggregates: formulae, domains/break-downs, units, rounding	Aggregation Specification	GSBPM 2.5
Specify analytical/forecasting models: inputs, assumptions, diagnostics	Model Specification	GSBPM 2.5
Define metadata and classification for every output statistic	Output-Statistic Standard	SAF-P09
Define seasonal adjustment / time-series treatment where applicable	Time-Series Treatment Spec	GSBPM 2.5

3.4 Design Validation and Disclosure-Control Policy

This sub-process designs how results are validated and protected before handover. Validation criteria cover statistical soundness (plausibility, consistency, model diagnostics within bounds), coherence with related and prior statistics, and the revision policy. The **statistical disclosure control (SDC)** policy is designed — disclosure-risk criteria for tables and any output microdata, and the protection methods (suppression, rounding, perturbation) — so the output reaches a state where it can potentially be released, aligned with GSBPM 6 design and SAF-P11. Reproducibility is designed in: an output must be regenerable from the processed input plus the recorded methodology and parameters.

Activity	Key Outputs	Framework Ref
Define validation criteria: soundness, coherence, model diagnostics, revision policy	Validation Policy	GAMSO QM
Define disclosure-risk criteria and SDC protection methods	Disclosure-Control Policy	SAF-P11
Define output metadata and methodology-documentation requirements	Output Documentation Standard	SAF-P09
Design reproducibility: re-generate outputs from inputs + methodology + parameters	Reproducibility Design	SAF-P10

3.5 Design Quality-Measurement and Versioning Framework

The final design sub-process ensures accuracy is measured and outputs are traceable. It defines the quality indicators to be produced (sampling error, coefficient of variation, response/coverage rates, model fit), the **output-versioning** policy (how versions are identified, what triggers a revision, immutability and retention), the lineage requirements from each statistic back to its processed inputs and the method applied, and the role-based access controls for outputs in line with SAF-P10.

Activity	Key Outputs	Framework Ref
Define quality indicators (sampling error, CV, response/coverage, model fit)	Quality Indicator Set	GAMSO QM
Define output-versioning and revision policy	Versioning Policy	CSDA Traceability
Define lineage from each statistic to processed inputs and method	Lineage Specification	CSDA Traceability
Design role-based access control for outputs	Access Control Design	SAF-P10




Figure 4: Design Process Decomposition. The processed data model, methodology set, calibration totals, and framework standards flow into five design sub-processes, producing metadata artefacts that govern Implementation, Execution, and Management.

4 Implementation Processes – “provides the execution process”

Framework	Mapping
GSBPM	Phase 3 (Build: 3.1–3.7)
GAMSO	Capability Management
CSDA	Data Processing / Analysis (setup), Data Governance (configuration)
SAF Capabilities	1.1.3 Build statistics product, 3.2.1 Application development, 3.2.2 Functional management

The implementation phase takes the metadata artefacts from Design and **builds, configures, and tests** the production-ready estimation and analysis pipeline. Nothing runs operationally until this phase is complete.

4.1 Build Weighting and Calibration Engines

This sub-process turns the weighting and calibration designs into operational tools. The weighting engine is built or configured to compute design weights and non-response adjustments, and the calibration engine to calibrate to the designed totals using the specified auxiliary variables, enforcing the weight bounds. The calibration-total connections are configured to the authoritative register/reference sources with version pinning, so the totals used are recorded and reproducible. All weighting logic is version-controlled in line with SAF-P10, following GSBPM 3.1–3.2.

Activity	Key Outputs	Framework Ref
Build/configure the weighting engine (design weights, non-response adjustment)	Configured weighting engine	GSBPM 3.2
Build/configure the calibration engine with auxiliary variables and bounds	Configured calibration engine	GSBPM 3.2
Configure calibration-total connections (versioned register sources)	Calibration-total integration	CSDA Reference Data
Version-control all weighting/calibration logic	Versioned methodology repository	SAF-P10

NSO Example – Household Survey:

The team configures a GREG calibration engine that pulls age × sex × region totals from a pinned version of the population register, applies weight bounds, and records the calibration totals and convergence diagnostics with every run so the weighting is reproducible.

4.2 Build Estimation and Aggregation Pipelines

The designed estimation and aggregation specifications are implemented as automated services. The estimation engine computes the target parameters with the designed accuracy measures, and the **variance-estimation** component computes sampling errors and confidence intervals – accounting for the survey design and for imputation uncertainty using the VS-03 imputation flags. The aggregation pipeline computes the specified output aggregates across the designed domains with the rounding/units conventions. Every output is produced with its methodology, parameters, weights, and accuracy measure attached, following GSBPM 3.2.

Activity	Key Outputs	Framework Ref
Build the estimation engine for the designed target parameters	Estimation pipeline	GSBPM 3.2
Build the variance-estimation component (design + imputation uncertainty)	Variance/accuracy component	GSBPM 3.2
Build the aggregation pipeline (domains, units, rounding)	Aggregation pipeline	GSBPM 3.2
Attach methodology, weights, and accuracy measure to every output	Output metadata binding	SAF-P09

4.3 Build Modeling Environment, Validation, and SDC Tooling

This sub-process implements model-based analysis, validation, and disclosure control. The modeling environment is built/configured to run the specified analytical, forecasting, and small-area models with their diagnostics, and (where applicable) seasonal adjustment. Validation tooling implements the designed soundness and coherence checks, including comparison against prior periods and related statistics. The **SDC tooling** implements the designed disclosure-risk checks and protection methods (suppression, rounding, perturbation). The output-versioning store is built so each accepted output version is immutable, identified, reproducible from inputs plus methodology, and accompanied by its lineage. Event notifications are configured to alert downstream consumers (VS-05.0) when an output version is registered.

Activity	Key Outputs	Framework Ref
Build/configure the modeling environment (models, diagnostics, seasonal adjustment)	Modeling environment	GSBPM 3.2
Implement validation tooling (soundness, coherence, prior-period comparison)	Validation tooling	GSBPM 3.2
Implement SDC tooling (disclosure-risk checks, suppression/rounding/perturbation)	SDC tooling	SAF-P11
Build the output-versioning store (immutable, identified, reproducible)	Versioning store	CSDA Traceability

Activity	Key Outputs	Framework Ref
Configure “Output Data Registered” event for downstream consumers	Event publication	GSBPM 3.2

4.4 Test and Validate the Pipeline

Before the pipeline goes into production, it must be rigorously verified. Technical testing covers all individual components — weighting, calibration, estimation, variance, aggregation, modeling, validation, SDC, and versioning store (GSBPM 3.5). Integration testing validates the end-to-end flow from processed intake through weighting, estimation, modeling, validation, SDC, to versioned registration. A **reproducibility test** confirms an output can be regenerated identically from the processed input plus the recorded methodology and parameters; a **benchmark/back-series test** compares results against a known or prior-period benchmark; and accuracy measures are checked against expectations. The phase concludes with finalization of the production system and documentation of operational procedures (GSBPM 3.6–3.7).

Activity	Key Outputs	Framework Ref
Technical testing of all individual components	Unit test reports	GSBPM 3.5
Integration testing: end-to-end flow from processed intake to versioned registration	Integration test report	GSBPM 3.5
Reproducibility test (regenerate an output from inputs + methodology)	Reproducibility report	GSBPM 3.6
Benchmark / back-series test against known or prior results	Benchmark test report	GSBPM 3.6
Check accuracy measures and model diagnostics against expectations	Accuracy verification report	GSBPM 3.6
Finalize production system and document operational procedures	Operational Procedures Manual, Production-Ready Pipeline	GSBPM 3.7




Figure 5: Implementation Pipeline from design artefacts through build/configure/test to production-ready system.

5 Execution Processes — “provides the statistical data”

Framework	Mapping
GSBPM	Phase 5 (Process: 5.6 Calculate weights, 5.7 Calculate aggregates) + Phase 6 (Analyze: 6.1 Prepare draft outputs, 6.2 Validate outputs, 6.3 Interpret & explain, 6.4 Apply disclosure control, 6.5 Finalise outputs)
GAMSO	Production (execution)
CSDA	Data Analysis (execution)
SAF Capabilities	2.1.2 Metadata management, 2.1.3 Statistical quality management

The execution phase runs the **designed and implemented pipeline** operationally for each production cycle. This corresponds to the five VS-04 value stream stages. In a mature steady state, much of the work has been pre-designed (Section 3) and pre-built (Section 4) — execution focuses on running the cycle, computing weights/estimates/models, and capturing the methodology, parameters, and accuracy measures so that every output is reproducible and defensible.

5.1 Confirm Estimation and Analytical Approach

Value created: *The right, pre-approved method selected for this cycle’s data and objective.*

When a “Processed Data Registered” event is received from VS-03.0, execution begins by confirming the estimation and analytical approach for the cycle. In a mature steady state the methodology has been designed (Section 3), so per-cycle execution confirms or selects the pre-approved approach for the data at hand, verifies that the calibration totals and reference sources are current, and confirms that the target parameters and domains apply. Significant changes (a new domain, a methodology revision) trigger a return to the design process rather than ad-hoc adaptation. This applies GSBPM 2.5/5.6 in their recurrent form.

Activity	Key Outputs	Framework Ref
Confirm or select the pre-approved estimation/analytical approach for the cycle	Confirmed approach for cycle	GSBPM 2.5
Verify calibration totals and reference sources are current	Reference-source confirmation	CSDA Reference Data
Confirm target parameters and domains of estimation	Confirmed estimation scope	GSBPM 5.6
Flag methodology changes for design review	Methodology-change exception (if any)	GAMSO QM

NSO Example — Labour Force Survey:

For cycle Q3-2026 the LFS team confirms the design-based estimation strategy and the calibration totals (latest population-register extract by age × sex × region), and confirms the domains (national and NUTS-2). No methodology change is needed, so the cycle proceeds without a return to design.

5.2 Apply Weighting and Calibration

Value created: *Bias from sampling, non-response, and coverage corrected so results represent the population.*

This sub-process computes the weights, aligned with GSBPM 5.6 (Calculate weights). The weighting engine applies the design weights and non-response adjustment, and the calibration engine calibrates to the confirmed population totals using the designed auxiliary variables, enforcing the weight bounds. Calibration convergence and the resulting weight distribution are checked against the designed constraints, and the calibration totals, auxiliary variables, and convergence diagnostics are recorded so the weighting is reproducible.

Activity	Key Outputs	Framework Ref
Compute design weights and non-response adjustment	Adjusted weights	GSBPM 5.6
Calibrate to confirmed population totals with designed auxiliary variables	Calibrated weights	GSBPM 5.6
Check convergence and weight distribution against bounds	Weight diagnostics	GSBPM 5.6

Activity	Key Outputs	Framework Ref
Record calibration totals, auxiliaries, and diagnostics as lineage	Weighting lineage	SAF-P09

NSO Example – Household Survey:

The GREG calibration converges in 6 iterations; weighted margins reproduce the register totals by age × sex × region, the calibration factor stays within the designed bounds, and the totals and diagnostics are stored with the run.

5.3 Estimate and Aggregate Data

Value created: *Representative statistics and aggregates, each carrying its accuracy.*

This sub-process computes the target estimates and aggregates, aligned with GSBPM 5.7 (Calculate aggregates) and 6.1 (Prepare draft outputs). The estimation engine computes the target parameters using the calibrated weights, and the aggregation pipeline computes the specified aggregates across the designed domains with the units/rounding conventions. The variance-estimation component computes sampling errors and confidence intervals, reflecting both the survey design and the imputation uncertainty signaled by the VS-03 imputation flags. Every estimate is produced with its methodology, weights, and accuracy measure attached.

Activity	Key Outputs	Framework Ref
Compute target estimates using calibrated weights	Point estimates	GSBPM 5.7
Compute aggregates across designed domains (units, rounding)	Output aggregates	GSBPM 5.7
Compute sampling errors and CIs (design + imputation uncertainty)	Accuracy measures	GSBPM 6.1
Attach methodology, weights, and accuracy to every estimate	Estimate metadata	SAF-P09




Figure 6: Estimation and Aggregation Architecture. Calibrated weights and imputation-flagged microdata feed point estimation and aggregation; variance estimation reflects both the survey design and the imputation uncertainty, and every output carries its accuracy and methodology.

🔍 NSO Example – Labour Force Survey:

The Q3-2026 employment rate is estimated at 71.4% with a 95% CI of ± 0.5 pp at national level and wider intervals at NUTS-2; the variance estimate is inflated appropriately for the income/non-response imputation flagged in VS-03. Each published cell carries its estimate, CV, and the method that produced it.

5.4 Perform Model-Based Analysis

Value created: *Deeper insight — relationships, trends, and small-domain estimates the direct counts cannot give.*

This sub-process conducts the designed model-based analyses, aligned with GSBPM 6.1/6.3. Analytical, regression, time-series/forecasting, and small-area models specified in design are run on the data, their diagnostics computed and checked against the designed bounds, and seasonal adjustment applied where applicable. Results are interpreted in context, with assumptions and limitations documented. As with direct estimates, every model output carries its specification, parameters, diagnostics, and uncertainty so it is reproducible and defensible.

Activity	Key Outputs	Framework Ref
Run the designed analytical/ forecasting/small-area models	Model outputs	GSBPM 6.1
Compute and check model diagnostics against designed bounds	Model diagnostics	GSBPM 6.2
Apply seasonal adjustment / time-series treatment where applicable	Adjusted series	GSBPM 6.1

Activity	Key Outputs	Framework Ref
Interpret results; document assumptions and limitations	Analytical commentary	GSBPM 6.3

NSO Example – Tax Register to Business Statistics:

For small NACE × region domains where the direct register aggregate is unstable, a small-area model borrows strength across domains to produce more reliable estimates; model diagnostics (fit, prediction intervals) are recorded, and the model-based cells are flagged distinctly from direct aggregates.

5.5 Validate and Document Results

Value created: *Statistically sound, coherent, documented, and disclosure-safe statistics ready for handover.*

The final execution sub-process validates the results and produces the official output version, aligned with GSBPM 6.2 (Validate outputs), 6.4 (Apply disclosure control), and 6.5 (Finalise outputs). Results are checked for statistical soundness and consistency, and for coherence with prior periods and related statistics; significant movements are explained, and revisions handled per policy. **Initial statistical disclosure control** is applied per the designed policy – disclosure risk assessed and protection methods (suppression, rounding, perturbation) applied – so the output can potentially be released. The methodology and quality indicators are documented, a persistent immutable output version is created with a unique identifier and full lineage, registered per SAF-P09, and access permissions applied per SAF-P10. The sub-process concludes by publishing an “Output Data Registered” event, notifying downstream VS-05.0 that new validated statistics are available for composition.

Output: Output Data / Statistics (Steady State #4) – the official handover artefact to the rest of the statistical value chain.

Activity	Key Outputs	Framework Ref
Validate soundness and coherence; explain movements; handle revisions	Validation Report	GSBPM 6.2
Apply initial statistical disclosure control per designed policy	Disclosure-controlled outputs	GSBPM 6.4
Document methodology and quality indicators	Methodology & Quality Documentation	SAF-P09

Activity	Key Outputs	Framework Ref
Create an immutable, identified output version with full lineage	Versioned Output Data	CSDA Traceability
Register metadata and publish “Output Data Registered” event to notify VS-05.0	Catalog registration, event	SAF-P07




Figure 7: Output Data Artefact Structure. Each output version contains estimates with accuracy measures, is linked to the methodology that produced it and the applied disclosure control, and is traceable to the processed source data.

6 Management Processes — “provides quality reports”

Framework	Mapping
GSBPM	Overarching processes (Quality Management, Metadata Management)
GAMSO	Corporate Support (Quality Management, Data Management, Metadata Management), Capability Management (improvement)
CSDA	Data Quality, Data Governance, Traceability
SAF Capabilities	2.1.3 Statistical quality management, 4.1.4 Improve management, 4.1.5 Accountability

The management phase runs **alongside and after** execution. It monitors the estimation domain's performance, assesses the accuracy and coherence of outputs, ensures every result is reproducible and disclosure-safe, and feeds improvement recommendations back into the design phase — closing the governance cycle.

6.1 Monitor Process Performance

Operational performance of the estimation domain must be tracked systematically across production cycles. The process owner and quality manager collect and aggregate key performance indicators, monitor throughput against the release calendar, and track paradata — which methods and parameter/software versions were run, when, by whom, and how many manual interventions occurred. This information feeds process performance dashboards that give the process owner a real-time view of domain health, aligned with the GAMSO Quality Management capability.

Key Performance Indicators (KPIs):

KPI	Description	Measurement
On-time output rate	Outputs produced within the release-calendar window	Per output, per cycle
Average sampling error / CV	Typical accuracy of key estimates	Per statistic, per cycle
Coherence-check pass rate	Outputs passing coherence checks on first run	Per cycle
Revision magnitude	Size of revisions vs. previously published figures	Per statistic, per cycle
Reproducibility rate	Outputs regenerable identically from inputs + methodology	Per cycle
Processing time	Duration from processed intake to versioned registration	Per output, per cycle

Activity	Key Outputs	Framework Ref
Collect and aggregate KPIs per production cycle	Process Performance Dashboard	GAMSO QM
Monitor throughput against the release calendar	Throughput Report	GAMSO QM
Track paradata: methods, parameter/software versions, interventions	Paradata Records	GAMSO QM

Activity	Key Outputs	Framework Ref
Generate process performance dashboards	Dashboard for Process Owner	GAMSO QM

6.2 Assess Output Quality

Beyond process performance, the quality of the outputs themselves must be evaluated against the criteria established in design. Each output is assessed across multiple quality dimensions: accuracy (sampling error, CV, model fit), coherence (consistency with related and prior statistics), timeliness (against the release calendar), and reliability (revision analysis comparing preliminary and final figures). Results are compared against the designed quality criteria from Section 3.5. Quality indicators are produced per statistic, per output, and per cycle, and trends are tracked to detect deteriorating accuracy, growing revisions, or models that need recalibration. This aligns with the CSDA Data Quality capability and SAF Capability 2.1.3.

Activity	Key Outputs	Framework Ref
Evaluate accuracy (sampling error, CV, model fit)	Accuracy Report (per cycle)	SAF 2.1.3
Assess coherence with related and prior statistics	Coherence Report	CSDA Data Quality
Conduct revision analysis (preliminary vs. final)	Revision Analysis	SAF 2.1.3
Identify quality trends across statistics and cycles	Quality Trend Analysis	SAF 2.1.3

6.3 Manage Methodology and Output-Version Lifecycle

The estimation methodology and the output versions it produces must remain current, complete, and well-governed. This sub-process governs the lifecycle of estimation methods, weighting/calibration specifications, and models — versioning them, managing transitions (e.g., a methodology change with back-series implications), and retiring obsolete methods. It verifies metadata completeness — that every output carries full methodology, weights, accuracy measures, and lineage as an SAF-P09 compliance check — and governs the output-version store: retention, immutability, and reconciliation that catalog entries match stored versions. Metadata lineage from processed through estimation to output state is tracked.

Activity	Key Outputs	Framework Ref
Govern estimation-method, weighting, and model lifecycle and versions	Methodology Version Register	SAF-P09

Activity	Key Outputs	Framework Ref
Verify metadata completeness (methodology, weights, accuracy, lineage)	Metadata Quality Report	SAF-P09
Govern the output-version store: retention, immutability, reconciliation	Version Store Audit	CSDA Traceability
Track metadata lineage from processed to output state	Metadata Lineage Audit	CSDA Traceability

6.4 Audit and Compliance Reporting

This sub-process produces the evidence that the estimation domain operates within methodological, legal, and organizational requirements. Reproducibility-audit reports demonstrate that every published figure can be regenerated from the processed input plus the recorded methodology and parameters – supporting methodological transparency and accountability. Disclosure-control reporting confirms that SDC was applied and that outputs meet the disclosure-risk criteria per SAF-P11. Methodology compliance reporting confirms that approved estimation and analytical methods were applied, and security compliance reporting verifies that designed access controls and the tamper-evident methodology record have been applied. These reports satisfy the SAF Capability 4.1.5 (Accountability) obligation and feed into VS-07.0 Governance and Compliance.

Activity	Key Outputs	Framework Ref
Produce reproducibility-audit reports: every figure regenerable	Reproducibility Audit Summary	SAF 4.1.5
Report on disclosure control applied and disclosure-risk outcomes	Disclosure-Control Report	SAF-P11
Report on methodology compliance (approved methods applied)	Methodology Compliance Report	SAF 4.1.5
Report on security compliance: access controls, methodology-record integrity	Compliance Report (per cycle)	SAF-P10

6.5 Continuous Improvement

The final management sub-process closes the governance loop by analyzing performance and quality data to identify and drive improvements. Quality trends across production cycles are examined: are sampling errors falling, are revisions shrinking, is coherence improving, are models

holding up? Improvement opportunities are identified — refining the calibration specification to reduce variance, recalibrating or replacing models, improving non-response adjustment, adopting better variance estimators, and tuning the release process to improve timeliness. These improvement recommendations are fed back to the design processes (Section 3), prioritized based on impact and feasibility, and tracked through subsequent design-implement-execute cycles. This is the SAF Capability 4.1.4 (Improve management) in action, and it connects to the GAMS0 concept of transferring mature capabilities from innovation into production.

Activity	Key Outputs	Framework Ref
Analyze quality trends across production cycles	Improvement Recommendations Report	SAF 4.1.4
Identify improvement opportunities: calibration, models, variance estimators, timeliness	Updated Design Inputs	SAF 4.1.4
Feed recommendations back to design processes (Section 3)	Design feedback (closing the governance loop)	SAF 4.1.4
Prioritize improvements based on impact and feasibility	Improvement Tracking Log	GAMS0 Capability Mgmt
Track implementation of accepted improvements	Improvement Tracking Log	GAMS0 Capability Mgmt




Figure 8: Management Feedback Loop. Execution data flows through monitoring, quality assessment, methodology version management, and audit processes. Continuous improvement feeds recommendations back to Design, closing the governance cycle.

7 Business Services and Interfaces

The VS-04.0 business domain exposes the following services:

Service	Direction	Consumers	Mapped Processes
Weighting and Calibration Service	Internal (VS-03.0 → NSO)	Processed data consumers, estimation teams	5.2 Apply Weighting and Calibration
Estimation and Aggregation Service	Internal	Estimation teams, analysts	5.3 Estimate and Aggregate Data
Modeling and Analysis Service	Internal	Analysts, methodologists	5.4 Perform Model-Based Analysis
Validation and Disclosure-Control Service	Internal	Quality managers, disclosure-control officers	5.5 Validate and Document Results
Output-Data Provisioning Service	Internal (NSO → VS-05.0)	Product composition teams, data analysts	5.5 Validate and Document Results
Output-Version Catalog Service	Internal	All data consumers across the NSO	6.3 Manage Methodology & Version Life-cycle
Design and Methodology Service	Internal	Methodologists, estimation/model designers	3.1–3.5 All design processes

Interface specifications:

- **Output-Data Provisioning Service** interface: event-driven notification (“Output Data Registered”) + catalog query API for downstream consumers to discover and access output versions, their accuracy measures, and methodology
- **Estimation and Aggregation Service** interface: estimation API returning estimates with accuracy measures, and a methodology/parameters query API
- **Output-Version Catalog Service** interface: search/browse API for output versions, accuracy measures, methodology documentation, and lineage

7.1 Boundary Interface Specifications

The domain is loosely coupled (SAF-P07) to its neighbors through two steady-state interfaces. Specifying each boundary explicitly — the handover artefact, the metadata it must carry, the event that triggers it, and where responsibility transfers — makes the loose-coupling contract concrete and testable.

Boundary		Handover fact	Arte- fact	Required data	Meta- data	Trigger Event	Responsibility Transfer
VS-03.0 VS-04.0 (intake)	→	Processed (State #3)	Data	Edit lineage, de- rived-variable definitions, im- putation flags and meth- ods , quality-im- provement as- sessment, qual- ity-version iden- tifier, BIV classi- fication		“Processed Data Registered” event	VS-03.0 retains custody of the processed ver- sion; VS-04.0 assumes re- sponsibility for weighting, esti- mation, model- ing, and valida- tion on event re- ceipt
VS-04.0 VS-05.0 (han- dover)	→	Output Data / Statistics (State #4)	Data	Methodology and parameters, weights, accu- racy measures (sampling error, CI), model diag- nostics, applied- SDC record, quality indica- tors, output- version iden- tifier, lineage to processed source, BIV clas- sification		“Output Data Registered” event	VS-04.0 retains custody of the output version; VS-05.0 assumes responsibility for composing integrated and composite prod- ucts on event re- ceipt

Each interface exchanges a registered, immutable steady-state artefact plus its metadata — never internal working data — so neither side needs knowledge of the other’s internal processing.

8 Business Objects and Data Flow




Figure 9: Business Object Lifecycle across all four process types. Design objects govern implementation, which produces the pipeline that estimates and analyses execution objects, which are assessed by management objects, which feed back to design.

9 Business Events



Syntax error in text

mermaid version 11.12.0

Figure 10: Event-Driven Choreography between the upstream domain (VS-03.0) and NSO teams, showing events across the Design → Implement → Execute → Manage cycle. The management phase closes the loop by feeding improvements back to design.

10 Applying This to Your NSO

10.1 Maturity Assessment Checklist

Use this checklist to assess your NSO's maturity across all four process types — not just execution.

Design Maturity

- ☐ Do we have a documented estimation strategy and accuracy-measurement approach per output?
- ☐ Do we have a formal weighting/calibration methodology with defined auxiliary variables and totals?
- ☐ Do we have documented aggregation and model specifications with required diagnostics?
- ☐ Do we have a validation policy and a statistical disclosure control policy defined before estimation begins?
- ☐ Do we have a quality-measurement and output-versioning policy?

Implementation Maturity

- ☐ Are our weighting/estimation engines built from design specifications (not ad-hoc scripts)?
- ☐ Does variance estimation reflect both the survey design and imputation uncertainty?
- ☐ Can an output be reproduced identically from the processed input plus the recorded methodology?
- ☐ Is disclosure-control tooling implemented and applied before handover?
- ☐ Do we have a formal testing process (technical, reproducibility, benchmark, accuracy)?

Execution Maturity

- ☐ Do we confirm the pre-approved approach and current calibration totals each cycle?
- ☐ Do we attach methodology, weights, and an accuracy measure to every estimate?
- ☐ Do we document model assumptions, diagnostics, and limitations?
- ☐ Do we validate soundness and coherence and explain movements/revisions?
- ☐ Do we apply disclosure control and register every output as an immutable version?

Management Maturity

- ☐ Do we track KPIs (accuracy/CV, revisions, reproducibility, timeliness) across cycles?
- ☐ Do we assess coherence and conduct revision analysis?
- ☐ Do we govern methodology/model versions and the output-version store?
- ☐ Do we produce reproducibility-audit, disclosure-control, and methodology-compliance reports?
- ☐ Do we have a formal improvement process that feeds back into design?

10.2 End-to-End Scenarios

Each scenario walks through **all four process types**, demonstrating how the governance pattern works in practice.

10.2.1 Scenario A: Labour Force Survey (Design-Based Estimation)

Design Phase: Estimation methodologists design a design-based strategy for the employment rate, calibrated to population totals by age $\times$ sex $\times$ region, with a variance estimator that accounts for the survey design and for the income/non-response imputation flagged in VS-03. Target parameters, domains (national and NUTS-2), coherence criteria with prior quarters, and the disclosure-control policy for small cells are specified.

Implementation Phase: Engineers configure the GREG calibration engine (pinned register totals), the estimation engine, and a replication-based variance component that inflates variance for imputed values; they implement coherence checks against prior quarters and small-cell suppression. Reproducibility and back-series tests pass; accuracy measures match expectations on test data.

Execution Phase: For Q3-2026, a Processed Data Registered event arrives. The approach and calibration totals are confirmed; calibration converges and weighted margins reproduce the register. The employment rate is estimated at 71.4% (95% CI ± 0.5 pp national, wider at NUTS-2), with variance inflated for imputation. Coherence checks against Q2 pass; small NUTS-2 cells are suppressed by SDC. An output version is created with methodology, weights, and accuracy, and registered; VS-05.0 is notified.

Management Phase: Average CV for key estimates is stable, the coherence-check pass rate is 100%, and the preliminary-vs-final revision is within tolerance. Reproducibility audit confirms the figures regenerate from inputs + methodology. Improvement recommendations: add an auxiliary variable to the calibration to reduce variance for youth-employment estimates. Recommendations fed back to design.

10.2.2 Scenario B: Tax Register to Business Statistics (Register-Based + Small-Area Estimation)

Design Phase: The team designs register-based aggregation of turnover and employment by NACE $\times$ region, and a small-area model for domains where direct aggregates are unstable. Accuracy measures, coherence criteria with national accounts inputs, and disclosure control for dominant-unit cells are specified.

Implementation Phase: Engineers build the aggregation pipeline (designed domains, units, rounding), the small-area model with its diagnostics, and dominance-rule suppression for confi-

dentiality. Reproducibility and benchmark tests against the prior year pass; the small-area model's prediction intervals are verified.

Execution Phase: Q3-2026: a Processed Data Registered event arrives for the integrated business dataset. Aggregates are computed by NACE × region; unstable small domains are estimated with the small-area model and flagged distinctly from direct aggregates. Dominant-unit cells are suppressed by SDC. Coherence with national-accounts inputs is checked. [0D-BUS-2026Q3-001](#) is created with methodology and accuracy, linked to [PD-BUS-2026Q3-001](#), and VS-05.0 is notified.

Management Phase: Coherence with national accounts is within tolerance; revision analysis shows stable estimates; the small-area model fit is monitored across cycles. Disclosure-control report confirms no dominant-unit disclosure. Improvement recommendation: recalibrate the small-area model after two more cycles of data. Recommendations fed back to design.

10.2.3 Scenario C: Web-Scraped Price Data (Index Estimation)

Design Phase: The team designs the price-index estimation (e.g., a GEKS or Törnqvist multilateral index) over the COICOP items coded in VS-03, with quality-adjustment treatment, an approach for new/disappearing products, and coherence criteria against the official CPI. The disclosure policy is light (aggregated indices), and the accuracy approach for the index is specified.

Implementation Phase: Engineers build the index estimator, the new/disappearing-product handling, and seasonal/quality adjustment, plus coherence checks against the official CPI. Reproducibility and back-series tests pass; the index is benchmarked against the official series on historical data.

Execution Phase: For the monthly run, a Processed Data Registered event arrives. The multilateral index is computed over COICOP items using the carry-forward-imputed daily prices flagged in VS-03 (their uncertainty noted), new products are chained in, and the index is validated for coherence against the official CPI movement. An output version with methodology and accuracy is created and registered; VS-05.0 is notified.

Management Phase: The scraped index tracks the official CPI within the agreed tolerance; revision magnitude is small. Reproducibility audit passes. Improvement recommendations: refine the new-product chaining rule for one volatile category, and evaluate a longer multilateral window. Recommendations fed back to design.