IC1

ICP-10111 Barometric Pressure Sensor Module

v1.0

2025-09-25
Rev. A

Professional electronic component

PRODUCT OVERVIEW

The UNIT ICP-10111 Barometric Pressure Sensor Module is a compact and efficient sensor designed for high-accuracy atmospheric pressure measurements with low power consumption. Based on MEMS capacitive technology, this module offers ultra-low noise performance, exceptional relative accuracy, and stable sensor throughput. Ideal for weather monitoring, altitude measurement, and environmental sensing, it delivers industry-leading precision in demanding applications.

PRODUCT VIEWS

TOP VIEW



Component placement and connectors

BOTTOM VIEW



Underside components and connections

KEY TECHNICAL SPECIFICATIONS

🔌 CONNECTIVITY

Primary Interface:	**I²C (up to 400 kHz, address 0x63)**
Connector Type:	**Qwiic + Pin Headers**
Logic Levels:	**VCC-referenced (1.8V – 5.5V tolerant)**

🔧 MECHANICAL

Board Dimensions:	**20.32 mm × 17.78 mm**
Mounting Holes:	**4 × Ø 2.2 mm**
Weight:	**~2.5 g**
Package Type:	**Compact breakout board**

PIN CONFIGURATION

VOLTAGE LEVEL	FUNCTION
`3.3 V – 5.5 V`	Provides power to the on-board regulator and sensor core.
`0 V`	Common reference for power and signals.
`1.8 V to VCC`	Serial data line for I²C communications.
`1.8 V to VCC`	Serial clock line for I²C communications.

KEY FEATURES

❓ feature not specified

No specific features found

🎯 Key Applications

Weather Stations & Barographs, Altimeters & UAVs, Indoor/Outdoor Navigation and more

TYPICAL APPLICATIONS

Weather Stations & Barographs	Altimeters & UAVs	Indoor/Outdoor Navigation
Wearables & IoT	Climatology & Research	Weather Forecasting

ADDITIONAL TECHNICAL INFORMATION

📦 OVERVIEW

FEATURE	SPECIFICATION
Pressure operating range	30 to 110 kPa
Noise and current consumption	ULN mode: 0.4 Pa @ 10.4 µALN mode: 0.8 Pa @ 5.2 µALP mode: 3.2 Pa @ 1.3 µA
Pressure Sensor Relative Accuracy	±1 Pa for any 10 hPa change over 950 hPa–1050 hPa at 25°C
Pressure Sensor Absolute Accuracy	±1 hPa over 950 hPa–1050 hPa, 0°C to 65°C

FEATURE	SPECIFICATION
Pressure Sensor Temperature Coefficient Offset	±0.5 Pa/°C over 25°C to 45°C at 100 kPa
Temperature Sensor Absolute Accuracy	±0.4°C
Temperature operating range	-40 °C to 85 °C
Host Interface	I2C at up to 400 kHz
Single Supply voltage	1.8V ±5%
RoHS and Green compliant	Yes

HARDWARE DOCUMENTATION

MECHANICAL DIMENSIONS



Physical dimensions and mounting specifications (measurements in millimeters)

SYSTEM TOPOLOGY



Connection topology and system integration diagram

Click image to open in full size

COMPONENT REFERENCE

REF.	DESCRIPTION
IC1	ICP-10111 Barometric Pressure Sensor
L1	Power On LED
U1	ME6206A18XG 1.8V Regulator
JP1	2.54 mm Castellated Holes
J1	QWIIC Connector (JST 1 mm pitch) for I2C

REF.	DESCRIPTION
IC1	ICP-10111 Barometric Pressure Sensor
L1	Power On LED
U1	ME6206A18XG 1.8V Regulator
JP1	2.54 mm Castellated Holes
J1	QWIIC Connector (JST 1 mm pitch) for I2C

CIRCUIT SCHEMATIC



Complete circuit schematic showing all component connections

View Complete Schematic PDF

PIN DESCRIPTION

Detailed pin assignment and electrical specifications

SIGNAL DESCRIPTION

FUNCTION	NOTES
Power Supply	3.3V or 5V
Ground	Common ground for all components

VOLTAGE LEVEL	FUNCTION
3.3 V – 5.5 V	Provides power to the on-board regulator and sensor core.
0 V	Common reference for power and signals.
1.8 V to VCC	Serial data line for I²C communications.
1.8 V to VCC	Serial clock line for I²C communications.

FUNCTION	NOTES
Power Supply	3.3V or 5V
Ground	Common ground for all components

VOLTAGE LEVEL	FUNCTION
3.3 V – 5.5 V	Provides power to the on-board regulator and sensor core.
0 V	Common reference for power and signals.
1.8 V to VCC	Serial data line for I²C communications.
1.8 V to VCC	Serial clock line for I²C communications.

PIN CONFIGURATION LAYOUT

Physical connector layout and pin positioning

PINOUT

Top view



Bottom view



Description:

- Supply voltage
- GND
- I2C
- QWIIC

Complete pin configuration diagram showing all connectors, pin assignments, and electrical connections for proper integration

© 2025 UNIT Electronics México
Technical document automatically generated