UDSG — GYUMRI / Shirak

UDSG AD 2.1 Aerodrome location indicator and name

UDSG — GYUMRI / Shirak

UDSG AD 2.2 Aerodrome geographical and administrative data

1	*ARP coordinates and site at AD*	404502N 0435134E at the center of the RWY
2	*Direction and distance from (city)*	5 KM south east from city Gyumri
3	*Elevation/Reference temperature*	5000 FT 20.2°C
4	*Geoid undulation at AD ELEV PSN*	-79 FT
5	*MAG VAR/Annual change*	7° E 2025/0.06°
6	*AD Administration, address, telephone, telefax, telex, AFS*	Post: AIA “Shirak” Airport Republic of Armenia Tel:+374312 41300 Fax:+374312 40958 AFS:UDSGYDYD
7	*Types of traffic permitted (IFR/VFR)*	IFR/VFR
8	*Remarks*	Nil

UDSG AD 2.3 Operational hours

1	*AD Administration*	*MON-FRI:0500-1400*
2	*Customs and immigration*	*0600-1800*
3	*Health and sanitation*	*0600-1800*
4	*AIS Briefing Office*	*0600-1800*
5	*ATS Reporting Office (ARO)*	*0600-1800*
6	*MET Briefing Office*	*0600-1800*
7	*ATS*	*0600-1800*
8	*Fuelling*	*0600-1800*
9	*Handling*	*0600-1800*
10	*Security*	*0600-1800*
11	*De-icing*	*0600-1800*
12	*Remarks*	Local time = UTC + 4 hours

UDSG AD 2.4 Handling services and facilities

1	*Cargo-handling facilities*	No Cargo Handling facilities.
2	*Fuel/oil types*	Jet A-1
3	*Fuelling facilities/capacity*	1 truck 22000 liters 700L/MIN
4	*De-icing facilities*	Available. See AD chart for location.
5	*Hangar space for visiting aircraft*	Nil
6	*Repair facilities for visiting aircraft*	Available.
7	*Remarks*	NIL.

© 2024 ARMATS CJSC

UDSG AD 2.5 Passenger facilities

1	*Hotels*	Near the AD and in the city.
2	*Restaurants*	At AD and in the city.
3	*Transportation*	Buses and Taxis
4	*Medical facilities*	First aid at AD. Hospitals in the city.
5	*Bank and Post Office*	Bank at AD, Post Office in the city.
6	*Tourist Office*	At AD.
7	*Remarks*	Nil

UDSG AD 2.6 Rescue and fire fighting services

1	*AD category for fire fighting*	CAT 6
2	*Rescue equipment*	Available
3	*Capability for removal of disabled aircraft*	Not available
4	*Remarks*	Operation department Shift Manager is coordinator for crashed aircraft removal procedure and he is also the head of ARFF works. Tel: 00374 93600571; 00374 10493000 ext 7279

UDSG AD 2.7 Seasonal availability - clearing

1	*Types of clearing equipment*	1 Snow Blower, 4 Snow Ploughs and Scrapers
2	*Clearance priorities*	RWY 02/20, associated TWY to Apron and ACFT stands
3	*Remarks*	Information on snow clearance published from November-April in NOTAM (SNOWTAM). See also the snow plan subsection AD 1.2.2.

UDSG AD 2.8 Aprons, taxiways and check locations data

1	*Apron surface and strength*	Surface: Asphalt/Concrete Strength: PCN 37/F/C/X/T
2	*Taxiway width, surface and strength*	Width: TWY-A- 22m Surface: Asphalt/Concrete Strength: PCN 45/F/C/X/T TWY-B and main TWY 22m Surface: Asphalt/Concrete Strength: PCN 44/F/C/X/T
3	*ACL location and elevation*	Location: RWY 20 / RWY 02 Elevation: 5000FT /4941FT
4	*VOR/INS checkpoints*	Nil
5	*Remarks*	Nil

© 2020 ARMATS CJSC

UDSG AD 2.9 Surface movement guidance and control system and markings

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands*	Taxiing guidance signs at all intersections with TWY and RWY and at all holding positions. Guide lines at apron. Nose-in guidance at aircraft stands.
2	*RWY and TWY markings and LGT*	RWY: Designation, THR, TDZ, centre line, edge runway end as appropriate are marked. TWY: Centre line, holding positions at all TWY/RWY intersections are marked.
3	*Stop bars*	-
4	*Remarks*	Nil

UDSG AD 2.10 Aerodrome obstacles

ADelectronic obstacle data are provided according ICAO ANNEX 15.

See GEN 3.1 for details of how electronic obstacle and terrain data may be obtained.

UDSG AD 2.11 Meteorological information provided

1	*Associated MET Office*	Gyumri/Shirak
2	*Hours of service* *MET Office outside hours*	H24 –
3	*Office responsible for TAF preparation* *Periods of validity*	Gyumri/Shirak 24 HR
4	*Type of landing forecast* *Interval of issuance*	TREND 0.5 HR
5	*Briefing/consultation provided*	Personal consultation.
6	*Flight documentation* *Language(s) used*	Charts, abbreviated plain language text English and Russian.
7	*Charts and other information available for briefing or consultation*	S,U,P, SIG WX charts
8	*Supplementary equipment available for providing information*	Self-briefing terminal
9	*ATS units provided with information*	Gyumri Tower
10	*Additional information (limitation of service, etc.)*	See GEN 3.5 for RVR reporting and location of transmissometer

UDSG AD 2.12 Runway physical characteristics

Designations **RWY** **NR**	**TRUE BRG**	**Dimensions of RWY (M)**	**Strength (PCN) and surface of RWY and SWY**	**THR coordinates**	**THR elevation and highest elevation of TDZ of precision APP RWY**
1	**2**	**3**	**4**	**5**	**6**
02	023.61˚	3220 x 45	66/F/C/W/T Asphalt/ Concrete	404413.91N 0435106.12E	THR 4941FT TDZ 4941FT
20	203.62˚	3220 x 45	66/F/C/W/T Asphalt/ Concrete	404549.51N 0435201.09E	THR 5000FT TDZ 5000FT
Slope of RWY-SWY	**SWY dimensions (M)**	**CWY dimensions (M)**	**Strip dimensions (M)**	**OFZ**	**Remarks**
7	**8**	**9**	**10**	**11**	**12**
0.56%	Nil	200x330	3570 X 330	According ICAO Annex 14	RESA 150m X 100m
0.56%	Nil	150x330	3570 X 330		RESA 150m X 100m

UDSG AD 2.13 Declared distances

RWY Designator	**TORA (M)**	**TODA (M)**	**ASDA (M)**	**LDA (M)**	**Remarks**
1	**2**	**3**	**4**	**5**	**6**
02	3220	3420	3220	3220	Nil
20	3220	3370	3220	3220	Nil

UDSG AD 2.14 Approach and runway lighting

RWY Designator	**APCH LGT type** **LEN** **INTST**	**THR LGT** **colour** **WBAR**	**VASIS** **(MEHT)** **PAPI**	**TDZ, LGT** **LEN**	**RWY Centre Line LGT** **Length, spacing** **colour, INTST**	**RWY edge LGT** **LEN, spacing** **colour, INTST**	**RWY End LGT** **colour** **WBAR**	**SWY LGT** **LEN (M)** **colour**	**Remarks**
1	**2**	**3**	**4**	**5**	**6**	**7**	**8**	**9**	**10**
02	CAT I 900 M	Green –	PAPI Left /3° (41 FT)	NIL	NIL	3220M, 49.53 M White Last 594 M Yellow HIRL	Red –	Nil	Nil
20	Nil	Green –	PAPI Left 3.5° (51 FT)	Nil	NIL	3220M, 49.53 M White Last 594 M Yellow HIRL	Red –	Nil	Nil

© 2025 ARMATS CJSC

UDSG AD 2.15 Other lighting, secondary power supply

1	*ABN/IBN location, characteristics and hours of operation*	Nil
2	*LDI location and LGT* *Anemometer location and LGT*	Nil
3	*TWY edge and centre line lighting*	Edge TWY A, B
4	*Secondary power supply/switch-over time*	Secondary power supply to all lighting at AD. Switch-over time: t=0
5	*Remarks*	Nil

UDSG AD 2.16 Helicopter landing area

1	*Coordinates TLOF or THR of FATO Geoid undulation*	Nil
2	*TLOF and/of FATO elevation M/FT*	Nil
3	*TLOF and FATO area dimensions, surface, strength, marking*	Nil
4	*True BRG of FATO*	Nil
5	*Declared distance available*	Nil
6	*APP and FATO lighting*	Nil
7	*Remarks*	Nil

Note: Same as for ACFT.

UDSG AD 2.17 Air traffic services airspace

1	*Designation and lateral limits*	Gyumri CTR 405007N 0434115E - Radius GRM DME 10 NM - 403643N 0434207E - Then along state border with Turkey to - 405007N 0434115E
2	*Vertical limits*	6600 FT
3	*Airspace classification*	C
4	*ATS unit call sign* *Language(s)*	Gyumri Tower English
5	*Transition altitude*	11500 FT
6	*Remarks*	Nil

UDSG AD 2.18 Air traffic services communication facilities

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	**2**	**3**	**4**	**5**
TWR	Gyumri Tower	127.700 MHz 121.500 MHZ	*0600-1800*	Primary frequency Emergency frequency

UDSG AD 2.19 Radio navigation and landing aids

Type of aid, CAT of ILS/MLS (For VOR/ILS/MLS, give VAR)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
DVOR/DME (7° E 2025)	GRM	113.400 MHz CH 81x	H24	404345.9N 0435050.1E	4950 FT	Coverage FL 100 30 NM
LLZ 02 ILS CAT I (7° E 2025)	IGM	110.300 MHz	*0600-1800*	404600.1N 0435207.2E	-	357 M beyond THR 20
GP 02 DME	-	335.000 MHz (CH 40x)	*0600-1800*	404420.7N 0435115.7E	-	3º RDH 52 FT/16M 281 M past THR 02 right side, 123 M from the centre line
MM 02	1 dot 1 dash	75 MHz	*0600-1800*	404343.7N 0435048.9E	-	197º MAG/1050 M to RWY 02

UDSG AD 2.20 Local traffic regulations

1 Airport regulations

At Gyumri “Shirak” Airport a number of local regulations apply. The regulations are collected in a manual which is available at the AIS Briefing Office and at the Terminal Building. This manual includes, among other subjects, the following:

a. Information about aircraft stands;
b. Information about taxiing to aircraft stands;
c. Information about taxiing from aircraft stands;
d. Limitations in the operation of aircraft stands, including limitations in use of own power for taxiing;
e. Information about Engine start-up positions;

Information about the regulations for taxiing can be obtained from Gyumri TWR on 127.700 MHZ.

When a local regulation is important for the safe operation of aircraft on the apron Gyumri TWR gives information to each aircraft.

2 Taxiing to and from stands

Arriving aircraft is allocated a stand number by Gyumri TWR.

Taxiing of aircraft will be guided by “FOLLOW-ME” vehicle only by crew request or in low visibility condition.

Departing aircraft obtains pushback, engine start-up clearance and taxi instruction from Gyumri TWR on 127.700 MHZ.

3 Parking area for small aircraft

Nil

4 Parking area for helicopters

Nil

5 Apron — taxiing during winter conditions

Nil

© 2024 ARMATS CJSC

6 Taxiing — limitations

Information concerning limitation for uses TWY and Apron of large aircraft is given to each aircraft from Gyumri TWR.

7 School and training flights — technical test flights — use of runways

School and training flights must be made only after permission thereto has been obtained from Gyumri ATS authority.

8 Helicopter traffic — limitation

Nil

9 Removal of disabled aircraft from runways

In case when the aircraft is wrecked on a runway, it is removed from the runway by the Airline operating the aircraft as quickly as possible.

Airdrome Operator will have its participation according to the point 2.13 of Emergency Response Plan of Shirak airport.

Information about coordinator is available in AIP UDSG AD 2.6.

UDSG AD 2.21 Noise abatement procedures

Nil

UDSG AD 2.22 Flight procedures

General

Flight within Gyumri TMA shall be conducted in accordance with the Instrument Flight Rules unless special permission is obtained from Gyumri Approach.

Procedures for IFR flights within Gyumri TMA

The inbound, transit and outbound routes shown on the charts may be varied at the discretion of ATS. If necessary, in case of congestion, inbound aircraft may also be instructed to hold at GRMor BERDO or AMGIK in accordance with RWY in use.

Radar procedures within Gyumri TMA

Radar vectoring and sequencing

Radar vectors and flight levels/heights are issued, as required, for spacing and separating the aircraft, so that correct landing intervals are maintained, taking into account aircraft characteristics.
Radar vectoring charts haven't been published since the instrument approach procedures and altitudes ensured that adequate terrain clearance exists at all times until the point where the pilot resumes his own navigation on final approach or in the circuit.

Surveillance radar approaches

Nil

Precision radar approach

Nil

Communication failure

In case of communication failure, the pilot shall act in accordance with the communication failure procedures in ICAO Doc 7030.

Procedures for VFR flights within Gyumri TMA

Nil

Advisory considerations in case of engine inoperative after take-off from AD Shirak Gyumri

← In case of engine failure/fire after take-off, each operator is responsible for developing an emergency approach procedure. It is advisable to take into account the local circumstances outlined below

1. The maneuver zone safe altitude in IMC is 6600FT, in VMC is 6000FT.

2. After take-off from RWY20 initiate right side maneuver not further 2NM to the West or left side maneuver not further 4NM to the East over point (RWY02 TRH 1NM, GRM D0.5NM/R197°) or at 5500FT, whichever is earlier.
3. After take-off from RWY02 initiate left or right side maneuver not further 4NM over point (RWY20 TRH 1NM, GRM D3.3NM/R017°) or at 5500FT, whichever is earlier.
4. During approach to RWY20 do not cross Arc GRM D6.1NM (North of aerodrome).
5. During approach to RWY02 do not cross Arc GRM D7NM (South of aerodrome).

UDSG AD 2.23 Additional information

Bird concentrations in the vicinity of the airport

Nil

© 2025 ARMATS CJSC

UDSG AD 2.24 Charts related to an aerodrome

Aerodrome ground Movement and aircraft Parking Chart — ICAO (see page UDSG AD 2.2-1)

Aerodrome Obstacle Chart — ICAO Type A (see page UDSG AD 2.2-3)

Aerodrome Chart — ICAO (see page UDSG AD 2.2-5)

Area Chart — ICAO (see page UDSG AD 2.2-7)

List Of Coordinates For RVA Gyumri TMA (see page UDSG AD 2.2-9)

ATC Surveillance Minimum Altitude Chart - ICAO (see page UDSG AD 2.2-11)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY02 (see page UDSG AD 2.2-13)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY02 (see page UDSG AD 2.2-15)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY02 (Waypoint Data/List) (see page UDSG AD 2.2-17)

Standard Departure Chart — Instrument SID - ICAO RNAV1 (GNSS) RWY02 (see page UDSG AD 2.2-19)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY20 (see page UDSG AD 2.2-21)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY20 (see page UDSG AD 2.2-23)

Standard Departure Route — Instrument SID RNAV1 (GNSS) RWY20 (Waypoint Data/List) (see page UDSG AD 2.2-25)

Standard Departure Chart — Instrument SID - ICAO RNAV1 (GNSS) RWY20 (see page UDSG AD 2.2-27)

Standard Arrival Route — Instrument STAR RNAV1 (GNSS) RWY20 (see page UDSG AD 2.2-29)

Standard Arrival Route — Instrument STAR RNAV1 (GNSS) RWY20 (Waypoint Data/List) (see page UDSG AD 2.2-31)

Standard Arrival Chart — Instrument STAR - ICAO RNAV1 (GNSS) RWY20 (see page UDSG AD 2.2-33)

Instrument Approach Chart — ICAO ILS/DME RWY 02 (see page UDSG AD 2.2-35)

Instrument Approach Chart — ICAO DVOR DME RWY 02 (see page UDSG AD 2.2-37)

RNP RWY 20 Instrument Approach (LNAV/VNAV) Route Data (see page UDSG AD 2.2-39)

RNAV (GNSS) Instrument Approach RWY 20 (Waypoint Data/List) (see page UDSG AD 2.2-41)

Instrument Approach Chart - ICAO RNP RWY 20 (LNAV/VNAV) (see page UDSG AD 2.2-43)

RNP RWY 02 Instrument Approach (LNAV/VNAV) Route Data (see page UDSG AD 2.2-45)

RNAV (GNSS) Instrument Approach RWY 02 (Waypoint Data/List) (see page UDSG AD 2.2-47)

Instrument Approach Chart - ICAO RNP RWY 02 (LNAV/VNAV) (see page UDSG AD 2.2-49)

Visual Approach Chart — ICAO RWY 02/20 (see page UDSG AD 2.2-51)

© 2025 ARMATS CJSC