OJAI AD 2.1 AERODROME LOCATION INDICATOR AND NAME
OJAI - Queen Alia/ International

OJAI AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA		
1	ARP coordinates and site at AD	31° 43' 26.857" N 35° 59' 40.641" E Between TWY F and TWY G
2	Direction and distance from city	15.6 NM South.
3	Elevation / Reference temperature	2396FT (730.30M) / 31.5ºC
4	Geoid undulation at AD ELEV PSN	20.3M (66.6 FT)
5	Magnetic variation / Annual change	5º E / 1' E (2025)
6	AD administration, address, telephone, fax, AFS	AMMAN/Queen Alia International Airport P.O.BOX : 39052 AMMAN – JORDAN TEL : + 962 6 4018021 FAX : + 962 6 4451136
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	Nil

OJAI AD 2.3 OPERATIONAL HOURS		
1	Aerodrome Administration	H24
2	Customs and immigration	H24
3	Health and sanitation	H24
4	AIS Briefing Office	H24
5	ATS Reporting Office (ARO)	H24
6	MET Briefing Office	H24
7	Air Traffic Service (ATS)	H24
8	Fueling	H24
9	Handling	H24
10	Security	H24
11	De-Icing	H24
12	Remarks	Nil

OJAI AD 2.4 HANDLING SERVICES AND FACILITIES		
1	Cargo-handling facilities	Full handling service available up to code E. Limited capacity for code F aircraft.
2	Fuel / oil Types	Fuel : JET A1 Oil : Turbo Oil 2380, Turbo Oil 2197, Skydrol, Fluid 41, Royco 756 , Tribolube 64RPC, WD-40, Skydrol 500 B4, and Skydrol Ld4.
3	Fueling facilities / Capacity	H24/No limit
4	De-icing facilities	De-icing location: Cargo Apron. TWY J, TWY T, TWY E and on Aircraft Stands on Hotel Apron Aircraft De-icing material used: -Name: Kilfrost ABC-S PLUS -Type: Aircraft De/Anti-Icing fluid type IV. Conforms to all of the technical requirements of SAE AMS 1428 for type IV and ISO11078 for aircraft De-icing/anti-icing fluids.
5	Hangar space for visiting aircraft	Available only for private companies, maintenance, and Royal Pavilion.
6	Repair Facilities for visiting aircraft	Available
7	Remarks	Nil

OJAI AD 2.5 PASSENGER FACILITIES		
1	Hotels	Limited capacity Airport Hotel, Near the AD and in the city
2	Restaurant	At AD and in the city
3	Transportation	Taxis and Buses to Amman city
4	Medical facilitates	First aid treatment, Ambulances to Hospitals in Amman City 15.6NM
5	Bank and Post Office	At AD - H24
6	Tourist Office	At AD – H24
7	Remarks	Nil

OJAI AD 2.6	RESCUE AND FIRE FIGHTING SERVICES	
1	Aerodrome category for fire fighting	CAT 10
2	Rescue equipment	Yes, Under the management of Jordanian Civil Defense Directorate
3	Capability for removal of disabled aircraft	Limited Equipment available, companies should use IATA pooling arrangement.
4	Remarks	Nil

OJAI AD 2.7	SEASONAL AVAILABILITY-CLEARING	
1	Types of clearing equipment	2 Fluid Spreaders(one equipped with hydraulic snow plough), 2 sweepers equipped with hydraulic snow ploughs and 5 snow removal blades installed on 4x4 pickups (Additional equipment subcontracted)
2	Clearance Priorities	Runway in use, Taxiways and Aprons.
3	Remarks	Nil

OJAI AD 2.8 APRONS TAXIWAYS AND CHECK LOCATIONS/ POSITION DATA		
1	**Apron surface and strength**	**1) North Apron** **East side (N05-N32)** Surface : Concrete (Rigid) Strength : PCR 680/R/B/W/T **West side (N01-N04)** Surface : Concrete (Rigid) Strength : PCR 610/R/A/W/T **2) South Apron** **East side (S05-S32)** Surface : Concrete (Rigid) Strength : PCR 800/R/B/W/T **West side (S02-S04)** Surface : Concrete (Rigid) Strength : PCR 590/R/A/W/T **3) Cargo Apron** Surface : Concrete (Rigid) Strength : PCR 480/R/A/W/T **4) Maintenance Apron** **Maintenance Apron 1** Surface : Concrete (Rigid) Strength : PCR 720/R/B/W/T **Maintenance Apron 2** Surface : Asphalt (Flexible) Strength : PCR 710/R/B/W/T **5) Hotel Apron** Surface : Asphalt (Flexible) Strength : PCR 1410/F/B/X/T **6) Royal Pavilion** Surface : Concrete (Rigid) Strength : PCR 1110/R/B/W/T

APRONS TAXIWAYS AND CHECK LOCATIONS/ POSITION DATA (Cont.)

2	**Taxiways width, surface, strength and usage limitations**	**(A)** Surface : Asphalt (Flexible) Strength : PCR 920/R/A/W/T Width : 30.5M **26L H.P** Surface : Asphalt (Flexible) Strength : PCR 740/R/A/W/T **08R H.P** Surface : Asphalt (Flexible) Strength : PCR 890/R/A/W/T	
		(B) Surface : Asphalt (Flexible) Strength : PCR 1160/R/A/W/T Width : 35M	Runway 26L/08R exit only (Runway entry through this taxiway prohibited)
		(C) Surface : Asphalt (Flexible) Strength : PCR 1020/R/A/W/T Width : 35M	Runway 26L/08R exit only (Runway entry through this taxiway prohibited)
		(D) Surface : Asphalt (Flexible) Strength : PCR 940/R/A/W/T Width : 35M	Runway 26L/08R exit only (Runway entry through this taxiway prohibited)
		(E) Surface : Concrete (Rigid) Strength : PCR 1150/R/C/W/T Width : 35M	
		(F) Surface : Concrete (Rigid) Strength : PCR 850/R/B/W/T Width : 30.5M	
		(G) Surface : Asphalt (Flexible) Strength : PCR 1040/R/B/W/T Width : 30.5M	
		(H) Surface : Asphalt (Flexible) Strength : PCR 2910/F/B/X/T Width : 30.5M	
		26R H.P Surface : Asphalt (Flexible) Strength : PCR 1670/R/B/W/T **08L H.P** Surface : Asphalt (Flexible) Strength : PCR 1610/R/A/W/T	

APRONS TAXIWAYS AND CHECK LOCATIONS/ POSITION DATA (Cont.)

2	**Taxiways width, surface, strength and usage limitations**	**(J)** Surface : Concrete (Rigid) Strength : PCR 830/R/A/W/T Width : 35M **(K)** Surface : Asphalt (Flexible) Strength : PCR 1120/F/B/X/T Width : 35M **(L)** Surface : Asphalt (Flexible) Strength : PCR 2890/F/A/X/T Width : 35M **(M)** Surface : Asphalt (Flexible) Strength : PCR 1280/F/B/X/T Width : 35M **(N)** Surface : Concrete (Rigid) Strength : PCR 890/R/C/W/T Width : 35M **(S)** Surface : Concrete (Rigid) Strength : PCR 790/R/B/W/T Width : 35M **(T)** Surface : Asphalt (Flexible) Strength : PCR 3000/F/B/X/T Width : 46M **(Y)** Surface : Concrete (Rigid) Strength : PCR 1110/R/B/W/T Width : 49M **(Z)** Surface : Concrete (Rigid) Strength : PCR 1110/R/B/W/T Width : 41M	Runway 26R/08L exit only (Runway entry through this taxiway prohibited) Runway 26R/08L exit only (Runway entry through this taxiway prohibited) Runway 26R/08L exit only (Runway entry through this taxiway prohibited)		
3	**Altimeter Checkpoint Location And Elevation**	Apron	LAT	LONG	ELEV
		N	314329.58875	355915.95503	2363FT (720M)
		S	314312.18804	355918.79585	2360FT (719M)
		Cargo	314317.58140	355959.81714	2363FT (720M)
		Maintenance	314319.46532	360019.71123	2362FT (720M)
		Royal Pavilion	314305.80970	355849.98544	2360FT (719M)
		H	314339.12830	360001.26750	2372FT (723M)
4	**VOR Check points**	Nil			
5	**INS checkpoints**	Nil			
6	**Remarks**	1- Pilots requested to pay extra caution ahead of intersection with service roads while taxing on TWY's F and G Illuminated Signage installed on the Terminal Fixed Link Bridge as an additional assistance for Pilots to identify Different Contact Stands			

OJAI AD 2.9	SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS	
1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Day and night : TWY sign boards Day: Finger sign boards. VDGS is not available on all aircraft stands (see: 2.9.1)
2	RWY and TWY markings and LGT	RWY: Designation, THR, TDZ, centerline, edge RWY end as appropriate, marked and lighted. TWY: Centre line, Intermediate holding positions, holding positions at all TWY/RWY intersections, marked and lighted. RWY Guard Lights 08R Nil – Available on 26L, 26R & 08L Holding Position
3	Stop bars	08R NIL - Available and Operational for H24 on 26L,26R & 08L Holding Positions (Marking, lighting & signage)
4	Remarks	Royal pavilion is Marked. See Charts: AD OJAI 2.24.1-1 and AD OJAI 2.24.2-1

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT:

NORTH APRON

	STAND NUMBER	*CAPACITY*	*GEOGRAPHICAL COORDINATES FOR AIRCRAFT STANDS*	
			LAT	**LONG**
Remote Stands	N01	Code C Maximum except A321, B737-900, MD80/90, DC9, CRJ, DH8,EMB195, B727 Series, B737 Max , EMB 195 E1/E2	31 43 31.29930	35 59 05.61286
	N03	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 31.52599	35 59 07.18510
	N05	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 31.75316	35 59 08.75877
	N07	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 31.97990	35 59 10.33139
	N09	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 32.20669	35 59 11.90445
	N11	Code C Maximum except MD80/90; DC9, DH8,B727 Series	31 43 32.43397	35 59 13.47764
	N13	Code C Maximum except MD80/90, DC9, DH8, B727 Series	31 43 32.66105	35 59 15.05068
	N15	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 32.88782	35 59 16.62369
	N17	Code C Maximum except MD80/90; DC9, DH8, B727 Series	31 43 33.11485	35 59 18.19662
	N19	Code E Maximum except A340-600, B777-300, B777-300ER A340-500, A350 Series and B747 Series	31 43 34.30926	35 59 23.95745
	N21	Code E Maximum	31 43 34.70115	35 59 26.67289
	N30	Code C Maximum except ATR42, ATR72, CRJ900, CRJ1000, MD82, MD83, MD87, MD88, MD90, F100, B727 Series	31 43 27.65176	35 59 25.98830
	N32	Up to code E excluding A330 Series, A340 Series, A350 Series, B747 Series, B777 Series, B789, B78X, B764 ER (maximum aircraft length58M)	31 43 27.79676	35 59 26.53850
	N34	Code C Maximum except ATR42,ATR72,CRJ900, CRJ1000,MD82,MD83,MD87,MD88, MD9,F100,A321,A321 NEO B717, B737-800, B727 Family, B737-800W, B737900, B737-900ER, B737-900W, B737-900ERW, B737-BBJ2, B737BBJ2W, B737-BBJ3, B737-BBJ3W, B737-700MAX, B737-800MAX, B737-900MAX, , EMBRAER Series	31 43 28.43487	35 59 27.17973

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT (Cont.):				
Contact Stands with Visual Docking Guidance System	N02	Code C Maximum except MD80/90; DC9, ATR F100, CRJ, DH8,EMB135,EMB145, B727 Series B717-200,A220 Series	31 43 25.71835	35 59 06.55923
	N04	Code E Maximum except: Code A, B and EMB 135,EMB 145 ,ATR42,AT72,CRJ700,CRJ900,CRJ1000, F100,MD82/ MD83/ MD87/ MD88/ MD90-30/ B717-200,B727 series	31 43 25.39305	35 59 09.41678
	N08	Code E Maximum except Code A, B and C	31 43 25.79973	35 59 12.45492
	N14	Code E Maximum except Code A, B and C	31 43 26.24726	35 59 15.48638
	N18	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 26.58759	35 59 18.62494
	N20	Code E Maximum except Code A, B and C	31 43 26.73470	35 59 19.17280
	N24	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 27.11488	35 59 22.34343
	N26	Code F Maximum Except AN124, AN225, Code A, B and C	31 43 27.28121	35 59 22.82909
Contact Stands without Visual Docking Guidance System	N06	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 25.78165	35 59 12.01523
	N10	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 26.90916	35 59 12.55933
	N12	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 26.21903	35 59 15.04891
	N16	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 27.37698	35 59 15.60944
	N22	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 27.66545	35 59 19.31815
	N28	Code C Maximum except, EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/ MD90-30/B717-200, B727 Series	31 43 28.18031	35 59 23.14478

Note 1: Code E & F aircraft pilots shall use minimum power while maneuvering on North Apron.
Note 2: Code E & F aircrafts and B734, B735, E295, E190 pilots to avoid using breakaway power at turning on North Apron
Note 3: GH Trained personnel availability is mandatory on north apron parking stands to monitor aircraft parking process even when the parking stands are equipped with Visual Docking Guidance System.
Note 4: Code A & B Aircraft can taxi-out from stand N19 without the need of pushback by following the lead-out line, marshaling shall be available during such operations.
Note 5: **Code F operations on North apron**:
At Arrival and Departure phases :
- Aircraft shall taxi with inner engines, and keep outer engines at idle thrust to minimize the impact of jet blast.

Code F entry to north apron:

- Code F entry to North apron via taxiway Juliet:
  - Code F Aircraft enter and exit via Taxiway Juliet and park on stand N26
  - A Follow-me vehicle shall be provided for guiding the aircraft upon pilot request.
  - Stands N17 shall be clear of all aircraft types.
  - Airside staff will inspect stands N17 & N19 before the aircraft arrival to TWY J.
  - Code-E aircrafts could be allocated on stand N19 but without any handling activities or equipment based on airport duty manager approval and coordination with ATC.
- Code F Aircraft enter and exit via Taxiway November and park on stand N26,
  - Stands N19, N21, N30, N32 and N34 shall be clear of all aircraft types.
  - Airside staff will inspect stands N19, N21, N30, N32 and N34 before the aircraft arrival to taxiway November.
  - A follow-me vehicle shall be provided for guiding the aircraft

Code F pushback procedure on north apron :

- Minimum engine power shall be maintained.
- Pushback procedure via taxiway Juliet:
  - The aircraft shall be pushed back facing south towards taxiway Juliet until it reaches taxiway Hotel then facing east if runway in use was 26R, 26L or 08R or facing west if runway in use was 08L, such that the aircraft main gear is aligned with the
    Taxiway centerline until its nose wheel becomes after the intermediate holding position marking, the aircraft may break away from this point when taxi clearance has been issued by the ATC.
- Airside OPS will ensure that there are no GSEs or any other type of equipment within the red hatched area of stands N17 & N19 to maintain the safe clearance of the A380 wingtips. In addition, Airside OPS will communicate with ATC to stop the aircraft push back if there were any GSEs equipment within the aircraft safety clearness's and follow up with concerned ground handler to have it removed. then confirm to ATC to communicate the safe status with pilot.
- Aircraft Pushback procedure via taxiway November:
- The aircraft shall be pushed back facing west towards taxiway November until it reaches taxiway Foxtrot then facing North if runway in use was 26R/08L or facing south if runway in use was 26L/08R, such that the aircraft main gear is aligned with the Taxiway centerline, the aircraft.

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT: (Cont.)

SOUTH APRON

	NAME	CAPACITY	GEOGRAPHICAL COORDINATES FOR AIRCRAFT STANDS	
			LAT	LONG
Remote Stands	S02	Code C maximum	31 43 13.59345	35 59 09.18005
	S05	Code C maximum	31 43 07.85891	35 59 11.90827
	S07	Code C maximum	31 43 08.08523	35 59 13.48073
	S09	Code C maximum	31 43 08.31231	35 59 15.05296
	S11	Code C maximum	31 43 08.53843	35 59 16.62519
	S13	Code C maximum	31 43 08.76056	35 59 18.16458
	S15	Code C maximum	31 43 09.45758	35 59 23.05060
	S17	Code C maximum	31 43 09.68556	35 59 24.63437
	S19	Code C maximum	31 43 09.91367	35 59 26.21861
	S21	Code C maximum	31 43 10.16645	35 59 27.98273
	S23	Code C maximum	31 43 10.42197	35 59 29.74499
	S25	Code C maximum	31 43 10.65615	35 59 31.36612
Contact Stands with Visual Docking Guidance System	S04	Code C maximum except B727 Series/MD80/90, DC9, ATR, CRJ, DH8, EMB 135/145, F100	31 43 13.42540	35 59 11.21549
	S06	Code E maximum except B727-200/W, CRJ, MD80/90, F100, EMB 135/145 , Code A & B	31 43 14.60295	35 59 13.21841
	S10	Code E maximum except Code A, B and C	31 43 15.04105	35 59 16.25292
	S16	Code E maximum except Code A, B and C	31 43 15.47801	35 59 19.28552
	S20	Code C maximum except EMB135, EMB145, ATR42, ATR72. CRJ. CRJ700. CRJ1000, MD82, MD83, MD87, MD88, MD90, F100, B717, B727 Series	31 43 15.65576	35 59 21.85444
	S24	Code E maximum except Code A, B and C	31 43 16.19915	35 59 24.20089

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT: (Cont.)

Contact Stands with Visual Docking Guidance System	S26	Code C maximum except EMB135, EMB145, ATR42, AT72, CRJ700, CRJ1000, F100, MD82/MD83/MD87/MD88/MD90, B717-200, B727 Series Code A and B	31 43 16.36257	35 59 24.74631
	S30	Code F except AN124 , AN225 ,B747-8 Code A and B	31 43 16.71613	35 59 27.78473
	S32	Code C maximum except EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, MD82/MD83/MD87/MD88/MD90-30 B717-200, B727 Series Code A and B	31 43 16.71613	35 59 28.33081
Contact Stands without Visual Docking Guidance System	S08	Code C maximum except A318, B737-200, B737-300/W, B737-400, B737-500/W, B737-600, B737-700/W, B737-BBJ, B737-800/W, B737-900/W/ER/ERW, B737-BBJ2/BBJ3, MD80/90; DC9, ATR, CRJ, DH8, EMB170LR/SU/SE/STD, EMB175LR/STD, F100, B727 Series	31 43 13.92802	35 59 16.15156
	S12	Code C maximum except MD80/90; DC9, ATR, CRJ, DH8, F100, EMB 135/145, B727 Series	31 43 15.05068	35 59 16.69326
	S14	Code C maximum except MD80/90,DC9, ATR, CRJ, DH8, F100, EMB, Series B737 Series & B727 Series.	31 43 14.37454	35 59 1922833
	S18	Code C maximum except MD80/90,DC9, ATR, CRJ, DH8, F100, EMB, Series B737 Series & B727 Series	31 43 15.51951	35 59 19.61635
	S22	Code C maximum except EMB135, EMB145, ATR42, AT72,CRJ700, CRJ900, CRJ1000, F100,B717, MD82, MD83, MD87, MD88, MD90 & B727 Series	31 43 15.28627	35 59 24.05205
	S28	Code C maximum except EMB135, EMB145, ATR42, AT72, CRJ700, CRJ900, CRJ1000, F100, B717, MD82, MD83, MD87, MD88, MD90 B727 Series	31 43 15.80455	35 59 27.63721

Note 1: GH Trained Personnel availability is mandatory on south apron parking stands to monitor the aircraft parking process even when the parking stands are equipped with Visual Docking Guidance System

Note 2: Code E & F, pilots shall use minimum power while maneuvering on South Apron.

Note 3: Code E & F aircrafts and B734, B735, E295, E190 pilots to avoid using breakaway power at turning on South Apron

Note 4: S02 is equipped with Visual Docking Guidance System.

Note 5: Code A & B Aircrafts can taxi-out from stand S15 without the need of pushback by following the lead-out line, marshaling shall be available during such operations.

Note 6 : **Code F operations on south apron:**

At Arrival and Departure phases :

- A follow – me vehicle shall be provided for guiding the aircraft on South Apron entrance at Taxiway S.
- Aircraft shall taxi with inner engines and keep outer engines at idle thrust to minimize the impact of jet blast
- Code F Aircraft shall enter only via Taxiway S, and park on stand S30
- Stands S21, S23 & S25 shall be clear of all aircraft types.

Code F Pushback procedure on south apron :

- Minimum engine power shall be maintained.
- The aircraft shall be pushed back facing west through taxiway S until it reaches taxiway F then facing south (26L, 08R in use) or facing north (26R, 08L in use) such that the aircraft main gear is aligned on the Taxiway centerline until its nose wheel becomes after the intermediate holding position marking, the aircraft may break away from this point after taxi clearance has been issued by the ATC Ground Controller

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT: (Cont.)

CARGO APRON

STAND NUMBER	CAPACITY	GEOGRAPHICAL COORDINATES FOR AIRCRAFT STANDS		Remark
		LAT	LONG	
C1	Code F maximum except A380-800, AN124, AN225 -wing span 68.5	31 43 19.49684	35 59 56.48185	NIL
C2	Code D except B767-400ER, IL76, IL86, L1011-500, DC10-30, MD11 – Maximum length 58m	31 43 19.96526	35 59 58.93869	Not available if 2A occupied
C2A	Code F maximum	31 43 19.90996	35 59 59.64942	Not available if 2, 3 and/or 3A occupied
C3	Code D except B767-400ER, IL76, IL86, L1011-500, DC10-30, MD11- maximum wing span 48 m and maximum length 58m	31 43 20.26794	36 00 01.02013	Not available if 2A or 3A occupied
C3A	Code E maximum length 71 m	31 43 20.32632	36 00 02.53649	Not available if 3 or 4 occupied
C4	Code D except B767-400ER, IL76, IL86, L1011-500, DC10-30,MD11- maximum wing span 48 m and maximum length 58m	31 43 20.09234	36 00 03.20445	Not available if 3A occupied

Note 1: Marshaling is Mandatory on all cargo parking stands.

Note 2: All cargo stands capacity are subject to compatibility requirements.

HOTEL APRON

STAND NUMBER	CAPACITY	GEOGRAPHICAL COORDINATES FOR AIRCRAFT STANDS		Remark
		LAT	LONG	
28	Code D except B767-400ER, IL76, IL86, L1011-500, DC10-30, MD11. Maximum wing span 48m & length 58m	31 43 37.99077	35 59 56.06989	Limited to B if 28A occupied
28A	Code C maximum to EMB175 /CRJ 900	31 43 38.56517	35 59 57.19030	
29	Code E maximum length 75.3m	31 43 37.89444	35 59 58.55975	Limited to B if 28A or 29A occupied
29A	Code C maximum to B737/300	31 43 38.96228	35 59 59.74235	
30	Code E maximum length 75.3m	31 43 38.35549	36 00 01.27826	Limited to B if 29A or 30A occupied
30A	Code C maximum to EMB175 /CRJ 900	31 43 39.29913	36 00 02.33629	
31	Code D except B767-400ER, IL76, IL86, L1011-500, DC10-30, MD11. Maximum wing span 48m & length 58m	31 43 39.20896	36 00 03.54814	Limited to B if 30A or 31A occupied
31A	Code C except B737-900/W/ERW, B737-800/W, B737-700/W, B737-600, B737BBJ, B737BBJ2, B737BBJ3. Maximum wing span 34 m & length 47m.	31 43 39.64364	36 00 05.36437	
32	Code F except AN 225, A380, B747-800 Maximum wing span 80m & length 76.3m	31 43 39.05673	36 00 06.09141	Not available when 31,31A and 32A occupied
32A	Code C maximum to B737/300	31 43 39.98959	36 00 06.62943	

Note 1: Marshaling is Mandatory on all hotel parking stands.
Note 2: All hotel stands capacity are subject to compatibility requirements.

2.9.1 AIRCRAFT PARKING STANDS AT AMMAN /QUEEN ALIA AIRPORT: (Cont.)

ROYAL PAVILION APRON			
STAND NUMBER	**CAPACITY**	**GEOGRAPHICAL COORDINATES FOR AIRCRAFT STANDS**	
		LAT	**LONG**
P00	Aircraft up to B747/ A340	31 43 05.43197	35 58 48.48128
P01	Aircraft up to G450/Challenger850	31 43 08.00891	35 58 47.35625
P02	Aircrafts up to A321/B737	31 43 08.53071	35 58 50.75941
P03	Aircraft up to G450/Challenger850	31 43 08.41364	35 58 49.94831
P04	Aircrafts up to A321/B737	31 43 08.92216	35 58 53.48056
P05	Aircraft up to G450/Challenger850	31 43 08.57088	35 58 51.03832
P06	Aircraft up to G450/Challenger850	31 43 08.72631	35 58 52.12907
P07	Aircraft up to G450/Challenger850	31 43 08.88454	35 58 53.21715
P08	Reserved		
P09	Aircraft up to B747/ A340	31 43 11.01972	35 58 54.06215
P10	Aircraft up to G450/Challenger850	31 43 11.83007	35 58 58.715
P11	Aircrafts up to A321/B737	31 43 12.03151	35 59 00.12841
Note: Marshaling is Mandatory on all Royal Pavilion Apron.			

OJAI AD 2.10 AERODROME OBSTACLES				
Obstacles in Approach and Take off Areas				
RWY	**TYPE**	**ELEV (M)**	**From RWY THR**	
			DIST(M)	**MAG**
26L 26R 08R 08L	* Telecommunication TWR Pole Pole	779 760 805	3500 2748 6681	- 266 252
* REMARK: Telecommunication Tower Geographical Coordinates is 314106N 355825E				

OJAI AD 2.11 METEROLOGICAL INFORMATION PROVIDED		
1	Associated MET Office	Amman/Queen Alia
2	Hours of service MET Office outside hours	H24 -----
3	Office responsible for TAF preparation Periods of validity	Queen Alia MET Office 18,24
4	Trend forecast Interval of issuance	TAF, TREND Sc Hourly
5	Briefing/consultation provided	P, T, FAX
6	Flight documentation Language(s) used	C, TAF Code Form English
7	Charts and other information available for briefing or consultation	S.W.C U "Upper" W "Wind" T^0 "TEMP"
8	Supplementary equipment available for Providing information	APT, WEFAX
9	ATS units provided with information	FIC, ACC, RCC, TWR
10	Additional information (limitation of service, etc.)	SPECI Warnings

OJAI 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	True & MAG BRG	Dimensions of RWY (M)	Strength(PCR) and surface of RWY and SWY	THR coordinates and THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
26L	260.41ºT 255.41ºMAG	3660 x 61	Runway(PCR) 1060/R/A/W/T Asphalt Flexible Stopway Asphalt Flexible	314311.59N 0360106.91E 20.3 M (66.6 FT)	THR 2366.3FT (721.2m) TDZ 2364.5FT (720.7M)
08R	080.39ºT 075.39ºMAG			314251.78N 0355849.85E 20.3 M (66.6 FT)	THR 2358.1 FT (718.8m) TDZ 2356.3FT (718.2M)
26R	260.41ºT 255.41ºMAG	3664 x 61	Runway(PCR) 1500/ F/A/X/T Asphalt Flexible Stopway Asphalt Flexible	314356.08N 0360027.48E 20.3 M (66.6 FT)	THR 2395.2FT (730.1M) TDZ 2395 FT (730.1M)
08L	080.39ºT 075.39ºMAG			314336.23N 0355810.09E 20.3M (66.6FT)	THR 2360.8 FT (719.6M) TDZ 2362 FT (720M)

Slopes of RWY-SWY	SWY Dimension (M)	CWY Dimension (M)	Strip Dimensions (M)	RESA Dimensions (M)	Location/ description of arresting system	OFZ	Remarks
7	8	9	10	11	12	13	14
08L/26R: SWY +1.13(150.0) RWY08L + 0.02 (1100.0) + 0.62 (1700.0) - 0.02 (864.9) RWY26R - 0.42(150.0) SWY	150 x 61	843 x 300	4084 x 300	240 x 150	Nil	1500x300	THR Asphalt
08R/26L: SWY 0.60 (150)- RWY 08R 0.23 (420)+ 0.45 (160)+ 0.00 (69.8)+ 0.80 (610)+ 0.02 (602.53)+ 0.02 (182.26)+ 0.14 (151.59)+ 0.41 (591.48)+ 0.24 (672.41)+ RWY 26L	150x61	843 x 300	4080 x 300	240 x 150	Nil	1500x120	THR Asphalt

OJAI AD 2.13 DECLARED DISTANCES					
RWY Designator	**TORA (M)**	**TODA (M)**	**ASDA (M)**	**LDA (M)**	**Remarks**
1	**2**	**3**	**4**	**5**	**6**
26L	3660	4503	3810	3660	Nil
26R	3664	4507	3814	3664	Nil
08L	3664	4507	3814	3664	Nil
08R	3660	4503	3810	3660	Nil

OJAI AD 2.14 APPROACH AND RUNWAY LIGHTING		
1	**RWY Designator**	26L
2	**APPROACH LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	900M
	INTENSITY	6.6A (5 Steps)
	Color	Approach Center: White, Approach Side Row: Red
3	**THR LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	COLOUR	Green
	WBAR	Green
	SPACING	3M
4	**PAPI**	
	(MEHT)	19.08M
	SPECIFICATIONS.	4 Units – 3 DEG – on both sides of RWY - 386.02M from THR
	INTENSITY	6.6A (5 Steps)
5	**TDZ LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	LENGTH	900M
	COLOUR	White
	SPACING	30M
6	**RWY CENTER LINE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3660M
	SPACING	15M
	COLOUR	White (last 900M – 600M White and Red, last 300M Red)
	INTENSITY	6.6A (5 Steps)
7	**RWY EDGE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3660M
	SPACING	60M
	COLOUR	White (last 600M Amber)
	INTENSITY	6.6A (5 Steps)
8	**RWY END LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	3M
	COLOUR	Red
9	**STOPWAY LIGHT**	Nil
10	**REMARK**	Nil
1	**RWY Designator**	26R
2	**APPROACH LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	900M
	INTENSITY	6.6A (5 Steps)
	Color	Approach Center: White, Approach Side Row: Red / sequential
3	**THR LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	3M
	COLOUR	Green
	WBAR	Green
4	**PAPI**	
	(MEHT)	22.80M
	SPECIFICATIONS.	4 Units – 3 DEG – on both sides of RWY - 426.23M from THR
	INTENSITY	6.6A (5 Steps)

OJAI AD 2.14 APPROACH AND RUNWAY LIGHTING (CONT)		
26R(CONT)		
5	**TDZ LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	COLOUR	White
	SPACING	30M
	LENGTH	901.4M
6	**RWY CENTER LINE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3664M
	SPACING	14.8M
	COLOUR	White (last 887.5M – 591.1M White and Red, last 296.4M Red)
	INTENSITY	6.6A (5 Steps)
7	**RWY EDGE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3664M
	SPACING	60M
	COLOUR	White (Last 600M Amber)
	INTENSITY	6.6A (5 Steps)
8	**RWY END LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	9M
	COLOUR	Red
9	**STOPWAY LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	60M
	COLOUR	Red
10	**REMARK**	Ni
1	RWY Designator	08L
2	**APPROACH LIGHT**	
	TYPE	CAT II / LED LIGHTS
	LENGTH	900M
	INTENSITY	6.6A (5 Steps)
	Color	Approach Center: White, Approach Side Row: Red
3	**THR LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	9M
	COLOUR	Green
	WBAR	Green
4	**PAPI**	
	(MEHT)	22.80M
	SPECIFICATIONS.	4 Units – 3 DEG – on both sides of RWY - 430.2M from THR
5	**TDZ LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	COLOUR	White
	SPACING	30M
	Length	901M
6	**RWY CENTER LINE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3664M
	SPACING	14.8M
	COLOUR	White (last 887.7M – 591.5M White and Red, last 296.4M Red)
	INTENSITY	6.6A (5 Steps)

OJAI AD 2.14 APPROACH AND RUNWAY LIGHTING (CONT.)		
08L(CONT.)		
7	**RWY EDGE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3664M
	SPACING	60M
	COLOUR	White (last 600M Amber)
	INTENSITY	6.6A (5 Steps)
8	**RWY END LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	9M
	COLOUR	Red
9	**STOPWAY LIGHT**	
	TYPE	CAT II/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	60M
	COLOUR	Red
10	**REMARK**	Nil
1	**RWY Designator**	08R
2	**APPROACH LIGHT**	Nil
3	**THR LIGHT**	
	TYPE	Non-Instrument/LED Light
	INTENSITY	6.6A (5 Steps)
	COLOUR	Green
	WBAR	Nil
4	**PAPI**	
	(MEHT)	19M
	SPECIFICATIONS.	4 Units – 3 DEG – on both sides of RWY - 474.93M from THR
5	**TDZ LIGHT**	Nil
6	**RWY CENTER LINE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3660M
	SPACING	15M
	COLOUR	White (last 900M – 600M White and Red, last 300M Red)
	INTENSITY	6.6A (5 Steps)
7	**RWY EDGE LIGHT**	
	TYPE	CAT II/LED Light
	LENGTH	3660M
	SPACING	60M
	COLOUR	White (last 600M Amber)
	INTENSITY	6.6A (5 Steps)
8	**RWY END LIGHT**	
	TYPE	Non-Instrument/LED Light
	INTENSITY	6.6A (5 Steps)
	SPACING	9M
	COLOUR	Red
9	**STOPWAY LIGHT**	Nil
10	**REMARK**	Nil

OJAI AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY		
1	ABN/IBN Location, characteristics and hours of operation	ABN On top of Control TWR, FLG Green + White HN + IMC, during night and low visibility IBN over maintenance Hanger FLG GREEN QA HN + IMC, during night
2	LDI location and LGT Anemometer location and LGT	Nil
3	TWY edge and centre line lighting	Edge: All TWYs curves / except H, K, L & M as they are equipped with reflective markers on curves Centre line: All TWYs
4	Secondary power supply switch-over time	Secondary power supply to all RWYs TWYs, NAV AIDS / Switch-over time: 0 SEC
5	Remarks	Nil

OJAI AD 2.16 HELICOPTER LANDING AREA		
1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation M/FT	
3	TLOF and FATO area dimensions, surface, strength, marking	
4	True BRG of FATO	
5	Declared distance available	
6	APP and FATO lighting	
7	Remarks	

OJAI AD 2.17 ATS AIRSPACE		
1	Designation and lateral limits	QUEEN ALIA CTR 315256N0362529E 313129N0363034E 312821N0354758E 314256N0354259E 315256N0354716E 315256N0362529E
2	Vertical limits	SFC to 5500 FT ALT
3	Airspace classification	C
4	ATS unit call sign Language(s)	Queen Alia TWR English, Arabic
5	Transition altitude	13000 FT AMSL
6	Remarks	Nil

OJAI AD 2.18 ATS COMMUNICATION FACILITIES				
Service designation	**Call Sign**	**Frequency**	**Hours of operation**	**Remarks**
1	**2**	**3**	**4**	**5**
APP	Amman Approach	128.9 MHZ	H24	Primary Frequency
		121.5 MHZ	H24	Emergency
TWR	Queen Alia TWR	119.8 MHZ	H24	Primary Frequency
		121.5 MHZ	H24	Emergency Frequency
	SMC	121.6 MHZ	H24	Fire Fighting Vehicles
	SMC	121.9 MHZ	H24	Used for aircraft

OJAI AD 2.19 RADIO NAVIGATION AND LANDING AIDS						
Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/MLS , give declination)	**ID**	**FREQ**	**Hours of operation**	**Position of transmitting antenna coordinates**	**Elevation of DME transmitting antenna**	**Remarks**
1	**2**	**3**	**4**	**5**	**6**	**7**
NDB	MDB	399 KHZ	H24	314233.51N 355100.84E		Out put power 62.5 Watts
DVOR/ DME	QAA	115.2 MHZ CH99X	H24	314423N 360927E	834M	7.3 NM FM THR RWY 26L
LOC RWY 08L ILS CAT II	IQAN	109.3 MHZ	H24	314357.63N 360038.20E		292M FM THR RWY 26R.
GP RWY 08L	Dots/Dashes	332.00 MHZ	H24	314342.11N 355822.31E		Angle 3 DEG.
DME	IQAN	991.00 MHZ CH 30X	H24	314342.11N 355822.31E	727M Including Antenna	345M FM THR RWY 08L. 125M FM CL RWY 08L.
LOC RWY 26R ILS CAT II	IQAR	111.10 MHZ	H24	314335.09N 355802.35E		207M FM THR RWY 08L
GP RWY 26R	Dots/Dashes	331.70 MHZ	H24	314358.25N 360015.05E		Angel 3 DEG. RDH 15.7M
DME	IQAR	1009.00 MHZ CH 48X	H24	314358.25N 360015.05E	737M Including Antenna	300M FM THR RWY 26R. 120M FM CL RWY 26R.
LOC RWY 26L ILS CAT II	IQA	110.90 MHZ	H24	314250.08N 355838.18E		310M FM THR RWY 08R.
GP RWY 26L	Dots/Dashes	330.80 MHZ	H24	314305.73N 360055.66E		Angel 3 DEG. RDH 16.67 M
DME	IQA	1007.00 MHZ CH 46X	H24	314305.73N 360055.66E	727M Including Antenna	332M FM THR RWY 26L. 127M FM CL RWY 26L.

OJAI AD 2.20 LOCAL TRAFFIC REGULATIONS

Regulations applicable to the traffic at aerodrome including:

→ **1. Disabled Aircraft Removal**

1.1 For removal of disabled aircraft from RWY and TWY, airlines and operators should use IATA pooling arrangement.
1.2 The telephone numbers of the office of the aerodrome coordinator of operations are as follows:-

Airport Duty Manager	+962798302555
Out-Source Company	+971506244781

→ **2. Aircraft 180° Turn**

Aircraft 180˚ turn on all aprons is prohibited. All aircrafts must consider ground handling arrangements for push back equipment.

→ **3. Landing Intervals RWY 26L and 08L**

3.1 Landing interval between successive arrivals is 5NM
3.2 Pilots shall use minimum required occupancy time to vacate RWY in the most expeditious manner. Pilots unable to comply with this requirement shall notify ATC prior landing.

4. TWY F and G

Pilots requested to pay extra caution ahead of intersection with service roads while taxing on TWY's Foxtrot and Golf

5. APU Usage

To reduce aircraft engines emission at OJAI, the usage of the aircraft auxiliary power unit (APU) is restricted. All aircrafts parked on any parking stand must have their APU switched off, all traffic types concerned, including, but not limited to, commercial, cargo, technical. General aviation, etc.
At contact and remote parking stand, APU usage is authorized within 10 minutes maximum after block-in to allow the ground handler to connect the aircraft to the bridge mounted 400hz, or to the mobile GPU unit, and if needed to the bridge mounted PCA, or to the mobile ACU unit.
APU is authorized 10 minutes maximum prior to TOBT to allow the ground handler to disconnect the 400hz/PCA/GPU/ACU from the aircraft. APU might be used, in case of very high temperature requesting additional power, or in case of no available GPU/ACU unit on remote stand, if shared with ATC and airport ground operations

OJAI AD 2.21 NOISE ABATEMENT PROCEDURE

NIL

OJAI AD 2.22 FLIGHT PROCEDURES

Local Flying Regulations: Controlled VFR flight – PPR

OJAI AD 2.23 ADDITIONAL INFORMATION

NIL

Reserved page

OJAI AD 2.24 CHARTS RELATED TO AN AERODROME		
No.	**CHART TYPE**	**PAGE NR**
1.	AERODROME CHART - ICAO	AD 2.24.1-1
2.	AIRCRAFT PARKING/DOCKING CHART - ICAO	AD 2.24.2-1
3.	AIRCRAFT PARKING/DOCKING CHART ICAO-NORTH APRON	AD 2.24.2-2
4.	AIRCRAFT PARKING/DOCKING CHART ICAO-SOUTH APRON	AD 2.24.2-3
5.	AIRCRAFT PARKING/DOCKING CHART ICAO-HOTEL APRON	AD 2.24.2-4
6.	AIRCRAFT PARKING/DOCKING CHART -CARGO APRON	AD 2.24.2-5
7.	AIRCRAFT PARKING/DOCKING CHART ICAO-ROYAL PAVILION APRON	AD 2.24.2-6
8.	AERODROME OBSTACLE CHART - ICAO - TYPE A RWY 08L	AD 2.24.4-1
9.	AERODROME OBSTACLE CHART - ICAO - TYPE A RWY 08R	AD 2.24.4-2
10.	AERODROME OBSTACLE CHART - ICAO - TYPE A RWY 26L	AD 2.24.4-3
11.	AERODROME OBSTACLE CHART - ICAO - TYPE A RWY 26R	AD 2.24.4-4
12.	PRECISION APPROACH TERRAIN CHART – ICAO RWY 26L	AD 2.24.5-1
13.	PRECISION APPROACH TERRAIN CHART – ICAO RWY 26R	AD 2.24.5-5
14.	PRECISION APPROACH TERRAIN CHART – ICAO RWY 08L	AD 2.24.5-7
15.	STANDARD DEPARTURE CHART INSTRUMENT - ICAO - RNAV RWY 08L/R	AD 2.24.6-1
16.	STANDARD DEPARTURE CHART INSTRUMENT - ICAO - RNAV RWY 26L/R	AD 2.24.6-9
17.	STANDARD DEPARTURE CHART INSTRUMENT - ICAO - RWY 08L/R	AD 2.24.6-17
18.	STANDARD DEPARTURE CHART INSTRUMENT - ICAO - RWY 26L/R	AD 2.24.6-21
19.	STANDARD ARRIVAL CHART INSTRUMENT - ICAO - RNAV RWY 08L/R	AD 2.24.7-1
20.	STANDARD ARRIVAL CHART INSTRUMENT - ICAO - RNAV RWY 26L/R	AD 2.24.7-7
21.	STANDARD ARRIVAL CHART INSTRUMENT - ICAO - RWY 08/26	AD 2.24.7-13
22.	INSTRUMENT APPROACH CHART - ICAO - RNP RWY 08L	AD 2.24.8-1
23.	INSTRUMENT APPROACH CHART - ICAO - RNP RWY 08R	AD 2.24.8-5
24.	INSTRUMENT APPROACH CHART - ICAO - RNP RWY 26L	AD 2.24.8-9
25.	INSTRUMENT APPROACH CHART - ICAO - RNP RWY 26R	AD 2.24.8-13
26.	INSTRUMENT APPROACH CHART - ICAO - ILS Z RWY 08L	AD 2.24.8-17
27.	INSTRUMENT APPROACH CHART - ICAO - ILS Z RWY 26L	AD 2.24.8-21
28.	INSTRUMENT APPROACH CHART - ICAO - ILS Z RWY 26R	AD 2.24.8-25
29.	INSTRUMENT APPROACH CHART - ICAO - ILS Y RWY 08L	AD 2.24.8-29
30.	INSTRUMENT APPROACH CHART - ICAO - ILS Y RWY 26L	AD 2.24.8-33
31.	INSTRUMENT APPROACH CHART - ICAO - ILS Y RWY 26R	AD 2.24.8-35
32.	INSTRUMENT APPROACH CHART - ICAO – VOR RWY 08R	AD 2.24.8-37
33.	INSTRUMENT APPROACH CHART - ICAO – VOR RWY 26L	AD 2.24.8-39