Exercise 3: Worked solutions

Electrical Engineering I · Module 92315 · Exercise 3

From Fundamentals to AI Apocalypse · personal study guide

Contents

Task 7: Electric field of a uniformly charged sphere **2**

Task 8: Parallel plates with a dielectric cylinder **3**

Answers **4**


Made by Thanate Amornjiraporn (Focus)

Try each part before opening the answer. We use symmetry to choose Gaussian surfaces, then split the capacitor into the dielectric core and the air annulus.

Task 7: Electric field of a uniformly charged sphere

A spherical volume charge has density ρ_0 for $0 \leq r \leq a$ and zero outside. Its centre is the origin. Find the field everywhere in vacuum, where $D = \epsilon_0 E$.

Connected topic: Gauss's law (§1.10) turns spherical symmetry into a flux equation on a concentric sphere.



Enclosed charge depends on the Gaussian radius. Inside the material only the smaller sphere contributes; outside it, the entire charged sphere is enclosed.

7: Field inside and outside

Try first: choose a concentric spherical Gaussian surface of radius r, and find its enclosed charge separately for $r \leq a$ and $r > a$.


Answers: see "Task 7: Electric field of a uniformly charged sphere" under Answers at the end.

Made by Thanate Anorrijiraporn (Focus)

Task 8: Parallel plates with a dielectric cylinder

Two circular metal plates have radius a_2 and separation h. A concentric dielectric cylinder of radius a_1 fills the gap between the plates; the annular region from a_1 to a_2 is air. The source assumes uniform axial fields in both regions and neglects fringing at the plate edge.

Connected topics: Capacitance (§1.13) relates charge and voltage; field energy (§1.14) gives the stored energy. Interpret ϵ_1 as the absolute permittivity of the cylinder, as distinguished from ϵ_0 for air in the figure.



Two materials share the same plate voltage. The axial field is uniform within each region; the radial material boundary separates the dielectric core from the air annulus.

The source labels the applied voltage U_{10} with an arrow from the upper plate to the lower one. Use the standard convention $U_{10} = V_1 - V_0$, upper minus lower; for positive U_{10}, the field points down, along $-e_z$.

8a: Field between the plates

Try first: relate the potential difference to the axial field, then use tangential-field continuity at the cylindrical material boundary.

Answers: see "Task 8: Parallel plates with a dielectric cylinder" under Answers at the end.

8b: Charge on the underside of the upper plate

Try first: find the free surface charge density in each patch from D = εE and the normal pointing from the upper conductor into the gap.

Answers: see "Task 8: Parallel plates with a dielectric cylinder" under Answers at the end.

8c: Capacitance

Try first: divide the upper-plate charge by the applied voltage.

Answers: see "Task 8: Parallel plates with a dielectric cylinder" under Answers at the end.

8d: Energy change when the dielectric is removed

Try first: compute the initial and final capacitances, then compare their field energies at the same fixed voltage.

Answers: see "Task 8: Parallel plates with a dielectric cylinder" under Answers at the end.

Made by Thalate Amornjitboorn (Focus)

Answers

Made by Thanate Amornjiraporn (Focus)

Task 7: Electric field of a uniformly charged sphere

7 · Gauss's law in the two regions

1. Spherical symmetry makes the field radial and equally strong everywhere on a concentric Gaussian sphere. Its area is $4\pi r^2$, so the flux law reduces to:

$$\oiint D \cdot \mathrm{d}A \;=\; D_{\mathrm{r}}(r)\, 4\pi r^2 \;=\; Q_{\mathrm{enc}}(r)$$

   Since $D = \epsilon_0 E$, solving this gives E_{r} once we know the enclosed charge.

2. For $0 < r \le a$, the Gaussian sphere contains only a smaller volume of the uniform density. The spherical volume is $\dfrac{4\pi r^3}{3}$:

$$Q_{\mathrm{enc}}(r) \;=\; \rho_0 \frac{4\pi r^3}{3}$$

3. Substitute that enclosed charge into Gauss's law and divide by $4\pi\epsilon_0 r^2$:

$$E_{\mathrm{r}}(r) \;=\; \frac{Q_{\mathrm{enc}}}{4\pi\varepsilon_0 r^2} \;=\; \frac{\rho_0 r}{3\varepsilon_0}, \qquad 0 \le r \le a$$

4. For $r > a$, the Gaussian sphere encloses all the charge, whose volume is the full sphere of radius a:

$$Q_{\mathrm{total}} \;=\; \rho_0 \frac{4\pi a^3}{3}; \qquad E_{\mathrm{r}}(r) \;=\; \frac{\rho_0 a^3}{3\varepsilon_0 r^2}, \qquad r > a$$

5. **Result:** for the positive density shown, the vector field points radially outward. Inside:


$$E(r) \;=\; \frac{\rho_0 r}{3\varepsilon_0} e_{\mathrm{r}}, \qquad 0 \le r \le a$$

   Outside, all charge is enclosed:

$$E(r) \;=\; \frac{\rho_0 a^3}{3\varepsilon_0 r^2} e_{\mathrm{r}}, \qquad r > a$$

   At the origin, $E = 0$; negative ρ_0 reverses the radial direction.

   Check: both formulas give $E(a) = \dfrac{\rho_0 a}{3\varepsilon_0}$, so the field is continuous at the surface. Far away it falls as $\dfrac{1}{r^2}$, as if the total charge were concentrated at the centre. With SI inputs, E is in N/C.



Field strength against radius. Inside the sphere the enclosed charge grows as r^3, so E_{r} rises linearly; outside it falls as $\dfrac{1}{r^2}$. The two pieces meet at $r = a$ with no jump.

Task 8: Parallel plates with a dielectric cylinder

8a · One voltage, two regions

1. The field is uniform and axial in each region. Moving from the lower plate at z = 0 to the upper plate at z = h gives the upper-minus-lower potential:

$$U_{10} = V_1 - V_0 = -\int_0^{\mathrm{h}} E_{\mathrm{z}}\,\mathrm{d}z$$

2. The radial boundary at $\rho = a_1$ is parallel to the z-directed field. Its tangential field component is continuous, so the assumed axial components agree:

$$E_1 = E_2 = E_{\mathrm{z}}$$

3. Because each field is uniform over the gap, the integral is $E_{\mathrm{z}}h$. Solve for the common component:

$$E_1 = E_2 = -\frac{U_{10}}{h}$$

4. **Result:** in the requested gap (not inside the metal), the field is the same everywhere:

$$E = -\frac{U_{10}}{h}\,e_z, \qquad 0 \le \rho \le a_2, \qquad 0 < z < h$$

The same field applies on both sides of $\rho = a_1$ under the uniform-field approximation. The material changes D, not this tangential E.

Check: E has units V/m. For positive upper-minus-lower voltage, potential decreases in the +z direction, so E points downward.

Made by Thana

Task 8: Parallel plates with a dielectric cylinder

8b · Add the two material patches

1. The outward normal from the lower face of the upper metal plate into the gap is $-e_z$. The conductor boundary relation gives free surface charge density $\sigma_f = D \cdot n$. Since $E = -(\frac{U_{10}}{h})e_z$, each patch has positive σ for positive U_{10}.
2. Over the dielectric circle, $D = \epsilon_1 E$; its area is $\pi {a_1}^2$:

$$Q_{core} = \sigma_1 \pi a_1^2 = \frac{\varepsilon_1 U_{10}}{h} \pi a_1^2$$

3. Over the air annulus, $D = \epsilon_0 E$; its area is the whole plate disk minus the core disk:

$$Q_{air} = \sigma_2 \pi (a_2^2 - a_1^2) = \frac{\varepsilon_0 U_{10}}{h} \pi (a_2^2 - a_1^2)$$

4. Add the two disjoint patches on the same metal face:

$$Q = Q_{core} + Q_{air} = \frac{\pi U_{10}}{h} [\varepsilon_1 a_1^2 + \varepsilon_0 (a_2^2 - a_1^2)]$$

Result: this is the charge on the underside of the upper plate. For positive U_{10} it is positive; the lower plate carries the opposite charge.

Check: each term has permittivity × voltage × area / length, which is coulombs. If $a_1 = 0$ the full plate is air; if $a_1 = a_2$ it is fully filled by the dielectric.

Task 8: Parallel plates with a dielectric cylinder

8c · Charge-to-voltage ratio

1. Capacitance is defined by $C = \frac{Q}{U}$. Divide the expression from 8b by U_{10}:

$$C = \frac{\pi}{h} [\varepsilon_1 a_1^2 + \varepsilon_0 (a_2^2 - a_1^2)]$$

2. **Result:** this is the capacitance under the stated uniform-field model. The two regions behave like capacitors in parallel because they span the same voltage and their charges add.

   Check: it equals the sum of area/permittivity contributions divided by h; capacitance has units farads.

Task 8: Parallel plates with a dielectric cylinder

8d · Fixed-voltage energy change

1. Initially the capacitance is the value from 8c. After removal, the whole plate area is air:

$$C_{\mathrm{i}} = \frac{\pi}{h}[\varepsilon_1 a_1^2 + \varepsilon_0(a_2^2 - a_1^2)]; \quad C_{\mathrm{f}} = \frac{\varepsilon_0 \pi a_2^2}{h}$$

2. With voltage held fixed, stored field energy is $W = \frac{1}{2} C\ U^2$. Subtract the initial energy from the final energy:

$$\Delta W_{\mathrm{field}} = \tfrac{1}{2}(C_{\mathrm{f}} - C_{\mathrm{i}})U_{10}^2$$

3. The air-region terms cancel, leaving the contribution from the removed core:

$$\Delta W_{\mathrm{field}} = -\frac{\pi a_1^2(\varepsilon_1 - \varepsilon_0)}{2h} U_{10}^2$$

4. Follow the energy that leaves. With U_{10} fixed, the plate charge changes by $\Delta Q = (C_{\mathrm{f}} - C_{\mathrm{i}})U_{10} < 0$, so charge flows back into the source. The energy the source delivers is $W_{\mathrm{source}} = U_{10}\Delta Q = 2\Delta W_{\mathrm{field}}$, a negative number: the source takes energy back. Whoever pulls the core out supplies the difference:

$$W_{\mathrm{mech}} = \Delta W_{\mathrm{field}} - W_{\mathrm{source}} = -\Delta W_{\mathrm{field}} = \frac{\pi a_1^2(\varepsilon_1 - \varepsilon_0)}{2h} U_{10}^2$$

5. **Result:** if $\epsilon_1 > \epsilon_0$, the stored field energy decreases by this amount ($\Delta W_{\mathrm{field}} < 0$), measured in joules. Positive mechanical work of the same size is needed to pull the core out: at fixed voltage the field draws the dielectric into the gap, and the source takes back twice the field-energy drop.

   Check: if the core is indistinguishable from air, $\varepsilon_1 = \varepsilon_0$, the change is zero. The magnitude scales with the removed area and with voltage squared.

Made by Th

Personal worked-solution guide based on the supplied EEI Exercise 3 sheet, written in my own words; no exercise text or figures are reproduced. Not an official FAU publication; check course details against current material. Made by **Thanate Amornjiraporn (Focus)**.