

# Lecture 9: Object Detection and Image Segmentation

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 1

April 30, 2024

Recall: Image Classification: A core task in Computer Vision



(assume given a set of possible labels)  
{dog, cat, truck, plane, ...}

cat

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 6

April 30, 2024


## Computer Vision Tasks

Classification



CAT

Semantic  
Segmentation



GRASS, CAT, TREE,  
SKY

No spatial extent

Object  
Detection



DOG, DOG, CAT

Instance  
Segmentation



DOG, DOG, CAT

This image is CC0 public domain

No objects, just pixels


## Semantic Segmentation

Classification



CAT

Semantic  
Segmentation



GRASS, CAT, TREE,  
SKY

No spatial extent

Object  
Detection



DOG, DOG, CAT

Instance  
Segmentation



DOG, DOG, CAT

No objects, just pixels

Multiple Object

Multiple Object


April 30, 2024

April 30, 2024

## Semantic Segmentation: The Problem



GRASS, CAT, TREE,  
SKY, ...



At test time, classify each pixel of a new image.

Paired training data: for each training image, each pixel is labeled with a semantic category.

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 9

April 30, 2024

## Semantic Segmentation Idea: Sliding Window



Full image

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 10

April 30, 2024

## Semantic Segmentation Idea: Sliding Window



Full image

Impossible to classify without context


Q: how do we include context?

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 11

April 30, 2024

## Semantic Segmentation Idea: Sliding Window



Full image


Q: how do we model this?

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 12

April 30, 2024

## Semantic Segmentation Idea: Sliding Window




Farabet et al., "Learning Hierarchical Features for Scene Labeling," TPAMI 2013  
Pinheiro and Collobert, "Recurrent Convolutional Neural Networks for Scene Labeling", ICML 2014

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 13

April 30, 2024

## Semantic Segmentation Idea: Sliding Window




Farabet et al., "Learning Hierarchical Features for Scene Labeling," TPAMI 2013  
Pinheiro and Collobert, "Recurrent Convolutional Neural Networks for Scene Labeling", ICML 2014

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 14

April 30, 2024

## Semantic Segmentation Idea: Convolution



An intuitive idea: encode the entire image with conv net, and do semantic segmentation on top.


Problem: classification architectures often reduce feature spatial sizes to go deeper, but semantic segmentation requires the output size to be the same as input size.

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 15

April 30, 2024

## Semantic Segmentation Idea: Fully Convolutional




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 16

April 30, 2024

## Semantic Segmentation Idea: Fully Convolutional

Design a network with only convolutional layers without downsampling operators to make predictions for pixels all at once!




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 17

April 30, 2024

## Semantic Segmentation Idea: Fully Convolutional

Design network as a bunch of convolutional layers, with **downsampling** and **upsampling** inside the network!



Long, Shelhamer, and Darrell, "Fully Convolutional Networks for Semantic Segmentation", CVPR 2015  
Noh et al., "Learning Deconvolution Network for Semantic Segmentation", ICCV 2015

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 18

April 30, 2024


## Semantic Segmentation Idea: Fully Convolutional

Downsampling:  
Pooling, stride convolution



Input:  
 $3 \times H \times W$

Design network as a bunch of convolutional layers, with **downsampling** and **upsampling** inside the network!



Long, Shelhamer, and Darrell, "Fully Convolutional Networks for Semantic Segmentation", CVPR 2015  
Noh et al., "Learning Deconvolution Network for Semantic Segmentation", ICCV 2015

Fei-Fei Li, Ehsan Adeli

Lecture 11 - 19

April 30, 2024

## In-Network upsampling: “Unpooling”

Nearest Neighbor

1	1	2	2
1	1	2	2
3	3	4	4

Input:  $2 \times 2$

1	1	2	2
1	1	2	2
3	3	4	4
3	3	4	4

Output:  $4 \times 4$

“Bed of Nails”

1	2		
0	0	0	0
3	4		

Input:  $2 \times 2$

1	0	2	0
0	0	0	0
3	0	4	0
0	0	0	0


Output:  $4 \times 4$

Fei-Fei Li, Ehsan Adeli


Lecture 11 - 20

April 30, 2024


## In-Network upsampling: “Max Unpooling”




## Learnable Upsampling



## Learnable Upsampling




## Learnable Upsampling



## Learnable Upsampling

Recall: Normal 3 x 3 convolution, stride 2 pad 1




Input: 4 x 4



Output: 2 x 2

## Learnable Upsampling

Recall: Normal 3 x 3 convolution, stride 2 pad 1



Input: 4 x 4


Dot product  
between filter  
and input



Output: 2 x 2

## Learnable Upsampling

Recall: Normal 3 x 3 convolution, stride 2 pad 1



Input: 4 x 4

Dot product  
between filter  
and input



Output: 2 x 2

Filter moves 2 pixels in the input for every one pixel in the output

Stride gives ratio between movement in input and output


We can interpret strided convolution as “learnable downsampling”.

## Learnable Upsampling: Transposed Convolution

3 x 3 transposed convolution, stride 2 pad 1




Input: 2 x 2



Output: 4 x 4

## Learnable Upsampling: Transposed Convolution

3 x 3 transposed convolution, stride 2 pad 1




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 29

April 30, 2024

## Learnable Upsampling: Transposed Convolution

3 x 3 transposed convolution, stride 2 pad 1




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 30

April 30, 2024

## Learnable Upsampling: Transposed Convolution

3 x 3 transposed convolution, stride 2 pad 1




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 31

April 30, 2024

## Learnable Upsampling: Transposed Convolution

3 x 3 transposed convolution, stride 2 pad 1




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 32

April 30, 2024

## Learnable Upsampling: 1D Example




Fei-Fei Li, Ehsan Adeli

Lecture 11 - 33

April 30, 2024

## Convolution layer




François Fleuret

Deep learning / 7.1. Transposed convolutions

5 / 14

## Transposed convolution layer




François Fleuret

Deep learning / 7.1. Transposed convolutions

6 / 14





## Transposed convolution layer









François Fleuret

Deep learning / 7.1. Transposed convolutions

6 / 14







## Convolution as Matrix Multiplication (1D Example)

We can express convolution in terms of a matrix multiplication

$$\vec{x} * \vec{a} = X\vec{a}$$

$$\begin{bmatrix} x & y & z & 0 & 0 & 0 \\ 0 & 0 & x & y & z & 0 \end{bmatrix} \begin{bmatrix} 0 \\ a \\ b \\ c \\ d \\ 0 \end{bmatrix} = \begin{bmatrix} ay + bz \\ bx + cy + dz \end{bmatrix}$$

Example: 1D conv, kernel size=3, stride=2, padding=1

## Convolution as Matrix Multiplication (1D Example)

We can express convolution in terms of a matrix multiplication

$$\vec{x} * \vec{a} = X\vec{a}$$

$$\begin{bmatrix} x & y & z & 0 & 0 & 0 \\ 0 & 0 & x & y & z & 0 \end{bmatrix} \begin{bmatrix} 0 \\ a \\ b \\ c \\ d \\ 0 \end{bmatrix} = \begin{bmatrix} ay + bz \\ bx + cy + dz \end{bmatrix}$$

Example: 1D conv, kernel size=3, stride=2, padding=1

Transposed convolution multiplies by the transpose of the same matrix:

$$\vec{x} *^T \vec{a} = X^T \vec{a}$$

$$\begin{bmatrix} x & 0 \\ y & 0 \\ z & x \\ 0 & y \\ 0 & z \\ 0 & 0 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ d \\ 0 \end{bmatrix} = \begin{bmatrix} ax \\ ay \\ az + bx \\ by \\ bz \\ 0 \end{bmatrix}$$

Example: 1D transposed conv, kernel size=3, stride=2, padding=0


## Semantic Segmentation Idea: Fully Convolutional

Downsampling:  
Pooling, strided convolution



Input:  
 $3 \times H \times W$

Design network as a bunch of convolutional layers, with  
downsampling and upsampling inside the network!



Upsampling:  
Unpooling or strided transposed convolution



Predictions:  
 $H \times W$

Long, Shelhamer, and Darrell, "Fully Convolutional Networks for Semantic Segmentation", CVPR 2015  
Noh et al., "Learning Deconvolution Network for Semantic Segmentation", ICCV 2015

Fei-Fei Li, Ehsan Adeli


Lecture 11 - 36

April 30, 2024

## Semantic Segmentation

Label each pixel in the image with a category label

Don't differentiate instances, only care about pixels



Fei-Fei Li, Ehsan Adeli

Lecture 11 - 38

April 30, 2024