Lecture 9: Object Detection and Image Segmentation

Object Detection: Single Object
(Classification + Localization)



Object Detection: Single Object
(Classification + Localization)



Treat localization as a regression problem!

Object Detection: Single Object
(Classification + Localization)



Treat localization as a regression problem!

Object Detection



Object Detection: Multiple Objects



Object Detection: Multiple Objects

Each image needs a different number of outputs!



Object Detection: Multiple Objects

Apply a CNN to many different crops of the image, CNN classifies each crop as object or background



Object Detection: Multiple Objects

Apply a CNN to many different crops of the image, CNN classifies each crop as object or background



Dog? YES
Cat? NO
Background? NO

Object Detection: Multiple Objects

Apply a CNN to many different crops of the image, CNN classifies each crop as object or background



Dog? YES
Cat? NO
Background? NO

Object Detection: Multiple Objects

Apply a CNN to many different crops of the image, CNN classifies each crop as object or background



Dog? NO
Cat? YES
Background? NO

Q: What's the problem with this approach?

Object Detection: Multiple Objects

Apply a CNN to many different crops of the image, CNN classifies each crop as object or background





Dog? NO
Cat? YES
Background? NO

Problem: Need to apply CNN to huge number of locations, scales, and aspect ratios, very computationally expensive!

Region Proposals: Selective Search

- Find "blobby" image regions that are likely to contain objects
- Relatively fast to run; e.g. Selective Search gives 2000 region proposals in a few seconds on CPU



Alexe et al, "Measuring the objectness of image windows", TPAMI 2012
Uijlings et al, "Selective Search for Object Recognition", IJCV 2013
Cheng et al, "BING: Binarized normed gradients for objectness estimation at 300fps", CVPR 2014
Zitnick and Dollar, "Edge boxes: Locating object proposals from edges", ECCV 2014

R-CNN

Input image

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN

Regions of Interest (RoI) from a proposal method (~2k)

Input image

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN



Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Input image

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN



Forward each region through ConvNet (ImageNet-pretranied)

Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN



Classify regions with SVMs

Forward each region through ConvNet (ImageNet-pretranied)

Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN

Predict "corrections" to the RoI: 4 numbers: (dx, dy, dw, dh)



Classify regions with SVMs

Forward each region through ConvNet (ImageNet-pretranied)

Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

R-CNN

Predict "corrections" to the RoI: 4 numbers: (dx, dy, dw, dh)



Classify regions with SVMs

Forward each region through ConvNet

Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Problem: Very slow! Need to do ~2k independent forward passes for each image!

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

"Slow" R-CNN

Predict "corrections" to the RoI: 4 numbers: (dx, dy, dw, dh)



Classify regions with SVMs

Forward each region through ConvNet

Warped image regions (224x224 pixels)

Regions of Interest (RoI) from a proposal method (~2k)

Problem: Very slow! Need to do ~2k independent forward passes for each image!

Idea: Pass the image through convnet before cropping! Crop the conv feature instead!

Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN

Input image

"Slow" R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN

"Backbone" network: AlexNet, VGG, ResNet, etc



"Slow" R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN

Regions of Interest (RoIs) from a proposal method

"Backbone" network: AlexNet, VGG, ResNet, etc



"Slow" R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Fast R-CNN



Girshick, "Fast R-CNN", ICCV 2015. Figure copyright Ross Girshick, 2015; source. Reproduced with permission.

Cropping Features: RoI Pool



Girshick, "Fast R-CNN", ICCV 2015.

Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Girshick, "Fast R-CNN", ICCV 2015.

Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Q: how do we resize the 512 x 5 x 4 region to, e.g., a 512 x 2 x 2 tensor?.

Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Divide into 2x2 grid of (roughly) equal subregions

Q: how do we resize the 512 x 5 x 4 region to, e.g., a 512 x 2 x 2 tensor?.

Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Girshick, "Fast R-CNN", ICCV 2015.

Cropping Features: RoI Pool



Girshick, "Fast R-CNN", ICCV 2015.

Problem: Region features slightly misaligned

Cropping Features: RoI Align



He et al, "Mask R-CNN", ICCV 2017

Cropping Features: RoI Align

Sample at regular points in each subregion using bilinear interpolation



He et al, "Mask R-CNN", ICCV 2017

Cropping Features: RoI Align



He et al, "Mask R-CNN", ICCV 2017

Cropping Features: RoI Align



$$f_{xy} = \sum_{i,j=1}^{2} f_{i,j} \max(0, 1 - |x - x_i|) \max(0, 1 - |y - y_j|)$$

He et al, "Mask R-CNN", ICCV 2017

Cropping Features: RoI Align



He et al, "Mask R-CNN", ICCV 2017

R-CNN vs Fast R-CNN



Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
He et al, "Spatial pyramid pooling in deep convolutional networks for visual recognition", ECCV 2014
Girshick, "Fast R-CNN", ICCV 2015

R-CNN vs Fast R-CNN



Girshick et al, "Rich feature hierarchies for accurate object detection and semantic segmentation", CVPR 2014.
He et al, "Spatial pyramid pooling in deep convolutional networks for visual recognition", ECCV 2014
Girshick, "Fast R-CNN", ICCV 2015

Faster R-CNN:

Make CNN do proposals!

Insert Region Proposal Network (RPN) to predict proposals from features

Otherwise same as Fast R-CNN: Crop features for each proposal, classify each one



Ren et al, "Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks", NIPS 2015
Figure copyright 2015, Ross Girshick; reproduced with permission

Region Proposal Network



Input Image
(e.g. 3 x 640 x 480)

Image features
(e.g. 512 x 20 x 15)

Region Proposal Network

Imagine an anchor box of fixed size at each point in the feature map



Input Image
(e.g. 3 x 640 x 480)

Image features
(e.g. 512 x 20 x 15)

Region Proposal Network

Imagine an anchor box of fixed size at each point in the feature map



At each point, predict whether the corresponding anchor contains an object (binary classification)

Region Proposal Network

Imagine an anchor box of fixed size at each point in the feature map



For positive boxes, also predict a corrections from the anchor to the ground-truth box (regress 4 numbers per pixel)

Region Proposal Network

In practice use K different anchor boxes of different size / scale at each point



Region Proposal Network

In practice use K different anchor boxes of different size / scale at each point



Sort the K*20*15 boxes by their “objectness” score, take top ~300 as our proposals

Faster R-CNN:

Make CNN do proposals!

Jointly train with 4 losses:

1. RPN classify object / not object
2. RPN regress box coordinates
3. Final classification score (object classes)
4. Final box coordinates



Ren et al, "Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks", NIPS 2015
Figure copyright 2015, Ross Girshick; reproduced with permission

Faster R-CNN:

Make CNN do proposals!



Faster R-CNN:

Make CNN do proposals!

Glossing over many details:

- Ignore overlapping proposals with non-max suppression
- How are anchors determined?
- How do we sample positive / negative samples for training the RPN?
- How to parameterize bounding box regression?



Ren et al, "Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks", NIPS 2015
Figure copyright 2015, Ross Girshick; reproduced with permission

Faster R-CNN:

Make CNN do proposals!

Faster R-CNN is a
Two-stage object detector

First stage: Run once per image
- Backbone network
- Region proposal network

Second stage: Run once per region
- Crop features: RoI pool / align
- Predict object class
- Prediction bbox offset



Faster R-CNN:
Make CNN do proposals!

Do we really need the second stage?

Faster R-CNN is a Two-stage object detector

First stage: Run once per image
- Backbone network
- Region proposal network

Second stage: Run once per region
- Crop features: RoI pool / align
- Predict object class
- Prediction bbox offset



Single-Stage Object Detectors: YOLO / SSD / RetinaNet

Input image
3 x H x W



Divide image into grid
7 x 7

Image a set of base boxes centered at each grid cell
Here B = 3

Within each grid cell:
- Regress from each of the B base boxes to a final box with 5 numbers: (dx, dy, dh, dw, confidence)
- Predict scores for each of C classes (including background as a class)
- Looks a lot like RPN, but category-specific!

Output:
7 x 7 x (5 * B + C)

Redmon et al, "You Only Look Once: Unified, Real-Time Object Detection", CVPR 2016
Liu et al, "SSD: Single-Shot MultiBox Detector", ECCV 2016
Lin et al, "Focal Loss for Dense Object Detection", ICCV 2017

YOLO– real-time object detection



Redmon et al. "You only look once: unified, real-time object detection (2015)."

Object Detection: Lots of variables ...

Backbone Network
VGG16
ResNet-101
Inception V2
Inception V3
Inception ResNet
MobileNet

"Meta-Architecture"
Two-stage: Faster R-CNN
Single-stage: YOLO / SSD
Hybrid: R-FCN

Image Size
Region Proposals
…

Takeaways
Faster R-CNN is slower but more accurate

SSD is much faster but not as accurate

Bigger / Deeper backbones work better

Huang et al, "Speed/accuracy trade-offs for modern convolutional object detectors", CVPR 2017

R-FCN: Dai et al, "R-FCN: Object Detection via Region-based Fully Convolutional Networks", NIPS 2016
Inception-V2: Ioffe and Szegedy, "Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift", ICML 2015
Inception V3: Szegedy et al, "Rethinking the Inception Architecture for Computer Vision", arXiv 2016
Inception ResNet: Szegedy et al, "Inception-V4, inception-ResNet and the Impact of Residual Connections on Learning", arXiv 2016
MobileNet: Howard et al, "Efficient Convolutional Neural Networks for Mobile Vision Applications", arXiv 2017

Object Detection: Lots of variables ...

Backbone Network
VGG16
ResNet-101
Inception V2
Inception V3
Inception ResNet
MobileNet

"Meta-Architecture"
Two-stage: Faster R-CNN
Single-stage: YOLO / SSD
Hybrid: R-FCN

Image Size
Region Proposals
…

Takeaways
Faster R-CNN is slower but more accurate

SSD is much faster but not as accurate

Bigger / Deeper backbones work better

Huang et al, "Speed/accuracy trade-offs for modern convolutional object detectors", CVPR 2017
Zou et al, "Object Detection in 20 Years: A Survey", arXiv 2019

R-FCN: Dai et al, "R-FCN: Object Detection via Region-based Fully Convolutional Networks", NIPS 2016
Inception-V2: Ioffe and Szegedy, "Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift", ICML 2015
Inception V3: Szegedy et al, "Rethinking the Inception Architecture for Computer Vision", arXiv 2016
Inception ResNet: Szegedy et al, "Inception-V4, Inception-ResNet and the Impact of Residual Connections on Learning", arXiv 2016
MobileNet: Howard et al, "Efficient Convolutional Neural Networks for Mobile Vision Applications", arXiv 2017

Instance Segmentation



Object Detection: Faster R-CNN



Instance Segmentation: Mask R-CNN



Add a small mask network that operates on each RoI and predicts a 28x28 binary mask

He et al, "Mask R-CNN", ICCV 2017

Mask R-CNN



He et al, "Mask R-CNN", arXiv 2017

Mask R-CNN: Example Mask Training Targets



Mask R-CNN: Example Mask Training Targets



Mask R-CNN: Example Mask Training Targets



Mask R-CNN: Example Mask Training Targets



Mask R-CNN: Very Good Results!

He et al, "Mask R-CNN", ICCV 2017

Mask R-CNN
Also does pose

He et al, "Mask R-CNN", ICCV 2017

Open Source Frameworks

Lots of good implementations on GitHub!

TensorFlow Detection API:
https://github.com/tensorflow/models/tree/master/research/object_detection
Faster RCNN, SSD, RFCN, Mask R-CNN, ...

Detectron2 (PyTorch)
https://github.com/facebookresearch/detectron2
Mask R-CNN, RetinaNet, Faster R-CNN, RPN, Fast R-CNN, R-FCN, ...

Finetune on your own dataset with pre-trained models

DETR (DEtection TRansformer)



Carion et al. "End-to-End Object Detection with Transformers" ECCV 2020

DETR (DEtection TRansformer)



Carion et al. "End-to-End Object Detection with Transformers" ECCV 2020

Recap: Lots of computer vision tasks!