

RWTH Aachen University - LELY Solution Documentation

RWTH Team

June 29, 2022

1 Abstract

Our solution to the LELY Challenge consists of a team of asymmetrical robots. Robot A navigates and maps its environment with use of a 2D LIDAR system. Robot B receives a map of the environment from Robot A and then uses its 3 ultrasonic sensors to navigate.

This document provides an outline of the design of the systems and the thought process behind their development.

2 Robot A

2.1 Overview

Robot A is a LIDAR-capable platform. Due to the walls of the challenge being only 37cm tall, the mounting point of the LIDAR is on the bottom front of the chassis, providing a 200 degree field of view.



Figure 1: The LIDAR sensor and 3D-printed mounting point attached to Robot A

2.2 Sensors

A RPLIDAR A1M8-R6 LIDAR is mounted on the front of the robot. The LIDAR interfaces with the laptop directly over USB.

2.3 Hardware

A 3D-printed mount was created for easy placement and adjustment of the LIDAR.




Figure 2: CAD rendering of LIDAR mount

2.4 Software

Robot A implements a wall following algorithem. Five equally-spaced lines in front of the robot are sampled via LIDAR.

3 Robot B

3.1 Overview

Robot B uses ultrasonic sensors mounted via aluminium frame to navigate its environment.



Figure 3: Robot B with mounting frame, 3D-printed connectors, and ultrasonic sensors

3.2 Sensors

Three HC-SR04 ultrasonic sensors are placed in an array around the robot. The sensors interface with the laptop via an Arduino Uno.

3.3 Hardware

An aluminium frame with 3D-printed connection points extends from the top mounting point to the bottom of the robot, allowing the sensors to attach to a low-enough point to read the walls of the maze.




Figure 4: Robot B with mounting frame, 3D-printed connectors, and ultrasonic sensors




Figure 5: Central mount for connection points

3.4 Software

DESCRIPTION OF SOFTWARE



Figure 6: Central mount with connections for ultrasonic sensors