

barry: Your go-to motif accountant

0.0-1

Generated by Doxygen 1.9.1



<b>1 Main Page</b>	<b>1</b>
<b>2 Module Index</b>	<b>5</b>
2.1 Modules	5
<b>3 Class Index</b>	<b>7</b>
3.1 Class List	7
<b>4 File Index</b>	<b>9</b>
4.1 File List	9
<b>5 Module Documentation</b>	<b>11</b>
5.1 Counting	11
5.1.1 Detailed Description	11
5.2 Statistical Models	11
5.2.1 Detailed Description	12
5.3 DEFMAArray counters	12
5.3.1 Detailed Description	13
5.3.2 Function Documentation	14
5.3.2.1 counter_absdiff()	14
5.3.2.2 counter_ctriads() [1/2]	14
5.3.2.3 counter_ctriads() [2/2]	14
5.3.2.4 counter_degree()	14
5.3.2.5 counter_density()	15
5.3.2.6 counter_diff()	15
5.3.2.7 counter_edges()	15
5.3.2.8 counter_fixed_effect()	15
5.3.2.9 counter_idegree() [1/2]	16
5.3.2.10 counter_idegree() [2/2]	16
5.3.2.11 counter_idegree15() [1/2]	16
5.3.2.12 counter_idegree15() [2/2]	16
5.3.2.13 counter_isolates() [1/2]	17
5.3.2.14 counter_isolates() [2/2]	17
5.3.2.15 counter_istar2() [1/2]	17
5.3.2.16 counter_istar2() [2/2]	17
5.3.2.17 counter_mutual()	17
5.3.2.18 counter_nodecov()	18
5.3.2.19 counter_nodeicov()	18
5.3.2.20 counter_nodematch()	18
5.3.2.21 counter_nodeocov()	18
5.3.2.22 counter_odegree() [1/2]	18
5.3.2.23 counter_odegree() [2/2]	19
5.3.2.24 counter_odegree15() [1/2]	19
5.3.2.25 counter_odegree15() [2/2]	19

5.3.2.26 counter_ones()	19
5.3.2.27 counter_ostar2() [1/2]	20
5.3.2.28 counter_ostar2() [2/2]	20
5.3.2.29 counter_transition()	20
5.3.2.30 counter_ttriads() [1/2]	20
5.3.2.31 counter_ttriads() [2/2]	21
5.3.2.32 NETWORK_COUNTER()	21
5.3.2.33 rules_markov_fixed()	21
5.4 Phylo counters	21
5.4.1 Detailed Description	22
5.4.2 Function Documentation	23
5.4.2.1 counter_co_opt()	23
5.4.2.2 counter_cogain()	23
5.4.2.3 counter_gains()	23
5.4.2.4 counter_gains_from_0()	24
5.4.2.5 counter_gains_k_offspring()	24
5.4.2.6 counter_genes_changing()	24
5.4.2.7 counter_k_genes_changing()	24
5.4.2.8 counter_less_than_p_prop_genes_changing()	25
5.4.2.9 counter_longest()	25
5.4.2.10 counter_loss()	25
5.4.2.11 counter_maxfun()	25
5.4.2.12 counter_neofun()	26
5.4.2.13 counter_neofun_a2b()	26
5.4.2.14 counter_overall_changes()	26
5.4.2.15 counter_overall_gains()	26
5.4.2.16 counter_overall_gains_from_0()	27
5.4.2.17 counter_overall_loss()	27
5.4.2.18 counter_pairwise_first_gain()	27
5.4.2.19 counter_pairwise_neofun_singlefun()	27
5.4.2.20 counter_pairwise_overall_change()	28
5.4.2.21 counter_pairwise_preserving()	28
5.4.2.22 counter_preserve_pseudogene()	28
5.4.2.23 counter_prop_genes_changing()	28
5.4.2.24 counter_subfun()	29
5.5 Phylo rules	29
5.5.1 Detailed Description	29
5.5.2 Function Documentation	29
5.5.2.1 rule_dyn_limit_changes()	29
<b>6 Namespace Documentation</b>	<b>31</b>
6.1 barry Namespace Reference	31

6.1.1 Detailed Description . . . . .	31
6.2 <code>barry::counters</code> Namespace Reference . . . . .	31
6.2.1 Detailed Description . . . . .	31
6.3 <code>barry::counters::defm</code> Namespace Reference . . . . .	32
6.4 <code>barry::counters::network</code> Namespace Reference . . . . .	32
6.5 <code>barry::counters::phylo</code> Namespace Reference . . . . .	32
6.6 CHECK Namespace Reference . . . . .	32
6.6.1 Detailed Description . . . . .	32
6.6.2 Variable Documentation . . . . .	32
6.6.2.1 BOTH . . . . .	32
6.6.2.2 NONE . . . . .	32
6.6.2.3 ONE . . . . .	33
6.6.2.4 TWO . . . . .	33
6.7 EXISTS Namespace Reference . . . . .	33
6.7.1 Detailed Description . . . . .	33
6.7.2 Variable Documentation . . . . .	33
6.7.2.1 AS_ONE . . . . .	33
6.7.2.2 AS_ZERO . . . . .	34
6.7.2.3 BOTH . . . . .	34
6.7.2.4 NONE . . . . .	34
6.7.2.5 ONE . . . . .	34
6.7.2.6 TWO . . . . .	34
6.7.2.7 UNKNOWN . . . . .	34
<b>7 Class Documentation</b> . . . . .	<b>35</b>
7.1 <code>BArray&lt; Cell_Type, Data_Type &gt;</code> Class Template Reference . . . . .	35
7.1.1 Detailed Description . . . . .	37
7.1.2 Constructor & Destructor Documentation . . . . .	38
7.1.2.1 <code>BArray()</code> [1/6] . . . . .	38
7.1.2.2 <code>BArray()</code> [2/6] . . . . .	38
7.1.2.3 <code>BArray()</code> [3/6] . . . . .	38
7.1.2.4 <code>BArray()</code> [4/6] . . . . .	39
7.1.2.5 <code>BArray()</code> [5/6] . . . . .	39
7.1.2.6 <code>BArray()</code> [6/6] . . . . .	39
7.1.2.7 <code>~BArray()</code> . . . . .	39
7.1.3 Member Function Documentation . . . . .	39
7.1.3.1 <code>clear()</code> . . . . .	39
7.1.3.2 <code>col()</code> . . . . .	40
7.1.3.3 <code>D()</code> [1/2] . . . . .	40
7.1.3.4 <code>D()</code> [2/2] . . . . .	40
7.1.3.5 <code>D_ptr()</code> [1/2] . . . . .	40
7.1.3.6 <code>D_ptr()</code> [2/2] . . . . .	40

7.1.3.7 default_val()	40
7.1.3.8 flush_data()	40
7.1.3.9 get_cell()	41
7.1.3.10 get_col_vec() [1/2]	41
7.1.3.11 get_col_vec() [2/2]	41
7.1.3.12 get_entries()	41
7.1.3.13 get_row_vec() [1/2]	41
7.1.3.14 get_row_vec() [2/2]	42
7.1.3.15 insert_cell() [1/3]	42
7.1.3.16 insert_cell() [2/3]	42
7.1.3.17 insert_cell() [3/3]	42
7.1.3.18 is_dense()	42
7.1.3.19 is_empty()	43
7.1.3.20 ncol()	43
7.1.3.21 nnozero()	43
7.1.3.22 nrow()	43
7.1.3.23 operator>() [1/2]	43
7.1.3.24 operator>() [2/2]	43
7.1.3.25 operator*=( )	44
7.1.3.26 operator+=( ) [1/3]	44
7.1.3.27 operator+=( ) [2/3]	44
7.1.3.28 operator+=( ) [3/3]	44
7.1.3.29 operator-=( ) [1/3]	44
7.1.3.30 operator-=( ) [2/3]	44
7.1.3.31 operator-=( ) [3/3]	45
7.1.3.32 operator/=( )	45
7.1.3.33 operator=( ) [1/2]	45
7.1.3.34 operator=( ) [2/2]	45
7.1.3.35 operator==( )	45
7.1.3.36 out_of_range()	45
7.1.3.37 print()	46
7.1.3.38 reserve()	46
7.1.3.39 resize()	46
7.1.3.40 rm_cell()	46
7.1.3.41 row()	46
7.1.3.42 set_data()	46
7.1.3.43 swap_cells()	47
7.1.3.44 swap_cols()	47
7.1.3.45 swap_rows()	47
7.1.3.46 toggle_cell()	47
7.1.3.47 toggle_lock()	48
7.1.3.48 transpose()	48

7.1.3.49 zero_col()	48
7.1.3.50 zero_row()	48
7.1.4 Friends And Related Function Documentation	48
7.1.4.1 BArrayCell< Cell_Type, Data_Type >	48
7.1.4.2 BArrayCell_const< Cell_Type, Data_Type >	49
7.1.5 Member Data Documentation	49
7.1.5.1 visited	49
7.2 BArrayCell< Cell_Type, Data_Type > Class Template Reference	49
7.2.1 Detailed Description	49
7.2.2 Constructor & Destructor Documentation	50
7.2.2.1 BArrayCell()	50
7.2.2.2 ~BArrayCell()	50
7.2.3 Member Function Documentation	50
7.2.3.1 operator Cell_Type()	50
7.2.3.2 operator*=( )	50
7.2.3.3 operator+=( )	51
7.2.3.4 operator-=( )	51
7.2.3.5 operator/=( )	51
7.2.3.6 operator=( )	51
7.2.3.7 operator==( )	51
7.3 BArrayCell_const< Cell_Type, Data_Type > Class Template Reference	52
7.3.1 Detailed Description	52
7.3.2 Constructor & Destructor Documentation	52
7.3.2.1 BArrayCell_const()	52
7.3.2.2 ~BArrayCell_const()	52
7.3.3 Member Function Documentation	53
7.3.3.1 operator Cell_Type()	53
7.3.3.2 operator!=( )	53
7.3.3.3 operator<( )	53
7.3.3.4 operator<=( )	53
7.3.3.5 operator==( )	53
7.3.3.6 operator>( )	54
7.3.3.7 operator>=( )	54
7.4 BArrayDense< Cell_Type, Data_Type > Class Template Reference	54
7.4.1 Detailed Description	57
7.4.2 Constructor & Destructor Documentation	57
7.4.2.1 BArrayDense() [ 1 / 6 ]	57
7.4.2.2 BArrayDense() [ 2 / 6 ]	57
7.4.2.3 BArrayDense() [ 3 / 6 ]	58
7.4.2.4 BArrayDense() [ 4 / 6 ]	58
7.4.2.5 BArrayDense() [ 5 / 6 ]	58
7.4.2.6 BArrayDense() [ 6 / 6 ]	58

7.4.2.7 <code>~BArrayDense()</code> . . . . .	59
7.4.3 Member Function Documentation . . . . .	59
7.4.3.1 <code>clear()</code> . . . . .	59
7.4.3.2 <code>col()</code> [1/2] . . . . .	59
7.4.3.3 <code>col()</code> [2/2] . . . . .	59
7.4.3.4 <code>colsum()</code> . . . . .	59
7.4.3.5 <code>D()</code> [1/2] . . . . .	60
7.4.3.6 <code>D()</code> [2/2] . . . . .	60
7.4.3.7 <code>D_ptr()</code> [1/2] . . . . .	60
7.4.3.8 <code>D_ptr()</code> [2/2] . . . . .	60
7.4.3.9 <code>default_val()</code> . . . . .	60
7.4.3.10 <code>get_cell()</code> . . . . .	60
7.4.3.11 <code>get_col_vec()</code> [1/2] . . . . .	61
7.4.3.12 <code>get_col_vec()</code> [2/2] . . . . .	61
7.4.3.13 <code>get_data()</code> . . . . .	61
7.4.3.14 <code>get_entries()</code> . . . . .	61
7.4.3.15 <code>get_row_vec()</code> [1/2] . . . . .	61
7.4.3.16 <code>get_row_vec()</code> [2/2] . . . . .	62
7.4.3.17 <code>insert_cell()</code> [1/2] . . . . .	62
7.4.3.18 <code>insert_cell()</code> [2/2] . . . . .	62
7.4.3.19 <code>is_dense()</code> . . . . .	62
7.4.3.20 <code>is_empty()</code> . . . . .	62
7.4.3.21 <code>ncol()</code> . . . . .	63
7.4.3.22 <code>nnozero()</code> . . . . .	63
7.4.3.23 <code>nrow()</code> . . . . .	63
7.4.3.24 <code>operator&gt;()</code> [1/2] . . . . .	63
7.4.3.25 <code>operator&gt;()</code> [2/2] . . . . .	63
7.4.3.26 <code>operator*=( )</code> . . . . .	63
7.4.3.27 <code>operator+=( )</code> [1/3] . . . . .	64
7.4.3.28 <code>operator+=( )</code> [2/3] . . . . .	64
7.4.3.29 <code>operator+=( )</code> [3/3] . . . . .	64
7.4.3.30 <code>operator-=( )</code> [1/3] . . . . .	64
7.4.3.31 <code>operator-=( )</code> [2/3] . . . . .	64
7.4.3.32 <code>operator-=( )</code> [3/3] . . . . .	64
7.4.3.33 <code>operator/=( )</code> . . . . .	65
7.4.3.34 <code>operator=( )</code> [1/2] . . . . .	65
7.4.3.35 <code>operator=( )</code> [2/2] . . . . .	65
7.4.3.36 <code>operator==( )</code> . . . . .	65
7.4.3.37 <code>out_of_range()</code> . . . . .	65
7.4.3.38 <code>print()</code> . . . . .	65
7.4.3.39 <code>reserve()</code> . . . . .	66
7.4.3.40 <code>resize()</code> . . . . .	66



7.4.3.41 rm_cell()	66
7.4.3.42 row() [1/2]	66
7.4.3.43 row() [2/2]	66
7.4.3.44 rowsum()	66
7.4.3.45 set_data()	67
7.4.3.46 swap_cells()	67
7.4.3.47 swap_cols()	67
7.4.3.48 swap_rows()	67
7.4.3.49 toggle_cell()	68
7.4.3.50 toggle_lock()	68
7.4.3.51 transpose()	68
7.4.3.52 zero_col()	68
7.4.3.53 zero_row()	68
7.4.4 Friends And Related Function Documentation	68
7.4.4.1 BArrayDenseCell< Cell_Type, Data_Type >	69
7.4.4.2 BArrayDenseCol< Cell_Type, Data_Type >	69
7.4.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >	69
7.4.4.4 BArrayDenseRow< Cell_Type, Data_Type >	69
7.4.4.5 BArrayDenseRow_const< Cell_Type, Data_Type >	69
7.4.5 Member Data Documentation	69
7.4.5.1 visited	70
7.5 BArrayDenseCell< Cell_Type, Data_Type > Class Template Reference	70
7.5.1 Detailed Description	70
7.5.2 Constructor & Destructor Documentation	71
7.5.2.1 BArrayDenseCell()	71
7.5.2.2 ~BArrayDenseCell()	71
7.5.3 Member Function Documentation	71
7.5.3.1 operator Cell_Type()	71
7.5.3.2 operator*=( )	71
7.5.3.3 operator+=( )	72
7.5.3.4 operator-=( )	72
7.5.3.5 operator/=( )	72
7.5.3.6 operator=( ) [1/2]	72
7.5.3.7 operator=( ) [2/2]	72
7.5.3.8 operator==( )	73
7.5.4 Friends And Related Function Documentation	73
7.5.4.1 BArrayDense< Cell_Type, Data_Type >	73
7.5.4.2 BArrayDenseCol< Cell_Type, Data_Type >	73
7.5.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >	73
7.6 BArrayDenseCell_const< Cell_Type, Data_Type > Class Template Reference	74
7.6.1 Detailed Description	74
7.7 BArrayDenseCol< Cell_Type, Data_Type > Class Template Reference	74

7.7.1 Detailed Description	74
7.7.2 Constructor & Destructor Documentation	74
7.7.2.1 BArrayDenseCol()	75
7.7.3 Member Function Documentation	75
7.7.3.1 begin()	75
7.7.3.2 end()	75
7.7.3.3 operator()()	75
7.7.3.4 size()	75
7.7.4 Friends And Related Function Documentation	76
7.7.4.1 BArrayDense< Cell_Type, Data_Type >	76
7.7.4.2 BArrayDenseCell< Cell_Type, Data_Type >	76
7.7.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >	76
7.8 BArrayDenseCol_const< Cell_Type, Data_Type > Class Template Reference	76
7.8.1 Detailed Description	77
7.8.2 Constructor & Destructor Documentation	77
7.8.2.1 BArrayDenseCol_const()	77
7.8.3 Member Function Documentation	77
7.8.3.1 begin()	77
7.8.3.2 end()	77
7.8.3.3 operator()()	78
7.8.3.4 size()	78
7.8.4 Friends And Related Function Documentation	78
7.8.4.1 BArrayDenseCell< Cell_Type, Data_Type >	78
7.8.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	78
7.9 BArrayDenseRow< Cell_Type, Data_Type > Class Template Reference	78
7.9.1 Detailed Description	79
7.9.2 Constructor & Destructor Documentation	79
7.9.2.1 BArrayDenseRow()	79
7.9.3 Member Function Documentation	79
7.9.3.1 begin()	79
7.9.3.2 end()	80
7.9.3.3 operator()()	80
7.9.3.4 size()	80
7.9.4 Friends And Related Function Documentation	80
7.9.4.1 BArrayDense< Cell_Type, Data_Type >	80
7.9.4.2 BArrayDenseCell< Cell_Type, Data_Type >	80
7.9.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >	81
7.10 BArrayDenseRow_const< Cell_Type, Data_Type > Class Template Reference	81
7.10.1 Detailed Description	81
7.10.2 Constructor & Destructor Documentation	81
7.10.2.1 BArrayDenseRow_const()	82
7.10.3 Member Function Documentation	82

7.10.3.1 begin()	82
7.10.3.2 end()	82
7.10.3.3 operator>()	82
7.10.3.4 size()	82
7.10.4 Friends And Related Function Documentation	83
7.10.4.1 BArrayDenseCell< Cell_Type, Data_Type >	83
7.10.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	83
7.11 BArrayRow< Cell_Type, Data_Type > Class Template Reference	83
7.11.1 Detailed Description	83
7.11.2 Constructor & Destructor Documentation	84
7.11.2.1 BArrayRow()	84
7.11.2.2 ~BArrayRow()	84
7.11.3 Member Function Documentation	84
7.11.3.1 operator BArrayRow< Cell_Type, Data_Type >()	84
7.11.3.2 operator*=( )	84
7.11.3.3 operator+=( )	84
7.11.3.4 operator-=( )	85
7.11.3.5 operator/=( )	85
7.11.3.6 operator=( )	85
7.11.3.7 operator==( )	85
7.12 BArrayRow_const< Cell_Type, Data_Type > Class Template Reference	85
7.12.1 Detailed Description	86
7.12.2 Constructor & Destructor Documentation	86
7.12.2.1 BArrayRow_const()	86
7.12.2.2 ~BArrayRow_const()	86
7.12.3 Member Function Documentation	86
7.12.3.1 operator BArrayRow_const< Cell_Type, Data_Type >()	86
7.12.3.2 operator"!=( )	86
7.12.3.3 operator<( )	87
7.12.3.4 operator<=( )	87
7.12.3.5 operator==( )	87
7.12.3.6 operator>( )	87
7.12.3.7 operator>=( )	87
7.13 BArrayVector< Cell_Type, Data_Type > Class Template Reference	87
7.13.1 Detailed Description	88
7.13.2 Constructor & Destructor Documentation	88
7.13.2.1 BArrayVector()	88
7.13.2.2 ~BArrayVector()	89
7.13.3 Member Function Documentation	89
7.13.3.1 begin()	89
7.13.3.2 end()	89
7.13.3.3 is_col()	89

7.13.3.4 is_row()	90
7.13.3.5 operator std::vector< Cell_Type >()	90
7.13.3.6 operator*=( )	90
7.13.3.7 operator+=( )	90
7.13.3.8 operator-=( )	90
7.13.3.9 operator/=( )	91
7.13.3.10 operator=( )	91
7.13.3.11 operator==( )	91
7.13.3.12 size()	91
7.14 BArrayVector_const< Cell_Type, Data_Type > Class Template Reference	91
7.14.1 Detailed Description	92
7.14.2 Constructor & Destructor Documentation	92
7.14.2.1 BArrayVector_const()	92
7.14.2.2 ~BArrayVector_const()	92
7.14.3 Member Function Documentation	93
7.14.3.1 begin()	93
7.14.3.2 end()	93
7.14.3.3 is_col()	93
7.14.3.4 is_row()	93
7.14.3.5 operator std::vector< Cell_Type >()	93
7.14.3.6 operator!=( )	94
7.14.3.7 operator<()	94
7.14.3.8 operator<=( )	94
7.14.3.9 operator==( )	94
7.14.3.10 operator>()	94
7.14.3.11 operator>=( )	95
7.14.3.12 size()	95
7.15 Cell< Cell_Type > Class Template Reference	95
7.15.1 Detailed Description	96
7.15.2 Constructor & Destructor Documentation	96
7.15.2.1 Cell() [1/7]	96
7.15.2.2 Cell() [2/7]	96
7.15.2.3 ~Cell()	96
7.15.2.4 Cell() [3/7]	97
7.15.2.5 Cell() [4/7]	97
7.15.2.6 Cell() [5/7]	97
7.15.2.7 Cell() [6/7]	97
7.15.2.8 Cell() [7/7]	97
7.15.3 Member Function Documentation	97
7.15.3.1 add() [1/4]	98
7.15.3.2 add() [2/4]	98
7.15.3.3 add() [3/4]	98

7.15.3.4 add() [ 4 / 4 ] . . . . .	98
7.15.3.5 operator Cell_Type() . . . . .	98
7.15.3.6 operator"!=( ) . . . . .	98
7.15.3.7 operator=( ) [ 1 / 2 ] . . . . .	99
7.15.3.8 operator=( ) [ 2 / 2 ] . . . . .	99
7.15.3.9 operator==( ) . . . . .	99
7.15.4 Member Data Documentation . . . . .	99
7.15.4.1 active . . . . .	99
7.15.4.2 value . . . . .	99
7.15.4.3 visited . . . . .	100
7.16 Cell_const< Cell_Type > Class Template Reference . . . . .	100
7.16.1 Detailed Description . . . . .	100
7.17 ConstBArrayRowIter< Cell_Type, Data_Type > Class Template Reference . . . . .	100
7.17.1 Detailed Description . . . . .	101
7.17.2 Constructor & Destructor Documentation . . . . .	101
7.17.2.1 ConstBArrayRowIter() . . . . .	101
7.17.2.2 ~ConstBArrayRowIter() . . . . .	101
7.17.3 Member Data Documentation . . . . .	101
7.17.3.1 Array . . . . .	102
7.17.3.2 current_col . . . . .	102
7.17.3.3 current_row . . . . .	102
7.17.3.4 iter . . . . .	102
7.18 Counter< Array_Type, Data_Type > Class Template Reference . . . . .	102
7.18.1 Detailed Description . . . . .	103
7.18.2 Constructor & Destructor Documentation . . . . .	103
7.18.2.1 Counter() [ 1 / 4 ] . . . . .	104
7.18.2.2 Counter() [ 2 / 4 ] . . . . .	104
7.18.2.3 Counter() [ 3 / 4 ] . . . . .	104
7.18.2.4 Counter() [ 4 / 4 ] . . . . .	104
7.18.2.5 ~Counter() . . . . .	104
7.18.3 Member Function Documentation . . . . .	105
7.18.3.1 count() . . . . .	105
7.18.3.2 get_description() . . . . .	105
7.18.3.3 get_name() . . . . .	105
7.18.3.4 init() . . . . .	105
7.18.3.5 operator=( ) [ 1 / 2 ] . . . . .	105
7.18.3.6 operator=( ) [ 2 / 2 ] . . . . .	106
7.18.4 Member Data Documentation . . . . .	106
7.18.4.1 count_fun . . . . .	106
7.18.4.2 data . . . . .	106
7.18.4.3 desc . . . . .	106
7.18.4.4 init_fun . . . . .	106

7.18.4.5 name	107
7.19 Counters< Array_Type, Data_Type > Class Template Reference	107
7.19.1 Detailed Description	107
7.19.2 Constructor & Destructor Documentation	108
7.19.2.1 Counters() [1/3]	108
7.19.2.2 ~Counters()	108
7.19.2.3 Counters() [2/3]	108
7.19.2.4 Counters() [3/3]	108
7.19.3 Member Function Documentation	109
7.19.3.1 add_counter() [1/2]	109
7.19.3.2 add_counter() [2/2]	109
7.19.3.3 get_descriptions()	109
7.19.3.4 get_names()	109
7.19.3.5 operator=() [1/2]	109
7.19.3.6 operator=() [2/2]	110
7.19.3.7 operator[]()	110
7.19.3.8 size()	111
7.20 DEFM Class Reference	111
7.20.1 Detailed Description	111
7.20.2 Constructor & Destructor Documentation	111
7.20.2.1 DEFM()	112
7.20.2.2 ~DEFM()	112
7.20.3 Member Function Documentation	112
7.20.3.1 get_ID()	112
7.20.3.2 get_m_order()	112
7.20.3.3 get_model()	112
7.20.3.4 get_n_covars()	113
7.20.3.5 get_n_obs()	113
7.20.3.6 get_n_rows()	113
7.20.3.7 get_n_y()	113
7.20.3.8 get_X()	113
7.20.3.9 get_Y()	113
7.20.3.10 init()	114
7.20.3.11 likelihood()	114
7.20.3.12 motif_census()	114
7.20.3.13 simulate()	114
7.21 DEFMCounterData Class Reference	114
7.21.1 Detailed Description	115
7.21.2 Constructor & Destructor Documentation	115
7.21.2.1 DEFMCounterData() [1/2]	115
7.21.2.2 DEFMCounterData() [2/2]	115
7.21.2.3 ~DEFMCounterData()	116

7.21.3 Member Function Documentation	116
7.21.3.1 idx()	116
7.21.3.2 is_true()	116
7.21.3.3 num()	116
7.21.4 Member Data Documentation	116
7.21.4.1 indices	116
7.21.4.2 logical	117
7.21.4.3 numbers	117
7.22 DEFMDData Class Reference	117
7.22.1 Detailed Description	118
7.22.2 Constructor & Destructor Documentation	118
7.22.2.1 DEFMDData() [1/2]	118
7.22.2.2 DEFMDData() [2/2]	118
7.22.2.3 ~DEFMDData()	119
7.22.3 Member Function Documentation	119
7.22.3.1 at()	119
7.22.3.2 ncol()	119
7.22.3.3 operator()()	119
7.22.3.4 print()	120
7.22.4 Member Data Documentation	120
7.22.4.1 array	120
7.22.4.2 covariates	120
7.22.4.3 obs_start	120
7.22.4.4 X_ncol	120
7.22.4.5 X_nrow	121
7.23 DEFMRuleData Class Reference	121
7.23.1 Detailed Description	121
7.23.2 Constructor & Destructor Documentation	121
7.23.2.1 DEFMRuleData() [1/2]	121
7.23.2.2 DEFMRuleData() [2/2]	121
7.23.3 Member Function Documentation	122
7.23.3.1 idx()	122
7.23.3.2 num()	122
7.24 Entries< Cell_Type > Class Template Reference	122
7.24.1 Detailed Description	122
7.24.2 Constructor & Destructor Documentation	123
7.24.2.1 Entries() [1/2]	123
7.24.2.2 Entries() [2/2]	123
7.24.2.3 ~Entries()	123
7.24.3 Member Function Documentation	123
7.24.3.1 resize()	123
7.24.4 Member Data Documentation	124

7.24.4.1 source	124
7.24.4.2 target	124
7.24.4.3 val	124
7.25 Flock Class Reference	124
7.25.1 Detailed Description	125
7.25.2 Constructor & Destructor Documentation	126
7.25.2.1 Flock()	126
7.25.2.2 ~Flock()	126
7.25.3 Member Function Documentation	126
7.25.3.1 add_data()	126
7.25.3.2 colnames()	127
7.25.3.3 get_counters()	127
7.25.3.4 get_model()	127
7.25.3.5 get_stats_support()	127
7.25.3.6 get_stats_target()	127
7.25.3.7 get_support_fun()	127
7.25.3.8 init()	128
7.25.3.9 likelihood_joint()	128
7.25.3.10 nfuns()	128
7.25.3.11 nleaves()	128
7.25.3.12 nnodes()	129
7.25.3.13 nterms()	129
7.25.3.14 ntrees()	129
7.25.3.15 operator()()	129
7.25.3.16 parse_polytomies()	129
7.25.3.17 print()	130
7.25.3.18 set_seed()	130
7.25.3.19 support_size()	130
7.25.4 Member Data Documentation	130
7.25.4.1 dat	130
7.25.4.2 initialized	131
7.25.4.3 model	131
7.25.4.4 nfunctions	131
7.25.4.5 rengine	131
7.26 FreqTable< T > Class Template Reference	131
7.26.1 Detailed Description	132
7.26.2 Constructor & Destructor Documentation	132
7.26.2.1 FreqTable()	132
7.26.2.2 ~FreqTable()	133
7.26.3 Member Function Documentation	133
7.26.3.1 add()	133
7.26.3.2 as_vector()	133



7.26.3.3 clear()	133
7.26.3.4 get_data()	133
7.26.3.5 get_index()	134
7.26.3.6 make_hash()	134
7.26.3.7 print()	134
7.26.3.8 reserve()	134
7.26.3.9 size()	134
7.27 Geese Class Reference	135
7.27.1 Detailed Description	138
7.27.2 Constructor & Destructor Documentation	138
7.27.2.1 Geese() [1/4]	138
7.27.2.2 Geese() [2/4]	139
7.27.2.3 Geese() [3/4]	139
7.27.2.4 Geese() [4/4]	139
7.27.2.5 ~Geese()	139
7.27.3 Member Function Documentation	139
7.27.3.1 calc_reduced_sequence()	139
7.27.3.2 calc_sequence()	140
7.27.3.3 colnames()	140
7.27.3.4 get_annotated_nodes()	140
7.27.3.5 get_counters()	140
7.27.3.6 get_model()	140
7.27.3.7 get_probabilities()	140
7.27.3.8 get_engine()	141
7.27.3.9 get_states()	141
7.27.3.10 get_support_fun()	141
7.27.3.11 inherit_support()	141
7.27.3.12 init()	141
7.27.3.13 init_node()	142
7.27.3.14 likelihood()	142
7.27.3.15 likelihood_exhaust()	142
7.27.3.16 nnotations()	142
7.27.3.17 nfuncs()	142
7.27.3.18 nleaves()	143
7.27.3.19 nnodes()	143
7.27.3.20 nterms()	143
7.27.3.21 observed_counts()	143
7.27.3.22 operator=() [1/2]	143
7.27.3.23 operator=() [2/2]	143
7.27.3.24 parse_polytomies()	144
7.27.3.25 predict()	144
7.27.3.26 predict_backend()	144

7.27.3.27 predict_exhaust()	144
7.27.3.28 predict_exhaust_backend()	145
7.27.3.29 predict_sim()	145
7.27.3.30 print()	145
7.27.3.31 print_observed_counts()	145
7.27.3.32 set_seed()	145
7.27.3.33 simulate()	146
7.27.3.34 support_size()	146
7.27.3.35 update_annotations()	146
7.27.4 Member Data Documentation	146
7.27.4.1 delete_engine	146
7.27.4.2 delete_support	146
7.27.4.3 initialized	147
7.27.4.4 map_to_nodes	147
7.27.4.5 nfunctions	147
7.27.4.6 nodes	147
7.27.4.7 pset_loc	147
7.27.4.8 reduced_sequence	147
7.27.4.9 sequence	148
7.28 Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	148
7.28.1 Detailed Description	150
7.28.2 Constructor & Destructor Documentation	151
7.28.2.1 Model() [1/3]	151
7.28.2.2 Model() [2/3]	151
7.28.2.3 Model() [3/3]	151
7.28.2.4 ~Model()	151
7.28.3 Member Function Documentation	152
7.28.3.1 add_array()	152
7.28.3.2 add_counter() [1/2]	152
7.28.3.3 add_counter() [2/2]	152
7.28.3.4 add_rule() [1/2]	153
7.28.3.5 add_rule() [2/2]	153
7.28.3.6 add_rule_dyn() [1/2]	153
7.28.3.7 add_rule_dyn() [2/2]	153
7.28.3.8 colnames()	153
7.28.3.9 conditional_prob()	154
7.28.3.10 gen_key()	154
7.28.3.11 get_arrays2support()	154
7.28.3.12 get_counters()	155
7.28.3.13 get_norm_const()	155
7.28.3.14 get_pset()	155

7.28.3.15	<a href="#">get_pset_arrays()</a>	155
7.28.3.16	<a href="#">get_pset_probs()</a>	155
7.28.3.17	<a href="#">get_pset_stats()</a> [1/2]	156
7.28.3.18	<a href="#">get_pset_stats()</a> [2/2]	156
7.28.3.19	<a href="#">get_rengine()</a>	156
7.28.3.20	<a href="#">get_rules()</a>	156
7.28.3.21	<a href="#">get_rules_dyn()</a>	156
7.28.3.22	<a href="#">get_stats_support()</a>	157
7.28.3.23	<a href="#">get_stats_target()</a>	157
7.28.3.24	<a href="#">get_support_fun()</a>	157
7.28.3.25	<a href="#">likelihood()</a> [1/4]	157
7.28.3.26	<a href="#">likelihood()</a> [2/4]	157
7.28.3.27	<a href="#">likelihood()</a> [3/4]	158
7.28.3.28	<a href="#">likelihood()</a> [4/4]	158
7.28.3.29	<a href="#">likelihood_total()</a>	158
7.28.3.30	<a href="#">nterms()</a>	158
7.28.3.31	<a href="#">operator=()</a>	158
7.28.3.32	<a href="#">print()</a>	159
7.28.3.33	<a href="#">print_stats()</a>	159
7.28.3.34	<a href="#">sample()</a> [1/2]	159
7.28.3.35	<a href="#">sample()</a> [2/2]	159
7.28.3.36	<a href="#">set_counters()</a>	159
7.28.3.37	<a href="#">set_keygen()</a>	160
7.28.3.38	<a href="#">set_rengine()</a>	160
7.28.3.39	<a href="#">set_rules()</a>	160
7.28.3.40	<a href="#">set_rules_dyn()</a>	160
7.28.3.41	<a href="#">set_seed()</a>	160
7.28.3.42	<a href="#">set_transform_model()</a>	161
7.28.3.43	<a href="#">size()</a>	161
7.28.3.44	<a href="#">size_unique()</a>	161
7.28.3.45	<a href="#">store_psets()</a>	161
7.28.3.46	<a href="#">support_size()</a>	162
7.28.3.47	<a href="#">transform_model()</a>	162
7.29	<a href="#">NetCounterData Class Reference</a>	162
7.29.1	<a href="#">Detailed Description</a>	162
7.29.2	<a href="#">Constructor &amp; Destructor Documentation</a>	163
7.29.2.1	<a href="#">NetCounterData()</a> [1/2]	163
7.29.2.2	<a href="#">NetCounterData()</a> [2/2]	163
7.29.2.3	<a href="#">~NetCounterData()</a>	163
7.29.3	<a href="#">Member Data Documentation</a>	163
7.29.3.1	<a href="#">indices</a>	163
7.29.3.2	<a href="#">numbers</a>	163

7.30 NetworkData Class Reference . . . . .	164
7.30.1 Detailed Description . . . . .	164
7.30.2 Constructor & Destructor Documentation . . . . .	164
7.30.2.1 NetworkData() [1/3] . . . . .	164
7.30.2.2 NetworkData() [2/3] . . . . .	164
7.30.2.3 NetworkData() [3/3] . . . . .	165
7.30.2.4 ~NetworkData() . . . . .	165
7.30.3 Member Data Documentation . . . . .	165
7.30.3.1 directed . . . . .	165
7.30.3.2 vertex_attr . . . . .	166
7.31 Node Class Reference . . . . .	166
7.31.1 Detailed Description . . . . .	167
7.31.2 Constructor & Destructor Documentation . . . . .	167
7.31.2.1 Node() [1/5] . . . . .	167
7.31.2.2 Node() [2/5] . . . . .	168
7.31.2.3 Node() [3/5] . . . . .	168
7.31.2.4 Node() [4/5] . . . . .	168
7.31.2.5 Node() [5/5] . . . . .	168
7.31.2.6 ~Node() . . . . .	168
7.31.3 Member Function Documentation . . . . .	168
7.31.3.1 get_parent() . . . . .	169
7.31.3.2 is_leaf() . . . . .	169
7.31.3.3 noffspring() . . . . .	169
7.31.4 Member Data Documentation . . . . .	169
7.31.4.1 annotations . . . . .	169
7.31.4.2 array . . . . .	169
7.31.4.3 arrays . . . . .	170
7.31.4.4 duplication . . . . .	170
7.31.4.5 id . . . . .	170
7.31.4.6 narray . . . . .	170
7.31.4.7 offspring . . . . .	170
7.31.4.8 ord . . . . .	171
7.31.4.9 parent . . . . .	171
7.31.4.10 probability . . . . .	171
7.31.4.11 subtree_prob . . . . .	171
7.31.4.12 visited . . . . .	171
7.32 NodeData Class Reference . . . . .	172
7.32.1 Detailed Description . . . . .	172
7.32.2 Constructor & Destructor Documentation . . . . .	172
7.32.2.1 NodeData() . . . . .	172
7.32.3 Member Data Documentation . . . . .	172
7.32.3.1 blengths . . . . .	173

7.32.3.2 duplication	173
7.32.3.3 states	173
7.33 PhyloCounterData Class Reference	173
7.33.1 Detailed Description	174
7.33.2 Constructor & Destructor Documentation	174
7.33.2.1 PhyloCounterData() [1/2]	174
7.33.2.2 PhyloCounterData() [2/2]	174
7.33.3 Member Function Documentation	174
7.33.3.1 at()	174
7.33.3.2 begin()	174
7.33.3.3 empty()	175
7.33.3.4 end()	175
7.33.3.5 get_counters()	175
7.33.3.6 operator>()	175
7.33.3.7 operator[]()	175
7.33.3.8 push_back()	175
7.33.3.9 reserve()	176
7.33.3.10 shrink_to_fit()	176
7.33.3.11 size()	176
7.34 PhyloRuleDynData Class Reference	176
7.34.1 Detailed Description	176
7.34.2 Constructor & Destructor Documentation	177
7.34.2.1 PhyloRuleDynData()	177
7.34.2.2 ~PhyloRuleDynData()	177
7.34.3 Member Data Documentation	177
7.34.3.1 counts	177
7.34.3.2 duplication	177
7.34.3.3 lb	177
7.34.3.4 pos	178
7.34.3.5 ub	178
7.35 PowerSet< Array_Type, Data_Rule_Type > Class Template Reference	178
7.35.1 Detailed Description	179
7.35.2 Constructor & Destructor Documentation	180
7.35.2.1 PowerSet() [1/3]	180
7.35.2.2 PowerSet() [2/3]	180
7.35.2.3 PowerSet() [3/3]	180
7.35.2.4 ~PowerSet()	180
7.35.3 Member Function Documentation	180
7.35.3.1 add_rule() [1/2]	181
7.35.3.2 add_rule() [2/2]	181
7.35.3.3 begin()	181
7.35.3.4 calc()	181

7.35.3.5 end()	181
7.35.3.6 get_data()	182
7.35.3.7 get_data_ptr()	182
7.35.3.8 init_support()	182
7.35.3.9 operator[]()	182
7.35.3.10 reset()	182
7.35.3.11 size()	183
7.35.4 Member Data Documentation	183
7.35.4.1 coordinates_free	183
7.35.4.2 coordinates_locked	183
7.35.4.3 data	183
7.35.4.4 EmptyArray	183
7.35.4.5 M	184
7.35.4.6 N	184
7.35.4.7 n_free	184
7.35.4.8 n_locked	184
7.35.4.9 rules	184
7.35.4.10 rules_deleted	185
7.36 Progress Class Reference	185
7.36.1 Detailed Description	185
7.36.2 Constructor & Destructor Documentation	185
7.36.2.1 Progress()	185
7.36.2.2 ~Progress()	186
7.36.3 Member Function Documentation	186
7.36.3.1 end()	186
7.36.3.2 next()	186
7.37 Rule< Array_Type, Data_Type > Class Template Reference	186
7.37.1 Detailed Description	187
7.37.2 Constructor & Destructor Documentation	187
7.37.2.1 Rule() [1/2]	187
7.37.2.2 Rule() [2/2]	187
7.37.2.3 ~Rule()	188
7.37.3 Member Function Documentation	188
7.37.3.1 D()	188
7.37.3.2 operator()()	188
7.38 Rules< Array_Type, Data_Type > Class Template Reference	188
7.38.1 Detailed Description	189
7.38.2 Constructor & Destructor Documentation	189
7.38.2.1 Rules() [1/2]	189
7.38.2.2 Rules() [2/2]	189
7.38.2.3 ~Rules()	190
7.38.3 Member Function Documentation	190

7.38.3.1 add_rule() [1/2]	190
7.38.3.2 add_rule() [2/2]	190
7.38.3.3 get_seq()	190
7.38.3.4 operator()()	191
7.38.3.5 operator=()	191
7.38.3.6 size()	191
7.39 StatsCounter< Array_Type, Data_Type > Class Template Reference	192
7.39.1 Detailed Description	192
7.39.2 Constructor & Destructor Documentation	192
7.39.2.1 StatsCounter() [1/3]	192
7.39.2.2 StatsCounter() [2/3]	193
7.39.2.3 StatsCounter() [3/3]	193
7.39.2.4 ~StatsCounter()	193
7.39.3 Member Function Documentation	193
7.39.3.1 add_counter()	193
7.39.3.2 count_all()	194
7.39.3.3 count_current()	194
7.39.3.4 count_init()	194
7.39.3.5 get_counters()	194
7.39.3.6 get_descriptions()	194
7.39.3.7 get_names()	194
7.39.3.8 reset_array()	194
7.39.3.9 set_counters()	195
7.39.3.10 size()	195
7.40 Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	195
7.40.1 Detailed Description	197
7.40.2 Constructor & Destructor Documentation	197
7.40.2.1 Support() [1/3]	197
7.40.2.2 Support() [2/3]	198
7.40.2.3 Support() [3/3]	198
7.40.2.4 ~Support()	198
7.40.3 Member Function Documentation	198
7.40.3.1 add_counter()	198
7.40.3.2 add_rule() [1/2]	199
7.40.3.3 add_rule() [2/2]	199
7.40.3.4 add_rule_dyn() [1/2]	199
7.40.3.5 add_rule_dyn() [2/2]	199
7.40.3.6 calc()	199
7.40.3.7 eval_rules_dyn()	200
7.40.3.8 get_counters()	200
7.40.3.9 get_counts()	200

7.40.3.10	<a href="#">get_current_stats()</a>	200
7.40.3.11	<a href="#">get_data()</a>	201
7.40.3.12	<a href="#">get_rules()</a>	201
7.40.3.13	<a href="#">get_rules_dyn()</a>	201
7.40.3.14	<a href="#">init_support()</a>	201
7.40.3.15	<a href="#">print()</a>	201
7.40.3.16	<a href="#">reset_array()</a> [1/2]	202
7.40.3.17	<a href="#">reset_array()</a> [2/2]	202
7.40.3.18	<a href="#">set_counters()</a>	202
7.40.3.19	<a href="#">set_rules()</a>	202
7.40.3.20	<a href="#">set_rules_dyn()</a>	202
7.40.4	<a href="#">Member Data Documentation</a>	202
7.40.4.1	<a href="#">change_stats</a>	203
7.40.4.2	<a href="#">cooriantes_n_free</a>	203
7.40.4.3	<a href="#">cooriantes_n_locked</a>	203
7.40.4.4	<a href="#">coordinates_free</a>	203
7.40.4.5	<a href="#">coordinates_locked</a>	203
7.40.4.6	<a href="#">current_stats</a>	204
7.40.4.7	<a href="#">delete_counters</a>	204
7.40.4.8	<a href="#">delete_rules</a>	204
7.40.4.9	<a href="#">delete_rules_dyn</a>	204
7.40.4.10	<a href="#">hashes</a>	204
7.40.4.11	<a href="#">hashes_initialized</a>	205
7.40.4.12	<a href="#">M</a>	205
7.40.4.13	<a href="#">max_num_elements</a>	205
7.40.4.14	<a href="#">N</a>	205
7.40.4.15	<a href="#">n_counters</a>	205
7.41	<a href="#">vecHasher&lt; T &gt; Struct Template Reference</a>	206
7.41.1	<a href="#">Detailed Description</a>	206
7.41.2	<a href="#">Member Function Documentation</a>	206
7.41.2.1	<a href="#">operator&gt;()</a>	206
<b>8</b>	<b>File Documentation</b>	<b>207</b>
8.1	<a href="#">include/barry/barray-bones.hpp File Reference</a>	207
8.2	<a href="#">include/barry/barray-iterator.hpp File Reference</a>	207
8.3	<a href="#">include/barry/barray-meat-operators.hpp File Reference</a>	208
8.3.1	<a href="#">Macro Definition Documentation</a>	208
8.3.1.1	<a href="#">BARRAY_TEMPLATE</a>	209
8.3.1.2	<a href="#">BARRAY_TEMPLATE_ARGS</a>	209
8.3.1.3	<a href="#">BARRAY_TYPE</a>	209
8.3.1.4	<a href="#">COL</a>	209
8.3.1.5	<a href="#">ROW</a>	209



8.3.2 Function Documentation	209
8.3.2.1 BARRAY_TEMPLATE() [1/6]	210
8.3.2.2 BARRAY_TEMPLATE() [2/6]	210
8.3.2.3 BARRAY_TEMPLATE() [3/6]	210
8.3.2.4 BARRAY_TEMPLATE() [4/6]	210
8.3.2.5 BARRAY_TEMPLATE() [5/6]	210
8.3.2.6 BARRAY_TEMPLATE() [6/6]	211
8.3.2.7 BARRAY_TEMPLATE_ARGS()	211
8.3.2.8 BARRAY_TYPE()	211
8.3.2.9 for()	211
8.3.2.10 operator()	211
8.3.3 Variable Documentation	211
8.3.3.1 rhs	212
8.3.3.2 this	212
8.4 include/barry/barray-meat.hpp File Reference	212
8.4.1 Macro Definition Documentation	214
8.4.1.1 BARRAY_TEMPLATE	214
8.4.1.2 BARRAY_TEMPLATE_ARGS	214
8.4.1.3 BARRAY_TYPE	215
8.4.1.4 COL	215
8.4.1.5 ROW	215
8.4.2 Function Documentation	215
8.4.2.1 ans()	215
8.4.2.2 BARRAY_TEMPLATE() [1/24]	215
8.4.2.3 BARRAY_TEMPLATE() [2/24]	216
8.4.2.4 BARRAY_TEMPLATE() [3/24]	216
8.4.2.5 BARRAY_TEMPLATE() [4/24]	216
8.4.2.6 BARRAY_TEMPLATE() [5/24]	216
8.4.2.7 BARRAY_TEMPLATE() [6/24]	216
8.4.2.8 BARRAY_TEMPLATE() [7/24]	216
8.4.2.9 BARRAY_TEMPLATE() [8/24]	217
8.4.2.10 BARRAY_TEMPLATE() [9/24]	217
8.4.2.11 BARRAY_TEMPLATE() [10/24]	217
8.4.2.12 BARRAY_TEMPLATE() [11/24]	217
8.4.2.13 BARRAY_TEMPLATE() [12/24]	217
8.4.2.14 BARRAY_TEMPLATE() [13/24]	218
8.4.2.15 BARRAY_TEMPLATE() [14/24]	218
8.4.2.16 BARRAY_TEMPLATE() [15/24]	218
8.4.2.17 BARRAY_TEMPLATE() [16/24]	218
8.4.2.18 BARRAY_TEMPLATE() [17/24]	218
8.4.2.19 BARRAY_TEMPLATE() [18/24]	218
8.4.2.20 BARRAY_TEMPLATE() [19/24]	219

8.4.2.21 BARRAY_TEMPLATE() [20/24]	219
8.4.2.22 BARRAY_TEMPLATE() [21/24]	219
8.4.2.23 BARRAY_TEMPLATE() [22/24]	219
8.4.2.24 BARRAY_TEMPLATE() [23/24]	219
8.4.2.25 BARRAY_TEMPLATE() [24/24]	219
8.4.2.26 COL()	220
8.4.2.27 for() [1/3]	220
8.4.2.28 for() [2/3]	220
8.4.2.29 for() [3/3]	220
8.4.2.30 if() [1/17]	220
8.4.2.31 if() [2/17]	220
8.4.2.32 if() [3/17]	221
8.4.2.33 if() [4/17]	221
8.4.2.34 if() [5/17]	221
8.4.2.35 if() [6/17]	221
8.4.2.36 if() [7/17]	221
8.4.2.37 if() [8/17]	221
8.4.2.38 if() [9/17]	222
8.4.2.39 if() [10/17]	222
8.4.2.40 if() [11/17]	222
8.4.2.41 if() [12/17]	222
8.4.2.42 if() [13/17]	222
8.4.2.43 if() [14/17]	222
8.4.2.44 if() [15/17]	222
8.4.2.45 if() [16/17]	223
8.4.2.46 if() [17/17]	223
8.4.2.47 M()	223
8.4.2.48 resize() [1/2]	223
8.4.2.49 resize() [2/2]	223
8.4.2.50 return()	223
8.4.2.51 ROW() [1/2]	224
8.4.2.52 ROW() [2/2]	224
8.4.3 Variable Documentation	224
8.4.3.1 add	224
8.4.3.2 ans	224
8.4.3.3 Array_	224
8.4.3.4 check_bounds	225
8.4.3.5 check_exists	225
8.4.3.6 col0	225
8.4.3.7 const	225
8.4.3.8 copy_data	226
8.4.3.9 data	226

8.4.3.10 delete_data	226
8.4.3.11 delete_data_	226
8.4.3.12 else	226
8.4.3.13 false	227
8.4.3.14 first	227
8.4.3.15 i1	227
8.4.3.16 j	227
8.4.3.17 j0	227
8.4.3.18 j1	227
8.4.3.19 M	228
8.4.3.20 M_	228
8.4.3.21 N	228
8.4.3.22 NCells	228
8.4.3.23 report	228
8.4.3.24 return	229
8.4.3.25 row0	229
8.4.3.26 search	229
8.4.3.27 source	229
8.4.3.28 target	229
8.4.3.29 v	229
8.4.3.30 value	230
8.5 include/barry/barraycell-bones.hpp File Reference	230
8.6 include/barry/barraycell-meat.hpp File Reference	230
8.7 include/barry/barraydense-bones.hpp File Reference	231
8.8 include/barry/barraydense-meat-operators.hpp File Reference	231
8.8.1 Macro Definition Documentation	232
8.8.1.1 BDENSE_TEMPLATE	232
8.8.1.2 BDENSE_TEMPLATE_ARGS	232
8.8.1.3 BDENSE_TYPE	232
8.8.1.4 COL	232
8.8.1.5 POS	233
8.8.1.6 POS_N	233
8.8.1.7 ROW	233
8.8.2 Function Documentation	233
8.8.2.1 BDENSE_TEMPLATE() [1/4]	233
8.8.2.2 BDENSE_TEMPLATE() [2/4]	233
8.8.2.3 BDENSE_TEMPLATE() [3/4]	234
8.8.2.4 BDENSE_TEMPLATE() [4/4]	234
8.8.2.5 BDENSE_TEMPLATE_ARGS()	234
8.8.2.6 BDENSE_TYPE()	234
8.9 include/barry/barraydense-meat.hpp File Reference	234
8.9.1 Macro Definition Documentation	237

8.9.1.1 BDENSE_TEMPLATE	237
8.9.1.2 BDENSE_TEMPLATE_ARGS	237
8.9.1.3 BDENSE_TYPE	237
8.9.1.4 COL	237
8.9.1.5 POS	237
8.9.1.6 POS_N	238
8.9.1.7 ROW	238
8.9.1.8 ZERO_CELL	238
8.9.2 Function Documentation	238
8.9.2.1 ans()	238
8.9.2.2 BDENSE_TEMPLATE() [1/39]	238
8.9.2.3 BDENSE_TEMPLATE() [2/39]	239
8.9.2.4 BDENSE_TEMPLATE() [3/39]	239
8.9.2.5 BDENSE_TEMPLATE() [4/39]	239
8.9.2.6 BDENSE_TEMPLATE() [5/39]	239
8.9.2.7 BDENSE_TEMPLATE() [6/39]	239
8.9.2.8 BDENSE_TEMPLATE() [7/39]	239
8.9.2.9 BDENSE_TEMPLATE() [8/39]	240
8.9.2.10 BDENSE_TEMPLATE() [9/39]	240
8.9.2.11 BDENSE_TEMPLATE() [10/39]	240
8.9.2.12 BDENSE_TEMPLATE() [11/39]	240
8.9.2.13 BDENSE_TEMPLATE() [12/39]	240
8.9.2.14 BDENSE_TEMPLATE() [13/39]	241
8.9.2.15 BDENSE_TEMPLATE() [14/39]	241
8.9.2.16 BDENSE_TEMPLATE() [15/39]	241
8.9.2.17 BDENSE_TEMPLATE() [16/39]	241
8.9.2.18 BDENSE_TEMPLATE() [17/39]	241
8.9.2.19 BDENSE_TEMPLATE() [18/39]	242
8.9.2.20 BDENSE_TEMPLATE() [19/39]	242
8.9.2.21 BDENSE_TEMPLATE() [20/39]	242
8.9.2.22 BDENSE_TEMPLATE() [21/39]	242
8.9.2.23 BDENSE_TEMPLATE() [22/39]	242
8.9.2.24 BDENSE_TEMPLATE() [23/39]	243
8.9.2.25 BDENSE_TEMPLATE() [24/39]	243
8.9.2.26 BDENSE_TEMPLATE() [25/39]	243
8.9.2.27 BDENSE_TEMPLATE() [26/39]	243
8.9.2.28 BDENSE_TEMPLATE() [27/39]	243
8.9.2.29 BDENSE_TEMPLATE() [28/39]	244
8.9.2.30 BDENSE_TEMPLATE() [29/39]	244
8.9.2.31 BDENSE_TEMPLATE() [30/39]	244
8.9.2.32 BDENSE_TEMPLATE() [31/39]	244
8.9.2.33 BDENSE_TEMPLATE() [32/39]	244

8.9.2.34	BDENSE_TEMPLATE() [33/39]	244
8.9.2.35	BDENSE_TEMPLATE() [34/39]	245
8.9.2.36	BDENSE_TEMPLATE() [35/39]	245
8.9.2.37	BDENSE_TEMPLATE() [36/39]	245
8.9.2.38	BDENSE_TEMPLATE() [37/39]	245
8.9.2.39	BDENSE_TEMPLATE() [38/39]	245
8.9.2.40	BDENSE_TEMPLATE() [39/39]	245
8.9.2.41	for()	246
8.9.2.42	if() [1/4]	246
8.9.2.43	if() [2/4]	246
8.9.2.44	if() [3/4]	246
8.9.2.45	if() [4/4]	246
8.9.2.46	insert_cell() [1/2]	246
8.9.2.47	insert_cell() [2/2]	247
8.9.2.48	M()	247
8.9.2.49	resize() [1/6]	247
8.9.2.50	resize() [2/6]	247
8.9.2.51	resize() [3/6]	247
8.9.2.52	resize() [4/6]	247
8.9.2.53	resize() [5/6]	248
8.9.2.54	resize() [6/6]	248
8.9.2.55	rm_cell() [1/3]	248
8.9.2.56	rm_cell() [2/3]	248
8.9.2.57	rm_cell() [3/3]	248
8.9.2.58	va_end()	248
8.9.2.59	va_start()	249
8.9.2.60	vprintf()	249
8.9.3	Variable Documentation	249
8.9.3.1	add	249
8.9.3.2	ans	249
8.9.3.3	check_bounds	249
8.9.3.4	check_exists	250
8.9.3.5	col	250
8.9.3.6	const	250
8.9.3.7	copy_data	250
8.9.3.8	data	250
8.9.3.9	delete_data	251
8.9.3.10	delete_data_	251
8.9.3.11	el	251
8.9.3.12	el_colsums	251
8.9.3.13	el_rowsums	251
8.9.3.14	else	252

8.9.3.15 false	252
8.9.3.16 i1	252
8.9.3.17 j	252
8.9.3.18 j0	252
8.9.3.19 j1	252
8.9.3.20 M	253
8.9.3.21 M_	253
8.9.3.22 N	253
8.9.3.23 report	253
8.9.3.24 return	253
8.9.3.25 source	254
8.9.3.26 target	254
8.9.3.27 v	254
8.9.3.28 val0	254
8.9.3.29 val1	254
8.9.3.30 value	254
8.10 include/barry/barraydensecell-bones.hpp File Reference	255
8.10.1 Macro Definition Documentation	255
8.10.1.1 POS	255
8.11 include/barry/barraydensecell-meat.hpp File Reference	256
8.11.1 Macro Definition Documentation	256
8.11.1.1 POS	256
8.12 include/barry/barraydensecol-bones.hpp File Reference	256
8.12.1 Macro Definition Documentation	257
8.12.1.1 POS	257
8.12.1.2 POS_N	257
8.12.1.3 ZERO_CELL	257
8.13 include/barry/barraydenserow-bones.hpp File Reference	258
8.13.1 Macro Definition Documentation	258
8.13.1.1 POS	258
8.13.1.2 POS_N	259
8.13.1.3 ZERO_CELL	259
8.14 include/barry/barrayrow-bones.hpp File Reference	259
8.15 include/barry/barrayrow-meat.hpp File Reference	259
8.15.1 Macro Definition Documentation	259
8.15.1.1 BROW_TEMPLATE	260
8.15.1.2 BROW_TEMPLATE_ARGS	260
8.15.1.3 BROW_TYPE	260
8.15.2 Function Documentation	260
8.15.2.1 BROW_TEMPLATE() [1/5]	260
8.15.2.2 BROW_TEMPLATE() [2/5]	260
8.15.2.3 BROW_TEMPLATE() [3/5]	261

8.15.2.4 BROW_TEMPLATE() [4/5]	261
8.15.2.5 BROW_TEMPLATE() [5/5]	261
8.16 include/barry/barrayvector-bones.hpp File Reference	261
8.17 include/barry/barrayvector-meat.hpp File Reference	262
8.18 include/barry/barry-configuration.hpp File Reference	262
8.18.1 Macro Definition Documentation	263
8.18.1.1 BARRY_CHECK_SUPPORT	263
8.18.1.2 BARRY_ISFINITE	263
8.18.1.3 BARRY_MAX_NUM_ELEMENTS	263
8.18.1.4 BARRY_SAFE_EXP	263
8.18.1.5 printf_barry	263
8.18.2 Typedef Documentation	263
8.18.2.1 Map	264
8.19 include/barry/barry-debug.hpp File Reference	264
8.19.1 Macro Definition Documentation	264
8.19.1.1 BARRY_DEBUG_LEVEL	264
8.20 include/barry/barry-macros.hpp File Reference	265
8.20.1 Macro Definition Documentation	265
8.20.1.1 BARRY_ONE	265
8.20.1.2 BARRY_ONE_DENSE	265
8.20.1.3 BARRY_UNUSED	266
8.20.1.4 BARRY_ZERO	266
8.20.1.5 BARRY_ZERO_DENSE	266
8.21 include/barry/barry.hpp File Reference	266
8.21.1 Macro Definition Documentation	267
8.21.1.1 BARRY_HPP	268
8.21.1.2 BARRY_VERSION	268
8.21.1.3 BARRY_VERSION_MAYOR	268
8.21.1.4 BARRY_VERSION_MINOR	268
8.21.1.5 COUNTER_FUNCTION	268
8.21.1.6 COUNTER_LAMBDA	269
8.21.1.7 RULE_FUNCTION	269
8.21.1.8 RULE_LAMBDA	269
8.22 include/barry/cell-bones.hpp File Reference	269
8.23 include/barry/cell-meat.hpp File Reference	270
8.24 include/barry/col-bones.hpp File Reference	270
8.25 include/barry/counters-bones.hpp File Reference	270
8.26 include/barry/counters-meat.hpp File Reference	271
8.26.1 Macro Definition Documentation	272
8.26.1.1 COUNTER_TEMPLATE	272
8.26.1.2 COUNTER_TEMPLATE_ARGS	272
8.26.1.3 COUNTER_TYPE	272

8.26.1.4 COUNTERS_TEMPLATE	273
8.26.1.5 COUNTERS_TEMPLATE_ARGS	273
8.26.1.6 COUNTERS_TYPE	273
8.26.2 Function Documentation	273
8.26.2.1 count_fun()	273
8.26.2.2 COUNTER_TEMPLATE() [1/7]	273
8.26.2.3 COUNTER_TEMPLATE() [2/7]	274
8.26.2.4 COUNTER_TEMPLATE() [3/7]	274
8.26.2.5 COUNTER_TEMPLATE() [4/7]	274
8.26.2.6 COUNTER_TEMPLATE() [5/7]	274
8.26.2.7 COUNTER_TEMPLATE() [6/7]	274
8.26.2.8 COUNTER_TEMPLATE() [7/7]	274
8.26.2.9 Counters()	275
8.26.2.10 COUNTERS_TEMPLATE() [1/7]	275
8.26.2.11 COUNTERS_TEMPLATE() [2/7]	275
8.26.2.12 COUNTERS_TEMPLATE() [3/7]	275
8.26.2.13 COUNTERS_TEMPLATE() [4/7]	275
8.26.2.14 COUNTERS_TEMPLATE() [5/7]	275
8.26.2.15 COUNTERS_TEMPLATE() [6/7]	276
8.26.2.16 COUNTERS_TEMPLATE() [7/7]	276
8.26.2.17 data()	276
8.26.2.18 desc()	276
8.26.2.19 init_fun() [1/3]	276
8.26.2.20 init_fun() [2/3]	277
8.26.2.21 init_fun() [3/3]	277
8.26.2.22 name()	277
8.26.3 Variable Documentation	277
8.26.3.1 count_fun_	277
8.26.3.2 counter	277
8.26.3.3 counter_	278
8.26.3.4 data_	278
8.26.3.5 desc_	278
8.26.3.6 i	278
8.26.3.7 init_fun_	279
8.26.3.8 j	279
8.26.3.9 name_	279
8.26.3.10 noexcept	279
8.26.3.11 return	279
8.26.3.12 this	280
8.27 include/barry/counters/defm.hpp File Reference	280
8.27.1 Macro Definition Documentation	281
8.27.1.1 DEFM_COUNTER	281



8.27.1.2 DEFM_COUNTER_LAMBDA	282
8.27.1.3 DEFM_RULE	282
8.27.1.4 DEFM_RULE_LAMBDA	282
8.27.1.5 UNI0S	282
8.27.1.6 UNI1S	282
8.27.1.7 UNI2S	283
8.27.1.8 UNI3S	283
8.27.1.9 UNI4S	283
8.27.1.10 UNI5S	283
8.27.1.11 UNI6S	283
8.27.1.12 UNI7S	283
8.27.1.13 UNI8S	283
8.27.1.14 UNI9S	283
8.27.1.15 UNI_SUB	284
8.27.2 Typedef Documentation	284
8.27.2.1 DEFMArray	284
8.27.2.2 DEFMCouNter	284
8.27.2.3 DEFMCouNters	284
8.27.2.4 DEFMMoDel	284
8.27.2.5 DEFMRule	285
8.27.2.6 DEFMRules	285
8.27.2.7 DEFMStatsCouNter	285
8.27.2.8 DEFMSupport	285
8.28 include/barry/models/defm.hpp File Reference	285
8.29 include/barry/counters/network-css.hpp File Reference	286
8.29.1 Macro Definition Documentation	287
8.29.1.1 CSS_APPEND	287
8.29.1.2 CSS_CASE_ELSE	288
8.29.1.3 CSS_CASE_PERCEIVED	288
8.29.1.4 CSS_CASE_TRUTH	288
8.29.1.5 CSS_CHECK_SIZE	288
8.29.1.6 CSS_CHECK_SIZE_INIT	288
8.29.1.7 CSS_NET_COUNTER_LAMBDA_INIT	289
8.29.1.8 CSS_PERCEIVED_CELLS	289
8.29.1.9 CSS_SIZE	289
8.29.1.10 CSS_TRUE_CELLS	289
8.29.2 Function Documentation	289
8.29.2.1 counter_css_census01()	290
8.29.2.2 counter_css_census02()	290
8.29.2.3 counter_css_census03()	290
8.29.2.4 counter_css_census04()	290
8.29.2.5 counter_css_census05()	291

8.29.2.6 counter_css_census06()	291
8.29.2.7 counter_css_census07()	291
8.29.2.8 counter_css_census08()	291
8.29.2.9 counter_css_census09()	292
8.29.2.10 counter_css_census10()	292
8.29.2.11 counter_css_completely_false_recip_comiss()	292
8.29.2.12 counter_css_completely_false_recip_omiss()	292
8.29.2.13 counter_css_mixed_recip()	293
8.29.2.14 counter_css_partially_false_recip_commi()	293
8.29.2.15 counter_css_partially_false_recip_omiss()	293
8.30 include/barry/counters/network.hpp File Reference	294
8.30.1 Macro Definition Documentation	296
8.30.1.1 BARRY_ZERO_NETWORK	297
8.30.1.2 BARRY_ZERO_NETWORK_DENSE	297
8.30.1.3 NET_C_DATA_IDX	297
8.30.1.4 NET_C_DATA_NUM	297
8.30.1.5 NETWORK_COUNTER	297
8.30.1.6 NETWORK_COUNTER_LAMBDA	298
8.30.1.7 NETWORK_RULE	298
8.30.1.8 NETWORK_RULE_LAMBDA	298
8.30.1.9 NETWORKDENSE_COUNTER_LAMBDA	298
8.30.2 Typedef Documentation	299
8.30.2.1 NetCounter	299
8.30.2.2 NetCounters	299
8.30.2.3 NetModel	299
8.30.2.4 NetRule	299
8.30.2.5 NetRules	299
8.30.2.6 NetStatsCounter	300
8.30.2.7 NetSupport	300
8.30.2.8 Network	300
8.30.2.9 NetworkDense	300
8.30.3 Function Documentation	300
8.30.3.1 rules_zerodiag()	300
8.31 include/barry/counters/phylo.hpp File Reference	301
8.31.1 Macro Definition Documentation	303
8.31.1.1 DEFAULT_DUPLICATION	303
8.31.1.2 DUPL_DUPL	303
8.31.1.3 DUPL_EITH	303
8.31.1.4 DUPL_SPEC	304
8.31.1.5 IF_MATCHES	304
8.31.1.6 IF_NOTMATCHES	304
8.31.1.7 IS_DUPLICATION	304

8.31.1.8 IS_EITHER	304
8.31.1.9 IS_SPECIATION	305
8.31.1.10 MAKE_DUPL_VARS	305
8.31.1.11 PHYLO_CHECK_MISSING	305
8.31.1.12 PHYLO_COUNTER_LAMBDA	305
8.31.1.13 PHYLO_RULE_DYN_LAMBDA	306
8.31.2 Typedef Documentation	306
8.31.2.1 PhyloArray	306
8.31.2.2 PhyloCounter	306
8.31.2.3 PhyloCounters	306
8.31.2.4 PhyloModel	306
8.31.2.5 PhyloPowerSet	307
8.31.2.6 PhyloRule	307
8.31.2.7 PhyloRuleData	307
8.31.2.8 PhyloRuleDyn	307
8.31.2.9 PhyloRules	307
8.31.2.10 PhyloRulesDyn	307
8.31.2.11 PhyloStatsCounter	308
8.31.2.12 PhyloSupport	308
8.31.3 Function Documentation	308
8.31.3.1 get_last_name()	308
8.32 include/barry/freqtable.hpp File Reference	308
8.33 include/barry/model-bones.hpp File Reference	309
8.33.1 Function Documentation	309
8.33.1.1 keygen_default()	309
8.34 include/barry/model-meat.hpp File Reference	310
8.34.1 Macro Definition Documentation	310
8.34.1.1 MODEL_TEMPLATE	310
8.34.1.2 MODEL_TEMPLATE_ARGS	311
8.34.1.3 MODEL_TYPE	311
8.34.2 Function Documentation	311
8.34.2.1 likelihood_()	311
8.34.2.2 MODEL_TEMPLATE() [1/2]	311
8.34.2.3 MODEL_TEMPLATE() [2/2]	312
8.34.2.4 update_normalizing_constant()	312
8.35 include/barry/models/defm/defm-bones.hpp File Reference	312
8.36 include/barry/models/defm/defm-meat.hpp File Reference	313
8.36.1 Macro Definition Documentation	313
8.36.1.1 DEFM_LOOP_ARRAYS	313
8.36.1.2 DEFM_RANGES	313
8.36.2 Function Documentation	314
8.36.2.1 keygen_defm()	314

8.37 include/barry/models/geese.hpp File Reference . . . . .	314
8.38 include/barry/models/geese/flock-bones.hpp File Reference . . . . .	314
8.39 include/barry/models/geese/flock-meat.hpp File Reference . . . . .	315
8.40 include/barry/models/geese/geese-bones.hpp File Reference . . . . .	315
8.40.1 Macro Definition Documentation . . . . .	316
8.40.1.1 INITIALIZED . . . . .	316
8.40.2 Function Documentation . . . . .	316
8.40.2.1 keygen_full() . . . . .	316
8.40.2.2 RULE_FUNCTION() . . . . .	317
8.40.2.3 vec_diff() . . . . .	317
8.40.2.4 vector_caster() . . . . .	317
8.41 include/barry/models/geese/geese-meat-constructors.hpp File Reference . . . . .	317
8.42 include/barry/models/geese/geese-meat-likelihood.hpp File Reference . . . . .	318
8.43 include/barry/models/geese/geese-meat-likelihood_exhaust.hpp File Reference . . . . .	319
8.44 include/barry/models/geese/geese-meat-predict.hpp File Reference . . . . .	319
8.45 include/barry/models/geese/geese-meat-predict_exhaust.hpp File Reference . . . . .	320
8.46 include/barry/models/geese/geese-meat-predict_sim.hpp File Reference . . . . .	320
8.47 include/barry/models/geese/geese-meat-simulate.hpp File Reference . . . . .	321
8.48 include/barry/models/geese/geese-meat.hpp File Reference . . . . .	321
8.49 include/barry/models/geese/geese-node-bones.hpp File Reference . . . . .	322
8.50 include/barry/powerset-bones.hpp File Reference . . . . .	322
8.51 include/barry/powerset-meat.hpp File Reference . . . . .	323
8.52 include/barry/progress.hpp File Reference . . . . .	323
8.52.1 Macro Definition Documentation . . . . .	324
8.52.1.1 BARRY_PROGRESS_BAR_WIDTH . . . . .	324
8.53 include/barry/rules-bones.hpp File Reference . . . . .	324
8.53.1 Function Documentation . . . . .	324
8.53.1.1 rule_fun_default() . . . . .	325
8.54 include/barry/rules-meat.hpp File Reference . . . . .	325
8.55 include/barry/statscounter-bones.hpp File Reference . . . . .	325
8.56 include/barry/statscounter-meat.hpp File Reference . . . . .	326
8.56.1 Macro Definition Documentation . . . . .	327
8.56.1.1 STATSCOUNTER_TEMPLATE . . . . .	327
8.56.1.2 STATSCOUNTER_TEMPLATE_ARGS . . . . .	327
8.56.1.3 STATSCOUNTER_TYPE . . . . .	327
8.56.2 Function Documentation . . . . .	327
8.56.2.1 clear() . . . . .	327
8.56.2.2 for() . . . . .	328
8.56.2.3 resize() . . . . .	328
8.56.2.4 STATSCOUNTER_TEMPLATE() [1/9] . . . . .	328
8.56.2.5 STATSCOUNTER_TEMPLATE() [2/9] . . . . .	328
8.56.2.6 STATSCOUNTER_TEMPLATE() [3/9] . . . . .	328

8.56.2.7 STATSCOUNTER_TEMPLATE() [4/9]	328
8.56.2.8 STATSCOUNTER_TEMPLATE() [5/9]	329
8.56.2.9 STATSCOUNTER_TEMPLATE() [6/9]	329
8.56.2.10 STATSCOUNTER_TEMPLATE() [7/9]	329
8.56.2.11 STATSCOUNTER_TEMPLATE() [8/9]	329
8.56.2.12 STATSCOUNTER_TEMPLATE() [9/9]	329
8.56.3 Variable Documentation	329
8.56.3.1 counter	330
8.56.3.2 counter_deleted	330
8.56.3.3 counters	330
8.56.3.4 counters_	330
8.56.3.5 current_stats	330
8.56.3.6 EmptyArray	331
8.56.3.7 f_	331
8.56.3.8 j	331
8.56.3.9 return	331
8.57 include/barry/support-bones.hpp File Reference	331
8.58 include/barry/support-meat.hpp File Reference	332
8.58.1 Macro Definition Documentation	333
8.58.1.1 BARRY_SUPPORT_MEAT_HPP	333
8.58.1.2 SUPPORT_TEMPLATE	333
8.58.1.3 SUPPORT_TEMPLATE_ARGS	334
8.58.1.4 SUPPORT_TYPE	334
8.58.2 Function Documentation	334
8.58.2.1 calc_backend_dense()	334
8.58.2.2 calc_backend_sparse()	334
8.58.2.3 for()	334
8.58.2.4 if() [1/3]	335
8.58.2.5 if() [2/3]	335
8.58.2.6 if() [3/3]	335
8.58.2.7 insert_cell() [1/2]	335
8.58.2.8 insert_cell() [2/2]	335
8.58.2.9 rm_cell()	336
8.58.2.10 SUPPORT_TEMPLATE() [1/17]	336
8.58.2.11 SUPPORT_TEMPLATE() [2/17]	336
8.58.2.12 SUPPORT_TEMPLATE() [3/17]	336
8.58.2.13 SUPPORT_TEMPLATE() [4/17]	336
8.58.2.14 SUPPORT_TEMPLATE() [5/17]	337
8.58.2.15 SUPPORT_TEMPLATE() [6/17]	337
8.58.2.16 SUPPORT_TEMPLATE() [7/17]	337
8.58.2.17 SUPPORT_TEMPLATE() [8/17]	337
8.58.2.18 SUPPORT_TEMPLATE() [9/17]	337

8.58.2.19 SUPPORT_TEMPLATE() [10/17]	337
8.58.2.20 SUPPORT_TEMPLATE() [11/17]	338
8.58.2.21 SUPPORT_TEMPLATE() [12/17]	338
8.58.2.22 SUPPORT_TEMPLATE() [13/17]	338
8.58.2.23 SUPPORT_TEMPLATE() [14/17]	338
8.58.2.24 SUPPORT_TEMPLATE() [15/17]	338
8.58.2.25 SUPPORT_TEMPLATE() [16/17]	339
8.58.2.26 SUPPORT_TEMPLATE() [17/17]	339
8.58.3 Variable Documentation	339
8.58.3.1 array_bank	339
8.58.3.2 change_stats_different	339
8.58.3.3 coord_i	339
8.58.3.4 coord_j	339
8.58.3.5 counters	340
8.58.3.6 counters_	340
8.58.3.7 delete_counters	340
8.58.3.8 delete_rules	340
8.58.3.9 delete_rules_dyn	340
8.58.3.10 else	341
8.58.3.11 f_	341
8.58.3.12 hashes	341
8.58.3.13 return	341
8.58.3.14 rules	341
8.58.3.15 rules_	342
8.58.3.16 rules_dyn	342
8.58.3.17 stats_bank	342
8.58.3.18 tmp_chng	342
8.59 include/barry/typedefs.hpp File Reference	343
8.59.1 Typedef Documentation	344
8.59.1.1 Col_type	345
8.59.1.2 Counter_fun_type	345
8.59.1.3 Counts_type	345
8.59.1.4 MapVec_type	345
8.59.1.5 Row_type	346
8.59.1.6 Rule_fun_type	346
8.59.1.7 uint	346
8.59.2 Function Documentation	346
8.59.2.1 vec_equal()	346
8.59.2.2 vec_equal_approx()	347
8.59.2.3 vec_inner_prod() [1/2]	347
8.59.2.4 vec_inner_prod() [2/2]	347
8.60 README.md File Reference	347







# Chapter 1

## Main Page

### Barry: your to-go motif accountant

This repository contains a C++ template library that essentially counts sufficient statistics on binary arrays. Its primary goal is to provide a general framework for building discrete exponential-family models. A particular example is Exponential Random Graph Models (ERGMs), but we can use `barry` to deal with non-square arrays.

Among the key features included in `barry`, we have:

- Sparse arrays.
- User-defined count statistics.
- User-defined constrain of the support set.
- Powerset generation of binary arrays.
- Discrete Exponential Family Models module (DEFMs).
- Pooled DEFMs.

To use `barry`, you can either download the entire repository or, since it is header-only, the single header version `barry.hpp`.

This library was created and maintained by Dr. George G. Vega Yon as part of his doctoral dissertation "Essays on Bioinformatics and Social Network Analysis: Statistical and Computational Methods for Complex Systems."

## Examples

### Counting statistics in a graph

In the following code we create an array of size 5x5 of class `Network` (available in the namespace `netcounters`), add/remove ties, print the graph, and count common statistics used in ERGMs:

```
#include <iostream>
#include <ostream>
#include "../include/barry.hpp"
typedef std::vector< unsigned int > vuint;
int main() {
    // Creating network of size six with five ties
    netcounters::Network net(
        6, 6,
        {0, 0, 4, 4, 2, 0, 1},
        {1, 2, 0, 2, 4, 0, 1}
    );

    // How does this looks like?
    net.print("Current view");

    // Adding extra ties
    net += {1, 0};
    net(2, 0) = true;

    // And removing a couple
    net(0, 0) = false;
    net -= {1, 1};
    net.print("New view");

    // Initializing the data. The program deals with freeing the memory
    net.set_data(new netcounters::NetworkData, true);
    // Creating counter object for the network and adding stats to count
    netcounters::NetStatsCounter counter(&net);
    netcounters::counter_edges(counter.counters);
    netcounters::counter_ttriads(counter.counters);
    netcounters::counter_isolates(counter.counters);
    netcounters::counter_ctriads(counter.counters);
    netcounters::counter_mutual(counter.counters);

    // Counting and printing the results
    std::vector< double > counts = counter.count_all();

    std::cout <<
        "Edges          : " << counts[0] << std::endl <<
        "Transitive triads : " << counts[1] << std::endl <<
        "Isolates         : " << counts[2] << std::endl <<
        "C triads         : " << counts[3] << std::endl <<
        "Mutuals          : " << counts[4] << std::endl;

    return 0;
}
```

Compiling this program using g++

```
g++ -std=c++11 -Wall -pedantic 08-counts.cpp -o counts && ./counts
```

Yields the following output:

```
Current view
[ 0,] 1 1 1 . . .
[ 1,] . 1 . . . .
[ 2,] . . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
New view
[ 0,] . 1 1 . . .
[ 1,] 1 . . . . .
[ 2,] 1 . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
Edges          : 7
Transitive triads : 3
Isolates       : 2
C triads       : 1
Mutuals        : 3
```

## Features

### Efficient memory usage

One of the key features of `barry` is that it will handle memory efficiently. In the case of pooled-data models, the module for statistical models avoids double-counting support when possible by keeping track of what datasets (networks, for instance) share the same.

## Documentation

More information can be found in the Doxygen website [here](#) and in the PDF version of the documentation [here](#).

## Code of Conduct

Please note that the `barry` project is released with a [Contributor Code of Conduct](#). By contributing to this project, you agree to abide by its terms.



## Chapter 2

# Module Index

### 2.1 Modules

Here is a list of all modules:

Counting . . . . .	<a href="#">11</a>
Statistical Models . . . . .	<a href="#">11</a>
DEFMArray counters . . . . .	<a href="#">12</a>
Phylo counters . . . . .	<a href="#">21</a>
Phylo rules . . . . .	<a href="#">29</a>



## Chapter 3

# Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">BArray&lt; Cell_Type, Data_Type &gt;</a>	
Baseline class for binary arrays	35
<a href="#">BArrayCell&lt; Cell_Type, Data_Type &gt;</a>	49
<a href="#">BArrayCell_const&lt; Cell_Type, Data_Type &gt;</a>	52
<a href="#">BArrayDense&lt; Cell_Type, Data_Type &gt;</a>	
Baseline class for binary arrays	54
<a href="#">BArrayDenseCell&lt; Cell_Type, Data_Type &gt;</a>	70
<a href="#">BArrayDenseCell_const&lt; Cell_Type, Data_Type &gt;</a>	74
<a href="#">BArrayDenseCol&lt; Cell_Type, Data_Type &gt;</a>	74
<a href="#">BArrayDenseCol_const&lt; Cell_Type, Data_Type &gt;</a>	76
<a href="#">BArrayDenseRow&lt; Cell_Type, Data_Type &gt;</a>	78
<a href="#">BArrayDenseRow_const&lt; Cell_Type, Data_Type &gt;</a>	81
<a href="#">BArrayRow&lt; Cell_Type, Data_Type &gt;</a>	83
<a href="#">BArrayRow_const&lt; Cell_Type, Data_Type &gt;</a>	85
<a href="#">BArrayVector&lt; Cell_Type, Data_Type &gt;</a>	
Row or column of a <a href="#">BArray</a>	87
<a href="#">BArrayVector_const&lt; Cell_Type, Data_Type &gt;</a>	91
<a href="#">Cell&lt; Cell_Type &gt;</a>	
Entries in <a href="#">BArray</a> . For now, it only has two members:	95
<a href="#">Cell_const&lt; Cell_Type &gt;</a>	100
<a href="#">ConstBArrayRowIter&lt; Cell_Type, Data_Type &gt;</a>	100
<a href="#">Counter&lt; Array_Type, Data_Type &gt;</a>	
A counter function based on change statistics	102
<a href="#">Counters&lt; Array_Type, Data_Type &gt;</a>	
Vector of counters	107
<a href="#">DEFM</a>	111
<a href="#">DEFMCounterData</a>	
Data class used to store arbitrary uint or double vectors	114
<a href="#">DEFMData</a>	117
<a href="#">DEFMRuleData</a>	121
<a href="#">Entries&lt; Cell_Type &gt;</a>	
A wrapper class to store source, target, val from a <a href="#">BArray</a> object	122
<a href="#">Flock</a>	
A <a href="#">Flock</a> is a group of <a href="#">Geese</a>	124
<a href="#">FreqTable&lt; T &gt;</a>	
Frequency table of vectors	131

<a href="#">Geese</a>	
Annotated Phylo <a href="#">Model</a>	135
<a href="#">Model</a> < <a href="#">Array_Type</a> , <a href="#">Data_Counter_Type</a> , <a href="#">Data_Rule_Type</a> , <a href="#">Data_Rule_Dyn_Type</a> >	
General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:	148
<a href="#">NetCounterData</a>	
Data class used to store arbitrary uint or double vectors	162
<a href="#">NetworkData</a>	
Data class for Networks	164
<a href="#">Node</a>	
A single node for the model	166
<a href="#">NodeData</a>	
Data definition for the <a href="#">PhyloArray</a> class	172
<a href="#">PhyloCounterData</a>	173
<a href="#">PhyloRuleDynData</a>	176
<a href="#">PowerSet</a> < <a href="#">Array_Type</a> , <a href="#">Data_Rule_Type</a> >	
Powerset of a binary array	178
<a href="#">Progress</a>	
A simple progress bar	185
<a href="#">Rule</a> < <a href="#">Array_Type</a> , <a href="#">Data_Type</a> >	
Rule for determining if a cell should be included in a sequence	186
<a href="#">Rules</a> < <a href="#">Array_Type</a> , <a href="#">Data_Type</a> >	
Vector of objects of class <a href="#">Rule</a>	188
<a href="#">StatsCounter</a> < <a href="#">Array_Type</a> , <a href="#">Data_Type</a> >	
Count stats for a single Array	192
<a href="#">Support</a> < <a href="#">Array_Type</a> , <a href="#">Data_Counter_Type</a> , <a href="#">Data_Rule_Type</a> , <a href="#">Data_Rule_Dyn_Type</a> >	
Compute the support of sufficient statistics	195
<a href="#">vecHasher</a> < <a href="#">T</a> >	206



## Chapter 4

# File Index

### 4.1 File List

Here is a list of all files with brief descriptions:

include/barry/barray-bones.hpp . . . . .	207
include/barry/barray-iterator.hpp . . . . .	207
include/barry/barray-meat-operators.hpp . . . . .	208
include/barry/barray-meat.hpp . . . . .	212
include/barry/barraycell-bones.hpp . . . . .	230
include/barry/barraycell-meat.hpp . . . . .	230
include/barry/barraydense-bones.hpp . . . . .	231
include/barry/barraydense-meat-operators.hpp . . . . .	231
include/barry/barraydense-meat.hpp . . . . .	234
include/barry/barraydensecell-bones.hpp . . . . .	255
include/barry/barraydensecell-meat.hpp . . . . .	256
include/barry/barraydensecol-bones.hpp . . . . .	256
include/barry/barraydenserow-bones.hpp . . . . .	258
include/barry/barrayrow-bones.hpp . . . . .	259
include/barry/barrayrow-meat.hpp . . . . .	259
include/barry/barrayvector-bones.hpp . . . . .	261
include/barry/barrayvector-meat.hpp . . . . .	262
include/barry/barray-configuration.hpp . . . . .	262
include/barry/barray-debug.hpp . . . . .	264
include/barry/barray-macros.hpp . . . . .	265
include/barry/barray.hpp . . . . .	266
include/barry/cell-bones.hpp . . . . .	269
include/barry/cell-meat.hpp . . . . .	270
include/barry/col-bones.hpp . . . . .	270
include/barry/counters-bones.hpp . . . . .	270
include/barry/counters-meat.hpp . . . . .	271
include/barry/freqtable.hpp . . . . .	308
include/barry/model-bones.hpp . . . . .	309
include/barry/model-meat.hpp . . . . .	310
include/barry/powerset-bones.hpp . . . . .	322
include/barry/powerset-meat.hpp . . . . .	323
include/barry/progress.hpp . . . . .	323
include/barry/rules-bones.hpp . . . . .	324
include/barry/rules-meat.hpp . . . . .	325
include/barry/statscounter-bones.hpp . . . . .	325

<a href="#">include/barry/statscounter-meat.hpp</a>	326
<a href="#">include/barry/support-bones.hpp</a>	331
<a href="#">include/barry/support-meat.hpp</a>	332
<a href="#">include/barry/typedefs.hpp</a>	343
<a href="#">include/barry/counters/defm.hpp</a>	280
<a href="#">include/barry/counters/network-css.hpp</a>	286
<a href="#">include/barry/counters/network.hpp</a>	294
<a href="#">include/barry/counters/phylo.hpp</a>	301
<a href="#">include/barry/models/defm.hpp</a>	285
<a href="#">include/barry/models/geese.hpp</a>	314
<a href="#">include/barry/models/defm/defm-bones.hpp</a>	312
<a href="#">include/barry/models/defm/defm-meat.hpp</a>	313
<a href="#">include/barry/models/geese/flock-bones.hpp</a>	314
<a href="#">include/barry/models/geese/flock-meat.hpp</a>	315
<a href="#">include/barry/models/geese/geese-bones.hpp</a>	315
<a href="#">include/barry/models/geese/geese-meat-constructors.hpp</a>	317
<a href="#">include/barry/models/geese/geese-meat-likelihood.hpp</a>	318
<a href="#">include/barry/models/geese/geese-meat-likelihood_exhaust.hpp</a>	319
<a href="#">include/barry/models/geese/geese-meat-predict.hpp</a>	319
<a href="#">include/barry/models/geese/geese-meat-predict_exhaust.hpp</a>	320
<a href="#">include/barry/models/geese/geese-meat-predict_sim.hpp</a>	320
<a href="#">include/barry/models/geese/geese-meat-simulate.hpp</a>	321
<a href="#">include/barry/models/geese/geese-meat.hpp</a>	321
<a href="#">include/barry/models/geese/geese-node-bones.hpp</a>	322

## Chapter 5

# Module Documentation

### 5.1 Counting

#### Classes

- class [NetworkData](#)  
*Data class for Networks.*
- class [NodeData](#)  
*Data definition for the `PhyloArray` class.*
- class [Counter](#)< [Array\\_Type](#), [Data\\_Type](#) >  
*A counter function based on change statistics.*

#### 5.1.1 Detailed Description

`barry` includes a flexible way to generate counters based on change statistics. Since most of the time we are counting many motifs in a graph, change statistics make a reasonable (and efficient) way to make such counts.

In particular, let the motif be defined as  $s(y)$ , with  $y$  as the binary array. The change statistic when adding cell  $y_{ij}$ , i.e. when the cell moves from being empty to have a one, is defined as

$$\delta(y_{ij}) = s_{ij}^+(y) - s_{ij}^-(y),$$

where  $s_{ij}^+(y)$  and  $s_{ij}^-(y)$  represent the motif statistic with and without the  $ij$ -cell. For example, in the case of networks, the change statistic for the number of edges is always 1.

To count statistics in an array, the [\[Counter\]](#) class will empty the array, initialize the counters, and then start counting while adding at each step a single cell, until matching the original array.

### 5.2 Statistical Models

Statistical models available in `barry`.

## Classes

- class [Model](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) >  
*General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:*
- class [Flock](#)  
*A [Flock](#) is a group of [Geese](#).*
- class [Geese](#)  
*Annotated Phylo [Model](#).*

### 5.2.1 Detailed Description

Statistical models available in `barry`.

## 5.3 DEFMArray counters

[Counters](#) for network models.

## Functions

- void [counter\\_ones](#) ([DEFMCounters](#) \*counters, int covar\_index=-1, std::string vname="")  
*Prevalence of ones.*
- void [counter\\_transition](#) ([DEFMCounters](#) \*counters, std::vector< size\_t > coords, std::vector< bool > signs, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="")  
*Prevalence of ones.*
- void [counter\\_fixed\\_effect](#) ([DEFMCounters](#) \*counters, int covar\_index, double k, std::string vname="")  
*Prevalence of ones.*
- template<typename Tnet = Network>  
void [counter\\_edges](#) ([NetCounters](#)< Tnet > \*counters)  
*Number of edges.*
- template<typename Tnet = Network>  
void [counter\\_isolates](#) ([NetCounters](#)< Tnet > \*counters)  
*Number of isolated vertices.*
- template<> void [counter\\_isolates](#) ([NetCounters](#)< [NetworkDense](#) > \*counters)
- template<typename Tnet = Network>  
void [counter\\_mutual](#) ([NetCounters](#)< Tnet > \*counters)  
*Number of mutual ties.*
- template<typename Tnet = Network>  
void [counter\\_istar2](#) ([NetCounters](#)< Tnet > \*counters)
- template<> void [counter\\_istar2](#) ([NetCounters](#)< [NetworkDense](#) > \*counters)
- template<typename Tnet = Network>  
void [counter\\_ostar2](#) ([NetCounters](#)< Tnet > \*counters)
- template<> void [counter\\_ostar2](#) ([NetCounters](#)< [NetworkDense](#) > \*counters)
- template<typename Tnet = Network>  
void [counter\\_ttriads](#) ([NetCounters](#)< Tnet > \*counters)
- template<> void [counter\\_ttriads](#) ([NetCounters](#)< [NetworkDense](#) > \*counters)
- template<typename Tnet = Network>  
void [counter\\_ctriads](#) ([NetCounters](#)< Tnet > \*counters)
- template<> void [counter\\_ctriads](#) ([NetCounters](#)< [NetworkDense](#) > \*counters)

- `template<typename Tnet = Network>`  
`void counter_density (NetCounters< Tnet > *counters)`
- `template<typename Tnet = Network>`  
`void counter_iddegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_iddegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_odegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_odegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_absdiff (NetCounters< Tnet > *counters, uint attr_id, double alpha=1.0)`  
*Sum of absolute attribute difference between ego and alter.*
- `template<typename Tnet = Network>`  
`void counter_diff (NetCounters< Tnet > *counters, uint attr_id, double alpha=1.0, double tail_head=true)`  
*Sum of attribute difference between ego and alter to pow(alpha)*
- **NETWORK\_COUNTER** (init\_single\_attr)
- `template<typename Tnet = Network>`  
`void counter_nodeicov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodeocov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodcov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodematch (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_iddegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given in-degree.*
- `template<> void counter_iddegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_degree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*

## Returns true if the cell is free

### Parameters

<i>rules</i>	A pointer to a DEFMRules object ( <code>Rules&lt;DEFMArray, bool&gt;</code> ).
--------------	--

- `void rules_markov_fixed (DEFMRules *rules, size_t markov_order)`  
*Number of edges.*

## 5.3.1 Detailed Description

`Counters` for network models.

### Parameters

<i>counters</i>	A pointer to a DEFMCounters object ( <code>Counters&lt;DEFMArray, DEFMCounterData&gt;</code> ).
<i>counters</i>	A pointer to a NetCounters object ( <code>Counters&lt;Network, NetCounterData&gt;</code> ).

## 5.3.2 Function Documentation

### 5.3.2.1 counter\_absdiff()

```
template<typename Tnet = Network>
void counter_absdiff (
    NetCounters< Tnet > * counters,
    uint attr_id,
    double alpha = 1.0 ) [inline]
```

Sum of absolute attribute difference between ego and alter.

Definition at line 910 of file network.hpp.

### 5.3.2.2 counter\_ctriads() [1/2]

```
template<>
void counter_ctriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 665 of file network.hpp.

### 5.3.2.3 counter\_ctriads() [2/2]

```
template<typename Tnet = Network>
void counter_ctriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 610 of file network.hpp.

### 5.3.2.4 counter\_degree()

```
template<typename Tnet = Network>
void counter_degree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1328 of file network.hpp.

### 5.3.2.5 counter\_density()

```
template<typename Tnet = Network>
void counter_density (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 731 of file network.hpp.

### 5.3.2.6 counter\_diff()

```
template<typename Tnet = Network>
void counter_diff (
    NetCounters< Tnet > * counters,
    uint attr_id,
    double alpha = 1.0,
    double tail_head = true ) [inline]
```

Sum of attribute difference between ego and alter to pow(alpha)

Definition at line 955 of file network.hpp.

### 5.3.2.7 counter\_edges()

```
template<typename Tnet = Network>
void counter_edges (
    NetCounters< Tnet > * counters ) [inline]
```

Number of edges.

Definition at line 152 of file network.hpp.

### 5.3.2.8 counter\_fixed\_effect()

```
void counter_fixed_effect (
    DEFMCounters * counters,
    int covar_index,
    double k,
    std::string vname = "" ) [inline]
```

Prevalence of ones.

#### Parameters

<i>counters</i>	Pointer ot a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 506 of file defm.hpp.

#### 5.3.2.9 counter\_iddegree() [1/2]

```
template<>
void counter_iddegree (
    NetCounters< NetworkDense > * counters,
    std::vector< uint > d ) [inline]
```

Definition at line 1172 of file network.hpp.

#### 5.3.2.10 counter\_iddegree() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given in-degree.

Definition at line 1125 of file network.hpp.

#### 5.3.2.11 counter\_iddegree15() [1/2]

```
template<>
void counter_iddegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 787 of file network.hpp.

#### 5.3.2.12 counter\_iddegree15() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 759 of file network.hpp.



**5.3.2.13 counter\_isolates()** [1/2]

```
template<>
void counter_isolates (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 215 of file network.hpp.

**5.3.2.14 counter\_isolates()** [2/2]

```
template<typename Tnet = Network>
void counter_isolates (
    NetCounters< Tnet > * counters ) [inline]
```

Number of isolated vertices.

Definition at line 175 of file network.hpp.

**5.3.2.15 counter\_istar2()** [1/2]

```
template<>
void counter_istar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 338 of file network.hpp.

**5.3.2.16 counter\_istar2()** [2/2]

```
template<typename Tnet = Network>
void counter_istar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 312 of file network.hpp.

**5.3.2.17 counter\_mutual()**

```
template<typename Tnet = Network>
void counter_mutual (
    NetCounters< Tnet > * counters ) [inline]
```

Number of mutual ties.

Definition at line 256 of file network.hpp.

#### 5.3.2.18 counter\_nodecov()

```
template<typename Tnet = Network>
void counter_nodecov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1068 of file network.hpp.

#### 5.3.2.19 counter\_nodeicov()

```
template<typename Tnet = Network>
void counter_nodeicov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1018 of file network.hpp.

#### 5.3.2.20 counter\_nodematch()

```
template<typename Tnet = Network>
void counter_nodematch (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1093 of file network.hpp.

#### 5.3.2.21 counter\_nodeocov()

```
template<typename Tnet = Network>
void counter_nodeocov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1043 of file network.hpp.

#### 5.3.2.22 counter\_odegree() [1/2]

```
template<>
void counter_odegree (
    NetCounters< NetworkDense > * counters,
    std::vector< uint > d ) [inline]
```

Definition at line 1273 of file network.hpp.

**5.3.2.23 counter\_odegree()** [2/2]

```
template<typename Tnet = Network>
void counter_odegree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1225 of file network.hpp.

**5.3.2.24 counter\_odegree15()** [1/2]

```
template<>
void counter_odegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 864 of file network.hpp.

**5.3.2.25 counter\_odegree15()** [2/2]

```
template<typename Tnet = Network>
void counter_odegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 836 of file network.hpp.

**5.3.2.26 counter\_ones()**

```
void counter_ones (
    DEFMCounters * counters,
    int covar_index = -1,
    std::string vname = "" ) [inline]
```

Prevalence of ones.

**Parameters**

<i>counters</i>	Pointer ot a vector of counters
<i>covar_index</i>	If $\geq$ than 0, then the interaction

Definition at line 189 of file defm.hpp.

**5.3.2.27 counter\_ostar2()** [1/2]

```
template<>
void counter_ostar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 404 of file network.hpp.

**5.3.2.28 counter\_ostar2()** [2/2]

```
template<typename Tnet = Network>
void counter_ostar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 376 of file network.hpp.

**5.3.2.29 counter\_transition()**

```
void counter_transition (
    DEFMCounters * counters,
    std::vector< size_t > coords,
    std::vector< bool > signs,
    size_t m_order,
    size_t n_y,
    int covar_index = -1,
    std::string vname = "" ) [inline]
```

Prevalence of ones.

**Parameters**

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 248 of file defm.hpp.

**5.3.2.30 counter\_ttriads()** [1/2]

```
template<>
void counter_ttriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 531 of file network.hpp.

**5.3.2.31 counter\_ttriads() [2/2]**

```
template<typename Tnet = Network>
void counter_ttriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 441 of file network.hpp.

**5.3.2.32 NETWORK\_COUNTER()**

```
NETWORK_COUNTER (
    init_single_attr )
```

Definition at line 999 of file network.hpp.

**5.3.2.33 rules\_markov\_fixed()**

```
void rules_markov_fixed (
    DEFMRules * rules,
    size_t markov_order ) [inline]
```

Number of edges.

Definition at line 542 of file defm.hpp.

**5.4 Phylo counters**

[Counters](#) for phylogenetic modeling.

**Functions**

- void [counter\\_overall\\_gains](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Overall functional gains.*
- void [counter\\_gains](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Functional gains for a specific function (nfun).*
- void [counter\\_gains\\_k\\_offspring](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, [uint](#) k=1u, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*k genes gain function nfun*
- void [counter\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- void [counter\\_preserve\\_pseudogene](#) ([PhyloCounters](#) \*counters, unsigned int nfunA, unsigned int nfunB, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many pairs of genes preserve pseudostate.*
- void [counter\\_prop\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*

- void `counter_overall_loss` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Overall functional loss.*
- void `counter_maxfun` (`PhyloCounters *counters`, uint lb, uint ub, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Cap the number of functions per gene.*
- void `counter_loss` (`PhyloCounters *counters`, std::vector< uint > nfun, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total count of losses for an specific function.*
- void `counter_overall_changes` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of changes. Use this statistic to account for "preservation".*
- void `counter_subfun` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total count of Sub-functionalization events.*
- void `counter_cogain` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Co-evolution (joint gain or loss)*
- void `counter_longest` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Longest branch mutates (either by gain or by loss)*
- void `counter_neofun` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events.*
- void `counter_pairwise_neofun_singlefun` (`PhyloCounters *counters`, uint nfunA, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events  $\sum_u \sum_{w < u} [x(u,a)*(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$  change  
stat:  $\delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void `counter_neofun_a2b` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events.*
- void `counter_co_opt` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Function co-opting.*
- void `counter_k_genes_changing` (`PhyloCounters *counters`, unsigned int k, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Indicator function. Equals to one if k genes changed and zero otherwise.*
- void `counter_less_than_p_prop_genes_changing` (`PhyloCounters *counters`, double p, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Indicator function. Equals to one if k genes changed and zero otherwise.*
- void `counter_gains_from_0` (`PhyloCounters *counters`, std::vector< uint > nfun, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_overall_gains_from_0` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_overall_change` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_preserving` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_first_gain` (`PhyloCounters *counters`, uint nfunA, uint nfunB, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*

## 5.4.1 Detailed Description

`Counters` for phylogenetic modeling.

### Parameters

<code>counters</code>	A pointer to a <code>PhyloCounters</code> object ( <code>Counters&lt;PhyloArray, PhyloCounterData&gt;</code> ).
-----------------------	---

## 5.4.2 Function Documentation

### 5.4.2.1 counter\_co\_opt()

```
void counter_co_opt (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Function co-opting.

Function co-opting of functions A and B happens when, for example, function B is gained as a new featured leveraging what function A already does; without losing function A. The sufficient statistic is defined as follows:

$$x_{pa}(1 - x_{pb}) \sum_{i < j} \left[ x_{ia}^p (1 - x_{ib}^p) x_{ja}^p x_{jb}^p + x_{ja}^p (1 - x_{jb}^p) x_{ia}^p x_{ib}^p \right]$$

This algorithm implements the change statistic.

Definition at line 1393 of file phylo.hpp.

### 5.4.2.2 counter\_cogain()

```
void counter_cogain (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Co-evolution (joint gain or loss)

Needs to specify pairs of functions (nfunA, nfunB).

Definition at line 888 of file phylo.hpp.

### 5.4.2.3 counter\_gains()

```
void counter_gains (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Functional gains for a specific function (nfun).

Definition at line 193 of file phylo.hpp.

#### 5.4.2.4 counter\_gains\_from\_0()

```
void counter_gains_from_0 (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1727 of file phylo.hpp.

#### 5.4.2.5 counter\_gains\_k\_offspring()

```
void counter_gains_k_offspring (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    uint k = 1u,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

k genes gain function nfun

Definition at line 253 of file phylo.hpp.

#### 5.4.2.6 counter\_genes\_changing()

```
void counter_genes_changing (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 325 of file phylo.hpp.

#### 5.4.2.7 counter\_k\_genes\_changing()

```
void counter_k_genes_changing (
    PhyloCounters * counters,
    unsigned int k,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Indicator function. Equals to one if  $k$  genes changed and zero otherwise.

Definition at line 1491 of file phylo.hpp.



#### 5.4.2.8 counter\_less\_than\_p\_prop\_genes\_changing()

```
void counter_less_than_p_prop_genes_changing (
    PhyloCounters * counters,
    double p,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Indicator function. Equals to one if  $k$  genes changed and zero otherwise.

< How many genes diverge the parent

Definition at line 1611 of file phylo.hpp.

#### 5.4.2.9 counter\_longest()

```
void counter_longest (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Longest branch mutates (either by gain or by loss)

Definition at line 945 of file phylo.hpp.

#### 5.4.2.10 counter\_loss()

```
void counter_loss (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total count of losses for an specific function.

Definition at line 688 of file phylo.hpp.

#### 5.4.2.11 counter\_maxfuns()

```
void counter_maxfuns (
    PhyloCounters * counters,
    uint lb,
    uint ub,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Cap the number of functions per gene.

Definition at line 626 of file phylo.hpp.

#### 5.4.2.12 counter\_neofun()

```
void counter_neofun (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1115 of file phylo.hpp.

#### 5.4.2.13 counter\_neofun\_a2b()

```
void counter_neofun_a2b (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1260 of file phylo.hpp.

#### 5.4.2.14 counter\_overall\_changes()

```
void counter_overall_changes (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of changes. Use this statistic to account for "preservation".

Definition at line 740 of file phylo.hpp.

#### 5.4.2.15 counter\_overall\_gains()

```
void counter_overall_gains (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional gains.

Total number of gains (irrespective of the function).

Definition at line 155 of file phylo.hpp.

**5.4.2.16 counter\_overall\_gains\_from\_0()**

```
void counter_overall_gains_from_0 (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1793 of file phylo.hpp.

**5.4.2.17 counter\_overall\_loss()**

```
void counter_overall_loss (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional loss.

Definition at line 578 of file phylo.hpp.

**5.4.2.18 counter\_pairwise\_first\_gain()**

```
void counter_pairwise_first_gain (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.  $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 2045 of file phylo.hpp.

**5.4.2.19 counter\_pairwise\_neofun\_singlefun()**

```
void counter_pairwise_neofun_singlefun (
    PhyloCounters * counters,
    uint nfunA,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events  $\sum_u \sum_{w < u} [x(u,a)*(1-x(w,a)) + (1-x(u,a)) * x(w,a)]$  change stat:  $\Delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$

Definition at line 1196 of file phylo.hpp.

#### 5.4.2.20 counter\_pairwise\_overall\_change()

```
void counter_pairwise_overall_change (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1841 of file phylo.hpp.

#### 5.4.2.21 counter\_pairwise\_preserving()

```
void counter_pairwise_preserving (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.  $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1906 of file phylo.hpp.

#### 5.4.2.22 counter\_preserve\_pseudogene()

```
void counter_preserve_pseudogene (
    PhyloCounters * counters,
    unsigned int nfunA,
    unsigned int nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many pairs of genes preserve pseudostate.

Definition at line 394 of file phylo.hpp.

#### 5.4.2.23 counter\_prop\_genes\_changing()

```
void counter_prop_genes_changing (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 476 of file phylo.hpp.

#### 5.4.2.24 counter\_subfun()

```
void counter_subfun (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total count of Sub-functionalization events.

It requires to specify data = {funA, funB}

Definition at line 799 of file phylo.hpp.

## 5.5 Phylo rules

[Rules](#) for phylogenetic modeling.

### Classes

- class [PhyloRuleDynData](#)

### Functions

- void [rule\\_dyn\\_limit\\_changes](#) ([PhyloSupport](#) \*support, [uint](#) pos, [uint](#) lb, [uint](#) ub, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Overall functional gains.*

#### 5.5.1 Detailed Description

[Rules](#) for phylogenetic modeling.

##### Parameters

<i>rules</i>	A pointer to a <a href="#">PhyloRules</a> object ( <a href="#">Rules</a> < <a href="#">PhyloArray</a> , <a href="#">PhyloRuleData</a> >).
--------------	---

#### 5.5.2 Function Documentation

##### 5.5.2.1 rule\_dyn\_limit\_changes()

```
void rule_dyn_limit_changes (
    PhyloSupport * support,
    uint pos,
```

```
uint lb,  
uint ub,  
unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional gains.

#### Parameters

<i>support</i>	Support of a model.
<i>pos</i>	Position of the focal statistic.
<i>lb</i>	Lower bound
<i>ub</i>	Upper bound

#### Returns

(void) adds a rule limiting the support of the model.

Definition at line 2177 of file phylo.hpp.

## Chapter 6

# Namespace Documentation

### 6.1 `barry` Namespace Reference

`barry`: Your go-to motif accountant

#### Namespaces

- [counters](#)

*Tree class and Treeliterator class.*

#### 6.1.1 Detailed Description

`barry`: Your go-to motif accountant

### 6.2 `barry::counters` Namespace Reference

Tree class and Treeliterator class.

#### Namespaces

- [defm](#)
- [network](#)
- [phylo](#)

#### 6.2.1 Detailed Description

Tree class and Treeliterator class.

### 6.3 `barry::counters::defm` Namespace Reference

### 6.4 `barry::counters::network` Namespace Reference

### 6.5 `barry::counters::phylo` Namespace Reference

### 6.6 `CHECK` Namespace Reference

Integer constants used to specify which cell should be check.

#### Variables

- `const int BOTH` = -1
- `const int NONE` = 0
- `const int ONE` = 1
- `const int TWO` = 2

#### 6.6.1 Detailed Description

Integer constants used to specify which cell should be check.

#### 6.6.2 Variable Documentation

##### 6.6.2.1 `BOTH`

```
const int CHECK::BOTH = -1
```

Definition at line 28 of file typedefs.hpp.

##### 6.6.2.2 `NONE`

```
const int CHECK::NONE = 0
```

Definition at line 29 of file typedefs.hpp.



### 6.6.2.3 ONE

```
const int CHECK::ONE = 1
```

Definition at line 30 of file typedefs.hpp.

### 6.6.2.4 TWO

```
const int CHECK::TWO = 2
```

Definition at line 31 of file typedefs.hpp.

## 6.7 EXISTS Namespace Reference

Integer constants used to specify which cell should be check to exist or not.

### Variables

- `const int BOTH = -1`
- `const int NONE = 0`
- `const int ONE = 1`
- `const int TWO = 1`
- `const int UNKNOWN = -1`
- `const int AS_ZERO = 0`
- `const int AS_ONE = 1`

### 6.7.1 Detailed Description

Integer constants used to specify which cell should be check to exist or not.

### 6.7.2 Variable Documentation

#### 6.7.2.1 AS\_ONE

```
const int EXISTS::AS_ONE = 1
```

Definition at line 46 of file typedefs.hpp.

#### 6.7.2.2 AS\_ZERO

```
const int EXISTS::AS_ZERO = 0
```

Definition at line 45 of file typedefs.hpp.

#### 6.7.2.3 BOTH

```
const int EXISTS::BOTH = -1
```

Definition at line 39 of file typedefs.hpp.

#### 6.7.2.4 NONE

```
const int EXISTS::NONE = 0
```

Definition at line 40 of file typedefs.hpp.

#### 6.7.2.5 ONE

```
const int EXISTS::ONE = 1
```

Definition at line 41 of file typedefs.hpp.

#### 6.7.2.6 TWO

```
const int EXISTS::TWO = 1
```

Definition at line 42 of file typedefs.hpp.

#### 6.7.2.7 UNKNOWN

```
const int EXISTS::UNKNOWN = -1
```

Definition at line 44 of file typedefs.hpp.

## Chapter 7

# Class Documentation

### 7.1 BArray< Cell\_Type, Data\_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barray-bones.hpp>
```

#### Public Member Functions

- bool `operator==` (const BArray< Cell\_Type, Data\_Type > &Array\_)
- ~BArray ()
- void `out_of_range` (uint i, uint j) const
- Cell\_Type `get_cell` (uint i, uint j, bool check\_bounds=true) const
- std::vector< Cell\_Type > `get_col_vec` (uint i, bool check\_bounds=true) const
- std::vector< Cell\_Type > `get_row_vec` (uint i, bool check\_bounds=true) const
- void `get_col_vec` (std::vector< Cell\_Type > \*x, uint i, bool check\_bounds=true) const
- void `get_row_vec` (std::vector< Cell\_Type > \*x, uint i, bool check\_bounds=true) const
- const Row\_type< Cell\_Type > & `row` (uint i, bool check\_bounds=true) const
- const Col\_type< Cell\_Type > & `col` (uint i, bool check\_bounds=true) const
- Entries< Cell\_Type > `get_entries` () const

*Get the edgelist.*

- void `transpose` ()
- void `clear` (bool hard=true)
- void `resize` (uint N\_, uint M\_)
- void `reserve` ()
- void `print` (const char \*fmt=nullptr,...) const
- bool `is_dense` () const noexcept

#### Constructors

##### Parameters

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An unsigned int vector ranging from 0 to M_
target	When <code>true</code> tries to add repeated observations.

- **BArray** ()  
*Zero-size array.*
  - **BArray** (uint N\_, uint M\_)  
*Empty array.*
  - **BArray** (uint N\_, uint M\_, const std::vector< uint > &source, const std::vector< uint > &target, const std::vector< Cell\_Type > &value, bool add=true)  
*Edgelist with data.*
  - **BArray** (uint N\_, uint M\_, const std::vector< uint > &source, const std::vector< uint > &target, bool add=true)  
*Edgelist with no data (simpler)*
  - **BArray** (const BArray< Cell\_Type, Data\_Type > &Array\_, bool copy\_data=false)  
*Copy constructor.*
  - **BArray**< Cell\_Type, Data\_Type > & operator= (const BArray< Cell\_Type, Data\_Type > &Array\_)  
*Assignment constructor.*
  - **BArray** (BArray< Cell\_Type, Data\_Type > &&x) noexcept  
*Move operator.*
  - **BArray**< Cell\_Type, Data\_Type > & operator= (BArray< Cell\_Type, Data\_Type > &&x) noexcept  
*Move assignment.*
- 
- void **set\_data** (Data\_Type \*data\_, bool delete\_data\_=false)  
*Set the data object.*
  - Data\_Type \* **D\_ptr** ()
  - const Data\_Type \* **D\_ptr** () const
  - Data\_Type & **D** ()
  - const Data\_Type & **D** () const
  - void **flush\_data** ()

### Queries

*is\_empty* queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

#### Parameters

i,j	<i>Coordinates</i>
check_bounds	<i>If false avoids checking bounds.</i>

- bool **is\_empty** (uint i, uint j, bool check\_bounds=true) const
- uint **nrow** () const noexcept
- uint **ncol** () const noexcept
- uint **nnozero** () const noexcept
- Cell< Cell\_Type > **default\_val** () const

### Cell-wise insertion/deletion

#### Parameters

i,j	<i>Row,column</i>
check_bounds	<i>When true and out of range, the function throws an error.</i>
check_exists	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of swap_cells, check if either of both cells exists/don't exist.</i>

- `BArray< Cell_Type, Data_Type > & operator+= (const std::pair< uint, uint > &coords)`
- `BArray< Cell_Type, Data_Type > & operator-= (const std::pair< uint, uint > &coords)`
- `BArrayCell< Cell_Type, Data_Type > operator() (uint i, uint j, bool check_bounds=true)`
- `const Cell_Type operator() (uint i, uint j, bool check_bounds=true) const`
- `void rm_cell (uint i, uint j, bool check_bounds=true, bool check_exists=true)`
- `void insert_cell (uint i, uint j, const Cell< Cell_Type > &v, bool check_bounds, bool check_exists)`
- `void insert_cell (uint i, uint j, Cell< Cell_Type > &&v, bool check_bounds, bool check_exists)`
- `void insert_cell (uint i, uint j, Cell_Type v, bool check_bounds, bool check_exists)`
- `void swap_cells (uint i0, uint j0, uint i1, uint j1, bool check_bounds=true, int check_exists=CHECK::BOTH, int *report=nullptr)`
- `void toggle_cell (uint i, uint j, bool check_bounds=true, int check_exists=EXISTS::UNKNOWN)`
- `void toggle_lock (uint i, uint j, bool check_bounds=true)`

### Column/row wise interchange

- `void swap_rows (uint i0, uint i1, bool check_bounds=true)`
- `void swap_cols (uint j0, uint j1, bool check_bounds=true)`
- `void zero_row (uint i, bool check_bounds=true)`
- `void zero_col (uint j, bool check_bounds=true)`

### Arithmetic operators

- `BArray< Cell_Type, Data_Type > & operator+= (const BArray< Cell_Type, Data_Type > &rhs)`
- `BArray< Cell_Type, Data_Type > & operator+= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator-= (const BArray< Cell_Type, Data_Type > &rhs)`
- `BArray< Cell_Type, Data_Type > & operator-= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator/= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator*= (const Cell_Type &rhs)`

### Public Attributes

- `bool visited = false`

### Friends

- `class BArrayCell< Cell_Type, Data_Type >`
- `class BArrayCell_const< Cell_Type, Data_Type >`

## 7.1.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArray< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

`BArray` class objects are arbitrary arrays in which non-empty cells hold data of type `Cell_Type`. The non-empty cells are stored by row and indexed using `unordered_maps`, i.e. `std::vector< std::unordered_map<unsigned int, Cell_Type> >`.

#### Template Parameters

<code>Cell_Type</code>	Type of cell (any type).
<code>Data_Type</code>	Data type of the array (bool default).

Definition at line 28 of file barray-bones.hpp.

## 7.1.2 Constructor & Destructor Documentation

### 7.1.2.1 BArray() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray ( ) [inline]
```

Zero-size array.

Definition at line 69 of file barray-bones.hpp.

### 7.1.2.2 BArray() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_ ) [inline]
```

Empty array.

Definition at line 72 of file barray-bones.hpp.

### 7.1.2.3 BArray() [3/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    const std::vector< Cell_Type > & value,
    bool add = true )
```

Edgelist with data.

#### 7.1.2.4 BArray() [4/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    bool add = true )
```

Edgelist with no data (simpler)

#### 7.1.2.5 BArray() [5/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    const BArray< Cell_Type, Data_Type > & Array_,
    bool copy_data = false )
```

Copy constructor.

#### 7.1.2.6 BArray() [6/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move operator.

#### 7.1.2.7 ~BArray()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::~~BArray ( )
```

### 7.1.3 Member Function Documentation

#### 7.1.3.1 clear()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::clear (
    bool hard = true )
```

#### 7.1.3.2 col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Col_type< Cell_Type >& BArray< Cell_Type, Data_Type >::col (
    uint i,
    bool check_bounds = true ) const
```

#### 7.1.3.3 D() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type& BArray< Cell_Type, Data_Type >::D ( )
```

#### 7.1.3.4 D() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type& BArray< Cell_Type, Data_Type >::D ( ) const
```

#### 7.1.3.5 D\_ptr() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( )
```

#### 7.1.3.6 D\_ptr() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( ) const
```

#### 7.1.3.7 default\_val()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell<Cell_Type> BArray< Cell_Type, Data_Type >::default_val ( ) const
```

#### 7.1.3.8 flush\_data()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::flush_data ( )
```



**7.1.3.9 get\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell_Type BArray< Cell_Type, Data_Type >::get_cell (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.1.3.10 get\_col\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**7.1.3.11 get\_col\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_col_vec (
    uint i,
    bool check_bounds = true ) const
```

**7.1.3.12 get\_entries()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Entries<Cell_Type> BArray< Cell_Type, Data_Type >::get_entries ( ) const
```

Get the edgelist.

`Entries` is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

Returns

`Entries<Cell_Type>`

**7.1.3.13 get\_row\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**7.1.3.14 get\_row\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_row_vec (
    uint i,
    bool check_bounds = true ) const
```

**7.1.3.15 insert\_cell() [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell< Cell_Type > && v,
    bool check_bounds,
    bool check_exists )
```

**7.1.3.16 insert\_cell() [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell_Type v,
    bool check_bounds,
    bool check_exists )
```

**7.1.3.17 insert\_cell() [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool check_exists )
```

**7.1.3.18 is\_dense()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 240 of file `barray-bones.hpp`.

**7.1.3.19 is\_empty()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_empty (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.1.3.20 ncol()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::ncol ( ) const [noexcept]
```

**7.1.3.21 nnozero()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::nnozero ( ) const [noexcept]
```

**7.1.3.22 nrow()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::nrow ( ) const [noexcept]
```

**7.1.3.23 operator()() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell<Cell_Type,Data_Type> BArray< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true )
```

**7.1.3.24 operator()() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArray< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.1.3.25 operator\*=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

**7.1.3.26 operator+=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

**7.1.3.27 operator+=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & rhs )
```

**7.1.3.28 operator+=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const std::pair< uint, uint > & coords )
```

**7.1.3.29 operator-=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

**7.1.3.30 operator-=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & rhs )
```

**7.1.3.31 operator-=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const std::pair< uint, uint > & coords )
```

**7.1.3.32 operator/=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & rhs )
```

**7.1.3.33 operator=( ) [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move assignment.

**7.1.3.34 operator=( ) [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

Assignment constructor.

**7.1.3.35 operator==( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::operator== (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

**7.1.3.36 out\_of\_range( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::out_of_range (
    uint i,
    uint j ) const
```

#### 7.1.3.37 print()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const
```

#### 7.1.3.38 reserve()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::reserve ( )
```

#### 7.1.3.39 resize()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::resize (
    uint N_,
    uint M_ )
```

#### 7.1.3.40 rm\_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::rm_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    bool check_exists = true )
```

#### 7.1.3.41 row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Row_type< Cell_Type >& BArray< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true ) const
```

#### 7.1.3.42 set\_data()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false )
```

Set the data object.

## Parameters

<i>data_</i>	
<i>delete_↔</i> <i>data_</i>	

**7.1.3.43 swap\_cells()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cells (
    uint i0,
    uint j0,
    uint i1,
    uint j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr )
```

**7.1.3.44 swap\_cols()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cols (
    uint j0,
    uint j1,
    bool check_bounds = true )
```

**7.1.3.45 swap\_rows()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_rows (
    uint i0,
    uint i1,
    bool check_bounds = true )
```

**7.1.3.46 toggle\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN )
```

#### 7.1.3.47 toggle\_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_lock (
    uint i,
    uint j,
    bool check_bounds = true )
```

#### 7.1.3.48 transpose()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::transpose ( )
```

#### 7.1.3.49 zero\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_col (
    uint j,
    bool check_bounds = true )
```

#### 7.1.3.50 zero\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_row (
    uint i,
    bool check_bounds = true )
```

### 7.1.4 Friends And Related Function Documentation

#### 7.1.4.1 BArrayCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barray-bones.hpp`.



### 7.1.4.2 BArrayCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barray-bones.hpp.

## 7.1.5 Member Data Documentation

### 7.1.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if cell.visited = true and visited = true, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 54 of file barray-bones.hpp.

The documentation for this class was generated from the following file:

- include/barry/barray-bones.hpp

## 7.2 BArrayCell< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

### Public Member Functions

- BArrayCell (BArray< Cell\_Type, Data\_Type > \*Array\_, uint i\_, uint j\_, bool check\_bounds=true)
- ~BArrayCell ()
- void operator= (const Cell\_Type &val)
- void operator+= (const Cell\_Type &val)
- void operator-= (const Cell\_Type &val)
- void operator\*= (const Cell\_Type &val)
- void operator/= (const Cell\_Type &val)
- operator Cell\_Type () const
- bool operator== (const Cell\_Type &val) const

### 7.2.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell< Cell_Type, Data_Type >
```

Definition at line 7 of file barraycell-bones.hpp.

## 7.2.2 Constructor & Destructor Documentation

### 7.2.2.1 BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::BArrayCell (
    BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    uint j_,
    bool check_bounds = true ) [inline]
```

Definition at line 16 of file barraycell-bones.hpp.

### 7.2.2.2 ~BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::~~BArrayCell ( ) [inline]
```

Definition at line 31 of file barraycell-bones.hpp.

## 7.2.3 Member Function Documentation

### 7.2.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 58 of file barraycell-meat.hpp.

### 7.2.3.2 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 40 of file barraycell-meat.hpp.

### 7.2.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 18 of file barraycell-meat.hpp.

### 7.2.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 29 of file barraycell-meat.hpp.

### 7.2.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 49 of file barraycell-meat.hpp.

### 7.2.3.6 operator=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 7 of file barraycell-meat.hpp.

### 7.2.3.7 operator==(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 63 of file barraycell-meat.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barray-bones.hpp](#)
- [include/barry/barraycell-bones.hpp](#)
- [include/barry/barraycell-meat.hpp](#)
- [include/barry/barrayrow-meat.hpp](#)

## 7.3 BArrayCell\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

### Public Member Functions

- [BArrayCell\\_const](#) (const [BArray](#)< Cell\_Type, Data\_Type > \*[Array\\_](#), [uint](#) [i\\_](#), [uint](#) [j\\_](#), bool [check\\_bounds](#)=true)
- [~BArrayCell\\_const](#) ()
- [operator Cell\\_Type](#) () const
- bool [operator==](#) (const [Cell\\_Type](#) &val) const
- bool [operator!=](#) (const [Cell\\_Type](#) &val) const
- bool [operator<](#) (const [Cell\\_Type](#) &val) const
- bool [operator>](#) (const [Cell\\_Type](#) &val) const
- bool [operator<=](#) (const [Cell\\_Type](#) &val) const
- bool [operator>=](#) (const [Cell\\_Type](#) &val) const

### 7.3.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell_const< Cell_Type, Data_Type >
```

Definition at line 46 of file `barraycell-bones.hpp`.

### 7.3.2 Constructor & Destructor Documentation

#### 7.3.2.1 BArrayCell\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::BArrayCell_const (
    const BArray< Cell_Type, Data_Type > * Array\_,
    uint i\_,
    uint j\_,
    bool check\_bounds = true ) [inline]
```

Definition at line 55 of file `barraycell-bones.hpp`.

#### 7.3.2.2 ~BArrayCell\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::~BArrayCell_const ( ) [inline]
```

Definition at line 67 of file `barraycell-bones.hpp`.

### 7.3.3 Member Function Documentation

#### 7.3.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell_const< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 68 of file barraycell-meat.hpp.

#### 7.3.3.2 operator"!=(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator!= (
    const Cell_Type & val ) const [inline]
```

Definition at line 78 of file barraycell-meat.hpp.

#### 7.3.3.3 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 83 of file barraycell-meat.hpp.

#### 7.3.3.4 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 93 of file barraycell-meat.hpp.

#### 7.3.3.5 operator==(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 73 of file barraycell-meat.hpp.

### 7.3.3.6 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 88 of file `barraycell-meat.hpp`.

### 7.3.3.7 operator>=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 98 of file `barraycell-meat.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barray-bones.hpp`
- `include/barry/barraycell-bones.hpp`
- `include/barry/barraycell-meat.hpp`
- `include/barry/barrayrow-meat.hpp`

## 7.4 BArrayDense< Cell\_Type, Data\_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barraydense-bones.hpp>
```

### Public Member Functions

- `bool operator== (const BArrayDense< Cell_Type, Data_Type > &Array_)`
- `~BArrayDense ()`
- `void out_of_range (uint i, uint j) const`
- `Cell_Type get_cell (uint i, uint j, bool check_bounds=true) const`
- `std::vector< Cell_Type > get_col_vec (uint i, bool check_bounds=true) const`
- `std::vector< Cell_Type > get_row_vec (uint i, bool check_bounds=true) const`
- `void get_col_vec (std::vector< Cell_Type > *x, uint i, bool check_bounds=true) const`
- `void get_row_vec (std::vector< Cell_Type > *x, uint i, bool check_bounds=true) const`
- `BArrayDenseRow< Cell_Type, Data_Type > & row (uint i, bool check_bounds=true)`
- `const BArrayDenseRow_const< Cell_Type, Data_Type > row (uint i, bool check_bounds=true) const`
- `BArrayDenseCol< Cell_Type, Data_Type > & col (uint j, bool check_bounds=true)`
- `const BArrayDenseCol_const< Cell_Type, Data_Type > col (uint j, bool check_bounds=true) const`
- `Entries< Cell_Type > get_entries () const`

*Get the edgelist.*

- `void transpose ()`
- `void clear (bool hard=true)`
- `void resize (uint N_, uint M_)`
- `void reserve ()`
- `void print (const char *fmt=nullptr,...) const`
- `bool is_dense () const noexcept`
- `const std::vector< Cell_Type > & get_data () const`
- `const Cell_Type rowsum (unsigned int i) const`
- `const Cell_Type colsum (unsigned int i) const`

### Constructors

*Parameters*

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An unsigned int vector ranging from 0 to M_
target	When <code>true</code> tries to add repeated observations.
value	Cell_Type default fill-in value (zero, by default.)

- `BArrayDense ()`  
*Zero-size array.*
  - `BArrayDense (uint N_, uint M_, Cell_Type value=static_cast< Cell_Type >(0))`  
*Empty array.*
  - `BArrayDense (uint N_, uint M_, const std::vector< uint > &source, const std::vector< uint > &target, const std::vector< Cell_Type > &value, bool add=true)`  
*Edgelist with data.*
  - `BArrayDense (uint N_, uint M_, const std::vector< uint > &source, const std::vector< uint > &target, bool add=true)`  
*Edgelist with no data (simpler)*
  - `BArrayDense (const BArrayDense< Cell_Type, Data_Type > &Array_, bool copy_data=false)`  
*Copy constructor.*
  - `BArrayDense< Cell_Type, Data_Type > & operator= (const BArrayDense< Cell_Type, Data_Type > &Array_)`  
*Assignment constructor.*
  - `BArrayDense (BArrayDense< Cell_Type, Data_Type > &&x) noexcept`  
*Move operator.*
  - `BArrayDense< Cell_Type, Data_Type > & operator= (BArrayDense< Cell_Type, Data_Type > &&x) noexcept`  
*Move assignment.*
- 
- `void set_data (Data_Type *data_, bool delete_data_=false)`  
*Set the data object.*
  - `Data_Type * D_ptr ()`
  - `const Data_Type * D_ptr () const`
  - `Data_Type & D ()`
  - `const Data_Type & D () const`

**Queries**

*is\_empty* queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

*Parameters*

i,j	Coordinates
check_bounds	If <code>false</code> avoids checking bounds.

- `bool is_empty (uint i, uint j, bool check_bounds=true) const`
- `uint nrow () const noexcept`
- `uint ncol () const noexcept`
- `uint nnozero () const noexcept`

- [Cell](#)< Cell\_Type > [default\\_val](#) () const

### Cell-wise insertion/deletion

#### Parameters

i,j	<i>Row,column</i>
check_bounds	<i>When true and out of range, the function throws an error.</i>
check_exists	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of swap_cells, check if either of both cells exists/don't exist.</i>

- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator+=](#) (const std::pair< uint, uint > &coords)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator-=](#) (const std::pair< uint, uint > &coords)
- [BArrayDenseCell](#)< Cell\_Type, Data\_Type > [operator\(\)](#) (uint i, uint j, bool check\_bounds=true)
- const Cell\_Type [operator\(\)](#) (uint i, uint j, bool check\_bounds=true) const
- void [rm\\_cell](#) (uint i, uint j, bool check\_bounds=true, bool check\_exists=true)
- void [insert\\_cell](#) (uint i, uint j, const Cell< Cell\_Type > &v, bool check\_bounds, bool check\_exists)
- void [insert\\_cell](#) (uint i, uint j, Cell\_Type v, bool check\_bounds, bool check\_exists)
- void [swap\\_cells](#) (uint i0, uint j0, uint i1, uint j1, bool check\_bounds=true, int check\_exists=CHECK::BOTH, int \*report=nullptr)
- void [toggle\\_cell](#) (uint i, uint j, bool check\_bounds=true, int check\_exists=EXISTS::UNKNOWN)
- void [toggle\\_lock](#) (uint i, uint j, bool check\_bounds=true)

### Column/row wise interchange

- void [swap\\_rows](#) (uint i0, uint i1, bool check\_bounds=true)
- void [swap\\_cols](#) (uint j0, uint j1, bool check\_bounds=true)
- void [zero\\_row](#) (uint i, bool check\_bounds=true)
- void [zero\\_col](#) (uint j, bool check\_bounds=true)

### Arithmetic operators

- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator+=](#) (const [BArrayDense](#)< Cell\_Type, Data\_Type > &rhs)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator+=](#) (const Cell\_Type &rhs)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator-=](#) (const [BArrayDense](#)< Cell\_Type, Data\_Type > &rhs)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator-=](#) (const Cell\_Type &rhs)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator/=](#) (const Cell\_Type &rhs)
- [BArrayDense](#)< Cell\_Type, Data\_Type > & [operator\\*=](#) (const Cell\_Type &rhs)

### Public Attributes

- bool [visited](#) = false

### Friends

- class [BArrayDenseCell](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCol](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCol\\_const](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseRow](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseRow\\_const](#)< Cell\_Type, Data\_Type >



### 7.4.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDense< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

[BArrayDense](#) class objects are arbitrary dense-arrays. The data is stored internally in the `el` member, which can be accessed using the member function `get_data()`, by column.

#### Template Parameters

<i>Cell_Type</i>	Type of cell (any type).
<i>Data_Type</i>	Data type of the array (bool default).

Definition at line 33 of file `barraydense-bones.hpp`.

### 7.4.2 Constructor & Destructor Documentation

#### 7.4.2.1 BArrayDense() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense ( ) [inline]
```

Zero-size array.

Definition at line 79 of file `barraydense-bones.hpp`.

#### 7.4.2.2 BArrayDense() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    Cell_Type value = static_cast<Cell_Type>(0) ) [inline]
```

Empty array.

Definition at line 82 of file `barraydense-bones.hpp`.

#### 7.4.2.3 BArrayDense() [3/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    const std::vector< Cell_Type > & value,
    bool add = true )
```

Edgelist with data.

#### 7.4.2.4 BArrayDense() [4/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    bool add = true )
```

Edgelist with no data (simpler)

#### 7.4.2.5 BArrayDense() [5/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    const BArrayDense< Cell_Type, Data_Type > & Array_,
    bool copy_data = false )
```

Copy constructor.

#### 7.4.2.6 BArrayDense() [6/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    BArrayDense< Cell_Type, Data_Type > && x ) [noexcept]
```

Move operator.

### 7.4.2.7 ~BArrayDense()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::~~BArrayDense ( )
```

## 7.4.3 Member Function Documentation

### 7.4.3.1 clear()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::clear (
    bool hard = true )
```

### 7.4.3.2 col() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCol< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::col (
    uint j,
    bool check_bounds = true ) [inline]
```

Definition at line 490 of file `barraydense-meat.hpp`.

### 7.4.3.3 col() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const BArrayDenseCol_const< Cell_Type, Data_Type > BArrayDense< Cell_Type, Data_Type >::col (
    uint j,
    bool check_bounds = true ) const [inline]
```

Definition at line 476 of file `barraydense-meat.hpp`.

### 7.4.3.4 colsum()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::colsum (
    unsigned int i ) const
```

#### 7.4.3.5 D() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type& BArrayDense< Cell_Type, Data_Type >::D ( )
```

#### 7.4.3.6 D() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type& BArrayDense< Cell_Type, Data_Type >::D ( ) const
```

#### 7.4.3.7 D\_ptr() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type* BArrayDense< Cell_Type, Data_Type >::D_ptr ( )
```

#### 7.4.3.8 D\_ptr() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type* BArrayDense< Cell_Type, Data_Type >::D_ptr ( ) const
```

#### 7.4.3.9 default\_val()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell<Cell_Type> BArrayDense< Cell_Type, Data_Type >::default_val ( ) const
```

#### 7.4.3.10 get\_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell_Type BArrayDense< Cell_Type, Data_Type >::get_cell (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.4.3.11 get\_col\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**7.4.3.12 get\_col\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    uint i,
    bool check_bounds = true ) const
```

**7.4.3.13 get\_data()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::vector< Cell_Type >& BArrayDense< Cell_Type, Data_Type >::get_data ( ) const
```

**7.4.3.14 get\_entries()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Entries<Cell_Type> BArrayDense< Cell_Type, Data_Type >::get_entries ( ) const
```

Get the edgelist.

`Entries` is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

**Returns**

`Entries<Cell_Type>`

**7.4.3.15 get\_row\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**7.4.3.16 get\_row\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    uint i,
    bool check_bounds = true ) const
```

**7.4.3.17 insert\_cell() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell_Type v,
    bool check_bounds,
    bool check_exists )
```

**7.4.3.18 insert\_cell() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool check_exists )
```

**7.4.3.19 is\_dense()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 256 of file `barraydense-bones.hpp`.

**7.4.3.20 is\_empty()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::is_empty (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.4.3.21 ncol()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::ncol ( ) const [noexcept]
```

**7.4.3.22 nnozero()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::nnozero ( ) const [noexcept]
```

**7.4.3.23 nrow()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::nrow ( ) const [noexcept]
```

**7.4.3.24 operator>() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell<Cell_Type,Data_Type> BArrayDense< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true )
```

**7.4.3.25 operator>() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**7.4.3.26 operator\*=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

**7.4.3.27 operator+=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

**7.4.3.28 operator+=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const Cell_Type & rhs )
```

**7.4.3.29 operator+=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const std::pair< uint, uint > & coords )
```

**7.4.3.30 operator-=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

**7.4.3.31 operator-=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const Cell_Type & rhs )
```

**7.4.3.32 operator-=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const std::pair< uint, uint > & coords )
```



**7.4.3.33 operator/=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & rhs )
```

**7.4.3.34 operator=( ) [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator= (
    BArrayDense< Cell_Type, Data_Type > && x ) [noexcept]
```

Move assignment.

**7.4.3.35 operator=( ) [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator= (
    const BArrayDense< Cell_Type, Data_Type > & Array_ )
```

Assignment constructor.

**7.4.3.36 operator==( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::operator== (
    const BArrayDense< Cell_Type, Data_Type > & Array_ )
```

**7.4.3.37 out\_of\_range( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::out_of_range (
    uint i,
    uint j ) const
```

**7.4.3.38 print( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const
```

**7.4.3.39 reserve()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::reserve ( )
```

**7.4.3.40 resize()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::resize (
    uint N_,
    uint M_ )
```

**7.4.3.41 rm\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::rm_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    bool check_exists = true )
```

**7.4.3.42 row() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true )
```

**7.4.3.43 row() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const BArrayDenseRow_const<Cell_Type,Data_Type> BArrayDense< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true ) const
```

**7.4.3.44 rowsum()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::rowsum (
    unsigned int i ) const
```

**7.4.3.45 set\_data()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false )
```

Set the data object.

**Parameters**

<i>data_</i>	
<i>delete_</i> ↔ <i>data_</i>	

**7.4.3.46 swap\_cells()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_cells (
    uint i0,
    uint j0,
    uint i1,
    uint j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr )
```

**7.4.3.47 swap\_cols()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_cols (
    uint j0,
    uint j1,
    bool check_bounds = true )
```

**7.4.3.48 swap\_rows()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_rows (
    uint i0,
    uint i1,
    bool check_bounds = true )
```

#### 7.4.3.49 toggle\_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::toggle_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN )
```

#### 7.4.3.50 toggle\_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::toggle_lock (
    uint i,
    uint j,
    bool check_bounds = true )
```

#### 7.4.3.51 transpose()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::transpose ( )
```

#### 7.4.3.52 zero\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::zero_col (
    uint j,
    bool check_bounds = true )
```

#### 7.4.3.53 zero\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::zero_row (
    uint i,
    bool check_bounds = true )
```

### 7.4.4 Friends And Related Function Documentation

#### 7.4.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 7.4.4.2 BArrayDenseCol< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 7.4.4.3 BArrayDenseCol\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 7.4.4.4 BArrayDenseRow< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 7.4.4.5 BArrayDenseRow\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

### 7.4.5 Member Data Documentation

#### 7.4.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if cell.visited = true and visited = true, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 63 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydense-meat.hpp`

## 7.5 BArrayDenseCell< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecell-bones.hpp>
```

### Public Member Functions

- `BArrayDenseCell` (`BArrayDense`< `Cell_Type`, `Data_Type` > \*`Array_`, `uint i_`, `uint j_`, `bool check_bounds=true`)
- `BArrayDenseCell`< `Cell_Type`, `Data_Type` > & `operator=` (`const BArrayDenseCell`< `Cell_Type`, `Data_Type` > &`other`)
- `~BArrayDenseCell` ()
- `void operator=` (`const Cell_Type` &`val`)
- `void operator+=` (`const Cell_Type` &`val`)
- `void operator-=` (`const Cell_Type` &`val`)
- `void operator*=` (`const Cell_Type` &`val`)
- `void operator/=` (`const Cell_Type` &`val`)
- `operator Cell_Type` () `const`
- `bool operator==` (`const Cell_Type` &`val`) `const`

### Friends

- `class BArrayDense`< `Cell_Type`, `Data_Type` >
- `class BArrayDenseCol`< `Cell_Type`, `Data_Type` >
- `class BArrayDenseCol_const`< `Cell_Type`, `Data_Type` >

#### 7.5.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCell< Cell_Type, Data_Type >
```

Definition at line 18 of file `barraydensecell-bones.hpp`.

## 7.5.2 Constructor & Destructor Documentation

### 7.5.2.1 BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::BArrayDenseCell (
    BArrayDense< Cell_Type, Data_Type > * Array_,
    uint i_,
    uint j_,
    bool check_bounds = true ) [inline]
```

Definition at line 30 of file `barraydensecell-bones.hpp`.

### 7.5.2.2 ~BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::~~BArrayDenseCell ( ) [inline]
```

Definition at line 56 of file `barraydensecell-bones.hpp`.

## 7.5.3 Member Function Documentation

### 7.5.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 72 of file `barraydensecell-meat.hpp`.

### 7.5.3.2 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 52 of file `barraydensecell-meat.hpp`.

### 7.5.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 34 of file `barraydensecell-meat.hpp`.

### 7.5.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 43 of file `barraydensecell-meat.hpp`.

### 7.5.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 62 of file `barraydensecell-meat.hpp`.

### 7.5.3.6 operator=() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type > & BArrayDenseCell< Cell_Type, Data_Type >::operator=
(
    const BArrayDenseCell< Cell_Type, Data_Type > & other ) [inline]
```

Definition at line 9 of file `barraydensecell-meat.hpp`.

### 7.5.3.7 operator=() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 24 of file `barraydensecell-meat.hpp`.



### 7.5.3.8 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayDenseCell< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 77 of file `barraydensecell-meat.hpp`.

## 7.5.4 Friends And Related Function Documentation

### 7.5.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

### 7.5.4.2 BArrayDenseCol< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

### 7.5.4.3 BArrayDenseCol\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecell-bones.hpp`
- `include/barry/barraydensecell-meat.hpp`

## 7.6 BArrayDenseCell\_const< Cell\_Type, Data\_Type > Class Template Reference

### 7.6.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class BArrayDenseCell_const< Cell_Type, Data_Type >
```

Definition at line 20 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following file:

- [include/barry/barraydense-bones.hpp](#)

## 7.7 BArrayDenseCol< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

### Public Member Functions

- [BArrayDenseCol](#) ([BArrayDense](#)< Cell\_Type, Data\_Type > &array\_, unsigned int j)
- [Col\\_type](#)< Cell\_Type >::iterator & [begin](#) ()
- [Col\\_type](#)< Cell\_Type >::iterator & [end](#) ()
- [size\\_t](#) [size](#) () [const](#) [noexcept](#)
- [std::pair](#)< unsigned int, Cell\_Type \* > & [operator\(\)](#) (unsigned int i)

### Friends

- class [BArrayDense](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell\\_const](#)< Cell\_Type, Data\_Type >

### 7.7.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydensecol-bones.hpp`.

### 7.7.2 Constructor & Destructor Documentation

### 7.7.2.1 BArrayDenseCol()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol< Cell_Type, Data_Type >::BArrayDenseCol (
    BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int j ) [inline]
```

Definition at line 38 of file barraydensecol-bones.hpp.

## 7.7.3 Member Function Documentation

### 7.7.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 44 of file barraydensecol-bones.hpp.

### 7.7.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 50 of file barraydensecol-bones.hpp.

### 7.7.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<unsigned int,Cell_Type*>& BArrayDenseCol< Cell_Type, Data_Type >::operator() (
    unsigned int i ) [inline]
```

Definition at line 62 of file barraydensecol-bones.hpp.

### 7.7.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 56 of file barraydensecol-bones.hpp.

## 7.7.4 Friends And Related Function Documentation

### 7.7.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

### 7.7.4.2 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

### 7.7.4.3 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

## 7.8 BArrayDenseCol\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

### Public Member Functions

- `BArrayDenseCol_const` (`const BArrayDense`< `Cell_Type`, `Data_Type` > &`array_`, unsigned int `j`)
- `Col_type`< `Cell_Type` >::iterator `begin` ()
- `Col_type`< `Cell_Type` >::iterator `end` ()
- `size_t` `size` () `const noexcept`
- `const` `std::pair`< unsigned int, `Cell_Type` \* > `operator()` (unsigned int `i`) `const`

## Friends

- class [BArrayDenseCell< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseCell\\_const< Cell\\_Type, Data\\_Type >](#)

### 7.8.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol_const< Cell_Type, Data_Type >
```

Definition at line 71 of file `barraydensecol-bones.hpp`.

### 7.8.2 Constructor & Destructor Documentation

#### 7.8.2.1 BArrayDenseCol\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol_const< Cell_Type, Data_Type >::BArrayDenseCol_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int j ) [inline]
```

Definition at line 80 of file `barraydensecol-bones.hpp`.

### 7.8.3 Member Function Documentation

#### 7.8.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 96 of file `barraydensecol-bones.hpp`.

#### 7.8.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 101 of file `barraydensecol-bones.hpp`.

### 7.8.3.3 operator()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<unsigned int,Cell_Type*> BArrayDenseCol_const< Cell_Type, Data_Type >::operator()
(
    unsigned int i ) const [inline]
```

Definition at line 112 of file `barraydensecol-bones.hpp`.

### 7.8.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 107 of file `barraydensecol-bones.hpp`.

## 7.8.4 Friends And Related Function Documentation

### 7.8.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

### 7.8.4.2 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

## 7.9 BArrayDenseRow< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```

## Public Member Functions

- [BArrayDenseRow](#) ([BArrayDense](#)< Cell\_Type, Data\_Type > &array\_, unsigned int i)
- [Row\\_type](#)< Cell\_Type >::iterator & [begin](#) ()
- [Row\\_type](#)< Cell\_Type >::iterator & [end](#) ()
- [size\\_t](#) [size](#) () [const noexcept](#)
- [std::pair](#)< unsigned int, [Cell](#)< Cell\_Type > > & [operator\(\)](#) (unsigned int i)

## Friends

- class [BArrayDense](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell\\_const](#)< Cell\_Type, Data\_Type >

### 7.9.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydenserow-bones.hpp`.

### 7.9.2 Constructor & Destructor Documentation

#### 7.9.2.1 BArrayDenseRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow< Cell_Type, Data_Type >::BArrayDenseRow (
    BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int i ) [inline]
```

Definition at line 40 of file `barraydenserow-bones.hpp`.

### 7.9.3 Member Function Documentation

#### 7.9.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 45 of file `barraydenserow-bones.hpp`.

### 7.9.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 53 of file bararraydenserow-bones.hpp.

### 7.9.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<unsigned int,Cell<Cell_Type> >& BArrayDenseRow< Cell_Type, Data_Type >::operator()
(
    unsigned int i ) [inline]
```

Definition at line 69 of file bararraydenserow-bones.hpp.

### 7.9.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 61 of file bararraydenserow-bones.hpp.

## 7.9.4 Friends And Related Function Documentation

### 7.9.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.

### 7.9.4.2 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.



### 7.9.4.3 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

## 7.10 BArrayDenseRow\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```

### Public Member Functions

- `BArrayDenseRow_const` (`const BArrayDense`< `Cell_Type`, `Data_Type` > &`array_`, unsigned int `i`)
- `Row_type`< `Cell_Type` >::const\_iterator `begin` () `const`
- `Row_type`< `Cell_Type` >::const\_iterator `end` () `const`
- `size_t` `size` () `const noexcept`
- `const` std::pair< unsigned int, `Cell`< `Cell_Type` > > `operator()` (unsigned int `i`) `const`

### Friends

- class `BArrayDenseCell`< `Cell_Type`, `Data_Type` >
- class `BArrayDenseCell_const`< `Cell_Type`, `Data_Type` >

### 7.10.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow_const< Cell_Type, Data_Type >
```

Definition at line 80 of file `barraydenserow-bones.hpp`.

### 7.10.2 Constructor & Destructor Documentation

### 7.10.2.1 BArrayDenseRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow_const< Cell_Type, Data_Type >::BArrayDenseRow_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int i ) [inline]
```

Definition at line 89 of file barraydenserow-bones.hpp.

## 7.10.3 Member Function Documentation

### 7.10.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::begin ( )
const [inline]
```

Definition at line 108 of file barraydenserow-bones.hpp.

### 7.10.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::end ( )
const [inline]
```

Definition at line 113 of file barraydenserow-bones.hpp.

### 7.10.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<unsigned int, Cell<Cell_Type> > BArrayDenseRow_const< Cell_Type, Data_Type
>::operator() (
    unsigned int i ) const [inline]
```

Definition at line 123 of file barraydenserow-bones.hpp.

### 7.10.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 118 of file barraydenserow-bones.hpp.

## 7.10.4 Friends And Related Function Documentation

### 7.10.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

### 7.10.4.2 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

## 7.11 BArrayRow< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

### Public Member Functions

- [BArrayRow](#) ([BArray](#)< Cell\_Type, Data\_Type > \*[Array\\_](#), [uint](#) i\_, [bool](#) [check\\_bounds](#)=true)
- [~BArrayRow](#) ()
- [void operator=](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val)
- [void operator+=](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val)
- [void operator-=](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val)
- [void operator\\*=](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val)
- [void operator/=](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val)
- [operator BArrayRow](#)< Cell\_Type, Data\_Type > () const
- [bool operator==](#) (const [BArrayRow](#)< Cell\_Type, Data\_Type > &val) const

### 7.11.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow< Cell_Type, Data_Type >
```

Definition at line 5 of file `barrayrow-bones.hpp`.

## 7.11.2 Constructor & Destructor Documentation

### 7.11.2.1 BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::BArrayRow (
    BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    bool check_bounds = true ) [inline]
```

Definition at line 13 of file bararrayrow-bones.hpp.

### 7.11.2.2 ~BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::~~BArrayRow ( ) [inline]
```

Definition at line 26 of file bararrayrow-bones.hpp.

## 7.11.3 Member Function Documentation

### 7.11.3.1 operator BArrayRow< Cell\_Type, Data\_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::operator BArrayRow< Cell_Type, Data_Type > ( ) const
```

### 7.11.3.2 operator\*=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator*= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

### 7.11.3.3 operator+=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator+= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 7.11.3.4 operator-=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator-= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 7.11.3.5 operator/=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator/= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 7.11.3.6 operator=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 7.11.3.7 operator==( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow< Cell_Type, Data_Type >::operator== (
    const BArrayRow< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

## 7.12 BArrayRow\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

### Public Member Functions

- [BArrayRow\\_const](#) (const BArray< Cell\_Type, Data\_Type > \*Array\_, uint i\_, bool check\_bounds=true)
- [~BArrayRow\\_const](#) ( )
- [operator BArrayRow\\_const< Cell\\_Type, Data\\_Type > \( \) const](#)
- [bool operator==](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator!=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator<](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator>](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator<=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator>=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const

### 7.12.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow_const< Cell_Type, Data_Type >
```

Definition at line 41 of file `barrayrow-bones.hpp`.

### 7.12.2 Constructor & Destructor Documentation

#### 7.12.2.1 BArrayRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::BArrayRow_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    bool check_bounds = true ) [inline]
```

Definition at line 49 of file `barrayrow-bones.hpp`.

#### 7.12.2.2 ~BArrayRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::~~BArrayRow_const ( ) [inline]
```

Definition at line 59 of file `barrayrow-bones.hpp`.

### 7.12.3 Member Function Documentation

#### 7.12.3.1 operator BArrayRow\_const< Cell\_Type, Data\_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::operator BArrayRow_const< Cell_Type, Data_Type > ( )
const
```

#### 7.12.3.2 operator"!="()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator!= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**7.12.3.3 operator<()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator< (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**7.12.3.4 operator<=()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator<= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**7.12.3.5 operator==(())**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator==(
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**7.12.3.6 operator>()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator> (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**7.12.3.7 operator>=()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator>= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

**7.13 BArrayVector< Cell\_Type, Data\_Type > Class Template Reference**

Row or column of a [BArray](#)

```
#include <barrayvector-bones.hpp>
```

## Public Member Functions

- [BArrayVector](#) ([BArray](#)< [Cell\\_Type](#), [Data\\_Type](#) > \*[Array\\_](#), [uint](#) &[dim\\_ uint](#) &[i\\_](#), [bool](#) [check\\_bounds](#)=true)  
Construct a new [BArrayVector](#) object.
- [~BArrayVector](#) ()
- [bool](#) [is\\_row](#) () [const](#) [noexcept](#)
- [bool](#) [is\\_col](#) () [const](#) [noexcept](#)
- [uint](#) [size](#) () [const](#) [noexcept](#)
- [std::vector](#)< [Cell\\_Type](#) >::[const\\_iterator](#) [begin](#) () [noexcept](#)
- [std::vector](#)< [Cell\\_Type](#) >::[const\\_iterator](#) [end](#) () [noexcept](#)
- [void](#) [operator=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator+=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator-=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator\\*=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator/=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [operator](#) [std::vector](#)< [Cell\\_Type](#) > () [const](#)
- [bool](#) [operator==](#) ([const](#) [Cell\\_Type](#) &[val](#)) [const](#)

### 7.13.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector< Cell_Type, Data_Type >
```

Row or column of a [BArray](#)

Template Parameters

<i>Cell_Type</i>	
<i>Data_Type</i>	

Definition at line 11 of file [barrayvector-bones.hpp](#).

### 7.13.2 Constructor & Destructor Documentation

#### 7.13.2.1 BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::BArrayVector (
    BArray< Cell_Type, Data_Type > * Array\_,
    uint &dim\_ uint & i\_,
    bool check\_bounds = true ) [inline]
```

Construct a new [BArrayVector](#) object.

Parameters

<i>Array_</i>	Pointer to a <a href="#">BArray</a> object
<i>dim_</i>	Dimension. 0 means row and 1 means column.
<i>i_</i>	Element to point.
<i>check_bounds</i>	When <a href="#">true</a> , check boundaries.



Definition at line 32 of file barrayvector-bones.hpp.

#### 7.13.2.2 ~BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::~~BArrayVector ( ) [inline]
```

Definition at line 53 of file barrayvector-bones.hpp.

### 7.13.3 Member Function Documentation

#### 7.13.3.1 begin()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::begin [inline],
[noexcept]
```

Definition at line 50 of file barrayvector-meat.hpp.

#### 7.13.3.2 end()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::end [inline],
[noexcept]
```

Definition at line 64 of file barrayvector-meat.hpp.

#### 7.13.3.3 is\_col()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_col [inline], [noexcept]
```

Definition at line 34 of file barrayvector-meat.hpp.

#### 7.13.3.4 is\_row()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_row [inline], [noexcept]
```

Definition at line 29 of file barrayvector-meat.hpp.

#### 7.13.3.5 operator std::vector< Cell\_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 175 of file barrayvector-meat.hpp.

#### 7.13.3.6 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 133 of file barrayvector-meat.hpp.

#### 7.13.3.7 operator+=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 91 of file barrayvector-meat.hpp.

#### 7.13.3.8 operator-=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 112 of file barrayvector-meat.hpp.

### 7.13.3.9 operator/=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 154 of file `barrayvector-meat.hpp`.

### 7.13.3.10 operator=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 69 of file `barrayvector-meat.hpp`.

### 7.13.3.11 operator==( )

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 185 of file `barrayvector-meat.hpp`.

### 7.13.3.12 size( )

```
template<typename Cell_Type , typename Data_Type >
uint BArrayVector< Cell_Type, Data_Type >::size [inline], [noexcept]
```

Definition at line 39 of file `barrayvector-meat.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barrayvector-bones.hpp`
- `include/barry/barrayvector-meat.hpp`

## 7.14 BArrayVector\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayvector-bones.hpp>
```

## Public Member Functions

- `BArrayVector_const` (`const BArray< Cell_Type, Data_Type > *Array_`, `uint &dim_` `uint &i_`, `bool check_bounds=true`)
- `~BArrayVector_const` ()
- `bool is_row` () `const noexcept`
- `bool is_col` () `const noexcept`
- `uint size` () `const noexcept`
- `std::vector< Cell_Type >::const_iterator begin` () `noexcept`
- `std::vector< Cell_Type >::const_iterator end` () `noexcept`
- `operator std::vector< Cell_Type >` () `const`
- `bool operator==` (`const Cell_Type &val`) `const`
- `bool operator!=` (`const Cell_Type &val`) `const`
- `bool operator<` (`const Cell_Type &val`) `const`
- `bool operator>` (`const Cell_Type &val`) `const`
- `bool operator<=` (`const Cell_Type &val`) `const`
- `bool operator>=` (`const Cell_Type &val`) `const`

### 7.14.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector_const< Cell_Type, Data_Type >
```

Definition at line 73 of file `barrayvector-bones.hpp`.

### 7.14.2 Constructor & Destructor Documentation

#### 7.14.2.1 BArrayVector\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::BArrayVector_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    uint &dim_ uint & i_,
    bool check_bounds = true ) [inline]
```

Definition at line 86 of file `barrayvector-bones.hpp`.

#### 7.14.2.2 ~BArrayVector\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::~~BArrayVector_const ( ) [inline]
```

Definition at line 108 of file `barrayvector-bones.hpp`.

### 7.14.3 Member Function Documentation

#### 7.14.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::begin (
) [noexcept]
```

#### 7.14.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::end ( )
[noexcept]
```

#### 7.14.3.3 is\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_col ( ) const [noexcept]
```

#### 7.14.3.4 is\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_row ( ) const [noexcept]
```

#### 7.14.3.5 operator std::vector< Cell\_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector_const< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 212 of file barrayvector-meat.hpp.

#### 7.14.3.6 operator"!=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator!= (
    const Cell_Type & val ) const [inline]
```

Definition at line 249 of file barrayvector-meat.hpp.

#### 7.14.3.7 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 254 of file barrayvector-meat.hpp.

#### 7.14.3.8 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 281 of file barrayvector-meat.hpp.

#### 7.14.3.9 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 222 of file barrayvector-meat.hpp.

#### 7.14.3.10 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 308 of file barrayvector-meat.hpp.

**7.14.3.11 operator>=()**

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 315 of file barrayvector-meat.hpp.

**7.14.3.12 size()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayVector_const< Cell_Type, Data_Type >::size ( ) const [noexcept]
```

The documentation for this class was generated from the following files:

- include/barry/barrayvector-bones.hpp
- include/barry/barrayvector-meat.hpp

**7.15 Cell< Cell\_Type > Class Template Reference**

Entries in [BArray](#). For now, it only has two members:

```
#include <cell-bones.hpp>
```

**Public Member Functions**

- [Cell](#) ()
- [Cell](#) (Cell\_Type value\_, bool visited\_[\\_false](#), bool active\_[\\_true](#))
- [~Cell](#) ()
- [Cell](#) (const [Cell](#)< Cell\_Type > &arg)
- [Cell](#)< Cell\_Type > & [operator=](#) (const [Cell](#)< Cell\_Type > &other)
- [Cell](#) ([Cell](#)< Cell\_Type > &&arg) [noexcept](#)
- [Cell](#)< Cell\_Type > & [operator=](#) ([Cell](#)< Cell\_Type > &&other) [noexcept](#)
- void [add](#) (Cell\_Type x)
- [operator Cell\\_Type](#) () const
- bool [operator==](#) (const [Cell](#)< Cell\_Type > &rhs) const
- bool [operator!=](#) (const [Cell](#)< Cell\_Type > &rhs) const
- void [add](#) (double x)
- void [add](#) (unsigned int x)
- void [add](#) (int x)
- [Cell](#) ()
- [Cell](#) ()
- [Cell](#) ()

**Public Attributes**

- Cell\_Type [value](#)
- bool [visited](#)
- bool [active](#)

### 7.15.1 Detailed Description

```
template<class Cell_Type>
class Cell< Cell_Type >
```

[Entries](#) in [BArray](#). For now, it only has two members:

- value: the content
- visited: boolean (just a convenient)

Definition at line 10 of file cell-bones.hpp.

### 7.15.2 Constructor & Destructor Documentation

#### 7.15.2.1 Cell() [1/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell ( )
```

#### 7.15.2.2 Cell() [2/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell_Type value_,
    bool visited_ = false,
    bool active_ = true ) [inline]
```

Definition at line 16 of file cell-bones.hpp.

#### 7.15.2.3 ~Cell()

```
template<class Cell_Type >
Cell< Cell_Type >::~Cell ( ) [inline]
```

Definition at line 18 of file cell-bones.hpp.



#### 7.15.2.4 Cell() [3/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    const Cell< Cell_Type > & arg ) [inline]
```

Definition at line 22 of file cell-bones.hpp.

#### 7.15.2.5 Cell() [4/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell< Cell_Type > && arg ) [inline], [noexcept]
```

Definition at line 29 of file cell-bones.hpp.

#### 7.15.2.6 Cell() [5/7]

```
Cell< double >::Cell ( ) [inline]
```

Definition at line 62 of file cell-meat.hpp.

#### 7.15.2.7 Cell() [6/7]

```
Cell< uint >::Cell ( ) [inline]
```

Definition at line 63 of file cell-meat.hpp.

#### 7.15.2.8 Cell() [7/7]

```
Cell< int >::Cell ( ) [inline]
```

Definition at line 64 of file cell-meat.hpp.

### 7.15.3 Member Function Documentation

#### 7.15.3.1 add() [1/4]

```
template<class Cell_Type >
void Cell< Cell_Type >::add (
    Cell_Type x )
```

#### 7.15.3.2 add() [2/4]

```
void Cell< double >::add (
    double x ) [inline]
```

Definition at line 42 of file cell-meat.hpp.

#### 7.15.3.3 add() [3/4]

```
void Cell< int >::add (
    int x ) [inline]
```

Definition at line 52 of file cell-meat.hpp.

#### 7.15.3.4 add() [4/4]

```
void Cell< unsigned int >::add (
    unsigned int x ) [inline]
```

Definition at line 47 of file cell-meat.hpp.

#### 7.15.3.5 operator Cell\_Type()

```
template<class Cell_Type >
Cell< Cell_Type >::operator Cell_Type ( ) const [inline]
```

Definition at line 41 of file cell-bones.hpp.

#### 7.15.3.6 operator"!=(

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator!= (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 31 of file cell-meat.hpp.

### 7.15.3.7 operator=() [1/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    Cell< Cell_Type > && other ) [noexcept]
```

Definition at line 13 of file cell-meat.hpp.

### 7.15.3.8 operator=() [2/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    const Cell< Cell_Type > & other )
```

Definition at line 5 of file cell-meat.hpp.

### 7.15.3.9 operator==()

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator== (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 21 of file cell-meat.hpp.

## 7.15.4 Member Data Documentation

### 7.15.4.1 active

```
template<class Cell_Type >
bool Cell< Cell_Type >::active
```

Definition at line 14 of file cell-bones.hpp.

### 7.15.4.2 value

```
template<class Cell_Type >
Cell_Type Cell< Cell_Type >::value
```

Definition at line 12 of file cell-bones.hpp.

### 7.15.4.3 visited

```
template<class Cell_Type >
bool Cell< Cell_Type >::visited
```

Definition at line 13 of file cell-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barray-meat.hpp](#)
- [include/barry/cell-bones.hpp](#)
- [include/barry/cell-meat.hpp](#)

## 7.16 Cell\_const< Cell\_Type > Class Template Reference

### 7.16.1 Detailed Description

```
template<typename Cell_Type>
class Cell_const< Cell_Type >
```

Definition at line 8 of file barray-meat.hpp.


The documentation for this class was generated from the following file:

- [include/barry/barray-meat.hpp](#)

## 7.17 ConstBArrayRowIter< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barray-iterator.hpp>
```

Collaboration diagram for ConstBArrayRowIter< Cell\_Type, Data\_Type >:



## Public Member Functions

- [ConstBArrayRowIter](#) ([const BArray](#)< Cell\_Type, Data\_Type > \*[Array\\_](#))
- [~ConstBArrayRowIter](#) ()

## Public Attributes

- [uint](#) [current\\_row](#)
- [uint](#) [current\\_col](#)
- [Row\\_type](#)< Cell\_Type >::const\_iterator [iter](#)
- [const BArray](#)< Cell\_Type, Data\_Type > \* [Array](#)

### 7.17.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class ConstBArrayRowIter< Cell_Type, Data_Type >
```

Definition at line 10 of file `barray-iterator.hpp`.

### 7.17.2 Constructor & Destructor Documentation

#### 7.17.2.1 ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::ConstBArrayRowIter (
    const BArray< Cell_Type, Data_Type > * Array_ ) [inline]
```

Definition at line 17 of file `barray-iterator.hpp`.

#### 7.17.2.2 ~ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::~~ConstBArrayRowIter ( ) [inline]
```

Definition at line 29 of file `barray-iterator.hpp`.

### 7.17.3 Member Data Documentation

### 7.17.3.1 Array

```
template<typename Cell_Type , typename Data_Type >
const BArray<Cell_Type,Data_Type>* ConstBArrayRowIter< Cell_Type, Data_Type >::Array
```

Definition at line 15 of file `barray-iterator.hpp`.

### 7.17.3.2 current\_col

```
template<typename Cell_Type , typename Data_Type >
uint ConstBArrayRowIter< Cell_Type, Data_Type >::current_col
```

Definition at line 13 of file `barray-iterator.hpp`.

### 7.17.3.3 current\_row

```
template<typename Cell_Type , typename Data_Type >
uint ConstBArrayRowIter< Cell_Type, Data_Type >::current_row
```

Definition at line 13 of file `barray-iterator.hpp`.

### 7.17.3.4 iter

```
template<typename Cell_Type , typename Data_Type >
Row_type<Cell_Type>::const_iterator ConstBArrayRowIter< Cell_Type, Data_Type >::iter
```

Definition at line 14 of file `barray-iterator.hpp`.

The documentation for this class was generated from the following file:

- `include/barry/barray-iterator.hpp`

## 7.18 Counter< Array\_Type, Data\_Type > Class Template Reference

A counter function based on change statistics.

```
#include <counters-bones.hpp>
```

### Public Member Functions

- `~Counter ()`
- `double count (Array_Type &Array, uint i, uint j)`
- `double init (Array_Type &Array, uint i, uint j)`
- `std::string get_name () const`
- `std::string get_description () const`

**Creator passing a counter and an initializer**

*Parameters*

count_fun↔ _	The main counter function.
init_fun_ _	The initializer function can also be used to check if the <a href="#">BArray</a> as the needed variables (see <a href="#">BArray::data</a> ).
data_ _	Data to be used with the counter.
delete_↔ data_ _	When <code>true</code> , the destructor will delete the pointer in the main data.

- [Counter](#) ()
- [Counter](#) ([Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [count\\_fun](#), [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun](#), Data\_Type [data](#)\_, std::string [name](#)\_="", std::string [desc](#)\_="")
- [Counter](#) (const [Counter](#)< Array\_Type, Data\_Type > &[counter](#)\_)  
Copy constructor.
- [Counter](#) ([Counter](#)< Array\_Type, Data\_Type > &&[counter](#)\_) noexcept  
Move constructor.
- [Counter](#)< Array\_Type, Data\_Type > [operator=](#) (const [Counter](#)< Array\_Type, Data\_Type > &[counter](#)\_)  
Copy assignment.
- [Counter](#)< Array\_Type, Data\_Type > & [operator=](#) ([Counter](#)< Array\_Type, Data\_Type > &&[counter](#)\_)  
noexcept  
Move assignment.

**Public Attributes**

- [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [count\\_fun](#)
- [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun](#)
- Data\_Type [data](#)
- std::string [name](#) = ""
- std::string [desc](#) = ""

**7.18.1 Detailed Description**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counter< Array_Type, Data_Type >
```

A counter function based on change statistics.

This class is used by `CountStats` and `StatsCounter` as a way to count statistics using change statistics.

Definition at line 35 of file `counters-bones.hpp`.

**7.18.2 Constructor & Destructor Documentation**

**7.18.2.1 Counter()** [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter ( ) [inline]
```

Definition at line 55 of file counters-bones.hpp.

**7.18.2.2 Counter()** [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" ) [inline]
```

Definition at line 57 of file counters-bones.hpp.

**7.18.2.3 Counter()** [3/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

**7.18.2.4 Counter()** [4/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move constructor.

**7.18.2.5 ~Counter()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::~Counter ( ) [inline]
```

Definition at line 72 of file counters-bones.hpp.



### 7.18.3 Member Function Documentation

#### 7.18.3.1 count()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::count (
    Array_Type & Array,
    uint i,
    uint j )
```

#### 7.18.3.2 get\_description()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_description ( ) const
```

#### 7.18.3.3 get\_name()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_name ( ) const
```

#### 7.18.3.4 init()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::init (
    Array_Type & Array,
    uint i,
    uint j )
```

#### 7.18.3.5 operator=() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::operator= (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy assignment.

### 7.18.3.6 operator=() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type>& Counter< Array_Type, Data_Type >::operator= (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment.

## 7.18.4 Member Data Documentation

### 7.18.4.1 count\_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::count_fun
```

Definition at line 38 of file counters-bones.hpp.

### 7.18.4.2 data

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Data_Type Counter< Array_Type, Data_Type >::data
```

Definition at line 40 of file counters-bones.hpp.

### 7.18.4.3 desc

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::desc = ""
```

Definition at line 42 of file counters-bones.hpp.

### 7.18.4.4 init\_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::init_fun
```

Definition at line 39 of file counters-bones.hpp.

## 7.18.4.5 name

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::name = ""
```

Definition at line 41 of file counters-bones.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters-bones.hpp

## 7.19 Counters&lt; Array\_Type, Data\_Type &gt; Class Template Reference

Vector of counters.

```
#include <counters-bones.hpp>
```

## Public Member Functions

- [Counters](#) ()
- [~Counters](#) ()
- [Counters](#) (const [Counters](#)< Array\_Type, Data\_Type > &[counter\\_](#))  
*Copy constructor.*
- [Counters](#) ([Counters](#)< Array\_Type, Data\_Type > &&[counters\\_](#)) noexcept  
*Move constructor.*
- [Counters](#)< Array\_Type, Data\_Type > [operator=](#) (const [Counters](#)< Array\_Type, Data\_Type > &[counter\\_](#))  
*Copy assignment constructor.*
- [Counters](#)< Array\_Type, Data\_Type > & [operator=](#) ([Counters](#)< Array\_Type, Data\_Type > &&[counter\\_](#)) noexcept  
*Move assignment constructor.*
- [Counter](#)< Array\_Type, Data\_Type > & [operator\[\]](#) (uint idx)  
*Returns a pointer to a particular counter.*
- std::size\_t [size](#) () const noexcept  
*Number of counters in the set.*
- void [add\\_counter](#) ([Counter](#)< Array\_Type, Data\_Type > [counter](#))
- void [add\\_counter](#) ([Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [count\\_fun\\_](#), [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun\\_](#), Data\_Type [data\\_](#), std::string [name\\_](#)="", std::string [desc\\_](#)="")
- std::vector< std::string > [get\\_names](#) () const
- std::vector< std::string > [get\\_descriptions](#) () const

## 7.19.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counters< Array_Type, Data_Type >
```

Vector of counters.

Various functions hold more than one counter, so this class is a helper class that allows managing multiple counters efficiently. The main data is a vector to pointers of counters.

Definition at line 92 of file counters-bones.hpp.

## 7.19.2 Constructor & Destructor Documentation

### 7.19.2.1 Counters() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters ( )
```

### 7.19.2.2 ~Counters()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::~~Counters ( ) [inline]
```

Definition at line 103 of file counters-bones.hpp.

### 7.19.2.3 Counters() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

#### Parameters

<i>counter_↔</i>	
—	

### 7.19.2.4 Counters() [3/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    Counters< Array_Type, Data_Type > && counters_ ) [noexcept]
```

Move constructor.

#### Parameters

<i>counters_↔</i>	
—	

### 7.19.3 Member Function Documentation

#### 7.19.3.1 add\_counter() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > counter )
```

#### 7.19.3.2 add\_counter() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" )
```

#### 7.19.3.3 get\_descriptions()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_descriptions ( ) const
```

#### 7.19.3.4 get\_names()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_names ( ) const
```

#### 7.19.3.5 operator=() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type> Counters< Array_Type, Data_Type >::operator= (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy assignment constructor.

## Parameters

<i>counter</i> ↔	
—	

## Returns

[Counters<Array\\_Type,Data\\_Type>](#)

## 7.19.3.6 operator=() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type>& Counters< Array_Type, Data_Type >::operator= (
    Counters< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment constructor.

## Parameters

<i>counter</i> ↔	
—	

## Returns

[Counters<Array\\_Type,Data\\_Type>&](#)

## 7.19.3.7 operator[]()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type>& Counters< Array_Type, Data_Type >::operator[] (
    uint idx )
```

Returns a pointer to a particular counter.

## Parameters

<i>idx</i>	Id of the counter
------------	-------------------

## Returns

[Counter<Array\\_Type,Data\\_Type>\\*](#)

### 7.19.3.8 size()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::size_t Counters< Array_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Number of counters in the set.

#### Returns

uint

Definition at line 147 of file counters-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/counters-bones.hpp](#)

## 7.20 DEFM Class Reference

```
#include <defm-bones.hpp>
```

### Public Member Functions

- [DEFM](#) ([const](#) int \*id, [const](#) int \*y, [const](#) double \*x, size\_t id\_length, size\_t y\_ncol, size\_t x\_ncol, size\_t m\_order)
- [~DEFM](#) ()
- [defmcounters::DEFMModel](#) & [get\\_model](#) ()
- void [init](#) ()
- double [likelihood](#) (std::vector< double > &par, bool as\_log=[false](#))
- void [simulate](#) (std::vector< double > par, int \*y\_out)
- size\_t [get\\_n\\_y](#) () [const](#)
- size\_t [get\\_n\\_obs](#) () [const](#)
- size\_t [get\\_n\\_covars](#) () [const](#)
- size\_t [get\\_m\\_order](#) () [const](#)
- size\_t [get\\_n\\_rows](#) () [const](#)
- [const](#) int \* [get\\_Y](#) () [const](#)
- [const](#) int \* [get\\_ID](#) () [const](#)
- [const](#) double \* [get\\_X](#) () [const](#)
- [barry::FreqTable](#)< int > [motif\\_census](#) (std::vector< size\_t > idx)

### 7.20.1 Detailed Description

Definition at line 4 of file defm-bones.hpp.

### 7.20.2 Constructor & Destructor Documentation

### 7.20.2.1 DEFM()

```
DEFM::DEFM (
    const int * id,
    const int * y,
    const double * x,
    size_t id_length,
    size_t y_ncol,
    size_t x_ncol,
    size_t m_order ) [inline]
```

Definition at line 110 of file defm-meat.hpp.

### 7.20.2.2 ~DEFM()

```
DEFM::~~DEFM ( ) [inline]
```

Definition at line 42 of file defm-bones.hpp.

## 7.20.3 Member Function Documentation

### 7.20.3.1 get\_ID()

```
const int * DEFM::get_ID ( ) const [inline]
```

Definition at line 259 of file defm-meat.hpp.

### 7.20.3.2 get\_m\_order()

```
size_t DEFM::get_m_order ( ) const [inline]
```

Definition at line 244 of file defm-meat.hpp.

### 7.20.3.3 get\_model()

```
defmcounters::DEFMModel& DEFM::get_model ( ) [inline]
```

Definition at line 44 of file defm-bones.hpp.



#### 7.20.3.4 get\_n\_covars()

```
size_t DEFM::get_n_covars ( ) const [inline]
```

Definition at line 239 of file defm-meat.hpp.

#### 7.20.3.5 get\_n\_obs()

```
size_t DEFM::get_n_obs ( ) const [inline]
```

Definition at line 234 of file defm-meat.hpp.

#### 7.20.3.6 get\_n\_rows()

```
size_t DEFM::get_n_rows ( ) const [inline]
```

Definition at line 249 of file defm-meat.hpp.

#### 7.20.3.7 get\_n\_y()

```
size_t DEFM::get_n_y ( ) const [inline]
```

Definition at line 229 of file defm-meat.hpp.

#### 7.20.3.8 get\_X()

```
const double * DEFM::get_X ( ) const [inline]
```

Definition at line 264 of file defm-meat.hpp.

#### 7.20.3.9 get\_Y()

```
const int * DEFM::get_Y ( ) const [inline]
```

Definition at line 254 of file defm-meat.hpp.

### 7.20.3.10 init()

```
void DEFM::init ( ) [inline]
```

Definition at line 188 of file defm-meat.hpp.

### 7.20.3.11 likelihood()

```
double DEFM::likelihood (
    std::vector< double > & par,
    bool as_log = false )
```

### 7.20.3.12 motif\_census()

```
barry::FreqTable< int > DEFM::motif_census (
    std::vector< size_t > idx ) [inline]
```

Definition at line 270 of file defm-meat.hpp.

### 7.20.3.13 simulate()

```
void DEFM::simulate (
    std::vector< double > par,
    int * y_out ) [inline]
```

Definition at line 44 of file defm-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/models/defm/[defm-bones.hpp](#)
- include/barry/models/defm/[defm-meat.hpp](#)

## 7.21 DEFMCounterData Class Reference

Data class used to store arbitrary uint or double vectors.

```
#include <defm.hpp>
```

## Public Member Functions

- [DEFMCOUNTERDATA](#) ()
- [DEFMCOUNTERDATA](#) ([const](#) std::vector< size\_t > [indices\\_](#), [const](#) std::vector< double > [numbers\\_](#), [const](#) std::vector< bool > [logical\\_](#))
- size\_t [idx](#) (size\_t [i](#))
- double [num](#) (size\_t [i](#))
- bool [is\\_true](#) (size\_t [i](#))
- [~DEFMCOUNTERDATA](#) ()

## Public Attributes

- std::vector< size\_t > [indices](#)
- std::vector< double > [numbers](#)
- std::vector< bool > [logical](#)

### 7.21.1 Detailed Description

Data class used to store arbitrary uint or double vectors.

Definition at line 70 of file `defm.hpp`.

### 7.21.2 Constructor & Destructor Documentation

#### 7.21.2.1 DEFMCOUNTERDATA() [1/2]

```
DEFMCOUNTERDATA::DEFMCOUNTERDATA ( ) [inline]
```

Definition at line 77 of file `defm.hpp`.

#### 7.21.2.2 DEFMCOUNTERDATA() [2/2]

```
DEFMCOUNTERDATA::DEFMCOUNTERDATA (
    const std::vector< size_t > indices\_,
    const std::vector< double > numbers\_,
    const std::vector< bool > logical\_ ) [inline]
```

Definition at line 78 of file `defm.hpp`.

### 7.21.2.3 ~DEFMCounterData()

```
DEFMCounterData::~~DEFMCounterData ( ) [inline]
```

Definition at line 89 of file defm.hpp.

## 7.21.3 Member Function Documentation

### 7.21.3.1 idx()

```
size_t DEFMCounterData::idx (
    size_t i ) [inline]
```

Definition at line 85 of file defm.hpp.

### 7.21.3.2 is\_true()

```
bool DEFMCounterData::is_true (
    size_t i ) [inline]
```

Definition at line 87 of file defm.hpp.

### 7.21.3.3 num()

```
double DEFMCounterData::num (
    size_t i ) [inline]
```

Definition at line 86 of file defm.hpp.

## 7.21.4 Member Data Documentation

### 7.21.4.1 indices

```
std::vector< size_t > DEFMCounterData::indices
```

Definition at line 73 of file defm.hpp.

### 7.21.4.2 logical

```
std::vector< bool > DEFMCounterData::logical
```

Definition at line 75 of file defm.hpp.

### 7.21.4.3 numbers

```
std::vector< double > DEFMCounterData::numbers
```

Definition at line 74 of file defm.hpp.


The documentation for this class was generated from the following file:

- include/barry/counters/[defm.hpp](#)

## 7.22 DEFMDData Class Reference

```
#include <defm.hpp>
```

Collaboration diagram for DEFMDData:



### Public Member Functions

- [DEFMDData](#) ()
- [DEFMDData](#) ([DEFMArray](#) \*array\_, [const](#) double \*covariates\_, [size\\_t](#) obs\_start\_, [size\\_t](#) X\_ncol\_, [size\\_t](#) X\_nrow\_)
  - Constructor.*
- [double](#) [operator\(\)](#) ([size\\_t](#) i, [size\\_t](#) j) [const](#)
  - Access to the row (i) column (j) data.*
- [double](#) [at](#) ([size\\_t](#) i, [size\\_t](#) j) [const](#)
- [size\\_t](#) [ncol](#) () [const](#)
- [void](#) [print](#) () [const](#)
- [~DEFMDData](#) ()

## Public Attributes

- [DEFMArray](#) \* [array](#)
- [const](#) double \* [covariates](#)  
*Vector of covariates (complete vector)*
- [size\\_t](#) [obs\\_start](#)  
*Index of the observation in the data.*
- [size\\_t](#) [X\\_ncol](#)  
*Number of covariates included in the model.*
- [size\\_t](#) [X\\_nrow](#)  
*Number of covariates included in the model.*

### 7.22.1 Detailed Description

Definition at line 25 of file defm.hpp.

### 7.22.2 Constructor & Destructor Documentation

#### 7.22.2.1 DEFMDData() [1/2]

```
DEFMDData::DEFMDData ( ) [inline]
```

Definition at line 34 of file defm.hpp.

#### 7.22.2.2 DEFMDData() [2/2]

```
DEFMDData::DEFMDData (
    DEFMArray * array_,
    const double * covariates_,
    size_t obs_start_,
    size_t X_ncol_,
    size_t X_nrow_ ) [inline]
```

Constructor.

#### Parameters

<a href="#">covariates_</a>	Pointer to the attribute data.
<a href="#">obs_start_</a>	Location of the current observation in the covariates vector
<a href="#">X_ncol_</a>	Number of columns (covariates.)

Definition at line 43 of file defm.hpp.

### 7.22.2.3 ~DEFMDData()

```
DEFMDData::~DEFMDData ( ) [inline]
```

Definition at line 64 of file defm.hpp.

## 7.22.3 Member Function Documentation

### 7.22.3.1 at()

```
double DEFMDData::at (
    size_t i,
    size_t j ) const
```

### 7.22.3.2 ncol()

```
size_t DEFMDData::ncol ( ) const [inline]
```

Definition at line 130 of file defm.hpp.

### 7.22.3.3 operator()()

```
double DEFMDData::operator() (
    size_t i,
    size_t j ) const [inline]
```

Access to the row (i) column (j) data.

#### Parameters

<i>i</i>	
<i>j</i>	

#### Returns

double

Definition at line 125 of file defm.hpp.

#### 7.22.3.4 print()

```
void DEFMDData::print ( ) const [inline]
```

Definition at line 134 of file defm.hpp.

### 7.22.4 Member Data Documentation

#### 7.22.4.1 array

```
DEFMArray* DEFMDData::array
```

Definition at line 28 of file defm.hpp.

#### 7.22.4.2 covariates

```
const double* DEFMDData::covariates
```

Vector of covariates (complete vector)

Definition at line 29 of file defm.hpp.

#### 7.22.4.3 obs\_start

```
size_t DEFMDData::obs_start
```

Index of the observation in the data.

Definition at line 30 of file defm.hpp.

#### 7.22.4.4 X\_ncol

```
size_t DEFMDData::X_ncol
```

Number of covariates included in the model.

Definition at line 31 of file defm.hpp.



#### 7.22.4.5 X\_nrow

```
size_t DEFMDData::X_nrow
```

Number of covariates included in the model.

Definition at line 32 of file defm.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[defm.hpp](#)

## 7.23 DEFMRuleData Class Reference

```
#include <defm.hpp>
```

### Public Member Functions

- double [num](#) (size\_t [i](#))
- size\_t [idx](#) (size\_t [i](#))
- [DEFMRuleData](#) ()
- [DEFMRuleData](#) (std::vector< double > [numbers\\_](#), std::vector< size\_t > [indices\\_](#))

#### 7.23.1 Detailed Description

Definition at line 93 of file defm.hpp.

#### 7.23.2 Constructor & Destructor Documentation

##### 7.23.2.1 DEFMRuleData() [1/2]

```
DEFMRuleData::DEFMRuleData ( ) [inline]
```

Definition at line 103 of file defm.hpp.

##### 7.23.2.2 DEFMRuleData() [2/2]

```
DEFMRuleData::DEFMRuleData (
    std::vector< double > numbers\_,
    std::vector< size_t > indices\_ ) [inline]
```

Definition at line 105 of file defm.hpp.

### 7.23.3 Member Function Documentation

#### 7.23.3.1 idx()

```
size_t DEFMRuleData::idx (
    size_t i ) [inline]
```

Definition at line 101 of file defm.hpp.

#### 7.23.3.2 num()

```
double DEFMRuleData::num (
    size_t i ) [inline]
```

Definition at line 100 of file defm.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[defm.hpp](#)

## 7.24 Entries< Cell\_Type > Class Template Reference

A wrapper class to store `source`, `target`, `val` from a [BArray](#) object.

```
#include <typedefs.hpp>
```

### Public Member Functions

- [Entries](#) ()
- [Entries](#) (uint n)
- [~Entries](#) ()
- void [resize](#) (uint n)

### Public Attributes

- std::vector< [uint](#) > [source](#)
- std::vector< [uint](#) > [target](#)
- std::vector< Cell\_Type > [val](#)

#### 7.24.1 Detailed Description

```
template<typename Cell_Type>
class Entries< Cell_Type >
```

A wrapper class to store `source`, `target`, `val` from a [BArray](#) object.

## Template Parameters

<i>Cell_Type</i>	Any type
------------------	----------

Definition at line 79 of file typedefs.hpp.

## 7.24.2 Constructor & Destructor Documentation

### 7.24.2.1 Entries() [1/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries ( ) [inline]
```

Definition at line 85 of file typedefs.hpp.

### 7.24.2.2 Entries() [2/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries (
    uint n ) [inline]
```

Definition at line 86 of file typedefs.hpp.

### 7.24.2.3 ~Entries()

```
template<typename Cell_Type >
Entries< Cell_Type >::~~Entries ( ) [inline]
```

Definition at line 93 of file typedefs.hpp.

## 7.24.3 Member Function Documentation

### 7.24.3.1 resize()

```
template<typename Cell_Type >
void Entries< Cell_Type >::resize (
    uint n ) [inline]
```

Definition at line 95 of file typedefs.hpp.

## 7.24.4 Member Data Documentation

### 7.24.4.1 source

```
template<typename Cell_Type >  
std::vector< uint > Entries< Cell_Type >::source
```

Definition at line 81 of file typedefs.hpp.

### 7.24.4.2 target

```
template<typename Cell_Type >  
std::vector< uint > Entries< Cell_Type >::target
```

Definition at line 82 of file typedefs.hpp.

### 7.24.4.3 val

```
template<typename Cell_Type >  
std::vector< Cell_Type > Entries< Cell_Type >::val
```

Definition at line 83 of file typedefs.hpp.

The documentation for this class was generated from the following file:

- [include/barry/typedefs.hpp](#)

## 7.25 Flock Class Reference

A [Flock](#) is a group of [Geese](#).

```
#include <flock-bones.hpp>
```

## Public Member Functions

- `Flock ()`
- `~Flock ()`
- `unsigned int add_data (std::vector< std::vector< unsigned int > > &annotations, std::vector< unsigned int > &geneid, std::vector< int > &parent, std::vector< bool > &duplication)`  
*Add a tree to the flock.*
- `void set_seed (const unsigned int &s)`  
*Set the seed of the model.*
- `void init (unsigned int bar_width=BARRY_PROGRESS_BAR_WIDTH)`
- `phylocounters::PhyloCounters * get_counters ()`
- `phylocounters::PhyloSupport * get_support_fun ()`
- `std::vector< std::vector< double > > * get_stats_support ()`
- `std::vector< std::vector< double > > * get_stats_target ()`
- `phylocounters::PhyloModel * get_model ()`
- `double likelihood_joint (const std::vector< double > &par, bool as_log=false, bool use_reduced_↔ sequence=true)`  
*Returns the joint likelihood of the model.*
- `Geese * operator() (unsigned int i, bool check_bounds=true)`  
*Access the i-th geese element.*

## Information about the model

- `unsigned int nfuncs () const noexcept`
- `unsigned int ntrees () const noexcept`
- `std::vector< unsigned int > nnodes () const noexcept`
- `std::vector< unsigned int > nleaves () const noexcept`
- `unsigned int nterms () const`
- `unsigned int support_size () const noexcept`
- `std::vector< std::string > colnames () const`
- `unsigned int parse_polytomies (bool verb=true, std::vector< size_t > *dist=nullptr) const noexcept`  
*Check polytomies and return the largest.*
- `void print () const`

## Public Attributes

- `std::vector< Geese > dat`
- `unsigned int nfunctions = 0u`
- `bool initialized = false`
- `std::mt19937 engine`
- `phylocounters::PhyloModel model = phylocounters::PhyloModel()`

### 7.25.1 Detailed Description

A `Flock` is a group of `Geese`.

This object builds a model with multiple trees (`Geese` objects), with all of these using the same `PhyloModel` object. Available counters (terms) can be found in `counter-phylo`.

Definition at line 14 of file `flock-bones.hpp`.

## 7.25.2 Constructor & Destructor Documentation

### 7.25.2.1 Flock()

```
Flock::Flock ( ) [inline]
```

Definition at line 25 of file flock-bones.hpp.

### 7.25.2.2 ~Flock()

```
Flock::~~Flock ( ) [inline]
```

Definition at line 26 of file flock-bones.hpp.

## 7.25.3 Member Function Documentation

### 7.25.3.1 add\_data()

```
unsigned int Flock::add_data (
    std::vector< std::vector< unsigned int > > & annotations,
    std::vector< unsigned int > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Add a tree to the flock.

#### Parameters

<i>annotations</i>	see <a href="#">Geese::Geese</a> .
<i>geneid</i>	see <a href="#">Geese</a> .
<i>parent</i>	see <a href="#">Geese</a> .
<i>duplication</i>	see <a href="#">Geese</a> .

#### Returns

unsigned int The number of tree in the model (starting from zero).

Definition at line 6 of file flock-meat.hpp.

### 7.25.3.2 colnames()

```
std::vector< std::string > Flock::colnames ( ) const [inline]
```

Definition at line 224 of file flock-meat.hpp.

### 7.25.3.3 get\_counters()

```
phylocounters::PhyloCounters * Flock::get_counters ( ) [inline]
```

Definition at line 100 of file flock-meat.hpp.

### 7.25.3.4 get\_model()

```
phylocounters::PhyloModel * Flock::get_model ( ) [inline]
```

Definition at line 131 of file flock-meat.hpp.

### 7.25.3.5 get\_stats\_support()

```
std::vector< std::vector< double > > * Flock::get_stats_support ( ) [inline]
```

Definition at line 117 of file flock-meat.hpp.

### 7.25.3.6 get\_stats\_target()

```
std::vector< std::vector< double > > * Flock::get_stats_target ( ) [inline]
```

Definition at line 124 of file flock-meat.hpp.

### 7.25.3.7 get\_support\_fun()

```
phylocounters::PhyloSupport * Flock::get_support_fun ( ) [inline]
```

Definition at line 110 of file flock-meat.hpp.

### 7.25.3.8 init()

```
void Flock::init (
    unsigned int bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 49 of file flock-meat.hpp.

### 7.25.3.9 likelihood\_joint()

```
double Flock::likelihood_joint (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Returns the joint likelihood of the model.

#### Parameters

<i>par</i>	Vector of model parameters.
<i>as_log</i>	When <i>true</i> it will return the value as log.
<i>use_reduced_sequence</i>	When <i>true</i> (default) will compute the likelihood using the reduced sequence, which is faster.

#### Returns

double

Definition at line 138 of file flock-meat.hpp.

### 7.25.3.10 nfuncs()

```
unsigned int Flock::nfuncs ( ) const [inline], [noexcept]
```

Definition at line 167 of file flock-meat.hpp.

### 7.25.3.11 nleafs()

```
std::vector< unsigned int > Flock::nleafs ( ) const [inline], [noexcept]
```

Definition at line 195 of file flock-meat.hpp.



### 7.25.3.12 nnodes()

```
std::vector< unsigned int > Flock::nnodes ( ) const [inline], [noexcept]
```

Definition at line 181 of file flock-meat.hpp.

### 7.25.3.13 nterms()

```
unsigned int Flock::nterms ( ) const [inline]
```

Definition at line 209 of file flock-meat.hpp.

### 7.25.3.14 ntrees()

```
unsigned int Flock::ntrees ( ) const [inline], [noexcept]
```

Definition at line 174 of file flock-meat.hpp.

### 7.25.3.15 operator>()()

```
Geese * Flock::operator() (
    unsigned int i,
    bool check_bounds = true ) [inline]
```

Access the i-th geese element.

#### Parameters

<i>i</i>	Element to access
<i>check_bounds</i>	When true, it will check bounds.

#### Returns

Geese\*

Definition at line 302 of file flock-meat.hpp.

### 7.25.3.16 parse\_polytomies()

```
unsigned int Flock::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 231 of file flock-meat.hpp.

#### 7.25.3.17 print()

```
void Flock::print ( ) const [inline]
```

Definition at line 258 of file flock-meat.hpp.

#### 7.25.3.18 set\_seed()

```
void Flock::set_seed (
    const unsigned int & s ) [inline]
```

Set the seed of the model.

##### Parameters

s	Passed to the <code>rengine.seed()</code> member object.
---	--

Definition at line 42 of file flock-meat.hpp.

#### 7.25.3.19 support\_size()

```
unsigned int Flock::support_size ( ) const [inline], [noexcept]
```

Definition at line 217 of file flock-meat.hpp.

### 7.25.4 Member Data Documentation

#### 7.25.4.1 dat

```
std::vector< Geese > Flock::dat
```

Definition at line 17 of file flock-bones.hpp.

#### 7.25.4.2 initialized

```
bool Flock::initialized = false
```

Definition at line 19 of file flock-bones.hpp.

#### 7.25.4.3 model

```
phylocounters::PhyloModel Flock::model = phylocounters::PhyloModel()
```

Definition at line 23 of file flock-bones.hpp.

#### 7.25.4.4 nfunctions

```
unsigned int Flock::nfunctions = 0u
```

Definition at line 18 of file flock-bones.hpp.

#### 7.25.4.5 engine

```
std::mt19937 Flock::engine
```

Definition at line 22 of file flock-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/models/geese/flock-bones.hpp](#)
- [include/barry/models/geese/flock-meat.hpp](#)

## 7.26 FreqTable< T > Class Template Reference

Frequency table of vectors.

```
#include <freqtable.hpp>
```

## Public Member Functions

- [FreqTable](#) ()
  - [~FreqTable](#) ()
  - [size\\_t add](#) ([const](#) std::vector< T > &x, [size\\_t](#) \*h\_precomp)
  - [Counts\\_type as\\_vector](#) () [const](#)
  - [const](#) std::vector< double > & [get\\_data](#) () [const](#)
  - [const](#) std::unordered\_map< [size\\_t](#), [size\\_t](#) > & [get\\_index](#) () [const](#)
  - void [clear](#) ()
  - void [reserve](#) ([size\\_t](#) n, [size\\_t](#) k)
  - void [print](#) () [const](#)
  - [size\\_t size](#) () [const](#) [noexcept](#)
- Number of unique elements in the table. (.*
- [size\\_t make\\_hash](#) ([const](#) std::vector< T > &x) [const](#)

### 7.26.1 Detailed Description

```
template<typename T = double>
class FreqTable< T >
```

Frequency table of vectors.

This is mostly used in [Support](#). The main data is contained in the `data` double vector. The matrix is stored in a row-wise fashion, where the first element is the frequency with which the vector is observed.

For example, in a model with `k` terms the first `k + 1` elements of `data` would be:

- weights
- term 1
- term 2
- ...
- term k

Definition at line 22 of file `freqtable.hpp`.

### 7.26.2 Constructor & Destructor Documentation

#### 7.26.2.1 FreqTable()

```
template<typename T = double>
FreqTable< T >::FreqTable ( ) [inline]
```

Definition at line 34 of file `freqtable.hpp`.

### 7.26.2.2 ~FreqTable()

```
template<typename T = double>
FreqTable< T >::~~FreqTable ( ) [inline]
```

Definition at line 35 of file freqtable.hpp.

## 7.26.3 Member Function Documentation

### 7.26.3.1 add()

```
template<typename T >
size_t FreqTable< T >::add (
    const std::vector< T > & x,
    size_t * h_precomp ) [inline]
```

Definition at line 59 of file freqtable.hpp.

### 7.26.3.2 as\_vector()

```
template<typename T >
Counts_type FreqTable< T >::as_vector [inline]
```

Definition at line 139 of file freqtable.hpp.

### 7.26.3.3 clear()

```
template<typename T >
void FreqTable< T >::clear [inline]
```

Definition at line 168 of file freqtable.hpp.

### 7.26.3.4 get\_data()

```
template<typename T = double>
const std::vector< double > FreqTable< T >::get_data ( ) const [inline]
```

Definition at line 40 of file freqtable.hpp.

### 7.26.3.5 get\_index()

```
template<typename T = double>
const std::unordered_map<size_t, size_t>& FreqTable< T >::get_index ( ) const [inline]
```

Definition at line 41 of file freqtable.hpp.

### 7.26.3.6 make\_hash()

```
template<typename T >
size_t FreqTable< T >::make_hash (
    const std::vector< T > & x ) const [inline]
```

Definition at line 239 of file freqtable.hpp.

### 7.26.3.7 print()

```
template<typename T >
void FreqTable< T >::print [inline]
```

Definition at line 204 of file freqtable.hpp.

### 7.26.3.8 reserve()

```
template<typename T >
void FreqTable< T >::reserve (
    size_t n,
    size_t k ) [inline]
```

Definition at line 182 of file freqtable.hpp.

### 7.26.3.9 size()

```
template<typename T >
size_t FreqTable< T >::size [inline], [noexcept]
```

Number of unique elements in the table. (.

#### Returns

size\_t

Definition at line 231 of file freqtable.hpp.

The documentation for this class was generated from the following file:

- [include/barry/freqtable.hpp](#)

## 7.27 Geese Class Reference

Annotated Phylo [Model](#).

```
#include <geese-bones.hpp>
```

### Public Member Functions

- [~Geese](#) ()
- void [init](#) (unsigned int bar\_width=[BARRY\\_PROGRESS\\_BAR\\_WIDTH](#))
- void [inherit\\_support](#) (const [Geese](#) &model\_, bool delete\_support\_[=false](#))
- void [calc\\_sequence](#) ([Node](#) \*n=nullptr)
- void [calc\\_reduced\\_sequence](#) ()
- double [likelihood](#) (const std::vector< double > &par, bool as\_log=[false](#), bool use\_reduced\_sequence=true)
- double [likelihood\\_exhaust](#) (const std::vector< double > &par)
- std::vector< double > [get\\_probabilities](#) () const
- void [set\\_seed](#) (const unsigned int &s)
- std::vector< std::vector< unsigned int > > & [simulate](#) (const std::vector< double > &par)
- std::vector< std::vector< double > > & [observed\\_counts](#) ()
- void [print\\_observed\\_counts](#) ()
- void [print](#) () const
 

*Prints information about the GEESE.*
- void [init\\_node](#) ([Node](#) &n)
- void [update\\_annotations](#) (unsigned int nodeid, std::vector< unsigned int > newann)
- std::vector< std::vector< bool > > & [get\\_states](#) () const
 

*Powerset of a gene's possible states.*
- std::vector< unsigned int > & [get\\_annotated\\_nodes](#) () const
 

*Returns the ids of the nodes with at least one annotation.*

### Construct a new Geese object

The model includes a total of  $N + 1$  nodes, the  $+ 1$  beign the root node.

#### Parameters

annotations	A vector of vectors with annotations. It should be of length $k$ (number of functions). Each vector should be of length $N$ (equal to the number of nodes, including interior). Possible values are 0, 1, and 9.
geneid	Id of the gene. It should be of length $N$ .
parent	Id of the parent gene. Also of length $N$
duplication	Logical scalar indicating the type of event (true: duplication, false: speciation.)

The ordering of the entries does not matter. Passing the nodes in post order or not makes no difference to the constructor.

- [Geese](#) ()
- [Geese](#) (std::vector< std::vector< unsigned int > > &annotations, std::vector< unsigned int > &geneid, std::vector< int > &parent, std::vector< bool > &duplication)
- [Geese](#) (const [Geese](#) &model\_, bool copy\_data=true)
- [Geese](#) ([Geese](#) &&x) noexcept
- [Geese](#) & operator= (const [Geese](#) &model\_)=delete
- [Geese](#) & operator= ([Geese](#) &&model\_) noexcept=delete

### Information about the model



**Parameters**

verb	When <i>true</i> it will print out information about the encountered polytomies.
------	--

- unsigned int `nfuncs` () `const noexcept`  
Number of functions analyzed.
- unsigned int `nnodes` () `const noexcept`  
Number of nodes (interior + leaf)
- unsigned int `nleafs` () `const noexcept`  
Number of leaf.
- unsigned int `nterms` () `const`  
Number of terms included.
- unsigned int `support_size` () `const noexcept`  
Number of unique sets of sufficient stats.
- `std::vector< unsigned int >` `nannotations` () `const noexcept`  
Number of annotations.
- `std::vector< std::string >` `colnames` () `const`  
Names of the terms in the model.
- unsigned int `parse_polytomies` (bool verb=*true*, `std::vector< size_t > *dist=nullptr`) `const noexcept`  
Check polytomies and return the largest.

**Geese prediction**

Calculate the conditional probability

**Parameters**

par	Vector of parameters (terms + root).
res_prob	Vector indicating each nodes' state probability.
leave_one_out	When <i>true</i> , it will compute the predictions using leave-one-out, thus the prediction will be repeated <i>nleaf</i> times.
only_annotated	When <i>true</i> , it will make the predictions only on the induced sub-tree with annotated leafs.
use_reduced_sequence	Passed to the <i>likelihood</i> method.
preorder	For the tree traversal.

When *res\_prob* is specified, the function will attach the member vector probabilities from the *Nodes* objects. This contains the probability that the *i*th node has either of the possible states.

**Returns**

`std::vector< double >` Returns the posterior probability

- `std::vector< std::vector< double > >` `predict` (`const std::vector< double > &par`, `std::vector< std::vector< double > > *res_prob=nullptr`, bool leave\_one\_out=*false*, bool only\_annotated=*false*, bool use\_reduced\_sequence=*true*)
- `std::vector< std::vector< double > >` `predict_backend` (`const std::vector< double > &par`, bool use\_reduced\_sequence, `const std::vector< uint > &preorder`)
- `std::vector< std::vector< double > >` `predict_exhaust_backend` (`const std::vector< double > &par`, `const std::vector< uint > &preorder`)
- `std::vector< std::vector< double > >` `predict_exhaust` (`const std::vector< double > &par`)
- `std::vector< std::vector< double > >` `predict_sim` (`const std::vector< double > &par`, bool only\_annotated=*false*, unsigned int nsims=10000u)

**Non-const pointers to shared objects in `<tt>Geese</tt>`**

These functions provide direct access to some member objects that are shared by the nodes within *Geese*.

**Returns**

*`get_engine()` returns the Pseudo-RNG engine used.*  
*`get_counters()` returns the vector of counters used.*  
*`get_model()` returns the [Model](#) object used.*  
*`get_support_fun()` returns the computed support of the model.*

- `std::mt19937 * get\_engine ()`
- `phylocounters::PhyloCounters * get\_counters ()`
- `phylocounters::PhyloModel * get\_model ()`
- `phylocounters::PhyloSupport * get\_support\_fun ()`

**Public Attributes**

- unsigned int [nfunctions](#)
- `std::map< unsigned int, Node > nodes`
- `barry::MapVec_type< unsigned int > map\_to\_nodes`
- `std::vector< std::vector< std::vector< size_t > > > pset\_loc`  
*Locations of columns.*
- `std::vector< unsigned int > sequence`
- `std::vector< unsigned int > reduced\_sequence`
- bool [initialized](#) = `false`
- bool [delete\\_engine](#) = `false`
- bool [delete\\_support](#) = `false`

**7.27.1 Detailed Description**

Annotated Phylo [Model](#).

A list of available terms for this model can be found in the [Phylo counters](#) section.

Definition at line 80 of file `geese-bones.hpp`.

**7.27.2 Constructor & Destructor Documentation****7.27.2.1 Geese() [1/4]**

```
Geese::Geese ( ) [inline]
```

Definition at line 6 of file `geese-meat-constructors.hpp`.

### 7.27.2.2 Geese() [2/4]

```
Geese::Geese (
    std::vector< std::vector< unsigned int > > & annotations,
    std::vector< unsigned int > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Definition at line 20 of file geese-meat-constructors.hpp.

### 7.27.2.3 Geese() [3/4]

```
Geese::Geese (
    const Geese & model_,
    bool copy_data = true ) [inline]
```

Definition at line 214 of file geese-meat-constructors.hpp.

### 7.27.2.4 Geese() [4/4]

```
Geese::Geese (
    Geese && x ) [inline], [noexcept]
```

Definition at line 293 of file geese-meat-constructors.hpp.

### 7.27.2.5 ~Geese()

```
Geese::~Geese ( ) [inline]
```

Definition at line 91 of file geese-meat.hpp.

## 7.27.3 Member Function Documentation

### 7.27.3.1 calc\_reduced\_sequence()

```
void Geese::calc_reduced_sequence ( ) [inline]
```

Definition at line 331 of file geese-meat.hpp.

### 7.27.3.2 calc\_sequence()

```
void Geese::calc_sequence (
    Node * n = nullptr ) [inline]
```

Definition at line 287 of file geese-meat.hpp.

### 7.27.3.3 colnames()

```
std::vector< std::string > Geese::colnames ( ) const [inline]
```

Names of the terms in the model.

Definition at line 453 of file geese-meat.hpp.

### 7.27.3.4 get\_annotated\_nodes()

```
std::vector< unsigned int > Geese::get_annotated_nodes ( ) const [inline]
```

Returns the ids of the nodes with at least one annotation.

Definition at line 669 of file geese-meat.hpp.

### 7.27.3.5 get\_counters()

```
phylocounters::PhyloCounters * Geese::get_counters ( ) [inline]
```

Definition at line 652 of file geese-meat.hpp.

### 7.27.3.6 get\_model()

```
phylocounters::PhyloModel * Geese::get_model ( ) [inline]
```

Definition at line 657 of file geese-meat.hpp.

### 7.27.3.7 get\_probabilities()

```
std::vector< double > Geese::get_probabilities ( ) const [inline]
```

Definition at line 379 of file geese-meat.hpp.

**7.27.3.8 get\_engine()**

```
std::mt19937 * Geese::get_engine ( ) [inline]
```

Definition at line 647 of file geese-meat.hpp.

**7.27.3.9 get\_states()**

```
std::vector< std::vector< bool > > Geese::get_states ( ) const [inline]
```

Powerset of a gene's possible states.

This list of vectors is used throughout [Geese](#). It lists all possible combinations of functional states for any gene. Thus, for  $P$  functions, there will be  $2^P$  possible combinations.

**Returns**

`std::vector< std::vector< bool > >` of length  $2^P$ .

Definition at line 665 of file geese-meat.hpp.

**7.27.3.10 get\_support\_fun()**

```
phylocounters::PhyloSupport * Geese::get_support_fun ( ) [inline]
```

Definition at line 661 of file geese-meat.hpp.

**7.27.3.11 inherit\_support()**

```
void Geese::inherit_support (
    const Geese & model_,
    bool delete_support_ = false ) [inline]
```

Definition at line 230 of file geese-meat.hpp.

**7.27.3.12 init()**

```
void Geese::init (
    unsigned int bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 103 of file geese-meat.hpp.

### 7.27.3.13 init\_node()

```
void Geese::init_node (
    Node & n ) [inline]
```

Definition at line 6 of file geese-meat.hpp.

### 7.27.3.14 likelihood()

```
double Geese::likelihood (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 6 of file geese-meat-likelihood.hpp.

### 7.27.3.15 likelihood\_exhaust()

```
double Geese::likelihood_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 7 of file geese-meat-likelihood\_exhaust.hpp.

### 7.27.3.16 nannotations()

```
std::vector< unsigned int > Geese::nannotations ( ) const [inline], [noexcept]
```

Number of annotations.

Definition at line 444 of file geese-meat.hpp.

### 7.27.3.17 nfuncs()

```
unsigned int Geese::nfuncs ( ) const [inline], [noexcept]
```

Number of functions analyzed.

Definition at line 400 of file geese-meat.hpp.

### 7.27.3.18 nleafs()

```
unsigned int Geese::nleafs ( ) const [inline], [noexcept]
```

Number of leaf.

Definition at line 414 of file geese-meat.hpp.

### 7.27.3.19 nnodes()

```
unsigned int Geese::nnodes ( ) const [inline], [noexcept]
```

Number of nodes (interior + leaf)

Definition at line 407 of file geese-meat.hpp.

### 7.27.3.20 nterms()

```
unsigned int Geese::nterms ( ) const [inline]
```

Number of terms included.

Definition at line 426 of file geese-meat.hpp.

### 7.27.3.21 observed\_counts()

```
std::vector< std::vector< double > > Geese::observed_counts ( ) [inline]
```

Definition at line 495 of file geese-meat.hpp.

### 7.27.3.22 operator=() [1/2]

```
Geese& Geese::operator= (
    const Geese & model_ ) [delete]
```

### 7.27.3.23 operator=() [2/2]

```
Geese& Geese::operator= (
    Geese && model_ ) [delete], [noexcept]
```

#### 7.27.3.24 parse\_polytomies()

```
unsigned int Geese::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 460 of file geese-meat.hpp.

#### 7.27.3.25 predict()

```
std::vector< std::vector< double > > Geese::predict (
    const std::vector< double > & par,
    std::vector< std::vector< double > > * res_prob = nullptr,
    bool leave_one_out = false,
    bool only_annotated = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 243 of file geese-meat-predict.hpp.

#### 7.27.3.26 predict\_backend()

```
std::vector< std::vector< double > > Geese::predict_backend (
    const std::vector< double > & par,
    bool use_reduced_sequence,
    const std::vector< uint > & preorder ) [inline]
```

< True if the array belongs to the set

Definition at line 6 of file geese-meat-predict.hpp.

#### 7.27.3.27 predict\_exhaust()

```
std::vector< std::vector< double > > Geese::predict_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 5 of file geese-meat-predict\_exhaust.hpp.



### 7.27.3.28 predict\_exhaust\_backend()

```
std::vector< std::vector< double > > Geese::predict_exhaust_backend (
    const std::vector< double > & par,
    const std::vector< uint > & preorder ) [inline]
```

Definition at line 47 of file geese-meat-predict\_exhaust.hpp.

### 7.27.3.29 predict\_sim()

```
std::vector< std::vector< double > > Geese::predict_sim (
    const std::vector< double > & par,
    bool only_annotated = false,
    unsigned int nsims = 10000u ) [inline]
```

Definition at line 6 of file geese-meat-predict\_sim.hpp.

### 7.27.3.30 print()

```
void Geese::print ( ) const [inline]
```

Prints information about the GEESE.

Definition at line 629 of file geese-meat.hpp.

### 7.27.3.31 print\_observed\_counts()

```
void Geese::print_observed_counts ( ) [inline]
```

Definition at line 566 of file geese-meat.hpp.

### 7.27.3.32 set\_seed()

```
void Geese::set_seed (
    const unsigned int & s ) [inline]
```

Definition at line 4 of file geese-meat-simulate.hpp.

### 7.27.3.33 simulate()

```
std::vector< std::vector< unsigned int > > Geese::simulate (
    const std::vector< double > & par ) [inline]
```

Definition at line 8 of file geese-meat-simulate.hpp.

### 7.27.3.34 support\_size()

```
unsigned int Geese::support_size ( ) const [inline], [noexcept]
```

Number of unique sets of sufficient stats.

Definition at line 434 of file geese-meat.hpp.

### 7.27.3.35 update\_annotations()

```
void Geese::update_annotations (
    unsigned int nodeid,
    std::vector< unsigned int > newann ) [inline]
```

Definition at line 258 of file geese-meat.hpp.

## 7.27.4 Member Data Documentation

### 7.27.4.1 delete\_engine

```
bool Geese::delete_engine = false
```

Definition at line 118 of file geese-bones.hpp.

### 7.27.4.2 delete\_support

```
bool Geese::delete_support = false
```

Definition at line 119 of file geese-bones.hpp.

### 7.27.4.3 initialized

```
bool Geese::initialized = false
```

Definition at line 117 of file geese-bones.hpp.

### 7.27.4.4 map\_to\_nodes

```
barry::MapVec_type< unsigned int > Geese::map_to_nodes
```

Definition at line 109 of file geese-bones.hpp.

### 7.27.4.5 nfunctions

```
unsigned int Geese::nfunctions
```

Definition at line 107 of file geese-bones.hpp.

### 7.27.4.6 nodes

```
std::map< unsigned int, Node > Geese::nodes
```

Definition at line 108 of file geese-bones.hpp.

### 7.27.4.7 pset\_loc

```
std::vector< std::vector< std::vector< size_t > > > Geese::pset_loc
```

Locations of columns.

Definition at line 110 of file geese-bones.hpp.

### 7.27.4.8 reduced\_sequence

```
std::vector< unsigned int > Geese::reduced_sequence
```

Definition at line 114 of file geese-bones.hpp.

### 7.27.4.9 sequence

```
std::vector< unsigned int > Geese::sequence
```

Definition at line 113 of file geese-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/models/geese/geese-bones.hpp
- include/barry/models/geese/geese-meat-constructors.hpp
- include/barry/models/geese/geese-meat-likelihood.hpp
- include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp
- include/barry/models/geese/geese-meat-predict.hpp
- include/barry/models/geese/geese-meat-predict\_exhaust.hpp
- include/barry/models/geese/geese-meat-predict\_sim.hpp
- include/barry/models/geese/geese-meat-simulate.hpp
- include/barry/models/geese/geese-meat.hpp

## 7.28 Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > Class Template Reference

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

```
#include <model-bones.hpp>
```

### Public Member Functions

- void [set\\_engine](#) (std::mt19937 \*engine\_, bool delete\_=false)
- void [set\\_seed](#) (unsigned int s)
- [Model](#) ()
- [Model](#) (uint size\_)
- [Model](#) (const [Model](#)< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > &Model\_)
- [Model](#)< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > & [operator=](#) (const [Model](#)< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > &Model\_)
- [~Model](#) ()
- void [store\\_psets](#) () [noexcept](#)
- void [set\\_keygen](#) (std::function< std::vector< double > (const Array\_Type &)> keygen\_)
- std::vector< double > [gen\\_key](#) (const Array\_Type &Array\_)
- uint [add\\_array](#) (const Array\_Type &Array\_, bool force\_new=false)  
*Adds an array to the support of not already included.*
- void [print\\_stats](#) (uint i) [const](#)
- void [print](#) () [const](#)  
*Prints information about the model.*
- Array\_Type [sample](#) (const Array\_Type &Array\_, const std::vector< double > &params={})
- Array\_Type [sample](#) (const uint &i, const std::vector< double > &params)
- double [conditional\\_prob](#) (const Array\_Type &Array\_, const std::vector< double > &params, unsigned int i, unsigned int j)  
*Conditional probability ("Gibbs sampler")*

- `const std::mt19937 * get_engine () const`
- `Counters< Array_Type, Data_Counter_Type > * get_counters ()`
- `Rules< Array_Type, Data_Rule_Type > * get_rules ()`
- `Rules< Array_Type, Data_Rule_Dyn_Type > * get_rules_dyn ()`
- `Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > * get_support_fun ()`

#### Wrappers for the `<tt>Counters</tt>` member.

These will add counters to the model, which are shared by the support and the actual counter function.

- `void add_counter (Counter< Array_Type, Data_Counter_Type > &counter)`
- `void add_counter (Counter_fun_type< Array_Type, Data_Counter_Type > count_fun_, Counter_fun_type< Array_Type, Data_Counter_Type > init_fun_=nullptr, Data_Counter_Type data_=nullptr)`
- `void set_counters (Counters< Array_Type, Data_Counter_Type > *counters_)`

#### Wrappers for the `<tt>Rules</tt>` member.

These will add rules to the model, which are shared by the support and the actual counter function.

- `void add_rule (Rule< Array_Type, Data_Rule_Type > &rule)`
- `void add_rule (Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_, Data_Rule_Type data_)`
- `void set_rules (Rules< Array_Type, Data_Rule_Type > *rules_)`
- `void add_rule_dyn (Rule< Array_Type, Data_Rule_Dyn_Type > &rule)`
- `void add_rule_dyn (Rule_fun_type< Array_Type, Data_Rule_Dyn_Type > count_fun_, Data_Rule_Dyn_Type data_)`
- `void set_rules_dyn (Rules< Array_Type, Data_Rule_Dyn_Type > *rules_)`

#### Likelihood functions.

Calculation of likelihood functions is done reusing normalizing constants. Before recalculating the normalizing constant, the function checks whether *params* matches the last set vector of parameters used to compute it.

##### Parameters

<code>params</code>	Vector of parameters
<code>as_log</code>	When <code>true</code> , the function returns the log-likelihood.

- `double likelihood (const std::vector< double > &params, const uint &i, bool as_log=false)`
- `double likelihood (const std::vector< double > &params, const Array_Type &Array_, int i=-1, bool as_log=false)`
- `double likelihood (const std::vector< double > &params, const std::vector< double > &target_, const uint &i, bool as_log=false)`
- `double likelihood (const std::vector< double > &params, const double *target_, const uint &i, bool as_log=false)`
- `double likelihood_total (const std::vector< double > &params, bool as_log=false)`

#### Extract elements by index

##### Parameters

<code>i</code>	Index relative to the array in the model.
<code>params</code>	A new vector of model parameters to compute the normalizing constant.
<code>as_log</code>	When <code>true</code> returns the logged version of the normalizing constant.

- `double get_norm_const (const std::vector< double > &params, const uint &i, bool as_log=false)`

- `const std::vector< Array_Type > * get_pset (const uint &i)`
- `const std::vector< double > * get_pset_stats (const uint &i)`

### Size of the model

Number of different supports included in the model

This will return the size of `stats_target`.

#### Returns

`size ()` returns the number of arrays in the model.  
`size_unique ()` returns the number of unique arrays (according to the hasher) in the model.  
`nterms ()` returns the number of terms in the model.

- unsigned int `size ()` `const noexcept`
- unsigned int `size_unique ()` `const noexcept`
- unsigned int `nterms ()` `const noexcept`
- unsigned int `support_size ()` `const noexcept`
- `std::vector< std::string > colnames ()` `const`

- `std::vector< std::vector< double > > * get_stats_target ()`

Raw pointers to the support and target statistics.

- `std::vector< std::vector< double > > * get_stats_support ()`
- `std::vector< unsigned int > * get_arrays2support ()`
- `std::vector< std::vector< Array_Type > > * get_pset_arrays ()`
- `std::vector< std::vector< double > > * get_pset_stats ()`

Statistics of the support(s)

- `std::vector< std::vector< double > > * get_pset_probs ()`

- void `set_transform_model (std::function< std::vector< double >(double *, unsigned int)> fun, std::vector< std::string > names)`

Set the transform\_model\_fun object.

- `std::vector< double > transform_model (double *data, unsigned int k)`

## 7.28.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename
Data_Rule_Dyn_Type = bool>
class Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

$$\frac{\exp\left(\theta^t c(A)\right)}{\sum_{A' \in \mathcal{A}} \exp\left(\theta^t c(A')\right)}$$

This implementation aims to reduce the number of times that the support needs to be computed. Models included here use more than a single array, and thus allow the function to recycle support sets as needed. For example, if we are looking at directed graphs all of the same size and without vertex level features, i.e. a model that only counts edges, triangles, etc. then the support needs to be fully computed only once.

#### Template Parameters

<i>Array_Type</i>	Class of <a href="#">BArray</a> object.
<i>Data_Counter_Type</i>	Any type.
<i>Data_Rule_Type</i>	Any type.

Definition at line 44 of file model-bones.hpp.

## 7.28.2 Constructor & Destructor Documentation

### 7.28.2.1 Model() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model ( )
```

### 7.28.2.2 Model() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model (
    uint size_ )
```

### 7.28.2.3 Model() [3/3]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
    & Model_ )
```

### 7.28.2.4 ~Model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~Model ( ) [inline]
```

Definition at line 173 of file model-bones.hpp.

## 7.28.3 Member Function Documentation

### 7.28.3.1 add\_array()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_array (
    const Array_Type & Array_,
    bool force_new = false )
```

Adds an array to the support of not already included.

#### Parameters

<i>Array_</i>	array to be added
<i>force_new</i>	If false, it will use <i>keygen</i> to obtain a double vector and create a hash of it. If the hash has been computed earlier, the support is recycled.

#### Returns

The number of the array.

### 7.28.3.2 add\_counter() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter< Array_Type, Data_Counter_Type > & counter )
```

### 7.28.3.3 add\_counter() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Counter_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Counter_Type > init_fun_ = nullptr,
    Data_Counter_Type data_ = nullptr )
```



#### 7.28.3.4 add\_rule() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > & rule )
```

#### 7.28.3.5 add\_rule() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ )
```

#### 7.28.3.6 add\_rule\_dyn() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule< Array_Type, Data_Rule_Dyn_Type > & rule )
```

#### 7.28.3.7 add\_rule\_dyn() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule_fun_type< Array_Type, Data_Rule_Dyn_Type > count_fun_,
    Data_Rule_Dyn_Type data_ )
```

#### 7.28.3.8 colnames()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::string > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::colnames ( ) const
```

### 7.28.3.9 conditional\_prob()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::conditional↵
_prob (
    const Array_Type & Array_,
    const std::vector< double > & params,
    unsigned int i,
    unsigned int j )
```

Conditional probability ("Gibbs sampler")

Computes the conditional probability of observing  $P\{Y(i,j) = | Y^{\wedge}C, \theta\}$ , i.e., the probability of observing the entry  $Y(i,j)$  equal to one given the rest of the array.

#### Parameters

<i>Array_↵</i>	Array to check
<i>params</i>	Vector of parameters
<i>i</i>	Row entry
<i>j</i>	Column entry

#### Returns

double The conditional probability

### 7.28.3.10 gen\_key()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
Type >::gen_key (
    const Array_Type & Array_ )
```

### 7.28.3.11 get\_arrays2support()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< unsigned int >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::get_arrays2support ( )
```

### 7.28.3.12 get\_counters()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model<Array_Type, Data_Counter_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_counters ( )
```

### 7.28.3.13 get\_norm\_const()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_norm_const (
    const std::vector< double > & params,
    const uint & i,
    bool as_log = false )
```

### 7.28.3.14 get\_pset()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< Array_Type >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset (
    const uint & i )
```

### 7.28.3.15 get\_pset\_arrays()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< Array_Type > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_arrays ( )
```

### 7.28.3.16 get\_pset\_probs()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_probs ( )
```

**7.28.3.17 get\_pset\_stats() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_pset_stats ( )
```

Statistics of the support(s)

**7.28.3.18 get\_pset\_stats() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< double >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::get_pset_stats (
    const uint & i )
```

**7.28.3.19 get\_rengine()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::mt19937* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::get_rengine ( ) const
```

**7.28.3.20 get\_rules()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
_Rule_Dyn_Type >::get_rules ( )
```

**7.28.3.21 get\_rules\_dyn()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn ( )
```

### 7.28.3.22 get\_stats\_support()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_stats_support ( )
```

### 7.28.3.23 get\_stats\_target()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_stats_target ( )
```

Raw pointers to the support and target statistics.

The support of the model is stored as a vector of vector<double>. Each element of it contains the support for an specific type of array included. It represents an array of size  $(k + 1) \times n$  unique elements, with the data stored by-row. The last element of each entry corresponds to the weights, i.e., the frequency with which such sufficient statistics are observed in the support.

### 7.28.3.24 get\_support\_fun()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support<Array_Type,Data_Counter_Type,Data_Rule_Type,Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_support_fun ( )
```

### 7.28.3.25 likelihood() [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood (
    const std::vector< double > & params,
    const Array_Type & Array_,
    int i = -1,
    bool as_log = false )
```

### 7.28.3.26 likelihood() [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood (
    const std::vector< double > & params,
    const double * target_,
    const uint & i,
    bool as_log = false )
```

**7.28.3.27 likelihood() [3/4]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const std::vector< double > & target_,
    const uint & i,
    bool as_log = false )
```

**7.28.3.28 likelihood() [4/4]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const uint & i,
    bool as_log = false )
```

**7.28.3.29 likelihood\_total()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood↵
_total (
    const std::vector< double > & params,
    bool as_log = false )
```

**7.28.3.30 nterms()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >↵
::nterms ( ) const [noexcept]
```

**7.28.3.31 operator=()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model<Array_Type,Data_Counter_Type,Data_Rule_Type,Data_Rule_Dyn_Type>& Model< Array_Type,
Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::operator= (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
& Model_ )
```

### 7.28.3.32 print()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print ( )
const
```

Prints information about the model.

### 7.28.3.33 print\_stats()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print_stats (
    uint i ) const
```

### 7.28.3.34 sample() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample (
    const Array_Type & Array_,
    const std::vector< double > & params = {} )
```

### 7.28.3.35 sample() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample (
    const uint & i,
    const std::vector< double > & params )
```

### 7.28.3.36 set\_counters()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_counters (
    Counters< Array_Type, Data_Counter_Type > * counters_ )
```

**7.28.3.37 set\_keygen()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_keygen (
    std::function< std::vector< double >(const Array_Type &)> keygen_ )
```

**7.28.3.38 set\_engine()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_engine (
    std::mt19937 * rengine_,
    bool delete_ = false ) [inline]
```

Definition at line 143 of file model-bones.hpp.

**7.28.3.39 set\_rules()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ )
```

**7.28.3.40 set\_rules\_dyn()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules_dyn
(
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ )
```

**7.28.3.41 set\_seed()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_seed (
    unsigned int s ) [inline]
```

Definition at line 153 of file model-bones.hpp.



### 7.28.3.42 set\_transform\_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_transform_model (
    std::function< std::vector< double >(double *, unsigned int)> fun,
    std::vector< std::string > names )
```

Set the transform\_model\_fun object.

The transform\_model function is used to transform the data

#### Parameters

<i>data</i>	
<i>target</i>	
<i>n_arrays</i>	
<i>arrays2support</i>	

### 7.28.3.43 size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size (
    ) const [noexcept]
```

### 7.28.3.44 size\_unique()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size_unique (
    ) const [noexcept]
```

### 7.28.3.45 store\_psets()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::store_psets (
    ) [noexcept]
```

### 7.28.3.46 support\_size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::support_size ( ) const [noexcept]
```

### 7.28.3.47 transform\_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector<double> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::transform_model (
    double * data,
    unsigned int k )
```

The documentation for this class was generated from the following file:

- [include/barry/model-bones.hpp](#)

## 7.29 NetCounterData Class Reference

Data class used to store arbitrary uint or double vectors.

```
#include <network.hpp>
```

### Public Member Functions

- [NetCounterData](#) ()
- [NetCounterData](#) (const std::vector< uint > indices\_, const std::vector< double > numbers\_)
- [~NetCounterData](#) ()

### Public Attributes

- std::vector< uint > [indices](#)
- std::vector< double > [numbers](#)

### 7.29.1 Detailed Description

Data class used to store arbitrary uint or double vectors.

Definition at line 56 of file network.hpp.

## 7.29.2 Constructor & Destructor Documentation

### 7.29.2.1 NetCounterData() [1/2]

```
NetCounterData::NetCounterData ( ) [inline]
```

Definition at line 62 of file network.hpp.

### 7.29.2.2 NetCounterData() [2/2]

```
NetCounterData::NetCounterData (
    const std::vector< uint > indices_,
    const std::vector< double > numbers_ ) [inline]
```

Definition at line 63 of file network.hpp.

### 7.29.2.3 ~NetCounterData()

```
NetCounterData::~~NetCounterData ( ) [inline]
```

Definition at line 68 of file network.hpp.

## 7.29.3 Member Data Documentation

### 7.29.3.1 indices

```
std::vector< uint > NetCounterData::indices
```

Definition at line 59 of file network.hpp.

### 7.29.3.2 numbers

```
std::vector< double > NetCounterData::numbers
```

Definition at line 60 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

## 7.30 NetworkData Class Reference

Data class for Networks.

```
#include <network.hpp>
```

### Public Member Functions

- [NetworkData](#) ()
- [NetworkData](#) (std::vector< double > vertex\_attr\_, bool directed\_=true)  
*Constructor using a single attribute.*
- [NetworkData](#) (std::vector< std::vector< double > > vertex\_attr\_, bool directed\_=true)  
*Constructor using multiple attributes.*
- [~NetworkData](#) ()

### Public Attributes

- bool [directed](#) = true
- std::vector< std::vector< double > > [vertex\\_attr](#)

#### 7.30.1 Detailed Description

Data class for Networks.

Details on the available counters for [NetworkData](#) can be found in the [DEFMArray counters](#) section.

This holds information about whether the graph is directed or not, and, if defined, vectors of node (vertex) attributes ([vertex\\_attr](#)).

Definition at line 19 of file [network.hpp](#).

#### 7.30.2 Constructor & Destructor Documentation

##### 7.30.2.1 NetworkData() [1/3]

```
NetworkData::NetworkData ( ) [inline]
```

Definition at line 25 of file [network.hpp](#).

##### 7.30.2.2 NetworkData() [2/3]

```
NetworkData::NetworkData (
    std::vector< double > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using a single attribute.

## Parameters

<i>vertex_↔ attr_</i>	Double vector of length equal to the number of vertices in the data.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 33 of file network.hpp.

**7.30.2.3 NetworkData()** [3/3]

```
NetworkData::NetworkData (
    std::vector< std::vector< double > > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using multiple attributes.

## Parameters

<i>vertex_↔ attr_</i>	Vector of double vectors. The size equals to the number of attributes to be created. Each individual vector should be of length equal to the number of vertices.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 45 of file network.hpp.

**7.30.2.4 ~NetworkData()**

```
NetworkData::~NetworkData ( ) [inline]
```

Definition at line 51 of file network.hpp.

**7.30.3 Member Data Documentation****7.30.3.1 directed**

```
bool NetworkData::directed = true
```

Definition at line 22 of file network.hpp.

### 7.30.3.2 vertex\_attr

```
std::vector< std::vector< double > > NetworkData::vertex_attr
```

Definition at line 23 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

## 7.31 Node Class Reference

A single node for the model.

```
#include <geese-node-bones.hpp>
```

Collaboration diagram for Node:



### Public Member Functions

- [~Node](#) ()
- int [get\\_parent](#) () const
- unsigned int [noffspring](#) () const noexcept
- bool [is\\_leaf](#) () const noexcept

#### Construct a new Node object

- [Node](#) ()
- [Node](#) (unsigned int id\_, unsigned int ord\_, bool duplication\_)
- [Node](#) (unsigned int id\_, unsigned int ord\_, std::vector< unsigned int > annotations\_, bool duplication\_)
- [Node](#) ([Node](#) &&x) noexcept
- [Node](#) (const [Node](#) &x)

## Public Attributes

- unsigned int [id](#)  
*Id of the node (as specified in the input)*
- unsigned int [ord](#)  
*Order in which the node was created.*
- [phylocounters::PhyloArray](#) array
- std::vector< unsigned int > [annotations](#)  
*Observed annotations (only defined for [Geese](#))*
- bool [duplication](#)
- std::vector< [phylocounters::PhyloArray](#) > [arrays](#) = {}  
*Arrays given all possible states.*
- [Node](#) \* [parent](#) = nullptr  
*Parent node.*
- std::vector< [Node](#) \* > [offspring](#) = {}  
*Offspring nodes.*
- std::vector< unsigned int > [narray](#) = {}  
*ID of the array in the model.*
- bool [visited](#) = false
- std::vector< double > [subtree\\_prob](#)  
*Induced subtree probabilities.*
- std::vector< double > [probability](#)  
*The probability of observing each state.*

### 7.31.1 Detailed Description

A single node for the model.

Each node contains all the information to compute the conditional probability of the pruning algorithm at that node.

Definition at line 11 of file `geese-node-bones.hpp`.

### 7.31.2 Constructor & Destructor Documentation

#### 7.31.2.1 Node() [1/5]

```
Node::Node ( ) [inline]
```

Definition at line 36 of file `geese-node-bones.hpp`.

### 7.31.2.2 Node() [2/5]

```
Node::Node (
    unsigned int id_,
    unsigned int ord_,
    bool duplication_ ) [inline]
```

Definition at line 56 of file geese-node-bones.hpp.

### 7.31.2.3 Node() [3/5]

```
Node::Node (
    unsigned int id_,
    unsigned int ord_,
    std::vector< unsigned int > annotations_,
    bool duplication_ ) [inline]
```

Definition at line 62 of file geese-node-bones.hpp.

### 7.31.2.4 Node() [4/5]

```
Node::Node (
    Node && x ) [inline], [noexcept]
```

Definition at line 69 of file geese-node-bones.hpp.

### 7.31.2.5 Node() [5/5]

```
Node::Node (
    const Node & x ) [inline]
```

Definition at line 83 of file geese-node-bones.hpp.

### 7.31.2.6 ~Node()

```
Node::~~Node ( ) [inline]
```

Definition at line 47 of file geese-node-bones.hpp.

## 7.31.3 Member Function Documentation



### 7.31.3.1 get\_parent()

```
int Node::get_parent ( ) const [inline]
```

Definition at line 97 of file geese-node-bones.hpp.

### 7.31.3.2 is\_leaf()

```
bool Node::is_leaf ( ) const [inline], [noexcept]
```

Definition at line 109 of file geese-node-bones.hpp.

### 7.31.3.3 noffspring()

```
unsigned int Node::noffspring ( ) const [inline], [noexcept]
```

Definition at line 103 of file geese-node-bones.hpp.

## 7.31.4 Member Data Documentation

### 7.31.4.1 annotations

```
std::vector< unsigned int > Node::annotations
```

Observed annotations (only defined for [Geese](#))

Definition at line 18 of file geese-node-bones.hpp.

### 7.31.4.2 array

```
phylocounters::PhyloArray Node::array
```

Definition at line 17 of file geese-node-bones.hpp.

#### 7.31.4.3 arrays

```
std::vector< phylocounters::PhyloArray > Node::arrays = {}
```

Arrays given all possible states.

Definition at line 21 of file geese-node-bones.hpp.

#### 7.31.4.4 duplication

```
bool Node::duplication
```

Definition at line 19 of file geese-node-bones.hpp.

#### 7.31.4.5 id

```
unsigned int Node::id
```

Id of the node (as specified in the input)

Definition at line 14 of file geese-node-bones.hpp.

#### 7.31.4.6 narray

```
std::vector< unsigned int > Node::narray = {}
```

ID of the array in the model.

Definition at line 24 of file geese-node-bones.hpp.

#### 7.31.4.7 offspring

```
std::vector< Node\* > Node::offspring = {}
```

Offspring nodes.

Definition at line 23 of file geese-node-bones.hpp.

#### 7.31.4.8 ord

```
unsigned int Node::ord
```

Order in which the node was created.

Definition at line 15 of file geese-node-bones.hpp.

#### 7.31.4.9 parent

```
Node* Node::parent = nullptr
```

Parent node.

Definition at line 22 of file geese-node-bones.hpp.

#### 7.31.4.10 probability

```
std::vector< double > Node::probability
```

The probability of observing each state.

Definition at line 28 of file geese-node-bones.hpp.

#### 7.31.4.11 subtree\_prob

```
std::vector< double > Node::subtree_prob
```

Induced subtree probabilities.

Definition at line 27 of file geese-node-bones.hpp.

#### 7.31.4.12 visited

```
bool Node::visited = false
```

Definition at line 25 of file geese-node-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/models/geese/geese-node-bones.hpp](#)

## 7.32 NodeData Class Reference

Data definition for the `PhyloArray` class.

```
#include <phylo.hpp>
```

### Public Member Functions

- `NodeData` (`const` `std::vector< double >` &`blengths_`, `const` `std::vector< bool >` &`states_`, `bool` `duplication_` ← `_ = true`)

### Public Attributes

- `std::vector< double >` `blengths` = {}
- `std::vector< bool >` `states` = {}
- `bool` `duplication` = true

### 7.32.1 Detailed Description

Data definition for the `PhyloArray` class.

Details about the available counters for `PhyloArray` objects can be found in the [Phylo counters](#) section.

This holds basic information about a given node.

Definition at line 38 of file `phylo.hpp`.

### 7.32.2 Constructor & Destructor Documentation

#### 7.32.2.1 NodeData()

```
NodeData::NodeData (
    const std::vector< double > & blengths_,
    const std::vector< bool > & states_,
    bool duplication_ = true ) [inline]
```

Definition at line 58 of file `phylo.hpp`.

### 7.32.3 Member Data Documentation

### 7.32.3.1 blengths

```
std::vector< double > NodeData::blengths = {}
```

Branch length.

Definition at line 44 of file phylo.hpp.

### 7.32.3.2 duplication

```
bool NodeData::duplication = true
```

Definition at line 54 of file phylo.hpp.

### 7.32.3.3 states

```
std::vector< bool > NodeData::states = {}
```

State of the parent node.

Definition at line 49 of file phylo.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[phylo.hpp](#)

## 7.33 PhyloCounterData Class Reference

```
#include <phylo.hpp>
```

### Public Member Functions

- [PhyloCounterData](#) (std::vector< [uint](#) > [data\\_](#), std::vector< double > \*[counters\\_](#)=nullptr)
- [PhyloCounterData](#) ()
- [uint](#) at ([uint](#) d)
- [uint](#) operator() ([uint](#) d)
- [uint](#) operator[] ([uint](#) d)
- void [reserve](#) ([uint](#) x)
- void [push\\_back](#) ([uint](#) x)
- void [shrink\\_to\\_fit](#) ()
- [uint](#) size ()
- std::vector< [uint](#) >::iterator [begin](#) ()
- std::vector< [uint](#) >::iterator [end](#) ()
- bool [empty](#) ()
- std::vector< double > \* [get\\_counters](#) ()

### 7.33.1 Detailed Description

Definition at line 69 of file phylo.hpp.

### 7.33.2 Constructor & Destructor Documentation

#### 7.33.2.1 PhyloCounterData() [1/2]

```
PhyloCounterData::PhyloCounterData (
    std::vector< uint > data_,
    std::vector< double > * counters_ = nullptr ) [inline]
```

Definition at line 75 of file phylo.hpp.

#### 7.33.2.2 PhyloCounterData() [2/2]

```
PhyloCounterData::PhyloCounterData ( ) [inline]
```

Definition at line 80 of file phylo.hpp.

### 7.33.3 Member Function Documentation

#### 7.33.3.1 at()

```
uint PhyloCounterData::at (
    uint d ) [inline]
```

Definition at line 82 of file phylo.hpp.

#### 7.33.3.2 begin()

```
std::vector< uint >::iterator PhyloCounterData::begin ( ) [inline]
```

Definition at line 90 of file phylo.hpp.

### 7.33.3.3 empty()

```
bool PhyloCounterData::empty ( ) [inline]
```

Definition at line 93 of file phylo.hpp.

### 7.33.3.4 end()

```
std::vector< uint >::iterator PhyloCounterData::end ( ) [inline]
```

Definition at line 91 of file phylo.hpp.

### 7.33.3.5 get\_counters()

```
std::vector< double >* PhyloCounterData::get_counters ( ) [inline]
```

Definition at line 94 of file phylo.hpp.

### 7.33.3.6 operator()()

```
uint PhyloCounterData::operator() (
    uint d ) [inline]
```

Definition at line 83 of file phylo.hpp.

### 7.33.3.7 operator[]()

```
uint PhyloCounterData::operator[] (
    uint d ) [inline]
```

Definition at line 84 of file phylo.hpp.

### 7.33.3.8 push\_back()

```
void PhyloCounterData::push_back (
    uint x ) [inline]
```

Definition at line 86 of file phylo.hpp.

### 7.33.3.9 reserve()

```
void PhyloCounterData::reserve (
    uint x ) [inline]
```

Definition at line 85 of file phylo.hpp.

### 7.33.3.10 shrink\_to\_fit()

```
void PhyloCounterData::shrink_to_fit ( ) [inline]
```

Definition at line 87 of file phylo.hpp.

### 7.33.3.11 size()

```
uint PhyloCounterData::size ( ) [inline]
```

Definition at line 88 of file phylo.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[phylo.hpp](#)

## 7.34 PhyloRuleDynData Class Reference

```
#include <phylo.hpp>
```

### Public Member Functions

- [PhyloRuleDynData](#) ([const](#) std::vector< double > \*counts\_, [uint](#) pos\_, [uint](#) lb\_, [uint](#) ub\_, [uint](#) duplication\_)
- [~PhyloRuleDynData](#) ()

### Public Attributes

- [const](#) std::vector< double > \* [counts](#)
- [uint](#) [pos](#)
- [uint](#) [lb](#)
- [uint](#) [ub](#)
- [uint](#) [duplication](#)

### 7.34.1 Detailed Description

Definition at line 2147 of file phylo.hpp.



## 7.34.2 Constructor & Destructor Documentation

### 7.34.2.1 PhyloRuleDynData()

```
PhyloRuleDynData::PhyloRuleDynData (
    const std::vector< double > * counts_,
    uint pos_,
    uint lb_,
    uint ub_,
    uint duplication_ ) [inline]
```

Definition at line 2155 of file phylo.hpp.

### 7.34.2.2 ~PhyloRuleDynData()

```
PhyloRuleDynData::~PhyloRuleDynData ( ) [inline]
```

Definition at line 2164 of file phylo.hpp.

## 7.34.3 Member Data Documentation

### 7.34.3.1 counts

```
const std::vector< double >* PhyloRuleDynData::counts
```

Definition at line 2149 of file phylo.hpp.

### 7.34.3.2 duplication

```
uint PhyloRuleDynData::duplication
```

Definition at line 2153 of file phylo.hpp.

### 7.34.3.3 lb

```
uint PhyloRuleDynData::lb
```

Definition at line 2151 of file phylo.hpp.

#### 7.34.3.4 pos

```
uint PhyloRuleDynData::pos
```

Definition at line 2150 of file phylo.hpp.

#### 7.34.3.5 ub

```
uint PhyloRuleDynData::ub
```

Definition at line 2152 of file phylo.hpp.

The documentation for this class was generated from the following file:


- include/barry/counters/[phylo.hpp](#)

### 7.35 PowerSet< Array\_Type, Data\_Rule\_Type > Class Template Reference

Powerset of a binary array.

```
#include <powerset-bones.hpp>
```

Collaboration diagram for PowerSet< Array\_Type, Data\_Rule\_Type >:



## Public Member Functions

- void [init\\_support](#) ()
- void [calc](#) ()
- void [reset](#) (uint N\_, uint M\_)

### Construct and destroy a PowerSet object

- [PowerSet](#) ()
- [PowerSet](#) (uint N\_, uint M\_)
- [PowerSet](#) (const Array\_Type &array)
- [~PowerSet](#) ()

### Wrappers for the `<tt>Rules</tt>` member.

*These will add rules to the model, which are shared by the support and the actual counter function.*

- void [add\\_rule](#) (Rule< Array\_Type, Data\_Rule\_Type > rule)
- void [add\\_rule](#) (Rule\_fun\_type< Array\_Type, Data\_Rule\_Type > count\_fun\_, Data\_Rule\_Type data\_)

### Getter functions

- const std::vector< Array\_Type > \* [get\\_data\\_ptr](#) () const
- std::vector< Array\_Type > [get\\_data](#) () const
- std::vector< Array\_Type >::iterator [begin](#) ()
- std::vector< Array\_Type >::iterator [end](#) ()
- std::size\_t [size](#) () const noexcept
- const Array\_Type & [operator\[\]](#) (const unsigned int &i) const

## Public Attributes

- Array\_Type [EmptyArray](#)
- std::vector< Array\_Type > [data](#)
- Rules< Array\_Type, Data\_Rule\_Type > \* [rules](#)
- uint [N](#)
- uint [M](#)
- bool [rules\\_deleted](#) = false
- std::vector< size\_t > [coordinates\\_free](#)
- std::vector< size\_t > [coordinates\\_locked](#)
- size\_t [n\\_free](#)
- size\_t [n\\_locked](#)

### 7.35.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
class PowerSet< Array_Type, Data_Rule_Type >
```

Powerset of a binary array.

#### Template Parameters

<i>Array_Type</i>	
<i>Data_Rule_Type</i>	

Definition at line 11 of file powerset-bones.hpp.

## 7.35.2 Constructor & Destructor Documentation

### 7.35.2.1 PowerSet() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet ( ) [inline]
```

Definition at line 36 of file powerset-bones.hpp.

### 7.35.2.2 PowerSet() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    uint N_,
    uint M_ ) [inline]
```

Definition at line 38 of file powerset-bones.hpp.

### 7.35.2.3 PowerSet() [3/3]

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    const Array_Type & array ) [inline]
```

Definition at line 5 of file powerset-meat.hpp.

### 7.35.2.4 ~PowerSet()

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::~~PowerSet [inline]
```

Definition at line 13 of file powerset-meat.hpp.

## 7.35.3 Member Function Documentation

### 7.35.3.1 add\_rule() [1/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > rule ) [inline]
```

Definition at line 173 of file powerset-meat.hpp.

### 7.35.3.2 add\_rule() [2/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ ) [inline]
```

Definition at line 182 of file powerset-meat.hpp.

### 7.35.3.3 begin()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::begin ( ) [inline]
```

Definition at line 68 of file powerset-bones.hpp.

### 7.35.3.4 calc()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::calc [inline]
```

Definition at line 144 of file powerset-meat.hpp.

### 7.35.3.5 end()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::end ( ) [inline]
```

Definition at line 69 of file powerset-bones.hpp.

### 7.35.3.6 get\_data()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::get_data ( ) const [inline]
```

Definition at line 67 of file powerset-bones.hpp.

### 7.35.3.7 get\_data\_ptr()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const std::vector< Array_Type >* PowerSet< Array_Type, Data_Rule_Type >::get_data_ptr ( )
const [inline]
```

Definition at line 66 of file powerset-bones.hpp.

### 7.35.3.8 init\_support()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::init_support [inline]
```

Definition at line 19 of file powerset-meat.hpp.

### 7.35.3.9 operator[]()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const Array_Type& PowerSet< Array_Type, Data_Rule_Type >::operator[] (
    const unsigned int & i ) const [inline]
```

Definition at line 71 of file powerset-bones.hpp.

### 7.35.3.10 reset()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::reset (
    uint N_,
    uint M_ ) [inline]
```

Definition at line 160 of file powerset-meat.hpp.

### 7.35.3.11 size()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::size_t PowerSet< Array_Type, Data_Rule_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 70 of file powerset-bones.hpp.

## 7.35.4 Member Data Documentation

### 7.35.4.1 coordinates\_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_free
```

Definition at line 26 of file powerset-bones.hpp.

### 7.35.4.2 coordinates\_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_locked
```

Definition at line 27 of file powerset-bones.hpp.

### 7.35.4.3 data

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::data
```

Definition at line 19 of file powerset-bones.hpp.

### 7.35.4.4 EmptyArray

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Array_Type PowerSet< Array_Type, Data_Rule_Type >::EmptyArray
```

Definition at line 18 of file powerset-bones.hpp.

#### 7.35.4.5 M

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
uint PowerSet< Array_Type, Data_Rule_Type >::M
```

Definition at line 22 of file powerset-bones.hpp.

#### 7.35.4.6 N

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
uint PowerSet< Array_Type, Data_Rule_Type >::N
```

Definition at line 22 of file powerset-bones.hpp.

#### 7.35.4.7 n\_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_free
```

Definition at line 28 of file powerset-bones.hpp.

#### 7.35.4.8 n\_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_locked
```

Definition at line 29 of file powerset-bones.hpp.

#### 7.35.4.9 rules

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Rules<Array_Type,Data_Rule_Type>* PowerSet< Array_Type, Data_Rule_Type >::rules
```

Definition at line 20 of file powerset-bones.hpp.



#### 7.35.4.10 rules\_deleted

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
bool PowerSet< Array_Type, Data_Rule_Type >::rules_deleted = false
```

Definition at line 23 of file powerset-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/powerset-bones.hpp
- include/barry/powerset-meat.hpp

## 7.36 Progress Class Reference

A simple progress bar.

```
#include <progress.hpp>
```

### Public Member Functions

- [Progress](#) (int n\_, int width\_)
- [~Progress](#) ()
- void [next](#) ()
- void [end](#) ()

#### 7.36.1 Detailed Description

A simple progress bar.

Definition at line 11 of file progress.hpp.

#### 7.36.2 Constructor & Destructor Documentation

##### 7.36.2.1 Progress()

```
Progress::Progress (
    int n_,
    int width_ ) [inline]
```

Definition at line 30 of file progress.hpp.

### 7.36.2.2 ~Progress()

```
Progress::~~Progress ( ) [inline]
```

Definition at line 23 of file progress.hpp.

## 7.36.3 Member Function Documentation

### 7.36.3.1 end()

```
void Progress::end ( ) [inline]
```

Definition at line 52 of file progress.hpp.

### 7.36.3.2 next()

```
void Progress::next ( ) [inline]
```

Definition at line 41 of file progress.hpp.

The documentation for this class was generated from the following file:

- [include/barry/progress.hpp](#)

## 7.37 Rule< Array\_Type, Data\_Type > Class Template Reference

[Rule](#) for determining if a cell should be included in a sequence.

```
#include <rules-bones.hpp>
```

### Public Member Functions

- [~Rule](#) ()
- Data\_Type & [D](#) ()  
*Read/Write access to the data.*
- bool [operator\(\)](#) (const Array\_Type &a, [uint i](#), [uint j](#))

#### Construct a new Rule object

Construct a new [Rule](#) object

*Parameters*

<code>fun_</code>	<i>A function of type <code>Rule_fun_type</code>.</i>
<code>dat_</code>	<i>Data pointer to be passed to <code>fun_</code></i>
<code>delete_↔ dat_</code>	<i>When <code>true</code>, the <a href="#">Rule</a> destructor will delete the pointer, if defined.</i>

- [Rule](#) ()
- [Rule](#) ([Rule\\_fun\\_type](#)< Array\_Type, Data\_Type > fun\_, Data\_Type dat\_)

**7.37.1 Detailed Description**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Rule< Array_Type, Data_Type >
```

[Rule](#) for determining if a cell should be included in a sequence.

[Rules](#) can be used together with [Support](#) and [PowerSet](#) to determine which cells should be included when enumerating all possible realizations of a binary array.

*Template Parameters*

<i>Array_Type</i>	An object of class <a href="#">BArray</a> .
<i>Data_Type</i>	Any type.

Definition at line 20 of file `rules-bones.hpp`.

**7.37.2 Constructor & Destructor Documentation****7.37.2.1 Rule() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule ( ) [inline]
```

Definition at line 38 of file `rules-bones.hpp`.

**7.37.2.2 Rule() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule (
    Rule\_fun\_type< Array_Type, Data_Type > fun_,
    Data_Type dat_ ) [inline]
```

Definition at line 39 of file `rules-bones.hpp`.

### 7.37.2.3 ~Rule()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::~~Rule ( ) [inline]
```

Definition at line 45 of file rules-bones.hpp.

## 7.37.3 Member Function Documentation

### 7.37.3.1 D()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Data_Type& Rule< Array_Type, Data_Type >::D ( )
```

Read/Write access to the data.

### 7.37.3.2 operator()()

```
template<typename Array_Type , typename Data_Type >
bool Rule< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    uint i,
    uint j ) [inline]
```

Definition at line 37 of file rules-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/rules-bones.hpp
- include/barry/rules-meat.hpp

## 7.38 Rules< Array\_Type, Data\_Type > Class Template Reference

Vector of objects of class [Rule](#).

```
#include <rules-bones.hpp>
```

### Public Member Functions

- [Rules](#) ()
- [Rules](#) (const [Rules](#)< Array\_Type, Data\_Type > &rules\_)
- [Rules](#)< Array\_Type, Data\_Type > [operator=](#) (const [Rules](#)< Array\_Type, Data\_Type > &rules\_)
- [~Rules](#) ()
- [uint size](#) () const noexcept
- bool [operator\(\)](#) (const Array\_Type &a, uint i, uint j)  
*Check whether a given cell is free or locked.*
- void [get\\_seq](#) (const Array\_Type &a, std::vector< size\_t > \*free, std::vector< size\_t > \*locked=nullptr)  
*Computes the sequence of free and locked cells in an [BArray](#).*

### Rule adding

*Parameters*

rule	
------	--

- void [add\\_rule](#) ([Rule](#)< Array\_Type, Data\_Type > rule)
- void [add\\_rule](#) ([Rule\\_fun\\_type](#)< Array\_Type, Data\_Type > rule\_, Data\_Type [data\\_](#))

**7.38.1 Detailed Description**

```
template<typename Array_Type, typename Data_Type>
class Rules< Array_Type, Data_Type >
```

Vector of objects of class [Rule](#).

*Template Parameters*

<i>Array_Type</i>	An object of class <a href="#">BArray</a>
<i>Data_Type</i>	Any type.

Definition at line 60 of file rules-bones.hpp.

**7.38.2 Constructor & Destructor Documentation****7.38.2.1 Rules() [1/2]**

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules ( ) [inline]
```

Definition at line 66 of file rules-bones.hpp.

**7.38.2.2 Rules() [2/2]**

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules (
    const Rules< Array_Type, Data_Type > & rules_ ) [inline]
```

Definition at line 5 of file rules-meat.hpp.

### 7.38.2.3 ~Rules()

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::~~Rules ( ) [inline]
```

Definition at line 71 of file rules-bones.hpp.

## 7.38.3 Member Function Documentation

### 7.38.3.1 add\_rule() [1/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule< Array_Type, Data_Type > rule ) [inline]
```

Definition at line 42 of file rules-meat.hpp.

### 7.38.3.2 add\_rule() [2/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Type > rule_,
    Data_Type data_ ) [inline]
```

Definition at line 52 of file rules-meat.hpp.

### 7.38.3.3 get\_seq()

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::get_seq (
    const Array_Type & a,
    std::vector< size_t > * free,
    std::vector< size_t > * locked = nullptr ) [inline]
```

Computes the sequence of free and locked cells in an [BArray](#).

#### Parameters

<i>a</i>	An object of class <a href="#">BArray</a> .
<i>free</i>	Pointer to a vector of pairs (i, j) listing the free cells.
<i>locked</i>	(optional) Pointer to a vector of pairs (i, j) listing the locked cells.

**Returns**

Nothing.

Definition at line 83 of file rules-meat.hpp.

**7.38.3.4 operator()**

```
template<typename Array_Type , typename Data_Type >
bool Rules< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    uint i,
    uint j ) [inline]
```

Check whether a given cell is free or locked.

**Parameters**

<i>a</i>	A <a href="#">BArray</a> object
<i>i</i>	row position
<i>j</i>	col position

**Returns**

true If the cell is locked  
false If the cell is free

Definition at line 67 of file rules-meat.hpp.

**7.38.3.5 operator=()**

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type > Rules< Array_Type, Data_Type >::operator= (
    const Rules< Array_Type, Data_Type > & rules_ )
```

Definition at line 19 of file rules-meat.hpp.

**7.38.3.6 size()**

```
template<typename Array_Type , typename Data_Type >
uint Rules< Array_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 73 of file rules-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/[rules-bones.hpp](#)
- include/barry/[rules-meat.hpp](#)

## 7.39 StatsCounter< Array\_Type, Data\_Type > Class Template Reference

Count stats for a single Array.

```
#include <statscounter-bones.hpp>
```

### Public Member Functions

- [StatsCounter](#) ([const](#) Array\_Type \*[Array\\_](#))  
*Creator of a [StatsCounter](#)*
- [StatsCounter](#) ([const](#) [StatsCounter](#)< Array\_Type, Data\_Type > &[counter](#))  
*Copy constructor.*
- [StatsCounter](#) ()  
*Can be created without setting the array.*
- [~StatsCounter](#) ()
- void [reset\\_array](#) ([const](#) Array\_Type \*[Array\\_](#))  
*Changes the reference array for the counting.*
- void [add\\_counter](#) ([Counter](#)< Array\_Type, Data\_Type > [f\\_](#))
- void [set\\_counters](#) ([Counters](#)< Array\_Type, Data\_Type > \*[counters\\_](#))
- void [count\\_init](#) (uint i, uint j)  
*[Counter](#) functions This function recurses through the entries of *Array* and at each step of adding a new cell it uses the functions to list the statistics.*
- void [count\\_current](#) (uint i, uint j)
- std::vector< double > [count\\_all](#) ()
- [Counters](#)< Array\_Type, Data\_Type > \* [get\\_counters](#) ()
- std::vector< std::string > [get\\_names](#) () [const](#)
- std::vector< std::string > [get\\_descriptions](#) () [const](#)
- size\_t [size](#) () [const](#)

### 7.39.1 Detailed Description

```
template<typename Array_Type, typename Data_Type>
class StatsCounter< Array_Type, Data_Type >
```

Count stats for a single Array.

Users can a list of functions that can be used with this. The baseline set of arguments is a pointer to a binary array and a dataset to add the counts to.

Definition at line 14 of file statscounter-bones.hpp.

### 7.39.2 Constructor & Destructor Documentation

#### 7.39.2.1 StatsCounter() [1/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const Array_Type * Array\_ ) [inline]
```

Creator of a [StatsCounter](#)



## Parameters

<i>Array</i> ↔	A const pointer to a <a href="#">BArray</a> .
—	

Definition at line 37 of file statscounter-bones.hpp.

## 7.39.2.2 StatsCounter() [2/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const StatsCounter< Array_Type, Data_Type > & counter )
```

Copy constructor.

## Parameters

<i>counter</i>	
----------------	--

## 7.39.2.3 StatsCounter() [3/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter ( ) [inline]
```

Can be created without setting the array.

Definition at line 59 of file statscounter-bones.hpp.

## 7.39.2.4 ~StatsCounter()

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::~StatsCounter ( )
```

## 7.39.3 Member Function Documentation

## 7.39.3.1 add\_counter()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > f_ )
```

**7.39.3.2 count\_all()**

```
template<typename Array_Type , typename Data_Type >
std::vector< double > StatsCounter< Array_Type, Data_Type >::count_all [inline]
```

Definition at line 99 of file statscounter-meat.hpp.

**7.39.3.3 count\_current()**

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_current (
    uint i,
    uint j )
```

**7.39.3.4 count\_init()**

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_init (
    uint i,
    uint j )
```

**Counter** functions This function recurses through the entries of `Array` and at each step of adding a new cell it uses the functions to list the statistics.

**7.39.3.5 get\_counters()**

```
template<typename Array_Type , typename Data_Type >
Counters<Array_Type,Data_Type>* StatsCounter< Array_Type, Data_Type >::get_counters ( )
```

**7.39.3.6 get\_descriptions()**

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_descriptions ( ) const
```

**7.39.3.7 get\_names()**

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_names ( ) const
```

**7.39.3.8 reset\_array()**

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::reset_array (
    const Array_Type * Array_ )
```

Changes the reference array for the counting.

#### Parameters

<i>Array_</i> _	A pointer to an array of class <code>Array_Type</code> .
--------------------	--

#### 7.39.3.9 set\_counters()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::set_counters (
    Counters< Array_Type, Data_Type > * counters_ )
```

#### 7.39.3.10 size()

```
template<typename Array_Type , typename Data_Type >
size_t StatsCounter< Array_Type, Data_Type >::size ( ) const [inline]
```

Definition at line 86 of file statscounter-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/statscounter-bones.hpp
- include/barry/statscounter-meat.hpp

## 7.40 Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > Class Template Reference

Compute the support of sufficient statistics.

```
#include <support-bones.hpp>
```

### Public Member Functions

- [Support](#) (const Array\_Type &Array\_)  
*Constructor passing a reference Array.*
- [Support](#) (uint N\_, uint M\_)  
*Constructor specifying the dimensions of the array (empty).*
- [Support](#) ()
- [~Support](#) ()
- void [init\\_support](#) (std::vector< Array\_Type > \*array\_bank=nullptr, std::vector< double > \*stats\_bank=nullptr)
- void [calc](#) (std::vector< Array\_Type > \*array\_bank=nullptr, std::vector< double > \*stats\_bank=nullptr, unsigned int max\_num\_elements\_=0u)  
*Computes the entire support.*
- std::vector< double > [get\\_counts](#) () const

- `std::vector< double > * get\_current\_stats ()`  
*List current statistics.*
- `void print () const`
- `const FreqTable< double > & get\_data () const`
- `Counters< Array_Type, Data_Counter_Type > * get\_counters ()`  
*Vector of counter functions.*
- `Rules< Array_Type, Data_Rule_Type > * get\_rules ()`  
*Vector of static rules (cells to iterate).*
- `Rules< Array_Type, Data_Rule_Dyn_Type > * get\_rules\_dyn ()`  
*Vector of dynamic rules (to include/exclude a realization).*

### Resets the support calculator

*If needed, the counters of a support object can be reused.*

#### Parameters

<code>Array↔</code>	<i>New array over which the support will be computed.</i>
<code>—</code>	

- `void reset\_array ()`
- `void reset\_array (const Array_Type &Array\_)`

### Manage counters

#### Parameters

<code>f_</code>	<i>A counter to be added.</i>
<code>counters↔</code>	<i>A vector of counters to be added.</i>
<code>—</code>	

- `void add\_counter (Counter< Array_Type, Data_Counter_Type > f\_)`
- `void set\_counters (Counters< Array_Type, Data_Counter_Type > *counters\_)`

### Manage rules

#### Parameters

<code>f_</code>	<i>A rule to be added.</i>
<code>counters↔</code>	<i>A vector of rules to be added.</i>
<code>—</code>	

- `void add\_rule (Rule< Array_Type, Data_Rule_Type > *f\_)`
- `void add\_rule (Rule< Array_Type, Data_Rule_Type > f\_)`
- `void set\_rules (Rules< Array_Type, Data_Rule_Type > *rules\_)`
- `void add\_rule\_dyn (Rule< Array_Type, Data_Rule_Dyn_Type > *f\_)`
- `void add\_rule\_dyn (Rule< Array_Type, Data_Rule_Dyn_Type > f\_)`
- `void set\_rules\_dyn (Rules< Array_Type, Data_Rule_Dyn_Type > *rules\_)`
- `bool eval\_rules\_dyn (const std::vector< double > &counts, const uint &i, const uint &j)`

### Public Attributes

- `uint N`

- `uint M`
- `bool delete_counters = true`
- `bool delete_rules = true`
- `bool delete_rules_dyn = true`
- `uint max_num_elements = BARRY_MAX_NUM_ELEMENTS`
- `std::vector< double > current_stats`
- `std::vector< size_t > coordinates_free`
- `std::vector< size_t > coordinates_locked`
- `size_t coordiantes_n_free`
- `size_t coordiantes_n_locked`
- `std::vector< double > change_stats`
- `std::vector< size_t > hashes`
- `std::vector< bool > hashes_initialized`
- `size_t n_counters`

### 7.40.1 Detailed Description

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool,
typename Data_Rule_Dyn_Type = bool>
class Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

Compute the support of sufficient statistics.

Given an array and a set of counters, this object iterates throughout the support set of the Array while at the same time computing the support of the sufficient statitics.

The members `rule` and `rule_dyn` allow constraining the support. The first will establish which cells of the array will be used to iterate, for example, in the case of social networks, self-loops are not allowed, so the entire diagonal would be fixed to zero, reducing the size of the support.

In the case of `rule_dyn`, the function will stablish dynamically whether the current state will be included in the counts or not. For example, this set of rules can be used to constrain the support to networks that have a prescribed degree sequence.

Definition at line 42 of file support-bones.hpp.

### 7.40.2 Constructor & Destructor Documentation

#### 7.40.2.1 Support() [1/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    const Array_Type & Array_ ) [inline]
```

Constructor passing a reference Array.

Definition at line 87 of file support-bones.hpp.

**7.40.2.2 Support()** [2/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    uint N_,
    uint M_ ) [inline]
```

Constructor specifying the dimensions of the array (empty).

Definition at line 96 of file support-bones.hpp.

**7.40.2.3 Support()** [3/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support ( )
[inline]
```

Definition at line 103 of file support-bones.hpp.

**7.40.2.4 ~Support()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~Support ( )
[inline]
```

Definition at line 110 of file support-bones.hpp.

**7.40.3 Member Function Documentation****7.40.3.1 add\_counter()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter
(
    Counter< Array_Type, Data_Counter_Type > f_ )
```

### 7.40.3.2 add\_rule() [1/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > * f_ )
```

### 7.40.3.3 add\_rule() [2/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > f_ )
```

### 7.40.3.4 add\_rule\_dyn() [1/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > * f_ )
```

### 7.40.3.5 add\_rule\_dyn() [2/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > f_ )
```

### 7.40.3.6 calc()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::calc (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr,
    unsigned int max_num_elements_ = 0u )
```

Computes the entire support.

Not to be used by the user. Sets the starting point in the array (column-major).

## Parameters

<i>array_bank</i>	If specified, the counter will add to the vector each possible state of the array, as it counts.
<i>stats_bank</i>	If specified, the counter will add to the vector each possible set of statistics, as it counts.

**7.40.3.7 eval\_rules\_dyn()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::eval_↵
rules_dyn (
    const std::vector< double > & counts,
    const uint & i,
    const uint & j )
```

**7.40.3.8 get\_counters()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Counters<Array_Type,Data_Counter_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_↵
Type, Data_Rule_Dyn_Type >::get_counters ( )
```

Vector of counter functions.

**7.40.3.9 get\_counts()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::get_counts ( ) const
```

**7.40.3.10 get\_current\_stats()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double >* Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_↵
Dyn_Type >::get_current_stats ( )
```

List current statistics.



### 7.40.3.11 get\_data()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const FreqTable< double >& Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::get_data ( ) const
```

### 7.40.3.12 get\_rules()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules ( )
```

Vector of static rules (cells to iterate).

### 7.40.3.13 get\_rules\_dyn()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Dyn_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn ( )
```

Vector of dynamic rules (to include/exclude a realization).

### 7.40.3.14 init\_support()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::init_↵
support (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr )
```

### 7.40.3.15 print()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print ( )
const
```

**7.40.3.16 reset\_array() [1/2]**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
( )
```

**7.40.3.17 reset\_array() [2/2]**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
(
    const Array_Type & Array_ )
```

**7.40.3.18 set\_counters()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_↵
counters (
    Counters< Array_Type, Data_Counter_Type > * counters_ )
```

**7.40.3.19 set\_rules()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ )
```

**7.40.3.20 set\_rules\_dyn()**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules↵
_dyn (
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ )
```

**7.40.4 Member Data Documentation**

#### 7.40.4.1 change\_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::change_stats
```

Definition at line 80 of file support-bones.hpp.

#### 7.40.4.2 coordiantes\_n\_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes↵
_n_free
```

Definition at line 78 of file support-bones.hpp.

#### 7.40.4.3 coordiantes\_n\_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes↵
_n_locked
```

Definition at line 79 of file support-bones.hpp.

#### 7.40.4.4 coordinates\_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::coordinates_free
```

Definition at line 76 of file support-bones.hpp.

#### 7.40.4.5 coordinates\_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::coordinates_locked
```

Definition at line 77 of file support-bones.hpp.

#### 7.40.4.6 current\_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::current_stats
```

Definition at line 75 of file support-bones.hpp.

#### 7.40.4.7 delete\_counters

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
counters = true
```

Definition at line 69 of file support-bones.hpp.

#### 7.40.4.8 delete\_rules

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
rules = true
```

Definition at line 70 of file support-bones.hpp.

#### 7.40.4.9 delete\_rules\_dyn

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
rules_dyn = true
```

Definition at line 71 of file support-bones.hpp.

#### 7.40.4.10 hashes

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::hashes
```

Definition at line 81 of file support-bones.hpp.

#### 7.40.4.11 hashes\_initialized

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< bool > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::hashes_initialized
```

Definition at line 82 of file support-bones.hpp.

#### 7.40.4.12 M

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::M
```

Definition at line 68 of file support-bones.hpp.

#### 7.40.4.13 max\_num\_elements

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::max_num_elements = BARRY_MAX_NUM_ELEMENTS
```

Definition at line 72 of file support-bones.hpp.

#### 7.40.4.14 N

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::N
```

Definition at line 68 of file support-bones.hpp.

#### 7.40.4.15 n\_counters

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::n_counters
```

Definition at line 83 of file support-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/support-bones.hpp](#)

## 7.41 vecHasher< T > Struct Template Reference

```
#include <typedefs.hpp>
```

### Public Member Functions

- `std::size_t operator()` (`std::vector< T > const &dat`) `const noexcept`

#### 7.41.1 Detailed Description

```
template<typename T>  
struct vecHasher< T >
```

Definition at line 106 of file typedefs.hpp.

#### 7.41.2 Member Function Documentation

##### 7.41.2.1 operator()

```
template<typename T >  
std::size_t vecHasher< T >::operator() (  
    std::vector< T > const & dat ) const [inline], [noexcept]
```

Definition at line 109 of file typedefs.hpp.

The documentation for this struct was generated from the following file:


- `include/barry/typedefs.hpp`

## Chapter 8

# File Documentation

### 8.1 `include/barry/barray-bones.hpp` File Reference

This graph shows which files directly or indirectly include this file:



#### Classes

- class `BArray< Cell_Type, Data_Type >`  
*Baseline class for binary arrays.*

### 8.2 `include/barry/barray-iterator.hpp` File Reference

#### Classes

- class `ConstBArrayRowIter< Cell_Type, Data_Type >`

## 8.3 include/barry/barray-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define BARRAY_TYPE() BArray<Cell_Type, Data_Type>`
- `#define BARRAY_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BARRAY_TEMPLATE(a, b) template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`

### Functions

- `template BARRAY_TEMPLATE_ARGS () inline void checkdim_(const BARRAY_TYPE() &lhs`
- `template const BARRAY_TYPE () &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+=)(const BArray< Cell_Type`
- `for (uint i=0u;i< nrow();++i) for(uint j=0u = el[POS(i, j)]`
- `j< ncol();++j) this-> operator() (i, j)+`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+=)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-=(const BArray< Cell_Type`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-=(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator*=(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator/=(const Cell_Type &rhs)`

### Variables

- `Data_Type & rhs`
- `return * this`

#### 8.3.1 Macro Definition Documentation



### 8.3.1.1 BARRAY\_TEMPLATE

```
#define BARRAY_TEMPLATE(  
    a,  
    b )  template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b
```

Definition at line 11 of file barray-meat-operators.hpp.

### 8.3.1.2 BARRAY\_TEMPLATE\_ARGS

```
template BARRAY_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file barray-meat-operators.hpp.

### 8.3.1.3 BARRAY\_TYPE

```
template Data_Type BARRAY_TYPE( ) BArray<Cell_Type, Data_Type>
```

Definition at line 7 of file barray-meat-operators.hpp.

### 8.3.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 15 of file barray-meat-operators.hpp.

### 8.3.1.5 ROW

```
#define ROW(  
    a )  this->el_ij[a]
```

Definition at line 14 of file barray-meat-operators.hpp.

## 8.3.2 Function Documentation

### 8.3.2.1 BARRAY\_TEMPLATE() [1/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator* ) const &
```

Definition at line 88 of file barray-meat-operators.hpp.

### 8.3.2.2 BARRAY\_TEMPLATE() [2/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const
```

### 8.3.2.3 BARRAY\_TEMPLATE() [3/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const &
```

Definition at line 46 of file barray-meat-operators.hpp.

### 8.3.2.4 BARRAY\_TEMPLATE() [4/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const
```

### 8.3.2.5 BARRAY\_TEMPLATE() [5/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const &
```

Definition at line 75 of file barray-meat-operators.hpp.

### 8.3.2.6 BARRAY\_TEMPLATE() [6/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator/ ) const &
```

Definition at line 105 of file barray-meat-operators.hpp.

### 8.3.2.7 BARRAY\_TEMPLATE\_ARGS()

```
template BARRAY_TEMPLATE_ARGS ( ) const &
```

### 8.3.2.8 BARRAY\_TYPE()

```
template const BARRAY_TYPE ( ) &
```

Definition at line 20 of file barray-meat-operators.hpp.

### 8.3.2.9 for()

```
for ( ) = el[POS(i, j)] [pure virtual]
```

Definition at line 66 of file barray-meat-operators.hpp.

### 8.3.2.10 operator>()

```
j< ncol(); ++j) this-> operator() (
    i ,
    j )
```

## 8.3.3 Variable Documentation

### 8.3.3.1 rhs

Data\_Type & rhs

#### Initial value:

```
{  
    checkdim_(*this, rhs)
```

Definition at line 33 of file `barray-meat-operators.hpp`.


### 8.3.3.2 this

```
return * this
```

Definition at line 43 of file `barray-meat-operators.hpp`.

## 8.4 include/barry/barray-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- #define `BARRAY_TYPE()` `BArray<Cell_Type, Data_Type>`
- #define `BARRAY_TEMPLATE_ARGS()` `<typename Cell_Type, typename Data_Type>`
- #define `BARRAY_TEMPLATE(a, b)` `template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b`
- #define `ROW(a) this->el_ij[a]`
- #define `COL(a) this->el_ji[a]`

## Functions

- [BARRAY\\_TEMPLATE](#) (, [BArray](#))([uint](#) N\_
- [el\\_ij](#) [resize](#) (N)
- [el\\_ji](#) [resize](#) (M)
- [for](#) ([uint](#) i=0u;i< source.size();++i)
- [Data\\_Type](#) [bool](#) [M](#) ([Array\\_](#).M)
- [BARRAY\\_TEMPLATE](#) ([BARRAY\\_TYPE](#)() &, operator=)([const](#) [BArray](#)< [Cell\\_Type](#)
- [BARRAY\\_TEMPLATE](#) (, [BArray](#))([BARRAY\\_TYPE](#)() &&x) [noexcept](#)
- [BARRAY\\_TEMPLATE](#) ([BARRAY\\_TYPE](#)() &, operator=)([BARRAY\\_TYPE](#)() &&x) [noexcept](#)
- [BARRAY\\_TEMPLATE](#) ([bool](#), operator=)([const](#) [BARRAY\\_TYPE](#)() &[Array\\_](#))
- [BARRAY\\_TEMPLATE](#) (,~[BArray](#)())()
- [BARRAY\\_TEMPLATE](#) ([void](#), [set\\_data](#))([Data\\_Type](#) \*[data\\_](#)
- [BARRAY\\_TEMPLATE](#) ([Data\\_Type](#) \*, [D\\_ptr](#)())()
- [BARRAY\\_TEMPLATE](#) ([Data\\_Type](#) &, [D](#)())()
- [BARRAY\\_TEMPLATE](#) ([void](#), [out\\_of\\_range](#))([uint](#) i
- [BARRAY\\_TEMPLATE](#) ([Cell\\_Type](#), [get\\_cell](#))([uint](#) i
- [if](#) ([ROW](#)(i).size()==0u) [return](#)([Cell\\_Type](#)) 0.0
- [if](#) ([search](#) !=[ROW](#)(i).end()) [return](#) [search](#) -> [second.value](#)
- [return](#) ([Cell\\_Type](#)) 0.0
- [BARRAY\\_TEMPLATE](#) ([std::vector](#)< [Cell\\_Type](#) >, [get\\_row\\_vec](#))([uint](#) i
- [std::vector](#)< [Cell\\_Type](#) > [ans](#) ([ncol](#)(),([Cell\\_Type](#)) [false](#))
- [for](#) ([const](#) [auto](#) &[iter](#) :[row](#)(i, [false](#))) [ans](#)[[iter.first](#)]
- [BARRAY\\_TEMPLATE](#) ([void](#), [get\\_row\\_vec](#))([std](#)
- [BARRAY\\_TEMPLATE](#) ([BARRAY\\_TYPE](#)() &, operator-)([const](#) [std](#)
- [BARRAY\\_TEMPLATE](#) ([void](#), [insert\\_cell](#))([uint](#) i
- [if](#) ([check\\_exists](#))
- [COL](#) (j).emplace(i
- & [ROW](#) (i)[j])
- [BARRAY\\_TEMPLATE](#) ([void](#), [swap\\_cells](#))([uint](#) i0
- [if](#) ([report](#) !=[nullptr](#))(\*[report](#))
- [if](#) ([check0](#) &[check1](#))
- [else if](#) (![check0](#) &[check1](#))
- [else if](#) ([check0](#) &![check1](#))
- [BARRAY\\_TEMPLATE](#) ([void](#), [toggle\\_cell](#))([uint](#) i
- [BARRAY\\_TEMPLATE](#) ([void](#), [swap\\_rows](#))([uint](#) i0
- [if](#) ([ROW](#)(i0).size()==0u) [move0](#)
- [if](#) ([ROW](#)(i1).size()==0u) [move1](#)
- [if](#) (![move0](#) &&![move1](#)) [return](#)
- [ROW](#) (i0).swap([ROW](#)(i1))
- [BARRAY\\_TEMPLATE](#) ([void](#), [swap\\_cols](#))([uint](#) j0
- [if](#) ([COL](#)(j0).size()==0u) [check0](#)
- [if](#) ([COL](#)(j1).size()==0u) [check1](#)
- [if](#) ([check0](#) &&[check1](#))
- [else if](#) ([check0](#) &&![check1](#))
- [else if](#) (![check0](#) &&[check1](#))
- [BARRAY\\_TEMPLATE](#) ([void](#), [zero\\_row](#))([uint](#) i
- [for](#) ([auto](#) [row](#)=[row0.begin](#)();[row](#) !=[row0.end](#)();++[row](#)) [rm\\_cell](#)(i
- [BARRAY\\_TEMPLATE](#) ([void](#), [zero\\_col](#))([uint](#) j
- [if](#) ([COL](#)(j).size()==0u) [return](#)
- [BARRAY\\_TEMPLATE](#) ([void](#), [transpose](#)())()
- [BARRAY\\_TEMPLATE](#) ([void](#), [clear](#))([bool](#) [hard](#))
- [BARRAY\\_TEMPLATE](#) ([void](#), [resize](#))([uint](#) N\_
- [if](#) ([M](#)< [M](#)) [for](#)([uint](#) j = N\_

## Variables

- `uint M_`
- `uint const std::vector< uint > & source`
- `uint const std::vector< uint > const std::vector< uint > & target`
- `uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type > & value`
- `uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type > bool add`
- `if(source.size() !=value.size()) throw std N = N_`
- `M = M_`
- `return`
- `Data_Type & Array_`
- `Data_Type bool copy_data`
- `bool delete_data_`
- `data = data_`
- `delete_data = delete_data_`
- `uint j const`
- `uint j`
- `auto search = ROW(i).find(j)`
- `return ans`
- `uint const Cell< Cell_Type > & v`
- `uint const Cell< Cell_Type > bool check_bounds`
- `uint const Cell< Cell_Type > bool bool check_exists`
- `else`
- `NCells`
- `uint j0`
- `uint uint i1`
- `uint uint uint j1`
- `uint uint uint bool int int * report`
- `auto row0 = ROW(i)`
- `row first`
- `row false`
- `auto col0 = COL(j)`

## 8.4.1 Macro Definition Documentation

### 8.4.1.1 BARRAY\_TEMPLATE

```
#define BARRAY_TEMPLATE(
    a,
    b )  template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b
```

Definition at line 17 of file `barray-meat.hpp`.

### 8.4.1.2 BARRAY\_TEMPLATE\_ARGS

```
#define BARRAY_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 15 of file `barray-meat.hpp`.

### 8.4.1.3 BARRAY\_TYPE

```
#define BARRAY_TYPE( ) BArray<Cell_Type, Data_Type>
```

Definition at line 13 of file barray-meat.hpp.

### 8.4.1.4 COL

```
#define COL(  
    a ) this->el_ji[a]
```

Definition at line 21 of file barray-meat.hpp.

### 8.4.1.5 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 20 of file barray-meat.hpp.

## 8.4.2 Function Documentation

### 8.4.2.1 ans()

```
std::vector< Cell_Type > ans (  
    ncol() ,  
    (Cell_Type) false )
```

### 8.4.2.2 BARRAY\_TEMPLATE() [1/24]

```
BARRAY_TEMPLATE (  
    BArray ) && [noexcept]
```

Definition at line 230 of file barray-meat.hpp.

#### 8.4.2.3 BARRAY\_TEMPLATE() [2/24]

```
BARRAY_TEMPLATE (
    BArray )
```

#### 8.4.2.4 BARRAY\_TEMPLATE() [3/24]

```
BARRAY_TEMPLATE (
    ~ BArray )
```

Definition at line 339 of file barray-meat.hpp.

#### 8.4.2.5 BARRAY\_TEMPLATE() [4/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const
```

Definition at line 597 of file barray-meat.hpp.

#### 8.4.2.6 BARRAY\_TEMPLATE() [5/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator ) && [noexcept]
```

Definition at line 272 of file barray-meat.hpp.

#### 8.4.2.7 BARRAY\_TEMPLATE() [6/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator ) const
```

#### 8.4.2.8 BARRAY\_TEMPLATE() [7/24]

```
BARRAY_TEMPLATE (
    bool ,
    operator == ) const &
```

Definition at line 321 of file barray-meat.hpp.



#### 8.4.2.9 BARRAY\_TEMPLATE() [8/24]

```
BARRAY_TEMPLATE (
    Cell_Type ,
    get_cell )
```

#### 8.4.2.10 BARRAY\_TEMPLATE() [9/24]

```
BARRAY_TEMPLATE (
    Data_Type & ,
    D )
```

Definition at line 372 of file barray-meat.hpp.

#### 8.4.2.11 BARRAY\_TEMPLATE() [10/24]

```
BARRAY_TEMPLATE (
    Data_Type * ,
    D_ptr )
```

Definition at line 361 of file barray-meat.hpp.

#### 8.4.2.12 BARRAY\_TEMPLATE() [11/24]

```
BARRAY_TEMPLATE (
    std::vector< Cell_Type > ,
    get_row_vec )
```

#### 8.4.2.13 BARRAY\_TEMPLATE() [12/24]

```
BARRAY_TEMPLATE (
    void ,
    clear )
```

Definition at line 1130 of file barray-meat.hpp.

**8.4.2.14 BARRAY\_TEMPLATE()** [13/24]

```
BARRAY_TEMPLATE (
    void ,
    get_row_vec )
```

Definition at line 452 of file barray-meat.hpp.

**8.4.2.15 BARRAY\_TEMPLATE()** [14/24]

```
BARRAY_TEMPLATE (
    void ,
    insert_cell )
```

**8.4.2.16 BARRAY\_TEMPLATE()** [15/24]

```
BARRAY_TEMPLATE (
    void ,
    out_of_range )
```

**8.4.2.17 BARRAY\_TEMPLATE()** [16/24]

```
BARRAY_TEMPLATE (
    void ,
    resize )
```

**8.4.2.18 BARRAY\_TEMPLATE()** [17/24]

```
BARRAY_TEMPLATE (
    void ,
    set_data )
```

**8.4.2.19 BARRAY\_TEMPLATE()** [18/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_cells )
```

**8.4.2.20 BARRAY\_TEMPLATE()** [19/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_cols )
```

**8.4.2.21 BARRAY\_TEMPLATE()** [20/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_rows )
```

**8.4.2.22 BARRAY\_TEMPLATE()** [21/24]

```
BARRAY_TEMPLATE (
    void ,
    toggle_cell )
```

**8.4.2.23 BARRAY\_TEMPLATE()** [22/24]

```
BARRAY_TEMPLATE (
    void ,
    transpose )
```

Definition at line 1069 of file barray-meat.hpp.

**8.4.2.24 BARRAY\_TEMPLATE()** [23/24]

```
BARRAY_TEMPLATE (
    void ,
    zero_col )
```

**8.4.2.25 BARRAY\_TEMPLATE()** [24/24]

```
BARRAY_TEMPLATE (
    void ,
    zero_row )
```

**8.4.2.26 COL()**

```
COL (
    j )
```

**8.4.2.27 for() [1/3]**

```
for (
    auto row = row0.begin(); row != row0.end(); ++row )
```

**8.4.2.28 for() [2/3]**

```
for (
    const auto &iter : rowi, false )
```

**8.4.2.29 for() [3/3]**

```
for ( )
```

Definition at line 51 of file barray-meat.hpp.

**8.4.2.30 if() [1/17]**

```
else if (
    !check0 && check1 )
```

Definition at line 1008 of file barray-meat.hpp.

**8.4.2.31 if() [2/17]**

```
else if (
    !check0 & check1 )
```

Definition at line 856 of file barray-meat.hpp.

**8.4.2.32 if() [3/17]**

```
if (
    !move0 &&!  move1 )
```

**8.4.2.33 if() [4/17]**

```
else if (
    check0 &!  check1 )
```

Definition at line 864 of file barray-meat.hpp.

**8.4.2.34 if() [5/17]**

```
else if (
    check0 &&!  check1 )
```

Definition at line 999 of file barray-meat.hpp.

**8.4.2.35 if() [6/17]**

```
if (
    check0 &&  check1 )
```

Definition at line 972 of file barray-meat.hpp.

**8.4.2.36 if() [7/17]**

```
if (
    check0 &  check1 )
```

Definition at line 838 of file barray-meat.hpp.

**8.4.2.37 if() [8/17]**

```
else if (
    check_exists  ==  CHECK::BOTH )
```

Definition at line 679 of file barray-meat.hpp.

**8.4.2.38 if()** [9/17]

```
if (
    COL(j).size() == 0u )
```

**8.4.2.39 if()** [10/17]

```
if (
    COL(j0).size() == 0u )
```

**8.4.2.40 if()** [11/17]

```
if (
    COL(j1).size() == 0u )
```

**8.4.2.41 if()** [12/17]

```
else if ( ) = N_
```

Definition at line 86 of file barray-meat.hpp.

**8.4.2.42 if()** [13/17]

```
if (
    report ! == nullptr )
```

**8.4.2.43 if()** [14/17]

```
if (
    ROW(i).size() == 0u )
```

**8.4.2.44 if()** [15/17]

```
if (
    ROW(i0).size() == 0u )
```

**8.4.2.45 if() [16/17]**

```
if (
    ROW(i1).size() == 0u )
```

**8.4.2.46 if() [17/17]**

```
if (
    search ! = ROW(i).end() ) -> second.value
```

**8.4.2.47 M()**

```
Data_Type bool M (
    Array_ M )
```

Definition at line 136 of file barray-meat.hpp.

**8.4.2.48 resize() [1/2]**

```
el_ji resize (
    M )
```

**8.4.2.49 resize() [2/2]**

```
el_ij resize (
    N )
```

**8.4.2.50 return()**

```
return (
    Cell_Type )
```

#### 8.4.2.51 ROW() [1/2]

```
& ROW (
    i )
```

#### 8.4.2.52 ROW() [2/2]

```
ROW (
    i0 )
```

### 8.4.3 Variable Documentation

#### 8.4.3.1 add

```
uint const std::vector< uint > const std::vector< uint > bool add
```

##### Initial value:

```
{
    if (source.size() != target.size())
        throw std::length_error("-source- and -target- don't match on length.")
```

Definition at line 34 of file barray-meat.hpp.

#### 8.4.3.2 ans

```
return ans
```

Definition at line 449 of file barray-meat.hpp.

#### 8.4.3.3 Array\_

```
Data_Type & Array_
```

Definition at line 134 of file barray-meat.hpp.



#### 8.4.3.4 check\_bounds

bool check\_bounds

##### Initial value:

```
{  
    if (check_bounds) {  
        out_of_range(i0,0u);  
        out_of_range(i1,0u);  
    }  
  
    bool move0=true, move1=true
```

Definition at line 672 of file barray-meat.hpp.

#### 8.4.3.5 check\_exists

uint bool int check\_exists

##### Initial value:

```
{  
    if (check_bounds)  
        out_of_range(i,j)
```

Definition at line 673 of file barray-meat.hpp.

#### 8.4.3.6 col0

auto col0 = COL(j)

Definition at line 1061 of file barray-meat.hpp.

#### 8.4.3.7 const

uint bool check\_bounds const

##### Initial value:

```
{  
    if (i >= N)  
        throw std::range_error("The row is out of range.")
```

Definition at line 402 of file barray-meat.hpp.

#### 8.4.3.8 copy\_data

```
Data_Type bool copy_data
```

Definition at line 135 of file barray-meat.hpp.

#### 8.4.3.9 data

```
data = data_
```

Definition at line 354 of file barray-meat.hpp.

#### 8.4.3.10 delete\_data

```
delete_data = delete_data_
```

Definition at line 355 of file barray-meat.hpp.

#### 8.4.3.11 delete\_data\_

```
bool delete_data_
```

##### Initial value:

```
{  
    if ((data != nullptr) && delete_data)  
        delete data
```

Definition at line 348 of file barray-meat.hpp.

#### 8.4.3.12 else

```
else (  
    void )
```

##### Initial value:

```
{  
    ROW(i).insert(std::pair< uint, Cell<Cell_Type>>(j, v))
```

Definition at line 703 of file barray-meat.hpp.

#### 8.4.3.13 false

```
row false
```

Definition at line 1042 of file barray-meat.hpp.

#### 8.4.3.14 first

```
row first
```

Definition at line 1042 of file barray-meat.hpp.

#### 8.4.3.15 i1

```
uint i1
```

Definition at line 776 of file barray-meat.hpp.

#### 8.4.3.16 j

```
uint j
```

##### Initial value:

```
{  
    if (init_fun == nullptr)  
        return 0.0
```

Definition at line 414 of file barray-meat.hpp.

#### 8.4.3.17 j0

```
uint j0
```

Definition at line 775 of file barray-meat.hpp.

#### 8.4.3.18 j1

```
uint j1
```

Definition at line 776 of file barray-meat.hpp.

**8.4.3.19 M**

M = M\_

Definition at line 44 of file barray-meat.hpp.

**8.4.3.20 M\_**

uint M\_

**Initial value:**

```
{
    if (N_ < N)
        for (uint i = N_; i < N; ++i)
            zero_row(i, false)
```

Definition at line 30 of file barray-meat.hpp.

**8.4.3.21 N**

```
if (source.size() != target.size()) throw std::if (source.size() != value.size()) throw std::N =
N_
```

Definition at line 43 of file barray-meat.hpp.

**8.4.3.22 NCells**

NCells

Definition at line 707 of file barray-meat.hpp.

**8.4.3.23 report**

uint uint uint bool int int\* report

Definition at line 779 of file barray-meat.hpp.

#### 8.4.3.24 return

```
return
```

Definition at line 66 of file barray-meat.hpp.

#### 8.4.3.25 row0

```
auto row0 = ROW(i)
```

Definition at line 1040 of file barray-meat.hpp.

#### 8.4.3.26 search

```
auto search = ROW(i).find(j)
```

Definition at line 426 of file barray-meat.hpp.

#### 8.4.3.27 source

```
uint const std::vector< uint > & source
```

Definition at line 31 of file barray-meat.hpp.

#### 8.4.3.28 target

```
uint const std::vector< uint > const std::vector< uint > & target
```

Definition at line 32 of file barray-meat.hpp.

#### 8.4.3.29 v

```
uint Cell_Type v
```

Definition at line 671 of file barray-meat.hpp.


#### 8.4.3.30 value

```
uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type >&  
value
```

Definition at line 33 of file barray-meat.hpp.

## 8.5 include/barry/barraycell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [BArrayCell< Cell\\_Type, Data\\_Type >](#)
- class [BArrayCell\\_const< Cell\\_Type, Data\\_Type >](#)


## 8.6 include/barry/barraycell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.7 include/barry/barraydense-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [BArrayDense< Cell\\_Type, Data\\_Type >](#)  
*Baseline class for binary arrays.*

## 8.8 include/barry/barraydense-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define [BDENSE\\_TYPE\(\)](#) [BArrayDense<Cell\\_Type, Data\\_Type>](#)
- #define [BDENSE\\_TEMPLATE\\_ARGS\(\)](#) [<typename Cell\\_Type, typename Data\\_Type>](#)
- #define [BDENSE\\_TEMPLATE\(a, b\)](#) [template BDENSE\\_TEMPLATE\\_ARGS\(\)](#) inline a [BDENSE\\_TYPE\(\)](#)::b
- #define [ROW\(a\)](#) [this->el\\_ij\[a\]](#)
- #define [COL\(a\)](#) [this->el\\_ji\[a\]](#)
- #define [POS\(a, b\)](#) (b)\*N + (a)
- #define [POS\\_N\(a, b, c\)](#) (b)\*(c) + (a)

## Functions

- template `BDENSE_TEMPLATE_ARGS` () inline void `checkdim_(const BDENSE_TYPE() &lhs`
- template `const BDENSE_TYPE` () &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator+=)(`const BDENSE_TYPE`() &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator-=)(`const BDENSE_TYPE`() &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator\*=)(`const Cell_Type` &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator/=(`const Cell_Type` &rhs)

## 8.8.1 Macro Definition Documentation

### 8.8.1.1 BDENSE\_TEMPLATE

```
#define BDENSE_TEMPLATE(  
    a,  
    b )  template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE()::b
```

Definition at line 11 of file `barraydense-meat-operators.hpp`.

### 8.8.1.2 BDENSE\_TEMPLATE\_ARGS

```
template BDENSE_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file `barraydense-meat-operators.hpp`.

### 8.8.1.3 BDENSE\_TYPE

```
template Data_Type BDENSE_TYPE( ) BArrayDense<Cell_Type, Data_Type>
```

Definition at line 7 of file `barraydense-meat-operators.hpp`.

### 8.8.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 15 of file `barraydense-meat-operators.hpp`.



### 8.8.1.5 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 16 of file barraydense-meat-operators.hpp.

### 8.8.1.6 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 17 of file barraydense-meat-operators.hpp.

### 8.8.1.7 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 14 of file barraydense-meat-operators.hpp.

## 8.8.2 Function Documentation

### 8.8.2.1 BDENSE\_TEMPLATE() [1/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator* ) const &
```

Definition at line 90 of file barraydense-meat-operators.hpp.

### 8.8.2.2 BDENSE\_TEMPLATE() [2/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator+ ) const &
```

Definition at line 34 of file barraydense-meat-operators.hpp.

### 8.8.2.3 BDENSE\_TEMPLATE() [3/4]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator- ) const &
```

Definition at line 61 of file barrydense-meat-operators.hpp.

### 8.8.2.4 BDENSE\_TEMPLATE() [4/4]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator/ ) const &
```

Definition at line 101 of file barrydense-meat-operators.hpp.

### 8.8.2.5 BDENSE\_TEMPLATE\_ARGS()

```
template BDENSE_TEMPLATE_ARGS ( ) const &
```


### 8.8.2.6 BDENSE\_TYPE()

```
template const BDENSE_TYPE ( ) &
```

Definition at line 22 of file barrydense-meat-operators.hpp.

## 8.9 include/barry/barrydense-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- `#define BDENSE_TYPE() BArrayDense<Cell_Type, Data_Type>`
- `#define BDENSE_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BDENSE_TEMPLATE(a, b) template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE():b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`
- `#define POS(a, b) (b)*N + (a)`
- `#define POS_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO_CELL static_cast<Cell_Type>(0.0)`

## Functions

- `BDENSE_TEMPLATE (, BArrayDense)(uint N_`
- `el resize (N *M, ZERO_CELL)`
- `el_rowsums resize (N, ZERO_CELL)`
- `el_colsums resize (M, ZERO_CELL)`
- `for (uint i=0u;i< source.size();++i)`
- `BDENSE_TEMPLATE (, BArrayDense)(const BDENSE_TYPE() &Array_`
- `bool M (Array_.M)`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator=)(const BDENSE_TYPE() &Array_)`
- `BDENSE_TEMPLATE (, BArrayDense)(BDENSE_TYPE() &&x) noexcept`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator=)(BDENSE_TYPE() &&x) noexcept`
- `BDENSE_TEMPLATE (bool, operator==)(const BDENSE_TYPE() &Array_)`
- `BDENSE_TEMPLATE (, ~BArrayDense)()`
- `BDENSE_TEMPLATE (void, set_data)(Data_Type *data_`
- `BDENSE_TEMPLATE (Data_Type *, D_ptr)()`
- `BDENSE_TEMPLATE (const Data_Type *, D_ptr)() const`
- `BDENSE_TEMPLATE (Data_Type &, D)()`
- `BDENSE_TEMPLATE (const Data_Type &, D)() const`
- `BDENSE_TEMPLATE (void, out_of_range)(uint i`
- `BDENSE_TEMPLATE (Cell_Type, get_cell)(uint i`
- `BDENSE_TEMPLATE (std::vector< Cell_Type >, get_row_vec)(uint i`
- `std::vector< Cell_Type > ans (ncol(), static_cast< Cell_Type >(false))`
- `BDENSE_TEMPLATE (void, get_row_vec)(std`
- `BDENSE_TEMPLATE (Entries< Cell_Type >, get_entries)() const`
- `BDENSE_TEMPLATE (bool, is_empty)(uint i`
- `BDENSE_TEMPLATE (unsigned int, nrow)() const noexcept`
- `BDENSE_TEMPLATE (unsigned int, ncol)() const noexcept`
- `BDENSE_TEMPLATE (unsigned int, nnonzero)() const noexcept`
- `BDENSE_TEMPLATE (Cell< Cell_Type >, default_val)() const`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator+=)(const std`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator-=)(const std`
- `BDENSE_TEMPLATE (void, insert_cell)(uint i`
- `if (el[POS(i, j)]==BARRY_ZERO_DENSE)`
- `BDENSE_TEMPLATE (void, swap_cells)(uint i0`
- `if ((i0==i1) &&(j0==j1)) return`
- `rm_cell (i0, j0, false, false)`
- `rm_cell (i1, j1, false, false)`
- `insert_cell (i0, j0, val1, false, false)`
- `insert_cell (i1, j1, val0, false, false)`
- `BDENSE_TEMPLATE (void, toggle_cell)(uint i`
- `else rm_cell (i, j, false, false)`
- `BDENSE_TEMPLATE (void, swap_rows)(uint i0`

- `BDENSE_TEMPLATE` (void, swap\_cols)(uint j0
- `BDENSE_TEMPLATE` (void, zero\_row)(uint i
- `if` (el\_rowsums[i]==ZERO\_CELL) `return`
- `BDENSE_TEMPLATE` (void, zero\_col)(uint j
- `if` (el\_colsums[j]==ZERO\_CELL) `return`
- `BDENSE_TEMPLATE` (void, transpose)()
- `BDENSE_TEMPLATE` (void, clear)(bool hard)
- `BDENSE_TEMPLATE` (void, resize)(uint N\_
- `el` `resize` (N\_\*M\_, ZERO\_CELL)
- `el_rowsums` `resize` (N\_, ZERO\_CELL)
- `el_colsums` `resize` (M\_, ZERO\_CELL)
- `BDENSE_TEMPLATE` (void, reserve)()
- `BDENSE_TEMPLATE` (void, print)(const char \*fmt
- `va_start` (args, fmt)
- `vprintf` (fmt, args)
- `va_end` (args)
- `BDENSE_TEMPLATE` (const std::vector< Cell\_Type > &, get\_data)() `const`
- `BDENSE_TEMPLATE` (const Cell\_Type, rowsum)(unsigned int i) `const`
- `BDENSE_TEMPLATE` (const Cell\_Type, colsum)(unsigned int j) `const`

## Variables

- `uint` `M_`
- `uint` `const` `std::vector< uint > & source`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > & target`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > const` `std::vector< Cell_Type > & value`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > const` `std::vector< Cell_Type > bool add`
- `if`(source.size() !=value.size()) `throw` `std` `N` = `N_`
- `M` = `M_`
- `return`
- `bool` `copy_data`
- `bool` `delete_data_`
- `data` = `data_`
- `delete_data` = `delete_data_`
- `uint` `j` `const`
- `uint` `j`
- `return` `el` [`POS`(i, j)] == `ZERO_CELL`
- `return` `ans`
- `uint` `const` `Cell`< `Cell_Type` > & `v`
- `uint` `const` `Cell`< `Cell_Type` > `bool` `check_bounds`
- `uint` `const` `Cell`< `Cell_Type` > `bool` `bool` `check_exists`
- `else`
- `el_rowsums` [`i`] = (`v.value` - `old`)
- `el_colsums` [`j`] = (`v.value` - `old`)
- `uint` `j0`
- `uint` `uint` `i1`
- `uint` `uint` `uint` `j1`
- `uint` `uint` `uint` `bool` `int` `int` \* `report`
- `Cell_Type` `val0` = `el`[`POS`(i0,j0)]
- `Cell_Type` `val1` = `el`[`POS`(i1,j1)]
- `false`
- `col`

## 8.9.1 Macro Definition Documentation

### 8.9.1.1 BDENSE\_TEMPLATE

```
#define BDENSE_TEMPLATE(  
    a,  
    b )  template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE()::b
```

Definition at line 27 of file barraydense-meat.hpp.

### 8.9.1.2 BDENSE\_TEMPLATE\_ARGS

```
#define BDENSE_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 25 of file barraydense-meat.hpp.

### 8.9.1.3 BDENSE\_TYPE

```
#define BDENSE_TYPE( ) BArrayDense<Cell_Type, Data_Type>
```

Definition at line 23 of file barraydense-meat.hpp.

### 8.9.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 31 of file barraydense-meat.hpp.

### 8.9.1.5 POS

```
#define POS(  
    a,  
    b )  (b)*N + (a)
```

Definition at line 32 of file barraydense-meat.hpp.

### 8.9.1.6 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 33 of file bararraydense-meat.hpp.

### 8.9.1.7 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 30 of file bararraydense-meat.hpp.

### 8.9.1.8 ZERO\_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 38 of file bararraydense-meat.hpp.

## 8.9.2 Function Documentation

### 8.9.2.1 ans()

```
std::vector< Cell_Type > ans (  
    ncol() ,  
    static_cast< Cell_Type > false )
```

### 8.9.2.2 BDENSE\_TEMPLATE() [1/39]

```
BDENSE_TEMPLATE (  
    BArrayDense ) && [noexcept]
```

Definition at line 240 of file bararraydense-meat.hpp.

### 8.9.2.3 BDENSE\_TEMPLATE() [2/39]

```
BDENSE_TEMPLATE (
    BArrayDense ) const &
```

### 8.9.2.4 BDENSE\_TEMPLATE() [3/39]

```
BDENSE_TEMPLATE (
    BArrayDense )
```

### 8.9.2.5 BDENSE\_TEMPLATE() [4/39]

```
BDENSE_TEMPLATE (
    ~ BArrayDense )
```

Definition at line 318 of file barraydense-meat.hpp.

### 8.9.2.6 BDENSE\_TEMPLATE() [5/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator+ ) const
```

Definition at line 566 of file barraydense-meat.hpp.

### 8.9.2.7 BDENSE\_TEMPLATE() [6/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator- ) const
```

Definition at line 584 of file barraydense-meat.hpp.

### 8.9.2.8 BDENSE\_TEMPLATE() [7/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator ) && [noexcept]
```

Definition at line 257 of file barraydense-meat.hpp.

#### 8.9.2.9 BDENSE\_TEMPLATE() [8/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator ) const &
```

Definition at line 194 of file bararraydense-meat.hpp.

#### 8.9.2.10 BDENSE\_TEMPLATE() [9/39]

```
BDENSE_TEMPLATE (
    bool ,
    is_empty )
```

#### 8.9.2.11 BDENSE\_TEMPLATE() [10/39]

```
BDENSE_TEMPLATE (
    bool ,
    operator == ) const &
```

Definition at line 300 of file bararraydense-meat.hpp.

#### 8.9.2.12 BDENSE\_TEMPLATE() [11/39]

```
BDENSE_TEMPLATE (
    Cell< Cell_Type > ,
    default_val ) const
```

Definition at line 562 of file bararraydense-meat.hpp.

#### 8.9.2.13 BDENSE\_TEMPLATE() [12/39]

```
BDENSE_TEMPLATE (
    Cell_Type ,
    get_cell )
```



**8.9.2.14 BDENSE\_TEMPLATE() [13/39]**

```
BDENSE_TEMPLATE (
    const Cell_Type,
    colsum ) const
```

Definition at line 999 of file barraydense-meat.hpp.

**8.9.2.15 BDENSE\_TEMPLATE() [14/39]**

```
BDENSE_TEMPLATE (
    const Cell_Type,
    rowsum ) const
```

Definition at line 994 of file barraydense-meat.hpp.

**8.9.2.16 BDENSE\_TEMPLATE() [15/39]**

```
BDENSE_TEMPLATE (
    const Data_Type & ,
    D ) const
```

Definition at line 353 of file barraydense-meat.hpp.

**8.9.2.17 BDENSE\_TEMPLATE() [16/39]**

```
BDENSE_TEMPLATE (
    const Data_Type * ,
    D_ptr ) const
```

Definition at line 345 of file barraydense-meat.hpp.

**8.9.2.18 BDENSE\_TEMPLATE() [17/39]**

```
BDENSE_TEMPLATE (
    const std::vector< Cell_Type > & ,
    get_data ) const
```

Definition at line 989 of file barraydense-meat.hpp.

**8.9.2.19 BDENSE\_TEMPLATE() [18/39]**

```
BDENSE_TEMPLATE (
    Data_Type & ,
    D )
```

Definition at line 349 of file bararraydense-meat.hpp.

**8.9.2.20 BDENSE\_TEMPLATE() [19/39]**

```
BDENSE_TEMPLATE (
    Data_Type * ,
    D_ptr )
```

Definition at line 341 of file bararraydense-meat.hpp.

**8.9.2.21 BDENSE\_TEMPLATE() [20/39]**

```
BDENSE_TEMPLATE (
    Entries< Cell_Type > ,
    get_entries ) const
```

Definition at line 502 of file bararraydense-meat.hpp.

**8.9.2.22 BDENSE\_TEMPLATE() [21/39]**

```
BDENSE_TEMPLATE (
    std::vector< Cell_Type > ,
    get_row_vec )
```

**8.9.2.23 BDENSE\_TEMPLATE() [22/39]**

```
BDENSE_TEMPLATE (
    unsigned int ,
    ncol ) const [noexcept]
```

Definition at line 548 of file bararraydense-meat.hpp.

**8.9.2.24 BDENSE\_TEMPLATE()** [23/39]

```
BDENSE_TEMPLATE (
    unsigned int ,
    nnozero ) const [noexcept]
```

Definition at line 552 of file barraydense-meat.hpp.

**8.9.2.25 BDENSE\_TEMPLATE()** [24/39]

```
BDENSE_TEMPLATE (
    unsigned int ,
    nrow ) const [noexcept]
```

Definition at line 544 of file barraydense-meat.hpp.

**8.9.2.26 BDENSE\_TEMPLATE()** [25/39]

```
BDENSE_TEMPLATE (
    void ,
    clear )
```

Definition at line 896 of file barraydense-meat.hpp.

**8.9.2.27 BDENSE\_TEMPLATE()** [26/39]

```
BDENSE_TEMPLATE (
    void ,
    get_row_vec )
```

Definition at line 402 of file barraydense-meat.hpp.

**8.9.2.28 BDENSE\_TEMPLATE()** [27/39]

```
BDENSE_TEMPLATE (
    void ,
    insert_cell )
```

**8.9.2.29 BDENSE\_TEMPLATE()** [28/39]

```
BDENSE_TEMPLATE (
    void ,
    out_of_range )
```

**8.9.2.30 BDENSE\_TEMPLATE()** [29/39]

```
BDENSE_TEMPLATE (
    void ,
    print ) const
```

**8.9.2.31 BDENSE\_TEMPLATE()** [30/39]

```
BDENSE_TEMPLATE (
    void ,
    reserve )
```

Definition at line 946 of file `barraydense-meat.hpp`.

**8.9.2.32 BDENSE\_TEMPLATE()** [31/39]

```
BDENSE_TEMPLATE (
    void ,
    resize )
```

**8.9.2.33 BDENSE\_TEMPLATE()** [32/39]

```
BDENSE_TEMPLATE (
    void ,
    set_data )
```

**8.9.2.34 BDENSE\_TEMPLATE()** [33/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_cells )
```

**8.9.2.35 BDENSE\_TEMPLATE()** [34/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_cols )
```

**8.9.2.36 BDENSE\_TEMPLATE()** [35/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_rows )
```

**8.9.2.37 BDENSE\_TEMPLATE()** [36/39]

```
BDENSE_TEMPLATE (
    void ,
    toggle_cell )
```

**8.9.2.38 BDENSE\_TEMPLATE()** [37/39]

```
BDENSE_TEMPLATE (
    void ,
    transpose )
```

Definition at line 868 of file barraydense-meat.hpp.

**8.9.2.39 BDENSE\_TEMPLATE()** [38/39]

```
BDENSE_TEMPLATE (
    void ,
    zero_col )
```

**8.9.2.40 BDENSE\_TEMPLATE()** [39/39]

```
BDENSE_TEMPLATE (
    void ,
    zero_row )
```

**8.9.2.41 for()**

```
for ( )
```

Definition at line 64 of file bararraydense-meat.hpp.

**8.9.2.42 if() [1/4]**

```
if (
    (i0==i1) && (j0==j1) )
```

**8.9.2.43 if() [2/4]**

```
if (
    el [POS(i, j)] == BARRY_ZERO_DENSE )
```

Definition at line 663 of file bararraydense-meat.hpp.

**8.9.2.44 if() [3/4]**

```
if (
    el_colsums [j] == ZERO_CELL )
```

**8.9.2.45 if() [4/4]**

```
if (
    el_rowsums [i] == ZERO_CELL )
```

**8.9.2.46 insert\_cell() [1/2]**

```
insert_cell (
    i0 ,
    j0 ,
    val1 ,
    false ,
    false )
```

**8.9.2.47 insert\_cell()** [2/2]

```
insert_cell (
    i1 ,
    j1 ,
    val0 ,
    false ,
    false )
```

**8.9.2.48 M()**

```
bool M (
    Array_. M )
```

Definition at line 157 of file barraydense-meat.hpp.

**8.9.2.49 resize()** [1/6]

```
el_colsums resize (
    M ,
    ZERO_CELL )
```

**8.9.2.50 resize()** [2/6]

```
el_colsums resize (
    M_ ,
    ZERO_CELL )
```

**8.9.2.51 resize()** [3/6]

```
el resize (
    N * M,
    ZERO_CELL )
```

**8.9.2.52 resize()** [4/6]

```
el_rowsums resize (
    N ,
    ZERO_CELL )
```

**8.9.2.53** `resize()` [5/6]

```
el_resize (
    N_ * M_,
    ZERO_CELL )
```

**8.9.2.54** `resize()` [6/6]

```
el_rowsums_resize (
    N_ ,
    ZERO_CELL )
```

**8.9.2.55** `rm_cell()` [1/3]

```
else rm_cell (
    i ,
    j ,
    false ,
    false )
```

**8.9.2.56** `rm_cell()` [2/3]

```
rm_cell (
    i0 ,
    j0 ,
    false ,
    false )
```

**8.9.2.57** `rm_cell()` [3/3]

```
rm_cell (
    i1 ,
    j1 ,
    false ,
    false )
```

**8.9.2.58** `va_end()`

```
va_end (
    args )
```



### 8.9.2.59 va\_start()

```
va_start (
    args ,
    fmt )
```

### 8.9.2.60 vprintf()

```
vprintf (
    fmt ,
    args )
```

## 8.9.3 Variable Documentation

### 8.9.3.1 add

```
uint const std::vector< uint > const std::vector< uint > bool add
```

#### Initial value:

```
{
    if (source.size() != target.size())
        throw std::length_error("-source- and -target- don't match on length.")
```

Definition at line 47 of file barraydense-meat.hpp.

### 8.9.3.2 ans

```
return ans
```

Definition at line 398 of file barraydense-meat.hpp.

### 8.9.3.3 check\_bounds

```
bool check_bounds
```

#### Initial value:

```
{
    if (check_bounds)
    {
        out_of_range(i0,0u);
        out_of_range(i1,0u);
    }

    for (uint j = 0u; j < M; ++j)
        std::swap(e1[POS(i0, j)], e1[POS(i1, j)])
```

Definition at line 654 of file barraydense-meat.hpp.

#### 8.9.3.4 check\_exists

```
uint bool int check_exists
```

##### Initial value:

```
{  
    if (check_bounds)  
        out_of_range(i, j)
```

Definition at line 655 of file baraydense-meat.hpp.

#### 8.9.3.5 col

```
col
```

Definition at line 843 of file baraydense-meat.hpp.

#### 8.9.3.6 const

```
const
```

##### Initial value:

```
{  
    if (i >= N)  
        throw std::range_error("The row is out of range.")
```

Definition at line 360 of file baraydense-meat.hpp.

#### 8.9.3.7 copy\_data

```
bool copy_data
```

Definition at line 156 of file baraydense-meat.hpp.

#### 8.9.3.8 data

```
data = data_
```

Definition at line 334 of file baraydense-meat.hpp.

### 8.9.3.9 delete\_data

```
delete_data = delete_data_
```

Definition at line 335 of file barraydense-meat.hpp.

### 8.9.3.10 delete\_data\_

```
bool delete_data_
```

#### Initial value:

```
{  
    if ((data != nullptr) && delete_data)  
        delete data
```

Definition at line 328 of file barraydense-meat.hpp.

### 8.9.3.11 el

```
return el == ZERO_CELL
```

Definition at line 381 of file barraydense-meat.hpp.

### 8.9.3.12 el\_colsums

```
el_colsums[j] = (v.value - old)
```

Definition at line 675 of file barraydense-meat.hpp.

### 8.9.3.13 el\_rowsums

```
el_rowsums[i] = (v.value - old)
```

Definition at line 674 of file barraydense-meat.hpp.

### 8.9.3.14 else

```
else (
    void )
```

#### Initial value:

```
{
    Cell_Type old = el[POS(i,j)]
```

Definition at line 670 of file bararraydense-meat.hpp.

### 8.9.3.15 false

```
false
```

Definition at line 767 of file bararraydense-meat.hpp.

### 8.9.3.16 i1

```
uint i1
```

Definition at line 721 of file bararraydense-meat.hpp.

### 8.9.3.17 j

```
j
```

Definition at line 373 of file bararraydense-meat.hpp.

### 8.9.3.18 j0

```
uint j0
```

Definition at line 720 of file bararraydense-meat.hpp.

### 8.9.3.19 j1

```
uint j1
```

Definition at line 721 of file bararraydense-meat.hpp.

### 8.9.3.20 M

M = M\_

Definition at line 57 of file barraydense-meat.hpp.

### 8.9.3.21 M\_

uint M\_

#### Initial value:

```
{  
    std::vector< Cell_Type > el_tmp(e1)
```

Definition at line 43 of file barraydense-meat.hpp.

### 8.9.3.22 N

N = N\_

Definition at line 56 of file barraydense-meat.hpp.

### 8.9.3.23 report

uint uint uint bool int int\* report

#### Initial value:

```
{  
    if (check_bounds) {  
        out_of_range(i0,j0);  
        out_of_range(i1,j1);  
    }  
  
    if (report != nullptr)  
        (*report) = EXISTS::BOTH
```

Definition at line 724 of file barraydense-meat.hpp.

### 8.9.3.24 return

return

Definition at line 94 of file barraydense-meat.hpp.

#### 8.9.3.25 source

```
uint const std::vector< uint >& source
```

Definition at line 44 of file bararraydense-meat.hpp.

#### 8.9.3.26 target

```
uint const std::vector< uint > const std::vector< uint >& target
```

Definition at line 45 of file bararraydense-meat.hpp.

#### 8.9.3.27 v

```
uint Cell_Type v
```

Definition at line 653 of file bararraydense-meat.hpp.

#### 8.9.3.28 val0

```
Cell_Type val0 = el[POS(i0,j0)]
```

Definition at line 742 of file bararraydense-meat.hpp.

#### 8.9.3.29 val1

```
Cell_Type val1 = el[POS(i1,j1)]
```

Definition at line 743 of file bararraydense-meat.hpp.


#### 8.9.3.30 value

```
uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type >&  
value
```

Definition at line 46 of file bararraydense-meat.hpp.

## 8.10 include/barry/barraydensecell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [BArrayDenseCell< Cell\\_Type, Data\\_Type >](#)

### Macros

- `#define POS(a, b) (a) + (b) * N`

### 8.10.1 Macro Definition Documentation


#### 8.10.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * N
```

Definition at line 6 of file barraydensecell-bones.hpp.

## 8.11 include/barry/barraydensecell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define POS(a, b) (a) + (b) * dat->N`

#### 8.11.1 Macro Definition Documentation


##### 8.11.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * dat->N
```

Definition at line 6 of file barraydensecell-meat.hpp.

## 8.12 include/barry/barraydensecol-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:





## Classes

- class [BArrayDenseCol< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseCol\\_const< Cell\\_Type, Data\\_Type >](#)

## Macros

- `#define POS(a, b) (b)*N + (a)`
- `#define POS\_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO\_CELL static_cast<Cell_Type>(0.0)`

### 8.12.1 Macro Definition Documentation

#### 8.12.1.1 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 4 of file `barraydensecol-bones.hpp`.

#### 8.12.1.2 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 5 of file `barraydensecol-bones.hpp`.


#### 8.12.1.3 ZERO\_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 6 of file `barraydensecol-bones.hpp`.

## 8.13 include/barry/barraydenserow-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [BArrayDenseRow< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseRow\\_const< Cell\\_Type, Data\\_Type >](#)

### Macros

- #define [POS](#)(a, b) (b) \* [N](#) + (a)
- #define [POS\\_N](#)(a, b, c) (b)\*(c) + (a)
- #define [ZERO\\_CELL](#) static\_cast< Cell\_Type >(0.0)

### 8.13.1 Macro Definition Documentation

#### 8.13.1.1 POS

```
#define POS(  
    a,  
    b ) (b) * N + (a)
```

Definition at line 4 of file barraydenserow-bones.hpp.

### 8.13.1.2 POS\_N

```
#define POS_N(
    a,
    b,
    c ) (b)*(c) + (a)
```

Definition at line 5 of file barraydenserow-bones.hpp.

### 8.13.1.3 ZERO\_CELL

```
#define ZERO_CELL static_cast< Cell_Type >(0.0)
```

Definition at line 6 of file barraydenserow-bones.hpp.

## 8.14 include/barry/barrayrow-bones.hpp File Reference

### Classes

- class [BArrayRow< Cell\\_Type, Data\\_Type >](#)
- class [BArrayRow\\_const< Cell\\_Type, Data\\_Type >](#)

## 8.15 include/barry/barrayrow-meat.hpp File Reference

### Macros

- #define [BROW\\_TYPE\(\)](#) [BArrayRow<Cell\\_Type, Data\\_Type>](#)
- #define [BROW\\_TEMPLATE\\_ARGS\(\)](#) <typename Cell\_Type, typename Data\_Type>
- #define [BROW\\_TEMPLATE\(a, b\)](#) template [BROW\\_TEMPLATE\\_ARGS\(\)](#) inline a [BROW\\_TYPE\(\)](#)::b

### Functions

- [BROW\\_TEMPLATE](#) (void, operator=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator+=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator-=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator\*=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator/=)(const [BROW\\_TYPE\(\)](#) &val)

### 8.15.1 Macro Definition Documentation

### 8.15.1.1 BROW\_TEMPLATE

```
#define BROW_TEMPLATE(  
    a,  
    b )  template BROW_TEMPLATE_ARGS() inline a BROW_TYPE():b
```

Definition at line 8 of file bararrayrow-meat.hpp.

### 8.15.1.2 BROW\_TEMPLATE\_ARGS

```
#define BROW_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 6 of file bararrayrow-meat.hpp.

### 8.15.1.3 BROW\_TYPE

```
#define BROW_TYPE( ) BArrayRow<Cell_Type, Data_Type>
```

Definition at line 4 of file bararrayrow-meat.hpp.

## 8.15.2 Function Documentation

### 8.15.2.1 BROW\_TEMPLATE() [1/5]

```
BROW_TEMPLATE (  
    void ,  
    operator* ) const &
```

Definition at line 45 of file bararrayrow-meat.hpp.

### 8.15.2.2 BROW\_TEMPLATE() [2/5]

```
BROW_TEMPLATE (  
    void ,  
    operator+ ) const &
```

Definition at line 25 of file bararrayrow-meat.hpp.

### 8.15.2.3 BROW\_TEMPLATE() [3/5]

```
BROW_TEMPLATE (
    void ,
    operator- ) const &
```

Definition at line 34 of file barrayrow-meat.hpp.

### 8.15.2.4 BROW\_TEMPLATE() [4/5]

```
BROW_TEMPLATE (
    void ,
    operator/ ) const &
```

Definition at line 55 of file barrayrow-meat.hpp.

### 8.15.2.5 BROW\_TEMPLATE() [5/5]

```
BROW_TEMPLATE (
    void ,
    operator ) const &
```

Definition at line 11 of file barrayrow-meat.hpp.

## 8.16 include/barry/barrayvector-bones.hpp File Reference


### Classes

- class [BArrayVector< Cell\\_Type, Data\\_Type >](#)  
*Row or column of a [BArray](#)*
- class [BArrayVector\\_const< Cell\\_Type, Data\\_Type >](#)

## 8.17 include/barry/barrayvector-meat.hpp File Reference

## 8.18 include/barry/barry-configuration.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Configuration MACROS

These are mostly related to performance. The definitions follow:

- `BARRY_USE_UNORDERED_MAP` If specified, then barry is compiled using `std::unordered_map`. Otherwise it will use `std::map` for the arrays.
  - `BARRY_USE_SAFE_EXP` When specified, it will multiply all likelihoods in [Model](#) by  $(1/100)/(1/100)$  so that numerical overflows are avoided.
  - `BARRY_USE_ISFINITE` When specified, it will introduce a macro that checks whether the likelihood is finite or not.
  - `printf_barry` If not specified, will be defined as `printf`.
  - `BARRY_DEBUG_LEVEL`, when defined, will make things verbose.
- 
- `#define BARRY_SAFE_EXP -100.0`
  - `#define BARRY_ISFINITE(a)`
  - `#define BARRY_CHECK_SUPPORT(x, maxs)`
  - `#define printf_barry printf`
  - `#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t >(UINT_MAX/2u)`
  - `template<typename Ta, typename Tb >`  
`using Map = std::map< Ta, Tb >`

## 8.18.1 Macro Definition Documentation

### 8.18.1.1 BARRY\_CHECK\_SUPPORT

```
#define BARRY_CHECK_SUPPORT(  
    x,  
    maxs )
```

Definition at line 47 of file barry-configuration.hpp.

### 8.18.1.2 BARRY\_ISFINITE

```
#define BARRY_ISFINITE(  
    a )
```

Definition at line 40 of file barry-configuration.hpp.

### 8.18.1.3 BARRY\_MAX\_NUM\_ELEMENTS

```
#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t > (UINT_MAX/2u)
```

Definition at line 55 of file barry-configuration.hpp.

### 8.18.1.4 BARRY\_SAFE\_EXP

```
#define BARRY_SAFE_EXP -100.0
```

Definition at line 33 of file barry-configuration.hpp.

### 8.18.1.5 printf\_barry

```
#define printf_barry printf
```

Definition at line 51 of file barry-configuration.hpp.

## 8.18.2 Typedef Documentation


### 8.18.2.1 Map

```
template<typename Ta , typename Tb >  
using Map = std::map<Ta,Tb>
```

Definition at line 27 of file barry-configuration.hpp.

## 8.19 include/barry/barry-debug.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define `BARRY_DEBUG_LEVEL` 0

### 8.19.1 Macro Definition Documentation

#### 8.19.1.1 BARRY\_DEBUG\_LEVEL

```
#define BARRY_DEBUG_LEVEL 0
```

Definition at line 5 of file barry-debug.hpp.



## 8.20 include/barry/barry-macros.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define BARRY_ZERO Cell<Cell_Type>(0.0)`
- `#define BARRY_ZERO_DENSE static_cast<Cell_Type>(0.0)`
- `#define BARRY_ONE Cell<Cell_Type>(1.0)`
- `#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)`
- `#define BARRY_UNUSED(expr) do { (void)(expr); } while (0);`

### 8.20.1 Macro Definition Documentation

#### 8.20.1.1 BARRY\_ONE

```
#define BARRY_ONE Cell<Cell_Type>(1.0)
```

Definition at line 7 of file barry-macros.hpp.

#### 8.20.1.2 BARRY\_ONE\_DENSE

```
#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)
```

Definition at line 8 of file barry-macros.hpp.

### 8.20.1.3 BARRY\_UNUSED

```
#define BARRY_UNUSED(  
    expr ) do { (void)(expr); } while (0);
```

Definition at line 10 of file barry-macros.hpp.

### 8.20.1.4 BARRY\_ZERO

```
#define BARRY_ZERO Cell<Cell\_Type>(0.0)
```

Definition at line 4 of file barry-macros.hpp.

### 8.20.1.5 BARRY\_ZERO\_DENSE

```
#define BARRY_ZERO_DENSE static_cast<Cell\_Type>(0.0)
```

Definition at line 5 of file barry-macros.hpp.

## 8.21 include/barry/barry.hpp File Reference

```
#include <iostream>  
#include <cstdint>  
#include <vector>  
#include <unordered_map>  
#include <functional>  
#include <stdexcept>  
#include <cmath>  
#include <map>  
#include <algorithm>  
#include <utility>  
#include <random>  
#include <climits>  
#include <cfloat>  
#include <string>  
#include <cstdint>  
#include <memory>  
#include "typedefs.hpp"  
#include "barry-macros.hpp"  
#include "freqtable.hpp"  
#include "cell-bones.hpp"  
#include "cell-meat.hpp"  
#include "barray-bones.hpp"  
#include "barraycell-bones.hpp"  
#include "barray-meat.hpp"  
#include "barraycell-meat.hpp"  
#include "barray-meat-operators.hpp"  
#include "barraydense-bones.hpp"
```

```
#include "barraydensecell-bones.hpp"
#include "barraydenserow-bones.hpp"
#include "barraydensecol-bones.hpp"
#include "barraydense-meat.hpp"
#include "barraydensecell-meat.hpp"
#include "barraydense-meat-operators.hpp"
#include "counters-bones.hpp"
#include "counters-meat.hpp"
#include "statscounter-bones.hpp"
#include "statscounter-meat.hpp"
#include "support-bones.hpp"
#include "support-meat.hpp"
#include "powerset-bones.hpp"
#include "powerset-meat.hpp"
#include "model-bones.hpp"
#include "model-meat.hpp"
#include "rules-bones.hpp"
#include "rules-meat.hpp"
#include "counters/network.hpp"
#include "counters/phylo.hpp"
#include "counters/defm.hpp"
```

Include dependency graph for barry.hpp:



## Namespaces

- [barry](#)  
*barry: Your go-to motif accountant*
- [barry::counters](#)  
*Tree class and TreeIterator class.*
- [barry::counters::network](#)
- [barry::counters::phylo](#)
- [barry::counters::defm](#)

## Macros

- `#define BARRY_HPP`
- `#define BARRY_VERSION_MAYOR 0`
- `#define BARRY_VERSION_MINOR 1`
- `#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR`
- `#define COUNTER_FUNCTION(a)`
- `#define COUNTER_LAMBDA(a)`
- `#define RULE_FUNCTION(a)`
- `#define RULE_LAMBDA(a)`

### 8.21.1 Macro Definition Documentation

#### 8.21.1.1 BARRY\_HPP

```
#define BARRY_HPP
```

Definition at line 23 of file barry.hpp.

#### 8.21.1.2 BARRY\_VERSION

```
#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR
```

Definition at line 27 of file barry.hpp.

#### 8.21.1.3 BARRY\_VERSION\_MAYOR

```
#define BARRY_VERSION_MAYOR 0
```

Definition at line 25 of file barry.hpp.

#### 8.21.1.4 BARRY\_VERSION\_MINOR

```
#define BARRY_VERSION_MINOR 1
```

Definition at line 26 of file barry.hpp.

#### 8.21.1.5 COUNTER\_FUNCTION

```
#define COUNTER_FUNCTION(  
    a )
```

**Value:**

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline double (a) (const Array_Type & Array, uint i, uint j, Data_Type & data) \  
{
```

Definition at line 94 of file barry.hpp.

### 8.21.1.6 COUNTER\_LAMBDA

```
#define COUNTER_LAMBDA(  
    a )
```

**Value:**

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Counter_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, uint i, uint j, Data_Type & data)
```

Definition at line 97 of file barry.hpp.

### 8.21.1.7 RULE\_FUNCTION

```
#define RULE_FUNCTION(  
    a )
```

**Value:**

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline bool (a) (const Array_Type & Array, uint i, uint j, Data_Type & data) \  
{
```

Definition at line 101 of file barry.hpp.

### 8.21.1.8 RULE\_LAMBDA

```
#define RULE_LAMBDA(  
    a )
```


**Value:**

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Rule_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, uint i, uint j, Data_Type & data)
```

Definition at line 104 of file barry.hpp.

## 8.22 include/barry/cell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [Cell< Cell\\_Type >](#)  
*Entries in [BArray](#). For now, it only has two members:*

## 8.23 include/barry/cell-meat.hpp File Reference


This graph shows which files directly or indirectly include this file:



## 8.24 include/barry/col-bones.hpp File Reference

## 8.25 include/barry/counters-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [Counter< Array\\_Type, Data\\_Type >](#)  
*A counter function based on change statistics.*
- class [Counters< Array\\_Type, Data\\_Type >](#)  
*Vector of counters.*

## 8.26 include/barry/counters-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define [COUNTER\\_TYPE](#)() [Counter](#)<Array\_Type,Data\_Type>
- #define [COUNTER\\_TEMPLATE\\_ARGS](#)() <typename Array\_Type, typename Data\_Type>
- #define [COUNTER\\_TEMPLATE](#)(a, b) template [COUNTER\\_TEMPLATE\\_ARGS](#)() inline a [COUNTER\\_TYPE](#)()↔  
::b
- #define [COUNTERS\\_TYPE](#)() [Counters](#)<Array\_Type,Data\_Type>
- #define [COUNTERS\\_TEMPLATE\\_ARGS](#)() <typename Array\_Type, typename Data\_Type>
- #define [COUNTERS\\_TEMPLATE](#)(a, b) template [COUNTERS\\_TEMPLATE\\_ARGS](#)() inline a [COUNTERS\\_TYPE](#)()↔  
::b

### Functions

- [COUNTER\\_TEMPLATE](#) (, [Counter](#))(const [Counter](#)< Array\_Type
- Data\_Type [init\\_fun](#) (counter\_.init\_fun)
- Data\_Type &&[counter\\_init\\_fun](#) (std::move(counter\_.init\_fun))
- Data\_Type &&[counter\\_data](#) (std::move(counter\_.data))
- Data\_Type &&[counter\\_name](#) (std::move(counter\_.name))
- Data\_Type &&[counter\\_desc](#) (std::move(counter\_.desc))
- *Move constructor.*
- [COUNTER\\_TEMPLATE](#) ([COUNTER\\_TYPE](#)(), operator=)(const [Counter](#)< Array\_Type
- [COUNTER\\_TEMPLATE](#) ([COUNTER\\_TYPE](#)() &, operator=)([Counter](#)< Array\_Type
- [COUNTER\\_TEMPLATE](#) (double, count)(Array\_Type &Array
- *< Move assignment*
- [return count\\_fun](#) (Array, i, j, [data](#))
- [COUNTER\\_TEMPLATE](#) (double, init)(Array\_Type &Array
- [return init\\_fun](#) (Array, i, j, [data](#))
- [COUNTER\\_TEMPLATE](#) (std::string, get\_name)() const
- [COUNTER\\_TEMPLATE](#) (std::string, get\_description)() const
- [COUNTERS\\_TEMPLATE](#) (, [Counters](#)())
- [COUNTERS\\_TEMPLATE](#) ([COUNTER\\_TYPE](#)() &, operator[])(uint idx)
- Data\_Type [Counters](#) ([Counters](#)< Array\_Type, Data\_Type > &&[counters\\_](#)) noexcept
- [COUNTERS\\_TEMPLATE](#) ([COUNTERS\\_TYPE](#)(), operator=)(const [Counters](#)< Array\_Type
- [COUNTERS\\_TEMPLATE](#) ([COUNTERS\\_TYPE](#)() &, operator=)([Counters](#)< Array\_Type
- [COUNTERS\\_TEMPLATE](#) (void, add\_counter)([Counter](#)< Array\_Type
- [COUNTERS\\_TEMPLATE](#) (std::vector< std::string >, get\_names)() const
- [COUNTERS\\_TEMPLATE](#) (std::vector< std::string >, get\_descriptions)() const

## Variables

- Data\_Type & [counter\\_](#)
- Data\_Type &&[counter\\_ noexcept](#)
- [uint i](#)
- [uint uint j](#)
- [return \\* this](#)
- Data\_Type [counter](#)
- [return](#)
- Data\_Type [count\\_fun\\_](#)
- Data\_Type [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun\\_](#)
- Data\_Type [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > Data\_Type [data\\_](#)
- Data\_Type [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > Data\_Type std::string [name\\_](#)
- Data\_Type [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > Data\_Type std::string std::string [desc\\_](#)

## 8.26.1 Macro Definition Documentation

### 8.26.1.1 COUNTER\_TEMPLATE

```
#define COUNTER_TEMPLATE(
    a,
    b )  template COUNTER\_TEMPLATE\_ARGS() inline a COUNTER\_TYPE()::b
```

Definition at line 8 of file counters-meat.hpp.

### 8.26.1.2 COUNTER\_TEMPLATE\_ARGS

```
#define COUNTER_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file counters-meat.hpp.

### 8.26.1.3 COUNTER\_TYPE

```
#define COUNTER_TYPE( ) Counter<Array_Type,Data_Type>
```

Definition at line 4 of file counters-meat.hpp.



#### 8.26.1.4 COUNTERS\_TEMPLATE

```
#define COUNTERS_TEMPLATE(  
    a,  
    b )  template COUNTERS_TEMPLATE_ARGS() inline a COUNTERS_TYPE()::b
```

Definition at line 116 of file counters-meat.hpp.

#### 8.26.1.5 COUNTERS\_TEMPLATE\_ARGS

```
#define COUNTERS_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 114 of file counters-meat.hpp.

#### 8.26.1.6 COUNTERS\_TYPE

```
#define COUNTERS_TYPE( ) Counters<Array_Type,Data_Type>
```

Definition at line 112 of file counters-meat.hpp.

### 8.26.2 Function Documentation

#### 8.26.2.1 count\_fun()

```
return count_fun (  
    Array ,  
    i ,  
    j ,  
    data )
```

#### 8.26.2.2 COUNTER\_TEMPLATE() [1/7]

```
COUNTER_TEMPLATE (  
    Counter ) const
```

### 8.26.2.3 COUNTER\_TEMPLATE() [2/7]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() & ,
    operator )
```

### 8.26.2.4 COUNTER\_TEMPLATE() [3/7]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() ,
    operator ) const
```

### 8.26.2.5 COUNTER\_TEMPLATE() [4/7]

```
COUNTER_TEMPLATE (
    double ,
    count ) &
```

< Move assignment

### 8.26.2.6 COUNTER\_TEMPLATE() [5/7]

```
COUNTER_TEMPLATE (
    double ,
    init ) &
```

### 8.26.2.7 COUNTER\_TEMPLATE() [6/7]

```
COUNTER_TEMPLATE (
    std::string ,
    get_description ) const
```

Definition at line 104 of file counters-meat.hpp.

### 8.26.2.8 COUNTER\_TEMPLATE() [7/7]

```
COUNTER_TEMPLATE (
    std::string ,
    get_name ) const
```

Definition at line 100 of file counters-meat.hpp.

### 8.26.2.9 Counters()

```
Data_Type Counters (
    Counters< Array_Type, Data_Type > && counters_ ) [noexcept]
```

Definition at line 130 of file counters-meat.hpp.

### 8.26.2.10 COUNTERS\_TEMPLATE() [1/7]

```
COUNTERS_TEMPLATE (
    Counters )
```

Definition at line 119 of file counters-meat.hpp.

### 8.26.2.11 COUNTERS\_TEMPLATE() [2/7]

```
COUNTERS_TEMPLATE (
    COUNTER_TYPE() & ,
    operator [] )
```

Definition at line 121 of file counters-meat.hpp.

### 8.26.2.12 COUNTERS\_TEMPLATE() [3/7]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() & ,
    operator )
```

### 8.26.2.13 COUNTERS\_TEMPLATE() [4/7]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() ,
    operator ) const
```

### 8.26.2.14 COUNTERS\_TEMPLATE() [5/7]

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 192 of file counters-meat.hpp.

### 8.26.2.15 COUNTERS\_TEMPLATE() [6/7]

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_names  ) const
```

Definition at line 181 of file counters-meat.hpp.

### 8.26.2.16 COUNTERS\_TEMPLATE() [7/7]

```
COUNTERS_TEMPLATE (
    void ,
    add_counter  )
```

### 8.26.2.17 data()

```
Data_Type&& counter_ data (
    std::move(counter_.data)  )
```

### 8.26.2.18 desc()

```
Data_Type&& counter_ desc (
    std::move(counter_.desc)  )
```

Move constructor.

Definition at line 31 of file counters-meat.hpp.

### 8.26.2.19 init\_fun() [1/3]

```
return init_fun (
    Array ,
    i ,
    j ,
    data  )
```

### 8.26.2.20 init\_fun() [2/3]

```
Data_Type init_fun (  
    counter_.  init_fun )
```

Definition at line 13 of file counters-meat.hpp.

### 8.26.2.21 init\_fun() [3/3]

```
Data_Type&& counter_ init_fun (  
    std::move(counter_.init_fun) )
```

### 8.26.2.22 name()

```
Data_Type&& counter_ name (  
    std::move(counter_.name) )
```

## 8.26.3 Variable Documentation

### 8.26.3.1 count\_fun\_

```
Data_Type count_fun_
```

Definition at line 161 of file counters-meat.hpp.

### 8.26.3.2 counter

```
Data_Type counter
```

#### Initial value:

```
{  
    data.push_back(counter)
```

Definition at line 152 of file counters-meat.hpp.

### 8.26.3.3 counter\_

Data\_Type & counter\_

#### Initial value:

```
{
    if (this != &counter_) {
        this->count_fun = counter_.count_fun;
        this->init_fun = counter_.init_fun;

        this->data = counter_.data;
        this->name = counter_.name;
        this->desc = counter_.desc;
    }
    return *this
}
```

Definition at line 12 of file counters-meat.hpp.

### 8.26.3.4 data\_

Data\_Type Counter\_fun\_type<Array\_Type,Data\_Type> Data\_Type data\_

Definition at line 163 of file counters-meat.hpp.

### 8.26.3.5 desc\_

Data\_Type Counter\_fun\_type<Array\_Type,Data\_Type> Data\_Type std::string std::string desc\_

#### Initial value:

```
{
    data.push_back(Counter<Array_Type,Data_Type>(
        count_fun_,
        init_fun_,
        data_,
        name_,
        desc_
    ))
}
```

Definition at line 165 of file counters-meat.hpp.

### 8.26.3.6 i

uint i

Definition at line 80 of file counters-meat.hpp.

### 8.26.3.7 init\_fun\_

Data\_Type Counter\_fun\_type<Array\_Type,Data\_Type> init\_fun\_

Definition at line 162 of file counters-meat.hpp.

### 8.26.3.8 j

uint uint j

#### Initial value:

```
{  
    if (count_fun == nullptr)  
        return 0.0
```

Definition at line 80 of file counters-meat.hpp.

### 8.26.3.9 name\_

Data\_Type Counter\_fun\_type<Array\_Type,Data\_Type> Data\_Type std::string name\_

Definition at line 164 of file counters-meat.hpp.

### 8.26.3.10 noexcept

Data\_Type &&counters\_ noexcept

#### Initial value:

```
{  
    if (this != &counter_)  
    {  
        this->data = std::move(counter_.data);  
  
        this->count_fun = std::move(counter_.count_fun);  
        this->init_fun = std::move(counter_.init_fun);  
  
        this->name = std::move(counter_.name);  
        this->desc = std::move(counter_.desc);  
    }  
    return *this
```

Definition at line 26 of file counters-meat.hpp.

### 8.26.3.11 return

return

Definition at line 157 of file counters-meat.hpp.


### 8.26.3.12 this

```
return* this
```

Definition at line 138 of file counters-meat.hpp.

## 8.27 include/barry/counters/defm.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [DEFMData](#)
- class [DEFMCounterData](#)  
*Data class used to store arbitrary uint or double vectors.*
- class [DEFMRuleData](#)

### Macros

- #define [UNI\\_SUB](#)(a)
- #define [UNI0S](#) \u2080
- #define [UNI1S](#) \u2081
- #define [UNI2S](#) \u2082
- #define [UNI3S](#) \u2083
- #define [UNI4S](#) \u2084
- #define [UNI5S](#) \u2085
- #define [UNI6S](#) \u2086
- #define [UNI7S](#) \u2087
- #define [UNI8S](#) \u2088
- #define [UNI9S](#) \u2089

#### Macros for defining counters

- #define [DEFM\\_COUNTER](#)(a) inline double (a) (const [DEFMArray](#) & Array, uint i, uint j, [DEFMCounterData](#) & data)
- #define [DEFM\\_COUNTER\\_LAMBDA](#)(a)

#### Macros for defining rules

- #define [DEFM\\_RULE](#)(a) inline bool (a) (const [DEFMArray](#) & Array, uint i, uint j, bool & data)
- #define [DEFM\\_RULE\\_LAMBDA](#)(a)



## Typedefs

- typedef [BArrayDense](#)< int, [DEFMData](#) > [DEFMArray](#)

### Convenient typedefs for network objects.

- typedef [Counter](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMCounter](#)
- typedef [Counters](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMCounters](#)
- typedef [Support](#)< [DEFMArray](#), [DEFMCounterData](#), [DEFMRuleData](#) > [DEFMSupport](#)
- typedef [StatsCounter](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMStatsCounter](#)
- typedef [Model](#)< [DEFMArray](#), [DEFMCounterData](#), [DEFMRuleData](#), [DEFMRuleData](#) > [DEFMModel](#)
- typedef [Rule](#)< [DEFMArray](#), [DEFMRuleData](#) > [DEFMRule](#)
- typedef [Rules](#)< [DEFMArray](#), [DEFMRuleData](#) > [DEFMRules](#)

## Functions

- void [counter\\_ones](#) ([DEFMCounters](#) \*counters, int covar\_index=-1, std::string vname="")  
*Prevalence of ones.*
- void [counter\\_transition](#) ([DEFMCounters](#) \*counters, std::vector< size\_t > coords, std::vector< bool > signs, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="")  
*Prevalence of ones.*
- void [counter\\_fixed\\_effect](#) ([DEFMCounters](#) \*counters, int covar\_index, double k, std::string vname="")  
*Prevalence of ones.*

### Returns true if the cell is free

#### Parameters

rules	A pointer to a <a href="#">DEFMRules</a> object ( <a href="#">Rules</a> < <a href="#">DEFMArray</a> , <a href="#">bool</a> >).
-------	--

- void [rules\\_markov\\_fixed](#) ([DEFMRules](#) \*rules, size\_t markov\_order)  
*Number of edges.*

## 8.27.1 Macro Definition Documentation

### 8.27.1.1 DEFM\_COUNTER

```
#define DEFM_COUNTER(  
    a ) inline double (a) (const DEFMArray & Array, uint i, uint j, DEFMCounterData  
    & data)
```

Function for definition of a network counter function

Definition at line 152 of file defm.hpp.

### 8.27.1.2 DEFM\_COUNTER\_LAMBDA

```
#define DEFM_COUNTER_LAMBDA(  
    a )
```

**Value:**

```
Counter_fun_type<DEFMArray, DEFMCOUNTERDATA> a = \  
    [](const DEFMArray & Array, uint i, uint j, DEFMCOUNTERDATA & data)
```

Lambda function for definition of a network counter function

Definition at line 156 of file defm.hpp.

### 8.27.1.3 DEFM\_RULE

```
#define DEFM_RULE(  
    a ) inline bool (a) (const DEFMArray & Array, uint i, uint j, bool & data)
```

Function for definition of a network counter function

Definition at line 167 of file defm.hpp.

### 8.27.1.4 DEFM\_RULE\_LAMBDA

```
#define DEFM_RULE_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<DEFMArray, DEFMRULEDATA> a = \  
    [](const DEFMArray & Array, uint i, uint j, DEFMRULEDATA & data)
```

Lambda function for definition of a network counter function

Definition at line 171 of file defm.hpp.

### 8.27.1.5 UNIOS

```
#define UNIOS \u2080
```

### 8.27.1.6 UNI1S

```
#define UNI1S \u2081
```

#### 8.27.1.7 UNI2S

```
#define UNI2S \u2082
```

#### 8.27.1.8 UNI3S

```
#define UNI3S \u2083
```

#### 8.27.1.9 UNI4S

```
#define UNI4S \u2084
```

#### 8.27.1.10 UNI5S

```
#define UNI5S \u2085
```

#### 8.27.1.11 UNI6S

```
#define UNI6S \u2086
```

#### 8.27.1.12 UNI7S

```
#define UNI7S \u2087
```

#### 8.27.1.13 UNI8S

```
#define UNI8S \u2088
```

#### 8.27.1.14 UNI9S

```
#define UNI9S \u2089
```

### 8.27.1.15 UNI\_SUB

```
#define UNI_SUB(
    a )
```

**Value:**

```
(\
  ((a) == 0) ? "\u2080" : (\
  ((a) == 1) ? "\u2081" : (\
  ((a) == 2) ? "\u2082" : (\
  ((a) == 3) ? "\u2083" : (\
  ((a) == 4) ? "\u2084" : (\
  ((a) == 5) ? "\u2085" : (\
  ((a) == 6) ? "\u2086" : (\
  ((a) == 7) ? "\u2087" : (\
  ((a) == 8) ? "\u2088" : \
  "\u2089")))))))\
)
```

## 8.27.2 Typedef Documentation

### 8.27.2.1 DEFMArrray

```
typedef BArrayDense<int, DEFMDData> DEFMArrray
```

Definition at line 23 of file defm.hpp.

### 8.27.2.2 DEFMCounter

```
typedef Counter<DEFMArrray, DEFMCounterData > DEFMCounter
```

Definition at line 116 of file defm.hpp.

### 8.27.2.3 DEFMCounters

```
typedef Counters<DEFMArrray, DEFMCounterData> DEFMCounters
```

Definition at line 117 of file defm.hpp.

### 8.27.2.4 DEFMModel

```
typedef Model<DEFMArrray, DEFMCounterData, DEFMRuleData, DEFMRuleData> DEFMModel
```

Definition at line 120 of file defm.hpp.

### 8.27.2.5 DEFMRule

```
typedef Rule<DEFMArray, DEFMRuleData> DEFMRule
```

Definition at line 121 of file defm.hpp.

### 8.27.2.6 DEFMRules

```
typedef Rules<DEFMArray, DEFMRuleData> DEFMRules
```

Definition at line 122 of file defm.hpp.

### 8.27.2.7 DEFMStatsCounter

```
typedef StatsCounter<DEFMArray, DEFMCounterData> DEFMStatsCounter
```

Definition at line 119 of file defm.hpp.

### 8.27.2.8 DEFMSupport

```
typedef Support<DEFMArray, DEFMCounterData, DEFMRuleData> DEFMSupport
```


Definition at line 118 of file defm.hpp.

## 8.28 include/barry/models/defm.hpp File Reference

```
#include "defm/defm-bones.hpp"
```


```
#include "defm/defm-meat.hpp"
```

Include dependency graph for defm.hpp:



## 8.29 include/barry/counters/network-css.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define CSS_SIZE()`
- `#define CSS_CASE_TRUTH() if ((i < n) && (j < n))`
- `#define CSS_TRUE_CELLS()`
- `#define CSS_CASE_PERCEIVED() else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))`
- `#define CSS_PERCEIVED_CELLS()`
- `#define CSS_CASE_ELSE()`
- `#define CSS_CHECK_SIZE_INIT()`
- `#define CSS_CHECK_SIZE()`
- `#define CSS_APPEND(name)`
- `#define CSS_NET_COUNTER_LAMBDA_INIT()`

### Functions

- `template<typename Tnet = Network>`  
`void counter_css_partially_false_recip_commi (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`  
*Counts errors of commission.*
- `template<typename Tnet = Network>`  
`void counter_css_partially_false_recip_omiss (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`  
*Counts errors of omission.*
- `template<typename Tnet = Network>`  
`void counter_css_completely_false_recip_comiss (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`  
*Counts completely false reciprocity (comission)*

- `template<typename Tnet = Network>`  
`void counter_css_completely_false_recip_omiss (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`  
*Counts completely false reciprocity (omission)*
- `template<typename Tnet = Network>`  
`void counter_css_mixed_recip (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`  
*Counts mixed reciprocity errors.*
- `template<typename Tnet = Network>`  
`void counter_css_census01 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census02 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census03 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census04 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census05 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census06 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census07 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census08 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census09 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`
- `template<typename Tnet = Network>`  
`void counter_css_census10 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_)`

## 8.29.1 Macro Definition Documentation

### 8.29.1.1 CSS\_APPEND

```
#define CSS_APPEND(  
    name )
```

#### Value:

```
std::string name_ = (name);\nfor (uint i = 0u; i < end_.size(); ++i) { \n\n    std::string tmpname = name_ + " (" + std::to_string(i) + ")";\n    counters->add_counter(tmp_count, tmp_init,\n        NetCounterData({netsize, i == 0u ? netsize : end_[i-1], end_[i]}, {}),\n        tmpname); }
```

Definition at line 42 of file network-css.hpp.

### 8.29.1.2 CSS\_CASE\_ELSE

```
#define CSS_CASE_ELSE( )
```

Definition at line 27 of file network-css.hpp.

### 8.29.1.3 CSS\_CASE\_PERCEIVED

```
#define CSS_CASE_PERCEIVED( ) else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))
```

Definition at line 20 of file network-css.hpp.

### 8.29.1.4 CSS\_CASE\_TRUTH

```
#define CSS_CASE_TRUTH( ) if ((i < n) && (j < n))
```

Definition at line 13 of file network-css.hpp.

### 8.29.1.5 CSS\_CHECK\_SIZE

```
#define CSS_CHECK_SIZE( )
```

**Value:**

```
for (uint i = 0u; i < end_.size(); ++i) {\
  if (i == 0u) continue; \
  else if (end_[i] < end_[i-1u]) \
    throw std::logic_error("Endpoints should be specified in order.");}
```

Definition at line 37 of file network-css.hpp.

### 8.29.1.6 CSS\_CHECK\_SIZE\_INIT

```
#define CSS_CHECK_SIZE_INIT( )
```

**Value:**

```
/* The indices fall within the network */ \
if ((data.indices.at(0) > Array.ncol()) \
| (data.indices.at(2) > Array.ncol())) \
  throw std::range_error("The network does not match the prescribed size.");
```

Definition at line 31 of file network-css.hpp.



### 8.29.1.7 CSS\_NET\_COUNTER\_LAMBDA\_INIT

```
#define CSS_NET_COUNTER_LAMBDA_INIT( )
```

**Value:**

```
NETWORK_COUNTER_LAMBDA(tmp_init) {\n    CSS_CHECK_SIZE_INIT() \n    return 0.0; \n};
```

Definition at line 49 of file network-css.hpp.

### 8.29.1.8 CSS\_PERCEIVED\_CELLS

```
#define CSS_PERCEIVED_CELLS( )
```

**Value:**

```
double tji = static_cast<double>(Array(j - s, i - s, false)); \ndouble pji = static_cast<double>(Array(j, i, false)); \ndouble tij = static_cast<double>(Array(i - s, j - s, false));
```

Definition at line 21 of file network-css.hpp.

### 8.29.1.9 CSS\_SIZE

```
#define CSS_SIZE( )
```

**Value:**

```
uint n = data.indices[0u]; \nuint s = data.indices[1u]; \nuint e = data.indices[2u];
```

Definition at line 7 of file network-css.hpp.

### 8.29.1.10 CSS\_TRUE\_CELLS

```
#define CSS_TRUE_CELLS( )
```

**Value:**

```
double tji = static_cast<double>(Array(j, i, false)); \ndouble pij = static_cast<double>(Array(i + s, j + s, false)); \ndouble pji = static_cast<double>(Array(j + s, i + s, false));
```

Definition at line 14 of file network-css.hpp.

## 8.29.2 Function Documentation

### 8.29.2.1 counter\_css\_census01()

```
template<typename Tnet = Network>
void counter_css_census01 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 275 of file network-css.hpp.

### 8.29.2.2 counter\_css\_census02()

```
template<typename Tnet = Network>
void counter_css_census02 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 325 of file network-css.hpp.

### 8.29.2.3 counter\_css\_census03()

```
template<typename Tnet = Network>
void counter_css_census03 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 364 of file network-css.hpp.

### 8.29.2.4 counter\_css\_census04()

```
template<typename Tnet = Network>
void counter_css_census04 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 403 of file network-css.hpp.

### 8.29.2.5 counter\_css\_census05()

```
template<typename Tnet = Network>
void counter_css_census05 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 442 of file network-css.hpp.

### 8.29.2.6 counter\_css\_census06()

```
template<typename Tnet = Network>
void counter_css_census06 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 481 of file network-css.hpp.

### 8.29.2.7 counter\_css\_census07()

```
template<typename Tnet = Network>
void counter_css_census07 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 520 of file network-css.hpp.

### 8.29.2.8 counter\_css\_census08()

```
template<typename Tnet = Network>
void counter_css_census08 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 559 of file network-css.hpp.

### 8.29.2.9 counter\_css\_census09()

```
template<typename Tnet = Network>
void counter_css_census09 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 598 of file network-css.hpp.

### 8.29.2.10 counter\_css\_census10()

```
template<typename Tnet = Network>
void counter_css_census10 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 637 of file network-css.hpp.

### 8.29.2.11 counter\_css\_completely\_false\_recip\_comiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_comiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts completely false reciprocity (comission)

Definition at line 154 of file network-css.hpp.

### 8.29.2.12 counter\_css\_completely\_false\_recip\_omiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_omiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts completely false reciprocity (omission)

Definition at line 194 of file network-css.hpp.

**8.29.2.13 counter\_css\_mixed\_recip()**

```
template<typename Tnet = Network>
void counter_css_mixed_recip (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts mixed reciprocity errors.

Definition at line 234 of file network-css.hpp.

**8.29.2.14 counter\_css\_partially\_false\_recip\_commi()**

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_commi (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts errors of commission.

**Parameters**

<i>netsize</i>	Size of the reference (true) network
<i>end_</i> —	Vector indicating one past the ending index of each network. (see details)

The *end\_* parameter should be of length *N* of *networks* - 1. It is assumed that the first network ends at *netsize*.

Definition at line 63 of file network-css.hpp.

**8.29.2.15 counter\_css\_partially\_false\_recip\_omiss()**

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_omiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```


Counts errors of omission.

Definition at line 110 of file network-css.hpp.


## 8.30 include/barry/counters/network.hpp File Reference

```
#include "network-css.hpp"
```

Include dependency graph for network.hpp:



This graph shows which files directly or indirectly include this file:



### Classes

- class [NetworkData](#)  
*Data class for Networks.*
- class [NetCounterData](#)  
*Data class used to store arbitrary uint or double vectors.*

### Macros

- #define [NET\\_C\\_DATA\\_IDX\(i\)](#) (data.indices[i])
- #define [NET\\_C\\_DATA\\_NUM\(i\)](#) (data.numbers[i])

### Macros for defining counters

- #define `NETWORK_COUNTER(a)`
- #define `NETWORK_COUNTER_LAMBDA(a)`
- #define `NETWORKDENSE_COUNTER_LAMBDA(a)`

### Macros for defining rules

- #define `NETWORK_RULE(a)`
- #define `NETWORK_RULE_LAMBDA(a)`

## Functions

- template<typename Tnet = Network>  
void `counter_edges` (NetCounters< Tnet > \*counters)  
*Number of edges.*
- template<typename Tnet = Network>  
void `counter_isolates` (NetCounters< Tnet > \*counters)  
*Number of isolated vertices.*
- template<> void `counter_isolates` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_mutual` (NetCounters< Tnet > \*counters)  
*Number of mutual ties.*
- template<typename Tnet = Network>  
void `counter_istar2` (NetCounters< Tnet > \*counters)
- template<> void `counter_istar2` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_ostar2` (NetCounters< Tnet > \*counters)
- template<> void `counter_ostar2` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_ttriads` (NetCounters< Tnet > \*counters)
- template<> void `counter_ttriads` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_ctriads` (NetCounters< Tnet > \*counters)
- template<> void `counter_ctriads` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_density` (NetCounters< Tnet > \*counters)
- template<typename Tnet = Network>  
void `counter_idegree15` (NetCounters< Tnet > \*counters)
- template<> void `counter_idegree15` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_odegree15` (NetCounters< Tnet > \*counters)
- template<> void `counter_odegree15` (NetCounters< NetworkDense > \*counters)
- template<typename Tnet = Network>  
void `counter_absdiff` (NetCounters< Tnet > \*counters, uint attr\_id, double alpha=1.0)  
*Sum of absolute attribute difference between ego and alter.*
- template<typename Tnet = Network>  
void `counter_diff` (NetCounters< Tnet > \*counters, uint attr\_id, double alpha=1.0, double tail\_head=true)  
*Sum of attribute difference between ego and alter to pow(alpha)*
- `NETWORK_COUNTER` (init\_single\_attr)
- template<typename Tnet = Network>  
void `counter_nodeicov` (NetCounters< Tnet > \*counters, uint attr\_id)
- template<typename Tnet = Network>  
void `counter_nodeocov` (NetCounters< Tnet > \*counters, uint attr\_id)

- `template<typename Tnet = Network>`  
`void counter_nodecov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodematch (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_idgree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given in-degree.*
- `template<> void counter_idgree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_degree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*

### Rules for network models

#### Parameters

rules	A pointer to a <i>NetRules</i> object ( <i>Rules&lt;Network, bool&gt;</i> ).
-------	--

- `template<typename Tnet = Network>`  
`void rules_zerodiag (NetRules< Tnet > *rules)`  
*Number of edges.*

### Convenient typedefs for network objects.

- `#define BARRY_ZERO_NETWORK 0.0`
- `#define BARRY_ZERO_NETWORK_DENSE 0`
- `typedef BArray< double, NetworkData > Network`
- `typedef BArrayDense< int, NetworkData > NetworkDense`
- `template<typename Tnet = Network>`  
`using NetCounter = Counter< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetCounters = Counters< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetSupport = Support< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetStatsCounter = StatsCounter< Tnet, NetCounterData >`
- `template<typename Tnet >`  
`using NetModel = Model< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetRule = Rule< Tnet, bool >`
- `template<typename Tnet = Network>`  
`using NetRules = Rules< Tnet, bool >`

## 8.30.1 Macro Definition Documentation



### 8.30.1.1 BARRY\_ZERO\_NETWORK

```
#define BARRY_ZERO_NETWORK 0.0
```

Definition at line 85 of file network.hpp.

### 8.30.1.2 BARRY\_ZERO\_NETWORK\_DENSE

```
#define BARRY_ZERO_NETWORK_DENSE 0
```

Definition at line 86 of file network.hpp.

### 8.30.1.3 NET\_C\_DATA\_IDX

```
#define NET_C_DATA_IDX(  
    i ) (data.indices[i])
```

Definition at line 74 of file network.hpp.

### 8.30.1.4 NET\_C\_DATA\_NUM

```
#define NET_C_DATA_NUM(  
    i ) (data.numbers[i])
```

Definition at line 75 of file network.hpp.

### 8.30.1.5 NETWORK\_COUNTER

```
#define NETWORK_COUNTER(  
    a )
```

#### Value:

```
template<typename Tnet = Network>\ninline double (a) (const Tnet & Array, uint i, uint j, NetCounterData & data)
```

Function for definition of a network counter function

Definition at line 114 of file network.hpp.

### 8.30.1.6 NETWORK\_COUNTER\_LAMBDA

```
#define NETWORK_COUNTER_LAMBDA(  
    a )
```

**Value:**

```
Counter_fun_type<Tnet, NetCounterData> a = \  
    [] (const Tnet & Array, uint i, uint j, NetCounterData & data)
```

Lambda function for definition of a network counter function

Definition at line 119 of file network.hpp.

### 8.30.1.7 NETWORK\_RULE

```
#define NETWORK_RULE(  
    a )
```

**Value:**

```
template<typename Tnet = Network>\  
inline bool (a) (const Tnet & Array, uint i, uint j, bool & data)
```

Function for definition of a network counter function

Definition at line 133 of file network.hpp.

### 8.30.1.8 NETWORK\_RULE\_LAMBDA

```
#define NETWORK_RULE_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<Tnet, bool> a = \  
    [] (const Tnet & Array, uint i, uint j, bool & data)
```

Lambda function for definition of a network counter function

Definition at line 138 of file network.hpp.

### 8.30.1.9 NETWORKDENSE\_COUNTER\_LAMBDA

```
#define NETWORKDENSE_COUNTER_LAMBDA(  
    a )
```

**Value:**

```
Counter_fun_type<NetworkDense, NetCounterData> a = \  
    [] (const NetworkDense & Array, uint i, uint j, NetCounterData & data)
```

Definition at line 123 of file network.hpp.

## 8.30.2 Typedef Documentation

### 8.30.2.1 NetCounter

```
template<typename Tnet = Network>  
using NetCounter = Counter<Tnet, NetCounterData >
```

Definition at line 89 of file network.hpp.

### 8.30.2.2 NetCounters

```
template<typename Tnet = Network>  
using NetCounters = Counters<Tnet, NetCounterData>
```

Definition at line 92 of file network.hpp.

### 8.30.2.3 NetModel

```
template<typename Tnet >  
using NetModel = Model<Tnet, NetCounterData>
```

Definition at line 101 of file network.hpp.

### 8.30.2.4 NetRule

```
template<typename Tnet = Network>  
using NetRule = Rule<Tnet, bool>
```

Definition at line 104 of file network.hpp.

### 8.30.2.5 NetRules

```
template<typename Tnet = Network>  
using NetRules = Rules<Tnet, bool>
```

Definition at line 107 of file network.hpp.

### 8.30.2.6 NetStatsCounter

```
template<typename Tnet = Network>
using NetStatsCounter = StatsCounter<Tnet, NetCounterData>
```

Definition at line 98 of file network.hpp.

### 8.30.2.7 NetSupport

```
template<typename Tnet = Network>
using NetSupport = Support<Tnet, NetCounterData >
```

Definition at line 95 of file network.hpp.

### 8.30.2.8 Network

```
typedef BArray<double, NetworkData> Network
```

Definition at line 82 of file network.hpp.

### 8.30.2.9 NetworkDense

```
typedef BArrayDense<int, NetworkData> NetworkDense
```

Definition at line 83 of file network.hpp.

## 8.30.3 Function Documentation

### 8.30.3.1 rules\_zerodiag()


```
template<typename Tnet = Network>
void rules_zerodiag (
    NetRules< Tnet > * rules ) [inline]
```

Number of edges.

Definition at line 1383 of file network.hpp.

## 8.31 include/barry/counters/phylo.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [NodeData](#)  
*Data definition for the `PhyloArray` class.*
- class [PhyloCounterData](#)
- class [PhyloRuleDynData](#)

### Macros

- `#define` [DEFAULT\\_DUPLICATION](#) 1u
- `#define` [DUPL\\_SPEC](#) 0u
- `#define` [DUPL\\_DUPL](#) 1u
- `#define` [DUPL\\_EITH](#) 2u
- `#define` [MAKE\\_DUPL\\_VARS](#)()
- `#define` [IS\\_EITHER](#)() (DATA\_AT == [DUPL\\_EITH](#))
- `#define` [IS\\_DUPLICATION](#)() ((DATA\_AT == [DUPL\\_DUPL](#)) & (DPL))
- `#define` [IS\\_SPECIATION](#)() ((DATA\_AT == [DUPL\\_SPEC](#)) & (!DPL))
- `#define` [IF\\_MATCHES](#)()
- `#define` [IF\\_NOTMATCHES](#)()
- `#define` [PHYLO\\_COUNTER\\_LAMBDA](#)(a)  
*Extension of a simple counter.*
- `#define` [PHYLO\\_RULE\\_DYN\\_LAMBDA](#)(a)
- `#define` [PHYLO\\_CHECK\\_MISSING](#)()

### Typedefs

- `typedef std::vector< std::pair< uint, uint > > PhyloRuleData`

### Convenient typedefs for Node objects.

- typedef [BArrayDense](#)< [uint](#), [NodeData](#) > [PhyloArray](#)
- typedef [Counter](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounter](#)
- typedef [Counters](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounters](#)
- typedef [Rule](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRule](#)
- typedef [Rules](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRules](#)
- typedef [Rule](#)< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRuleDyn](#)
- typedef [Rules](#)< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRulesDyn](#)
- typedef [Support](#)< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloSupport](#)
- typedef [StatsCounter](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloStatsCounter](#)
- typedef [Model](#)< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloModel](#)
- typedef [PowerSet](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloPowerSet](#)

### Functions

- std::string [get\\_last\\_name](#) (unsigned int d)
- void [counter\\_overall\\_gains](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Overall functional gains.*
- void [counter\\_gains](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Functional gains for a specific function (nfun).*
- void [counter\\_gains\\_k\\_offspring](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, [uint](#) k=1u, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*k genes gain function nfun*
- void [counter\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- void [counter\\_preserve\\_pseudogene](#) ([PhyloCounters](#) \*counters, unsigned int nfunA, unsigned int nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Keeps track of how many pairs of genes preserve pseudostate.*
- void [counter\\_prop\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- void [counter\\_overall\\_loss](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Overall functional loss.*
- void [counter\\_maxfuns](#) ([PhyloCounters](#) \*counters, [uint](#) lb, [uint](#) ub, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Cap the number of functions per gene.*
- void [counter\\_loss](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total count of losses for an specific function.*
- void [counter\\_overall\\_changes](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total number of changes. Use this statistic to account for "preservation".*
- void [counter\\_subfun](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, [uint](#) nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total count of Sub-functionalization events.*
- void [counter\\_cogain](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, [uint](#) nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Co-evolution (joint gain or loss)*
- void [counter\\_longest](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Longest branch mutates (either by gain or by loss)*
- void [counter\\_neofun](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, [uint](#) nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total number of neofunctionalization events.*
- void [counter\\_pairwise\\_neofun\\_singlefun](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total number of neofunctionalization events  $\sum_u \sum_{\{w < u\}} [x(u,a) * (1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$  change  
stat:  $\delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void [counter\\_neofun\\_a2b](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, [uint](#) nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))  
*Total number of neofunctionalization events.*
- void [counter\\_co\\_opt](#) ([PhyloCounters](#) \*counters, [uint](#) nfunA, [uint](#) nfunB, unsigned int duplication=[DEFAULT\\_DUPPLICATION](#))

*Function co-opting.*

- void `counter_k_genes_changing` (PhyloCounters \*counters, unsigned int k, unsigned int duplication=DEFAULT\_DUPLICATION)

*Indicator function. Equals to one if k genes changed and zero otherwise.*

- void `counter_less_than_p_prop_genes_changing` (PhyloCounters \*counters, double p, unsigned int duplication=DEFAULT\_DUPLICATION)

*Indicator function. Equals to one if k genes changed and zero otherwise.*

- void `counter_gains_from_0` (PhyloCounters \*counters, std::vector< uint > nfun, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_overall_gains_from_0` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_pairwise_overall_change` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_pairwise_preserving` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_pairwise_first_gain` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `rule_dyn_limit_changes` (PhyloSupport \*support, uint pos, uint lb, uint ub, unsigned int duplication=DEFAULT\_DUPLICATION)

*Overall functional gains.*

## 8.31.1 Macro Definition Documentation

### 8.31.1.1 DEFAULT\_DUPLICATION

```
#define DEFAULT_DUPLICATION 1u
```

Definition at line 5 of file phylo.hpp.

### 8.31.1.2 DUPL\_DUPL

```
#define DUPL_DUPL 1u
```

Definition at line 7 of file phylo.hpp.

### 8.31.1.3 DUPL\_EITH

```
#define DUPL_EITH 2u
```

Definition at line 8 of file phylo.hpp.

#### 8.31.1.4 DUPL\_SPEC

```
#define DUPL_SPEC 0u
```

Definition at line 6 of file phylo.hpp.

#### 8.31.1.5 IF\_MATCHES

```
#define IF_MATCHES( )
```

**Value:**

```
MAKE_DUPL_VARS() \
if (IS_EITHER() | IS_DUPLICATION() | IS_SPECIATION())
```

Definition at line 19 of file phylo.hpp.

#### 8.31.1.6 IF\_NOTMATCHES

```
#define IF_NOTMATCHES( )
```

**Value:**

```
MAKE_DUPL_VARS() \
if (!IS_EITHER() & !IS_DUPLICATION() & !IS_SPECIATION())
```

Definition at line 21 of file phylo.hpp.

#### 8.31.1.7 IS\_DUPLICATION

```
#define IS_DUPLICATION( ) ((DATA_AT == DUPL_DUPL) & (DPL))
```

Definition at line 16 of file phylo.hpp.

#### 8.31.1.8 IS\_EITHER

```
#define IS_EITHER( ) (DATA_AT == DUPL_EITH)
```

Definition at line 15 of file phylo.hpp.



### 8.31.1.9 IS\_SPECIATION

```
#define IS_SPECIATION( ) ((DATA_AT == DUPL_SPEC) & (!DPL))
```

Definition at line 17 of file phylo.hpp.

### 8.31.1.10 MAKE\_DUPL\_VARS

```
#define MAKE_DUPL_VARS( )
```

**Value:**

```
bool DPL = Array.D_ptr()->duplication; \  
unsigned int DATA_AT = data[0u];
```

Definition at line 11 of file phylo.hpp.

### 8.31.1.11 PHYLO\_CHECK\_MISSING

```
#define PHYLO_CHECK_MISSING( )
```

**Value:**

```
if (Array.D_ptr() == nullptr) \  
throw std::logic_error("The array data is nullptr."); \  

```

Definition at line 139 of file phylo.hpp.

### 8.31.1.12 PHYLO\_COUNTER\_LAMBDA

```
#define PHYLO_COUNTER_LAMBDA(  
    a )
```

**Value:**

```
Counter_fun_type<PhyloArray, PhyloCounterData> a = \  
[] (const PhyloArray & Array, uint i, uint j, PhyloCounterData & data)
```

Extension of a simple counter.

It allows specifying extra arguments, in particular, the corresponding sets of rows to which this statistic may be relevant. This could be important in the case of, for example, counting correlation type statistics between function 1 and 2, and between function 1 and 3.

Definition at line 133 of file phylo.hpp.

### 8.31.1.13 PHYLO\_RULE\_DYN\_LAMBDA

```
#define PHYLO_RULE_DYN_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<PhyloArray, PhyloRuleDynData> a = \  
[] (const PhyloArray & Array, uint i, uint j, PhyloRuleDynData & data)
```

Definition at line 136 of file phylo.hpp.

## 8.31.2 Typedef Documentation

### 8.31.2.1 PhyloArray

```
typedef BArrayDense<uint, NodeData> PhyloArray
```

Definition at line 106 of file phylo.hpp.

### 8.31.2.2 PhyloCounter

```
typedef Counter<PhyloArray, PhyloCounterData > PhyloCounter
```

Definition at line 107 of file phylo.hpp.

### 8.31.2.3 PhyloCounters

```
typedef Counters< PhyloArray, PhyloCounterData> PhyloCounters
```

Definition at line 108 of file phylo.hpp.

### 8.31.2.4 PhyloModel

```
typedef Model<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloModel
```

Definition at line 118 of file phylo.hpp.

### 8.31.2.5 PhyloPowerSet

```
typedef PowerSet<PhyloArray, PhyloRuleData> PhyloPowerSet
```

Definition at line 119 of file phylo.hpp.

### 8.31.2.6 PhyloRule

```
typedef Rule<PhyloArray,PhyloRuleData> PhyloRule
```

Definition at line 110 of file phylo.hpp.

### 8.31.2.7 PhyloRuleData

```
typedef std::vector< std::pair< uint, uint > > PhyloRuleData
```

Definition at line 99 of file phylo.hpp.

### 8.31.2.8 PhyloRuleDyn

```
typedef Rule<PhyloArray,PhyloRuleDynData> PhyloRuleDyn
```

Definition at line 113 of file phylo.hpp.

### 8.31.2.9 PhyloRules

```
typedef Rules<PhyloArray,PhyloRuleData> PhyloRules
```

Definition at line 111 of file phylo.hpp.

### 8.31.2.10 PhyloRulesDyn

```
typedef Rules<PhyloArray,PhyloRuleDynData> PhyloRulesDyn
```

Definition at line 114 of file phylo.hpp.

### 8.31.2.11 PhyloStatsCounter

```
typedef StatsCounter<PhyloArray, PhyloCounterData> PhyloStatsCounter
```

Definition at line 117 of file phylo.hpp.

### 8.31.2.12 PhyloSupport

```
typedef Support<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloSupport
```

Definition at line 116 of file phylo.hpp.

## 8.31.3 Function Documentation


### 8.31.3.1 get\_last\_name()

```
std::string get_last_name (
    unsigned int d ) [inline]
```

Definition at line 142 of file phylo.hpp.

## 8.32 include/barry/freqtable.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class `FreqTable< T >`  
*Frequency table of vectors.*

## 8.33 include/barry/model-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [Model< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#)

*General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:*

### Functions

- `template<typename Array_Type >`  
`std::vector< double > keygen\_default (const Array_Type &Array\_)`

*Array Hasher class (used for computing support)*

#### 8.33.1 Function Documentation

##### 8.33.1.1 [keygen\\_default\(\)](#)


```
template<typename Array_Type >
std::vector< double > keygen_default (
    const Array_Type & Array_ ) [inline]
```

Array Hasher class (used for computing support)

Definition at line 9 of file model-bones.hpp.

## 8.34 include/barry/model-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define MODEL_TYPE()`
- `#define MODEL_TEMPLATE_ARGS()`
- `#define MODEL_TEMPLATE(a, b) template MODEL_TEMPLATE_ARGS() inline a MODEL_TYPE()::b`

### Functions

- `double update_normalizing_constant(const double *params, const double *support, size_t k, size_t n)`
- `double likelihood_(const double *stats_target, const std::vector< double > &params, const double normalizing_constant, size_t n_params, bool log_=false)`
- `MODEL_TEMPLATE(, Model)()`
- `MODEL_TEMPLATE(, Model)(const MODEL_TYPE() &Model_)`

### 8.34.1 Macro Definition Documentation

#### 8.34.1.1 MODEL\_TEMPLATE

```

#define MODEL_TEMPLATE(
    a,
    b )  template MODEL_TEMPLATE_ARGS() inline a MODEL_TYPE()::b
  
```

Definition at line 87 of file model-meat.hpp.

### 8.34.1.2 MODEL\_TEMPLATE\_ARGS

```
#define MODEL_TEMPLATE_ARGS( )
```

**Value:**

```
<typename Array_Type, typename Data_Counter_Type,\  
    typename Data_Rule_Type, typename Data_Rule_Dyn_Type>
```

Definition at line 84 of file model-meat.hpp.

### 8.34.1.3 MODEL\_TYPE

```
#define MODEL_TYPE( )
```

**Value:**

```
Model<Array_Type, Data_Counter_Type, Data_Rule_Type,\  
    Data_Rule_Dyn_Type>
```

Definition at line 81 of file model-meat.hpp.

## 8.34.2 Function Documentation

### 8.34.2.1 likelihood\_()

```
double likelihood_ (  
    const double * stats_target,  
    const std::vector< double > & params,  
    const double normalizing_constant,  
    size_t n_params,  
    bool log_ = false ) [inline]
```

Definition at line 45 of file model-meat.hpp.

### 8.34.2.2 MODEL\_TEMPLATE() [1/2]

```
MODEL_TEMPLATE (  
    Model )
```

Definition at line 91 of file model-meat.hpp.

### 8.34.2.3 MODEL\_TEMPLATE() [2/2]

```
MODEL_TEMPLATE (
    Model ) const &
```

Definition at line 155 of file model-meat.hpp.


### 8.34.2.4 update\_normalizing\_constant()

```
double update_normalizing_constant (
    const double * params,
    const double * support,
    size_t k,
    size_t n ) [inline]
```

Definition at line 9 of file model-meat.hpp.

## 8.35 include/barry/models/defm/defm-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [DEFM](#)



## 8.36 include/barry/models/defm/defm-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define` [DEFM\\_RANGES](#)(a)
- `#define` [DEFM\\_LOOP\\_ARRAYS](#)(a) `for` (size\_t a = 0u; a < (nobs\_i - M\_order); ++a)

### Functions

- `std::vector< double >` [keygen\\_defm](#) (const defmcounters::DEFMArray &Array\_)

## 8.36.1 Macro Definition Documentation

### 8.36.1.1 DEFM\_LOOP\_ARRAYS

```
#define DEFM_LOOP_ARRAYS(
    a )    for (size_t a = 0u; a < (nobs_i - M_order); ++a)
```

Definition at line 41 of file defm-meat.hpp.

### 8.36.1.2 DEFM\_RANGES

```
#define DEFM_RANGES(
    a )
```

#### Value:

```
size_t __CONCAT(start_,a) = start_end[a * 2u];\
size_t __CONCAT(end_,a)   = start_end[a * 2u + 1u];\
size_t __CONCAT(nobs_,a)  = __CONCAT(end_,i) - __CONCAT(start_,i) + 1u;
```

Definition at line 36 of file defm-meat.hpp.

## 8.36.2 Function Documentation

### 8.36.2.1 keygen\_defm()

```
std::vector< double > keygen_defm (
    const defmcounters::DEFMArray & Array_ ) [inline]
```

Definition at line 4 of file defm-meat.hpp.

## 8.37 include/barry/models/geese.hpp File Reference


```
#include "geese/geese-node-bones.hpp"
#include "geese/geese-bones.hpp"
#include "geese/geese-meat.hpp"
#include "geese/geese-meat-constructors.hpp"
#include "geese/geese-meat-likelihood.hpp"
#include "geese/geese-meat-likelihood_exhaust.hpp"
#include "geese/geese-meat-simulate.hpp"
#include "geese/geese-meat-predict.hpp"
#include "geese/geese-meat-predict_exhaust.hpp"
#include "geese/geese-meat-predict_sim.hpp"
#include "geese/flock-bones.hpp"
#include "geese/flock-meat.hpp"
```

Include dependency graph for geese.hpp:



## 8.38 include/barry/models/geese/flock-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [Flock](#)

A [Flock](#) is a group of [Geese](#).


## 8.39 include/barry/models/geese/flock-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.40 include/barry/models/geese/geese-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Classes

- class [Geese](#)  
*Annotated Phylo [Model](#).*

## Macros

- `#define` [INITIALIZED\(\)](#)

## Functions

- `template<typename Ta , typename Tb >`  
  `std::vector< Ta > vector\_caster (const std::vector< Tb > &x)`
- [RULE\\_FUNCTION](#) (rule\_empty\_free)
- `std::vector< double > keygen\_full (const phylocounters::PhyloArray &array)`
- `bool vec\_diff (const std::vector< unsigned int > &s, const std::vector< unsigned int > &a)`

### 8.40.1 Macro Definition Documentation

#### 8.40.1.1 INITIALIZED

```
#define INITIALIZED( )
```

##### Value:

```
if (!this->initialized) \
    throw std::logic_error("The model has not been initialized yet.");
```

Definition at line 22 of file geese-bones.hpp.

### 8.40.2 Function Documentation

#### 8.40.2.1 keygen\_full()

```
std::vector< double > keygen_full (
    const phylocounters::PhyloArray & array ) [inline]
```

Definition at line 35 of file geese-bones.hpp.

### 8.40.2.2 RULE\_FUNCTION()

```
RULE_FUNCTION (
    rule_empty_free )
```

Definition at line 26 of file geese-bones.hpp.

### 8.40.2.3 vec\_diff()

```
bool vec_diff (
    const std::vector< unsigned int > & s,
    const std::vector< unsigned int > & a ) [inline]
```

Definition at line 59 of file geese-bones.hpp.


### 8.40.2.4 vector\_caster()

```
template<typename Ta , typename Tb >
std::vector< Ta > vector_caster (
    const std::vector< Tb > & x ) [inline]
```

Definition at line 10 of file geese-bones.hpp.

## 8.41 include/barry/models/geese/geese-meat-constructors.hpp File Reference


This graph shows which files directly or indirectly include this file:




## 8.42 include/barry/models/geese/geese-meat-likelihood.hpp File Reference

```
#include "geese-bones.hpp"
```

Include dependency graph for geese-meat-likelihood.hpp:




This graph shows which files directly or indirectly include this file:




## 8.43 include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 8.44 include/barry/models/geese/geese-meat-predict.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 8.45 include/barry/models/geese/geese-meat-predict\_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.46 include/barry/models/geese/geese-meat-predict\_sim.hpp File Reference


This graph shows which files directly or indirectly include this file:






## 8.47 include/barry/models/geese/geese-meat-simulate.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 8.48 include/barry/models/geese/geese-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.49 include/barry/models/geese/geese-node-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [Node](#)  
*A single node for the model.*

## 8.50 include/barry/powerset-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [PowerSet< Array\\_Type, Data\\_Rule\\_Type >](#)  
*Powerset of a binary array.*


## 8.51 include/barry/powerset-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.52 include/barry/progress.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [Progress](#)  
*A simple progress bar.*

### Macros

- #define [BARRY\\_PROGRESS\\_BAR\\_WIDTH](#) 80

## 8.52.1 Macro Definition Documentation


### 8.52.1.1 BARRY\_PROGRESS\_BAR\_WIDTH

```
#define BARRY_PROGRESS_BAR_WIDTH 80
```

Definition at line 5 of file progress.hpp.

## 8.53 include/barry/rules-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Classes

- class [Rule< Array\\_Type, Data\\_Type >](#)  
*[Rule](#) for determining if a cell should be included in a sequence.*
- class [Rules< Array\\_Type, Data\\_Type >](#)  
*Vector of objects of class [Rule](#).*

## Functions

- template<typename Array\_Type , typename Data\_Type >  
bool [rule\\_fun\\_default](#) (const Array\_Type \*array, uint i, uint j, Data\_Type \*dat)

### 8.53.1 Function Documentation


### 8.53.1.1 rule\_fun\_default()

```
template<typename Array_Type , typename Data_Type >
bool rule_fun_default (
    const Array_Type * array,
    uint i,
    uint j,
    Data_Type * dat )
```

Definition at line 5 of file rules-bones.hpp.


## 8.54 include/barry/rules-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 8.55 include/barry/statscounter-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [StatsCounter< Array\\_Type, Data\\_Type >](#)  
*Count stats for a single Array.*

## 8.56 include/barry/statscounter-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- #define [STATSCOUNTER\\_TYPE\(\)](#) [StatsCounter<Array\\_Type,Data\\_Type>](#)
- #define [STATSCOUNTER\\_TEMPLATE\\_ARGS\(\)](#) <typename Array\_Type, typename Data\_Type>
- #define [STATSCOUNTER\\_TEMPLATE\(a, b\)](#) template [STATSCOUNTER\\_TEMPLATE\\_ARGS\(\)](#) inline a [STATSCOUNTER\\_TYPE\(\)](#)::b

## Functions

- [STATSCOUNTER\\_TEMPLATE](#) (, [StatsCounter](#))(const [StatsCounter](#)< Array\_Type
- [EmptyArray](#) clear ()
- [STATSCOUNTER\\_TEMPLATE](#) (,~[StatsCounter](#))()
- [STATSCOUNTER\\_TEMPLATE](#) (void, reset\_array)(const Array\_Type \*[Array\\_](#))
- [STATSCOUNTER\\_TEMPLATE](#) (void, add\_counter)([Counter](#)< Array\_Type
- [STATSCOUNTER\\_TEMPLATE](#) (void, set\_counters)([Counters](#)< Array\_Type
- [STATSCOUNTER\\_TEMPLATE](#) (void, count\_init)(uint i
- [current\\_stats](#) resize (counters->size(), 0.0)
- for (uint n=0u;n< counters->size();++n) [current\\_stats](#)[n]
- [STATSCOUNTER\\_TEMPLATE](#) (void, count\_current)(uint i
- [STATSCOUNTER\\_TEMPLATE](#) (std::vector< std::string >, get\_names)() const
- [STATSCOUNTER\\_TEMPLATE](#) (std::vector< std::string >, get\_descriptions)() const

## Variables

- `Data_Type & counter`
- `EmptyArray = *Array`
- `current_stats = counter.current_stats`
- `counters = new Counters<Array_Type,Data_Type>((*counter.counters))`
- `counter_deleted = false`
- `Data_Type f_`
- `return`
- `Data_Type * counters_`
- `uint j`

## 8.56.1 Macro Definition Documentation

### 8.56.1.1 STATSCOUNTER\_TEMPLATE

```
#define STATSCOUNTER_TEMPLATE(
    a,
    b )  template STATSCOUNTER_TEMPLATE_ARGS() inline a STATSCOUNTER_TYPE()::b
```

Definition at line 8 of file statscounter-meat.hpp.

### 8.56.1.2 STATSCOUNTER\_TEMPLATE\_ARGS

```
template STATSCOUNTER_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file statscounter-meat.hpp.

### 8.56.1.3 STATSCOUNTER\_TYPE

```
template Data_Type * STATSCOUNTER_TYPE( ) StatsCounter<Array_Type,Data_Type>
```

Definition at line 4 of file statscounter-meat.hpp.

## 8.56.2 Function Documentation

### 8.56.2.1 clear()

```
EmptyArray clear ( )
```

**8.56.2.2 for()**

```
for (
    uint n = 0; n < counters->size(); ++n )
```

**8.56.2.3 resize()**

```
current_stats resize (
    counters-> size(),
    0. 0 )
```

**8.56.2.4 STATSCOUNTER\_TEMPLATE() [1/9]**

```
STATSCOUNTER_TEMPLATE (
    StatsCounter ) const
```

**8.56.2.5 STATSCOUNTER\_TEMPLATE() [2/9]**

```
STATSCOUNTER_TEMPLATE (
    ~ StatsCounter )
```

Definition at line 27 of file statscounter-meat.hpp.

**8.56.2.6 STATSCOUNTER\_TEMPLATE() [3/9]**

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 256 of file statscounter-meat.hpp.

**8.56.2.7 STATSCOUNTER\_TEMPLATE() [4/9]**

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_names ) const
```

Definition at line 251 of file statscounter-meat.hpp.



**8.56.2.8 STATSCOUNTER\_TEMPLATE()** [5/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    add_counter )
```

**8.56.2.9 STATSCOUNTER\_TEMPLATE()** [6/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_current )
```

**8.56.2.10 STATSCOUNTER\_TEMPLATE()** [7/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_init )
```

**8.56.2.11 STATSCOUNTER\_TEMPLATE()** [8/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    reset_array ) const
```

Definition at line 34 of file statscounter-meat.hpp.

**8.56.2.12 STATSCOUNTER\_TEMPLATE()** [9/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    set_counters )
```

**8.56.3 Variable Documentation**

#### 8.56.3.1 counter

```
Data_Type& counter
```

**Initial value:**

```
{  
    Array      = counter.Array
```

Definition at line 12 of file statscounter-meat.hpp.

#### 8.56.3.2 counter\_deleted

```
counter_deleted = false
```

Definition at line 23 of file statscounter-meat.hpp.

#### 8.56.3.3 counters

```
counters = new Counters<Array_Type,Data_Type>((*counter.counters))
```

Definition at line 22 of file statscounter-meat.hpp.

#### 8.56.3.4 counters\_

```
Data_Type* counters_
```

**Initial value:**

```
{  
  
    if (!counter_deleted)  
        delete counters
```

Definition at line 53 of file statscounter-meat.hpp.

#### 8.56.3.5 current\_stats

```
current_stats = counter.current_stats
```

Definition at line 19 of file statscounter-meat.hpp.

### 8.56.3.6 EmptyArray

```
EmptyArray = *Array
```

Definition at line 17 of file statscounter-meat.hpp.

### 8.56.3.7 f\_

```
Data_Rule_Dyn_Type f_
```

**Initial value:**

```
{  
    counters->add_counter(f_)
```

Definition at line 44 of file statscounter-meat.hpp.

### 8.56.3.8 j

```
uint j
```

**Initial value:**

```
{  
  
    if (counters->size() == 0u)  
        throw std::logic_error("No counters added: Cannot count without knowing what to count!")
```

Definition at line 66 of file statscounter-meat.hpp.


### 8.56.3.9 return

```
return
```

Definition at line 49 of file statscounter-meat.hpp.

## 8.57 include/barry/support-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [Support](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) >  
*Compute the support of sufficient statistics.*

## 8.58 include/barry/support-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- #define [BARRY\\_SUPPORT\\_MEAT\\_HPP](#) 1
- #define [SUPPORT\\_TEMPLATE\\_ARGS](#)()
- #define [SUPPORT\\_TYPE](#)()
- #define [SUPPORT\\_TEMPLATE](#)(a, b)

## Functions

- [SUPPORT\\_TEMPLATE](#) (void, init\_support)(std
- [SUPPORT\\_TEMPLATE](#) (void, reset\_array)()
- [SUPPORT\\_TEMPLATE](#) (void, reset\_array)(const [Array\\_Type](#) &[Array\\_](#))
- [SUPPORT\\_TEMPLATE](#) (void, calc\_backend\_sparse)(uint pos
- [calc\\_backend\\_sparse](#) (pos+1u, [array\\_bank](#), [stats\\_bank](#))
- [EmptyArray](#) insert\_cell ([coord\\_i](#), [coord\\_j](#), [EmptyArray.default\\_val\(\).value](#), false, false)
- for (uint n=0u;n< n\_counters;++n)
- if ([rules\\_dyn->size\(\)](#) > 0u)
- if ([array\\_bank != nullptr](#)) [array\\_bank](#) -> push\_back([EmptyArray](#))
- [EmptyArray](#) rm\_cell ([coord\\_i](#), [coord\\_j](#), false, false)
- if ([change\\_stats\\_different](#) > 0u)
- [SUPPORT\\_TEMPLATE](#) (void, calc\_backend\_dense)(uint pos
- [calc\\_backend\\_dense](#) (pos+1u, [array\\_bank](#), [stats\\_bank](#))
- [EmptyArray](#) insert\_cell ([coord\\_i](#), [coord\\_j](#), 1, false, false)
- [SUPPORT\\_TEMPLATE](#) (void, calc)(std
- [SUPPORT\\_TEMPLATE](#) (void, add\_counter)([Counter](#)< [Array\\_Type](#)
- [SUPPORT\\_TEMPLATE](#) (void, set\_counters)([Counters](#)< [Array\\_Type](#)

- `SUPPORT_TEMPLATE` (void, add\_rule)(Rule< Array\_Type
- `SUPPORT_TEMPLATE` (void, set\_rules)(Rules< Array\_Type
- `SUPPORT_TEMPLATE` (void, add\_rule\_dyn)(Rule< Array\_Type
- `SUPPORT_TEMPLATE` (void, set\_rules\_dyn)(Rules< Array\_Type
- `SUPPORT_TEMPLATE` (bool, eval\_rules\_dyn)(const std
- `SUPPORT_TEMPLATE` (std::vector< double >, get\_counts)() const
- `SUPPORT_TEMPLATE` (std::vector< double > \*, get\_current\_stats)()
- `SUPPORT_TEMPLATE` (void, print)() const
- `SUPPORT_TEMPLATE` (const FreqTable< double > &, get\_data)() const

## Variables

- std::vector< Array\_Type > \* `array_bank`
- std::vector< Array\_Type > std::vector< double > \* `stats_bank`
- const size\_t & `coord_i` = coordinates\_free[pos \* 2u]
- const size\_t & `coord_j` = coordinates\_free[pos \* 2u + 1u]
- double `tmp_chng`
- unsigned int `change_stats_different` = hashes\_initialized[pos] ? 0u : 1u
- else
- & `hashes` [pos]
- return
- Data\_Counter\_Type `f_`
- Data\_Counter\_Type \* `counters_`
- `delete_counters` = false
- `counters` = `counters_`
- Data\_Rule\_Type \* `rules_`
- `delete_rules` = false
- `rules` = `rules_`
- `delete_rules_dyn` = false
- `rules_dyn` = `rules_`

## 8.58.1 Macro Definition Documentation

### 8.58.1.1 BARRY\_SUPPORT\_MEAT\_HPP

```
#define BARRY_SUPPORT_MEAT_HPP 1
```

Definition at line 2 of file support-meat.hpp.

### 8.58.1.2 SUPPORT\_TEMPLATE

```
#define SUPPORT_TEMPLATE(  
    a,  
    b )
```

#### Value:

```
template SUPPORT_TEMPLATE_ARGS() \  
inline a SUPPORT_TYPE()::b
```

Definition at line 10 of file support-meat.hpp.

### 8.58.1.3 SUPPORT\_TEMPLATE\_ARGS

```
template SUPPORT_TEMPLATE_ARGS( )
```

**Value:**

```
<typename Array_Type, typename \
Data_Counter_Type, typename Data_Rule_Type, typename Data_Rule_Dyn_Type>
```

Definition at line 4 of file support-meat.hpp.

### 8.58.1.4 SUPPORT\_TYPE

```
template Data_Rule_Dyn_Type * SUPPORT_TYPE( )
```

**Value:**

```
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, \
Data_Rule_Dyn_Type>
```

Definition at line 7 of file support-meat.hpp.

## 8.58.2 Function Documentation

### 8.58.2.1 calc\_backend\_dense()

```
calc_backend_dense (
    pos+ 1u,
    array_bank ,
    stats_bank )
```

### 8.58.2.2 calc\_backend\_sparse()

```
calc_backend_sparse (
    pos+ 1u,
    array_bank ,
    stats_bank )
```

### 8.58.2.3 for()

```
for ( )
```

Definition at line 159 of file support-meat.hpp.

**8.58.2.4 if() [1/3]**

```
if (
    array_bank !    = nullptr ) -> push_back(EmptyArray)
```

**8.58.2.5 if() [2/3]**

```
if (
    change_stats_different ,
    Ou )
```

Definition at line 239 of file support-meat.hpp.

**8.58.2.6 if() [3/3]**

```
if (
    rules_dyn-> size(),
    Ou )
```

Definition at line 187 of file support-meat.hpp.

**8.58.2.7 insert\_cell() [1/2]**

```
EmptyArray insert_cell (
    coord_i ,
    coord_j ,
    1 ,
    false ,
    false )
```

**8.58.2.8 insert\_cell() [2/2]**

```
EmptyArray insert_cell (
    coord_i ,
    coord_j ,
    EmptyArray.default_val(). value,
    false ,
    false )
```

### 8.58.2.9 rm\_cell()

```
EmptyArray rm_cell (
    coord_i ,
    coord_j ,
    false ,
    false )
```

### 8.58.2.10 SUPPORT\_TEMPLATE() [1/17]

```
SUPPORT_TEMPLATE (
    bool ,
    eval_rules_dyn ) const
```

Definition at line 488 of file support-meat.hpp.

### 8.58.2.11 SUPPORT\_TEMPLATE() [2/17]

```
SUPPORT_TEMPLATE (
    const FreqTable< double > & ,
    get_data ) const
```

Definition at line 557 of file support-meat.hpp.

### 8.58.2.12 SUPPORT\_TEMPLATE() [3/17]

```
SUPPORT_TEMPLATE (
    std::vector< double > * ,
    get_current_stats )
```

Definition at line 542 of file support-meat.hpp.

### 8.58.2.13 SUPPORT\_TEMPLATE() [4/17]

```
SUPPORT_TEMPLATE (
    std::vector< double > ,
    get_counts ) const
```

Definition at line 530 of file support-meat.hpp.



**8.58.2.14 SUPPORT\_TEMPLATE()** [5/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_counter )
```

**8.58.2.15 SUPPORT\_TEMPLATE()** [6/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_rule )
```

**8.58.2.16 SUPPORT\_TEMPLATE()** [7/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_rule_dyn )
```

**8.58.2.17 SUPPORT\_TEMPLATE()** [8/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc )
```

Definition at line 371 of file support-meat.hpp.

**8.58.2.18 SUPPORT\_TEMPLATE()** [9/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc_backend_dense )
```

**8.58.2.19 SUPPORT\_TEMPLATE()** [10/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc_backend_sparse )
```

**8.58.2.20 SUPPORT\_TEMPLATE() [11/17]**

```
SUPPORT_TEMPLATE (
    void ,
    init_support )
```

Definition at line 13 of file support-meat.hpp.

**8.58.2.21 SUPPORT\_TEMPLATE() [12/17]**

```
SUPPORT_TEMPLATE (
    void ,
    print ) const
```

Definition at line 546 of file support-meat.hpp.

**8.58.2.22 SUPPORT\_TEMPLATE() [13/17]**

```
SUPPORT_TEMPLATE (
    void ,
    reset_array )
```

Definition at line 114 of file support-meat.hpp.

**8.58.2.23 SUPPORT\_TEMPLATE() [14/17]**

```
SUPPORT_TEMPLATE (
    void ,
    reset_array ) const &
```

Definition at line 120 of file support-meat.hpp.

**8.58.2.24 SUPPORT\_TEMPLATE() [15/17]**

```
SUPPORT_TEMPLATE (
    void ,
    set_counters )
```

### 8.58.2.25 SUPPORT\_TEMPLATE() [16/17]

```
SUPPORT_TEMPLATE (
    void ,
    set_rules )
```

### 8.58.2.26 SUPPORT\_TEMPLATE() [17/17]

```
SUPPORT_TEMPLATE (
    void ,
    set_rules_dyn )
```

## 8.58.3 Variable Documentation

### 8.58.3.1 array\_bank

```
std::vector< Array_Type > * array_bank
```

Definition at line 131 of file support-meat.hpp.

### 8.58.3.2 change\_stats\_different

```
unsigned int change_stats_different = hashes_initialized[pos] ? 0u : 1u
```

Definition at line 158 of file support-meat.hpp.

### 8.58.3.3 coord\_i

```
const size_t & coord_i = coordinates_free[pos * 2u]
```

Definition at line 144 of file support-meat.hpp.

### 8.58.3.4 coord\_j

```
const size_t & coord_j = coordinates_free[pos * 2u + 1u]
```

Definition at line 145 of file support-meat.hpp.

#### 8.58.3.5 counters

```
counters = counters_
```

Definition at line 416 of file support-meat.hpp.

#### 8.58.3.6 counters\_

```
Data_Counter_Type* counters_
```

##### Initial value:

```
{  
  
    if (delete_counters)  
        delete counters
```

Definition at line 409 of file support-meat.hpp.

#### 8.58.3.7 delete\_counters

```
delete_counters = false
```

Definition at line 415 of file support-meat.hpp.

#### 8.58.3.8 delete\_rules

```
delete_rules = false
```

Definition at line 449 of file support-meat.hpp.

#### 8.58.3.9 delete\_rules\_dyn

```
delete_rules_dyn = false
```

Definition at line 481 of file support-meat.hpp.

### 8.58.3.10 else

```
else (  
    void )
```

#### Initial value:

```
{  
    if (change_stats_different > 0u)  
        hashes[pos] = data.add(current_stats, nullptr)
```

Definition at line 212 of file support-meat.hpp.

### 8.58.3.11 f\_

```
Data_Rule_Dyn_Type f_
```

#### Initial value:

```
{  
    counters->add_counter(f_)
```

Definition at line 400 of file support-meat.hpp.

### 8.58.3.12 hashes

```
& hashes
```

Definition at line 217 of file support-meat.hpp.

### 8.58.3.13 return

```
return
```

Definition at line 251 of file support-meat.hpp.

### 8.58.3.14 rules

```
rules = rules_
```

Definition at line 450 of file support-meat.hpp.

### 8.58.3.15 rules\_

Data\_Rule\_Dyn\_Type \* rules\_

#### Initial value:

```
{  
  
    if (delete_rules)  
        delete rules
```

Definition at line 443 of file support-meat.hpp.

### 8.58.3.16 rules\_dyn

rules\_dyn = rules\_

Definition at line 482 of file support-meat.hpp.

### 8.58.3.17 stats\_bank

std::vector< Array\_Type > std::vector< double > \* stats\_bank

#### Initial value:

```
{  
  
    if (pos >= coordiantes_n_free)  
        return
```

Definition at line 132 of file support-meat.hpp.

### 8.58.3.18 tmp\_chng


double tmp\_chng

Definition at line 157 of file support-meat.hpp.


## 8.59 include/barry/typedefs.hpp File Reference

```
#include "barry-configuration.hpp"  
#include "barry-debug.hpp"  
#include "progress.hpp"
```

Include dependency graph for typedefs.hpp:



This graph shows which files directly or indirectly include this file:



### Classes

- class [Entries< Cell\\_Type >](#)  
*A wrapper class to store source, target, val from a [BArray](#) object.*
- struct [vecHasher< T >](#)

### Namespaces

- [CHECK](#)  
*Integer constants used to specify which cell should be check.*
- [EXISTS](#)  
*Integer constants used to specify which cell should be check to exist or not.*

## Typedefs

- typedef unsigned int [uint](#)
- typedef std::vector< std::pair< std::vector< double >, [uint](#) > > [Counts\\_type](#)
- template<typename Cell\_Type >  
using [Row\\_type](#) = [Map](#)< [uint](#), [Cell](#)< Cell\_Type > >
- template<typename Cell\_Type >  
using [Col\\_type](#) = [Map](#)< [uint](#), [Cell](#)< Cell\_Type > \* >
- template<typename Ta = double, typename Tb = uint>  
using [MapVec\\_type](#) = std::unordered\_map< std::vector< Ta >, Tb, [vecHasher](#)< Ta > >
- template<typename Array\_Type , typename Data\_Type >  
using [Counter\\_fun\\_type](#) = std::function< double([const](#) Array\_Type &, [uint](#), [uint](#), Data\_Type &)>  
*[Counter](#) and rule functions.*
- template<typename Array\_Type , typename Data\_Type >  
using [Rule\\_fun\\_type](#) = std::function< bool([const](#) Array\_Type &, [uint](#), [uint](#), Data\_Type &)>

## Functions

- template<typename T >  
T [vec\\_inner\\_prod](#) ([const](#) T \*a, [const](#) T \*b, size\_t n)
- template<> double [vec\\_inner\\_prod](#) ([const](#) double \*a, [const](#) double \*b, size\_t n)
- template<typename T >  
bool [vec\\_equal](#) ([const](#) std::vector< T > &a, [const](#) std::vector< T > &b)  
*Compares if -a- and -b- are equal.*
- template<typename T >  
bool [vec\\_equal\\_approx](#) ([const](#) std::vector< T > &a, [const](#) std::vector< T > &b, double eps=1e-100)

## Variables

- [const](#) int [CHECK::BOTH](#) = -1
- [const](#) int [CHECK::NONE](#) = 0
- [const](#) int [CHECK::ONE](#) = 1
- [const](#) int [CHECK::TWO](#) = 2
- [const](#) int [EXISTS::BOTH](#) = -1
- [const](#) int [EXISTS::NONE](#) = 0
- [const](#) int [EXISTS::ONE](#) = 1
- [const](#) int [EXISTS::TWO](#) = 1
- [const](#) int [EXISTS::UNKNOWN](#) = -1
- [const](#) int [EXISTS::AS\\_ZERO](#) = 0
- [const](#) int [EXISTS::AS\\_ONE](#) = 1

### 8.59.1 Typedef Documentation



### 8.59.1.1 Col\_type

```
template<typename Cell_Type >
using Col_type = Map< uint, Cell<Cell_Type>* >
```

Definition at line 71 of file typedefs.hpp.

### 8.59.1.2 Counter\_fun\_type

```
template<typename Array_Type , typename Data_Type >
using Counter_fun_type = std::function<double(const Array_Type &, uint, uint, Data_Type &)>
```

[Counter](#) and rule functions.

#### Parameters

<i>Array_Type</i>	a <a href="#">BArray</a>
<i>unit,uint</i>	Focal cell
<i>Data_Type</i>	Data associated with the function, for example, id of the attribute in the Array.

#### Returns

[Counter\\_fun\\_type](#) a double (the change statistic)

[Rule\\_fun\\_type](#) a bool. True if the cell is blocked.

Definition at line 148 of file typedefs.hpp.

### 8.59.1.3 Counts\_type

```
typedef std::vector< std::pair< std::vector<double>, uint > > Counts_type
```

Definition at line 52 of file typedefs.hpp.

### 8.59.1.4 MapVec\_type

```
template<typename Ta = double, typename Tb = uint>
using MapVec_type = std::unordered_map< std::vector< Ta >, Tb, vecHasher<Ta> >
```

Definition at line 129 of file typedefs.hpp.

### 8.59.1.5 Row\_type

```
template<typename Cell_Type >
using Row_type = Map< uint, Cell<Cell_Type> >
```

Definition at line 68 of file typedefs.hpp.

### 8.59.1.6 Rule\_fun\_type

```
template<typename Array_Type , typename Data_Type >
using Rule_fun_type = std::function<bool(const Array_Type &, uint, uint, Data_Type &)>
```

Definition at line 151 of file typedefs.hpp.

### 8.59.1.7 uint

```
typedef unsigned int uint
```

Definition at line 18 of file typedefs.hpp.

## 8.59.2 Function Documentation

### 8.59.2.1 vec\_equal()

```
template<typename T >
bool vec_equal (
    const std::vector< T > & a,
    const std::vector< T > & b ) [inline]
```

Compares if -a- and -b- are equal.

#### Parameters

<i>a,b</i>	Two vectors of the same length
------------	--------------------------------

#### Returns

`true` if all elements are equal.

Definition at line 162 of file typedefs.hpp.

### 8.59.2.2 `vec_equal_approx()`

```
template<typename T >
bool vec_equal_approx (
    const std::vector< T > & a,
    const std::vector< T > & b,
    double eps = 1e-100 ) [inline]
```

Definition at line 180 of file typedefs.hpp.

### 8.59.2.3 `vec_inner_prod()` [1/2]

```
template<>
double vec_inner_prod (
    const double * a,
    const double * b,
    size_t n ) [inline]
```

Definition at line 226 of file typedefs.hpp.

### 8.59.2.4 `vec_inner_prod()` [2/2]

```
template<typename T >
T vec_inner_prod (
    const T * a,
    const T * b,
    size_t n ) [inline]
```

Definition at line 203 of file typedefs.hpp.

## 8.60 README.md File Reference



# Index

- ~BArray
  - BArray< Cell\_Type, Data\_Type >, [39](#)
- ~BArrayCell
  - BArrayCell< Cell\_Type, Data\_Type >, [50](#)
- ~BArrayCell\_const
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [52](#)
- ~BArrayDense
  - BArrayDense< Cell\_Type, Data\_Type >, [58](#)
- ~BArrayDenseCell
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [71](#)
- ~BArrayRow
  - BArrayRow< Cell\_Type, Data\_Type >, [84](#)
- ~BArrayRow\_const
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [86](#)
- ~BArrayVector
  - BArrayVector< Cell\_Type, Data\_Type >, [89](#)
- ~BArrayVector\_const
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [92](#)
- ~Cell
  - Cell< Cell\_Type >, [96](#)
- ~ConstBArrayRowIter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, [101](#)
- ~Counter
  - Counter< Array\_Type, Data\_Type >, [104](#)
- ~Counters
  - Counters< Array\_Type, Data\_Type >, [108](#)
- ~DEFM
  - DEFM, [112](#)
- ~DEFMCounterData
  - DEFMCounterData, [115](#)
- ~DEFMData
  - DEFMData, [119](#)
- ~Entries
  - Entries< Cell\_Type >, [123](#)
- ~Flock
  - Flock, [126](#)
- ~FreqTable
  - FreqTable< T >, [132](#)
- ~Geese
  - Geese, [139](#)
- ~Model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [151](#)
- ~NetCounterData
  - NetCounterData, [163](#)
- ~NetworkData
  - NetworkData, [165](#)
- ~Node
  - Node, [168](#)
- ~PhyloRuleDynData
  - PhyloRuleDynData, [177](#)
- ~PowerSet
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [180](#)
- ~Progress
  - Progress, [185](#)
- ~Rule
  - Rule< Array\_Type, Data\_Type >, [187](#)
- ~Rules
  - Rules< Array\_Type, Data\_Type >, [189](#)
- ~StatsCounter
  - StatsCounter< Array\_Type, Data\_Type >, [193](#)
- ~Support
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [198](#)
- active
  - Cell< Cell\_Type >, [99](#)
- add
  - barray-meat.hpp, [224](#)
  - barraydense-meat.hpp, [249](#)
  - Cell< Cell\_Type >, [97](#), [98](#)
  - FreqTable< T >, [133](#)
- add\_array
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [152](#)
- add\_counter
  - Counters< Array\_Type, Data\_Type >, [109](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [152](#)
  - StatsCounter< Array\_Type, Data\_Type >, [193](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [198](#)
- add\_data
  - Flock, [126](#)
- add\_rule
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [152](#), [153](#)
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [180](#), [181](#)
  - Rules< Array\_Type, Data\_Type >, [190](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [198](#)

- 198, 199
- add\_rule\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 153
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 199
- annotations
  - Node, 169
- ans
  - barray-meat.hpp, 215, 224
  - barraydense-meat.hpp, 238, 249
- Array
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 101
- array
  - DEFMData, 120
  - Node, 169
- Array\_
  - barray-meat.hpp, 224
- array\_bank
  - support-meat.hpp, 339
- arrays
  - Node, 169
- AS\_ONE
  - EXISTS, 33
- as\_vector
  - FreqTable< T >, 133
- AS\_ZERO
  - EXISTS, 33
- at
  - DEFMData, 119
  - PhyloCounterData, 174
- BArray
  - BArray< Cell\_Type, Data\_Type >, 38, 39
- BArray< Cell\_Type, Data\_Type >, 35
  - ~BArray, 39
  - BArray, 38, 39
  - BArrayCell< Cell\_Type, Data\_Type >, 48
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 48
  - clear, 39
  - col, 39
  - D, 40
  - D\_ptr, 40
  - default\_val, 40
  - flush\_data, 40
  - get\_cell, 40
  - get\_col\_vec, 41
  - get\_entries, 41
  - get\_row\_vec, 41
  - insert\_cell, 42
  - is\_dense, 42
  - is\_empty, 42
  - ncol, 43
  - nnozero, 43
  - nrow, 43
  - operator\*=: 43
  - operator(), 43
  - operator+=, 44
  - operator-=, 44
  - operator/=: 45
  - operator=: 45
  - operator==, 45
  - out\_of\_range, 45
  - print, 45
  - reserve, 46
  - resize, 46
  - rm\_cell, 46
  - row, 46
  - set\_data, 46
  - swap\_cells, 47
  - swap\_cols, 47
  - swap\_rows, 47
  - toggle\_cell, 47
  - toggle\_lock, 47
  - transpose, 48
  - visited, 49
  - zero\_col, 48
  - zero\_row, 48
- barray-meat-operators.hpp
  - BARRAY\_TEMPLATE, 208–210
  - BARRAY\_TEMPLATE\_ARGS, 209, 211
  - BARRAY\_TYPE, 209, 211
  - COL, 209
  - for, 211
  - operator(), 211
  - rhs, 211
  - ROW, 209
  - this, 212
- barray-meat.hpp
  - add, 224
  - ans, 215, 224
  - Array\_, 224
  - BARRAY\_TEMPLATE, 214–219
  - BARRAY\_TEMPLATE\_ARGS, 214
  - BARRAY\_TYPE, 214
  - check\_bounds, 224
  - check\_exists, 225
  - COL, 215, 219
  - col0, 225
  - const, 225
  - copy\_data, 225
  - data, 226
  - delete\_data, 226
  - delete\_data\_, 226
  - else, 226
  - false, 226
  - first, 227
  - for, 220
  - i1, 227
  - if, 220–223
  - j, 227
  - j0, 227
  - j1, 227
  - M, 223, 227

- M\_, 228
- N, 228
- NCells, 228
- report, 228
- resize, 223
- return, 223, 228
- ROW, 215, 223, 224
- row0, 229
- search, 229
- source, 229
- target, 229
- v, 229
- value, 229
- BARRAY\_TEMPLATE
  - barray-meat-operators.hpp, 208–210
  - barray-meat.hpp, 214–219
- BARRAY\_TEMPLATE\_ARGS
  - barray-meat-operators.hpp, 209, 211
  - barray-meat.hpp, 214
- BARRAY\_TYPE
  - barray-meat-operators.hpp, 209, 211
  - barray-meat.hpp, 214
- BArrayCell
  - BArrayCell< Cell\_Type, Data\_Type >, 50
- BArrayCell< Cell\_Type, Data\_Type >, 49
  - ~BArrayCell, 50
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayCell, 50
  - operator Cell\_Type, 50
  - operator\*=: 50
  - operator+=, 50
  - operator-=, 51
  - operator/=: 51
  - operator=, 51
  - operator==, 51
- BArrayCell\_const
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 52
- BArrayCell\_const< Cell\_Type, Data\_Type >, 52
  - ~BArrayCell\_const, 52
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayCell\_const, 52
  - operator Cell\_Type, 53
  - operator!=, 53
  - operator<, 53
  - operator<=, 53
  - operator>, 53
  - operator>=, 54
  - operator==, 53
- BArrayDense
  - BArrayDense< Cell\_Type, Data\_Type >, 57, 58
- BArrayDense< Cell\_Type, Data\_Type >, 54
  - ~BArrayDense, 58
  - BArrayDense, 57, 58
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 68, 73
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 69, 76
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 69
- BArrayDenseRow< Cell\_Type, Data\_Type >, 69, 80
- BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 69
- clear, 59
- col, 59
- colsum, 59
- D, 59, 60
- D\_ptr, 60
- default\_val, 60
- get\_cell, 60
- get\_col\_vec, 60, 61
- get\_data, 61
- get\_entries, 61
- get\_row\_vec, 61
- insert\_cell, 62
- is\_dense, 62
- is\_empty, 62
- ncol, 62
- nnozero, 63
- nrow, 63
- operator\*=: 63
- operator(), 63
- operator+=, 63, 64
- operator-=, 64
- operator/=: 64
- operator=, 65
- operator==, 65
- out\_of\_range, 65
- print, 65
- reserve, 65
- resize, 66
- rm\_cell, 66
- row, 66
- rowsum, 66
- set\_data, 66
- swap\_cells, 67
- swap\_cols, 67
- swap\_rows, 67
- toggle\_cell, 67
- toggle\_lock, 68
- transpose, 68
- visited, 69
- zero\_col, 68
- zero\_row, 68
- barraydense-meat-operators.hpp
  - BDENSE\_TEMPLATE, 232–234
  - BDENSE\_TEMPLATE\_ARGS, 232, 234
  - BDENSE\_TYPE, 232, 234
  - COL, 232
  - POS, 232
  - POS\_N, 233
  - ROW, 233
- barraydense-meat.hpp
  - add, 249
  - ans, 238, 249
  - BDENSE\_TEMPLATE, 237–245
  - BDENSE\_TEMPLATE\_ARGS, 237

- BDENSE\_TYPE, 237
- check\_bounds, 249
- check\_exists, 249
- COL, 237
- col, 250
- const, 250
- copy\_data, 250
- data, 250
- delete\_data, 250
- delete\_data\_, 251
- el, 251
- el\_colsums, 251
- el\_rowsums, 251
- else, 251
- false, 252
- for, 245
- i1, 252
- if, 246
- insert\_cell, 246
- j, 252
- j0, 252
- j1, 252
- M, 247, 252
- M\_, 253
- N, 253
- POS, 237
- POS\_N, 237
- report, 253
- resize, 247, 248
- return, 253
- rm\_cell, 248
- ROW, 238
- source, 253
- target, 254
- v, 254
- va\_end, 248
- va\_start, 248
- val0, 254
- val1, 254
- value, 254
- vprintf, 249
- ZERO\_CELL, 238
- BArrayDenseCell
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 71
- BArrayDenseCell< Cell\_Type, Data\_Type >, 70
  - ~BArrayDenseCell, 71
  - BArrayDense< Cell\_Type, Data\_Type >, 68, 73
  - BArrayDenseCell, 71
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 73, 76
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 73, 78
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 80
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 83
  - operator Cell\_Type, 71
  - operator\*=: 71
  - operator+=, 71
  - operator-=, 72
  - operator/=: 72
  - operator=: 72
  - operator==, 72
- barraydensecell-bones.hpp
  - POS, 255
- barraydensecell-meat.hpp
  - POS, 256
- BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 74
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 76
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 78
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 80
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 83
- BArrayDenseCol
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 74
- BArrayDenseCol< Cell\_Type, Data\_Type >, 74
  - BArrayDense< Cell\_Type, Data\_Type >, 69, 76
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 73, 76
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 76
  - BArrayDenseCol, 74
  - begin, 75
  - end, 75
  - operator(), 75
  - size, 75
- barraydensecol-bones.hpp
  - POS, 257
  - POS\_N, 257
  - ZERO\_CELL, 257
- BArrayDenseCol\_const
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 77
- BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 76
  - BArrayDense< Cell\_Type, Data\_Type >, 69
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 73, 78
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 78
  - BArrayDenseCol\_const, 77
  - begin, 77
  - end, 77
  - operator(), 77
  - size, 78
- BArrayDenseRow
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 79
- BArrayDenseRow< Cell\_Type, Data\_Type >, 78
  - BArrayDense< Cell\_Type, Data\_Type >, 69, 80
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 80
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 80
  - BArrayDenseRow, 79
  - begin, 79
  - end, 79
  - operator(), 80
  - size, 80
- barraydenserow-bones.hpp



- POS, 258
- POS\_N, 258
- ZERO\_CELL, 259
- BArrayDenseRow\_const
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 81
- BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 81
  - BArrayDense< Cell\_Type, Data\_Type >, 69
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 83
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 83
  - BArrayDenseRow\_const, 81
  - begin, 82
  - end, 82
  - operator(), 82
  - size, 82
- BArrayRow
  - BArrayRow< Cell\_Type, Data\_Type >, 84
- BArrayRow< Cell\_Type, Data\_Type >, 83
  - ~BArrayRow, 84
  - BArrayRow, 84
  - operator BArrayRow< Cell\_Type, Data\_Type >, 84
  - operator\*=, 84
  - operator+=, 84
  - operator-=, 84
  - operator/=: 85
  - operator=, 85
  - operator==, 85
- barrayrow-meat.hpp
  - BROW\_TEMPLATE, 259–261
  - BROW\_TEMPLATE\_ARGS, 260
  - BROW\_TYPE, 260
- BArrayRow\_const
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 86
- BArrayRow\_const< Cell\_Type, Data\_Type >, 85
  - ~BArrayRow\_const, 86
  - BArrayRow\_const, 86
  - operator BArrayRow\_const< Cell\_Type, Data\_Type >, 86
  - operator!=, 86
  - operator<, 86
  - operator<=, 87
  - operator>, 87
  - operator>=, 87
  - operator==, 87
- BArrayVector
  - BArrayVector< Cell\_Type, Data\_Type >, 88
- BArrayVector< Cell\_Type, Data\_Type >, 87
  - ~BArrayVector, 89
  - BArrayVector, 88
  - begin, 89
  - end, 89
  - is\_col, 89
  - is\_row, 89
  - operator std::vector< Cell\_Type >, 90
  - operator\*=, 90
  - operator+=, 90
  - operator-=, 90
  - operator/=: 90
  - operator=, 91
  - operator==, 91
  - size, 91
- BArrayVector\_const
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 92
- BArrayVector\_const< Cell\_Type, Data\_Type >, 91
  - ~BArrayVector\_const, 92
  - BArrayVector\_const, 92
  - begin, 93
  - end, 93
  - is\_col, 93
  - is\_row, 93
  - operator std::vector< Cell\_Type >, 93
  - operator!=, 93
  - operator<, 94
  - operator<=, 94
  - operator>, 94
  - operator>=, 94
  - operator==, 94
  - size, 95
- barry, 31
- barry-configuration.hpp
  - BARRY\_CHECK\_SUPPORT, 263
  - BARRY\_ISFINITE, 263
  - BARRY\_MAX\_NUM\_ELEMENTS, 263
  - BARRY\_SAFE\_EXP, 263
  - Map, 263
  - printf\_barry, 263
- barry-debug.hpp
  - BARRY\_DEBUG\_LEVEL, 264
- barry-macros.hpp
  - BARRY\_ONE, 265
  - BARRY\_ONE\_DENSE, 265
  - BARRY\_UNUSED, 265
  - BARRY\_ZERO, 266
  - BARRY\_ZERO\_DENSE, 266
- barry.hpp
  - BARRY\_HPP, 267
  - BARRY\_VERSION, 268
  - BARRY\_VERSION\_MAYOR, 268
  - BARRY\_VERSION\_MINOR, 268
  - COUNTER\_FUNCTION, 268
  - COUNTER\_LAMBDA, 268
  - RULE\_FUNCTION, 269
  - RULE\_LAMBDA, 269
- barry::counters, 31
- barry::counters::defm, 32
- barry::counters::network, 32
- barry::counters::phylo, 32
- BARRY\_CHECK\_SUPPORT
  - barry-configuration.hpp, 263
- BARRY\_DEBUG\_LEVEL
  - barry-debug.hpp, 264
- BARRY\_HPP
  - barry.hpp, 267
- BARRY\_ISFINITE
  - barry-configuration.hpp, 263

- BARRY\_MAX\_NUM\_ELEMENTS
  - barry-configuration.hpp, [263](#)
- BARRY\_ONE
  - barry-macros.hpp, [265](#)
- BARRY\_ONE\_DENSE
  - barry-macros.hpp, [265](#)
- BARRY\_PROGRESS\_BAR\_WIDTH
  - progress.hpp, [324](#)
- BARRY\_SAFE\_EXP
  - barry-configuration.hpp, [263](#)
- BARRY\_SUPPORT\_MEAT\_HPP
  - support-meat.hpp, [333](#)
- BARRY\_UNUSED
  - barry-macros.hpp, [265](#)
- BARRY\_VERSION
  - barry.hpp, [268](#)
- BARRY\_VERSION\_MAYOR
  - barry.hpp, [268](#)
- BARRY\_VERSION\_MINOR
  - barry.hpp, [268](#)
- BARRY\_ZERO
  - barry-macros.hpp, [266](#)
- BARRY\_ZERO\_DENSE
  - barry-macros.hpp, [266](#)
- BARRY\_ZERO\_NETWORK
  - network.hpp, [296](#)
- BARRY\_ZERO\_NETWORK\_DENSE
  - network.hpp, [297](#)
- BDENSE\_TEMPLATE
  - barraydense-meat-operators.hpp, [232–234](#)
  - barraydense-meat.hpp, [237–245](#)
- BDENSE\_TEMPLATE\_ARGS
  - barraydense-meat-operators.hpp, [232, 234](#)
  - barraydense-meat.hpp, [237](#)
- BDENSE\_TYPE
  - barraydense-meat-operators.hpp, [232, 234](#)
  - barraydense-meat.hpp, [237](#)
- begin
  - BArrayDenseCol< Cell\_Type, Data\_Type >, [75](#)
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, [77](#)
  - BArrayDenseRow< Cell\_Type, Data\_Type >, [79](#)
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, [82](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [89](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [93](#)
  - PhyloCounterData, [174](#)
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [181](#)
- blengths
  - NodeData, [172](#)
- BOTH
  - CHECK, [32](#)
  - EXISTS, [34](#)
- BROW\_TEMPLATE
  - barrayrow-meat.hpp, [259–261](#)
- BROW\_TEMPLATE\_ARGS
  - barrayrow-meat.hpp, [260](#)
- BROW\_TYPE
  - barrayrow-meat.hpp, [260](#)
- calc
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [181](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [199](#)
- calc\_backend\_dense
  - support-meat.hpp, [334](#)
- calc\_backend\_sparse
  - support-meat.hpp, [334](#)
- calc\_reduced\_sequence
  - Geese, [139](#)
- calc\_sequence
  - Geese, [139](#)
- Cell
  - Cell< Cell\_Type >, [96, 97](#)
- Cell< Cell\_Type >, [95](#)
  - ~Cell, [96](#)
  - active, [99](#)
  - add, [97, 98](#)
  - Cell, [96, 97](#)
  - operator Cell\_Type, [98](#)
  - operator!=, [98](#)
  - operator=, [98, 99](#)
  - operator==, [99](#)
  - value, [99](#)
  - visited, [99](#)
- Cell\_const< Cell\_Type >, [100](#)
- change\_stats
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [202](#)
- change\_stats\_different
  - support-meat.hpp, [339](#)
- CHECK, [32](#)
  - BOTH, [32](#)
  - NONE, [32](#)
  - ONE, [32](#)
  - TWO, [33](#)
- check\_bounds
  - barray-meat.hpp, [224](#)
  - barraydense-meat.hpp, [249](#)
- check\_exists
  - barray-meat.hpp, [225](#)
  - barraydense-meat.hpp, [249](#)
- clear
  - BArray< Cell\_Type, Data\_Type >, [39](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [59](#)
  - FreqTable< T >, [133](#)
  - statscounter-meat.hpp, [327](#)
- COL
  - barray-meat-operators.hpp, [209](#)
  - barray-meat.hpp, [215, 219](#)
  - barraydense-meat-operators.hpp, [232](#)
  - barraydense-meat.hpp, [237](#)
- col
  - BArray< Cell\_Type, Data\_Type >, [39](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [59](#)

- barraydense-meat.hpp, 250
- col0
  - barray-meat.hpp, 225
- Col\_type
  - typedefs.hpp, 344
- colnames
  - Flock, 126
  - Geese, 140
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 153
- colsum
  - BArrayDense< Cell\_Type, Data\_Type >, 59
- conditional\_prob
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 153
- const
  - barray-meat.hpp, 225
  - barraydense-meat.hpp, 250
- ConstBArrayRowIter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 101
- ConstBArrayRowIter< Cell\_Type, Data\_Type >, 100
  - ~ConstBArrayRowIter, 101
  - Array, 101
  - ConstBArrayRowIter, 101
  - current\_col, 102
  - current\_row, 102
  - iter, 102
- coord\_i
  - support-meat.hpp, 339
- coord\_j
  - support-meat.hpp, 339
- cooriantes\_n\_free
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 203
- cooriantes\_n\_locked
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 203
- coordinates\_free
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 183
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 203
- coordinates\_locked
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 183
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 203
- copy\_data
  - barray-meat.hpp, 225
  - barraydense-meat.hpp, 250
- count
  - Counter< Array\_Type, Data\_Type >, 105
- count\_all
  - StatsCounter< Array\_Type, Data\_Type >, 193
- count\_current
  - StatsCounter< Array\_Type, Data\_Type >, 194
- count\_fun
  - Counter< Array\_Type, Data\_Type >, 106
  - counters-meat.hpp, 273
- count\_fun\_
  - counters-meat.hpp, 277
- count\_init
  - StatsCounter< Array\_Type, Data\_Type >, 194
- Counter
  - Counter< Array\_Type, Data\_Type >, 103, 104
- counter
  - counters-meat.hpp, 277
  - statscounter-meat.hpp, 329
- Counter< Array\_Type, Data\_Type >, 102
  - ~Counter, 104
  - count, 105
  - count\_fun, 106
  - Counter, 103, 104
  - data, 106
  - desc, 106
  - get\_description, 105
  - get\_name, 105
  - init, 105
  - init\_fun, 106
  - name, 106
  - operator=, 105
- counter\_
  - counters-meat.hpp, 277
- counter\_absdiff
  - DEFMArray counters, 14
- counter\_co\_opt
  - Phylo counters, 23
- counter\_cogain
  - Phylo counters, 23
- counter\_css\_census01
  - network-css.hpp, 289
- counter\_css\_census02
  - network-css.hpp, 290
- counter\_css\_census03
  - network-css.hpp, 290
- counter\_css\_census04
  - network-css.hpp, 290
- counter\_css\_census05
  - network-css.hpp, 290
- counter\_css\_census06
  - network-css.hpp, 291
- counter\_css\_census07
  - network-css.hpp, 291
- counter\_css\_census08
  - network-css.hpp, 291
- counter\_css\_census09
  - network-css.hpp, 291
- counter\_css\_census10
  - network-css.hpp, 292
- counter\_css\_completely\_false\_recip\_comiss
  - network-css.hpp, 292

- counter\_css\_completely\_false\_recip\_omiss  
network-css.hpp, [292](#)
- counter\_css\_mixed\_recip  
network-css.hpp, [292](#)
- counter\_css\_partially\_false\_recip\_commi  
network-css.hpp, [293](#)
- counter\_css\_partially\_false\_recip\_omiss  
network-css.hpp, [293](#)
- counter\_ctriads  
DEFMArray counters, [14](#)
- counter\_degree  
DEFMArray counters, [14](#)
- counter\_deleted  
statscounter-meat.hpp, [330](#)
- counter\_density  
DEFMArray counters, [14](#)
- counter\_diff  
DEFMArray counters, [15](#)
- counter\_edges  
DEFMArray counters, [15](#)
- counter\_fixed\_effect  
DEFMArray counters, [15](#)
- Counter\_fun\_type  
typedefs.hpp, [345](#)
- COUNTER\_FUNCTION  
barry.hpp, [268](#)
- counter\_gains  
Phylo counters, [23](#)
- counter\_gains\_from\_0  
Phylo counters, [23](#)
- counter\_gains\_k\_offspring  
Phylo counters, [24](#)
- counter\_genes\_changing  
Phylo counters, [24](#)
- counter\_idegree  
DEFMArray counters, [16](#)
- counter\_idegree15  
DEFMArray counters, [16](#)
- counter\_isolates  
DEFMArray counters, [16](#), [17](#)
- counter\_istar2  
DEFMArray counters, [17](#)
- counter\_k\_genes\_changing  
Phylo counters, [24](#)
- COUNTER\_LAMBDA  
barry.hpp, [268](#)
- counter\_less\_than\_p\_prop\_genes\_changing  
Phylo counters, [24](#)
- counter\_longest  
Phylo counters, [25](#)
- counter\_loss  
Phylo counters, [25](#)
- counter\_maxfuns  
Phylo counters, [25](#)
- counter\_mutual  
DEFMArray counters, [17](#)
- counter\_neofun  
Phylo counters, [25](#)
- counter\_neofun\_a2b  
Phylo counters, [26](#)
- counter\_nodecov  
DEFMArray counters, [17](#)
- counter\_nodeicov  
DEFMArray counters, [18](#)
- counter\_nodematch  
DEFMArray counters, [18](#)
- counter\_nodeocov  
DEFMArray counters, [18](#)
- counter\_odegree  
DEFMArray counters, [18](#)
- counter\_odegree15  
DEFMArray counters, [19](#)
- counter\_ones  
DEFMArray counters, [19](#)
- counter\_ostar2  
DEFMArray counters, [19](#), [20](#)
- counter\_overall\_changes  
Phylo counters, [26](#)
- counter\_overall\_gains  
Phylo counters, [26](#)
- counter\_overall\_gains\_from\_0  
Phylo counters, [26](#)
- counter\_overall\_loss  
Phylo counters, [27](#)
- counter\_pairwise\_first\_gain  
Phylo counters, [27](#)
- counter\_pairwise\_neofun\_singlefun  
Phylo counters, [27](#)
- counter\_pairwise\_overall\_change  
Phylo counters, [27](#)
- counter\_pairwise\_preserving  
Phylo counters, [28](#)
- counter\_preserve\_pseudogene  
Phylo counters, [28](#)
- counter\_prop\_genes\_changing  
Phylo counters, [28](#)
- counter\_subfun  
Phylo counters, [28](#)
- COUNTER\_TEMPLATE  
counters-meat.hpp, [272–274](#)
- COUNTER\_TEMPLATE\_ARGS  
counters-meat.hpp, [272](#)
- counter\_transition  
DEFMArray counters, [20](#)
- counter\_ttriads  
DEFMArray counters, [20](#)
- COUNTER\_TYPE  
counters-meat.hpp, [272](#)
- Counters  
Counters< Array\_Type, Data\_Type >, [108](#)  
counters-meat.hpp, [274](#)
- counters  
statscounter-meat.hpp, [330](#)  
support-meat.hpp, [339](#)
- Counters< Array\_Type, Data\_Type >, [107](#)  
~Counters, [108](#)

- add\_counter, 109
- Counters, 108
- get\_descriptions, 109
- get\_names, 109
- operator=, 109, 110
- operator[], 110
- size, 110
- counters-meat.hpp
  - count\_fun, 273
  - count\_fun\_, 277
  - counter, 277
  - counter\_, 277
  - COUNTER\_TEMPLATE, 272–274
  - COUNTER\_TEMPLATE\_ARGS, 272
  - COUNTER\_TYPE, 272
  - Counters, 274
  - COUNTERS\_TEMPLATE, 272, 275, 276
  - COUNTERS\_TEMPLATE\_ARGS, 273
  - COUNTERS\_TYPE, 273
  - data, 276
  - data\_, 278
  - desc, 276
  - desc\_, 278
  - i, 278
  - init\_fun, 276, 277
  - init\_fun\_, 278
  - j, 279
  - name, 277
  - name\_, 279
  - noexcept, 279
  - return, 279
  - this, 279
- counters\_
  - statscounter-meat.hpp, 330
  - support-meat.hpp, 340
- COUNTERS\_TEMPLATE
  - counters-meat.hpp, 272, 275, 276
- COUNTERS\_TEMPLATE\_ARGS
  - counters-meat.hpp, 273
- COUNTERS\_TYPE
  - counters-meat.hpp, 273
- Counting, 11
- counts
  - PhyloRuleDynData, 177
- Counts\_type
  - typedefs.hpp, 345
- covariates
  - DEFMData, 120
- CSS\_APPEND
  - network-css.hpp, 287
- CSS\_CASE\_ELSE
  - network-css.hpp, 287
- CSS\_CASE\_PERCEIVED
  - network-css.hpp, 288
- CSS\_CASE\_TRUTH
  - network-css.hpp, 288
- CSS\_CHECK\_SIZE
  - network-css.hpp, 288
- CSS\_CHECK\_SIZE\_INIT
  - network-css.hpp, 288
- CSS\_NET\_COUNTER\_LAMBDA\_INIT
  - network-css.hpp, 288
- CSS\_PERCEIVED\_CELLS
  - network-css.hpp, 289
- CSS\_SIZE
  - network-css.hpp, 289
- CSS\_TRUE\_CELLS
  - network-css.hpp, 289
- current\_col
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 102
- current\_row
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 102
- current\_stats
  - statscounter-meat.hpp, 330
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 203
- D
  - BArray< Cell\_Type, Data\_Type >, 40
  - BArrayDense< Cell\_Type, Data\_Type >, 59, 60
  - Rule< Array\_Type, Data\_Type >, 188
- D\_ptr
  - BArray< Cell\_Type, Data\_Type >, 40
  - BArrayDense< Cell\_Type, Data\_Type >, 60
- dat
  - Flock, 130
- data
  - barray-meat.hpp, 226
  - barraydense-meat.hpp, 250
  - Counter< Array\_Type, Data\_Type >, 106
  - counters-meat.hpp, 276
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 183
- data\_
  - counters-meat.hpp, 278
- DEFAULT\_DUPLICATION
  - phylo.hpp, 303
- default\_val
  - BArray< Cell\_Type, Data\_Type >, 40
  - BArrayDense< Cell\_Type, Data\_Type >, 60
- DEFM, 111
  - ~DEFM, 112
  - DEFM, 111
  - get\_ID, 112
  - get\_m\_order, 112
  - get\_model, 112
  - get\_n\_covars, 112
  - get\_n\_obs, 113
  - get\_n\_rows, 113
  - get\_n\_y, 113
  - get\_X, 113
  - get\_Y, 113
  - init, 113
  - likelihood, 114
  - motif\_census, 114

- simulate, 114
- defm-meat.hpp
  - DEFM\_LOOP\_ARRAYS, 313
  - DEFM\_RANGES, 313
  - keygen\_defm, 314
- defm.hpp
  - DEFM\_COUNTER, 281
  - DEFM\_COUNTER\_LAMBDA, 281
  - DEFM\_RULE, 282
  - DEFM\_RULE\_LAMBDA, 282
  - DEFMArray, 284
  - DEFMCounter, 284
  - DEFMCounters, 284
  - DEFMModel, 284
  - DEFMRule, 284
  - DEFMRules, 285
  - DEFMStatsCounter, 285
  - DEFMSupport, 285
  - UNI0S, 282
  - UNI1S, 282
  - UNI2S, 282
  - UNI3S, 283
  - UNI4S, 283
  - UNI5S, 283
  - UNI6S, 283
  - UNI7S, 283
  - UNI8S, 283
  - UNI9S, 283
  - UNI\_SUB, 283
- DEFM\_COUNTER
  - defm.hpp, 281
- DEFM\_COUNTER\_LAMBDA
  - defm.hpp, 281
- DEFM\_LOOP\_ARRAYS
  - defm-meat.hpp, 313
- DEFM\_RANGES
  - defm-meat.hpp, 313
- DEFM\_RULE
  - defm.hpp, 282
- DEFM\_RULE\_LAMBDA
  - defm.hpp, 282
- DEFMArray
  - defm.hpp, 284
- DEFMArray counters, 12
  - counter\_absdiff, 14
  - counter\_ctriads, 14
  - counter\_degree, 14
  - counter\_density, 14
  - counter\_diff, 15
  - counter\_edges, 15
  - counter\_fixed\_effect, 15
  - counter\_iddegree, 16
  - counter\_iddegree15, 16
  - counter\_isolates, 16, 17
  - counter\_istar2, 17
  - counter\_mutual, 17
  - counter\_nodecov, 17
  - counter\_nodeicov, 18
  - counter\_nodematch, 18
  - counter\_nodecov, 18
  - counter\_odegree, 18
  - counter\_odegree15, 19
  - counter\_ones, 19
  - counter\_ostar2, 19, 20
  - counter\_transition, 20
  - counter\_ttriads, 20
  - NETWORK\_COUNTER, 21
  - rules\_markov\_fixed, 21
- DEFMCounter
  - defm.hpp, 284
- DEFMCounterData, 114
  - ~DEFMCounterData, 115
  - DEFMCounterData, 115
  - idx, 116
  - indices, 116
  - is\_true, 116
  - logical, 116
  - num, 116
  - numbers, 117
- DEFMCounters
  - defm.hpp, 284
- DEFMData, 117
  - ~DEFMData, 119
  - array, 120
  - at, 119
  - covariates, 120
  - DEFMData, 118
  - ncol, 119
  - obs\_start, 120
  - operator(), 119
  - print, 119
  - X\_ncol, 120
  - X\_nrow, 120
- DEFMModel
  - defm.hpp, 284
- DEFMRule
  - defm.hpp, 284
- DEFMRuleData, 121
  - DEFMRuleData, 121
  - idx, 122
  - num, 122
- DEFMRules
  - defm.hpp, 285
- DEFMStatsCounter
  - defm.hpp, 285
- DEFMSupport
  - defm.hpp, 285
- delete\_counters
  - Support< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 204
  - support-meat.hpp, 340
- delete\_data
  - barray-meat.hpp, 226
  - barraydense-meat.hpp, 250
- delete\_data\_

- barray-meat.hpp, 226
  - barraydense-meat.hpp, 251
- delete\_engine
  - Geese, 146
- delete\_rules
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 204
  - support-meat.hpp, 340
- delete\_rules\_dyn
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 204
  - support-meat.hpp, 340
- delete\_support
  - Geese, 146
- desc
  - Counter< Array\_Type, Data\_Type >, 106
  - counters-meat.hpp, 276
- desc\_
  - counters-meat.hpp, 278
- directed
  - NetworkData, 165
- DUPL\_DUPL
  - phylo.hpp, 303
- DUPL\_EITH
  - phylo.hpp, 303
- DUPL\_SPEC
  - phylo.hpp, 303
- duplication
  - Node, 170
  - NodeData, 173
  - PhyloRuleDynData, 177
- el
  - barraydense-meat.hpp, 251
- el\_colsums
  - barraydense-meat.hpp, 251
- el\_rowsums
  - barraydense-meat.hpp, 251
- else
  - barray-meat.hpp, 226
  - barraydense-meat.hpp, 251
  - support-meat.hpp, 340
- empty
  - PhyloCounterData, 174
- EmptyArray
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 183
  - statscounter-meat.hpp, 330
- end
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 75
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 77
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 79
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 82
  - BArrayVector< Cell\_Type, Data\_Type >, 89
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 93
  - PhyloCounterData, 175
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 181
  - Progress, 186
- Entries
  - Entries< Cell\_Type >, 123
- Entries< Cell\_Type >, 122
  - ~Entries, 123
  - Entries, 123
  - resize, 123
  - source, 124
  - target, 124
  - val, 124
- eval\_rules\_dyn
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 200
- EXISTS, 33
  - AS\_ONE, 33
  - AS\_ZERO, 33
  - BOTH, 34
  - NONE, 34
  - ONE, 34
  - TWO, 34
  - UNKNOWN, 34
- f\_
  - statscounter-meat.hpp, 331
  - support-meat.hpp, 341
- false
  - barray-meat.hpp, 226
  - barraydense-meat.hpp, 252
- first
  - barray-meat.hpp, 227
- Flock, 124
  - ~Flock, 126
  - add\_data, 126
  - colnames, 126
  - dat, 130
  - Flock, 126
  - get\_counters, 127
  - get\_model, 127
  - get\_stats\_support, 127
  - get\_stats\_target, 127
  - get\_support\_fun, 127
  - init, 127
  - initialized, 130
  - likelihood\_joint, 128
  - model, 131
  - nfunctions, 131
  - nfuncs, 128
  - nleaves, 128
  - nnodes, 128
  - nterms, 129
  - ntrees, 129
  - operator(), 129
  - parse\_polytomies, 129
  - print, 130
  - rengine, 131
  - set\_seed, 130
  - support\_size, 130



- flush\_data
  - BArray< Cell\_Type, Data\_Type >, 40
- for
  - barray-meat-operators.hpp, 211
  - barray-meat.hpp, 220
  - barraydense-meat.hpp, 245
  - statscounter-meat.hpp, 327
  - support-meat.hpp, 334
- FreqTable
  - FreqTable< T >, 132
- FreqTable< T >, 131
  - ~FreqTable, 132
  - add, 133
  - as\_vector, 133
  - clear, 133
  - FreqTable, 132
  - get\_data, 133
  - get\_index, 133
  - make\_hash, 134
  - print, 134
  - reserve, 134
  - size, 134
- Geese, 135
  - ~Geese, 139
  - calc\_reduced\_sequence, 139
  - calc\_sequence, 139
  - colnames, 140
  - delete\_engine, 146
  - delete\_support, 146
  - Geese, 138, 139
  - get\_annotated\_nodes, 140
  - get\_counters, 140
  - get\_model, 140
  - get\_probabilities, 140
  - get\_engine, 140
  - get\_states, 141
  - get\_support\_fun, 141
  - inherit\_support, 141
  - init, 141
  - init\_node, 141
  - initialized, 146
  - likelihood, 142
  - likelihood\_exhaust, 142
  - map\_to\_nodes, 147
  - nannotations, 142
  - nfunctions, 147
  - nfuncs, 142
  - nleaves, 142
  - nnodes, 143
  - nodes, 147
  - nterms, 143
  - observed\_counts, 143
  - operator=, 143
  - parse\_polytomies, 143
  - predict, 144
  - predict\_backend, 144
  - predict\_exhaust, 144
  - predict\_exhaust\_backend, 144
  - predict\_sim, 145
  - print, 145
  - print\_observed\_counts, 145
  - pset\_loc, 147
  - reduced\_sequence, 147
  - sequence, 147
  - set\_seed, 145
  - simulate, 145
  - support\_size, 146
  - update\_annotations, 146
- geese-bones.hpp
  - INITIALIZED, 316
  - keygen\_full, 316
  - RULE\_FUNCTION, 316
  - vec\_diff, 317
  - vector\_caster, 317
- gen\_key
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 154
- get\_annotated\_nodes
  - Geese, 140
- get\_arrays2support
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 154
- get\_cell
  - BArray< Cell\_Type, Data\_Type >, 40
  - BArrayDense< Cell\_Type, Data\_Type >, 60
- get\_col\_vec
  - BArray< Cell\_Type, Data\_Type >, 41
  - BArrayDense< Cell\_Type, Data\_Type >, 60, 61
- get\_counters
  - Flock, 127
  - Geese, 140
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 154
  - PhyloCounterData, 175
  - StatsCounter< Array\_Type, Data\_Type >, 194
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 200
- get\_counts
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 200
- get\_current\_stats
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 200
- get\_data
  - BArrayDense< Cell\_Type, Data\_Type >, 61
  - FreqTable< T >, 133
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 181
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 200



- get\_data\_ptr
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 182
- get\_description
  - Counter< Array\_Type, Data\_Type >, 105
- get\_descriptions
  - Counters< Array\_Type, Data\_Type >, 109
  - StatsCounter< Array\_Type, Data\_Type >, 194
- get\_entries
  - BArray< Cell\_Type, Data\_Type >, 41
  - BArrayDense< Cell\_Type, Data\_Type >, 61
- get\_ID
  - DEFM, 112
- get\_index
  - FreqTable< T >, 133
- get\_last\_name
  - phylo.hpp, 308
- get\_m\_order
  - DEFM, 112
- get\_model
  - DEFM, 112
  - Flock, 127
  - Geese, 140
- get\_n\_covars
  - DEFM, 112
- get\_n\_obs
  - DEFM, 113
- get\_n\_rows
  - DEFM, 113
- get\_n\_y
  - DEFM, 113
- get\_name
  - Counter< Array\_Type, Data\_Type >, 105
- get\_names
  - Counters< Array\_Type, Data\_Type >, 109
  - StatsCounter< Array\_Type, Data\_Type >, 194
- get\_norm\_const
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 155
- get\_parent
  - Node, 168
- get\_probabilities
  - Geese, 140
- get\_pset
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 155
- get\_pset\_arrays
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 155
- get\_pset\_probs
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 155
- get\_pset\_stats
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 155, 156
- get\_rengine
  - Geese, 140
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 156
- get\_row\_vec
  - BArray< Cell\_Type, Data\_Type >, 41
  - BArrayDense< Cell\_Type, Data\_Type >, 61
- get\_rules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 156
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 201
- get\_rules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 156
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 201
- get\_seq
  - Rules< Array\_Type, Data\_Type >, 190
- get\_states
  - Geese, 141
- get\_stats\_support
  - Flock, 127
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 156
- get\_stats\_target
  - Flock, 127
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 157
- get\_support\_fun
  - Flock, 127
  - Geese, 141
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 157
- get\_X
  - DEFM, 113
- get\_Y
  - DEFM, 113
- hashes
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 204
  - support-meat.hpp, 341
- hashes\_initialized
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 204

i

- counters-meat.hpp, 278
- i1
  - barray-meat.hpp, 227
  - barraydense-meat.hpp, 252
- id
  - Node, 170
- idx
  - DEFMCounterData, 116
  - DEFMRuleData, 122
- if
  - barray-meat.hpp, 220–223
  - barraydense-meat.hpp, 246
  - support-meat.hpp, 334, 335
- IF\_MATCHES
  - phylo.hpp, 304
- IF\_NOTMATCHES
  - phylo.hpp, 304
- include/barry/barray-bones.hpp, 207
- include/barry/barray-iterator.hpp, 207
- include/barry/barray-meat-operators.hpp, 208
- include/barry/barray-meat.hpp, 212
- include/barry/barraycell-bones.hpp, 230
- include/barry/barraycell-meat.hpp, 230
- include/barry/barraydense-bones.hpp, 231
- include/barry/barraydense-meat-operators.hpp, 231
- include/barry/barraydense-meat.hpp, 234
- include/barry/barraydensecell-bones.hpp, 255
- include/barry/barraydensecell-meat.hpp, 256
- include/barry/barraydensecol-bones.hpp, 256
- include/barry/barraydenserow-bones.hpp, 258
- include/barry/barrayrow-bones.hpp, 259
- include/barry/barrayrow-meat.hpp, 259
- include/barry/barrayvector-bones.hpp, 261
- include/barry/barrayvector-meat.hpp, 262
- include/barry/barray-configuration.hpp, 262
- include/barry/barray-debug.hpp, 264
- include/barry/barray-macros.hpp, 265
- include/barry/barray.hpp, 266
- include/barry/cell-bones.hpp, 269
- include/barry/cell-meat.hpp, 270
- include/barry/col-bones.hpp, 270
- include/barry/counters-bones.hpp, 270
- include/barry/counters-meat.hpp, 271
- include/barry/counters/defm.hpp, 280
- include/barry/counters/network-css.hpp, 286
- include/barry/counters/network.hpp, 294
- include/barry/counters/phylo.hpp, 301
- include/barry/freqtable.hpp, 308
- include/barry/model-bones.hpp, 309
- include/barry/model-meat.hpp, 310
- include/barry/models/defm.hpp, 285
- include/barry/models/defm/defm-bones.hpp, 312
- include/barry/models/defm/defm-meat.hpp, 313
- include/barry/models/geese.hpp, 314
- include/barry/models/geese/flock-bones.hpp, 314
- include/barry/models/geese/flock-meat.hpp, 315
- include/barry/models/geese/geese-bones.hpp, 315
- include/barry/models/geese/geese-meat-constructors.hpp, 317
- include/barry/models/geese/geese-meat-likelihood.hpp, 318
- include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp, 319
- include/barry/models/geese/geese-meat-predict.hpp, 319
- include/barry/models/geese/geese-meat-predict\_exhaust.hpp, 320
- include/barry/models/geese/geese-meat-predict\_sim.hpp, 320
- include/barry/models/geese/geese-meat-simulate.hpp, 321
- include/barry/models/geese/geese-meat.hpp, 321
- include/barry/models/geese/geese-node-bones.hpp, 322
- include/barry/powerset-bones.hpp, 322
- include/barry/powerset-meat.hpp, 323
- include/barry/progress.hpp, 323
- include/barry/rules-bones.hpp, 324
- include/barry/rules-meat.hpp, 325
- include/barry/statscounter-bones.hpp, 325
- include/barry/statscounter-meat.hpp, 326
- include/barry/support-bones.hpp, 331
- include/barry/support-meat.hpp, 332
- include/barry/typedefs.hpp, 343
- indices
  - DEFMCounterData, 116
  - NetCounterData, 163
- inherit\_support
  - Geese, 141
- init
  - Counter< Array\_Type, Data\_Type >, 105
  - DEFM, 113
  - Flock, 127
  - Geese, 141
- init\_fun
  - Counter< Array\_Type, Data\_Type >, 106
  - counters-meat.hpp, 276, 277
- init\_fun\_
  - counters-meat.hpp, 278
- init\_node
  - Geese, 141
- init\_support
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 182
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 201
- INITIALIZED
  - geese-bones.hpp, 316
- initialized
  - Flock, 130
  - Geese, 146
- insert\_cell
  - BArray< Cell\_Type, Data\_Type >, 42
  - BArrayDense< Cell\_Type, Data\_Type >, 62
  - barraydense-meat.hpp, 246

- support-meat.hpp, 335
- is\_col
  - BArrayVector< Cell\_Type, Data\_Type >, 89
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 93
- is\_dense
  - BArray< Cell\_Type, Data\_Type >, 42
  - BArrayDense< Cell\_Type, Data\_Type >, 62
- IS\_DUPLICATION
  - phylo.hpp, 304
- IS\_EITHER
  - phylo.hpp, 304
- is\_empty
  - BArray< Cell\_Type, Data\_Type >, 42
  - BArrayDense< Cell\_Type, Data\_Type >, 62
- is\_leaf
  - Node, 169
- is\_row
  - BArrayVector< Cell\_Type, Data\_Type >, 89
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 93
- IS\_SPECIATION
  - phylo.hpp, 304
- is\_true
  - DEFMCounterData, 116
- iter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 102
- j
  - barray-meat.hpp, 227
  - barraydense-meat.hpp, 252
  - counters-meat.hpp, 279
  - statscounter-meat.hpp, 331
- j0
  - barray-meat.hpp, 227
  - barraydense-meat.hpp, 252
- j1
  - barray-meat.hpp, 227
  - barraydense-meat.hpp, 252
- keygen\_default
  - model-bones.hpp, 309
- keygen\_defm
  - defm-meat.hpp, 314
- keygen\_full
  - geese-bones.hpp, 316
- lb
  - PhyloRuleDynData, 177
- likelihood
  - DEFM, 114
  - Geese, 142
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 157, 158
- likelihood\_
  - model-meat.hpp, 311
- likelihood\_exhaust
  - Geese, 142
- likelihood\_joint
  - Flock, 128
- likelihood\_total
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 158
- logical
  - DEFMCounterData, 116
- M
  - barray-meat.hpp, 223, 227
  - barraydense-meat.hpp, 247, 252
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 183
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 205
- M\_
  - barray-meat.hpp, 228
  - barraydense-meat.hpp, 253
- MAKE\_DUPL\_VARS
  - phylo.hpp, 305
- make\_hash
  - FreqTable< T >, 134
- Map
  - barry-configuration.hpp, 263
- map\_to\_nodes
  - Geese, 147
- MapVec\_type
  - typedefs.hpp, 345
- max\_num\_elements
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 205
- Model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 151
- model
  - Flock, 131
- Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 148
  - ~Model, 151
  - add\_array, 152
  - add\_counter, 152
  - add\_rule, 152, 153
  - add\_rule\_dyn, 153
  - colnames, 153
  - conditional\_prob, 153
  - gen\_key, 154
  - get\_arrays2support, 154
  - get\_counters, 154
  - get\_norm\_const, 155
  - get\_pset, 155
  - get\_pset\_arrays, 155
  - get\_pset\_probs, 155
  - get\_pset\_stats, 155, 156
  - get\_engine, 156
  - get\_rules, 156
  - get\_rules\_dyn, 156
  - get\_stats\_support, 156

- get\_stats\_target, 157
- get\_support\_fun, 157
- likelihood, 157, 158
- likelihood\_total, 158
- Model, 151
- nterms, 158
- operator=, 158
- print, 158
- print\_stats, 159
- sample, 159
- set\_counters, 159
- set\_keygen, 159
- set\_rengine, 160
- set\_rules, 160
- set\_rules\_dyn, 160
- set\_seed, 160
- set\_transform\_model, 160
- size, 161
- size\_unique, 161
- store\_psets, 161
- support\_size, 161
- transform\_model, 162
- model-bones.hpp
  - keygen\_default, 309
- model-meat.hpp
  - likelihood\_, 311
  - MODEL\_TEMPLATE, 310, 311
  - MODEL\_TEMPLATE\_ARGS, 310
  - MODEL\_TYPE, 311
  - update\_normalizing\_constant, 312
- MODEL\_TEMPLATE
  - model-meat.hpp, 310, 311
- MODEL\_TEMPLATE\_ARGS
  - model-meat.hpp, 310
- MODEL\_TYPE
  - model-meat.hpp, 311
- motif\_census
  - DEFM, 114
- N
  - barray-meat.hpp, 228
  - barraydense-meat.hpp, 253
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 184
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 205
- n\_counters
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 205
- n\_free
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 184
- n\_locked
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 184
- name
  - Counter< Array\_Type, Data\_Type >, 106
  - counters-meat.hpp, 277
- name\_
  - counters-meat.hpp, 279
- nannotations
  - Geese, 142
- narray
  - Node, 170
- NCells
  - barray-meat.hpp, 228
- ncol
  - BArray< Cell\_Type, Data\_Type >, 43
  - BArrayDense< Cell\_Type, Data\_Type >, 62
  - DEFMData, 119
- NET\_C\_DATA\_IDX
  - network.hpp, 297
- NET\_C\_DATA\_NUM
  - network.hpp, 297
- NetCounter
  - network.hpp, 299
- NetCounterData, 162
  - ~NetCounterData, 163
  - indices, 163
  - NetCounterData, 163
  - numbers, 163
- NetCounters
  - network.hpp, 299
- NetModel
  - network.hpp, 299
- NetRule
  - network.hpp, 299
- NetRules
  - network.hpp, 299
- NetStatsCounter
  - network.hpp, 299
- NetSupport
  - network.hpp, 300
- Network
  - network.hpp, 300
- network-css.hpp
  - counter\_css\_census01, 289
  - counter\_css\_census02, 290
  - counter\_css\_census03, 290
  - counter\_css\_census04, 290
  - counter\_css\_census05, 290
  - counter\_css\_census06, 291
  - counter\_css\_census07, 291
  - counter\_css\_census08, 291
  - counter\_css\_census09, 291
  - counter\_css\_census10, 292
  - counter\_css\_completely\_false\_recip\_comiss, 292
  - counter\_css\_completely\_false\_recip\_omiss, 292
  - counter\_css\_mixed\_recip, 292
  - counter\_css\_partially\_false\_recip\_commi, 293
  - counter\_css\_partially\_false\_recip\_omiss, 293
  - CSS\_APPEND, 287
  - CSS\_CASE\_ELSE, 287
  - CSS\_CASE\_PERCEIVED, 288
  - CSS\_CASE\_TRUTH, 288
  - CSS\_CHECK\_SIZE, 288
  - CSS\_CHECK\_SIZE\_INIT, 288
  - CSS\_NET\_COUNTER\_LAMBDA\_INIT, 288

- CSS\_PERCEIVED\_CELLS, 289
- CSS\_SIZE, 289
- CSS\_TRUE\_CELLS, 289
- network.hpp
  - BARRY\_ZERO\_NETWORK, 296
  - BARRY\_ZERO\_NETWORK\_DENSE, 297
  - NET\_C\_DATA\_IDX, 297
  - NET\_C\_DATA\_NUM, 297
  - NetCounter, 299
  - NetCounters, 299
  - NetModel, 299
  - NetRule, 299
  - NetRules, 299
  - NetStatsCounter, 299
  - NetSupport, 300
  - Network, 300
  - NETWORK\_COUNTER, 297
  - NETWORK\_COUNTER\_LAMBDA, 297
  - NETWORK\_RULE, 298
  - NETWORK\_RULE\_LAMBDA, 298
  - NetworkDense, 300
  - NETWORKDENSE\_COUNTER\_LAMBDA, 298
  - rules\_zerodiag, 300
- NETWORK\_COUNTER
  - DEFMArray counters, 21
  - network.hpp, 297
- NETWORK\_COUNTER\_LAMBDA
  - network.hpp, 297
- NETWORK\_RULE
  - network.hpp, 298
- NETWORK\_RULE\_LAMBDA
  - network.hpp, 298
- NetworkData, 164
  - ~NetworkData, 165
  - directed, 165
  - NetworkData, 164, 165
  - vertex\_attr, 165
- NetworkDense
  - network.hpp, 300
- NETWORKDENSE\_COUNTER\_LAMBDA
  - network.hpp, 298
- next
  - Progress, 186
- nfunctions
  - Flock, 131
  - Geese, 147
- nfuncs
  - Flock, 128
  - Geese, 142
- nleafs
  - Flock, 128
  - Geese, 142
- nnodes
  - Flock, 128
  - Geese, 143
- nnozero
  - BArray< Cell\_Type, Data\_Type >, 43
  - BArrayDense< Cell\_Type, Data\_Type >, 63
- Node, 166
  - ~Node, 168
  - annotations, 169
  - array, 169
  - arrays, 169
  - duplication, 170
  - get\_parent, 168
  - id, 170
  - is\_leaf, 169
  - narray, 170
  - Node, 167, 168
  - noffspring, 169
  - offspring, 170
  - ord, 170
  - parent, 171
  - probability, 171
  - subtree\_prob, 171
  - visited, 171
- NodeData, 172
  - blengths, 172
  - duplication, 173
  - NodeData, 172
  - states, 173
- nodes
  - Geese, 147
- noexcept
  - counters-meat.hpp, 279
- noffspring
  - Node, 169
- NONE
  - CHECK, 32
  - EXISTS, 34
- nrow
  - BArray< Cell\_Type, Data\_Type >, 43
  - BArrayDense< Cell\_Type, Data\_Type >, 63
- nterms
  - Flock, 129
  - Geese, 143
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 158
- ntrees
  - Flock, 129
- num
  - DEFMCounterData, 116
  - DEFMRuleData, 122
- numbers
  - DEFMCounterData, 117
  - NetCounterData, 163
- obs\_start
  - DEFMData, 120
- observed\_counts
  - Geese, 143
- offspring
  - Node, 170
- ONE
  - CHECK, 32
  - EXISTS, 34

- operator BArrayRow< Cell\_Type, Data\_Type >
  - BArrayRow< Cell\_Type, Data\_Type >, [84](#)
- operator BArrayRow\_const< Cell\_Type, Data\_Type >
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [86](#)
- operator Cell\_Type
  - BArrayCell< Cell\_Type, Data\_Type >, [50](#)
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [71](#)
  - Cell< Cell\_Type >, [98](#)
- operator std::vector< Cell\_Type >
  - BArrayVector< Cell\_Type, Data\_Type >, [90](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [93](#)
- operator!=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [86](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [93](#)
  - Cell< Cell\_Type >, [98](#)
- operator<
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [86](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [94](#)
- operator<=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [87](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [94](#)
- operator>
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [87](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [94](#)
- operator>=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [54](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [87](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [94](#)
- operator\*=
  - BArray< Cell\_Type, Data\_Type >, [43](#)
  - BArrayCell< Cell\_Type, Data\_Type >, [50](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [63](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [71](#)
  - BArrayRow< Cell\_Type, Data\_Type >, [84](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [90](#)
- operator()
  - BArray< Cell\_Type, Data\_Type >, [43](#)
  - barray-meat-operators.hpp, [211](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [63](#)
  - BArrayDenseCol< Cell\_Type, Data\_Type >, [75](#)
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, [77](#)
  - BArrayDenseRow< Cell\_Type, Data\_Type >, [80](#)
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, [82](#)
  - DEFMDData, [119](#)
  - Flock, [129](#)
  - PhyloCounterData, [175](#)
  - Rule< Array\_Type, Data\_Type >, [188](#)
  - Rules< Array\_Type, Data\_Type >, [191](#)
  - vecHasher< T >, [206](#)
- operator+=
  - BArray< Cell\_Type, Data\_Type >, [44](#)
- BArrayCell< Cell\_Type, Data\_Type >, [50](#)
- BArrayDense< Cell\_Type, Data\_Type >, [63](#), [64](#)
- BArrayDenseCell< Cell\_Type, Data\_Type >, [71](#)
- BArrayRow< Cell\_Type, Data\_Type >, [84](#)
- BArrayVector< Cell\_Type, Data\_Type >, [90](#)
- operator==
  - BArray< Cell\_Type, Data\_Type >, [44](#)
  - BArrayCell< Cell\_Type, Data\_Type >, [51](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [64](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [72](#)
  - BArrayRow< Cell\_Type, Data\_Type >, [84](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [90](#)
- operator/=
  - BArray< Cell\_Type, Data\_Type >, [45](#)
  - BArrayCell< Cell\_Type, Data\_Type >, [51](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [64](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [72](#)
  - BArrayRow< Cell\_Type, Data\_Type >, [85](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [90](#)
- operator=
  - BArray< Cell\_Type, Data\_Type >, [45](#)
  - BArrayCell< Cell\_Type, Data\_Type >, [51](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [65](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [72](#)
  - BArrayRow< Cell\_Type, Data\_Type >, [85](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [91](#)
  - Cell< Cell\_Type >, [98](#), [99](#)
  - Counter< Array\_Type, Data\_Type >, [105](#)
  - Counters< Array\_Type, Data\_Type >, [109](#), [110](#)
  - Geese, [143](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [158](#)
  - Rules< Array\_Type, Data\_Type >, [191](#)
- operator==
  - BArray< Cell\_Type, Data\_Type >, [45](#)
  - BArrayCell< Cell\_Type, Data\_Type >, [51](#)
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [53](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [65](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [72](#)
  - BArrayRow< Cell\_Type, Data\_Type >, [85](#)
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [87](#)
  - BArrayVector< Cell\_Type, Data\_Type >, [91](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [94](#)
  - Cell< Cell\_Type >, [99](#)
- operator[]
  - Counters< Array\_Type, Data\_Type >, [110](#)
  - PhyloCounterData, [175](#)
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [182](#)
- ord
  - Node, [170](#)
- out\_of\_range
  - BArray< Cell\_Type, Data\_Type >, [45](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [65](#)
- parent
  - Node, [171](#)
- parse\_polytomies
  - Flock, [129](#)

- Geese, [143](#)
- Phylo counters, [21](#)
  - counter\_co\_opt, [23](#)
  - counter\_cogain, [23](#)
  - counter\_gains, [23](#)
  - counter\_gains\_from\_0, [23](#)
  - counter\_gains\_k\_offspring, [24](#)
  - counter\_genes\_changing, [24](#)
  - counter\_k\_genes\_changing, [24](#)
  - counter\_less\_than\_p\_prop\_genes\_changing, [24](#)
  - counter\_longest, [25](#)
  - counter\_loss, [25](#)
  - counter\_maxfun, [25](#)
  - counter\_neofun, [25](#)
  - counter\_neofun\_a2b, [26](#)
  - counter\_overall\_changes, [26](#)
  - counter\_overall\_gains, [26](#)
  - counter\_overall\_gains\_from\_0, [26](#)
  - counter\_overall\_loss, [27](#)
  - counter\_pairwise\_first\_gain, [27](#)
  - counter\_pairwise\_neofun\_singlefun, [27](#)
  - counter\_pairwise\_overall\_change, [27](#)
  - counter\_pairwise\_preserving, [28](#)
  - counter\_preserve\_pseudogene, [28](#)
  - counter\_prop\_genes\_changing, [28](#)
  - counter\_subfun, [28](#)
- Phylo rules, [29](#)
  - rule\_dyn\_limit\_changes, [29](#)
- phylo.hpp
  - DEFAULT\_DUPLICATION, [303](#)
  - DUPL\_DUPL, [303](#)
  - DUPL\_EITH, [303](#)
  - DUPL\_SPEC, [303](#)
  - get\_last\_name, [308](#)
  - IF\_MATCHES, [304](#)
  - IF\_NOTMATCHES, [304](#)
  - IS\_DUPLICATION, [304](#)
  - IS\_EITHER, [304](#)
  - IS\_SPECIATION, [304](#)
  - MAKE\_DUPL\_VARS, [305](#)
  - PHYLO\_CHECK\_MISSING, [305](#)
  - PHYLO\_COUNTER\_LAMBDA, [305](#)
  - PHYLO\_RULE\_DYN\_LAMBDA, [305](#)
  - PhyloArray, [306](#)
  - PhyloCounter, [306](#)
  - PhyloCounters, [306](#)
  - PhyloModel, [306](#)
  - PhyloPowerSet, [306](#)
  - PhyloRule, [307](#)
  - PhyloRuleData, [307](#)
  - PhyloRuleDyn, [307](#)
  - PhyloRules, [307](#)
  - PhyloRulesDyn, [307](#)
  - PhyloStatsCounter, [307](#)
  - PhyloSupport, [308](#)
- PHYLO\_CHECK\_MISSING
  - phylo.hpp, [305](#)
- PHYLO\_COUNTER\_LAMBDA
  - phylo.hpp, [305](#)
- PHYLO\_RULE\_DYN\_LAMBDA
  - phylo.hpp, [305](#)
- PhyloArray
  - phylo.hpp, [306](#)
- PhyloCounter
  - phylo.hpp, [306](#)
- PhyloCounterData, [173](#)
  - at, [174](#)
  - begin, [174](#)
  - empty, [174](#)
  - end, [175](#)
  - get\_counters, [175](#)
  - operator(), [175](#)
  - operator[], [175](#)
  - PhyloCounterData, [174](#)
  - push\_back, [175](#)
  - reserve, [175](#)
  - shrink\_to\_fit, [176](#)
  - size, [176](#)
- PhyloCounters
  - phylo.hpp, [306](#)
- PhyloModel
  - phylo.hpp, [306](#)
- PhyloPowerSet
  - phylo.hpp, [306](#)
- PhyloRule
  - phylo.hpp, [307](#)
- PhyloRuleData
  - phylo.hpp, [307](#)
- PhyloRuleDyn
  - phylo.hpp, [307](#)
- PhyloRuleDynData, [176](#)
  - ~PhyloRuleDynData, [177](#)
  - counts, [177](#)
  - duplication, [177](#)
  - lb, [177](#)
  - PhyloRuleDynData, [177](#)
  - pos, [177](#)
  - ub, [178](#)
- PhyloRules
  - phylo.hpp, [307](#)
- PhyloRulesDyn
  - phylo.hpp, [307](#)
- PhyloStatsCounter
  - phylo.hpp, [307](#)
- PhyloSupport
  - phylo.hpp, [308](#)
- POS
  - barraydense-meat-operators.hpp, [232](#)
  - barraydense-meat.hpp, [237](#)
  - barraydensecell-bones.hpp, [255](#)
  - barraydensecell-meat.hpp, [256](#)
  - barraydensecol-bones.hpp, [257](#)
  - barraydenserow-bones.hpp, [258](#)
- pos
  - PhyloRuleDynData, [177](#)
- POS\_N



- barraydense-meat-operators.hpp, 233
  - barraydense-meat.hpp, 237
  - barraydensecol-bones.hpp, 257
  - barraydenserow-bones.hpp, 258
- PowerSet
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 180
- PowerSet< Array\_Type, Data\_Rule\_Type >, 178
  - ~PowerSet, 180
  - add\_rule, 180, 181
  - begin, 181
  - calc, 181
  - coordinates\_free, 183
  - coordinates\_locked, 183
  - data, 183
  - EmptyArray, 183
  - end, 181
  - get\_data, 181
  - get\_data\_ptr, 182
  - init\_support, 182
  - M, 183
  - N, 184
  - n\_free, 184
  - n\_locked, 184
  - operator[], 182
  - PowerSet, 180
  - reset, 182
  - rules, 184
  - rules\_deleted, 184
  - size, 182
- predict
  - Geese, 144
- predict\_backend
  - Geese, 144
- predict\_exhaust
  - Geese, 144
- predict\_exhaust\_backend
  - Geese, 144
- predict\_sim
  - Geese, 145
- print
  - BArray< Cell\_Type, Data\_Type >, 45
  - BArrayDense< Cell\_Type, Data\_Type >, 65
  - DEFMDData, 119
  - Flock, 130
  - FreqTable< T >, 134
  - Geese, 145
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 158
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 201
- print\_observed\_counts
  - Geese, 145
- print\_stats
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 159
- printf\_barry
  - barry-configuration.hpp, 263
- probability
  - Node, 171
- Progress, 185
  - ~Progress, 185
  - end, 186
  - next, 186
  - Progress, 185
- progress.hpp
  - BARRY\_PROGRESS\_BAR\_WIDTH, 324
- pset\_loc
  - Geese, 147
- push\_back
  - PhyloCounterData, 175
- README.md, 347
- reduced\_sequence
  - Geese, 147
- engine
  - Flock, 131
- report
  - barray-meat.hpp, 228
  - barraydense-meat.hpp, 253
- reserve
  - BArray< Cell\_Type, Data\_Type >, 46
  - BArrayDense< Cell\_Type, Data\_Type >, 65
  - FreqTable< T >, 134
  - PhyloCounterData, 175
- reset
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 182
- reset\_array
  - StatsCounter< Array\_Type, Data\_Type >, 194
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 201, 202
- resize
  - BArray< Cell\_Type, Data\_Type >, 46
  - barray-meat.hpp, 223
  - BArrayDense< Cell\_Type, Data\_Type >, 66
  - barraydense-meat.hpp, 247, 248
  - Entries< Cell\_Type >, 123
  - statscounter-meat.hpp, 328
- return
  - barray-meat.hpp, 223, 228
  - barraydense-meat.hpp, 253
  - counters-meat.hpp, 279
  - statscounter-meat.hpp, 331
  - support-meat.hpp, 341
- rhs
  - barray-meat-operators.hpp, 211
- rm\_cell
  - BArray< Cell\_Type, Data\_Type >, 46
  - BArrayDense< Cell\_Type, Data\_Type >, 66
  - barraydense-meat.hpp, 248
  - support-meat.hpp, 335
- ROW
  - barray-meat-operators.hpp, 209
  - barray-meat.hpp, 215, 223, 224



- barraydense-meat-operators.hpp, 233
  - barraydense-meat.hpp, 238
- row
  - BArray< Cell\_Type, Data\_Type >, 46
  - BArrayDense< Cell\_Type, Data\_Type >, 66
- row0
  - barray-meat.hpp, 229
- Row\_type
  - typedefs.hpp, 345
- rowsum
  - BArrayDense< Cell\_Type, Data\_Type >, 66
- Rule
  - Rule< Array\_Type, Data\_Type >, 187
- Rule< Array\_Type, Data\_Type >, 186
  - ~Rule, 187
  - D, 188
  - operator(), 188
  - Rule, 187
- rule\_dyn\_limit\_changes
  - Phylo rules, 29
- rule\_fun\_default
  - rules-bones.hpp, 324
- Rule\_fun\_type
  - typedefs.hpp, 346
- RULE\_FUNCTION
  - barry.hpp, 269
  - geese-bones.hpp, 316
- RULE\_LAMBDA
  - barry.hpp, 269
- Rules
  - Rules< Array\_Type, Data\_Type >, 189
- rules
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 184
  - support-meat.hpp, 341
- Rules< Array\_Type, Data\_Type >, 188
  - ~Rules, 189
  - add\_rule, 190
  - get\_seq, 190
  - operator(), 191
  - operator=, 191
  - Rules, 189
  - size, 191
- rules-bones.hpp
  - rule\_fun\_default, 324
- rules\_
  - support-meat.hpp, 341
- rules\_deleted
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 184
- rules\_dyn
  - support-meat.hpp, 342
- rules\_markov\_fixed
  - DEFMArray counters, 21
- rules\_zerodiag
  - network.hpp, 300
- sample
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 159
- search
  - barray-meat.hpp, 229
- sequence
  - Geese, 147
- set\_counters
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 159
  - StatsCounter< Array\_Type, Data\_Type >, 195
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 202
- set\_data
  - BArray< Cell\_Type, Data\_Type >, 46
  - BArrayDense< Cell\_Type, Data\_Type >, 66
- set\_keygen
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 159
- set\_rengine
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 160
- set\_rules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 160
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 202
- set\_rules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 160
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 202
- set\_seed
  - Flock, 130
  - Geese, 145
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 160
- set\_transform\_model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 160
- shrink\_to\_fit
  - PhyloCounterData, 176
- simulate
  - DEFM, 114
  - Geese, 145
- size
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 75
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 78
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 80
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >

- [>](#), [82](#)
- [BArrayVector< Cell\\_Type, Data\\_Type >](#), [91](#)
- [BArrayVector\\_const< Cell\\_Type, Data\\_Type >](#), [95](#)
- [Counters< Array\\_Type, Data\\_Type >](#), [110](#)
- [FreqTable< T >](#), [134](#)
- [Model< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#), [161](#)
- [PhyloCounterData](#), [176](#)
- [PowerSet< Array\\_Type, Data\\_Rule\\_Type >](#), [182](#)
- [Rules< Array\\_Type, Data\\_Type >](#), [191](#)
- [StatsCounter< Array\\_Type, Data\\_Type >](#), [195](#)
- [size\\_unique](#)
  - [Model< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#), [161](#)
- [source](#)
  - [barray-meat.hpp](#), [229](#)
  - [barraydense-meat.hpp](#), [253](#)
  - [Entries< Cell\\_Type >](#), [124](#)
- [states](#)
  - [NodeData](#), [173](#)
- [Statistical Models](#), [11](#)
- [stats\\_bank](#)
  - [support-meat.hpp](#), [342](#)
- [StatsCounter](#)
  - [StatsCounter< Array\\_Type, Data\\_Type >](#), [192](#), [193](#)
- [StatsCounter< Array\\_Type, Data\\_Type >](#), [192](#)
  - [~StatsCounter](#), [193](#)
  - [add\\_counter](#), [193](#)
  - [count\\_all](#), [193](#)
  - [count\\_current](#), [194](#)
  - [count\\_init](#), [194](#)
  - [get\\_counters](#), [194](#)
  - [get\\_descriptions](#), [194](#)
  - [get\\_names](#), [194](#)
  - [reset\\_array](#), [194](#)
  - [set\\_counters](#), [195](#)
  - [size](#), [195](#)
  - [StatsCounter](#), [192](#), [193](#)
- [statscounter-meat.hpp](#)
  - [clear](#), [327](#)
  - [counter](#), [329](#)
  - [counter\\_deleted](#), [330](#)
  - [counters](#), [330](#)
  - [counters\\_](#), [330](#)
  - [current\\_stats](#), [330](#)
  - [EmptyArray](#), [330](#)
  - [f\\_](#), [331](#)
  - [for](#), [327](#)
  - [j](#), [331](#)
  - [resize](#), [328](#)
  - [return](#), [331](#)
  - [STATSCOUNTER\\_TEMPLATE](#), [327–329](#)
  - [STATSCOUNTER\\_TEMPLATE\\_ARGS](#), [327](#)
  - [STATSCOUNTER\\_TYPE](#), [327](#)
- [STATSCOUNTER\\_TEMPLATE](#)
  - [statscounter-meat.hpp](#), [327–329](#)
- [STATSCOUNTER\\_TEMPLATE\\_ARGS](#)
  - [statscounter-meat.hpp](#), [327](#)
- [STATSCOUNTER\\_TYPE](#)
  - [statscounter-meat.hpp](#), [327](#)
- [store\\_psets](#)
  - [Model< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#), [161](#)
- [subtree\\_prob](#)
  - [Node](#), [171](#)
- [Support](#)
  - [Support< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#), [197](#), [198](#)
- [Support< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#), [195](#)
  - [~Support](#), [198](#)
  - [add\\_counter](#), [198](#)
  - [add\\_rule](#), [198](#), [199](#)
  - [add\\_rule\\_dyn](#), [199](#)
  - [calc](#), [199](#)
  - [change\\_stats](#), [202](#)
  - [cooriantes\\_n\\_free](#), [203](#)
  - [cooriantes\\_n\\_locked](#), [203](#)
  - [coordinates\\_free](#), [203](#)
  - [coordinates\\_locked](#), [203](#)
  - [current\\_stats](#), [203](#)
  - [delete\\_counters](#), [204](#)
  - [delete\\_rules](#), [204](#)
  - [delete\\_rules\\_dyn](#), [204](#)
  - [eval\\_rules\\_dyn](#), [200](#)
  - [get\\_counters](#), [200](#)
  - [get\\_counts](#), [200](#)
  - [get\\_current\\_stats](#), [200](#)
  - [get\\_data](#), [200](#)
  - [get\\_rules](#), [201](#)
  - [get\\_rules\\_dyn](#), [201](#)
  - [hashes](#), [204](#)
  - [hashes\\_initialized](#), [204](#)
  - [init\\_support](#), [201](#)
  - [M](#), [205](#)
  - [max\\_num\\_elements](#), [205](#)
  - [N](#), [205](#)
  - [n\\_counters](#), [205](#)
  - [print](#), [201](#)
  - [reset\\_array](#), [201](#), [202](#)
  - [set\\_counters](#), [202](#)
  - [set\\_rules](#), [202](#)
  - [set\\_rules\\_dyn](#), [202](#)
  - [Support](#), [197](#), [198](#)
- [support-meat.hpp](#)
  - [array\\_bank](#), [339](#)
  - [BARRY\\_SUPPORT\\_MEAT\\_HPP](#), [333](#)
  - [calc\\_backend\\_dense](#), [334](#)
  - [calc\\_backend\\_sparse](#), [334](#)
  - [change\\_stats\\_different](#), [339](#)
  - [coord\\_i](#), [339](#)

- coord\_j, 339
- counters, 339
- counters\_, 340
- delete\_counters, 340
- delete\_rules, 340
- delete\_rules\_dyn, 340
- else, 340
- f\_, 341
- for, 334
- hashes, 341
- if, 334, 335
- insert\_cell, 335
- return, 341
- rm\_cell, 335
- rules, 341
- rules\_, 341
- rules\_dyn, 342
- stats\_bank, 342
- SUPPORT\_TEMPLATE, 333, 336–339
- SUPPORT\_TEMPLATE\_ARGS, 333
- SUPPORT\_TYPE, 334
- tmp\_chng, 342
- support\_size
  - Flock, 130
  - Geese, 146
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 161
- SUPPORT\_TEMPLATE
  - support-meat.hpp, 333, 336–339
- SUPPORT\_TEMPLATE\_ARGS
  - support-meat.hpp, 333
- SUPPORT\_TYPE
  - support-meat.hpp, 334
- swap\_cells
  - BArray< Cell\_Type, Data\_Type >, 47
  - BArrayDense< Cell\_Type, Data\_Type >, 67
- swap\_cols
  - BArray< Cell\_Type, Data\_Type >, 47
  - BArrayDense< Cell\_Type, Data\_Type >, 67
- swap\_rows
  - BArray< Cell\_Type, Data\_Type >, 47
  - BArrayDense< Cell\_Type, Data\_Type >, 67
- target
  - barray-meat.hpp, 229
  - barraydense-meat.hpp, 254
  - Entries< Cell\_Type >, 124
- this
  - barray-meat-operators.hpp, 212
  - counters-meat.hpp, 279
- tmp\_chng
  - support-meat.hpp, 342
- toggle\_cell
  - BArray< Cell\_Type, Data\_Type >, 47
  - BArrayDense< Cell\_Type, Data\_Type >, 67
- toggle\_lock
  - BArray< Cell\_Type, Data\_Type >, 47
  - BArrayDense< Cell\_Type, Data\_Type >, 68
- transform\_model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 162
- transpose
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayDense< Cell\_Type, Data\_Type >, 68
- TWO
  - CHECK, 33
  - EXISTS, 34
- typedefs.hpp
  - Col\_type, 344
  - Counter\_fun\_type, 345
  - Counts\_type, 345
  - MapVec\_type, 345
  - Row\_type, 345
  - Rule\_fun\_type, 346
  - uint, 346
  - vec\_equal, 346
  - vec\_equal\_approx, 346
  - vec\_inner\_prod, 347
- ub
  - PhyloRuleDynData, 178
- uint
  - typedefs.hpp, 346
- UNKNOWN
  - EXISTS, 34
- UNI0S
  - defm.hpp, 282
- UNI1S
  - defm.hpp, 282
- UNI2S
  - defm.hpp, 282
- UNI3S
  - defm.hpp, 283
- UNI4S
  - defm.hpp, 283
- UNI5S
  - defm.hpp, 283
- UNI6S
  - defm.hpp, 283
- UNI7S
  - defm.hpp, 283
- UNI8S
  - defm.hpp, 283
- UNI9S
  - defm.hpp, 283
- UNI\_SUB
  - defm.hpp, 283
- update\_annotations
  - Geese, 146
- update\_normalizing\_constant
  - model-meat.hpp, 312
- v
  - barray-meat.hpp, 229
  - barraydense-meat.hpp, 254
- va\_end

- barraydense-meat.hpp, [248](#)
- va\_start
  - barraydense-meat.hpp, [248](#)
- val
  - Entries< Cell\_Type >, [124](#)
- val0
  - barraydense-meat.hpp, [254](#)
- val1
  - barraydense-meat.hpp, [254](#)
- value
  - barray-meat.hpp, [229](#)
  - barraydense-meat.hpp, [254](#)
  - Cell< Cell\_Type >, [99](#)
- vec\_diff
  - geese-bones.hpp, [317](#)
- vec\_equal
  - typedefs.hpp, [346](#)
- vec\_equal\_approx
  - typedefs.hpp, [346](#)
- vec\_inner\_prod
  - typedefs.hpp, [347](#)
- vecHasher< T >, [206](#)
  - operator(), [206](#)
- vector\_caster
  - geese-bones.hpp, [317](#)
- vertex\_attr
  - NetworkData, [165](#)
- visited
  - BArray< Cell\_Type, Data\_Type >, [49](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [69](#)
  - Cell< Cell\_Type >, [99](#)
  - Node, [171](#)
- vprintf
  - barraydense-meat.hpp, [249](#)
- X\_ncol
  - DEFMData, [120](#)
- X\_nrow
  - DEFMData, [120](#)
- ZERO\_CELL
  - barraydense-meat.hpp, [238](#)
  - barraydensecol-bones.hpp, [257](#)
  - barraydenserow-bones.hpp, [259](#)
- zero\_col
  - BArray< Cell\_Type, Data\_Type >, [48](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [68](#)
- zero\_row
  - BArray< Cell\_Type, Data\_Type >, [48](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [68](#)