

barry: Your go-to motif accountant

0.0-1

Generated by Doxygen 1.9.1



<b>1 Main Page</b>	<b>1</b>
<b>2 Module Index</b>	<b>5</b>
2.1 Modules	5
<b>3 Hierarchical Index</b>	<b>7</b>
3.1 Class Hierarchy	7
<b>4 Class Index</b>	<b>9</b>
4.1 Class List	9
<b>5 File Index</b>	<b>11</b>
5.1 File List	11
<b>6 Module Documentation</b>	<b>13</b>
6.1 Counting	13
6.1.1 Detailed Description	13
6.2 Statistical Models	13
6.2.1 Detailed Description	14
6.3 Phylo rules	14
6.3.1 Detailed Description	15
6.3.2 Macro Definition Documentation	15
6.3.2.1 DEFM_COUNTER	15
6.3.2.2 DEFM_COUNTER_LAMBDA	15
6.3.2.3 DEFM_RULE	16
6.3.2.4 DEFM_RULE_LAMBDA	16
6.3.2.5 DEFM_RULEDYN_LAMBDA	16
6.3.2.6 MAKE_DEFM_HASHER	16
6.3.3 Typedef Documentation	17
6.3.3.1 DEFMCOUNTER	17
6.3.3.2 DEFMCOUNTERS	17
6.3.3.3 DEFMMODEL	17
6.3.3.4 DEFMRULE	17
6.3.3.5 DEFMRULEDYN	17
6.3.3.6 DEFMRULES	18
6.3.3.7 DEFMRULESDYN	18
6.3.3.8 DEFMSTATSCOUNTER	18
6.3.3.9 DEFMSUPPORT	18
6.3.4 Function Documentation	18
6.3.4.1 ncol()	18
6.3.4.2 nrow()	18
6.3.4.3 operator()()	18
6.3.4.4 print()	19
6.3.4.5 rule_dyn_limit_changes()	19

6.4 DEFMArray counters	19
6.4.1 Detailed Description	21
6.4.2 Function Documentation	21
6.4.2.1 counter_absdiff()	22
6.4.2.2 counter_ctriads() [1/2]	22
6.4.2.3 counter_ctriads() [2/2]	22
6.4.2.4 counter_degree()	22
6.4.2.5 counter_density()	23
6.4.2.6 counter_diff()	23
6.4.2.7 counter_edges()	23
6.4.2.8 counter_fixed_effect()	23
6.4.2.9 counter_idegree() [1/2]	24
6.4.2.10 counter_idegree() [2/2]	24
6.4.2.11 counter_idegree15() [1/2]	24
6.4.2.12 counter_idegree15() [2/2]	24
6.4.2.13 counter_isolates() [1/2]	25
6.4.2.14 counter_isolates() [2/2]	25
6.4.2.15 counter_istar2() [1/2]	25
6.4.2.16 counter_istar2() [2/2]	25
6.4.2.17 counter_logit_intercept()	25
6.4.2.18 counter_mutual()	26
6.4.2.19 counter_nodecov()	26
6.4.2.20 counter_nodeicov()	26
6.4.2.21 counter_nodematch()	26
6.4.2.22 counter_nodeocov()	26
6.4.2.23 counter_odegree() [1/2]	27
6.4.2.24 counter_odegree() [2/2]	27
6.4.2.25 counter_odegree15() [1/2]	27
6.4.2.26 counter_odegree15() [2/2]	27
6.4.2.27 counter_ones()	27
6.4.2.28 counter_ostar2() [1/2]	28
6.4.2.29 counter_ostar2() [2/2]	28
6.4.2.30 counter_transition()	28
6.4.2.31 counter_transition_formula()	29
6.4.2.32 counter_ttriads() [1/2]	29
6.4.2.33 counter_ttriads() [2/2]	29
6.4.2.34 NETWORK_COUNTER()	29
6.4.2.35 rules_dont_become_zero()	30
6.4.2.36 rules_markov_fixed()	30
6.5 Phylo counters	30
6.5.1 Detailed Description	31
6.5.2 Function Documentation	32

6.5.2.1 counter_co_opt()	32
6.5.2.2 counter_cogain()	32
6.5.2.3 counter_gains()	32
6.5.2.4 counter_gains_from_0()	33
6.5.2.5 counter_gains_k_offspring()	33
6.5.2.6 counter_genes_changing()	33
6.5.2.7 counter_k_genes_changing()	33
6.5.2.8 counter_less_than_p_prop_genes_changing()	34
6.5.2.9 counter_longest()	34
6.5.2.10 counter_loss()	34
6.5.2.11 counter_maxfuns()	34
6.5.2.12 counter_neofun()	35
6.5.2.13 counter_neofun_a2b()	35
6.5.2.14 counter_overall_changes()	35
6.5.2.15 counter_overall_gains()	35
6.5.2.16 counter_overall_gains_from_0()	36
6.5.2.17 counter_overall_loss()	36
6.5.2.18 counter_pairwise_first_gain()	36
6.5.2.19 counter_pairwise_neofun_singlefun()	36
6.5.2.20 counter_pairwise_overall_change()	37
6.5.2.21 counter_pairwise_preserving()	37
6.5.2.22 counter_preserve_pseudogene()	37
6.5.2.23 counter_prop_genes_changing()	37
6.5.2.24 counter_subfun()	38
<b>7 Namespace Documentation</b>	<b>39</b>
7.1 barry Namespace Reference	39
7.1.1 Detailed Description	39
7.2 barry::counters Namespace Reference	39
7.2.1 Detailed Description	39
7.3 barry::counters::defm Namespace Reference	40
7.4 barry::counters::network Namespace Reference	40
7.5 barry::counters::phylo Namespace Reference	40
7.6 CHECK Namespace Reference	40
7.6.1 Detailed Description	40
7.6.2 Variable Documentation	40
7.6.2.1 BOTH	40
7.6.2.2 NONE	40
7.6.2.3 ONE	41
7.6.2.4 TWO	41
7.7 EXISTS Namespace Reference	41
7.7.1 Detailed Description	41

7.7.2 Variable Documentation . . . . .	41
7.7.2.1 AS_ONE . . . . .	41
7.7.2.2 AS_ZERO . . . . .	42
7.7.2.3 BOTH . . . . .	42
7.7.2.4 NONE . . . . .	42
7.7.2.5 ONE . . . . .	42
7.7.2.6 TWO . . . . .	42
7.7.2.7 UNKNOWN . . . . .	42
<b>8 Class Documentation</b>	<b>43</b>
8.1 BArray< Cell_Type, Data_Type > Class Template Reference . . . . .	43
8.1.1 Detailed Description . . . . .	45
8.1.2 Constructor & Destructor Documentation . . . . .	46
8.1.2.1 BArray() [1/6] . . . . .	46
8.1.2.2 BArray() [2/6] . . . . .	46
8.1.2.3 BArray() [3/6] . . . . .	46
8.1.2.4 BArray() [4/6] . . . . .	47
8.1.2.5 BArray() [5/6] . . . . .	47
8.1.2.6 BArray() [6/6] . . . . .	47
8.1.2.7 ~BArray() . . . . .	47
8.1.3 Member Function Documentation . . . . .	47
8.1.3.1 clear() . . . . .	47
8.1.3.2 col() . . . . .	48
8.1.3.3 D() [1/2] . . . . .	48
8.1.3.4 D() [2/2] . . . . .	48
8.1.3.5 D_ptr() [1/2] . . . . .	48
8.1.3.6 D_ptr() [2/2] . . . . .	48
8.1.3.7 default_val() . . . . .	48
8.1.3.8 flush_data() . . . . .	48
8.1.3.9 get_cell() . . . . .	49
8.1.3.10 get_col_vec() [1/2] . . . . .	49
8.1.3.11 get_col_vec() [2/2] . . . . .	49
8.1.3.12 get_entries() . . . . .	49
8.1.3.13 get_row_vec() [1/2] . . . . .	49
8.1.3.14 get_row_vec() [2/2] . . . . .	50
8.1.3.15 insert_cell() [1/3] . . . . .	50
8.1.3.16 insert_cell() [2/3] . . . . .	50
8.1.3.17 insert_cell() [3/3] . . . . .	50
8.1.3.18 is_dense() . . . . .	50
8.1.3.19 is_empty() . . . . .	51
8.1.3.20 ncol() . . . . .	51
8.1.3.21 nzero() . . . . .	51

8.1.3.22 <code>nrow()</code> . . . . .	51
8.1.3.23 <code>operator&gt;()</code> [1/2] . . . . .	51
8.1.3.24 <code>operator&gt;()</code> [2/2] . . . . .	51
8.1.3.25 <code>operator*==()</code> . . . . .	52
8.1.3.26 <code>operator+=()</code> [1/3] . . . . .	52
8.1.3.27 <code>operator+=()</code> [2/3] . . . . .	52
8.1.3.28 <code>operator+=()</code> [3/3] . . . . .	52
8.1.3.29 <code>operator-=()</code> [1/3] . . . . .	52
8.1.3.30 <code>operator-=()</code> [2/3] . . . . .	52
8.1.3.31 <code>operator-=()</code> [3/3] . . . . .	53
8.1.3.32 <code>operator/=( )</code> . . . . .	53
8.1.3.33 <code>operator=()</code> [1/2] . . . . .	53
8.1.3.34 <code>operator=()</code> [2/2] . . . . .	53
8.1.3.35 <code>operator==( )</code> . . . . .	53
8.1.3.36 <code>out_of_range()</code> . . . . .	53
8.1.3.37 <code>print()</code> . . . . .	54
8.1.3.38 <code>reserve()</code> . . . . .	54
8.1.3.39 <code>resize()</code> . . . . .	54
8.1.3.40 <code>rm_cell()</code> . . . . .	54
8.1.3.41 <code>row()</code> . . . . .	54
8.1.3.42 <code>set_data()</code> . . . . .	54
8.1.3.43 <code>swap_cells()</code> . . . . .	55
8.1.3.44 <code>swap_cols()</code> . . . . .	55
8.1.3.45 <code>swap_rows()</code> . . . . .	55
8.1.3.46 <code>toggle_cell()</code> . . . . .	55
8.1.3.47 <code>toggle_lock()</code> . . . . .	56
8.1.3.48 <code>transpose()</code> . . . . .	56
8.1.3.49 <code>zero_col()</code> . . . . .	56
8.1.3.50 <code>zero_row()</code> . . . . .	56
8.1.4 Friends And Related Function Documentation . . . . .	56
8.1.4.1 <code>BArrayCell&lt; Cell_Type, Data_Type &gt;</code> . . . . .	56
8.1.4.2 <code>BArrayCell_const&lt; Cell_Type, Data_Type &gt;</code> . . . . .	57
8.1.5 Member Data Documentation . . . . .	57
8.1.5.1 <code>visited</code> . . . . .	57
8.2 <code>BArrayCell&lt; Cell_Type, Data_Type &gt;</code> Class Template Reference . . . . .	57
8.2.1 Detailed Description . . . . .	57
8.2.2 Constructor & Destructor Documentation . . . . .	58
8.2.2.1 <code>BArrayCell()</code> . . . . .	58
8.2.2.2 <code>~BArrayCell()</code> . . . . .	58
8.2.3 Member Function Documentation . . . . .	58
8.2.3.1 <code>operator Cell_Type()</code> . . . . .	58
8.2.3.2 <code>operator*==( )</code> . . . . .	58

8.2.3.3 operator+=()	59
8.2.3.4 operator-=()	59
8.2.3.5 operator/=( )	59
8.2.3.6 operator=()	59
8.2.3.7 operator==( )	59
8.3 BArrayCell_const< Cell_Type, Data_Type > Class Template Reference	60
8.3.1 Detailed Description	60
8.3.2 Constructor & Destructor Documentation	60
8.3.2.1 BArrayCell_const()	60
8.3.2.2 ~BArrayCell_const()	60
8.3.3 Member Function Documentation	61
8.3.3.1 operator Cell_Type()	61
8.3.3.2 operator"!=( )	61
8.3.3.3 operator<( )	61
8.3.3.4 operator<=( )	61
8.3.3.5 operator==( )	61
8.3.3.6 operator>( )	62
8.3.3.7 operator>=( )	62
8.4 BArrayDense< Cell_Type, Data_Type > Class Template Reference	62
8.4.1 Detailed Description	65
8.4.2 Constructor & Destructor Documentation	65
8.4.2.1 BArrayDense() [ 1 / 6 ]	65
8.4.2.2 BArrayDense() [ 2 / 6 ]	65
8.4.2.3 BArrayDense() [ 3 / 6 ]	66
8.4.2.4 BArrayDense() [ 4 / 6 ]	66
8.4.2.5 BArrayDense() [ 5 / 6 ]	66
8.4.2.6 BArrayDense() [ 6 / 6 ]	66
8.4.2.7 ~BArrayDense()	67
8.4.3 Member Function Documentation	67
8.4.3.1 clear()	67
8.4.3.2 col() [ 1 / 2 ]	67
8.4.3.3 col() [ 2 / 2 ]	67
8.4.3.4 colsum()	67
8.4.3.5 D() [ 1 / 2 ]	68
8.4.3.6 D() [ 2 / 2 ]	68
8.4.3.7 D_ptr() [ 1 / 2 ]	68
8.4.3.8 D_ptr() [ 2 / 2 ]	68
8.4.3.9 default_val()	68
8.4.3.10 get_cell()	68
8.4.3.11 get_col_vec() [ 1 / 2 ]	69
8.4.3.12 get_col_vec() [ 2 / 2 ]	69
8.4.3.13 get_data()	69



8.4.3.14	<a href="#">get_entries()</a>	69
8.4.3.15	<a href="#">get_row_vec()</a> [1/2]	69
8.4.3.16	<a href="#">get_row_vec()</a> [2/2]	70
8.4.3.17	<a href="#">insert_cell()</a> [1/2]	70
8.4.3.18	<a href="#">insert_cell()</a> [2/2]	70
8.4.3.19	<a href="#">is_dense()</a>	70
8.4.3.20	<a href="#">is_empty()</a>	70
8.4.3.21	<a href="#">ncol()</a>	71
8.4.3.22	<a href="#">nnozero()</a>	71
8.4.3.23	<a href="#">nrow()</a>	71
8.4.3.24	<a href="#">operator&gt;()</a> [1/2]	71
8.4.3.25	<a href="#">operator&gt;()</a> [2/2]	71
8.4.3.26	<a href="#">operator*=( )</a>	71
8.4.3.27	<a href="#">operator+=( )</a> [1/3]	72
8.4.3.28	<a href="#">operator+=( )</a> [2/3]	72
8.4.3.29	<a href="#">operator+=( )</a> [3/3]	72
8.4.3.30	<a href="#">operator-=( )</a> [1/3]	72
8.4.3.31	<a href="#">operator-=( )</a> [2/3]	72
8.4.3.32	<a href="#">operator-=( )</a> [3/3]	72
8.4.3.33	<a href="#">operator/=( )</a>	73
8.4.3.34	<a href="#">operator=()</a> [1/2]	73
8.4.3.35	<a href="#">operator=()</a> [2/2]	73
8.4.3.36	<a href="#">operator==( )</a>	73
8.4.3.37	<a href="#">out_of_range()</a>	73
8.4.3.38	<a href="#">print()</a>	73
8.4.3.39	<a href="#">reserve()</a>	74
8.4.3.40	<a href="#">resize()</a>	74
8.4.3.41	<a href="#">rm_cell()</a>	74
8.4.3.42	<a href="#">row()</a> [1/2]	74
8.4.3.43	<a href="#">row()</a> [2/2]	74
8.4.3.44	<a href="#">rowsum()</a>	74
8.4.3.45	<a href="#">set_data()</a>	75
8.4.3.46	<a href="#">swap_cells()</a>	75
8.4.3.47	<a href="#">swap_cols()</a>	75
8.4.3.48	<a href="#">swap_rows()</a>	75
8.4.3.49	<a href="#">toggle_cell()</a>	76
8.4.3.50	<a href="#">toggle_lock()</a>	76
8.4.3.51	<a href="#">transpose()</a>	76
8.4.3.52	<a href="#">zero_col()</a>	76
8.4.3.53	<a href="#">zero_row()</a>	76
8.4.4	<a href="#">Friends And Related Function Documentation</a>	76
8.4.4.1	<a href="#">BArrayDenseCell&lt; Cell_Type, Data_Type &gt;</a>	77

8.4.4.2 BArrayDenseCol< Cell_Type, Data_Type > . . . . .	77
8.4.4.3 BArrayDenseCol_const< Cell_Type, Data_Type > . . . . .	77
8.4.4.4 BArrayDenseRow< Cell_Type, Data_Type > . . . . .	77
8.4.4.5 BArrayDenseRow_const< Cell_Type, Data_Type > . . . . .	77
8.4.5 Member Data Documentation . . . . .	77
8.4.5.1 visited . . . . .	78
8.5 BArrayDenseCell< Cell_Type, Data_Type > Class Template Reference . . . . .	78
8.5.1 Detailed Description . . . . .	78
8.5.2 Constructor & Destructor Documentation . . . . .	79
8.5.2.1 BArrayDenseCell() . . . . .	79
8.5.2.2 ~BArrayDenseCell() . . . . .	79
8.5.3 Member Function Documentation . . . . .	79
8.5.3.1 operator Cell_Type() . . . . .	79
8.5.3.2 operator*=( ) . . . . .	79
8.5.3.3 operator+=( ) . . . . .	80
8.5.3.4 operator-=( ) . . . . .	80
8.5.3.5 operator/=( ) . . . . .	80
8.5.3.6 operator=( ) [ 1 / 2 ] . . . . .	80
8.5.3.7 operator=( ) [ 2 / 2 ] . . . . .	80
8.5.3.8 operator==( ) . . . . .	81
8.5.4 Friends And Related Function Documentation . . . . .	81
8.5.4.1 BArrayDense< Cell_Type, Data_Type > . . . . .	81
8.5.4.2 BArrayDenseCol< Cell_Type, Data_Type > . . . . .	81
8.5.4.3 BArrayDenseCol_const< Cell_Type, Data_Type > . . . . .	81
8.6 BArrayDenseCell_const< Cell_Type, Data_Type > Class Template Reference . . . . .	82
8.6.1 Detailed Description . . . . .	82
8.7 BArrayDenseCol< Cell_Type, Data_Type > Class Template Reference . . . . .	82
8.7.1 Detailed Description . . . . .	82
8.7.2 Constructor & Destructor Documentation . . . . .	82
8.7.2.1 BArrayDenseCol() . . . . .	83
8.7.3 Member Function Documentation . . . . .	83
8.7.3.1 begin() . . . . .	83
8.7.3.2 end() . . . . .	83
8.7.3.3 operator()( ) . . . . .	83
8.7.3.4 size() . . . . .	83
8.7.4 Friends And Related Function Documentation . . . . .	84
8.7.4.1 BArrayDense< Cell_Type, Data_Type > . . . . .	84
8.7.4.2 BArrayDenseCell< Cell_Type, Data_Type > . . . . .	84
8.7.4.3 BArrayDenseCell_const< Cell_Type, Data_Type > . . . . .	84
8.8 BArrayDenseCol_const< Cell_Type, Data_Type > Class Template Reference . . . . .	84
8.8.1 Detailed Description . . . . .	85
8.8.2 Constructor & Destructor Documentation . . . . .	85

8.8.2.1 BArrayDenseCol_const()	85
8.8.3 Member Function Documentation	85
8.8.3.1 begin()	85
8.8.3.2 end()	85
8.8.3.3 operator>()	86
8.8.3.4 size()	86
8.8.4 Friends And Related Function Documentation	86
8.8.4.1 BArrayDenseCell< Cell_Type, Data_Type >	86
8.8.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	86
8.9 BArrayDenseRow< Cell_Type, Data_Type > Class Template Reference	86
8.9.1 Detailed Description	87
8.9.2 Constructor & Destructor Documentation	87
8.9.2.1 BArrayDenseRow()	87
8.9.3 Member Function Documentation	87
8.9.3.1 begin()	87
8.9.3.2 end()	88
8.9.3.3 operator>()	88
8.9.3.4 size()	88
8.9.4 Friends And Related Function Documentation	88
8.9.4.1 BArrayDense< Cell_Type, Data_Type >	88
8.9.4.2 BArrayDenseCell< Cell_Type, Data_Type >	88
8.9.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >	89
8.10 BArrayDenseRow_const< Cell_Type, Data_Type > Class Template Reference	89
8.10.1 Detailed Description	89
8.10.2 Constructor & Destructor Documentation	89
8.10.2.1 BArrayDenseRow_const()	90
8.10.3 Member Function Documentation	90
8.10.3.1 begin()	90
8.10.3.2 end()	90
8.10.3.3 operator>()	90
8.10.3.4 size()	90
8.10.4 Friends And Related Function Documentation	91
8.10.4.1 BArrayDenseCell< Cell_Type, Data_Type >	91
8.10.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	91
8.11 BArrayRow< Cell_Type, Data_Type > Class Template Reference	91
8.11.1 Detailed Description	91
8.11.2 Constructor & Destructor Documentation	92
8.11.2.1 BArrayRow()	92
8.11.2.2 ~BArrayRow()	92
8.11.3 Member Function Documentation	92
8.11.3.1 operator BArrayRow< Cell_Type, Data_Type >()	92
8.11.3.2 operator*=( )	92

8.11.3.3 operator+=( ) . . . . .	92
8.11.3.4 operator-=( ) . . . . .	93
8.11.3.5 operator/=( ) . . . . .	93
8.11.3.6 operator=( ) . . . . .	93
8.11.3.7 operator==( ) . . . . .	93
8.12 BArrayRow_const< Cell_Type, Data_Type > Class Template Reference . . . . .	93
8.12.1 Detailed Description . . . . .	94
8.12.2 Constructor & Destructor Documentation . . . . .	94
8.12.2.1 BArrayRow_const( ) . . . . .	94
8.12.2.2 ~BArrayRow_const( ) . . . . .	94
8.12.3 Member Function Documentation . . . . .	94
8.12.3.1 operator BArrayRow_const< Cell_Type, Data_Type >( ) . . . . .	94
8.12.3.2 operator!=( ) . . . . .	94
8.12.3.3 operator<( ) . . . . .	95
8.12.3.4 operator<=( ) . . . . .	95
8.12.3.5 operator==( ) . . . . .	95
8.12.3.6 operator>( ) . . . . .	95
8.12.3.7 operator>=( ) . . . . .	95
8.13 BArrayVector< Cell_Type, Data_Type > Class Template Reference . . . . .	95
8.13.1 Detailed Description . . . . .	96
8.13.2 Constructor & Destructor Documentation . . . . .	96
8.13.2.1 BArrayVector( ) . . . . .	96
8.13.2.2 ~BArrayVector( ) . . . . .	97
8.13.3 Member Function Documentation . . . . .	97
8.13.3.1 begin( ) . . . . .	97
8.13.3.2 end( ) . . . . .	97
8.13.3.3 is_col( ) . . . . .	97
8.13.3.4 is_row( ) . . . . .	98
8.13.3.5 operator std::vector< Cell_Type >( ) . . . . .	98
8.13.3.6 operator*=( ) . . . . .	98
8.13.3.7 operator+=( ) . . . . .	98
8.13.3.8 operator-=( ) . . . . .	98
8.13.3.9 operator/=( ) . . . . .	99
8.13.3.10 operator=( ) . . . . .	99
8.13.3.11 operator==( ) . . . . .	99
8.13.3.12 size( ) . . . . .	99
8.14 BArrayVector_const< Cell_Type, Data_Type > Class Template Reference . . . . .	99
8.14.1 Detailed Description . . . . .	100
8.14.2 Constructor & Destructor Documentation . . . . .	100
8.14.2.1 BArrayVector_const( ) . . . . .	100
8.14.2.2 ~BArrayVector_const( ) . . . . .	100
8.14.3 Member Function Documentation . . . . .	101

8.14.3.1 begin()	101
8.14.3.2 end()	101
8.14.3.3 is_col()	101
8.14.3.4 is_row()	101
8.14.3.5 operator std::vector< Cell_Type >()	101
8.14.3.6 operator!=(())	102
8.14.3.7 operator<()	102
8.14.3.8 operator<=()	102
8.14.3.9 operator==(())	102
8.14.3.10 operator>()	102
8.14.3.11 operator>=()	103
8.14.3.12 size()	103
8.15 Cell< Cell_Type > Class Template Reference	103
8.15.1 Detailed Description	104
8.15.2 Constructor & Destructor Documentation	104
8.15.2.1 Cell() [1/7]	104
8.15.2.2 Cell() [2/7]	104
8.15.2.3 ~Cell()	104
8.15.2.4 Cell() [3/7]	105
8.15.2.5 Cell() [4/7]	105
8.15.2.6 Cell() [5/7]	105
8.15.2.7 Cell() [6/7]	105
8.15.2.8 Cell() [7/7]	105
8.15.3 Member Function Documentation	105
8.15.3.1 add() [1/4]	106
8.15.3.2 add() [2/4]	106
8.15.3.3 add() [3/4]	106
8.15.3.4 add() [4/4]	106
8.15.3.5 operator Cell_Type()	106
8.15.3.6 operator!=(())	106
8.15.3.7 operator=() [1/2]	107
8.15.3.8 operator=() [2/2]	107
8.15.3.9 operator==(())	107
8.15.4 Member Data Documentation	107
8.15.4.1 active	107
8.15.4.2 value	107
8.15.4.3 visited	108
8.16 Cell_const< Cell_Type > Class Template Reference	108
8.16.1 Detailed Description	108
8.17 ConstBArrayRowIter< Cell_Type, Data_Type > Class Template Reference	108
8.17.1 Detailed Description	109
8.17.2 Constructor & Destructor Documentation	109

8.17.2.1 ConstBArrayRowIter()	109
8.17.2.2 ~ConstBArrayRowIter()	109
8.17.3 Member Data Documentation	109
8.17.3.1 Array	110
8.17.3.2 current_col	110
8.17.3.3 current_row	110
8.17.3.4 iter	110
8.18 Counter< Array_Type, Data_Type > Class Template Reference	110
8.18.1 Detailed Description	111
8.18.2 Constructor & Destructor Documentation	112
8.18.2.1 Counter() [1/4]	112
8.18.2.2 Counter() [2/4]	112
8.18.2.3 Counter() [3/4]	112
8.18.2.4 Counter() [4/4]	112
8.18.2.5 ~Counter()	113
8.18.3 Member Function Documentation	113
8.18.3.1 count()	113
8.18.3.2 get_description()	113
8.18.3.3 get_hasher()	113
8.18.3.4 get_name()	113
8.18.3.5 init()	113
8.18.3.6 operator=() [1/2]	114
8.18.3.7 operator=() [2/2]	114
8.18.3.8 set_hasher()	114
8.18.4 Member Data Documentation	114
8.18.4.1 count_fun	114
8.18.4.2 data	115
8.18.4.3 desc	115
8.18.4.4 hasher_fun	115
8.18.4.5 init_fun	115
8.18.4.6 name	115
8.19 Counters< Array_Type, Data_Type > Class Template Reference	116
8.19.1 Detailed Description	116
8.19.2 Constructor & Destructor Documentation	116
8.19.2.1 Counters() [1/3]	117
8.19.2.2 ~Counters()	117
8.19.2.3 Counters() [2/3]	117
8.19.2.4 Counters() [3/3]	117
8.19.3 Member Function Documentation	117
8.19.3.1 add_counter() [1/2]	118
8.19.3.2 add_counter() [2/2]	118
8.19.3.3 add_hash()	118

8.19.3.4 gen_hash()	118
8.19.3.5 get_descriptions()	119
8.19.3.6 get_names()	119
8.19.3.7 operator=() [1/2]	119
8.19.3.8 operator=() [2/2]	119
8.19.3.9 operator[]()	120
8.19.3.10 size()	120
8.20 DEFM Class Reference	121
8.20.1 Detailed Description	122
8.20.2 Constructor & Destructor Documentation	122
8.20.2.1 DEFM()	122
8.20.2.2 ~DEFM()	122
8.20.3 Member Function Documentation	122
8.20.3.1 get_ID()	122
8.20.3.2 get_m_order()	123
8.20.3.3 get_model()	123
8.20.3.4 get_n_covars()	123
8.20.3.5 get_n_obs()	123
8.20.3.6 get_n_rows()	123
8.20.3.7 get_n_y()	123
8.20.3.8 get_X()	124
8.20.3.9 get_X_names()	124
8.20.3.10 get_Y()	124
8.20.3.11 get_Y_names()	124
8.20.3.12 init()	124
8.20.3.13 likelihood()	124
8.20.3.14 logodds()	125
8.20.3.15 motif_census()	125
8.20.3.16 set_names()	125
8.20.3.17 simulate()	125
8.21 DEFMCounterData Class Reference	125
8.21.1 Detailed Description	126
8.21.2 Constructor & Destructor Documentation	126
8.21.2.1 DEFMCounterData() [1/2]	126
8.21.2.2 DEFMCounterData() [2/2]	126
8.21.2.3 ~DEFMCounterData()	127
8.21.3 Member Function Documentation	127
8.21.3.1 idx()	127
8.21.3.2 is_true()	127
8.21.3.3 num()	127
8.21.4 Member Data Documentation	127
8.21.4.1 indices	127

8.21.4.2 logical	128
8.21.4.3 numbers	128
8.22 DEFMDData Class Reference	128
8.22.1 Detailed Description	129
8.22.2 Constructor & Destructor Documentation	129
8.22.2.1 DEFMDData() [1/2]	129
8.22.2.2 DEFMDData() [2/2]	129
8.22.2.3 ~DEFMDData()	130
8.22.3 Member Function Documentation	130
8.22.3.1 at()	130
8.22.4 Member Data Documentation	130
8.22.4.1 array	130
8.22.4.2 covar_sort	130
8.22.4.3 covar_used	130
8.22.4.4 covariates	131
8.22.4.5 obs_start	131
8.22.4.6 X_ncol	131
8.22.4.7 X_nrow	131
8.23 DEFMRuleData Class Reference	132
8.23.1 Detailed Description	132
8.23.2 Constructor & Destructor Documentation	132
8.23.2.1 DEFMRuleData() [1/3]	133
8.23.2.2 DEFMRuleData() [2/3]	133
8.23.2.3 DEFMRuleData() [3/3]	133
8.23.3 Member Function Documentation	133
8.23.3.1 idx()	133
8.23.3.2 is_true()	133
8.23.3.3 num()	134
8.23.4 Member Data Documentation	134
8.23.4.1 indices	134
8.23.4.2 init	134
8.23.4.3 logical	134
8.23.4.4 numbers	134
8.24 DEFMRuleDynData Class Reference	135
8.24.1 Detailed Description	135
8.24.2 Constructor & Destructor Documentation	136
8.24.2.1 DEFMRuleDynData()	136
8.24.2.2 ~DEFMRuleDynData()	136
8.24.3 Member Data Documentation	136
8.24.3.1 counts	136
8.25 Entries< Cell_Type > Class Template Reference	136
8.25.1 Detailed Description	137



8.25.2 Constructor & Destructor Documentation	137
8.25.2.1 Entries() [1/2]	137
8.25.2.2 Entries() [2/2]	137
8.25.2.3 ~Entries()	137
8.25.3 Member Function Documentation	138
8.25.3.1 resize()	138
8.25.4 Member Data Documentation	138
8.25.4.1 source	138
8.25.4.2 target	138
8.25.4.3 val	138
8.26 Flock Class Reference	139
8.26.1 Detailed Description	140
8.26.2 Constructor & Destructor Documentation	140
8.26.2.1 Flock()	140
8.26.2.2 ~Flock()	140
8.26.3 Member Function Documentation	140
8.26.3.1 add_data()	140
8.26.3.2 colnames()	141
8.26.3.3 get_counters()	141
8.26.3.4 get_model()	141
8.26.3.5 get_stats_support()	141
8.26.3.6 get_stats_target()	141
8.26.3.7 get_support_fun()	142
8.26.3.8 init()	142
8.26.3.9 likelihood_joint()	142
8.26.3.10 nfuncs()	142
8.26.3.11 nleaves()	143
8.26.3.12 nnodes()	143
8.26.3.13 nterms()	143
8.26.3.14 ntrees()	143
8.26.3.15 operator()()	143
8.26.3.16 parse_polytomies()	144
8.26.3.17 print()	144
8.26.3.18 set_seed()	144
8.26.3.19 support_size()	144
8.26.4 Member Data Documentation	144
8.26.4.1 dat	145
8.26.4.2 initialized	145
8.26.4.3 model	145
8.26.4.4 nfunctions	145
8.26.4.5 rengine	145
8.27 FreqTable< T > Class Template Reference	145

8.27.1 Detailed Description	146
8.27.2 Constructor & Destructor Documentation	146
8.27.2.1 FreqTable()	146
8.27.2.2 ~FreqTable()	147
8.27.3 Member Function Documentation	147
8.27.3.1 add()	147
8.27.3.2 as_vector()	147
8.27.3.3 clear()	147
8.27.3.4 get_data()	147
8.27.3.5 get_index()	148
8.27.3.6 make_hash()	148
8.27.3.7 print()	148
8.27.3.8 reserve()	148
8.27.3.9 size()	148
8.28 Geese Class Reference	149
8.28.1 Detailed Description	152
8.28.2 Constructor & Destructor Documentation	152
8.28.2.1 Geese() [1/4]	152
8.28.2.2 Geese() [2/4]	153
8.28.2.3 Geese() [3/4]	153
8.28.2.4 Geese() [4/4]	153
8.28.2.5 ~Geese()	153
8.28.3 Member Function Documentation	153
8.28.3.1 calc_reduced_sequence()	153
8.28.3.2 calc_sequence()	154
8.28.3.3 colnames()	154
8.28.3.4 get_annotated_nodes()	154
8.28.3.5 get_counters()	154
8.28.3.6 get_model()	154
8.28.3.7 get_probabilities()	154
8.28.3.8 get_rengine()	155
8.28.3.9 get_states()	155
8.28.3.10 get_support_fun()	155
8.28.3.11 inherit_support()	155
8.28.3.12 init()	155
8.28.3.13 init_node()	156
8.28.3.14 likelihood()	156
8.28.3.15 likelihood_exhaust()	156
8.28.3.16 nannotations()	156
8.28.3.17 nfuncs()	156
8.28.3.18 nleaves()	157
8.28.3.19 nnodes()	157

8.28.3.20 nterms()	157
8.28.3.21 observed_counts()	157
8.28.3.22 operator=() [1/2]	157
8.28.3.23 operator=() [2/2]	157
8.28.3.24 parse_polytomies()	158
8.28.3.25 predict()	158
8.28.3.26 predict_backend()	158
8.28.3.27 predict_exhaust()	158
8.28.3.28 predict_exhaust_backend()	159
8.28.3.29 predict_sim()	159
8.28.3.30 print()	159
8.28.3.31 print_observed_counts()	159
8.28.3.32 set_seed()	159
8.28.3.33 simulate()	160
8.28.3.34 support_size()	160
8.28.3.35 update_annotations()	160
8.28.4 Member Data Documentation	160
8.28.4.1 delete_engine	160
8.28.4.2 delete_support	160
8.28.4.3 initialized	161
8.28.4.4 map_to_nodes	161
8.28.4.5 nfunctions	161
8.28.4.6 nodes	161
8.28.4.7 pset_loc	161
8.28.4.8 reduced_sequence	161
8.28.4.9 sequence	162
8.29 Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	162
8.29.1 Detailed Description	166
8.29.2 Constructor & Destructor Documentation	166
8.29.2.1 Model() [1/3]	167
8.29.2.2 Model() [2/3]	167
8.29.2.3 Model() [3/3]	167
8.29.2.4 ~Model()	167
8.29.3 Member Function Documentation	167
8.29.3.1 add_array()	167
8.29.3.2 add_counter() [1/2]	168
8.29.3.3 add_counter() [2/2]	168
8.29.3.4 add_hasher()	168
8.29.3.5 add_rule() [1/2]	168
8.29.3.6 add_rule() [2/2]	169
8.29.3.7 add_rule_dyn() [1/2]	169

8.29.3.8 add_rule_dyn() [2/2]	169
8.29.3.9 colnames()	169
8.29.3.10 conditional_prob()	169
8.29.3.11 gen_key()	170
8.29.3.12 get_arrays2support()	170
8.29.3.13 get_counters()	170
8.29.3.14 get_norm_const()	170
8.29.3.15 get_pset()	171
8.29.3.16 get_pset_arrays()	171
8.29.3.17 get_pset_probs()	171
8.29.3.18 get_pset_stats() [1/2]	171
8.29.3.19 get_pset_stats() [2/2]	171
8.29.3.20 get_rengine()	172
8.29.3.21 get_rules()	172
8.29.3.22 get_rules_dyn()	172
8.29.3.23 get_stats_support()	172
8.29.3.24 get_stats_target()	172
8.29.3.25 get_support_fun()	173
8.29.3.26 likelihood() [1/4]	173
8.29.3.27 likelihood() [2/4]	173
8.29.3.28 likelihood() [3/4]	173
8.29.3.29 likelihood() [4/4]	174
8.29.3.30 likelihood_total()	174
8.29.3.31 nrules()	174
8.29.3.32 nrules_dyn()	174
8.29.3.33 nterms()	174
8.29.3.34 operator=()	175
8.29.3.35 print()	175
8.29.3.36 print_stats()	175
8.29.3.37 sample() [1/2]	175
8.29.3.38 sample() [2/2]	175
8.29.3.39 set_counters()	176
8.29.3.40 set_rengine()	176
8.29.3.41 set_rules()	176
8.29.3.42 set_rules_dyn()	176
8.29.3.43 set_seed()	176
8.29.3.44 set_transform_model()	177
8.29.3.45 size()	177
8.29.3.46 size_unique()	177
8.29.3.47 store_psets()	177
8.29.3.48 support_size()	178
8.29.3.49 transform_model()	178

8.29.4 Member Data Documentation	178
8.29.4.1 arrays2support	178
8.29.4.2 counter_fun	178
8.29.4.3 counters	178
8.29.4.4 delete_counters	179
8.29.4.5 delete_engine	179
8.29.4.6 delete_rules	179
8.29.4.7 delete_rules_dyn	179
8.29.4.8 first_calc_done	179
8.29.4.9 keys2support	180
8.29.4.10 normalizing_constants	180
8.29.4.11 params_last	180
8.29.4.12 pset_arrays	180
8.29.4.13 pset_probs	181
8.29.4.14 pset_stats	181
8.29.4.15 engine	181
8.29.4.16 rules	181
8.29.4.17 rules_dyn	182
8.29.4.18 stats_support	182
8.29.4.19 stats_support_n_arrays	182
8.29.4.20 stats_target	182
8.29.4.21 support_fun	183
8.29.4.22 transform_model_fun	183
8.29.4.23 transform_model_term_names	183
8.29.4.24 with_pset	184
8.30 NetCounterData Class Reference	184
8.30.1 Detailed Description	184
8.30.2 Constructor & Destructor Documentation	184
8.30.2.1 NetCounterData() [1/2]	184
8.30.2.2 NetCounterData() [2/2]	185
8.30.2.3 ~NetCounterData()	185
8.30.3 Member Data Documentation	185
8.30.3.1 indices	185
8.30.3.2 numbers	185
8.31 NetworkData Class Reference	185
8.31.1 Detailed Description	186
8.31.2 Constructor & Destructor Documentation	186
8.31.2.1 NetworkData() [1/3]	186
8.31.2.2 NetworkData() [2/3]	186
8.31.2.3 NetworkData() [3/3]	187
8.31.2.4 ~NetworkData()	187
8.31.3 Member Data Documentation	187

8.31.3.1 directed	187
8.31.3.2 vertex_attr	188
8.32 Node Class Reference	188
8.32.1 Detailed Description	189
8.32.2 Constructor & Destructor Documentation	189
8.32.2.1 Node() [1/5]	189
8.32.2.2 Node() [2/5]	190
8.32.2.3 Node() [3/5]	190
8.32.2.4 Node() [4/5]	190
8.32.2.5 Node() [5/5]	190
8.32.2.6 ~Node()	190
8.32.3 Member Function Documentation	190
8.32.3.1 get_parent()	191
8.32.3.2 is_leaf()	191
8.32.3.3 noffspring()	191
8.32.4 Member Data Documentation	191
8.32.4.1 annotations	191
8.32.4.2 array	191
8.32.4.3 arrays	192
8.32.4.4 duplication	192
8.32.4.5 id	192
8.32.4.6 narray	192
8.32.4.7 offspring	192
8.32.4.8 ord	193
8.32.4.9 parent	193
8.32.4.10 probability	193
8.32.4.11 subtree_prob	193
8.32.4.12 visited	193
8.33 NodeData Class Reference	194
8.33.1 Detailed Description	194
8.33.2 Constructor & Destructor Documentation	194
8.33.2.1 NodeData()	194
8.33.3 Member Data Documentation	194
8.33.3.1 blengths	195
8.33.3.2 duplication	195
8.33.3.3 states	195
8.34 PhyloCounterData Class Reference	195
8.34.1 Detailed Description	196
8.34.2 Constructor & Destructor Documentation	196
8.34.2.1 PhyloCounterData() [1/2]	196
8.34.2.2 PhyloCounterData() [2/2]	196
8.34.3 Member Function Documentation	196

8.34.3.1 at()	196
8.34.3.2 begin()	196
8.34.3.3 empty()	197
8.34.3.4 end()	197
8.34.3.5 get_counters()	197
8.34.3.6 operator>()	197
8.34.3.7 operator[]()	197
8.34.3.8 push_back()	197
8.34.3.9 reserve()	198
8.34.3.10 shrink_to_fit()	198
8.34.3.11 size()	198
8.35 PhyloRuleDynData Class Reference	198
8.35.1 Detailed Description	198
8.35.2 Constructor & Destructor Documentation	199
8.35.2.1 PhyloRuleDynData()	199
8.35.2.2 ~PhyloRuleDynData()	199
8.35.3 Member Data Documentation	199
8.35.3.1 counts	199
8.35.3.2 duplication	199
8.35.3.3 lb	199
8.35.3.4 pos	200
8.35.3.5 ub	200
8.36 PowerSet< Array_Type, Data_Rule_Type > Class Template Reference	200
8.36.1 Detailed Description	201
8.36.2 Constructor & Destructor Documentation	202
8.36.2.1 PowerSet() [1/3]	202
8.36.2.2 PowerSet() [2/3]	202
8.36.2.3 PowerSet() [3/3]	202
8.36.2.4 ~PowerSet()	202
8.36.3 Member Function Documentation	202
8.36.3.1 add_rule() [1/2]	203
8.36.3.2 add_rule() [2/2]	203
8.36.3.3 begin()	203
8.36.3.4 calc()	203
8.36.3.5 end()	203
8.36.3.6 get_data()	204
8.36.3.7 get_data_ptr()	204
8.36.3.8 init_support()	204
8.36.3.9 operator[]()	204
8.36.3.10 reset()	204
8.36.3.11 size()	205
8.36.4 Member Data Documentation	205

8.36.4.1 coordinates_free . . . . .	205
8.36.4.2 coordinates_locked . . . . .	205
8.36.4.3 data . . . . .	205
8.36.4.4 EmptyArray . . . . .	205
8.36.4.5 M . . . . .	206
8.36.4.6 N . . . . .	206
8.36.4.7 n_free . . . . .	206
8.36.4.8 n_locked . . . . .	206
8.36.4.9 rules . . . . .	206
8.36.4.10 rules_deleted . . . . .	207
8.37 Progress Class Reference . . . . .	207
8.37.1 Detailed Description . . . . .	207
8.37.2 Constructor & Destructor Documentation . . . . .	207
8.37.2.1 Progress() . . . . .	207
8.37.2.2 ~Progress() . . . . .	208
8.37.3 Member Function Documentation . . . . .	208
8.37.3.1 end() . . . . .	208
8.37.3.2 next() . . . . .	208
8.38 Rule< Array_Type, Data_Type > Class Template Reference . . . . .	208
8.38.1 Detailed Description . . . . .	209
8.38.2 Constructor & Destructor Documentation . . . . .	209
8.38.2.1 Rule() [1/2] . . . . .	209
8.38.2.2 Rule() [2/2] . . . . .	209
8.38.2.3 ~Rule() . . . . .	210
8.38.3 Member Function Documentation . . . . .	210
8.38.3.1 D() . . . . .	210
8.38.3.2 get_description() [1/2] . . . . .	210
8.38.3.3 get_description() [2/2] . . . . .	210
8.38.3.4 get_name() [1/2] . . . . .	210
8.38.3.5 get_name() [2/2] . . . . .	211
8.38.3.6 operator>() . . . . .	211
8.39 Rules< Array_Type, Data_Type > Class Template Reference . . . . .	211
8.39.1 Detailed Description . . . . .	212
8.39.2 Constructor & Destructor Documentation . . . . .	212
8.39.2.1 Rules() [1/2] . . . . .	212
8.39.2.2 Rules() [2/2] . . . . .	212
8.39.2.3 ~Rules() . . . . .	212
8.39.3 Member Function Documentation . . . . .	213
8.39.3.1 add_rule() [1/2] . . . . .	213
8.39.3.2 add_rule() [2/2] . . . . .	213
8.39.3.3 get_descriptions() . . . . .	213
8.39.3.4 get_names() . . . . .	213



8.39.3.5 get_seq()	213
8.39.3.6 operator>()	214
8.39.3.7 operator=()	214
8.39.3.8 size()	215
8.40 StatsCounter< Array_Type, Data_Type > Class Template Reference	215
8.40.1 Detailed Description	215
8.40.2 Constructor & Destructor Documentation	216
8.40.2.1 StatsCounter() [1/3]	216
8.40.2.2 StatsCounter() [2/3]	216
8.40.2.3 StatsCounter() [3/3]	216
8.40.2.4 ~StatsCounter()	216
8.40.3 Member Function Documentation	217
8.40.3.1 add_counter()	217
8.40.3.2 count_all()	217
8.40.3.3 count_current()	217
8.40.3.4 count_init()	217
8.40.3.5 get_counters()	217
8.40.3.6 get_descriptions()	218
8.40.3.7 get_names()	218
8.40.3.8 reset_array()	218
8.40.3.9 set_counters()	218
8.40.3.10 size()	218
8.41 Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	219
8.41.1 Detailed Description	220
8.41.2 Constructor & Destructor Documentation	221
8.41.2.1 Support() [1/3]	221
8.41.2.2 Support() [2/3]	221
8.41.2.3 Support() [3/3]	221
8.41.2.4 ~Support()	221
8.41.3 Member Function Documentation	222
8.41.3.1 add_counter()	222
8.41.3.2 add_rule() [1/2]	222
8.41.3.3 add_rule() [2/2]	222
8.41.3.4 add_rule_dyn() [1/2]	222
8.41.3.5 add_rule_dyn() [2/2]	222
8.41.3.6 calc()	223
8.41.3.7 eval_rules_dyn()	223
8.41.3.8 get_counters()	223
8.41.3.9 get_counts()	223
8.41.3.10 get_current_stats()	224
8.41.3.11 get_data()	224

8.41.3.12	<a href="#">get_rules()</a>	224
8.41.3.13	<a href="#">get_rules_dyn()</a>	224
8.41.3.14	<a href="#">init_support()</a>	224
8.41.3.15	<a href="#">print()</a>	225
8.41.3.16	<a href="#">reset_array()</a> [1/2]	225
8.41.3.17	<a href="#">reset_array()</a> [2/2]	225
8.41.3.18	<a href="#">set_counters()</a>	225
8.41.3.19	<a href="#">set_rules()</a>	225
8.41.3.20	<a href="#">set_rules_dyn()</a>	226
8.41.4	<a href="#">Member Data Documentation</a>	226
8.41.4.1	<a href="#">change_stats</a>	226
8.41.4.2	<a href="#">cooriantes_n_free</a>	226
8.41.4.3	<a href="#">cooriantes_n_locked</a>	226
8.41.4.4	<a href="#">coordinates_free</a>	227
8.41.4.5	<a href="#">coordinates_locked</a>	227
8.41.4.6	<a href="#">current_stats</a>	227
8.41.4.7	<a href="#">delete_counters</a>	227
8.41.4.8	<a href="#">delete_rules</a>	227
8.41.4.9	<a href="#">delete_rules_dyn</a>	228
8.41.4.10	<a href="#">hashes</a>	228
8.41.4.11	<a href="#">hashes_initialized</a>	228
8.41.4.12	<a href="#">M</a>	228
8.41.4.13	<a href="#">max_num_elements</a>	228
8.41.4.14	<a href="#">N</a>	229
8.41.4.15	<a href="#">n_counters</a>	229
8.42	<a href="#">vecHasher&lt; T &gt; Struct Template Reference</a>	229
8.42.1	<a href="#">Detailed Description</a>	229
8.42.2	<a href="#">Member Function Documentation</a>	229
8.42.2.1	<a href="#">operator()()</a>	229
<b>9</b>	<b>File Documentation</b>	<b>231</b>
9.1	<a href="#">include/barry/barray-bones.hpp File Reference</a>	231
9.2	<a href="#">include/barry/barray-iterator.hpp File Reference</a>	231
9.3	<a href="#">include/barry/barray-meat-operators.hpp File Reference</a>	232
9.3.1	<a href="#">Macro Definition Documentation</a>	232
9.3.1.1	<a href="#">BARRAY_TEMPLATE</a>	233
9.3.1.2	<a href="#">BARRAY_TEMPLATE_ARGS</a>	233
9.3.1.3	<a href="#">BARRAY_TYPE</a>	233
9.3.1.4	<a href="#">COL</a>	233
9.3.1.5	<a href="#">ROW</a>	233
9.3.2	<a href="#">Function Documentation</a>	233
9.3.2.1	<a href="#">BARRAY_TEMPLATE()</a> [1/6]	234

9.3.2.2 BARRAY_TEMPLATE() [2/6]	234
9.3.2.3 BARRAY_TEMPLATE() [3/6]	234
9.3.2.4 BARRAY_TEMPLATE() [4/6]	234
9.3.2.5 BARRAY_TEMPLATE() [5/6]	234
9.3.2.6 BARRAY_TEMPLATE() [6/6]	235
9.3.2.7 BARRAY_TEMPLATE_ARGS()	235
9.3.2.8 BARRAY_TYPE()	235
9.3.2.9 for()	235
9.3.2.10 operator()()	235
9.3.3 Variable Documentation	235
9.3.3.1 rhs	236
9.3.3.2 this	236
9.4 include/barry/barray-meat.hpp File Reference	236
9.4.1 Macro Definition Documentation	238
9.4.1.1 BARRAY_TEMPLATE	238
9.4.1.2 BARRAY_TEMPLATE_ARGS	238
9.4.1.3 BARRAY_TYPE	239
9.4.1.4 COL	239
9.4.1.5 ROW	239
9.4.2 Function Documentation	239
9.4.2.1 ans()	239
9.4.2.2 BARRAY_TEMPLATE() [1/24]	239
9.4.2.3 BARRAY_TEMPLATE() [2/24]	240
9.4.2.4 BARRAY_TEMPLATE() [3/24]	240
9.4.2.5 BARRAY_TEMPLATE() [4/24]	240
9.4.2.6 BARRAY_TEMPLATE() [5/24]	240
9.4.2.7 BARRAY_TEMPLATE() [6/24]	240
9.4.2.8 BARRAY_TEMPLATE() [7/24]	240
9.4.2.9 BARRAY_TEMPLATE() [8/24]	241
9.4.2.10 BARRAY_TEMPLATE() [9/24]	241
9.4.2.11 BARRAY_TEMPLATE() [10/24]	241
9.4.2.12 BARRAY_TEMPLATE() [11/24]	241
9.4.2.13 BARRAY_TEMPLATE() [12/24]	241
9.4.2.14 BARRAY_TEMPLATE() [13/24]	242
9.4.2.15 BARRAY_TEMPLATE() [14/24]	242
9.4.2.16 BARRAY_TEMPLATE() [15/24]	242
9.4.2.17 BARRAY_TEMPLATE() [16/24]	242
9.4.2.18 BARRAY_TEMPLATE() [17/24]	242
9.4.2.19 BARRAY_TEMPLATE() [18/24]	242
9.4.2.20 BARRAY_TEMPLATE() [19/24]	243
9.4.2.21 BARRAY_TEMPLATE() [20/24]	243
9.4.2.22 BARRAY_TEMPLATE() [21/24]	243

9.4.2.23 BARRAY_TEMPLATE() [22/24]	243
9.4.2.24 BARRAY_TEMPLATE() [23/24]	243
9.4.2.25 BARRAY_TEMPLATE() [24/24]	243
9.4.2.26 COL()	244
9.4.2.27 for() [1/3]	244
9.4.2.28 for() [2/3]	244
9.4.2.29 for() [3/3]	244
9.4.2.30 if() [1/17]	244
9.4.2.31 if() [2/17]	244
9.4.2.32 if() [3/17]	245
9.4.2.33 if() [4/17]	245
9.4.2.34 if() [5/17]	245
9.4.2.35 if() [6/17]	245
9.4.2.36 if() [7/17]	245
9.4.2.37 if() [8/17]	245
9.4.2.38 if() [9/17]	246
9.4.2.39 if() [10/17]	246
9.4.2.40 if() [11/17]	246
9.4.2.41 if() [12/17]	246
9.4.2.42 if() [13/17]	246
9.4.2.43 if() [14/17]	246
9.4.2.44 if() [15/17]	246
9.4.2.45 if() [16/17]	247
9.4.2.46 if() [17/17]	247
9.4.2.47 M()	247
9.4.2.48 resize() [1/2]	247
9.4.2.49 resize() [2/2]	247
9.4.2.50 return()	247
9.4.2.51 ROW() [1/2]	248
9.4.2.52 ROW() [2/2]	248
9.4.3 Variable Documentation	248
9.4.3.1 add	248
9.4.3.2 ans	248
9.4.3.3 Array_	248
9.4.3.4 check_bounds	249
9.4.3.5 check_exists	249
9.4.3.6 col0	249
9.4.3.7 const	249
9.4.3.8 copy_data	250
9.4.3.9 data	250
9.4.3.10 delete_data	250
9.4.3.11 delete_data_	250

9.4.3.12 else	250
9.4.3.13 false	251
9.4.3.14 first	251
9.4.3.15 i1	251
9.4.3.16 j	251
9.4.3.17 j0	251
9.4.3.18 j1	251
9.4.3.19 M	252
9.4.3.20 M_	252
9.4.3.21 N	252
9.4.3.22 NCells	252
9.4.3.23 report	252
9.4.3.24 return	253
9.4.3.25 row0	253
9.4.3.26 search	253
9.4.3.27 source	253
9.4.3.28 target	253
9.4.3.29 v	253
9.4.3.30 value	254
9.5 include/barry/barraycell-bones.hpp File Reference	254
9.6 include/barry/barraycell-meat.hpp File Reference	254
9.7 include/barry/barraydense-bones.hpp File Reference	255
9.8 include/barry/barraydense-meat-operators.hpp File Reference	255
9.8.1 Macro Definition Documentation	256
9.8.1.1 BDENSE_TEMPLATE	256
9.8.1.2 BDENSE_TEMPLATE_ARGS	256
9.8.1.3 BDENSE_TYPE	256
9.8.1.4 COL	256
9.8.1.5 POS	257
9.8.1.6 POS_N	257
9.8.1.7 ROW	257
9.8.2 Function Documentation	257
9.8.2.1 BDENSE_TEMPLATE() [1/4]	257
9.8.2.2 BDENSE_TEMPLATE() [2/4]	257
9.8.2.3 BDENSE_TEMPLATE() [3/4]	258
9.8.2.4 BDENSE_TEMPLATE() [4/4]	258
9.8.2.5 BDENSE_TEMPLATE_ARGS()	258
9.8.2.6 BDENSE_TYPE()	258
9.9 include/barry/barraydense-meat.hpp File Reference	258
9.9.1 Macro Definition Documentation	261
9.9.1.1 BDENSE_TEMPLATE	261
9.9.1.2 BDENSE_TEMPLATE_ARGS	261

9.9.1.3 BDENSE_TYPE	261
9.9.1.4 COL	261
9.9.1.5 POS	261
9.9.1.6 POS_N	262
9.9.1.7 ROW	262
9.9.1.8 ZERO_CELL	262
9.9.2 Function Documentation	262
9.9.2.1 ans()	262
9.9.2.2 BDENSE_TEMPLATE() [1/39]	262
9.9.2.3 BDENSE_TEMPLATE() [2/39]	263
9.9.2.4 BDENSE_TEMPLATE() [3/39]	263
9.9.2.5 BDENSE_TEMPLATE() [4/39]	263
9.9.2.6 BDENSE_TEMPLATE() [5/39]	263
9.9.2.7 BDENSE_TEMPLATE() [6/39]	263
9.9.2.8 BDENSE_TEMPLATE() [7/39]	263
9.9.2.9 BDENSE_TEMPLATE() [8/39]	264
9.9.2.10 BDENSE_TEMPLATE() [9/39]	264
9.9.2.11 BDENSE_TEMPLATE() [10/39]	264
9.9.2.12 BDENSE_TEMPLATE() [11/39]	264
9.9.2.13 BDENSE_TEMPLATE() [12/39]	264
9.9.2.14 BDENSE_TEMPLATE() [13/39]	265
9.9.2.15 BDENSE_TEMPLATE() [14/39]	265
9.9.2.16 BDENSE_TEMPLATE() [15/39]	265
9.9.2.17 BDENSE_TEMPLATE() [16/39]	265
9.9.2.18 BDENSE_TEMPLATE() [17/39]	265
9.9.2.19 BDENSE_TEMPLATE() [18/39]	266
9.9.2.20 BDENSE_TEMPLATE() [19/39]	266
9.9.2.21 BDENSE_TEMPLATE() [20/39]	266
9.9.2.22 BDENSE_TEMPLATE() [21/39]	266
9.9.2.23 BDENSE_TEMPLATE() [22/39]	266
9.9.2.24 BDENSE_TEMPLATE() [23/39]	267
9.9.2.25 BDENSE_TEMPLATE() [24/39]	267
9.9.2.26 BDENSE_TEMPLATE() [25/39]	267
9.9.2.27 BDENSE_TEMPLATE() [26/39]	267
9.9.2.28 BDENSE_TEMPLATE() [27/39]	267
9.9.2.29 BDENSE_TEMPLATE() [28/39]	268
9.9.2.30 BDENSE_TEMPLATE() [29/39]	268
9.9.2.31 BDENSE_TEMPLATE() [30/39]	268
9.9.2.32 BDENSE_TEMPLATE() [31/39]	268
9.9.2.33 BDENSE_TEMPLATE() [32/39]	268
9.9.2.34 BDENSE_TEMPLATE() [33/39]	268
9.9.2.35 BDENSE_TEMPLATE() [34/39]	269

9.9.2.36 BDENSE_TEMPLATE() [35/39]	269
9.9.2.37 BDENSE_TEMPLATE() [36/39]	269
9.9.2.38 BDENSE_TEMPLATE() [37/39]	269
9.9.2.39 BDENSE_TEMPLATE() [38/39]	269
9.9.2.40 BDENSE_TEMPLATE() [39/39]	269
9.9.2.41 for()	270
9.9.2.42 if() [1/4]	270
9.9.2.43 if() [2/4]	270
9.9.2.44 if() [3/4]	270
9.9.2.45 if() [4/4]	270
9.9.2.46 insert_cell() [1/2]	270
9.9.2.47 insert_cell() [2/2]	271
9.9.2.48 M()	271
9.9.2.49 resize() [1/6]	271
9.9.2.50 resize() [2/6]	271
9.9.2.51 resize() [3/6]	271
9.9.2.52 resize() [4/6]	271
9.9.2.53 resize() [5/6]	272
9.9.2.54 resize() [6/6]	272
9.9.2.55 rm_cell() [1/3]	272
9.9.2.56 rm_cell() [2/3]	272
9.9.2.57 rm_cell() [3/3]	272
9.9.2.58 va_end()	272
9.9.2.59 va_start()	273
9.9.2.60 vprintf()	273
9.9.3 Variable Documentation	273
9.9.3.1 add	273
9.9.3.2 ans	273
9.9.3.3 check_bounds	273
9.9.3.4 check_exists	274
9.9.3.5 col	274
9.9.3.6 const	274
9.9.3.7 copy_data	274
9.9.3.8 data	274
9.9.3.9 delete_data	275
9.9.3.10 delete_data_	275
9.9.3.11 el	275
9.9.3.12 el_colsums	275
9.9.3.13 el_rowsums	275
9.9.3.14 else	276
9.9.3.15 false	276
9.9.3.16 i1	276

9.9.3.17 j	276
9.9.3.18 j0	276
9.9.3.19 j1	276
9.9.3.20 M	277
9.9.3.21 M_	277
9.9.3.22 N	277
9.9.3.23 report	277
9.9.3.24 return	277
9.9.3.25 source	278
9.9.3.26 target	278
9.9.3.27 v	278
9.9.3.28 val0	278
9.9.3.29 val1	278
9.9.3.30 value	278
9.10 include/barry/barraydensecell-bones.hpp File Reference	279
9.10.1 Macro Definition Documentation	279
9.10.1.1 POS	279
9.11 include/barry/barraydensecell-meat.hpp File Reference	280
9.11.1 Macro Definition Documentation	280
9.11.1.1 POS	280
9.12 include/barry/barraydensecol-bones.hpp File Reference	280
9.12.1 Macro Definition Documentation	281
9.12.1.1 POS	281
9.12.1.2 POS_N	281
9.12.1.3 ZERO_CELL	281
9.13 include/barry/barraydenserow-bones.hpp File Reference	282
9.13.1 Macro Definition Documentation	282
9.13.1.1 POS	282
9.13.1.2 POS_N	283
9.13.1.3 ZERO_CELL	283
9.14 include/barry/barrayrow-bones.hpp File Reference	283
9.15 include/barry/barrayrow-meat.hpp File Reference	283
9.15.1 Macro Definition Documentation	283
9.15.1.1 BROW_TEMPLATE	284
9.15.1.2 BROW_TEMPLATE_ARGS	284
9.15.1.3 BROW_TYPE	284
9.15.2 Function Documentation	284
9.15.2.1 BROW_TEMPLATE() [1/5]	284
9.15.2.2 BROW_TEMPLATE() [2/5]	284
9.15.2.3 BROW_TEMPLATE() [3/5]	285
9.15.2.4 BROW_TEMPLATE() [4/5]	285
9.15.2.5 BROW_TEMPLATE() [5/5]	285



9.16 include/barry/barrayvector-bones.hpp File Reference . . . . .	285
9.17 include/barry/barrayvector-meat.hpp File Reference . . . . .	286
9.18 include/barry/barry-configuration.hpp File Reference . . . . .	286
9.18.1 Macro Definition Documentation . . . . .	287
9.18.1.1 BARRY_CHECK_SUPPORT . . . . .	287
9.18.1.2 BARRY_ISFINITE . . . . .	287
9.18.1.3 BARRY_MAX_NUM_ELEMENTS . . . . .	287
9.18.1.4 BARRY_SAFE_EXP . . . . .	287
9.18.1.5 printf_barry . . . . .	287
9.18.2 Typedef Documentation . . . . .	287
9.18.2.1 Map . . . . .	288
9.19 include/barry/barry-debug.hpp File Reference . . . . .	288
9.19.1 Macro Definition Documentation . . . . .	288
9.19.1.1 BARRY_DEBUG_LEVEL . . . . .	288
9.20 include/barry/barry-macros.hpp File Reference . . . . .	289
9.20.1 Macro Definition Documentation . . . . .	289
9.20.1.1 BARRY_ONE . . . . .	289
9.20.1.2 BARRY_ONE_DENSE . . . . .	289
9.20.1.3 BARRY_UNUSED . . . . .	290
9.20.1.4 BARRY_ZERO . . . . .	290
9.20.1.5 BARRY_ZERO_DENSE . . . . .	290
9.21 include/barry/barry.hpp File Reference . . . . .	290
9.21.1 Macro Definition Documentation . . . . .	291
9.21.1.1 BARRY_HPP . . . . .	292
9.21.1.2 BARRY_VERSION . . . . .	292
9.21.1.3 BARRY_VERSION_MAYOR . . . . .	292
9.21.1.4 BARRY_VERSION_MINOR . . . . .	292
9.21.1.5 COUNTER_FUNCTION . . . . .	292
9.21.1.6 COUNTER_LAMBDA . . . . .	293
9.21.1.7 RULE_FUNCTION . . . . .	293
9.21.1.8 RULE_LAMBDA . . . . .	293
9.22 include/barry/cell-bones.hpp File Reference . . . . .	293
9.23 include/barry/cell-meat.hpp File Reference . . . . .	294
9.24 include/barry/col-bones.hpp File Reference . . . . .	294
9.25 include/barry/counters-bones.hpp File Reference . . . . .	294
9.26 include/barry/counters-meat.hpp File Reference . . . . .	295
9.26.1 Macro Definition Documentation . . . . .	296
9.26.1.1 COUNTER_TEMPLATE . . . . .	296
9.26.1.2 COUNTER_TEMPLATE_ARGS . . . . .	297
9.26.1.3 COUNTER_TYPE . . . . .	297
9.26.1.4 COUNTERS_TEMPLATE . . . . .	297
9.26.1.5 COUNTERS_TEMPLATE_ARGS . . . . .	297

9.26.1.6 COUNTERS_TYPE	297
9.26.1.7 TMP_HASHER_CALL	297
9.26.2 Function Documentation	298
9.26.2.1 count_fun()	298
9.26.2.2 COUNTER_TEMPLATE() [1/9]	298
9.26.2.3 COUNTER_TEMPLATE() [2/9]	298
9.26.2.4 COUNTER_TEMPLATE() [3/9]	298
9.26.2.5 COUNTER_TEMPLATE() [4/9]	298
9.26.2.6 COUNTER_TEMPLATE() [5/9]	299
9.26.2.7 COUNTER_TEMPLATE() [6/9]	299
9.26.2.8 COUNTER_TEMPLATE() [7/9]	299
9.26.2.9 COUNTER_TEMPLATE() [8/9]	299
9.26.2.10 COUNTER_TEMPLATE() [9/9]	299
9.26.2.11 COUNTERS_TEMPLATE() [1/9]	300
9.26.2.12 COUNTERS_TEMPLATE() [2/9]	300
9.26.2.13 COUNTERS_TEMPLATE() [3/9]	300
9.26.2.14 COUNTERS_TEMPLATE() [4/9]	300
9.26.2.15 COUNTERS_TEMPLATE() [5/9]	300
9.26.2.16 COUNTERS_TEMPLATE() [6/9]	300
9.26.2.17 COUNTERS_TEMPLATE() [7/9]	301
9.26.2.18 COUNTERS_TEMPLATE() [8/9]	301
9.26.2.19 COUNTERS_TEMPLATE() [9/9]	301
9.26.2.20 data()	301
9.26.2.21 desc()	301
9.26.2.22 for()	301
9.26.2.23 hasher() [1/2]	302
9.26.2.24 hasher() [2/2]	302
9.26.2.25 hasher_fun() [1/2]	302
9.26.2.26 hasher_fun() [2/2]	302
9.26.2.27 if() [1/3]	302
9.26.2.28 if() [2/3]	302
9.26.2.29 if() [3/3]	303
9.26.2.30 init_fun() [1/3]	303
9.26.2.31 init_fun() [2/3]	303
9.26.2.32 init_fun() [3/3]	303
9.26.2.33 name()	303
9.26.3 Variable Documentation	303
9.26.3.1 add_dims	303
9.26.3.2 count_fun_	304
9.26.3.3 counter	304
9.26.3.4 counter_	304
9.26.3.5 data_	304

9.26.3.6 desc_ . . . . .	305
9.26.3.7 fun . . . . .	305
9.26.3.8 fun_ . . . . .	305
9.26.3.9 hasher_fun_ . . . . .	305
9.26.3.10 i . . . . .	306
9.26.3.11 init_fun_ . . . . .	306
9.26.3.12 j . . . . .	306
9.26.3.13 name_ . . . . .	306
9.26.3.14 noexcept . . . . .	306
9.26.3.15 res . . . . .	307
9.26.3.16 return . . . . .	307
9.27 include/barry/counters/defm-formula.hpp File Reference . . . . .	307
9.27.1 Function Documentation . . . . .	307
9.27.1.1 defm_motif_parser() . . . . .	308
9.28 include/barry/counters/defm.hpp File Reference . . . . .	309
9.28.1 Macro Definition Documentation . . . . .	311
9.28.1.1 UNI_SUB . . . . .	311
9.28.2 Typedef Documentation . . . . .	311
9.28.2.1 DEFMArray . . . . .	311
9.29 include/barry/models/defm.hpp File Reference . . . . .	312
9.30 include/barry/counters/network-css.hpp File Reference . . . . .	312
9.30.1 Macro Definition Documentation . . . . .	314
9.30.1.1 CSS_APPEND . . . . .	314
9.30.1.2 CSS_CASE_ELSE . . . . .	314
9.30.1.3 CSS_CASE_PERCEIVED . . . . .	314
9.30.1.4 CSS_CASE_TRUTH . . . . .	314
9.30.1.5 CSS_CHECK_SIZE . . . . .	315
9.30.1.6 CSS_CHECK_SIZE_INIT . . . . .	315
9.30.1.7 CSS_NET_COUNTER_LAMBDA_INIT . . . . .	315
9.30.1.8 CSS_PERCEIVED_CELLS . . . . .	315
9.30.1.9 CSS_SIZE . . . . .	316
9.30.1.10 CSS_TRUE_CELLS . . . . .	316
9.30.2 Function Documentation . . . . .	316
9.30.2.1 counter_css_census01() . . . . .	316
9.30.2.2 counter_css_census02() . . . . .	316
9.30.2.3 counter_css_census03() . . . . .	317
9.30.2.4 counter_css_census04() . . . . .	317
9.30.2.5 counter_css_census05() . . . . .	317
9.30.2.6 counter_css_census06() . . . . .	317
9.30.2.7 counter_css_census07() . . . . .	318
9.30.2.8 counter_css_census08() . . . . .	318
9.30.2.9 counter_css_census09() . . . . .	318

9.30.2.10 counter_css_census10()	318
9.30.2.11 counter_css_completely_false_recip_comiss()	319
9.30.2.12 counter_css_completely_false_recip_omiss()	319
9.30.2.13 counter_css_mixed_recip()	319
9.30.2.14 counter_css_partially_false_recip_commi()	319
9.30.2.15 counter_css_partially_false_recip_omiss()	320
9.31 include/barry/counters/network.hpp File Reference	320
9.31.1 Macro Definition Documentation	323
9.31.1.1 BARRY_ZERO_NETWORK	323
9.31.1.2 BARRY_ZERO_NETWORK_DENSE	324
9.31.1.3 NET_C_DATA_IDX	324
9.31.1.4 NET_C_DATA_NUM	324
9.31.1.5 NETWORK_COUNTER	324
9.31.1.6 NETWORK_COUNTER_LAMBDA	324
9.31.1.7 NETWORK_RULE	325
9.31.1.8 NETWORK_RULE_LAMBDA	325
9.31.1.9 NETWORKDENSE_COUNTER_LAMBDA	325
9.31.2 Typedef Documentation	325
9.31.2.1 NetCounter	325
9.31.2.2 NetCounters	326
9.31.2.3 NetModel	326
9.31.2.4 NetRule	326
9.31.2.5 NetRules	326
9.31.2.6 NetStatsCounter	326
9.31.2.7 NetSupport	326
9.31.2.8 Network	327
9.31.2.9 NetworkDense	327
9.31.3 Function Documentation	327
9.31.3.1 rules_zerodiag()	327
9.32 include/barry/counters/phylo.hpp File Reference	327
9.32.1 Macro Definition Documentation	330
9.32.1.1 DEFAULT_DUPLICATION	330
9.32.1.2 DUPL_DUPL	330
9.32.1.3 DUPL_EITH	330
9.32.1.4 DUPL_SPEC	330
9.32.1.5 IF_MATCHES	331
9.32.1.6 IF_NOTMATCHES	331
9.32.1.7 IS_DUPLICATION	331
9.32.1.8 IS_EITHER	331
9.32.1.9 IS_SPECIATION	331
9.32.1.10 MAKE_DUPL_VARS	332
9.32.1.11 PHYLO_CHECK_MISSING	332

9.32.1.12 PHYLO_COUNTER_LAMBDA . . . . .	332
9.32.1.13 PHYLO_RULE_DYN_LAMBDA . . . . .	332
9.32.2 Typedef Documentation . . . . .	333
9.32.2.1 PhyloArray . . . . .	333
9.32.2.2 PhyloCounter . . . . .	333
9.32.2.3 PhyloCounters . . . . .	333
9.32.2.4 PhyloModel . . . . .	333
9.32.2.5 PhyloPowerSet . . . . .	333
9.32.2.6 PhyloRule . . . . .	334
9.32.2.7 PhyloRuleData . . . . .	334
9.32.2.8 PhyloRuleDyn . . . . .	334
9.32.2.9 PhyloRules . . . . .	334
9.32.2.10 PhyloRulesDyn . . . . .	334
9.32.2.11 PhyloStatsCounter . . . . .	334
9.32.2.12 PhyloSupport . . . . .	335
9.32.3 Function Documentation . . . . .	335
9.32.3.1 get_last_name() . . . . .	335
9.33 include/barry/freqtable.hpp File Reference . . . . .	335
9.34 include/barry/model-bones.hpp File Reference . . . . .	336
9.35 include/barry/model-meat.hpp File Reference . . . . .	336
9.35.1 Macro Definition Documentation . . . . .	338
9.35.1.1 MODEL_TEMPLATE . . . . .	338
9.35.1.2 MODEL_TEMPLATE_ARGS . . . . .	339
9.35.1.3 MODEL_TYPE . . . . .	339
9.35.2 Function Documentation . . . . .	339
9.35.2.1 for() . . . . .	339
9.35.2.2 if() [1/4] . . . . .	339
9.35.2.3 if() [2/4] . . . . .	339
9.35.2.4 if() [3/4] . . . . .	340
9.35.2.5 if() [4/4] . . . . .	340
9.35.2.6 insert_cell() . . . . .	340
9.35.2.7 likelihood_() . . . . .	340
9.35.2.8 MODEL_TEMPLATE() [1/33] . . . . .	340
9.35.2.9 MODEL_TEMPLATE() [2/33] . . . . .	341
9.35.2.10 MODEL_TEMPLATE() [3/33] . . . . .	341
9.35.2.11 MODEL_TEMPLATE() [4/33] . . . . .	341
9.35.2.12 MODEL_TEMPLATE() [5/33] . . . . .	341
9.35.2.13 MODEL_TEMPLATE() [6/33] . . . . .	341
9.35.2.14 MODEL_TEMPLATE() [7/33] . . . . .	342
9.35.2.15 MODEL_TEMPLATE() [8/33] . . . . .	342
9.35.2.16 MODEL_TEMPLATE() [9/33] . . . . .	342
9.35.2.17 MODEL_TEMPLATE() [10/33] . . . . .	342

9.35.2.18 MODEL_TEMPLATE()	[11/33]	342
9.35.2.19 MODEL_TEMPLATE()	[12/33]	343
9.35.2.20 MODEL_TEMPLATE()	[13/33]	343
9.35.2.21 MODEL_TEMPLATE()	[14/33]	343
9.35.2.22 MODEL_TEMPLATE()	[15/33]	343
9.35.2.23 MODEL_TEMPLATE()	[16/33]	343
9.35.2.24 MODEL_TEMPLATE()	[17/33]	344
9.35.2.25 MODEL_TEMPLATE()	[18/33]	344
9.35.2.26 MODEL_TEMPLATE()	[19/33]	344
9.35.2.27 MODEL_TEMPLATE()	[20/33]	344
9.35.2.28 MODEL_TEMPLATE()	[21/33]	344
9.35.2.29 MODEL_TEMPLATE()	[22/33]	345
9.35.2.30 MODEL_TEMPLATE()	[23/33]	345
9.35.2.31 MODEL_TEMPLATE()	[24/33]	345
9.35.2.32 MODEL_TEMPLATE()	[25/33]	345
9.35.2.33 MODEL_TEMPLATE()	[26/33]	345
9.35.2.34 MODEL_TEMPLATE()	[27/33]	345
9.35.2.35 MODEL_TEMPLATE()	[28/33]	346
9.35.2.36 MODEL_TEMPLATE()	[29/33]	346
9.35.2.37 MODEL_TEMPLATE()	[30/33]	346
9.35.2.38 MODEL_TEMPLATE()	[31/33]	346
9.35.2.39 MODEL_TEMPLATE()	[32/33]	346
9.35.2.40 MODEL_TEMPLATE()	[33/33]	346
9.35.2.41 push_back()	[1/2]	347
9.35.2.42 push_back()	[2/2]	347
9.35.2.43 return()		347
9.35.2.44 set_counters()		347
9.35.2.45 set_rules()		347
9.35.2.46 set_rules_dyn()		347
9.35.2.47 size()		347
9.35.2.48 temp_stats()		348
9.35.2.49 tmp_counts()		348
9.35.2.50 update_normalizing_constant()		348
9.35.2.51 urand()		348
9.35.3 Variable Documentation		348
9.35.3.1 a		348
9.35.3.2 count_fun_		349
9.35.3.3 counter		349
9.35.3.4 counters_		349
9.35.3.5 cumprob		349
9.35.3.6 data_		349
9.35.3.7 Data_Counter_Type		350

9.35.3.8 Data_Rule_Type . . . . .	350
9.35.3.9 delete_rules . . . . .	350
9.35.3.10 delete_rules_dyn . . . . .	350
9.35.3.11 else . . . . .	350
9.35.3.12 force_new . . . . .	351
9.35.3.13 fun_ . . . . .	351
9.35.3.14 i . . . . .	351
9.35.3.15 i_matches . . . . .	351
9.35.3.16 init_fun_ . . . . .	351
9.35.3.17 j . . . . .	352
9.35.3.18 k . . . . .	352
9.35.3.19 key . . . . .	352
9.35.3.20 locator . . . . .	352
9.35.3.21 params . . . . .	352
9.35.3.22 probs . . . . .	352
9.35.3.23 pset_arrays . . . . .	353
9.35.3.24 r . . . . .	353
9.35.3.25 return . . . . .	353
9.35.3.26 rule_fun_ . . . . .	353
9.35.3.27 rules . . . . .	353
9.35.3.28 rules_ . . . . .	354
9.35.3.29 rules_dyn . . . . .	354
9.35.3.30 stats . . . . .	354
9.35.3.31 stats_support_n_arrays . . . . .	354
9.36 include/barry/models/defm/defm-bones.hpp File Reference . . . . .	354
9.37 include/barry/models/defm/defm-meat.hpp File Reference . . . . .	355
9.37.1 Macro Definition Documentation . . . . .	355
9.37.1.1 DEFM_LOOP_ARRAYS . . . . .	355
9.37.1.2 DEFM_RANGES . . . . .	356
9.37.2 Function Documentation . . . . .	356
9.37.2.1 keygen_defm() . . . . .	356
9.38 include/barry/models/geese.hpp File Reference . . . . .	356
9.39 include/barry/models/geese/flock-bones.hpp File Reference . . . . .	357
9.40 include/barry/models/geese/flock-meat.hpp File Reference . . . . .	357
9.41 include/barry/models/geese/geese-bones.hpp File Reference . . . . .	358
9.41.1 Macro Definition Documentation . . . . .	358
9.41.1.1 INITIALIZED . . . . .	359
9.41.2 Function Documentation . . . . .	359
9.41.2.1 keygen_full() . . . . .	359
9.41.2.2 RULE_FUNCTION() . . . . .	359
9.41.2.3 vec_diff() . . . . .	359
9.41.2.4 vector_caster() . . . . .	359

9.42 include/barry/models/geese/geese-meat-constructors.hpp File Reference	360
9.43 include/barry/models/geese/geese-meat-likelihood.hpp File Reference	360
9.44 include/barry/models/geese/geese-meat-likelihood_exhaust.hpp File Reference	361
9.45 include/barry/models/geese/geese-meat-predict.hpp File Reference	362
9.46 include/barry/models/geese/geese-meat-predict_exhaust.hpp File Reference	362
9.47 include/barry/models/geese/geese-meat-predict_sim.hpp File Reference	363
9.48 include/barry/models/geese/geese-meat-simulate.hpp File Reference	363
9.49 include/barry/models/geese/geese-meat.hpp File Reference	364
9.50 include/barry/models/geese/geese-node-bones.hpp File Reference	364
9.51 include/barry/powerset-bones.hpp File Reference	365
9.52 include/barry/powerset-meat.hpp File Reference	365
9.53 include/barry/progress.hpp File Reference	366
9.53.1 Macro Definition Documentation	366
9.53.1.1 BARRY_PROGRESS_BAR_WIDTH	366
9.54 include/barry/rules-bones.hpp File Reference	367
9.54.1 Function Documentation	367
9.54.1.1 rule_fun_default()	367
9.55 include/barry/rules-meat.hpp File Reference	368
9.56 include/barry/statscounter-bones.hpp File Reference	368
9.57 include/barry/statscounter-meat.hpp File Reference	369
9.57.1 Macro Definition Documentation	370
9.57.1.1 STATSCOUNTER_TEMPLATE	370
9.57.1.2 STATSCOUNTER_TEMPLATE_ARGS	370
9.57.1.3 STATSCOUNTER_TYPE	370
9.57.2 Function Documentation	370
9.57.2.1 clear()	370
9.57.2.2 for()	370
9.57.2.3 resize()	371
9.57.2.4 STATSCOUNTER_TEMPLATE() [1/9]	371
9.57.2.5 STATSCOUNTER_TEMPLATE() [2/9]	371
9.57.2.6 STATSCOUNTER_TEMPLATE() [3/9]	371
9.57.2.7 STATSCOUNTER_TEMPLATE() [4/9]	371
9.57.2.8 STATSCOUNTER_TEMPLATE() [5/9]	371
9.57.2.9 STATSCOUNTER_TEMPLATE() [6/9]	372
9.57.2.10 STATSCOUNTER_TEMPLATE() [7/9]	372
9.57.2.11 STATSCOUNTER_TEMPLATE() [8/9]	372
9.57.2.12 STATSCOUNTER_TEMPLATE() [9/9]	372
9.57.3 Variable Documentation	372
9.57.3.1 counter	372
9.57.3.2 counter_deleted	373
9.57.3.3 counters	373
9.57.3.4 counters_	373



9.57.3.5 current_stats	373
9.57.3.6 EmptyArray	373
9.57.3.7 f_	374
9.57.3.8 j	374
9.57.3.9 return	374
9.58 include/barry/support-bones.hpp File Reference	374
9.59 include/barry/support-meat.hpp File Reference	375
9.59.1 Macro Definition Documentation	376
9.59.1.1 BARRY_SUPPORT_MEAT_HPP	376
9.59.1.2 SUPPORT_TEMPLATE	376
9.59.1.3 SUPPORT_TEMPLATE_ARGS	377
9.59.1.4 SUPPORT_TYPE	377
9.59.2 Function Documentation	377
9.59.2.1 calc_backend_dense()	377
9.59.2.2 calc_backend_sparse()	377
9.59.2.3 for()	377
9.59.2.4 if() [1/3]	378
9.59.2.5 if() [2/3]	378
9.59.2.6 if() [3/3]	378
9.59.2.7 insert_cell() [1/2]	378
9.59.2.8 insert_cell() [2/2]	378
9.59.2.9 rm_cell()	379
9.59.2.10 SUPPORT_TEMPLATE() [1/17]	379
9.59.2.11 SUPPORT_TEMPLATE() [2/17]	379
9.59.2.12 SUPPORT_TEMPLATE() [3/17]	379
9.59.2.13 SUPPORT_TEMPLATE() [4/17]	379
9.59.2.14 SUPPORT_TEMPLATE() [5/17]	380
9.59.2.15 SUPPORT_TEMPLATE() [6/17]	380
9.59.2.16 SUPPORT_TEMPLATE() [7/17]	380
9.59.2.17 SUPPORT_TEMPLATE() [8/17]	380
9.59.2.18 SUPPORT_TEMPLATE() [9/17]	380
9.59.2.19 SUPPORT_TEMPLATE() [10/17]	380
9.59.2.20 SUPPORT_TEMPLATE() [11/17]	381
9.59.2.21 SUPPORT_TEMPLATE() [12/17]	381
9.59.2.22 SUPPORT_TEMPLATE() [13/17]	381
9.59.2.23 SUPPORT_TEMPLATE() [14/17]	381
9.59.2.24 SUPPORT_TEMPLATE() [15/17]	381
9.59.2.25 SUPPORT_TEMPLATE() [16/17]	382
9.59.2.26 SUPPORT_TEMPLATE() [17/17]	382
9.59.3 Variable Documentation	382
9.59.3.1 array_bank	382
9.59.3.2 change_stats_different	382

9.59.3.3 coord_i . . . . .	382
9.59.3.4 coord_j . . . . .	382
9.59.3.5 counters . . . . .	383
9.59.3.6 counters_ . . . . .	383
9.59.3.7 delete_counters . . . . .	383
9.59.3.8 delete_rules . . . . .	383
9.59.3.9 delete_rules_dyn . . . . .	383
9.59.3.10 else . . . . .	384
9.59.3.11 f_ . . . . .	384
9.59.3.12 hashes . . . . .	384
9.59.3.13 return . . . . .	384
9.59.3.14 rules . . . . .	384
9.59.3.15 rules_ . . . . .	385
9.59.3.16 rules_dyn . . . . .	385
9.59.3.17 stats_bank . . . . .	385
9.59.3.18 tmp_chng . . . . .	385
9.60 include/barry/typedefs.hpp File Reference . . . . .	386
9.60.1 Typedef Documentation . . . . .	388
9.60.1.1 Col_type . . . . .	388
9.60.1.2 Counter_fun_type . . . . .	388
9.60.1.3 Counts_type . . . . .	388
9.60.1.4 Hasher_fun_type . . . . .	388
9.60.1.5 MapVec_type . . . . .	389
9.60.1.6 Row_type . . . . .	389
9.60.1.7 Rule_fun_type . . . . .	389
9.60.1.8 uint . . . . .	389
9.60.2 Function Documentation . . . . .	389
9.60.2.1 sort_array() . . . . .	389
9.60.2.2 vec_equal() . . . . .	390
9.60.2.3 vec_equal_approx() . . . . .	390
9.60.2.4 vec_inner_prod() [1/2] . . . . .	391
9.60.2.5 vec_inner_prod() [2/2] . . . . .	391
9.61 README.md File Reference . . . . .	391
<b>Index</b>	<b>393</b>

# Chapter 1

## Main Page

### Barry: your to-go motif accountant

This repository contains a C++ template library that essentially counts sufficient statistics on binary arrays. Its primary goal is to provide a general framework for building discrete exponential-family models. A particular example is Exponential Random Graph Models (ERGMs), but we can use `barry` to deal with non-square arrays.

Among the key features included in `barry`, we have:

- Sparse arrays.
- User-defined count statistics.
- User-defined constrain of the support set.
- Powerset generation of binary arrays.
- Discrete Exponential Family Models module (DEFMs).
- Pooled DEFMs.

To use `barry`, you can either download the entire repository or, since it is header-only, the single header version `barry.hpp`.

This library was created and maintained by Dr. George G. Vega Yon as part of his doctoral dissertation "Essays on Bioinformatics and Social Network Analysis: Statistical and Computational Methods for Complex Systems."

## Examples

### Counting statistics in a graph

In the following code we create an array of size 5x5 of class `Network` (available in the namespace `netcounters`), add/remove ties, print the graph, and count common statistics used in ERGMs:

```
#include <iostream>
#include <ostream>
#include "../include/barry.hpp"
typedef std::vector< unsigned int > vuint;
int main() {
    // Creating network of size six with five ties
    netcounters::Network net(
        6, 6,
        {0, 0, 4, 4, 2, 0, 1},
        {1, 2, 0, 2, 4, 0, 1}
    );

    // How does this looks like?
    net.print("Current view");

    // Adding extra ties
    net += {1, 0};
    net(2, 0) = true;

    // And removing a couple
    net(0, 0) = false;
    net -= {1, 1};
    net.print("New view");

    // Initializing the data. The program deals with freeing the memory
    net.set_data(new netcounters::NetworkData, true);
    // Creating counter object for the network and adding stats to count
    netcounters::NetStatsCounter counter(&net);
    netcounters::counter_edges(counter.counters);
    netcounters::counter_ttriads(counter.counters);
    netcounters::counter_isolates(counter.counters);
    netcounters::counter_ctriads(counter.counters);
    netcounters::counter_mutual(counter.counters);

    // Counting and printing the results
    std::vector< double > counts = counter.count_all();

    std::cout <<
        "Edges          : " << counts[0] << std::endl <<
        "Transitive triads : " << counts[1] << std::endl <<
        "Isolates         : " << counts[2] << std::endl <<
        "C triads         : " << counts[3] << std::endl <<
        "Mutuals         : " << counts[4] << std::endl;

    return 0;
}
```

Compiling this program using g++

```
g++ -std=c++11 -Wall -pedantic 08-counts.cpp -o counts && ./counts
```

Yields the following output:

```
Current view
[ 0,] 1 1 1 . . .
[ 1,] . 1 . . . .
[ 2,] . . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
New view
[ 0,] . 1 1 . . .
[ 1,] 1 . . . . .
[ 2,] 1 . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
Edges          : 7
Transitive triads : 3
Isolates       : 2
C triads       : 1
Mutuals        : 3
```

## Features

### Efficient memory usage

One of the key features of `barry` is that it will handle memory efficiently. In the case of pooled-data models, the module for statistical models avoids double-counting support when possible by keeping track of what datasets (networks, for instance) share the same.

## Documentation

More information can be found in the Doxygen website [here](#) and in the PDF version of the documentation [here](#).

## Code of Conduct

Please note that the `barry` project is released with a [Contributor Code of Conduct](#). By contributing to this project, you agree to abide by its terms.



## Chapter 2

# Module Index

### 2.1 Modules

Here is a list of all modules:

Counting . . . . .	13
Statistical Models . . . . .	13
Phylo rules . . . . .	14
DEFMArray counters . . . . .	19
Phylo counters . . . . .	30





## Chapter 3

# Hierarchical Index

### 3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

BArray< Cell_Type, Data_Type > . . . . .	43
BArray< bool, bool > . . . . .	43
BArray< Cell_Type, Data_Type > . . . . .	43
BArrayCell< Cell_Type, Data_Type > . . . . .	57
BArrayCell_const< Cell_Type, Data_Type > . . . . .	60
BArrayDense< Cell_Type, Data_Type > . . . . .	62
BArrayDense< bool, bool > . . . . .	62
BArrayDenseCell< Cell_Type, Data_Type > . . . . .	78
BArrayDenseCell_const< Cell_Type, Data_Type > . . . . .	82
BArrayDenseCol< Cell_Type, Data_Type > . . . . .	82
BArrayDenseCol_const< Cell_Type, Data_Type > . . . . .	84
BArrayDenseRow< Cell_Type, Data_Type > . . . . .	86
BArrayDenseRow_const< Cell_Type, Data_Type > . . . . .	89
BArrayRow< Cell_Type, Data_Type > . . . . .	91
BArrayRow_const< Cell_Type, Data_Type > . . . . .	93
BArrayVector< Cell_Type, Data_Type > . . . . .	95
BArrayVector_const< Cell_Type, Data_Type > . . . . .	99
Cell< Cell_Type > . . . . .	103
Cell< bool > . . . . .	103
Cell_const< Cell_Type > . . . . .	108
ConstBArrayRowIter< Cell_Type, Data_Type > . . . . .	108
Counter< Array_Type, Data_Type > . . . . .	110
Counters< Array_Type, Data_Type > . . . . .	116
Counters< Array_Type, Data_Type > . . . . .	116
Counters< BArray< bool, bool >, bool > . . . . .	116
Counters< BArray<>, bool > . . . . .	116
DEFMCounterData . . . . .	125
DEFMData . . . . .	128
barry::counters::defm::DEFMModel	
DEFM . . . . .	121
DEFMRuleData . . . . .	132
DEFMRuleDynData . . . . .	135
Entries< Cell_Type > . . . . .	136
Flock . . . . .	139
FreqTable< T > . . . . .	145

Geese . . . . .	149
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > . . . . .	162
NetCounterData . . . . .	184
NetworkData . . . . .	185
Node . . . . .	188
NodeData . . . . .	194
PhyloCounterData . . . . .	195
PhyloRuleDynData . . . . .	198
PowerSet< Array_Type, Data_Rule_Type > . . . . .	200
Progress . . . . .	207
Rule< Array_Type, Data_Type > . . . . .	208
Rules< Array_Type, Data_Type > . . . . .	211
Rules< BArray< bool, bool >, bool > . . . . .	211
Rules< BArray<>, bool > . . . . .	211
StatsCounter< Array_Type, Data_Type > . . . . .	215
StatsCounter< BArray<>, bool > . . . . .	215
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > . . . . .	219
Support< BArray<>, bool, bool, bool > . . . . .	219
vecHasher< T > . . . . .	229

## Chapter 4

# Class Index

### 4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">BArray&lt; Cell_Type, Data_Type &gt;</a>	
Baseline class for binary arrays	43
<a href="#">BArrayCell&lt; Cell_Type, Data_Type &gt;</a>	57
<a href="#">BArrayCell_const&lt; Cell_Type, Data_Type &gt;</a>	60
<a href="#">BArrayDense&lt; Cell_Type, Data_Type &gt;</a>	
Baseline class for binary arrays	62
<a href="#">BArrayDenseCell&lt; Cell_Type, Data_Type &gt;</a>	78
<a href="#">BArrayDenseCell_const&lt; Cell_Type, Data_Type &gt;</a>	82
<a href="#">BArrayDenseCol&lt; Cell_Type, Data_Type &gt;</a>	82
<a href="#">BArrayDenseCol_const&lt; Cell_Type, Data_Type &gt;</a>	84
<a href="#">BArrayDenseRow&lt; Cell_Type, Data_Type &gt;</a>	86
<a href="#">BArrayDenseRow_const&lt; Cell_Type, Data_Type &gt;</a>	89
<a href="#">BArrayRow&lt; Cell_Type, Data_Type &gt;</a>	91
<a href="#">BArrayRow_const&lt; Cell_Type, Data_Type &gt;</a>	93
<a href="#">BArrayVector&lt; Cell_Type, Data_Type &gt;</a>	
Row or column of a <a href="#">BArray</a>	95
<a href="#">BArrayVector_const&lt; Cell_Type, Data_Type &gt;</a>	99
<a href="#">Cell&lt; Cell_Type &gt;</a>	
Entries in <a href="#">BArray</a> . For now, it only has two members:	103
<a href="#">Cell_const&lt; Cell_Type &gt;</a>	108
<a href="#">ConstBArrayRowIter&lt; Cell_Type, Data_Type &gt;</a>	108
<a href="#">Counter&lt; Array_Type, Data_Type &gt;</a>	
A counter function based on change statistics	110
<a href="#">Counters&lt; Array_Type, Data_Type &gt;</a>	
Vector of counters	116
<a href="#">DEFM</a>	121
<a href="#">DEFMCounterData</a>	
Data class used to store arbitrary uint or double vectors	125
<a href="#">DEFMData</a>	128
<a href="#">DEFMRuleData</a>	132
<a href="#">DEFMRuleDynData</a>	135
<a href="#">Entries&lt; Cell_Type &gt;</a>	
A wrapper class to store <code>source</code> , <code>target</code> , <code>val</code> from a <a href="#">BArray</a> object	136
<a href="#">Flock</a>	
A <a href="#">Flock</a> is a group of <a href="#">Geese</a>	139

<a href="#">FreqTable&lt; T &gt;</a>	
Frequency table of vectors	145
<a href="#">Geese</a>	
Annotated Phylo <a href="#">Model</a>	149
<a href="#">Model&lt; Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type &gt;</a>	
General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:	162
<a href="#">NetCounterData</a>	
Data class used to store arbitrary uint or double vectors	184
<a href="#">NetworkData</a>	
Data class for Networks	185
<a href="#">Node</a>	
A single node for the model	188
<a href="#">NodeData</a>	
Data definition for the <a href="#">PhyloArray</a> class	194
<a href="#">PhyloCounterData</a>	195
<a href="#">PhyloRuleDynData</a>	198
<a href="#">PowerSet&lt; Array_Type, Data_Rule_Type &gt;</a>	
Powerset of a binary array	200
<a href="#">Progress</a>	
A simple progress bar	207
<a href="#">Rule&lt; Array_Type, Data_Type &gt;</a>	
Rule for determining if a cell should be included in a sequence	208
<a href="#">Rules&lt; Array_Type, Data_Type &gt;</a>	
Vector of objects of class <a href="#">Rule</a>	211
<a href="#">StatsCounter&lt; Array_Type, Data_Type &gt;</a>	
Count stats for a single Array	215
<a href="#">Support&lt; Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type &gt;</a>	
Compute the support of sufficient statistics	219
<a href="#">vecHasher&lt; T &gt;</a>	229

## Chapter 5

# File Index

### 5.1 File List

Here is a list of all files with brief descriptions:

include/barry/barray-bones.hpp	231
include/barry/barray-iterator.hpp	231
include/barry/barray-meat-operators.hpp	232
include/barry/barray-meat.hpp	236
include/barry/barraycell-bones.hpp	254
include/barry/barraycell-meat.hpp	254
include/barry/barraydense-bones.hpp	255
include/barry/barraydense-meat-operators.hpp	255
include/barry/barraydense-meat.hpp	258
include/barry/barraydensecell-bones.hpp	279
include/barry/barraydensecell-meat.hpp	280
include/barry/barraydensecol-bones.hpp	280
include/barry/barraydenserow-bones.hpp	282
include/barry/barrayrow-bones.hpp	283
include/barry/barrayrow-meat.hpp	283
include/barry/barrayvector-bones.hpp	285
include/barry/barrayvector-meat.hpp	286
include/barry/barray-configuration.hpp	286
include/barry/barray-debug.hpp	288
include/barry/barray-macros.hpp	289
include/barry/barray.hpp	290
include/barry/cell-bones.hpp	293
include/barry/cell-meat.hpp	294
include/barry/col-bones.hpp	294
include/barry/counters-bones.hpp	294
include/barry/counters-meat.hpp	295
include/barry/freqtable.hpp	335
include/barry/model-bones.hpp	336
include/barry/model-meat.hpp	336
include/barry/powerset-bones.hpp	365
include/barry/powerset-meat.hpp	365
include/barry/progress.hpp	366
include/barry/rules-bones.hpp	367
include/barry/rules-meat.hpp	368
include/barry/statscounter-bones.hpp	368

include/barry/statscounter-meat.hpp	369
include/barry/support-bones.hpp	374
include/barry/support-meat.hpp	375
include/barry/typedefs.hpp	386
include/barry/counters/defm-formula.hpp	307
include/barry/counters/defm.hpp	309
include/barry/counters/network-css.hpp	312
include/barry/counters/network.hpp	320
include/barry/counters/phylo.hpp	327
include/barry/models/defm.hpp	312
include/barry/models/geese.hpp	356
include/barry/models/defm/defm-bones.hpp	354
include/barry/models/defm/defm-meat.hpp	355
include/barry/models/geese/flock-bones.hpp	357
include/barry/models/geese/flock-meat.hpp	357
include/barry/models/geese/geese-bones.hpp	358
include/barry/models/geese/geese-meat-constructors.hpp	360
include/barry/models/geese/geese-meat-likelihood.hpp	360
include/barry/models/geese/geese-meat-likelihood_exhaust.hpp	361
include/barry/models/geese/geese-meat-predict.hpp	362
include/barry/models/geese/geese-meat-predict_exhaust.hpp	362
include/barry/models/geese/geese-meat-predict_sim.hpp	363
include/barry/models/geese/geese-meat-simulate.hpp	363
include/barry/models/geese/geese-meat.hpp	364
include/barry/models/geese/geese-node-bones.hpp	364

## Chapter 6

# Module Documentation

### 6.1 Counting

#### Classes

- class [NetworkData](#)  
*Data class for Networks.*
- class [NodeData](#)  
*Data definition for the `PhyloArray` class.*
- class [Counter](#)< [Array\\_Type](#), [Data\\_Type](#) >  
*A counter function based on change statistics.*

#### 6.1.1 Detailed Description

`barry` includes a flexible way to generate counters based on change statistics. Since most of the time we are counting many motifs in a graph, change statistics make a reasonable (and efficient) way to make such counts.

In particular, let the motif be defined as  $s(y)$ , with  $y$  as the binary array. The change statistic when adding cell  $y_{ij}$ , i.e. when the cell moves from being empty to have a one, is defined as

$$\delta(y_{ij}) = s_{ij}^+(y) - s_{ij}^-(y),$$

where  $s_{ij}^+(y)$  and  $s_{ij}^-(y)$  represent the motif statistic with and without the  $ij$ -cell. For example, in the case of networks, the change statistic for the number of edges is always 1.

To count statistics in an array, the [\[Counter\]](#) class will empty the array, initialize the counters, and then start counting while adding at each step a single cell, until matching the original array.

### 6.2 Statistical Models

Statistical models available in `barry`.

## Classes

- class [Model](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) >  
*General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:*
- class [Flock](#)  
*A [Flock](#) is a group of [Geese](#).*
- class [Geese](#)  
*Annotated Phylo [Model](#).*

### 6.2.1 Detailed Description

Statistical models available in `barry`.

## 6.3 Phylo rules

[Rules](#) for phylogenetic modeling.

## Classes

- class [DEFMRuleDynData](#)
- class [PhyloRuleDynData](#)

## Macros

- `#define MAKE\_DEFM\_HASHER(hasher, a, cov)`
- `#define DEFM\_RULEDYN\_LAMBDA(a)`

## Functions

- void [rule\\_dyn\\_limit\\_changes](#) ([PhyloSupport](#) \*support, [uint](#) pos, [uint](#) lb, [uint](#) ub, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Overall functional gains.*
- double [DEFMData::operator\(\)](#) (size\_t i, size\_t j) const  
*Access to the row (i) colum (j) data.*
- size\_t [DEFMData::ncol](#) () const
- size\_t [DEFMData::nrow](#) () const
- void [DEFMData::print](#) () const

### Convenient typedefs for network objects.

- typedef [Counter](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMCounter](#)
- typedef [Counters](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMCounters](#)
- typedef [Support](#)< [DEFMArray](#), [DEFMCounterData](#), [DEFMRuleData](#), [DEFMRuleDynData](#) > [DEFMSupport](#)
- typedef [StatsCounter](#)< [DEFMArray](#), [DEFMCounterData](#) > [DEFMStatsCounter](#)
- typedef [Model](#)< [DEFMArray](#), [DEFMCounterData](#), [DEFMRuleData](#), [DEFMRuleDynData](#) > [DEFMModel](#)
- typedef [Rule](#)< [DEFMArray](#), [DEFMRuleData](#) > [DEFMRule](#)
- typedef [Rules](#)< [DEFMArray](#), [DEFMRuleData](#) > [DEFMRules](#)
- typedef [Rule](#)< [DEFMArray](#), [DEFMRuleDynData](#) > [DEFMRuleDyn](#)
- typedef [Rules](#)< [DEFMArray](#), [DEFMRuleDynData](#) > [DEFMRulesDyn](#)



## Macros for defining counters

- `#define DEFM_COUNTER(a) inline double (a) (const DEFMArr & Array, uint i, uint j, DEFMCOUNTERData & data)`
- `#define DEFM_COUNTER_LAMBDA(a)`

## Macros for defining rules

- `#define DEFM_RULE(a) inline bool (a) (const DEFMArr & Array, uint i, uint j, bool & data)`
- `#define DEFM_RULE_LAMBDA(a)`

### 6.3.1 Detailed Description

[Rules](#) for phylogenetic modeling.

#### Parameters

<i>rules</i>	A pointer to a <code>PhyloRules</code> object ( <code>Rules&lt;PhyloArray, PhyloRuleData&gt;</code> ).
--------------	--

### 6.3.2 Macro Definition Documentation

#### 6.3.2.1 DEFM\_COUNTER

```
#define DEFM_COUNTER(  
    a ) inline double (a) (const DEFMArr & Array, uint i, uint j, DEFMCOUNTERData  
& data)
```

Function for definition of a network counter function

Definition at line 212 of file `defm.hpp`.

#### 6.3.2.2 DEFM\_COUNTER\_LAMBDA

```
#define DEFM_COUNTER_LAMBDA(  
    a )
```

#### Value:

```
Counter_fun_type<DEFMArr, DEFMCOUNTERData> a = \  
[] (const DEFMArr & Array, uint i, uint j, DEFMCOUNTERData & data) -> double
```

Lambda function for definition of a network counter function

Definition at line 216 of file `defm.hpp`.

### 6.3.2.3 DEFM\_RULE

```
#define DEFM_RULE(  
    a ) inline bool (a) (const DEFMArray & Array, uint i, uint j, bool & data)
```

Function for definition of a network counter function

Definition at line 226 of file defm.hpp.

### 6.3.2.4 DEFM\_RULE\_LAMBDA

```
#define DEFM_RULE_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<DEFMArray, DEFMRuleData> a = \  
[] (const DEFMArray & Array, uint i, uint j, DEFMRuleData & data) -> bool
```

Lambda function for definition of a network counter function

Definition at line 230 of file defm.hpp.

### 6.3.2.5 DEFM\_RULEDYN\_LAMBDA

```
#define DEFM_RULEDYN_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<DEFMArray, DEFMRuleDynData> a = \  
[] (const DEFMArray & Array, uint i, uint j, DEFMRuleDynData & data) -> bool
```

Lambda function for definition of a network counter function

Definition at line 236 of file defm.hpp.

### 6.3.2.6 MAKE\_DEFM\_HASHER

```
#define MAKE_DEFM_HASHER(  
    hasher,  
    a,  
    cov )
```

**Value:**

```
Hasher_fun_type<DEFMArray,DEFMCounterData> hasher = [cov] (const DEFMArray & array,  
DEFMCounterData * d) { \  
    std::vector< double > res; \  
    /* Adding the column feature */ \  
    for (size_t i = 0u; i < array.nrow(); ++i) \  
        res.push_back(array.D()(i, cov)); \  
    /* Adding the fixed dims */ \  
    for (size_t i = 0u; i < (array.nrow() - 1); ++i) \  
        for (size_t j = 0u; j < array.ncol(); ++j) \  
            res.push_back(array(i, j)); \  
    return res; \  
};
```

Definition at line 195 of file defm.hpp.

### 6.3.3 Typedef Documentation

#### 6.3.3.1 DEFMCOUNTER

```
typedef Counter<DEFMArray, DEFMCOUNTERData > DEFMCOUNTER
```

Definition at line 152 of file defm.hpp.

#### 6.3.3.2 DEFMCOUNTERS

```
typedef Counters<DEFMArray, DEFMCOUNTERData> DEFMCOUNTERS
```

Definition at line 153 of file defm.hpp.

#### 6.3.3.3 DEFMMODEL

```
typedef Model<DEFMArray, DEFMCOUNTERData,DEFMRULEData,DEFMRULEDynData> DEFMMODEL
```

Definition at line 156 of file defm.hpp.

#### 6.3.3.4 DEFMRULE

```
typedef Rule<DEFMArray, DEFMRULEData> DEFMRULE
```

Definition at line 159 of file defm.hpp.

#### 6.3.3.5 DEFMRULEDYN

```
typedef Rule<DEFMArray, DEFMRULEDynData> DEFMRULEDYN
```

Definition at line 161 of file defm.hpp.

#### 6.3.3.6 DEFMRules

```
typedef Rules<DEFMArray, DEFMRuleData> DEFMRules
```

Definition at line 160 of file defm.hpp.

#### 6.3.3.7 DEFMRulesDyn

```
typedef Rules<DEFMArray, DEFMRuleDynData> DEFMRulesDyn
```

Definition at line 162 of file defm.hpp.

#### 6.3.3.8 DEFMStatsCounter

```
typedef StatsCounter<DEFMArray, DEFMCounterData> DEFMStatsCounter
```

Definition at line 155 of file defm.hpp.

#### 6.3.3.9 DEFMSupport

```
typedef Support<DEFMArray, DEFMCounterData, DEFMRuleData,DEFMRuleDynData> DEFMSupport
```

Definition at line 154 of file defm.hpp.

### 6.3.4 Function Documentation

#### 6.3.4.1 ncol()

```
size_t DEFMData::ncol ( ) const [inline]
```

Definition at line 173 of file defm.hpp.

#### 6.3.4.2 nrow()

```
size_t DEFMData::nrow ( ) const [inline]
```

Definition at line 177 of file defm.hpp.

#### 6.3.4.3 operator()(i)

```
double DEFMData::operator() (
    size_t i,
    size_t j ) const [inline]
```

Access to the row (i) column (j) data.

## Parameters

<i>i</i>	
<i>j</i>	

## Returns

double

Definition at line 168 of file defm.hpp.

**6.3.4.4 print()**

```
void DEFMDData::print ( ) const [inline]
```

Definition at line 181 of file defm.hpp.

**6.3.4.5 rule\_dyn\_limit\_changes()**

```
void rule_dyn_limit_changes (
    PhyloSupport * support,
    uint pos,
    uint lb,
    uint ub,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional gains.

## Parameters

<i>support</i>	<a href="#">Support</a> of a model.
<i>pos</i>	Position of the focal statistic.
<i>lb</i>	Lower bound
<i>ub</i>	Upper bound

## Returns

(void) adds a rule limiting the support of the model.

Definition at line 2177 of file phylo.hpp.

**6.4 DEFMArray counters**[Counters](#) for network models.

## Functions

- void `counter_ones` (`DEFMCounters` \*counters, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr)
 

*Prevalence of ones.*
- void `counter_logit_intercept` (`DEFMCounters` \*counters, size\_t n\_y, std::vector< size\_t > which={}, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)
 

*Prevalence of ones.*
- void `counter_transition` (`DEFMCounters` \*counters, std::vector< size\_t > coords, std::vector< bool > signs, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)
 

*Prevalence of ones.*
- void `counter_transition_formula` (`DEFMCounters` \*counters, std::string formula, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)
 

*Prevalence of ones.*
- void `counter_fixed_effect` (`DEFMCounters` \*counters, int covar\_index, double k, std::string vname="", const std::vector< std::string > \*x\_names=nullptr)
 

*Prevalence of ones.*
- template<typename Tnet = Network>
 void `counter_edges` (`NetCounters`< Tnet > \*counters)
 

*Number of edges.*
- template<typename Tnet = Network>
 void `counter_isolates` (`NetCounters`< Tnet > \*counters)
 

*Number of isolated vertices.*
- template<> void `counter_isolates` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_mutual` (`NetCounters`< Tnet > \*counters)
 

*Number of mutual ties.*
- template<typename Tnet = Network>
 void `counter_istar2` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_istar2` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_ostar2` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_ostar2` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_ttriads` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_ttriads` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_ctriads` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_ctriads` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_density` (`NetCounters`< Tnet > \*counters)
- template<typename Tnet = Network>
 void `counter_idegree15` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_idegree15` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_odegree15` (`NetCounters`< Tnet > \*counters)
- template<> void `counter_odegree15` (`NetCounters`< `NetworkDense` > \*counters)
- template<typename Tnet = Network>
 void `counter_absdiff` (`NetCounters`< Tnet > \*counters, uint attr\_id, double alpha=1.0)
 

*Sum of absolute attribute difference between ego and alter.*
- template<typename Tnet = Network>
 void `counter_diff` (`NetCounters`< Tnet > \*counters, uint attr\_id, double alpha=1.0, double tail\_head=true)
 

*Sum of attribute difference between ego and alter to pow(alpha)*

- [NETWORK\\_COUNTER](#) (init\_single\_attr)
- `template<typename Tnet = Network>`  
`void counter_nodeicov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodeocov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodecov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodematch (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_iddegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given in-degree.*
- `template<> void counter_iddegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_degree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*

## Returns true if the cell is free

### Parameters

<i>rules</i>	A pointer to a DEFMRules object ( <a href="#">Rules</a> <DEFMArray, bool>).
--------------	---

- `void rules_markov_fixed (DEFMRules *rules, size_t markov_order)`  
*Number of edges.*
- `void rules_dont_become_zero (DEFMSupport *support, std::vector< size_t > ids)`  
*Blocks switching a one to zero.*

## 6.4.1 Detailed Description

[Counters](#) for network models.

### Parameters

<i>counters</i>	A pointer to a DEFMCounters object ( <a href="#">Counters</a> <DEFMArray, DEFMCOUNTERData>).
<i>counters</i>	A pointer to a NetCounters object ( <a href="#">Counters</a> <Network, NetCounterData>).

## 6.4.2 Function Documentation

#### 6.4.2.1 counter\_absdiff()

```
template<typename Tnet = Network>
void counter_absdiff (
    NetCounters< Tnet > * counters,
    uint attr_id,
    double alpha = 1.0 ) [inline]
```

Sum of absolute attribute difference between ego and alter.

Definition at line 910 of file network.hpp.

#### 6.4.2.2 counter\_ctriads() [1/2]

```
template<>
void counter_ctriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 665 of file network.hpp.

#### 6.4.2.3 counter\_ctriads() [2/2]

```
template<typename Tnet = Network>
void counter_ctriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 610 of file network.hpp.

#### 6.4.2.4 counter\_degree()

```
template<typename Tnet = Network>
void counter_degree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1328 of file network.hpp.



#### 6.4.2.5 counter\_density()

```
template<typename Tnet = Network>
void counter_density (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 731 of file network.hpp.

#### 6.4.2.6 counter\_diff()

```
template<typename Tnet = Network>
void counter_diff (
    NetCounters< Tnet > * counters,
    uint attr_id,
    double alpha = 1.0,
    double tail_head = true ) [inline]
```

Sum of attribute difference between ego and alter to pow(alpha)

Definition at line 955 of file network.hpp.

#### 6.4.2.7 counter\_edges()

```
template<typename Tnet = Network>
void counter_edges (
    NetCounters< Tnet > * counters ) [inline]
```

Number of edges.

Definition at line 152 of file network.hpp.

#### 6.4.2.8 counter\_fixed\_effect()

```
void counter_fixed_effect (
    DEFMArrays * counters,
    int covar_index,
    double k,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr ) [inline]
```

Prevalence of ones.

##### Parameters

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 780 of file defm.hpp.

#### 6.4.2.9 counter\_iddegree() [1/2]

```
template<>
void counter_iddegree (
    NetCounters< NetworkDense > * counters,
    std::vector< uint > d ) [inline]
```

Definition at line 1172 of file network.hpp.

#### 6.4.2.10 counter\_iddegree() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given in-degree.

Definition at line 1125 of file network.hpp.

#### 6.4.2.11 counter\_iddegree15() [1/2]

```
template<>
void counter_iddegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 787 of file network.hpp.

#### 6.4.2.12 counter\_iddegree15() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 759 of file network.hpp.

**6.4.2.13 counter\_isolates() [1/2]**

```
template<>
void counter_isolates (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 215 of file network.hpp.

**6.4.2.14 counter\_isolates() [2/2]**

```
template<typename Tnet = Network>
void counter_isolates (
    NetCounters< Tnet > * counters ) [inline]
```

Number of isolated vertices.

Definition at line 175 of file network.hpp.

**6.4.2.15 counter\_istar2() [1/2]**

```
template<>
void counter_istar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 338 of file network.hpp.

**6.4.2.16 counter\_istar2() [2/2]**

```
template<typename Tnet = Network>
void counter_istar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 312 of file network.hpp.

**6.4.2.17 counter\_logit\_intercept()**

```
void counter_logit_intercept (
    DEFMArrays * counters,
    size_t n_y,
    std::vector< size_t > which = {},
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Definition at line 321 of file defm.hpp.

#### 6.4.2.18 counter\_mutual()

```
template<typename Tnet = Network>
void counter_mutual (
    NetCounters< Tnet > * counters ) [inline]
```

Number of mutual ties.

Definition at line 256 of file network.hpp.

#### 6.4.2.19 counter\_nodecov()

```
template<typename Tnet = Network>
void counter_nodecov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1068 of file network.hpp.

#### 6.4.2.20 counter\_nodeicov()

```
template<typename Tnet = Network>
void counter_nodeicov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1018 of file network.hpp.

#### 6.4.2.21 counter\_nodematch()

```
template<typename Tnet = Network>
void counter_nodematch (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1093 of file network.hpp.

#### 6.4.2.22 counter\_nodeocov()

```
template<typename Tnet = Network>
void counter_nodeocov (
    NetCounters< Tnet > * counters,
    uint attr_id ) [inline]
```

Definition at line 1043 of file network.hpp.

**6.4.2.23 counter\_odegree()** [1/2]

```
template<>
void counter_odegree (
    NetCounters< NetworkDense > * counters,
    std::vector< uint > d ) [inline]
```

Definition at line 1273 of file network.hpp.

**6.4.2.24 counter\_odegree()** [2/2]

```
template<typename Tnet = Network>
void counter_odegree (
    NetCounters< Tnet > * counters,
    std::vector< uint > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1225 of file network.hpp.

**6.4.2.25 counter\_odegree15()** [1/2]

```
template<>
void counter_odegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 864 of file network.hpp.

**6.4.2.26 counter\_odegree15()** [2/2]

```
template<typename Tnet = Network>
void counter_odegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 836 of file network.hpp.

**6.4.2.27 counter\_ones()**

```
void counter_ones (
    DEFMArrays * counters,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr ) [inline]
```

Prevalence of ones.

**Parameters**

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If $\geq$ than 0, then the interaction

Definition at line 254 of file defm.hpp.

**6.4.2.28 counter\_ostar2() [1/2]**

```
template<>
void counter_ostar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 404 of file network.hpp.

**6.4.2.29 counter\_ostar2() [2/2]**

```
template<typename Tnet = Network>
void counter_ostar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 376 of file network.hpp.

**6.4.2.30 counter\_transition()**

```
void counter_transition (
    DEFMCounters * counters,
    std::vector< size_t > coords,
    std::vector< bool > signs,
    size_t m_order,
    size_t n_y,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Prevalence of ones.

**Parameters**

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If $\geq$ than 0, then the interaction

Definition at line 440 of file defm.hpp.

**6.4.2.31 counter\_transition\_formula()**

```
void counter_transition_formula (
    DEFMCounters * counters,
    std::string formula,
    size_t m_order,
    size_t n_y,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Prevalence of ones.

**Parameters**

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 749 of file defm.hpp.

**6.4.2.32 counter\_ttriads() [1/2]**

```
template<>
void counter_ttriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 531 of file network.hpp.

**6.4.2.33 counter\_ttriads() [2/2]**

```
template<typename Tnet = Network>
void counter_ttriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 441 of file network.hpp.

**6.4.2.34 NETWORK\_COUNTER()**

```
NETWORK_COUNTER (
    init_single_attr )
```

Definition at line 999 of file network.hpp.

#### 6.4.2.35 rules\_dont\_become\_zero()

```
void rules_dont_become_zero (
    DEFMSupport * support,
    std::vector< size_t > ids ) [inline]
```

Blocks switching a one to zero.

##### Parameters

<i>rules</i>	
<i>ids</i>	Ids of the variables that will follow this rule.

Definition at line 848 of file defm.hpp.

#### 6.4.2.36 rules\_markov\_fixed()

```
void rules_markov_fixed (
    DEFMRules * rules,
    size_t markov_order ) [inline]
```

Number of edges.

Definition at line 823 of file defm.hpp.

## 6.5 Phylo counters

[Counters](#) for phylogenetic modeling.

### Functions

- void [counter\\_overall\\_gains](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Overall functional gains.*
- void [counter\\_gains](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Functional gains for a specific function (nfun).*
- void [counter\\_gains\\_k\\_offspring](#) ([PhyloCounters](#) \*counters, std::vector< [uint](#) > nfun, [uint](#) k=1u, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*k genes gain function nfun*
- void [counter\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- void [counter\\_preserve\\_pseudogene](#) ([PhyloCounters](#) \*counters, unsigned int nfunA, unsigned int nfunB, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many pairs of genes preserve pseudostate.*
- void [counter\\_prop\\_genes\\_changing](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- void [counter\\_overall\\_loss](#) ([PhyloCounters](#) \*counters, unsigned int duplication=[DEFAULT\\_DUPLICATION](#))  
*Overall functional loss.*



- void `counter_maxfuns` (`PhyloCounters *counters`, `uint lb`, `uint ub`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Cap the number of functions per gene.*
- void `counter_loss` (`PhyloCounters *counters`, `std::vector< uint > nfun`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total count of losses for an specific function.*
- void `counter_overall_changes` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of changes. Use this statistic to account for "preservation".*
- void `counter_subfun` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total count of Sub-functionalization events.*
- void `counter_cogain` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Co-evolution (joint gain or loss)*
- void `counter_longest` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Longest branch mutates (either by gain or by loss)*
- void `counter_neofun` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events.*
- void `counter_pairwise_neofun_singlefun` (`PhyloCounters *counters`, `uint nfunA`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events  $\sum_u \sum_{w < u} [x(u,a)*(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$  change  
stat:  $\Delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void `counter_neofun_a2b` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Total number of neofunctionalization events.*
- void `counter_co_opt` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Function co-opting.*
- void `counter_k_genes_changing` (`PhyloCounters *counters`, unsigned int `k`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Indicator function. Equals to one if  $k$  genes changed and zero otherwise.*
- void `counter_less_than_p_prop_genes_changing` (`PhyloCounters *counters`, double `p`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Indicator function. Equals to one if  $k$  genes changed and zero otherwise.*
- void `counter_gains_from_0` (`PhyloCounters *counters`, `std::vector< uint > nfun`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_overall_gains_from_0` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_overall_change` (`PhyloCounters *counters`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_preserving` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*
- void `counter_pairwise_first_gain` (`PhyloCounters *counters`, `uint nfunA`, `uint nfunB`, unsigned int duplication=`DEFAULT_DUPLICATION`)  
*Used when all the functions are in 0 (like the root node prob.)*

### 6.5.1 Detailed Description

`Counters` for phylogenetic modeling.

Parameters

<code>counters</code>	A pointer to a <code>PhyloCounters</code> object ( <code>Counters&lt;PhyloArray, PhyloCounterData&gt;</code> ).
-----------------------	---

## 6.5.2 Function Documentation

### 6.5.2.1 counter\_co\_opt()

```
void counter_co_opt (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Function co-opting.

Function co-opting of functions A and B happens when, for example, function B is gained as a new featured leveraging what function A already does; without losing function A. The sufficient statistic is defined as follows:

$$x_{pa}(1 - x_{pb}) \sum_{i < j} \left[ x_{ia}^p (1 - x_{ib}^p) x_{ja}^p x_{jb}^p + x_{ja}^p (1 - x_{jb}^p) x_{ia}^p x_{ib}^p \right]$$

This algorithm implements the change statistic.

Definition at line 1393 of file phylo.hpp.

### 6.5.2.2 counter\_cogain()

```
void counter_cogain (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Co-evolution (joint gain or loss)

Needs to specify pairs of functions (nfunA, nfunB).

Definition at line 888 of file phylo.hpp.

### 6.5.2.3 counter\_gains()

```
void counter_gains (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Functional gains for a specific function (nfun).

Definition at line 193 of file phylo.hpp.

#### 6.5.2.4 counter\_gains\_from\_0()

```
void counter_gains_from_0 (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1727 of file phylo.hpp.

#### 6.5.2.5 counter\_gains\_k\_offspring()

```
void counter_gains_k_offspring (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    uint k = 1u,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

k genes gain function nfun

Definition at line 253 of file phylo.hpp.

#### 6.5.2.6 counter\_genes\_changing()

```
void counter_genes_changing (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 325 of file phylo.hpp.

#### 6.5.2.7 counter\_k\_genes\_changing()

```
void counter_k_genes_changing (
    PhyloCounters * counters,
    unsigned int k,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Indicator function. Equals to one if  $k$  genes changed and zero otherwise.

Definition at line 1491 of file phylo.hpp.

#### 6.5.2.8 counter\_less\_than\_p\_prop\_genes\_changing()

```
void counter_less_than_p_prop_genes_changing (
    PhyloCounters * counters,
    double p,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Indicator function. Equals to one if  $k$  genes changed and zero otherwise.

< How many genes diverge the parent

Definition at line 1611 of file phylo.hpp.

#### 6.5.2.9 counter\_longest()

```
void counter_longest (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Longest branch mutates (either by gain or by loss)

Definition at line 945 of file phylo.hpp.

#### 6.5.2.10 counter\_loss()

```
void counter_loss (
    PhyloCounters * counters,
    std::vector< uint > nfun,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total count of losses for an specific function.

Definition at line 688 of file phylo.hpp.

#### 6.5.2.11 counter\_maxfuns()

```
void counter_maxfuns (
    PhyloCounters * counters,
    uint lb,
    uint ub,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Cap the number of functions per gene.

Definition at line 626 of file phylo.hpp.

#### 6.5.2.12 counter\_neofun()

```
void counter_neofun (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1115 of file phylo.hpp.

#### 6.5.2.13 counter\_neofun\_a2b()

```
void counter_neofun_a2b (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1260 of file phylo.hpp.

#### 6.5.2.14 counter\_overall\_changes()

```
void counter_overall_changes (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of changes. Use this statistic to account for "preservation".

Definition at line 740 of file phylo.hpp.

#### 6.5.2.15 counter\_overall\_gains()

```
void counter_overall_gains (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional gains.

Total number of gains (irrespective of the function).

Definition at line 155 of file phylo.hpp.

#### 6.5.2.16 counter\_overall\_gains\_from\_0()

```
void counter_overall_gains_from_0 (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1793 of file phylo.hpp.

#### 6.5.2.17 counter\_overall\_loss()

```
void counter_overall_loss (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Overall functional loss.

Definition at line 578 of file phylo.hpp.

#### 6.5.2.18 counter\_pairwise\_first\_gain()

```
void counter_pairwise_first_gain (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.  $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 2045 of file phylo.hpp.

#### 6.5.2.19 counter\_pairwise\_neofun\_singlefun()

```
void counter_pairwise_neofun_singlefun (
    PhyloCounters * counters,
    uint nfunA,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total number of neofunctionalization events  $\sum_u \sum_{w < u} [x(u,a)*(1-x(w,a)) + (1-x(u,a)) * x(w,a)]$  change stat:  $\Delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$

Definition at line 1196 of file phylo.hpp.

**6.5.2.20 counter\_pairwise\_overall\_change()**

```
void counter_pairwise_overall_change (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1841 of file phylo.hpp.

**6.5.2.21 counter\_pairwise\_preserving()**

```
void counter_pairwise_preserving (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.  $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1906 of file phylo.hpp.

**6.5.2.22 counter\_preserve\_pseudogene()**

```
void counter_preserve_pseudogene (
    PhyloCounters * counters,
    unsigned int nfunA,
    unsigned int nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many pairs of genes preserve pseudostate.

Definition at line 394 of file phylo.hpp.

**6.5.2.23 counter\_prop\_genes\_changing()**

```
void counter_prop_genes_changing (
    PhyloCounters * counters,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 476 of file phylo.hpp.

#### 6.5.2.24 counter\_subfun()

```
void counter_subfun (
    PhyloCounters * counters,
    uint nfunA,
    uint nfunB,
    unsigned int duplication = DEFAULT_DUPLICATION ) [inline]
```

Total count of Sub-functionalization events.

It requires to specify data = {funA, funB}

Definition at line 799 of file phylo.hpp.



## Chapter 7

# Namespace Documentation

### 7.1 `barry` Namespace Reference

`barry`: Your go-to motif accountant

#### Namespaces

- [counters](#)

*Tree class and Treeliterator class.*

#### 7.1.1 Detailed Description

`barry`: Your go-to motif accountant

### 7.2 `barry::counters` Namespace Reference

Tree class and Treeliterator class.

#### Namespaces

- [defm](#)
- [network](#)
- [phylo](#)

#### 7.2.1 Detailed Description

Tree class and Treeliterator class.

### 7.3 `barry::counters::defm` Namespace Reference

### 7.4 `barry::counters::network` Namespace Reference

### 7.5 `barry::counters::phylo` Namespace Reference

### 7.6 `CHECK` Namespace Reference

Integer constants used to specify which cell should be check.

#### Variables

- `const int BOTH` = -1
- `const int NONE` = 0
- `const int ONE` = 1
- `const int TWO` = 2

#### 7.6.1 Detailed Description

Integer constants used to specify which cell should be check.

#### 7.6.2 Variable Documentation

##### 7.6.2.1 `BOTH`

```
const int CHECK::BOTH = -1
```

Definition at line 28 of file typedefs.hpp.

##### 7.6.2.2 `NONE`

```
const int CHECK::NONE = 0
```

Definition at line 29 of file typedefs.hpp.

### 7.6.2.3 ONE

```
const int CHECK::ONE = 1
```

Definition at line 30 of file typedefs.hpp.

### 7.6.2.4 TWO

```
const int CHECK::TWO = 2
```

Definition at line 31 of file typedefs.hpp.

## 7.7 EXISTS Namespace Reference

Integer constants used to specify which cell should be check to exist or not.

### Variables

- `const int BOTH = -1`
- `const int NONE = 0`
- `const int ONE = 1`
- `const int TWO = 1`
- `const int UNKNOWN = -1`
- `const int AS_ZERO = 0`
- `const int AS_ONE = 1`

### 7.7.1 Detailed Description

Integer constants used to specify which cell should be check to exist or not.

### 7.7.2 Variable Documentation

#### 7.7.2.1 AS\_ONE

```
const int EXISTS::AS_ONE = 1
```

Definition at line 46 of file typedefs.hpp.

### 7.7.2.2 AS\_ZERO

```
const int EXISTS::AS_ZERO = 0
```

Definition at line 45 of file typedefs.hpp.

### 7.7.2.3 BOTH

```
const int EXISTS::BOTH = -1
```

Definition at line 39 of file typedefs.hpp.

### 7.7.2.4 NONE

```
const int EXISTS::NONE = 0
```

Definition at line 40 of file typedefs.hpp.

### 7.7.2.5 ONE

```
const int EXISTS::ONE = 1
```

Definition at line 41 of file typedefs.hpp.

### 7.7.2.6 TWO

```
const int EXISTS::TWO = 1
```

Definition at line 42 of file typedefs.hpp.

### 7.7.2.7 UNKNOWN

```
const int EXISTS::UNKNOWN = -1
```

Definition at line 44 of file typedefs.hpp.

## Chapter 8

# Class Documentation

### 8.1 BArray< Cell\_Type, Data\_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barray-bones.hpp>
```

#### Public Member Functions

- bool `operator==` (const BArray< Cell\_Type, Data\_Type > &Array\_)
- ~BArray ()
- void `out_of_range` (uint i, uint j) const
- Cell\_Type `get_cell` (uint i, uint j, bool check\_bounds=true) const
- std::vector< Cell\_Type > `get_col_vec` (uint i, bool check\_bounds=true) const
- std::vector< Cell\_Type > `get_row_vec` (uint i, bool check\_bounds=true) const
- void `get_col_vec` (std::vector< Cell\_Type > \*x, uint i, bool check\_bounds=true) const
- void `get_row_vec` (std::vector< Cell\_Type > \*x, uint i, bool check\_bounds=true) const
- const Row\_type< Cell\_Type > & `row` (uint i, bool check\_bounds=true) const
- const Col\_type< Cell\_Type > & `col` (uint i, bool check\_bounds=true) const
- Entries< Cell\_Type > `get_entries` () const

*Get the edgelist.*

- void `transpose` ()
- void `clear` (bool hard=true)
- void `resize` (uint N\_, uint M\_)
- void `reserve` ()
- void `print` (const char \*fmt=nullptr,...) const
- bool `is_dense` () const noexcept

#### Constructors

##### Parameters

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An unsigned int vector ranging from 0 to M_
target	When <code>true</code> tries to add repeated observations.

- **BArray** ()  
*Zero-size array.*
  - **BArray** (uint N\_, uint M\_)  
*Empty array.*
  - **BArray** (uint N\_, uint M\_, const std::vector< uint > &source, const std::vector< uint > &target, const std::vector< Cell\_Type > &value, bool add=true)  
*Edgelist with data.*
  - **BArray** (uint N\_, uint M\_, const std::vector< uint > &source, const std::vector< uint > &target, bool add=true)  
*Edgelist with no data (simpler)*
  - **BArray** (const BArray< Cell\_Type, Data\_Type > &Array\_, bool copy\_data=false)  
*Copy constructor.*
  - **BArray**< Cell\_Type, Data\_Type > & operator= (const BArray< Cell\_Type, Data\_Type > &Array\_)  
*Assignment constructor.*
  - **BArray** (BArray< Cell\_Type, Data\_Type > &&x) noexcept  
*Move operator.*
  - **BArray**< Cell\_Type, Data\_Type > & operator= (BArray< Cell\_Type, Data\_Type > &&x) noexcept  
*Move assignment.*
- 
- void **set\_data** (Data\_Type \*data\_, bool delete\_data\_=false)  
*Set the data object.*
  - Data\_Type \* **D\_ptr** ()
  - const Data\_Type \* **D\_ptr** () const
  - Data\_Type & **D** ()
  - const Data\_Type & **D** () const
  - void **flush\_data** ()

### Queries

*is\_empty* queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

#### Parameters

i,j	<i>Coordinates</i>
check_bounds	<i>If false avoids checking bounds.</i>

- bool **is\_empty** (uint i, uint j, bool check\_bounds=true) const
- uint **nrow** () const noexcept
- uint **ncol** () const noexcept
- uint **nnozero** () const noexcept
- Cell< Cell\_Type > **default\_val** () const

### Cell-wise insertion/deletion

#### Parameters

i,j	<i>Row,column</i>
check_bounds	<i>When true and out of range, the function throws an error.</i>
check_exists	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of swap_cells, check if either of both cells exists/don't exist.</i>

- `BArray< Cell_Type, Data_Type > & operator+= (const std::pair< uint, uint > &coords)`
- `BArray< Cell_Type, Data_Type > & operator-= (const std::pair< uint, uint > &coords)`
- `BArrayCell< Cell_Type, Data_Type > operator() (uint i, uint j, bool check_bounds=true)`
- `const Cell_Type operator() (uint i, uint j, bool check_bounds=true) const`
- `void rm_cell (uint i, uint j, bool check_bounds=true, bool check_exists=true)`
- `void insert_cell (uint i, uint j, const Cell< Cell_Type > &v, bool check_bounds, bool check_exists)`
- `void insert_cell (uint i, uint j, Cell< Cell_Type > &&v, bool check_bounds, bool check_exists)`
- `void insert_cell (uint i, uint j, Cell_Type v, bool check_bounds, bool check_exists)`
- `void swap_cells (uint i0, uint j0, uint i1, uint j1, bool check_bounds=true, int check_exists=CHECK::BOTH, int *report=nullptr)`
- `void toggle_cell (uint i, uint j, bool check_bounds=true, int check_exists=EXISTS::UNKNOWN)`
- `void toggle_lock (uint i, uint j, bool check_bounds=true)`

### Column/row wise interchange

- `void swap_rows (uint i0, uint i1, bool check_bounds=true)`
- `void swap_cols (uint j0, uint j1, bool check_bounds=true)`
- `void zero_row (uint i, bool check_bounds=true)`
- `void zero_col (uint j, bool check_bounds=true)`

### Arithmetic operators

- `BArray< Cell_Type, Data_Type > & operator+= (const BArray< Cell_Type, Data_Type > &rhs)`
- `BArray< Cell_Type, Data_Type > & operator+= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator-= (const BArray< Cell_Type, Data_Type > &rhs)`
- `BArray< Cell_Type, Data_Type > & operator-= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator/= (const Cell_Type &rhs)`
- `BArray< Cell_Type, Data_Type > & operator*= (const Cell_Type &rhs)`

### Public Attributes

- `bool visited = false`

### Friends

- `class BArrayCell< Cell_Type, Data_Type >`
- `class BArrayCell_const< Cell_Type, Data_Type >`

## 8.1.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArray< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

`BArray` class objects are arbitrary arrays in which non-empty cells hold data of type `Cell_Type`. The non-empty cells are stored by row and indexed using `unordered_maps`, i.e. `std::vector< std::unordered_map<unsigned int, Cell_Type> >`.

#### Template Parameters

<i>Cell_Type</i>	Type of cell (any type).
<i>Data_Type</i>	Data type of the array (bool default).

Definition at line 28 of file barray-bones.hpp.

## 8.1.2 Constructor & Destructor Documentation

### 8.1.2.1 BArray() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray ( ) [inline]
```

Zero-size array.

Definition at line 69 of file barray-bones.hpp.

### 8.1.2.2 BArray() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_ ) [inline]
```

Empty array.

Definition at line 72 of file barray-bones.hpp.

### 8.1.2.3 BArray() [3/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    const std::vector< Cell_Type > & value,
    bool add = true )
```

Edgelist with data.



#### 8.1.2.4 BArray() [4/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    bool add = true )
```

Edgelist with no data (simpler)

#### 8.1.2.5 BArray() [5/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    const BArray< Cell_Type, Data_Type > & Array_,
    bool copy_data = false )
```

Copy constructor.

#### 8.1.2.6 BArray() [6/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move operator.

#### 8.1.2.7 ~BArray()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::~~BArray ( )
```

### 8.1.3 Member Function Documentation

#### 8.1.3.1 clear()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::clear (
    bool hard = true )
```

### 8.1.3.2 col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Col_type< Cell_Type >& BArray< Cell_Type, Data_Type >::col (
    uint i,
    bool check_bounds = true ) const
```

### 8.1.3.3 D() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type& BArray< Cell_Type, Data_Type >::D ( )
```

### 8.1.3.4 D() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type& BArray< Cell_Type, Data_Type >::D ( ) const
```

### 8.1.3.5 D\_ptr() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( )
```

### 8.1.3.6 D\_ptr() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( ) const
```

### 8.1.3.7 default\_val()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell<Cell_Type> BArray< Cell_Type, Data_Type >::default_val ( ) const
```

### 8.1.3.8 flush\_data()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::flush_data ( )
```

**8.1.3.9 get\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell_Type BArray< Cell_Type, Data_Type >::get_cell (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**8.1.3.10 get\_col\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**8.1.3.11 get\_col\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_col_vec (
    uint i,
    bool check_bounds = true ) const
```

**8.1.3.12 get\_entries()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Entries<Cell_Type> BArray< Cell_Type, Data_Type >::get_entries ( ) const
```

Get the edgelist.

`Entries` is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

Returns

`Entries<Cell_Type>`

**8.1.3.13 get\_row\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**8.1.3.14 get\_row\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_row_vec (
    uint i,
    bool check_bounds = true ) const
```

**8.1.3.15 insert\_cell() [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell< Cell_Type > && v,
    bool check_bounds,
    bool check_exists )
```

**8.1.3.16 insert\_cell() [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell_Type v,
    bool check_bounds,
    bool check_exists )
```

**8.1.3.17 insert\_cell() [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool check_exists )
```

**8.1.3.18 is\_dense()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 240 of file `barray-bones.hpp`.

#### 8.1.3.19 is\_empty()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_empty (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

#### 8.1.3.20 ncol()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::ncol ( ) const [noexcept]
```

#### 8.1.3.21 nnozero()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::nnozero ( ) const [noexcept]
```

#### 8.1.3.22 nrow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArray< Cell_Type, Data_Type >::nrow ( ) const [noexcept]
```

#### 8.1.3.23 operator()() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell<Cell_Type,Data_Type> BArray< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true )
```

#### 8.1.3.24 operator()() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArray< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**8.1.3.25 operator\*=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

**8.1.3.26 operator+=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

**8.1.3.27 operator+=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & rhs )
```

**8.1.3.28 operator+=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const std::pair< uint, uint > & coords )
```

**8.1.3.29 operator-=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

**8.1.3.30 operator-=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & rhs )
```

**8.1.3.31 operator-=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const std::pair< uint, uint > & coords )
```

**8.1.3.32 operator/=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & rhs )
```

**8.1.3.33 operator=( ) [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move assignment.

**8.1.3.34 operator=( ) [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

Assignment constructor.

**8.1.3.35 operator==( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::operator== (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

**8.1.3.36 out\_of\_range( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::out_of_range (
    uint i,
    uint j ) const
```

**8.1.3.37 print()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const
```

**8.1.3.38 reserve()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::reserve ( )
```

**8.1.3.39 resize()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::resize (
    uint N_,
    uint M_ )
```

**8.1.3.40 rm\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::rm_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    bool check_exists = true )
```

**8.1.3.41 row()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Row_type< Cell_Type >& BArray< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true ) const
```

**8.1.3.42 set\_data()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false )
```

Set the data object.



## Parameters

<i>data_</i>	
<i>delete_↔</i> <i>data_</i>	

**8.1.3.43 swap\_cells()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cells (
    uint i0,
    uint j0,
    uint i1,
    uint j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr )
```

**8.1.3.44 swap\_cols()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cols (
    uint j0,
    uint j1,
    bool check_bounds = true )
```

**8.1.3.45 swap\_rows()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_rows (
    uint i0,
    uint i1,
    bool check_bounds = true )
```

**8.1.3.46 toggle\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN )
```

#### 8.1.3.47 toggle\_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_lock (
    uint i,
    uint j,
    bool check_bounds = true )
```

#### 8.1.3.48 transpose()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::transpose ( )
```

#### 8.1.3.49 zero\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_col (
    uint j,
    bool check_bounds = true )
```

#### 8.1.3.50 zero\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_row (
    uint i,
    bool check_bounds = true )
```

### 8.1.4 Friends And Related Function Documentation

#### 8.1.4.1 BArrayCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barray-bones.hpp.

### 8.1.4.2 BArrayCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barray-bones.hpp.

## 8.1.5 Member Data Documentation

### 8.1.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if cell.visited = true and visited = true, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 54 of file barray-bones.hpp.

The documentation for this class was generated from the following file:

- include/barry/barray-bones.hpp

## 8.2 BArrayCell< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

### Public Member Functions

- BArrayCell (BArray< Cell\_Type, Data\_Type > \*Array\_, uint i\_, uint j\_, bool check\_bounds=true)
- ~BArrayCell ()
- void operator= (const Cell\_Type &val)
- void operator+= (const Cell\_Type &val)
- void operator-= (const Cell\_Type &val)
- void operator\*= (const Cell\_Type &val)
- void operator/= (const Cell\_Type &val)
- operator Cell\_Type () const
- bool operator== (const Cell\_Type &val) const

### 8.2.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell< Cell_Type, Data_Type >
```

Definition at line 7 of file barraycell-bones.hpp.

## 8.2.2 Constructor & Destructor Documentation

### 8.2.2.1 BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::BArrayCell (
    BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    uint j_,
    bool check_bounds = true ) [inline]
```

Definition at line 16 of file barraycell-bones.hpp.

### 8.2.2.2 ~BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::~~BArrayCell ( ) [inline]
```

Definition at line 31 of file barraycell-bones.hpp.

## 8.2.3 Member Function Documentation

### 8.2.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 58 of file barraycell-meat.hpp.

### 8.2.3.2 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 40 of file barraycell-meat.hpp.

### 8.2.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 18 of file barraycell-meat.hpp.

### 8.2.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 29 of file barraycell-meat.hpp.

### 8.2.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 49 of file barraycell-meat.hpp.

### 8.2.3.6 operator=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 7 of file barraycell-meat.hpp.

### 8.2.3.7 operator==(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 63 of file barraycell-meat.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barray-bones.hpp](#)
- [include/barry/barraycell-bones.hpp](#)
- [include/barry/barraycell-meat.hpp](#)
- [include/barry/barrayrow-meat.hpp](#)

## 8.3 BArrayCell\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

### Public Member Functions

- [BArrayCell\\_const](#) (const [BArray](#)< Cell\_Type, Data\_Type > \*[Array\\_](#), [uint](#) [i\\_](#), [uint](#) [j\\_](#), bool [check\\_bounds](#)=true)
- [~BArrayCell\\_const](#) ()
- [operator Cell\\_Type](#) () const
- bool [operator==](#) (const [Cell\\_Type](#) &[val](#)) const
- bool [operator!=](#) (const [Cell\\_Type](#) &[val](#)) const
- bool [operator<](#) (const [Cell\\_Type](#) &[val](#)) const
- bool [operator>](#) (const [Cell\\_Type](#) &[val](#)) const
- bool [operator<=](#) (const [Cell\\_Type](#) &[val](#)) const
- bool [operator>=](#) (const [Cell\\_Type](#) &[val](#)) const

### 8.3.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell_const< Cell_Type, Data_Type >
```

Definition at line 46 of file `barraycell-bones.hpp`.

### 8.3.2 Constructor & Destructor Documentation

#### 8.3.2.1 BArrayCell\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::BArrayCell_const (
    const BArray< Cell_Type, Data_Type > * Array\_,
    uint i\_,
    uint j\_,
    bool check\_bounds = true ) [inline]
```

Definition at line 55 of file `barraycell-bones.hpp`.

#### 8.3.2.2 ~BArrayCell\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::~BArrayCell_const ( ) [inline]
```

Definition at line 67 of file `barraycell-bones.hpp`.

### 8.3.3 Member Function Documentation

#### 8.3.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell_const< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 68 of file barraycell-meat.hpp.

#### 8.3.3.2 operator"!="()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator!= (
    const Cell_Type & val ) const [inline]
```

Definition at line 78 of file barraycell-meat.hpp.

#### 8.3.3.3 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 83 of file barraycell-meat.hpp.

#### 8.3.3.4 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 93 of file barraycell-meat.hpp.

#### 8.3.3.5 operator==(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 73 of file barraycell-meat.hpp.

### 8.3.3.6 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 88 of file `barraycell-meat.hpp`.

### 8.3.3.7 operator>=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 98 of file `barraycell-meat.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barray-bones.hpp`
- `include/barry/barraycell-bones.hpp`
- `include/barry/barraycell-meat.hpp`
- `include/barry/barrayrow-meat.hpp`

## 8.4 BArrayDense< Cell\_Type, Data\_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barraydense-bones.hpp>
```

### Public Member Functions

- `bool operator== (const BArrayDense< Cell_Type, Data_Type > &Array_)`
- `~BArrayDense ()`
- `void out_of_range (uint i, uint j) const`
- `Cell_Type get_cell (uint i, uint j, bool check_bounds=true) const`
- `std::vector< Cell_Type > get_col_vec (uint i, bool check_bounds=true) const`
- `std::vector< Cell_Type > get_row_vec (uint i, bool check_bounds=true) const`
- `void get_col_vec (std::vector< Cell_Type > *x, uint i, bool check_bounds=true) const`
- `void get_row_vec (std::vector< Cell_Type > *x, uint i, bool check_bounds=true) const`
- `BArrayDenseRow< Cell_Type, Data_Type > & row (uint i, bool check_bounds=true)`
- `const BArrayDenseRow_const< Cell_Type, Data_Type > row (uint i, bool check_bounds=true) const`
- `BArrayDenseCol< Cell_Type, Data_Type > & col (uint j, bool check_bounds=true)`
- `const BArrayDenseCol_const< Cell_Type, Data_Type > col (uint j, bool check_bounds=true) const`
- `Entries< Cell_Type > get_entries () const`

*Get the edgelist.*

- `void transpose ()`
- `void clear (bool hard=true)`
- `void resize (uint N_, uint M_)`
- `void reserve ()`
- `void print (const char *fmt=nullptr,...) const`
- `bool is_dense () const noexcept`
- `const std::vector< Cell_Type > & get_data () const`
- `const Cell_Type rowsum (unsigned int i) const`
- `const Cell_Type colsum (unsigned int i) const`

### Constructors



*Parameters*

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An unsigned int vector ranging from 0 to M_
target	When <code>true</code> tries to add repeated observations.
value	Cell_Type default fill-in value (zero, by default.)

- `BArrayDense ()`  
*Zero-size array.*
  - `BArrayDense (uint N_, uint M_, Cell_Type value=static_cast< Cell_Type >(0))`  
*Empty array.*
  - `BArrayDense (uint N_, uint M_, const std::vector< uint > &source, const std::vector< uint > &target, const std::vector< Cell_Type > &value, bool add=true)`  
*Edgelist with data.*
  - `BArrayDense (uint N_, uint M_, const std::vector< uint > &source, const std::vector< uint > &target, bool add=true)`  
*Edgelist with no data (simpler)*
  - `BArrayDense (const BArrayDense< Cell_Type, Data_Type > &Array_, bool copy_data=false)`  
*Copy constructor.*
  - `BArrayDense< Cell_Type, Data_Type > & operator= (const BArrayDense< Cell_Type, Data_Type > &Array_)`  
*Assignment constructor.*
  - `BArrayDense (BArrayDense< Cell_Type, Data_Type > &&x) noexcept`  
*Move operator.*
  - `BArrayDense< Cell_Type, Data_Type > & operator= (BArrayDense< Cell_Type, Data_Type > &&x) noexcept`  
*Move assignment.*
- 
- `void set_data (Data_Type *data_, bool delete_data_=false)`  
*Set the data object.*
  - `Data_Type * D_ptr ()`
  - `const Data_Type * D_ptr () const`
  - `Data_Type & D ()`
  - `const Data_Type & D () const`

**Queries**

*is\_empty* queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

*Parameters*

i,j	Coordinates
check_bounds	If <i>false</i> avoids checking bounds.

- `bool is_empty (uint i, uint j, bool check_bounds=true) const`
- `uint nrow () const noexcept`
- `uint ncol () const noexcept`
- `uint nnozero () const noexcept`

- `Cell< Cell_Type > default_val () const`

### Cell-wise insertion/deletion

#### Parameters

<code>i,j</code>	<i>Row,column</i>
<code>check_bounds</code>	<i>When <code>true</code> and out of range, the function throws an error.</i>
<code>check_exists</code>	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of <code>swap_cells</code>, check if either of both cells exists/don't exist.</i>

- `BArrayDense< Cell_Type, Data_Type > & operator+= (const std::pair< uint, uint > &coords)`
- `BArrayDense< Cell_Type, Data_Type > & operator-= (const std::pair< uint, uint > &coords)`
- `BArrayDenseCell< Cell_Type, Data_Type > operator() (uint i, uint j, bool check_bounds=true)`
- `const Cell_Type operator() (uint i, uint j, bool check_bounds=true) const`
- `void rm_cell (uint i, uint j, bool check_bounds=true, bool check_exists=true)`
- `void insert_cell (uint i, uint j, const Cell< Cell_Type > &v, bool check_bounds, bool check_exists)`
- `void insert_cell (uint i, uint j, Cell_Type v, bool check_bounds, bool check_exists)`
- `void swap_cells (uint i0, uint j0, uint i1, uint j1, bool check_bounds=true, int check_exists=CHECK::BOTH, int *report=nullptr)`
- `void toggle_cell (uint i, uint j, bool check_bounds=true, int check_exists=EXISTS::UNKNOWN)`
- `void toggle_lock (uint i, uint j, bool check_bounds=true)`

### Column/row wise interchange

- `void swap_rows (uint i0, uint i1, bool check_bounds=true)`
- `void swap_cols (uint j0, uint j1, bool check_bounds=true)`
- `void zero_row (uint i, bool check_bounds=true)`
- `void zero_col (uint j, bool check_bounds=true)`

### Arithmetic operators

- `BArrayDense< Cell_Type, Data_Type > & operator+= (const BArrayDense< Cell_Type, Data_Type > &rhs)`
- `BArrayDense< Cell_Type, Data_Type > & operator+= (const Cell_Type &rhs)`
- `BArrayDense< Cell_Type, Data_Type > & operator-= (const BArrayDense< Cell_Type, Data_Type > &rhs)`
- `BArrayDense< Cell_Type, Data_Type > & operator-= (const Cell_Type &rhs)`
- `BArrayDense< Cell_Type, Data_Type > & operator/= (const Cell_Type &rhs)`
- `BArrayDense< Cell_Type, Data_Type > & operator*= (const Cell_Type &rhs)`

### Public Attributes

- `bool visited = false`

### Friends

- `class BArrayDenseCell< Cell_Type, Data_Type >`
- `class BArrayDenseCol< Cell_Type, Data_Type >`
- `class BArrayDenseCol_const< Cell_Type, Data_Type >`
- `class BArrayDenseRow< Cell_Type, Data_Type >`
- `class BArrayDenseRow_const< Cell_Type, Data_Type >`

### 8.4.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDense< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

[BArrayDense](#) class objects are arbitrary dense-arrays. The data is stored internally in the `el` member, which can be accessed using the member function `get_data()`, by column.

#### Template Parameters

<i>Cell_Type</i>	Type of cell (any type).
<i>Data_Type</i>	Data type of the array (bool default).

Definition at line 33 of file `barraydense-bones.hpp`.

### 8.4.2 Constructor & Destructor Documentation

#### 8.4.2.1 BArrayDense() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense ( ) [inline]
```

Zero-size array.

Definition at line 79 of file `barraydense-bones.hpp`.

#### 8.4.2.2 BArrayDense() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    Cell_Type value = static_cast<Cell_Type>(0) ) [inline]
```

Empty array.

Definition at line 82 of file `barraydense-bones.hpp`.

**8.4.2.3 BArrayDense()** [3/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    const std::vector< Cell_Type > & value,
    bool add = true )
```

Edgelist with data.

**8.4.2.4 BArrayDense()** [4/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    uint N_,
    uint M_,
    const std::vector< uint > & source,
    const std::vector< uint > & target,
    bool add = true )
```

Edgelist with no data (simpler)

**8.4.2.5 BArrayDense()** [5/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    const BArrayDense< Cell_Type, Data_Type > & Array_,
    bool copy_data = false )
```

Copy constructor.

**8.4.2.6 BArrayDense()** [6/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    BArrayDense< Cell_Type, Data_Type > && x ) [noexcept]
```

Move operator.

#### 8.4.2.7 ~BArrayDense()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::~~BArrayDense ( )
```

### 8.4.3 Member Function Documentation

#### 8.4.3.1 clear()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::clear (
    bool hard = true )
```

#### 8.4.3.2 col() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCol< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::col (
    uint j,
    bool check_bounds = true ) [inline]
```

Definition at line 490 of file `barraydense-meat.hpp`.

#### 8.4.3.3 col() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const BArrayDenseCol_const< Cell_Type, Data_Type > BArrayDense< Cell_Type, Data_Type >::col (
    uint j,
    bool check_bounds = true ) const [inline]
```

Definition at line 476 of file `barraydense-meat.hpp`.

#### 8.4.3.4 colsum()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::colsum (
    unsigned int i ) const
```

#### 8.4.3.5 D() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type& BArrayDense< Cell_Type, Data_Type >::D ( )
```

#### 8.4.3.6 D() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type& BArrayDense< Cell_Type, Data_Type >::D ( ) const
```

#### 8.4.3.7 D\_ptr() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type* BArrayDense< Cell_Type, Data_Type >::D_ptr ( )
```

#### 8.4.3.8 D\_ptr() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type* BArrayDense< Cell_Type, Data_Type >::D_ptr ( ) const
```

#### 8.4.3.9 default\_val()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell<Cell_Type> BArrayDense< Cell_Type, Data_Type >::default_val ( ) const
```

#### 8.4.3.10 get\_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell_Type BArrayDense< Cell_Type, Data_Type >::get_cell (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**8.4.3.11 get\_col\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**8.4.3.12 get\_col\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    uint i,
    bool check_bounds = true ) const
```

**8.4.3.13 get\_data()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::vector< Cell_Type >& BArrayDense< Cell_Type, Data_Type >::get_data ( ) const
```

**8.4.3.14 get\_entries()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Entries<Cell_Type> BArrayDense< Cell_Type, Data_Type >::get_entries ( ) const
```

Get the edgelist.

`Entries` is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

**Returns**

`Entries<Cell_Type>`

**8.4.3.15 get\_row\_vec() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    uint i,
    bool check_bounds = true ) const
```

**8.4.3.16 get\_row\_vec() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    uint i,
    bool check_bounds = true ) const
```

**8.4.3.17 insert\_cell() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    Cell_Type v,
    bool check_bounds,
    bool check_exists )
```

**8.4.3.18 insert\_cell() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    uint i,
    uint j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool check_exists )
```

**8.4.3.19 is\_dense()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 256 of file `barraydense-bones.hpp`.

**8.4.3.20 is\_empty()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::is_empty (
    uint i,
    uint j,
    bool check_bounds = true ) const
```



**8.4.3.21 ncol()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::ncol ( ) const [noexcept]
```

**8.4.3.22 nnozero()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::nnozero ( ) const [noexcept]
```

**8.4.3.23 nrow()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayDense< Cell_Type, Data_Type >::nrow ( ) const [noexcept]
```

**8.4.3.24 operator>() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell<Cell_Type,Data_Type> BArrayDense< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true )
```

**8.4.3.25 operator>() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::operator() (
    uint i,
    uint j,
    bool check_bounds = true ) const
```

**8.4.3.26 operator\*=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

**8.4.3.27 operator+=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

**8.4.3.28 operator+=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const Cell_Type & rhs )
```

**8.4.3.29 operator+=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const std::pair< uint, uint > & coords )
```

**8.4.3.30 operator-=( ) [1/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

**8.4.3.31 operator-=( ) [2/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const Cell_Type & rhs )
```

**8.4.3.32 operator-=( ) [3/3]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const std::pair< uint, uint > & coords )
```

**8.4.3.33 operator/=( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & rhs )
```

**8.4.3.34 operator=( ) [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator= (
    BArrayDense< Cell_Type, Data_Type > && x ) [noexcept]
```

Move assignment.

**8.4.3.35 operator=( ) [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator= (
    const BArrayDense< Cell_Type, Data_Type > & Array_ )
```

Assignment constructor.

**8.4.3.36 operator==( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::operator== (
    const BArrayDense< Cell_Type, Data_Type > & Array_ )
```

**8.4.3.37 out\_of\_range( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::out_of_range (
    uint i,
    uint j ) const
```

**8.4.3.38 print( )**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const
```

**8.4.3.39 reserve()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::reserve ( )
```

**8.4.3.40 resize()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::resize (
    uint N_,
    uint M_ )
```

**8.4.3.41 rm\_cell()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::rm_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    bool check_exists = true )
```

**8.4.3.42 row() [1/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true )
```

**8.4.3.43 row() [2/2]**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const BArrayDenseRow_const<Cell_Type,Data_Type> BArrayDense< Cell_Type, Data_Type >::row (
    uint i,
    bool check_bounds = true ) const
```

**8.4.3.44 rowsum()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArrayDense< Cell_Type, Data_Type >::rowsum (
    unsigned int i ) const
```

**8.4.3.45 set\_data()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false )
```

Set the data object.

**Parameters**

<i>data_</i>	
<i>delete_ ↔ data_</i>	

**8.4.3.46 swap\_cells()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_cells (
    uint i0,
    uint j0,
    uint i1,
    uint j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr )
```

**8.4.3.47 swap\_cols()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_cols (
    uint j0,
    uint j1,
    bool check_bounds = true )
```

**8.4.3.48 swap\_rows()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::swap_rows (
    uint i0,
    uint i1,
    bool check_bounds = true )
```

#### 8.4.3.49 toggle\_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::toggle_cell (
    uint i,
    uint j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN )
```

#### 8.4.3.50 toggle\_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::toggle_lock (
    uint i,
    uint j,
    bool check_bounds = true )
```

#### 8.4.3.51 transpose()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::transpose ( )
```

#### 8.4.3.52 zero\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::zero_col (
    uint j,
    bool check_bounds = true )
```

#### 8.4.3.53 zero\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::zero_row (
    uint i,
    bool check_bounds = true )
```

### 8.4.4 Friends And Related Function Documentation

#### 8.4.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 8.4.4.2 BArrayDenseCol< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 8.4.4.3 BArrayDenseCol\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 8.4.4.4 BArrayDenseRow< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

#### 8.4.4.5 BArrayDenseRow\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

### 8.4.5 Member Data Documentation

#### 8.4.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if cell.visited = true and visited = true, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 63 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydense-meat.hpp`

## 8.5 BArrayDenseCell< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecell-bones.hpp>
```

### Public Member Functions

- `BArrayDenseCell (BArrayDense< Cell_Type, Data_Type > *Array_, uint i_, uint j_, bool check_bounds=true)`
- `BArrayDenseCell< Cell_Type, Data_Type > & operator= (const BArrayDenseCell< Cell_Type, Data_Type > &other)`
- `~BArrayDenseCell ()`
- `void operator= (const Cell_Type &val)`
- `void operator+= (const Cell_Type &val)`
- `void operator-= (const Cell_Type &val)`
- `void operator*= (const Cell_Type &val)`
- `void operator/= (const Cell_Type &val)`
- `operator Cell_Type () const`
- `bool operator== (const Cell_Type &val) const`

### Friends

- `class BArrayDense< Cell_Type, Data_Type >`
- `class BArrayDenseCol< Cell_Type, Data_Type >`
- `class BArrayDenseCol_const< Cell_Type, Data_Type >`

#### 8.5.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCell< Cell_Type, Data_Type >
```

Definition at line 18 of file `barraydensecell-bones.hpp`.



## 8.5.2 Constructor & Destructor Documentation

### 8.5.2.1 BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::BArrayDenseCell (
    BArrayDense< Cell_Type, Data_Type > * Array_,
    uint i_,
    uint j_,
    bool check_bounds = true ) [inline]
```

Definition at line 30 of file `barraydensecell-bones.hpp`.

### 8.5.2.2 ~BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::~~BArrayDenseCell ( ) [inline]
```

Definition at line 56 of file `barraydensecell-bones.hpp`.

## 8.5.3 Member Function Documentation

### 8.5.3.1 operator Cell\_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 72 of file `barraydensecell-meat.hpp`.

### 8.5.3.2 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 52 of file `barraydensecell-meat.hpp`.

### 8.5.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 34 of file baraydensecell-meat.hpp.

### 8.5.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 43 of file baraydensecell-meat.hpp.

### 8.5.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 62 of file baraydensecell-meat.hpp.

### 8.5.3.6 operator=() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type > & BArrayDenseCell< Cell_Type, Data_Type >::operator=
(
    const BArrayDenseCell< Cell_Type, Data_Type > & other ) [inline]
```

Definition at line 9 of file baraydensecell-meat.hpp.

### 8.5.3.7 operator=() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 24 of file baraydensecell-meat.hpp.

#### 8.5.3.8 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayDenseCell< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 77 of file `barraydensecell-meat.hpp`.

### 8.5.4 Friends And Related Function Documentation

#### 8.5.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

#### 8.5.4.2 BArrayDenseCol< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

#### 8.5.4.3 BArrayDenseCol\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecell-bones.hpp`
- `include/barry/barraydensecell-meat.hpp`

## 8.6 BArrayDenseCell\_const< Cell\_Type, Data\_Type > Class Template Reference

### 8.6.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class BArrayDenseCell_const< Cell_Type, Data_Type >
```

Definition at line 20 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following file:

- [include/barry/barraydense-bones.hpp](#)

## 8.7 BArrayDenseCol< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

### Public Member Functions

- [BArrayDenseCol](#) ([BArrayDense](#)< Cell\_Type, Data\_Type > &array\_, unsigned int j)
- [Col\\_type](#)< Cell\_Type >::iterator & [begin](#) ()
- [Col\\_type](#)< Cell\_Type >::iterator & [end](#) ()
- [size\\_t](#) [size](#) () [const](#) [noexcept](#)
- [std::pair](#)< unsigned int, Cell\_Type \* > & [operator\(\)](#) (unsigned int i)

### Friends

- class [BArrayDense](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell\\_const](#)< Cell\_Type, Data\_Type >

### 8.7.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydensecol-bones.hpp`.

### 8.7.2 Constructor & Destructor Documentation

### 8.7.2.1 BArrayDenseCol()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol< Cell_Type, Data_Type >::BArrayDenseCol (
    BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int j ) [inline]
```

Definition at line 38 of file barraydensecol-bones.hpp.

## 8.7.3 Member Function Documentation

### 8.7.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 44 of file barraydensecol-bones.hpp.

### 8.7.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 50 of file barraydensecol-bones.hpp.

### 8.7.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<unsigned int,Cell_Type*>& BArrayDenseCol< Cell_Type, Data_Type >::operator() (
    unsigned int i ) [inline]
```

Definition at line 62 of file barraydensecol-bones.hpp.

### 8.7.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 56 of file barraydensecol-bones.hpp.

## 8.7.4 Friends And Related Function Documentation

### 8.7.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

### 8.7.4.2 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

### 8.7.4.3 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

## 8.8 BArrayDenseCol\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

### Public Member Functions

- `BArrayDenseCol_const` (`const BArrayDense`< `Cell_Type`, `Data_Type` > &`array_`, unsigned int `j`)
- `Col_type`< `Cell_Type` >::iterator `begin` ()
- `Col_type`< `Cell_Type` >::iterator `end` ()
- `size_t` `size` () `const noexcept`
- `const` `std::pair`< unsigned int, `Cell_Type` \* > `operator()` (unsigned int `i`) `const`

## Friends

- class [BArrayDenseCell< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseCell\\_const< Cell\\_Type, Data\\_Type >](#)

### 8.8.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol_const< Cell_Type, Data_Type >
```

Definition at line 71 of file `barraydensecol-bones.hpp`.

### 8.8.2 Constructor & Destructor Documentation

#### 8.8.2.1 BArrayDenseCol\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol_const< Cell_Type, Data_Type >::BArrayDenseCol_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int j ) [inline]
```

Definition at line 80 of file `barraydensecol-bones.hpp`.

### 8.8.3 Member Function Documentation

#### 8.8.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 96 of file `barraydensecol-bones.hpp`.

#### 8.8.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 101 of file `barraydensecol-bones.hpp`.

### 8.8.3.3 operator()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<unsigned int,Cell_Type*> BArrayDenseCol_const< Cell_Type, Data_Type >::operator()
(
    unsigned int i ) const [inline]
```

Definition at line 112 of file `barraydensecol-bones.hpp`.

### 8.8.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 107 of file `barraydensecol-bones.hpp`.

## 8.8.4 Friends And Related Function Documentation

### 8.8.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

### 8.8.4.2 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

## 8.9 BArrayDenseRow< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```



## Public Member Functions

- [BArrayDenseRow](#) ([BArrayDense](#)< Cell\_Type, Data\_Type > &array\_, unsigned int i)
- [Row\\_type](#)< Cell\_Type >::iterator & [begin](#) ()
- [Row\\_type](#)< Cell\_Type >::iterator & [end](#) ()
- [size\\_t](#) [size](#) () [const noexcept](#)
- [std::pair](#)< unsigned int, [Cell](#)< Cell\_Type > > & [operator\(\)](#) (unsigned int i)

## Friends

- class [BArrayDense](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell](#)< Cell\_Type, Data\_Type >
- class [BArrayDenseCell\\_const](#)< Cell\_Type, Data\_Type >

### 8.9.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydenserow-bones.hpp`.

### 8.9.2 Constructor & Destructor Documentation

#### 8.9.2.1 BArrayDenseRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow< Cell_Type, Data_Type >::BArrayDenseRow (
    BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int i ) [inline]
```

Definition at line 40 of file `barraydenserow-bones.hpp`.

### 8.9.3 Member Function Documentation

#### 8.9.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 45 of file `barraydenserow-bones.hpp`.

### 8.9.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 53 of file bararraydenserow-bones.hpp.

### 8.9.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<unsigned int,Cell<Cell_Type> >& BArrayDenseRow< Cell_Type, Data_Type >::operator()
(
    unsigned int i ) [inline]
```

Definition at line 69 of file bararraydenserow-bones.hpp.

### 8.9.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 61 of file bararraydenserow-bones.hpp.

## 8.9.4 Friends And Related Function Documentation

### 8.9.4.1 BArrayDense< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.

### 8.9.4.2 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.

### 8.9.4.3 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

## 8.10 BArrayDenseRow\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```

### Public Member Functions

- `BArrayDenseRow_const` (`const BArrayDense`< `Cell_Type`, `Data_Type` > &`array_`, unsigned int `i`)
- `Row_type`< `Cell_Type` >::const\_iterator `begin` () `const`
- `Row_type`< `Cell_Type` >::const\_iterator `end` () `const`
- `size_t` `size` () `const noexcept`
- `const` std::pair< unsigned int, `Cell`< `Cell_Type` > > `operator()` (unsigned int `i`) `const`

### Friends

- class `BArrayDenseCell`< `Cell_Type`, `Data_Type` >
- class `BArrayDenseCell_const`< `Cell_Type`, `Data_Type` >

### 8.10.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow_const< Cell_Type, Data_Type >
```

Definition at line 80 of file `barraydenserow-bones.hpp`.

### 8.10.2 Constructor & Destructor Documentation

### 8.10.2.1 BArrayDenseRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow_const< Cell_Type, Data_Type >::BArrayDenseRow_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    unsigned int i ) [inline]
```

Definition at line 89 of file barraydenserow-bones.hpp.

## 8.10.3 Member Function Documentation

### 8.10.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::begin ( )
const [inline]
```

Definition at line 108 of file barraydenserow-bones.hpp.

### 8.10.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::end ( )
const [inline]
```

Definition at line 113 of file barraydenserow-bones.hpp.

### 8.10.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<unsigned int, Cell<Cell_Type> > BArrayDenseRow_const< Cell_Type, Data_Type
>::operator() (
    unsigned int i ) const [inline]
```

Definition at line 123 of file barraydenserow-bones.hpp.

### 8.10.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 118 of file barraydenserow-bones.hpp.

### 8.10.4 Friends And Related Function Documentation

#### 8.10.4.1 BArrayDenseCell< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

#### 8.10.4.2 BArrayDenseCell\_const< Cell\_Type, Data\_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

## 8.11 BArrayRow< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

### Public Member Functions

- `BArrayRow` (`BArray`< `Cell_Type`, `Data_Type` > \*`Array_`, `uint` `i_`, `bool` `check_bounds`=true)
- `~BArrayRow` ()
- `void operator=` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`)
- `void operator+=` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`)
- `void operator-=` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`)
- `void operator*=` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`)
- `void operator/=` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`)
- `operator BArrayRow`< `Cell_Type`, `Data_Type` > () `const`
- `bool operator==` (`const BArrayRow`< `Cell_Type`, `Data_Type` > &`val`) `const`

#### 8.11.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow< Cell_Type, Data_Type >
```

Definition at line 5 of file `barrayrow-bones.hpp`.

## 8.11.2 Constructor & Destructor Documentation

### 8.11.2.1 BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::BArrayRow (
    BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    bool check_bounds = true ) [inline]
```

Definition at line 13 of file bararrayrow-bones.hpp.

### 8.11.2.2 ~BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::~~BArrayRow ( ) [inline]
```

Definition at line 26 of file bararrayrow-bones.hpp.

## 8.11.3 Member Function Documentation

### 8.11.3.1 operator BArrayRow< Cell\_Type, Data\_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::operator BArrayRow< Cell_Type, Data_Type > ( ) const
```

### 8.11.3.2 operator\*=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator*= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

### 8.11.3.3 operator+=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator+= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 8.11.3.4 operator-=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator-= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 8.11.3.5 operator/=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator/= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 8.11.3.6 operator=( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

#### 8.11.3.7 operator==( )

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow< Cell_Type, Data_Type >::operator== (
    const BArrayRow< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

## 8.12 BArrayRow\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

### Public Member Functions

- [BArrayRow\\_const](#) (const BArray< Cell\_Type, Data\_Type > \*Array\_, uint i\_, bool check\_bounds=true)
- [~BArrayRow\\_const](#) ( )
- [operator BArrayRow\\_const< Cell\\_Type, Data\\_Type > \( \)](#) const
- [bool operator==](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator!=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator<](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator>](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator<=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const
- [bool operator>=](#) (const BArrayRow\_const< Cell\_Type, Data\_Type > &val) const

### 8.12.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow_const< Cell_Type, Data_Type >
```

Definition at line 41 of file `barrayrow-bones.hpp`.

### 8.12.2 Constructor & Destructor Documentation

#### 8.12.2.1 BArrayRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::BArrayRow_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    uint i_,
    bool check_bounds = true ) [inline]
```

Definition at line 49 of file `barrayrow-bones.hpp`.

#### 8.12.2.2 ~BArrayRow\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::~~BArrayRow_const ( ) [inline]
```

Definition at line 59 of file `barrayrow-bones.hpp`.

### 8.12.3 Member Function Documentation

#### 8.12.3.1 operator BArrayRow\_const< Cell\_Type, Data\_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::operator BArrayRow_const< Cell_Type, Data_Type > ( )
const
```

#### 8.12.3.2 operator"!="()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator!= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```



**8.12.3.3 operator<()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator< (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**8.12.3.4 operator<=()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator<= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**8.12.3.5 operator==(())**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator==(
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**8.12.3.6 operator>()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator> (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

**8.12.3.7 operator>=()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator>= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

**8.13 BArrayVector< Cell\_Type, Data\_Type > Class Template Reference**

Row or column of a [BArray](#)

```
#include <barrayvector-bones.hpp>
```

## Public Member Functions

- [BArrayVector](#) ([BArray](#)< [Cell\\_Type](#), [Data\\_Type](#) > \*[Array\\_](#), [uint](#) &[dim\\_ uint](#) &[i\\_](#), [bool](#) [check\\_bounds](#)=true)  
Construct a new [BArrayVector](#) object.
- [~BArrayVector](#) ()
- [bool](#) [is\\_row](#) () [const](#) [noexcept](#)
- [bool](#) [is\\_col](#) () [const](#) [noexcept](#)
- [uint](#) [size](#) () [const](#) [noexcept](#)
- [std::vector](#)< [Cell\\_Type](#) >::[const\\_iterator](#) [begin](#) () [noexcept](#)
- [std::vector](#)< [Cell\\_Type](#) >::[const\\_iterator](#) [end](#) () [noexcept](#)
- [void](#) [operator=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator+=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator-=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator\\*=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [void](#) [operator/=](#) ([const](#) [Cell\\_Type](#) &[val](#))
- [operator](#) [std::vector](#)< [Cell\\_Type](#) > () [const](#)
- [bool](#) [operator==](#) ([const](#) [Cell\\_Type](#) &[val](#)) [const](#)

### 8.13.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector< Cell_Type, Data_Type >
```

Row or column of a [BArray](#)

Template Parameters

<i>Cell_Type</i>	
<i>Data_Type</i>	

Definition at line 11 of file [barrayvector-bones.hpp](#).

### 8.13.2 Constructor & Destructor Documentation

#### 8.13.2.1 BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::BArrayVector (
    BArray< Cell_Type, Data_Type > * Array\_,
    uint &dim\_ uint & i\_,
    bool check\_bounds = true ) [inline]
```

Construct a new [BArrayVector](#) object.

Parameters

<i>Array_</i>	Pointer to a <a href="#">BArray</a> object
<i>dim_</i>	Dimension. 0 means row and 1 means column.
<i>i_</i>	Element to point.
<i>check_bounds</i>	When <a href="#">true</a> , check boundaries.

Definition at line 32 of file barrayvector-bones.hpp.

#### 8.13.2.2 ~BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::~~BArrayVector ( ) [inline]
```

Definition at line 53 of file barrayvector-bones.hpp.

### 8.13.3 Member Function Documentation

#### 8.13.3.1 begin()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::begin [inline],
[noexcept]
```

Definition at line 50 of file barrayvector-meat.hpp.

#### 8.13.3.2 end()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::end [inline],
[noexcept]
```

Definition at line 64 of file barrayvector-meat.hpp.

#### 8.13.3.3 is\_col()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_col [inline], [noexcept]
```

Definition at line 34 of file barrayvector-meat.hpp.

#### 8.13.3.4 is\_row()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_row [inline], [noexcept]
```

Definition at line 29 of file barrayvector-meat.hpp.

#### 8.13.3.5 operator std::vector< Cell\_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 175 of file barrayvector-meat.hpp.

#### 8.13.3.6 operator\*=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 133 of file barrayvector-meat.hpp.

#### 8.13.3.7 operator+=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 91 of file barrayvector-meat.hpp.

#### 8.13.3.8 operator-=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 112 of file barrayvector-meat.hpp.

### 8.13.3.9 operator/=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 154 of file barrayvector-meat.hpp.

### 8.13.3.10 operator=( )

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 69 of file barrayvector-meat.hpp.

### 8.13.3.11 operator==( )

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 185 of file barrayvector-meat.hpp.

### 8.13.3.12 size( )

```
template<typename Cell_Type , typename Data_Type >
uint BArrayVector< Cell_Type, Data_Type >::size [inline], [noexcept]
```

Definition at line 39 of file barrayvector-meat.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barrayvector-bones.hpp](#)
- [include/barry/barrayvector-meat.hpp](#)

## 8.14 BArrayVector\_const< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barrayvector-bones.hpp>
```

## Public Member Functions

- `BArrayVector_const` (`const BArray< Cell_Type, Data_Type > *Array_, uint &dim_ uint &i_, bool check_bounds=true`)
- `~BArrayVector_const` ()
- `bool is_row () const noexcept`
- `bool is_col () const noexcept`
- `uint size () const noexcept`
- `std::vector< Cell_Type >::const_iterator begin () noexcept`
- `std::vector< Cell_Type >::const_iterator end () noexcept`
- `operator std::vector< Cell_Type > () const`
- `bool operator== (const Cell_Type &val) const`
- `bool operator!= (const Cell_Type &val) const`
- `bool operator< (const Cell_Type &val) const`
- `bool operator> (const Cell_Type &val) const`
- `bool operator<= (const Cell_Type &val) const`
- `bool operator>= (const Cell_Type &val) const`

### 8.14.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector_const< Cell_Type, Data_Type >
```

Definition at line 73 of file `barrayvector-bones.hpp`.

### 8.14.2 Constructor & Destructor Documentation

#### 8.14.2.1 BArrayVector\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::BArrayVector_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    uint &dim_ uint &i_,
    bool check_bounds = true ) [inline]
```

Definition at line 86 of file `barrayvector-bones.hpp`.

#### 8.14.2.2 ~BArrayVector\_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::~~BArrayVector_const ( ) [inline]
```

Definition at line 108 of file `barrayvector-bones.hpp`.

### 8.14.3 Member Function Documentation

#### 8.14.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::begin (
) [noexcept]
```

#### 8.14.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::end ( )
[noexcept]
```

#### 8.14.3.3 is\_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_col ( ) const [noexcept]
```

#### 8.14.3.4 is\_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_row ( ) const [noexcept]
```

#### 8.14.3.5 operator std::vector< Cell\_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector_const< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 212 of file barrayvector-meat.hpp.

#### 8.14.3.6 operator"!=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator!= (
    const Cell_Type & val ) const [inline]
```

Definition at line 249 of file barrayvector-meat.hpp.

#### 8.14.3.7 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 254 of file barrayvector-meat.hpp.

#### 8.14.3.8 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 281 of file barrayvector-meat.hpp.

#### 8.14.3.9 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 222 of file barrayvector-meat.hpp.

#### 8.14.3.10 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 308 of file barrayvector-meat.hpp.



**8.14.3.11 operator>=()**

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 315 of file barrayvector-meat.hpp.

**8.14.3.12 size()**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
uint BArrayVector_const< Cell_Type, Data_Type >::size ( ) const [noexcept]
```

The documentation for this class was generated from the following files:

- include/barry/barrayvector-bones.hpp
- include/barry/barrayvector-meat.hpp

**8.15 Cell< Cell\_Type > Class Template Reference**

Entries in [BArray](#). For now, it only has two members:

```
#include <cell-bones.hpp>
```

**Public Member Functions**

- [Cell](#) ()
- [Cell](#) (Cell\_Type value\_, bool visited\_[\\_false](#), bool active\_[\\_true](#))
- [~Cell](#) ()
- [Cell](#) (const [Cell](#)< Cell\_Type > &arg)
- [Cell](#)< Cell\_Type > & [operator=](#) (const [Cell](#)< Cell\_Type > &other)
- [Cell](#) ([Cell](#)< Cell\_Type > &&arg) [noexcept](#)
- [Cell](#)< Cell\_Type > & [operator=](#) ([Cell](#)< Cell\_Type > &&other) [noexcept](#)
- void [add](#) (Cell\_Type x)
- [operator Cell\\_Type](#) () const
- bool [operator==](#) (const [Cell](#)< Cell\_Type > &rhs) const
- bool [operator!=](#) (const [Cell](#)< Cell\_Type > &rhs) const
- void [add](#) (double x)
- void [add](#) (unsigned int x)
- void [add](#) (int x)
- [Cell](#) ()
- [Cell](#) ()
- [Cell](#) ()

**Public Attributes**

- Cell\_Type [value](#)
- bool [visited](#)
- bool [active](#)

### 8.15.1 Detailed Description

```
template<class Cell_Type>
class Cell< Cell_Type >
```

[Entries](#) in [BArray](#). For now, it only has two members:

- value: the content
- visited: boolean (just a convenient)

Definition at line 10 of file cell-bones.hpp.

### 8.15.2 Constructor & Destructor Documentation

#### 8.15.2.1 Cell() [1/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell ( )
```

#### 8.15.2.2 Cell() [2/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell_Type value_,
    bool visited_ = false,
    bool active_ = true ) [inline]
```

Definition at line 16 of file cell-bones.hpp.

#### 8.15.2.3 ~Cell()

```
template<class Cell_Type >
Cell< Cell_Type >::~Cell ( ) [inline]
```

Definition at line 18 of file cell-bones.hpp.

#### 8.15.2.4 Cell() [3/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    const Cell< Cell_Type > & arg ) [inline]
```

Definition at line 22 of file cell-bones.hpp.

#### 8.15.2.5 Cell() [4/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell< Cell_Type > && arg ) [inline], [noexcept]
```

Definition at line 29 of file cell-bones.hpp.

#### 8.15.2.6 Cell() [5/7]

```
Cell< double >::Cell ( ) [inline]
```

Definition at line 62 of file cell-meat.hpp.

#### 8.15.2.7 Cell() [6/7]

```
Cell< uint >::Cell ( ) [inline]
```

Definition at line 63 of file cell-meat.hpp.

#### 8.15.2.8 Cell() [7/7]

```
Cell< int >::Cell ( ) [inline]
```

Definition at line 64 of file cell-meat.hpp.

### 8.15.3 Member Function Documentation

**8.15.3.1 add() [1/4]**

```
template<class Cell_Type >
void Cell< Cell_Type >::add (
    Cell_Type x )
```

**8.15.3.2 add() [2/4]**

```
void Cell< double >::add (
    double x ) [inline]
```

Definition at line 42 of file cell-meat.hpp.

**8.15.3.3 add() [3/4]**

```
void Cell< int >::add (
    int x ) [inline]
```

Definition at line 52 of file cell-meat.hpp.

**8.15.3.4 add() [4/4]**

```
void Cell< unsigned int >::add (
    unsigned int x ) [inline]
```

Definition at line 47 of file cell-meat.hpp.

**8.15.3.5 operator Cell\_Type()**

```
template<class Cell_Type >
Cell< Cell_Type >::operator Cell_Type ( ) const [inline]
```

Definition at line 41 of file cell-bones.hpp.

**8.15.3.6 operator"!="()**

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator!= (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 31 of file cell-meat.hpp.

### 8.15.3.7 operator=() [1/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    Cell< Cell_Type > && other ) [noexcept]
```

Definition at line 13 of file cell-meat.hpp.

### 8.15.3.8 operator=() [2/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    const Cell< Cell_Type > & other )
```

Definition at line 5 of file cell-meat.hpp.

### 8.15.3.9 operator==()

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator== (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 21 of file cell-meat.hpp.

## 8.15.4 Member Data Documentation

### 8.15.4.1 active

```
template<class Cell_Type >
bool Cell< Cell_Type >::active
```

Definition at line 14 of file cell-bones.hpp.

### 8.15.4.2 value

```
template<class Cell_Type >
Cell_Type Cell< Cell_Type >::value
```

Definition at line 12 of file cell-bones.hpp.

### 8.15.4.3 visited

```
template<class Cell_Type >
bool Cell< Cell_Type >::visited
```

Definition at line 13 of file cell-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/barray-meat.hpp
- include/barry/cell-bones.hpp
- include/barry/cell-meat.hpp

## 8.16 Cell\_const< Cell\_Type > Class Template Reference

### 8.16.1 Detailed Description

```
template<typename Cell_Type>
class Cell_const< Cell_Type >
```

Definition at line 8 of file barray-meat.hpp.


The documentation for this class was generated from the following file:

- include/barry/barray-meat.hpp

## 8.17 ConstBArrayRowIter< Cell\_Type, Data\_Type > Class Template Reference

```
#include <barray-iterator.hpp>
```

Collaboration diagram for ConstBArrayRowIter< Cell\_Type, Data\_Type >:



## Public Member Functions

- [ConstBArrayRowIter](#) ([const BArray](#)< Cell\_Type, Data\_Type > \*[Array\\_](#))
- [~ConstBArrayRowIter](#) ()

## Public Attributes

- [uint](#) [current\\_row](#)
- [uint](#) [current\\_col](#)
- [Row\\_type](#)< Cell\_Type >::const\_iterator [iter](#)
- [const BArray](#)< Cell\_Type, Data\_Type > \* [Array](#)

### 8.17.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class ConstBArrayRowIter< Cell_Type, Data_Type >
```

Definition at line 10 of file `barray-iterator.hpp`.

### 8.17.2 Constructor & Destructor Documentation

#### 8.17.2.1 ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::ConstBArrayRowIter (
    const BArray< Cell_Type, Data_Type > * Array_ ) [inline]
```

Definition at line 17 of file `barray-iterator.hpp`.

#### 8.17.2.2 ~ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::~~ConstBArrayRowIter ( ) [inline]
```

Definition at line 29 of file `barray-iterator.hpp`.

### 8.17.3 Member Data Documentation

### 8.17.3.1 Array

```
template<typename Cell_Type , typename Data_Type >
const BArray<Cell_Type,Data_Type>* ConstBArrayRowIter< Cell_Type, Data_Type >::Array
```

Definition at line 15 of file `barray-iterator.hpp`.

### 8.17.3.2 current\_col

```
template<typename Cell_Type , typename Data_Type >
uint ConstBArrayRowIter< Cell_Type, Data_Type >::current_col
```

Definition at line 13 of file `barray-iterator.hpp`.

### 8.17.3.3 current\_row

```
template<typename Cell_Type , typename Data_Type >
uint ConstBArrayRowIter< Cell_Type, Data_Type >::current_row
```

Definition at line 13 of file `barray-iterator.hpp`.

### 8.17.3.4 iter

```
template<typename Cell_Type , typename Data_Type >
Row_type<Cell_Type>::const_iterator ConstBArrayRowIter< Cell_Type, Data_Type >::iter
```

Definition at line 14 of file `barray-iterator.hpp`.

The documentation for this class was generated from the following file:

- `include/barry/barray-iterator.hpp`

## 8.18 Counter< Array\_Type, Data\_Type > Class Template Reference

A counter function based on change statistics.

```
#include <counters-bones.hpp>
```

### Public Member Functions

- `~Counter ()`
- `double count (Array_Type &Array, uint i, uint j)`
- `double init (Array_Type &Array, uint i, uint j)`
- `std::string get_name () const`
- `std::string get_description () const`

**Creator passing a counter and an initializer**



*Parameters*

count_fun↔ _	<i>The main counter function.</i>
init_fun_ _	<i>The initializer function can also be used to check if the <a href="#">BArray</a> as the needed variables (see <a href="#">BArray::data</a>).</i>
data_ _	<i>Data to be used with the counter.</i>
delete_↔ data_ _	<i>When <code>true</code>, the destructor will delete the pointer in the main data.</i>

- [Counter](#) ()
- [Counter](#) ([Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [count\\_fun](#), [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun](#), [Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > [hasher\\_fun](#), Data\_Type [data](#), std::string [name](#)="", std::string [desc](#)="")
- [Counter](#) (const [Counter](#)< Array\_Type, Data\_Type > &[counter](#)\_)  
*Copy constructor.*
- [Counter](#) ([Counter](#)< Array\_Type, Data\_Type > &&[counter](#)\_) noexcept  
*Move constructor.*
- [Counter](#)< Array\_Type, Data\_Type > [operator=](#) (const [Counter](#)< Array\_Type, Data\_Type > &[counter](#)\_)  
*Copy assignment.*
- [Counter](#)< Array\_Type, Data\_Type > & [operator=](#) ([Counter](#)< Array\_Type, Data\_Type > &&[counter](#)\_) noexcept  
*Move assignment.*

- void [set\\_hasher](#) ([Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > [fun](#))  
*Get and set the hasher function.*
- [Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > [get\\_hasher](#) ()

**Public Attributes**

- [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [count\\_fun](#)
- [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > [init\\_fun](#)
- [Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > [hasher\\_fun](#)
- Data\_Type [data](#)
- std::string [name](#) = ""
- std::string [desc](#) = ""

**8.18.1 Detailed Description**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counter< Array_Type, Data_Type >
```

A counter function based on change statistics.

This class is used by `CountStats` and `StatsCounter` as a way to count statistics using change statistics.

Definition at line 35 of file `counters-bones.hpp`.

## 8.18.2 Constructor & Destructor Documentation

### 8.18.2.1 Counter() [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter ( ) [inline]
```

Definition at line 57 of file counters-bones.hpp.

### 8.18.2.2 Counter() [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Hasher_fun_type< Array_Type, Data_Type > hasher_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" ) [inline]
```

Definition at line 59 of file counters-bones.hpp.

### 8.18.2.3 Counter() [3/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

### 8.18.2.4 Counter() [4/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move constructor.

### 8.18.2.5 ~Counter()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::~~Counter ( ) [inline]
```

Definition at line 75 of file counters-bones.hpp.

## 8.18.3 Member Function Documentation

### 8.18.3.1 count()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::count (
    Array_Type & Array,
    uint i,
    uint j )
```

### 8.18.3.2 get\_description()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_description ( ) const
```

### 8.18.3.3 get\_hasher()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Hasher_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::get_hasher ( )
```

### 8.18.3.4 get\_name()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_name ( ) const
```

### 8.18.3.5 init()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::init (
    Array_Type & Array,
    uint i,
    uint j )
```

**8.18.3.6 operator=()** [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::operator= (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy assignment.

**8.18.3.7 operator=()** [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type>& Counter< Array_Type, Data_Type >::operator= (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment.

**8.18.3.8 set\_hasher()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counter< Array_Type, Data_Type >::set_hasher (
    Hasher_fun_type< Array_Type, Data_Type > fun )
```

Get and set the hasher function.

The hasher function is used to characterize the support of the array. This way, if possible, the support enumeration is recycled.

**Parameters**

<i>fun</i>	
------------	--

**8.18.4 Member Data Documentation****8.18.4.1 count\_fun**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::count_fun
```

Definition at line 38 of file counters-bones.hpp.

#### 8.18.4.2 data

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Data_Type Counter< Array_Type, Data_Type >::data
```

Definition at line 42 of file counters-bones.hpp.

#### 8.18.4.3 desc

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::desc = ""
```

Definition at line 44 of file counters-bones.hpp.

#### 8.18.4.4 hasher\_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Hasher_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::hasher_fun
```

Definition at line 40 of file counters-bones.hpp.

#### 8.18.4.5 init\_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::init_fun
```

Definition at line 39 of file counters-bones.hpp.

#### 8.18.4.6 name

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::name = ""
```

Definition at line 43 of file counters-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/counters-bones.hpp](#)

## 8.19 Counters< Array\_Type, Data\_Type > Class Template Reference

Vector of counters.

```
#include <counters-bones.hpp>
```

### Public Member Functions

- [Counters](#) ()
- [~Counters](#) ()
- [Counters](#) (const [Counters](#)< Array\_Type, Data\_Type > &counter\_)
- Copy constructor.*
- [Counters](#) ([Counters](#)< Array\_Type, Data\_Type > &&counters\_) noexcept
- Move constructor.*
- [Counters](#)< Array\_Type, Data\_Type > operator= (const [Counters](#)< Array\_Type, Data\_Type > &counter\_)
- Copy assignment constructor.*
- [Counters](#)< Array\_Type, Data\_Type > & operator= ([Counters](#)< Array\_Type, Data\_Type > &&counter\_)
- noexcept
- Move assignment constructor.*
- [Counter](#)< Array\_Type, Data\_Type > & operator[] (uint idx)
- Returns a pointer to a particular counter.*
- std::size\_t [size](#) () const noexcept
- Number of counters in the set.*
- void [add\\_counter](#) ([Counter](#)< Array\_Type, Data\_Type > counter)
- void [add\\_counter](#) ([Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > count\_fun\_, [Counter\\_fun\\_type](#)< Array\_Type, Data\_Type > init\_fun\_, [Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > hasher\_fun\_, Data\_Type data\_, std::string name\_="", std::string desc\_="")
- std::vector< std::string > [get\\_names](#) () const
- std::vector< std::string > [get\\_descriptions](#) () const
- std::vector< double > [gen\\_hash](#) (const Array\_Type &array, bool add\_dims=true)
- Generates a hash for the given array according to the counters.*
- void [add\\_hash](#) ([Hasher\\_fun\\_type](#)< Array\_Type, Data\_Type > fun\_)

### 8.19.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counters< Array_Type, Data_Type >
```

Vector of counters.

Various functions hold more than one counter, so this class is a helper class that allows managing multiple counters efficiently. The main data is a vector to pointers of counters.

Definition at line 108 of file counters-bones.hpp.

### 8.19.2 Constructor & Destructor Documentation

**8.19.2.1 Counters()** [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters ( )
```

**8.19.2.2 ~Counters()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::~~Counters ( ) [inline]
```

Definition at line 120 of file counters-bones.hpp.

**8.19.2.3 Counters()** [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

**Parameters**

<i>counter_↔</i>	
—	

**8.19.2.4 Counters()** [3/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    Counters< Array_Type, Data_Type > && counters_ ) [noexcept]
```

Move constructor.

**Parameters**

<i>counters_↔</i>	
—	

**8.19.3 Member Function Documentation**

**8.19.3.1 add\_counter() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > counter )
```

**8.19.3.2 add\_counter() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Hasher_fun_type< Array_Type, Data_Type > hasher_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" )
```

**8.19.3.3 add\_hash()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_hash (
    Hasher_fun_type< Array_Type, Data_Type > fun_ )
```

**8.19.3.4 gen\_hash()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< double > Counters< Array_Type, Data_Type >::gen_hash (
    const Array_Type & array,
    bool add_dims = true )
```

Generates a hash for the given array according to the counters.

**Parameters**

<i>array</i>	
<i>add_dims</i>	When <code>true</code> (default) the dimension of the array will be added to the hash.

**Returns**

`std::vector< double >` That can be hashed later.



**8.19.3.5 get\_descriptions()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_descriptions ( ) const
```

**8.19.3.6 get\_names()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_names ( ) const
```

**8.19.3.7 operator=() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type> Counters< Array_Type, Data_Type >::operator= (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy assignment constructor.

**Parameters**

<i>counter_↔</i>	
—	

**Returns**

[Counters<Array\\_Type,Data\\_Type>](#)

**8.19.3.8 operator=() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type>& Counters< Array_Type, Data_Type >::operator= (
    Counters< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment constructor.

**Parameters**

<i>counter_↔</i>	
—	

## Returns

[Counters](#)<[Array\\_Type](#),[Data\\_Type](#)>&

**8.19.3.9 operator[]()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array\_Type,Data\_Type>& Counters< Array\_Type, Data\_Type >::operator[] (
    uint idx )
```

Returns a pointer to a particular counter.

## Parameters

<i>idx</i>	Id of the counter
------------	-------------------

## Returns

[Counter](#)<[Array\\_Type](#),[Data\\_Type](#)>\*

**8.19.3.10 size()**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::size_t Counters< Array\_Type, Data\_Type >::size ( ) const [inline], [noexcept]
```

Number of counters in the set.

## Returns

[uint](#)

Definition at line 164 of file counters-bones.hpp.


The documentation for this class was generated from the following file:

- [include/barry/counters-bones.hpp](#)


## 8.20 DEFM Class Reference

```
#include <defm-bones.hpp>
```

Inheritance diagram for DEFM:



Collaboration diagram for DEFM:



### Public Member Functions

- `DEFM` (`const` int \*id, `const` int \*y, `const` double \*x, size\_t id\_length, size\_t y\_ncol, size\_t x\_ncol, size\_t m\_order)
- `~DEFM` ()
- `defmcounters::DEFMModel` & `get_model` ()
- void `init` ()
- double `likelihood` (std::vector< double > &par, bool as\_log=false)
- void `simulate` (std::vector< double > par, int \*y\_out)
- size\_t `get_n_y` () `const`
- size\_t `get_n_obs` () `const`
- size\_t `get_n_covars` () `const`
- size\_t `get_m_order` () `const`
- size\_t `get_n_rows` () `const`
- `const` int \* `get_Y` () `const`
- `const` int \* `get_ID` () `const`

- `const double * get_X () const`
- `barry::FreqTable< int > motif_census (std::vector< size_t > idx)`
- `std::vector< double > logodds (const std::vector< double > &par, size_t i, size_t j)`
- `void set_names (std::vector< std::string > Y_names_, std::vector< std::string > X_names_)`
- `const std::vector< std::string > & get_Y_names ()`
- `const std::vector< std::string > & get_X_names ()`

### 8.20.1 Detailed Description

Definition at line 4 of file defm-bones.hpp.

### 8.20.2 Constructor & Destructor Documentation

#### 8.20.2.1 DEFM()

```
DEFM::DEFM (
    const int * id,
    const int * y,
    const double * x,
    size_t id_length,
    size_t y_ncol,
    size_t x_ncol,
    size_t m_order ) [inline]
```

Definition at line 104 of file defm-meat.hpp.

#### 8.20.2.2 ~DEFM()

```
DEFM::~DEFM ( ) [inline]
```

Definition at line 44 of file defm-bones.hpp.

### 8.20.3 Member Function Documentation

#### 8.20.3.1 get\_ID()

```
const int * DEFM::get_ID ( ) const [inline]
```

Definition at line 259 of file defm-meat.hpp.

### 8.20.3.2 get\_m\_order()

```
size_t DEFM::get_m_order ( ) const [inline]
```

Definition at line 244 of file defm-meat.hpp.

### 8.20.3.3 get\_model()

```
defmcounters::DEFMModel& DEFM::get_model ( ) [inline]
```

Definition at line 46 of file defm-bones.hpp.

### 8.20.3.4 get\_n\_covars()

```
size_t DEFM::get_n_covars ( ) const [inline]
```

Definition at line 239 of file defm-meat.hpp.

### 8.20.3.5 get\_n\_obs()

```
size_t DEFM::get_n_obs ( ) const [inline]
```

Definition at line 234 of file defm-meat.hpp.

### 8.20.3.6 get\_n\_rows()

```
size_t DEFM::get_n_rows ( ) const [inline]
```

Definition at line 249 of file defm-meat.hpp.

### 8.20.3.7 get\_n\_y()

```
size_t DEFM::get_n_y ( ) const [inline]
```

Definition at line 229 of file defm-meat.hpp.

#### 8.20.3.8 get\_X()

```
const double * DEFM::get_X ( ) const [inline]
```

Definition at line 264 of file defm-meat.hpp.

#### 8.20.3.9 get\_X\_names()

```
const std::vector< std::string > & DEFM::get_X_names ( ) [inline]
```

Definition at line 371 of file defm-meat.hpp.

#### 8.20.3.10 get\_Y()

```
const int * DEFM::get_Y ( ) const [inline]
```

Definition at line 254 of file defm-meat.hpp.

#### 8.20.3.11 get\_Y\_names()

```
const std::vector< std::string > & DEFM::get_Y_names ( ) [inline]
```

Definition at line 367 of file defm-meat.hpp.

#### 8.20.3.12 init()

```
void DEFM::init ( ) [inline]
```

Definition at line 188 of file defm-meat.hpp.

#### 8.20.3.13 likelihood()

```
double DEFM::likelihood (
    std::vector< double > & par,
    bool as_log = false )
```

#### 8.20.3.14 logodds()

```
std::vector< double > DEFM::logodds (
    const std::vector< double > & par,
    size_t i,
    size_t j ) [inline]
```

Definition at line 308 of file defm-meat.hpp.

#### 8.20.3.15 motif\_census()

```
barry::FreqTable< int > DEFM::motif_census (
    std::vector< size_t > idx ) [inline]
```

Definition at line 270 of file defm-meat.hpp.

#### 8.20.3.16 set\_names()

```
void DEFM::set_names (
    std::vector< std::string > Y_names_,
    std::vector< std::string > X_names_ ) [inline]
```

Definition at line 350 of file defm-meat.hpp.

#### 8.20.3.17 simulate()

```
void DEFM::simulate (
    std::vector< double > par,
    int * y_out ) [inline]
```

Definition at line 38 of file defm-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/models/defm/[defm-bones.hpp](#)
- include/barry/models/defm/[defm-meat.hpp](#)

## 8.21 DEFMCounterData Class Reference

Data class used to store arbitrary uint or double vectors.

```
#include <defm.hpp>
```

## Public Member Functions

- [DEFMCounterData](#) ()
- [DEFMCounterData](#) ([const](#) std::vector< size\_t > [indices\\_](#), [const](#) std::vector< double > [numbers\\_](#), [const](#) std::vector< bool > [logical\\_](#))
- size\_t [idx](#) (size\_t [i](#)) [const](#)
- double [num](#) (size\_t [i](#)) [const](#)
- bool [is\\_true](#) (size\_t [i](#)) [const](#)
- [~DEFMCounterData](#) ()

## Public Attributes

- std::vector< size\_t > [indices](#)
- std::vector< double > [numbers](#)
- std::vector< bool > [logical](#)

### 8.21.1 Detailed Description

Data class used to store arbitrary uint or double vectors.

Definition at line 75 of file `defm.hpp`.

### 8.21.2 Constructor & Destructor Documentation

#### 8.21.2.1 DEFMCounterData() [1/2]

```
DEFMCounterData::DEFMCounterData ( ) [inline]
```

Definition at line 82 of file `defm.hpp`.

#### 8.21.2.2 DEFMCounterData() [2/2]

```
DEFMCounterData::DEFMCounterData (
    const std::vector< size_t > indices\_,
    const std::vector< double > numbers\_,
    const std::vector< bool > logical\_ ) [inline]
```

Definition at line 83 of file `defm.hpp`.



### 8.21.2.3 ~DEFMCOUNTERDATA()

```
DEFMCOUNTERDATA::~DEFMCOUNTERDATA ( ) [inline]
```

Definition at line 94 of file defm.hpp.

## 8.21.3 Member Function Documentation

### 8.21.3.1 idx()

```
size_t DEFMCOUNTERDATA::idx (
    size_t i ) const [inline]
```

Definition at line 90 of file defm.hpp.

### 8.21.3.2 is\_true()

```
bool DEFMCOUNTERDATA::is_true (
    size_t i ) const [inline]
```

Definition at line 92 of file defm.hpp.

### 8.21.3.3 num()

```
double DEFMCOUNTERDATA::num (
    size_t i ) const [inline]
```

Definition at line 91 of file defm.hpp.

## 8.21.4 Member Data Documentation

### 8.21.4.1 indices

```
std::vector< size_t > DEFMCOUNTERDATA::indices
```

Definition at line 78 of file defm.hpp.

### 8.21.4.2 logical

```
std::vector< bool > DEFMCOUNTERData::logical
```

Definition at line 80 of file defm.hpp.

### 8.21.4.3 numbers

```
std::vector< double > DEFMCOUNTERData::numbers
```

Definition at line 79 of file defm.hpp.


The documentation for this class was generated from the following file:

- include/barry/counters/[defm.hpp](#)

## 8.22 DEFMDData Class Reference

```
#include <defm.hpp>
```

Collaboration diagram for DEFMDData:



### Public Member Functions

- [DEFMDData](#) ()  
*Vector indicating which covariates are included in the model.*
- [DEFMDData](#) ([DEFMArray](#) \*array\_, [const](#) double \*covariates\_, size\_t obs\_start\_, size\_t X\_ncol\_, size\_t X\_nrow\_)  
*Constructor.*
- double [operator\(\)](#) (size\_t i, size\_t j) [const](#)  
*Access to the row (i) column (j) data.*
- double [at](#) (size\_t i, size\_t j) [const](#)
- size\_t [ncol](#) () [const](#)
- size\_t [nrow](#) () [const](#)
- void [print](#) () [const](#)
- [~DEFMDData](#) ()

## Public Attributes

- [DEFMArray](#) \* [array](#)
- [const](#) double \* [covariates](#)  
*Vector of covariates (complete vector)*
- [size\\_t](#) [obs\\_start](#)  
*Index of the observation in the data.*
- [size\\_t](#) [X\\_ncol](#)  
*Number of columns in the array of covariates.*
- [size\\_t](#) [X\\_nrow](#)  
*Number of rows in the array of covariates.*
- [std::vector](#)< [size\\_t](#) > [covar\\_sort](#)
- [std::vector](#)< [size\\_t](#) > [covar\\_used](#)  
*Value where the sorting of the covariates is stored.*

### 8.22.1 Detailed Description

Definition at line 27 of file defm.hpp.

### 8.22.2 Constructor & Destructor Documentation

#### 8.22.2.1 DEFMDData() [1/2]

```
DEFMDData::DEFMDData ( ) [inline]
```

Vector indicating which covariates are included in the model.

Definition at line 38 of file defm.hpp.

#### 8.22.2.2 DEFMDData() [2/2]

```
DEFMDData::DEFMDData (
    DEFMArray * array_,
    const double * covariates_,
    size_t obs_start_,
    size_t X_ncol_,
    size_t X_nrow_ ) [inline]
```

Constructor.

#### Parameters

<a href="#">covariates</a> ↔	Pointer to the attribute data.
<a href="#">obs_start</a> ↔	Location of the current observation in the covariates vector
<a href="#">X_ncol</a>	Number of columns (covariates.)

Definition at line 47 of file defm.hpp.

### 8.22.2.3 ~DEFMData()

```
DEFMData::~DEFMData ( ) [inline]
```

Definition at line 69 of file defm.hpp.

## 8.22.3 Member Function Documentation

### 8.22.3.1 at()

```
double DEFMData::at (
    size_t i,
    size_t j ) const
```

## 8.22.4 Member Data Documentation

### 8.22.4.1 array

```
DEFMArray* DEFMData::array
```

Definition at line 30 of file defm.hpp.

### 8.22.4.2 covar\_sort

```
std::vector< size_t > DEFMData::covar_sort
```

Definition at line 35 of file defm.hpp.

### 8.22.4.3 covar\_used

```
std::vector< size_t > DEFMData::covar_used
```

Value where the sorting of the covariates is stored.

Definition at line 36 of file defm.hpp.

#### 8.22.4.4 covariates

```
const double* DEFMDData::covariates
```

Vector of covariates (complete vector)

Definition at line 31 of file defm.hpp.

#### 8.22.4.5 obs\_start

```
size_t DEFMDData::obs_start
```

Index of the observation in the data.

Definition at line 32 of file defm.hpp.

#### 8.22.4.6 X\_ncol

```
size_t DEFMDData::X_ncol
```

Number of columns in the array of covariates.

Definition at line 33 of file defm.hpp.

#### 8.22.4.7 X\_nrow

```
size_t DEFMDData::X_nrow
```

Number of rows in the array of covariates.

Definition at line 34 of file defm.hpp.

The documentation for this class was generated from the following file:

- [include/barry/counters/defm.hpp](#)

## 8.23 DEFMRuleData Class Reference

```
#include <defm.hpp>
```

Inheritance diagram for DEFMRuleData:



### Public Member Functions

- double [num](#) (size\_t i) **const**
- size\_t [idx](#) (size\_t i) **const**
- bool [is\\_true](#) (size\_t i) **const**
- [DEFMRuleData](#) ()
- [DEFMRuleData](#) (std::vector< double > numbers\_, std::vector< size\_t > indices\_, std::vector< bool > logical\_)
- [DEFMRuleData](#) (std::vector< double > numbers\_, std::vector< size\_t > indices\_)

### Public Attributes

- std::vector< double > [numbers](#)
- std::vector< size\_t > [indices](#)
- std::vector< bool > [logical](#)
- bool [init](#) = [false](#)

#### 8.23.1 Detailed Description

Definition at line 98 of file defm.hpp.

#### 8.23.2 Constructor & Destructor Documentation

### 8.23.2.1 DEFMRuleData() [1/3]

```
DEFMRuleData::DEFMRuleData ( ) [inline]
```

Definition at line 111 of file defm.hpp.

### 8.23.2.2 DEFMRuleData() [2/3]

```
DEFMRuleData::DEFMRuleData (
    std::vector< double > numbers_,
    std::vector< size_t > indices_,
    std::vector< bool > logical_ ) [inline]
```

Definition at line 113 of file defm.hpp.

### 8.23.2.3 DEFMRuleData() [3/3]

```
DEFMRuleData::DEFMRuleData (
    std::vector< double > numbers_,
    std::vector< size_t > indices_ ) [inline]
```

Definition at line 119 of file defm.hpp.

## 8.23.3 Member Function Documentation

### 8.23.3.1 idx()

```
size_t DEFMRuleData::idx (
    size_t i ) const [inline]
```

Definition at line 108 of file defm.hpp.

### 8.23.3.2 is\_true()

```
bool DEFMRuleData::is_true (
    size_t i ) const [inline]
```

Definition at line 109 of file defm.hpp.

### 8.23.3.3 num()

```
double DEFMRuleData::num (
    size_t i ) const [inline]
```

Definition at line 107 of file defm.hpp.

## 8.23.4 Member Data Documentation

### 8.23.4.1 indices

```
std::vector< size_t > DEFMRuleData::indices
```

Definition at line 102 of file defm.hpp.

### 8.23.4.2 init

```
bool DEFMRuleData::init = false
```

Definition at line 105 of file defm.hpp.

### 8.23.4.3 logical

```
std::vector< bool > DEFMRuleData::logical
```

Definition at line 103 of file defm.hpp.

### 8.23.4.4 numbers

```
std::vector< double > DEFMRuleData::numbers
```

Definition at line 101 of file defm.hpp.

The documentation for this class was generated from the following file:


- [include/barry/counters/defm.hpp](#)




## 8.24 DEFMRuleDynData Class Reference

```
#include <defm.hpp>
```

Inheritance diagram for DEFMRuleDynData:



Collaboration diagram for DEFMRuleDynData:



### Public Member Functions

- [DEFMRuleDynData](#) (`const` std::vector< double > \*counts\_, std::vector< double > numbers\_={}, std::vector< size\_t > indices\_={}, std::vector< bool > logical\_={})
- [~DEFMRuleDynData](#) ()

### Public Attributes

- `const` std::vector< double > \* [counts](#)

#### 8.24.1 Detailed Description

Definition at line 133 of file defm.hpp.

## 8.24.2 Constructor & Destructor Documentation

### 8.24.2.1 DEFMRuleDynData()

```
DEFMRuleDynData::DEFMRuleDynData (
    const std::vector< double > * counts_,
    std::vector< double > numbers_ = {},
    std::vector< size_t > indices_ = {},
    std::vector< bool > logical_ = {} ) [inline]
```

Definition at line 137 of file defm.hpp.

### 8.24.2.2 ~DEFMRuleDynData()

```
DEFMRuleDynData::~DEFMRuleDynData ( ) [inline]
```

Definition at line 144 of file defm.hpp.

## 8.24.3 Member Data Documentation

### 8.24.3.1 counts

```
const std::vector< double >* DEFMRuleDynData::counts
```

Definition at line 135 of file defm.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[defm.hpp](#)

## 8.25 Entries< Cell\_Type > Class Template Reference

A wrapper class to store `source`, `target`, `val` from a [BArray](#) object.

```
#include <typedefs.hpp>
```

### Public Member Functions

- [Entries](#) ()
- [Entries](#) (uint n)
- [~Entries](#) ()
- void [resize](#) (uint n)

## Public Attributes

- `std::vector< uint >` [source](#)
- `std::vector< uint >` [target](#)
- `std::vector< Cell_Type >` [val](#)

### 8.25.1 Detailed Description

```
template<typename Cell_Type>
class Entries< Cell_Type >
```

A wrapper class to store `source`, `target`, `val` from a [BArray](#) object.

#### Template Parameters

<i>Cell_Type</i>	Any type
------------------	----------

Definition at line 79 of file `typedefs.hpp`.

### 8.25.2 Constructor & Destructor Documentation

#### 8.25.2.1 Entries() [1/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries ( ) [inline]
```

Definition at line 85 of file `typedefs.hpp`.

#### 8.25.2.2 Entries() [2/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries (
    uint n ) [inline]
```

Definition at line 86 of file `typedefs.hpp`.

#### 8.25.2.3 ~Entries()

```
template<typename Cell_Type >
Entries< Cell_Type >::~~Entries ( ) [inline]
```

Definition at line 93 of file `typedefs.hpp`.

## 8.25.3 Member Function Documentation

### 8.25.3.1 `resize()`

```
template<typename Cell_Type >
void Entries< Cell_Type >::resize (
    uint n ) [inline]
```

Definition at line 95 of file typedefs.hpp.

## 8.25.4 Member Data Documentation

### 8.25.4.1 `source`

```
template<typename Cell_Type >
std::vector< uint > Entries< Cell_Type >::source
```

Definition at line 81 of file typedefs.hpp.

### 8.25.4.2 `target`

```
template<typename Cell_Type >
std::vector< uint > Entries< Cell_Type >::target
```

Definition at line 82 of file typedefs.hpp.

### 8.25.4.3 `val`

```
template<typename Cell_Type >
std::vector< Cell_Type > Entries< Cell_Type >::val
```

Definition at line 83 of file typedefs.hpp.

The documentation for this class was generated from the following file:

- [include/barry/typedefs.hpp](#)

## 8.26 Flock Class Reference

A [Flock](#) is a group of [Geese](#).

```
#include <flock-bones.hpp>
```

### Public Member Functions

- [Flock](#) ()
- [~Flock](#) ()
- unsigned int [add\\_data](#) (std::vector< std::vector< unsigned int > > &annotations, std::vector< unsigned int > &geneid, std::vector< int > &parent, std::vector< bool > &duplication)  
*Add a tree to the flock.*
- void [set\\_seed](#) (const unsigned int &s)  
*Set the seed of the model.*
- void [init](#) (unsigned int bar\_width=[BARRY\\_PROGRESS\\_BAR\\_WIDTH](#))
- [phylocounters::PhyloCounters](#) \* [get\\_counters](#) ()
- [phylocounters::PhyloSupport](#) \* [get\\_support\\_fun](#) ()
- std::vector< std::vector< double > > \* [get\\_stats\\_support](#) ()
- std::vector< std::vector< double > > \* [get\\_stats\\_target](#) ()
- [phylocounters::PhyloModel](#) \* [get\\_model](#) ()
- double [likelihood\\_joint](#) (const std::vector< double > &par, bool as\_log=[false](#), bool use\_reduced\_↔ sequence=true)  
*Returns the joint likelihood of the model.*
- [Geese](#) \* [operator\(\)](#) (unsigned int i, bool [check\\_bounds](#)=true)  
*Access the i-th geese element.*

### Information about the model

- unsigned int [nfuncs](#) () const noexcept
- unsigned int [ntrees](#) () const noexcept
- std::vector< unsigned int > [nnodes](#) () const noexcept
- std::vector< unsigned int > [nleafs](#) () const noexcept
- unsigned int [nterms](#) () const
- unsigned int [support\\_size](#) () const noexcept
- std::vector< std::string > [colnames](#) () const
- unsigned int [parse\\_polytomies](#) (bool verb=true, std::vector< size\_t > \*dist=nullptr) const noexcept  
*Check polytomies and return the largest.*
- void [print](#) () const

### Public Attributes

- std::vector< [Geese](#) > [dat](#)
- unsigned int [nfunctions](#) = 0u
- bool [initialized](#) = false
- std::mt19937 [engine](#)
- [phylocounters::PhyloModel](#) [model](#) = [phylocounters::PhyloModel](#)()

### 8.26.1 Detailed Description

A [Flock](#) is a group of [Geese](#).

This object builds a model with multiple trees ([Geese](#) objects), with all of these using the same `PhyloModel` object. Available counters (terms) can be found in `counter-phylo`.

Definition at line 14 of file `flock-bones.hpp`.

### 8.26.2 Constructor & Destructor Documentation

#### 8.26.2.1 `Flock()`

```
Flock::Flock ( ) [inline]
```

Definition at line 25 of file `flock-bones.hpp`.

#### 8.26.2.2 `~Flock()`

```
Flock::~~Flock ( ) [inline]
```

Definition at line 26 of file `flock-bones.hpp`.

### 8.26.3 Member Function Documentation

#### 8.26.3.1 `add_data()`

```
unsigned int Flock::add_data (
    std::vector< std::vector< unsigned int > > & annotations,
    std::vector< unsigned int > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Add a tree to the flock.

##### Parameters

<i>annotations</i>	see <a href="#">Geese::Geese</a> .
<i>geneid</i>	see <a href="#">Geese</a> .
<i>parent</i>	see <a href="#">Geese</a> .
<i>duplication</i>	see <a href="#">Geese</a> .

**Returns**

unsigned int The number of tree in the model (starting from zero).

Definition at line 6 of file flock-meat.hpp.

**8.26.3.2 colnames()**

```
std::vector< std::string > Flock::colnames ( ) const [inline]
```

Definition at line 224 of file flock-meat.hpp.

**8.26.3.3 get\_counters()**

```
phylocounters::PhyloCounters * Flock::get_counters ( ) [inline]
```

Definition at line 100 of file flock-meat.hpp.

**8.26.3.4 get\_model()**

```
phylocounters::PhyloModel * Flock::get_model ( ) [inline]
```

Definition at line 131 of file flock-meat.hpp.

**8.26.3.5 get\_stats\_support()**

```
std::vector< std::vector< double > > * Flock::get_stats_support ( ) [inline]
```

Definition at line 117 of file flock-meat.hpp.

**8.26.3.6 get\_stats\_target()**

```
std::vector< std::vector< double > > * Flock::get_stats_target ( ) [inline]
```

Definition at line 124 of file flock-meat.hpp.

### 8.26.3.7 get\_support\_fun()

```
phylocounters::PhyloSupport * Flock::get_support_fun ( ) [inline]
```

Definition at line 110 of file flock-meat.hpp.

### 8.26.3.8 init()

```
void Flock::init (
    unsigned int bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 49 of file flock-meat.hpp.

### 8.26.3.9 likelihood\_joint()

```
double Flock::likelihood_joint (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Returns the joint likelihood of the model.

#### Parameters

<i>par</i>	Vector of model parameters.
<i>as_log</i>	When <code>true</code> it will return the value as log.
<i>use_reduced_sequence</i>	When <code>true</code> (default) will compute the likelihood using the reduced sequence, which is faster.

#### Returns

double

Definition at line 138 of file flock-meat.hpp.

### 8.26.3.10 nfuncs()

```
unsigned int Flock::nfuncs ( ) const [inline], [noexcept]
```

Definition at line 167 of file flock-meat.hpp.



### 8.26.3.11 nleafs()

```
std::vector< unsigned int > Flock::nleafs ( ) const [inline], [noexcept]
```

Definition at line 195 of file flock-meat.hpp.

### 8.26.3.12 nnodes()

```
std::vector< unsigned int > Flock::nnodes ( ) const [inline], [noexcept]
```

Definition at line 181 of file flock-meat.hpp.

### 8.26.3.13 nterms()

```
unsigned int Flock::nterms ( ) const [inline]
```

Definition at line 209 of file flock-meat.hpp.

### 8.26.3.14 ntrees()

```
unsigned int Flock::ntrees ( ) const [inline], [noexcept]
```

Definition at line 174 of file flock-meat.hpp.

### 8.26.3.15 operator>()()

```
Geese * Flock::operator() (
    unsigned int i,
    bool check_bounds = true ) [inline]
```

Access the i-th geese element.

#### Parameters

<i>i</i>	Element to access
<i>check_bounds</i>	When true, it will check bounds.

#### Returns

Geese\*

Definition at line 302 of file flock-meat.hpp.

#### 8.26.3.16 parse\_polytomies()

```
unsigned int Flock::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 231 of file flock-meat.hpp.

#### 8.26.3.17 print()

```
void Flock::print ( ) const [inline]
```

Definition at line 258 of file flock-meat.hpp.

#### 8.26.3.18 set\_seed()

```
void Flock::set_seed (
    const unsigned int & s ) [inline]
```

Set the seed of the model.

##### Parameters

s	Passed to the <code>engine.seed()</code> member object.
---	---

Definition at line 42 of file flock-meat.hpp.

#### 8.26.3.19 support\_size()

```
unsigned int Flock::support_size ( ) const [inline], [noexcept]
```

Definition at line 217 of file flock-meat.hpp.

### 8.26.4 Member Data Documentation

#### 8.26.4.1 dat

```
std::vector< Geese > Flock::dat
```

Definition at line 17 of file flock-bones.hpp.

#### 8.26.4.2 initialized

```
bool Flock::initialized = false
```

Definition at line 19 of file flock-bones.hpp.

#### 8.26.4.3 model

```
phylocounters::PhyloModel Flock::model = phylocounters::PhyloModel()
```

Definition at line 23 of file flock-bones.hpp.

#### 8.26.4.4 nfunctions

```
unsigned int Flock::nfunctions = 0u
```

Definition at line 18 of file flock-bones.hpp.

#### 8.26.4.5 engine

```
std::mt19937 Flock::engine
```

Definition at line 22 of file flock-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/models/geese/flock-bones.hpp](#)
- [include/barry/models/geese/flock-meat.hpp](#)

## 8.27 FreqTable< T > Class Template Reference

Frequency table of vectors.

```
#include <freqtable.hpp>
```

## Public Member Functions

- [FreqTable](#) ()
  - [~FreqTable](#) ()
  - [size\\_t add](#) ([const](#) std::vector< T > &x, [size\\_t](#) \*h\_precomp)
  - [Counts\\_type as\\_vector](#) () [const](#)
  - [const](#) std::vector< double > & [get\\_data](#) () [const](#)
  - [const](#) std::unordered\_map< [size\\_t](#), [size\\_t](#) > & [get\\_index](#) () [const](#)
  - void [clear](#) ()
  - void [reserve](#) ([size\\_t](#) n, [size\\_t](#) k)
  - void [print](#) () [const](#)
  - [size\\_t size](#) () [const](#) [noexcept](#)
- Number of unique elements in the table. (.*
- [size\\_t make\\_hash](#) ([const](#) std::vector< T > &x) [const](#)

### 8.27.1 Detailed Description

```
template<typename T = double>
class FreqTable< T >
```

Frequency table of vectors.

This is mostly used in [Support](#). The main data is contained in the `data` double vector. The matrix is stored in a row-wise fashion, where the first element is the frequency with which the vector is observed.

For example, in a model with `k` terms the first `k + 1` elements of `data` would be:

- weights
- term 1
- term 2
- ...
- term k

Definition at line 22 of file `freqtable.hpp`.

### 8.27.2 Constructor & Destructor Documentation

#### 8.27.2.1 FreqTable()

```
template<typename T = double>
FreqTable< T >::FreqTable ( ) [inline]
```

Definition at line 34 of file `freqtable.hpp`.

### 8.27.2.2 ~FreqTable()

```
template<typename T = double>
FreqTable< T >::~~FreqTable ( ) [inline]
```

Definition at line 35 of file freqtable.hpp.

## 8.27.3 Member Function Documentation

### 8.27.3.1 add()

```
template<typename T >
size_t FreqTable< T >::add (
    const std::vector< T > & x,
    size_t * h_precomp ) [inline]
```

Definition at line 59 of file freqtable.hpp.

### 8.27.3.2 as\_vector()

```
template<typename T >
Counts_type FreqTable< T >::as_vector [inline]
```

Definition at line 139 of file freqtable.hpp.

### 8.27.3.3 clear()

```
template<typename T >
void FreqTable< T >::clear [inline]
```

Definition at line 168 of file freqtable.hpp.

### 8.27.3.4 get\_data()

```
template<typename T = double>
const std::vector< double > FreqTable< T >::get_data ( ) const [inline]
```

Definition at line 40 of file freqtable.hpp.

### 8.27.3.5 get\_index()

```
template<typename T = double>
const std::unordered_map<size_t, size_t>& FreqTable< T >::get_index ( ) const [inline]
```

Definition at line 41 of file freqtable.hpp.

### 8.27.3.6 make\_hash()

```
template<typename T >
size_t FreqTable< T >::make_hash (
    const std::vector< T > & x ) const [inline]
```

Definition at line 239 of file freqtable.hpp.

### 8.27.3.7 print()

```
template<typename T >
void FreqTable< T >::print [inline]
```

Definition at line 204 of file freqtable.hpp.

### 8.27.3.8 reserve()

```
template<typename T >
void FreqTable< T >::reserve (
    size_t n,
    size_t k ) [inline]
```

Definition at line 182 of file freqtable.hpp.

### 8.27.3.9 size()

```
template<typename T >
size_t FreqTable< T >::size [inline], [noexcept]
```

Number of unique elements in the table. (.

#### Returns

size\_t

Definition at line 231 of file freqtable.hpp.

The documentation for this class was generated from the following file:

- [include/barry/freqtable.hpp](#)

## 8.28 Geese Class Reference

Annotated Phylo [Model](#).

```
#include <geese-bones.hpp>
```

### Public Member Functions

- [~Geese](#) ()
- void [init](#) (unsigned int bar\_width=[BARRY\\_PROGRESS\\_BAR\\_WIDTH](#))
- void [inherit\\_support](#) (const [Geese](#) &model\_, bool delete\_support\_[=false](#))
- void [calc\\_sequence](#) ([Node](#) \*n=nullptr)
- void [calc\\_reduced\\_sequence](#) ()
- double [likelihood](#) (const std::vector< double > &par, bool as\_log=[false](#), bool use\_reduced\_sequence=true)
- double [likelihood\\_exhaust](#) (const std::vector< double > &par)
- std::vector< double > [get\\_probabilities](#) () const
- void [set\\_seed](#) (const unsigned int &s)
- std::vector< std::vector< unsigned int > > & [simulate](#) (const std::vector< double > &par)
- std::vector< std::vector< double > > & [observed\\_counts](#) ()
- void [print\\_observed\\_counts](#) ()
- void [print](#) () const
 

*Prints information about the GEESE.*
- void [init\\_node](#) ([Node](#) &n)
- void [update\\_annotations](#) (unsigned int nodeid, std::vector< unsigned int > newann)
- std::vector< std::vector< bool > > & [get\\_states](#) () const
 

*Powerset of a gene's possible states.*
- std::vector< unsigned int > & [get\\_annotated\\_nodes](#) () const
 

*Returns the ids of the nodes with at least one annotation.*

### Construct a new Geese object

The model includes a total of  $N + 1$  nodes, the  $+ 1$  beign the root node.

#### Parameters

annotations	A vector of vectors with annotations. It should be of length $k$ (number of functions). Each vector should be of length $N$ (equal to the number of nodes, including interior). Possible values are 0, 1, and 9.
geneid	Id of the gene. It should be of length $N$ .
parent	Id of the parent gene. Also of length $N$
duplication	Logical scalar indicating the type of event (true: duplication, false: speciation.)

The ordering of the entries does not matter. Passing the nodes in post order or not makes no difference to the constructor.

- [Geese](#) ()
- [Geese](#) (std::vector< std::vector< unsigned int > > &annotations, std::vector< unsigned int > &geneid, std::vector< int > &parent, std::vector< bool > &duplication)
- [Geese](#) (const [Geese](#) &model\_, bool copy\_data=true)
- [Geese](#) ([Geese](#) &&x) noexcept
- [Geese](#) & operator= (const [Geese](#) &model\_)=delete
- [Geese](#) & operator= ([Geese](#) &&model\_) noexcept=delete

### Information about the model



*Parameters*

verb	When <i>true</i> it will print out information about the encountered polytomies.
------	--

- unsigned int `nfuncs` () `const noexcept`  
Number of functions analyzed.
- unsigned int `nnodes` () `const noexcept`  
Number of nodes (interior + leaf)
- unsigned int `nleafs` () `const noexcept`  
Number of leaf.
- unsigned int `nterms` () `const`  
Number of terms included.
- unsigned int `support_size` () `const noexcept`  
Number of unique sets of sufficient stats.
- `std::vector< unsigned int >` `nannotations` () `const noexcept`  
Number of annotations.
- `std::vector< std::string >` `colnames` () `const`  
Names of the terms in the model.
- unsigned int `parse_polytomies` (bool verb=*true*, `std::vector< size_t >` \*dist=nullptr) `const noexcept`  
Check polytomies and return the largest.

**Geese prediction***Calculate the conditional probability**Parameters*

par	Vector of parameters (terms + root).
res_prob	Vector indicating each nodes' state probability.
leave_one_out	When <i>true</i> , it will compute the predictions using leave-one-out, thus the prediction will be repeated <i>nleaf</i> times.
only_annotated	When <i>true</i> , it will make the predictions only on the induced sub-tree with annotated leafs.
use_reduced_sequence	Passed to the <i>likelihood</i> method.
preorder	For the tree traversal.

When *res\_prob* is specified, the function will attach the member vector probabilities from the *Nodes* objects. This contains the probability that the *ith* node has either of the possible states.

*Returns*

`std::vector< double >` Returns the posterior probability

- `std::vector< std::vector< double > >` `predict` (`const` `std::vector< double >` &par, `std::vector< std::vector< double > >` \*res\_prob=nullptr, bool leave\_one\_out=*false*, bool only\_annotated=*false*, bool use\_reduced\_sequence=*true*)
- `std::vector< std::vector< double > >` `predict_backend` (`const` `std::vector< double >` &par, bool use\_reduced\_sequence, `const` `std::vector< uint >` &preorder)
- `std::vector< std::vector< double > >` `predict_exhaust_backend` (`const` `std::vector< double >` &par, `const` `std::vector< uint >` &preorder)
- `std::vector< std::vector< double > >` `predict_exhaust` (`const` `std::vector< double >` &par)
- `std::vector< std::vector< double > >` `predict_sim` (`const` `std::vector< double >` &par, bool only\_annotated=*false*, unsigned int nsims=10000u)

**Non-const pointers to shared objects in `<tt>Geese</tt>`**

These functions provide direct access to some member objects that are shared by the nodes within *Geese*.

**Returns**

*`get_engine()` returns the Pseudo-RNG engine used.*  
*`get_counters()` returns the vector of counters used.*  
*`get_model()` returns the [Model](#) object used.*  
*`get_support_fun()` returns the computed support of the model.*

- `std::mt19937 * get\_engine ()`
- `phylocounters::PhyloCounters * get\_counters ()`
- `phylocounters::PhyloModel * get\_model ()`
- `phylocounters::PhyloSupport * get\_support\_fun ()`

**Public Attributes**

- unsigned int [nfunctions](#)
- `std::map< unsigned int, Node > nodes`
- `barry::MapVec_type< unsigned int > map\_to\_nodes`
- `std::vector< std::vector< std::vector< size_t > > > pset\_loc`  
*Locations of columns.*
- `std::vector< unsigned int > sequence`
- `std::vector< unsigned int > reduced\_sequence`
- bool [initialized](#) = `false`
- bool [delete\\_engine](#) = `false`
- bool [delete\\_support](#) = `false`

**8.28.1 Detailed Description**

Annotated Phylo [Model](#).

A list of available terms for this model can be found in the [Phylo counters](#) section.

Definition at line 82 of file `geese-bones.hpp`.

**8.28.2 Constructor & Destructor Documentation****8.28.2.1 Geese() [1/4]**

```
Geese::Geese ( ) [inline]
```

Definition at line 6 of file `geese-meat-constructors.hpp`.

### 8.28.2.2 Geese() [2/4]

```
Geese::Geese (
    std::vector< std::vector< unsigned int > > & annotations,
    std::vector< unsigned int > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Definition at line 20 of file geese-meat-constructors.hpp.

### 8.28.2.3 Geese() [3/4]

```
Geese::Geese (
    const Geese & model_,
    bool copy_data = true ) [inline]
```

Definition at line 214 of file geese-meat-constructors.hpp.

### 8.28.2.4 Geese() [4/4]

```
Geese::Geese (
    Geese && x ) [inline], [noexcept]
```

Definition at line 293 of file geese-meat-constructors.hpp.

### 8.28.2.5 ~Geese()

```
Geese::~Geese ( ) [inline]
```

Definition at line 91 of file geese-meat.hpp.

## 8.28.3 Member Function Documentation

### 8.28.3.1 calc\_reduced\_sequence()

```
void Geese::calc_reduced_sequence ( ) [inline]
```

Definition at line 330 of file geese-meat.hpp.

### 8.28.3.2 calc\_sequence()

```
void Geese::calc_sequence (
    Node * n = nullptr ) [inline]
```

Definition at line 286 of file geese-meat.hpp.

### 8.28.3.3 colnames()

```
std::vector< std::string > Geese::colnames ( ) const [inline]
```

Names of the terms in the model.

Definition at line 452 of file geese-meat.hpp.

### 8.28.3.4 get\_annotated\_nodes()

```
std::vector< unsigned int > Geese::get_annotated_nodes ( ) const [inline]
```

Returns the ids of the nodes with at least one annotation.

Definition at line 668 of file geese-meat.hpp.

### 8.28.3.5 get\_counters()

```
phylocounters::PhyloCounters * Geese::get_counters ( ) [inline]
```

Definition at line 651 of file geese-meat.hpp.

### 8.28.3.6 get\_model()

```
phylocounters::PhyloModel * Geese::get_model ( ) [inline]
```

Definition at line 656 of file geese-meat.hpp.

### 8.28.3.7 get\_probabilities()

```
std::vector< double > Geese::get_probabilities ( ) const [inline]
```

Definition at line 378 of file geese-meat.hpp.

### 8.28.3.8 get\_engine()

```
std::mt19937 * Geese::get_engine ( ) [inline]
```

Definition at line 646 of file geese-meat.hpp.

### 8.28.3.9 get\_states()

```
std::vector< std::vector< bool > > Geese::get_states ( ) const [inline]
```

Powerset of a gene's possible states.

This list of vectors is used throughout [Geese](#). It lists all possible combinations of functional states for any gene. Thus, for  $P$  functions, there will be  $2^P$  possible combinations.

#### Returns

`std::vector< std::vector< bool > >` of length  $2^P$ .

Definition at line 664 of file geese-meat.hpp.

### 8.28.3.10 get\_support\_fun()

```
phylocounters::PhyloSupport * Geese::get_support_fun ( ) [inline]
```

Definition at line 660 of file geese-meat.hpp.

### 8.28.3.11 inherit\_support()

```
void Geese::inherit_support (
    const Geese & model_,
    bool delete_support_ = false ) [inline]
```

Definition at line 229 of file geese-meat.hpp.

### 8.28.3.12 init()

```
void Geese::init (
    unsigned int bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 103 of file geese-meat.hpp.

### 8.28.3.13 init\_node()

```
void Geese::init_node (
    Node & n ) [inline]
```

Definition at line 6 of file geese-meat.hpp.

### 8.28.3.14 likelihood()

```
double Geese::likelihood (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 6 of file geese-meat-likelihood.hpp.

### 8.28.3.15 likelihood\_exhaust()

```
double Geese::likelihood_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 7 of file geese-meat-likelihood\_exhaust.hpp.

### 8.28.3.16 nannotations()

```
std::vector< unsigned int > Geese::nannotations ( ) const [inline], [noexcept]
```

Number of annotations.

Definition at line 443 of file geese-meat.hpp.

### 8.28.3.17 nfuncs()

```
unsigned int Geese::nfuncs ( ) const [inline], [noexcept]
```

Number of functions analyzed.

Definition at line 399 of file geese-meat.hpp.

**8.28.3.18 nleafs()**

```
unsigned int Geese::nleafs ( ) const [inline], [noexcept]
```

Number of leaf.

Definition at line 413 of file geese-meat.hpp.

**8.28.3.19 nnodes()**

```
unsigned int Geese::nnodes ( ) const [inline], [noexcept]
```

Number of nodes (interior + leaf)

Definition at line 406 of file geese-meat.hpp.

**8.28.3.20 nterms()**

```
unsigned int Geese::nterms ( ) const [inline]
```

Number of terms included.

Definition at line 425 of file geese-meat.hpp.

**8.28.3.21 observed\_counts()**

```
std::vector< std::vector< double > > Geese::observed_counts ( ) [inline]
```

Definition at line 494 of file geese-meat.hpp.

**8.28.3.22 operator=() [1/2]**

```
Geese& Geese::operator= (
    const Geese & model_ ) [delete]
```

**8.28.3.23 operator=() [2/2]**

```
Geese& Geese::operator= (
    Geese && model_ ) [delete], [noexcept]
```

#### 8.28.3.24 parse\_polytomies()

```
unsigned int Geese::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 459 of file geese-meat.hpp.

#### 8.28.3.25 predict()

```
std::vector< std::vector< double > > Geese::predict (
    const std::vector< double > & par,
    std::vector< std::vector< double > > * res_prob = nullptr,
    bool leave_one_out = false,
    bool only_annotated = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 243 of file geese-meat-predict.hpp.

#### 8.28.3.26 predict\_backend()

```
std::vector< std::vector< double > > Geese::predict_backend (
    const std::vector< double > & par,
    bool use_reduced_sequence,
    const std::vector< uint > & preorder ) [inline]
```

< True if the array belongs to the set

Definition at line 6 of file geese-meat-predict.hpp.

#### 8.28.3.27 predict\_exhaust()

```
std::vector< std::vector< double > > Geese::predict_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 5 of file geese-meat-predict\_exhaust.hpp.



### 8.28.3.28 predict\_exhaust\_backend()

```
std::vector< std::vector< double > > Geese::predict_exhaust_backend (
    const std::vector< double > & par,
    const std::vector< uint > & preorder ) [inline]
```

Definition at line 47 of file geese-meat-predict\_exhaust.hpp.

### 8.28.3.29 predict\_sim()

```
std::vector< std::vector< double > > Geese::predict_sim (
    const std::vector< double > & par,
    bool only_annotated = false,
    unsigned int nsims = 10000u ) [inline]
```

Definition at line 6 of file geese-meat-predict\_sim.hpp.

### 8.28.3.30 print()

```
void Geese::print ( ) const [inline]
```

Prints information about the GEESE.

Definition at line 628 of file geese-meat.hpp.

### 8.28.3.31 print\_observed\_counts()

```
void Geese::print_observed_counts ( ) [inline]
```

Definition at line 565 of file geese-meat.hpp.

### 8.28.3.32 set\_seed()

```
void Geese::set_seed (
    const unsigned int & s ) [inline]
```

Definition at line 4 of file geese-meat-simulate.hpp.

### 8.28.3.33 simulate()

```
std::vector< std::vector< unsigned int > > Geese::simulate (
    const std::vector< double > & par ) [inline]
```

Definition at line 8 of file geese-meat-simulate.hpp.

### 8.28.3.34 support\_size()

```
unsigned int Geese::support_size ( ) const [inline], [noexcept]
```

Number of unique sets of sufficient stats.

Definition at line 433 of file geese-meat.hpp.

### 8.28.3.35 update\_annotations()

```
void Geese::update_annotations (
    unsigned int nodeid,
    std::vector< unsigned int > newann ) [inline]
```

Definition at line 257 of file geese-meat.hpp.

## 8.28.4 Member Data Documentation

### 8.28.4.1 delete\_engine

```
bool Geese::delete_engine = false
```

Definition at line 120 of file geese-bones.hpp.

### 8.28.4.2 delete\_support

```
bool Geese::delete_support = false
```

Definition at line 121 of file geese-bones.hpp.

### 8.28.4.3 initialized

```
bool Geese::initialized = false
```

Definition at line 119 of file geese-bones.hpp.

### 8.28.4.4 map\_to\_nodes

```
barry::MapVec_type< unsigned int > Geese::map_to_nodes
```

Definition at line 111 of file geese-bones.hpp.

### 8.28.4.5 nfunctions

```
unsigned int Geese::nfunctions
```

Definition at line 109 of file geese-bones.hpp.

### 8.28.4.6 nodes

```
std::map< unsigned int, Node > Geese::nodes
```

Definition at line 110 of file geese-bones.hpp.

### 8.28.4.7 pset\_loc

```
std::vector< std::vector< std::vector< size_t > > > Geese::pset_loc
```

Locations of columns.

Definition at line 112 of file geese-bones.hpp.

### 8.28.4.8 reduced\_sequence

```
std::vector< unsigned int > Geese::reduced_sequence
```

Definition at line 116 of file geese-bones.hpp.

### 8.28.4.9 sequence

```
std::vector< unsigned int > Geese::sequence
```

Definition at line 115 of file geese-bones.hpp.

The documentation for this class was generated from the following files:


- include/barry/models/geese/geese-bones.hpp
- include/barry/models/geese/geese-meat-constructors.hpp
- include/barry/models/geese/geese-meat-likelihood.hpp
- include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp
- include/barry/models/geese/geese-meat-predict.hpp
- include/barry/models/geese/geese-meat-predict\_exhaust.hpp
- include/barry/models/geese/geese-meat-predict\_sim.hpp
- include/barry/models/geese/geese-meat-simulate.hpp
- include/barry/models/geese/geese-meat.hpp

## 8.29 Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > Class Template Reference

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

```
#include <model-bones.hpp>
```

Collaboration diagram for Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >:



## Public Member Functions

- void [set\\_engine](#) (std::mt19937 \*engine\_, bool delete\_=false)
- void [set\\_seed](#) (unsigned int s)
- [Model](#) ()
- [Model](#) (uint size\_)
- [Model](#) (const [Model](#)< Array\_Type, [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > &Model\_)
- [Model](#)< Array\_Type, [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > & [operator=](#) (const [Model](#)< Array\_Type, [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > &Model\_)
- [~Model](#) ()
- void [store\\_psets](#) () noexcept
- std::vector< double > [gen\\_key](#) (const Array\_Type &Array\_)
- [uint](#) [add\\_array](#) (const Array\_Type &Array\_, bool force\_new=false)  
*Adds an array to the support of not already included.*
- void [print\\_stats](#) (uint i) const
- void [print](#) () const  
*Prints information about the model.*
- Array\_Type [sample](#) (const Array\_Type &Array\_, const std::vector< double > &params={})
- Array\_Type [sample](#) (const uint &i, const std::vector< double > &params)
- double [conditional\\_prob](#) (const Array\_Type &Array\_, const std::vector< double > &params, unsigned int i, unsigned int j)  
*Conditional probability ("Gibbs sampler")*
- const std::mt19937 \* [get\\_engine](#) () const
- [Counters](#)< Array\_Type, [Data\\_Counter\\_Type](#) > \* [get\\_counters](#) ()
- [Rules](#)< Array\_Type, [Data\\_Rule\\_Type](#) > \* [get\\_rules](#) ()
- [Rules](#)< Array\_Type, [Data\\_Rule\\_Dyn\\_Type](#) > \* [get\\_rules\\_dyn](#) ()
- [Support](#)< Array\_Type, [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > \* [get\\_support\\_fun](#) ()

### Wrappers for the `<tt>Counters</tt>` member.

*These will add counters to the model, which are shared by the support and the actual counter function.*

- void [add\\_counter](#) ([Counter](#)< Array\_Type, [Data\\_Counter\\_Type](#) > &counter)
- void [add\\_counter](#) ([Counter\\_fun\\_type](#)< Array\_Type, [Data\\_Counter\\_Type](#) > count\_fun\_, [Counter\\_fun\\_type](#)< Array\_Type, [Data\\_Counter\\_Type](#) > init\_fun\_=nullptr, [Data\\_Counter\\_Type](#) data\_=nullptr)
- void [set\\_counters](#) ([Counters](#)< Array\_Type, [Data\\_Counter\\_Type](#) > \*counters\_)
- void [add\\_hasher](#) ([Hasher\\_fun\\_type](#)< Array\_Type, [Data\\_Counter\\_Type](#) > fun\_)

### Wrappers for the `<tt>Rules</tt>` member.

*These will add rules to the model, which are shared by the support and the actual counter function.*

- void [add\\_rule](#) ([Rule](#)< Array\_Type, [Data\\_Rule\\_Type](#) > &rule)
- void [add\\_rule](#) ([Rule\\_fun\\_type](#)< Array\_Type, [Data\\_Rule\\_Type](#) > count\_fun\_, [Data\\_Rule\\_Type](#) data\_)
- void [set\\_rules](#) ([Rules](#)< Array\_Type, [Data\\_Rule\\_Type](#) > \*rules\_)
- void [add\\_rule\\_dyn](#) ([Rule](#)< Array\_Type, [Data\\_Rule\\_Dyn\\_Type](#) > &rule)
- void [add\\_rule\\_dyn](#) ([Rule\\_fun\\_type](#)< Array\_Type, [Data\\_Rule\\_Dyn\\_Type](#) > count\_fun\_, [Data\\_Rule\\_Dyn\\_Type](#) data\_)
- void [set\\_rules\\_dyn](#) ([Rules](#)< Array\_Type, [Data\\_Rule\\_Dyn\\_Type](#) > \*rules\_)

### Likelihood functions.

*Calculation of likelihood functions is done reusing normalizing constants. Before recalculating the normalizing constant, the function checks whether `params` matches the last set vector of parameters used to compute it.*

*Parameters*

params	<i>Vector of parameters</i>
as_log	<i>When <code>true</code>, the function returns the log-likelihood.</i>

- double `likelihood` (`const` `std::vector< double >` &params, `const` `uint` &i, `bool` as\_log=`false`)
- double `likelihood` (`const` `std::vector< double >` &params, `const` `Array_Type` &Array\_, `int` i=-1, `bool` as\_log=`false`)
- double `likelihood` (`const` `std::vector< double >` &params, `const` `std::vector< double >` &target\_, `const` `uint` &i, `bool` as\_log=`false`)
- double `likelihood` (`const` `std::vector< double >` &params, `const` `double` \*target\_, `const` `uint` &i, `bool` as\_log=`false`)
- double `likelihood_total` (`const` `std::vector< double >` &params, `bool` as\_log=`false`)

**Extract elements by index***Parameters*

i	<i>Index relative to the array in the model.</i>
params	<i>A new vector of model parameters to compute the normalizing constant.</i>
as_log	<i>When <code>true</code> returns the logged version of the normalizing constant.</i>

- double `get_norm_const` (`const` `std::vector< double >` &params, `const` `uint` &i, `bool` as\_log=`false`)
- `const` `std::vector< Array_Type >` \* `get_pset` (`const` `uint` &i)
- `const` `std::vector< double >` \* `get_pset_stats` (`const` `uint` &i)

**Size of the model**

*Number of different supports included in the model*

*This will return the size of `stats_target`.*

*Returns*

`size()` *returns the number of arrays in the model.*

`size_unique()` *returns the number of unique arrays (according to the hasher) in the model.*

`nterms()` *returns the number of terms in the model.*

- unsigned int `size()` `const` `noexcept`
- unsigned int `size_unique()` `const` `noexcept`
- unsigned int `nterms()` `const` `noexcept`
- unsigned int `nrules()` `const` `noexcept`
- unsigned int `nrules_dyn()` `const` `noexcept`
- unsigned int `support_size()` `const` `noexcept`
- `std::vector< std::string >` `colnames()` `const`
- `std::vector< std::vector< double > >` \* `get_stats_target()`  
*Raw pointers to the support and target statistics.*
- `std::vector< std::vector< double > >` \* `get_stats_support()`
- `std::vector< unsigned int >` \* `get_arrays2support()`
- `std::vector< std::vector< Array_Type > >` \* `get_pset_arrays()`
- `std::vector< std::vector< double > >` \* `get_pset_stats()`  
*Statistics of the support(s)*

- `std::vector< std::vector< double > > * get_pset_probs ()`
- `void set_transform_model (std::function< std::vector< double >(double *, unsigned int)> fun, std::vector< std::string > names)`  
*Set the transform\_model\_fun object.*
- `std::vector< double > transform_model (double *data, unsigned int k)`

## Protected Attributes

- `MapVec_type< double, uint > keys2support`  
*Map of types of arrays to support sets.*
- `std::vector< std::vector< double > > params_last`  
*Vector of the previously used parameters.*
- `std::vector< double > normalizing_constants`
- `std::vector< bool > first_calc_done`
- `bool delete_counters = false`
- `bool delete_rules = false`
- `bool delete_rules_dyn = false`
- `std::function< std::vector< double >double *, unsigned int k)> transform_model_fun = nullptr`  
*Transformation of the model.*
- `std::vector< std::string > transform_model_term_names`

## Random number generation

*Random number generation*

- `std::mt19937 * rengine = nullptr`
- `bool delete_rengine = false`

## Information about the arrays used in the model

*stats\_target holds the observed sufficient statistics for each array in the dataset. array\_↔ frequency contains the frequency with which each of the target stats\_target (arrays) shows in the support. array2support maps array indices (0, 1, ...) to the corresponding support.*

*Each vector of stats\_support has the data stored in a row-wise order, with each row starting with the weights, e.g., in a model with k terms the first k + 1 elements of stats\_support would be:*

- *weights*
- *term 1*
- *term 2*
- *...*
- *term k*
- `std::vector< std::vector< double > > stats_support`  
*Sufficient statistics of the model (support)*
- `std::vector< uint > stats_support_n_arrays`  
*Number of arrays included per support.*
- `std::vector< std::vector< double > > stats_target`  
*Target statistics of the model.*
- `std::vector< uint > arrays2support`

### Container space for the powerset (and its sufficient stats\_target)

This is useful in the case of using simulations or evaluating functions that need to account for the full set of states.

- bool `with_pset = false`
- `std::vector< std::vector< Array_Type > >` `pset_arrays`  
Arrays of the support(s)
- `std::vector< std::vector< double > >` `pset_stats`  
Statistics of the support(s)
- `std::vector< std::vector< double > >` `pset_probs`  
Probabilities of the support(s)

### Functions to compute statistics

Arguments are recycled to save memory and computation.

- `Counters< Array_Type, Data_Counter_Type > * counters`
- `Rules< Array_Type, Data_Rule_Type > * rules`
- `Rules< Array_Type, Data_Rule_Dyn_Type > * rules_dyn`
- `Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >` `support_fun`
- `StatsCounter< Array_Type, Data_Counter_Type >` `counter_fun`

## 8.29.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename
Data_Rule_Dyn_Type = bool>
class Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

$$\frac{\exp\left(\theta^t c(A)\right)}{\sum_{A' \in \mathcal{A}} \exp\left(\theta^t c(A')\right)}$$

This implementation aims to reduce the number of times that the support needs to be computed. Models included here use more than a single array, and thus allow the function to recycle support sets as needed. For example, if we are looking at directed graphs all of the same size and without vertex level features, i.e. a model that only counts edges, triangles, etc. then the support needs to be fully computed only once.

#### Template Parameters

<i>Array_Type</i>	Class of <code>BArray</code> object.
<i>Data_Counter_Type</i>	Any type.
<i>Data_Rule_Type</i>	Any type.

Definition at line 34 of file `model-bones.hpp`.

## 8.29.2 Constructor & Destructor Documentation



**8.29.2.1 Model() [1/3]**

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model [inline]
```

Definition at line 96 of file model-meat.hpp.

**8.29.2.2 Model() [2/3]**

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model (
    uint size_ ) [inline]
```

Definition at line 130 of file model-meat.hpp.

**8.29.2.3 Model() [3/3]**

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
    & Model_ ) [inline]
```

Definition at line 168 of file model-meat.hpp.

**8.29.2.4 ~Model()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~Model ( ) [inline]
```

Definition at line 159 of file model-bones.hpp.

**8.29.3 Member Function Documentation****8.29.3.1 add\_array()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_array (
    const Array_Type & Array_,
    bool force_new = false )
```

Adds an array to the support of not already included.

## Parameters

<i>Array_</i>	array to be added
<i>force_new</i>	If false, it will use <code>keygen</code> to obtain a double vector and create a hash of it. If the hash has been computed earlier, the support is recycled.

## Returns

The number of the array.

**8.29.3.2 add\_counter() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter< Array_Type, Data_Counter_Type > & counter )
```

**8.29.3.3 add\_counter() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Counter_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Counter_Type > init_fun_ = nullptr,
    Data_Counter_Type data_ = nullptr )
```

**8.29.3.4 add\_hasher()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_hasher (
    Hasher_fun_type< Array_Type, Data_Counter_Type > fun_ )
```

**8.29.3.5 add\_rule() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > & rule )
```

### 8.29.3.6 add\_rule() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ )
```

### 8.29.3.7 add\_rule\_dyn() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule< Array_Type, Data_Rule_Dyn_Type > & rule )
```

### 8.29.3.8 add\_rule\_dyn() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule_fun_type< Array_Type, Data_Rule_Dyn_Type > count_fun_,
    Data_Rule_Dyn_Type data_ )
```

### 8.29.3.9 colnames()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::string > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_↵
Dyn_Type >::colnames ( ) const
```

### 8.29.3.10 conditional\_prob()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::conditional_↵
_prob (
    const Array_Type & Array_,
    const std::vector< double > & params,
    unsigned int i,
    unsigned int j )
```

Conditional probability ("Gibbs sampler")

Computes the conditional probability of observing  $P\{Y(i,j) = Y^C, \theta\}$ , i.e., the probability of observing the entry  $Y(i,j)$  equal to one given the rest of the array.

## Parameters

<i>Array</i> ↔ —	Array to check
<i>params</i>	Vector of parameters
<i>i</i>	Row entry
<i>j</i>	Column entry

## Returns

double The conditional probability

## 8.29.3.11 gen\_key()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↔
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↔
Type >::gen_key (
    const Array_Type & Array_ )
```

## 8.29.3.12 get\_arrays2support()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↔
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< unsigned int >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↔
Rule_Dyn_Type >::get_arrays2support ( )
```

## 8.29.3.13 get\_counters()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↔
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Counters<Array_Type, Data_Counter_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_counters ( )
```

## 8.29.3.14 get\_norm\_const()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↔
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_norm_↔
const (
    const std::vector< double > & params,
    const uint & i,
    bool as_log = false )
```

### 8.29.3.15 get\_pset()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< Array_Type >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset (
    const uint & i )
```

### 8.29.3.16 get\_pset\_arrays()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< Array_Type > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_arrays ( )
```

### 8.29.3.17 get\_pset\_probs()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_probs ( )
```

### 8.29.3.18 get\_pset\_stats() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_stats ( )
```

Statistics of the support(s)

### 8.29.3.19 get\_pset\_stats() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< double >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_pset_stats (
    const uint & i )
```

**8.29.3.20 get\_engine()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::mt19937* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::get_engine ( ) const
```

**8.29.3.21 get\_rules()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
_Rule_Dyn_Type >::get_rules ( )
```

**8.29.3.22 get\_rules\_dyn()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn ( )
```

**8.29.3.23 get\_stats\_support()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_stats_support ( )
```

**8.29.3.24 get\_stats\_target()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_stats_target ( )
```

Raw pointers to the support and target statistics.

The support of the model is stored as a vector of vector<double>. Each element of it contains the support for an specific type of array included. It represents an array of size  $(k + 1) \times n$  unique elements, with the data stored by-row. The last element of each entry corresponds to the weights, i.e., the frequency with which such sufficient statistics are observed in the support.

### 8.29.3.25 get\_support\_fun()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type>* Model< Array_Type,
Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_support_fun ( )
```

### 8.29.3.26 likelihood() [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const Array_Type & Array_,
    int i = -1,
    bool as_log = false )
```

### 8.29.3.27 likelihood() [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const double * target_,
    const uint & i,
    bool as_log = false )
```

### 8.29.3.28 likelihood() [3/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const std::vector< double > & target_,
    const uint & i,
    bool as_log = false )
```

**8.29.3.29 likelihood() [4/4]**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const uint & i,
    bool as_log = false )
```

**8.29.3.30 likelihood\_total()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood_total (
    const std::vector< double > & params,
    bool as_log = false )
```

**8.29.3.31 nrules()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nrules ( ) const [noexcept]
```

**8.29.3.32 nrules\_dyn()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nrules_dyn ( ) const [noexcept]
```

**8.29.3.33 nterms()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nterms ( ) const [noexcept]
```



### 8.29.3.34 operator=()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > & Model< Array_↵
Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::operator= (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
& Model_ ) [inline]
```

Definition at line 212 of file model-meat.hpp.

### 8.29.3.35 print()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print [inline]
```

Prints information about the model.

Definition at line 914 of file model-meat.hpp.

### 8.29.3.36 print\_stats()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print_stats (
    uint i ) const
```

### 8.29.3.37 sample() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample
(
    const Array_Type & Array_,
    const std::vector< double > & params = {} )
```

### 8.29.3.38 sample() [2/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample
(
    const uint & i,
    const std::vector< double > & params ) [inline]
```

Definition at line 1041 of file model-meat.hpp.

**8.29.3.39 set\_counters()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_counters
(
    Counters< Array_Type, Data_Counter_Type > * counters_ )
```

**8.29.3.40 set\_engine()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_engine (
    std::mt19937 * rengine_,
    bool delete_ = false ) [inline]
```

Definition at line 129 of file model-bones.hpp.

**8.29.3.41 set\_rules()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ )
```

**8.29.3.42 set\_rules\_dyn()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules_dyn
(
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ )
```

**8.29.3.43 set\_seed()**

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_seed (
    unsigned int s ) [inline]
```

Definition at line 139 of file model-bones.hpp.

### 8.29.3.44 set\_transform\_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_transform_model (
    std::function< std::vector< double >(double *, unsigned int)> fun,
    std::vector< std::string > names )
```

Set the transform\_model\_fun object.

The transform\_model function is used to transform the data

#### Parameters

<i>data</i>	
<i>target</i>	
<i>n_arrays</i>	
<i>arrays2support</i>	

### 8.29.3.45 size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size ( ) const [noexcept]
```

### 8.29.3.46 size\_unique()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size_unique ( ) const [noexcept]
```

### 8.29.3.47 store\_psets()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::store_psets ( ) [noexcept]
```

### 8.29.3.48 support\_size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
unsigned int Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >↵
::support_size ( ) const [noexcept]
```

### 8.29.3.49 transform\_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector<double> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::transform_model (
    double * data,
    unsigned int k )
```

## 8.29.4 Member Data Documentation

### 8.29.4.1 arrays2support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< uint > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::arrays2support [protected]
```

Definition at line 65 of file model-bones.hpp.

### 8.29.4.2 counter\_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
StatsCounter<Array_Type,Data_Counter_Type> Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::counter_fun [protected]
```

Definition at line 95 of file model-bones.hpp.

### 8.29.4.3 counters

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Counters<Array_Type,Data_Counter_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::counters [protected]
```

Definition at line 91 of file model-bones.hpp.

#### 8.29.4.4 delete\_counters

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_counters = false [protected]
```

Definition at line 103 of file model-bones.hpp.

#### 8.29.4.5 delete\_rengine

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rengine = false [protected]
```

Definition at line 43 of file model-bones.hpp.

#### 8.29.4.6 delete\_rules

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rules = false [protected]
```

Definition at line 104 of file model-bones.hpp.

#### 8.29.4.7 delete\_rules\_dyn

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rules_dyn = false [protected]
```

Definition at line 105 of file model-bones.hpp.

#### 8.29.4.8 first\_calc\_done

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< bool > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::first_calc_done [protected]
```

Definition at line 101 of file model-bones.hpp.

#### 8.29.4.9 keys2support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
MapVec_type< double, uint > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::keys2support [protected]
```

Map of types of arrays to support sets.

This is of the same length as the vector stats\_target.

Definition at line 72 of file model-bones.hpp.

#### 8.29.4.10 normalizing\_constants

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::normalizing_constants [protected]
```

Definition at line 100 of file model-bones.hpp.

#### 8.29.4.11 params\_last

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::params_last [protected]
```

Vector of the previously used parameters.

Definition at line 99 of file model-bones.hpp.

#### 8.29.4.12 pset\_arrays

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< Array_Type > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_arrays [protected]
```

Arrays of the support(s)

Definition at line 81 of file model-bones.hpp.

#### 8.29.4.13 pset\_probs

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_probs [protected]
```

Probabilities of the support(s)

Definition at line 83 of file model-bones.hpp.

#### 8.29.4.14 pset\_stats

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_stats [protected]
```

Statistics of the support(s)

Definition at line 82 of file model-bones.hpp.

#### 8.29.4.15 rengine

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::mt19937* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rengine = nullptr [protected]
```

Definition at line 42 of file model-bones.hpp.

#### 8.29.4.16 rules

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rules [protected]
```

Definition at line 92 of file model-bones.hpp.

#### 8.29.4.17 rules\_dyn

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type, Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rules_dyn [protected]
```

Definition at line 93 of file model-bones.hpp.

#### 8.29.4.18 stats\_support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_support [protected]
```

Sufficient statistics of the model (support)

Definition at line 62 of file model-bones.hpp.

#### 8.29.4.19 stats\_support\_n\_arrays

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< uint > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_support_n_arrays [protected]
```

Number of arrays included per support.

Definition at line 63 of file model-bones.hpp.

#### 8.29.4.20 stats\_target

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_target [protected]
```

Target statistics of the model.

Definition at line 64 of file model-bones.hpp.



#### 8.29.4.21 support\_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type> Model< Array_Type,
Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::support_fun [protected]
```

Definition at line 94 of file model-bones.hpp.

#### 8.29.4.22 transform\_model\_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::function<std::vector<double>double *, unsigned int k)> Model< Array_Type, Data_Counter_Type,
Data_Rule_Type, Data_Rule_Dyn_Type >::transform_model_fun = nullptr [protected]
```

Transformation of the model.

When specified, this function will update the model by modifying the linear equation. For example, if the user wanted to add interaction terms, rescale, or apply other operations of the sorts, the user can do such through this function.

The function should return `void` and receive the following arguments:

- `data` Pointer to the first element of the set of sufficient statistics
- `k` unsigned int indicating the number of sufficient statistics

#### Returns

Nothing, but it will modify the model data.

Definition at line 123 of file model-bones.hpp.

#### 8.29.4.23 transform\_model\_term\_names

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::string > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_↵
Dyn_Type >::transform_model_term_names [protected]
```

Definition at line 125 of file model-bones.hpp.

#### 8.29.4.24 with\_pset

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::with_pset =
false [protected]
```

Definition at line 80 of file model-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/model-bones.hpp
- include/barry/model-meat.hpp

## 8.30 NetCounterData Class Reference

Data class used to store arbitrary uint or double vectors.

```
#include <network.hpp>
```

### Public Member Functions

- [NetCounterData](#) ()
- [NetCounterData](#) (const std::vector< uint > indices\_, const std::vector< double > numbers\_)
- [~NetCounterData](#) ()

### Public Attributes

- std::vector< uint > [indices](#)
- std::vector< double > [numbers](#)

#### 8.30.1 Detailed Description

Data class used to store arbitrary uint or double vectors.

Definition at line 56 of file network.hpp.

#### 8.30.2 Constructor & Destructor Documentation

##### 8.30.2.1 NetCounterData() [1/2]

```
NetCounterData::NetCounterData ( ) [inline]
```

Definition at line 62 of file network.hpp.

### 8.30.2.2 NetCounterData() [2/2]

```
NetCounterData::NetCounterData (
    const std::vector< uint > indices_,
    const std::vector< double > numbers_ ) [inline]
```

Definition at line 63 of file network.hpp.

### 8.30.2.3 ~NetCounterData()

```
NetCounterData::~~NetCounterData ( ) [inline]
```

Definition at line 68 of file network.hpp.

## 8.30.3 Member Data Documentation

### 8.30.3.1 indices

```
std::vector< uint > NetCounterData::indices
```

Definition at line 59 of file network.hpp.

### 8.30.3.2 numbers

```
std::vector< double > NetCounterData::numbers
```

Definition at line 60 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

## 8.31 NetworkData Class Reference

Data class for Networks.

```
#include <network.hpp>
```

## Public Member Functions

- [NetworkData](#) ()
- [NetworkData](#) (std::vector< double > vertex\_attr\_, bool directed\_=true)  
*Constructor using a single attribute.*
- [NetworkData](#) (std::vector< std::vector< double > > vertex\_attr\_, bool directed\_=true)  
*Constructor using multiple attributes.*
- [~NetworkData](#) ()

## Public Attributes

- bool [directed](#) = true
- std::vector< std::vector< double > > [vertex\\_attr](#)

### 8.31.1 Detailed Description

Data class for Networks.

Details on the available counters for [NetworkData](#) can be found in the [DEFMArray counters](#) section.

This holds information about whether the graph is directed or not, and, if defined, vectors of node (vertex) attributes ([vertex\\_attr](#)).

Definition at line 19 of file network.hpp.

### 8.31.2 Constructor & Destructor Documentation

#### 8.31.2.1 NetworkData() [1/3]

```
NetworkData::NetworkData ( ) [inline]
```

Definition at line 25 of file network.hpp.

#### 8.31.2.2 NetworkData() [2/3]

```
NetworkData::NetworkData (
    std::vector< double > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using a single attribute.

## Parameters

<i>vertex_↔ attr_</i>	Double vector of length equal to the number of vertices in the data.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 33 of file network.hpp.

### 8.31.2.3 NetworkData() [3/3]

```
NetworkData::NetworkData (
    std::vector< std::vector< double > > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using multiple attributes.

## Parameters

<i>vertex_↔ attr_</i>	Vector of double vectors. The size equals to the number of attributes to be created. Each individual vector should be of length equal to the number of vertices.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 45 of file network.hpp.

### 8.31.2.4 ~NetworkData()

```
NetworkData::~NetworkData ( ) [inline]
```

Definition at line 51 of file network.hpp.

## 8.31.3 Member Data Documentation

### 8.31.3.1 directed

```
bool NetworkData::directed = true
```

Definition at line 22 of file network.hpp.

### 8.31.3.2 vertex\_attr

```
std::vector< std::vector< double > > NetworkData::vertex_attr
```

Definition at line 23 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

## 8.32 Node Class Reference

A single node for the model.

```
#include <geese-node-bones.hpp>
```

Collaboration diagram for Node:



### Public Member Functions

- [~Node](#) ()
- int [get\\_parent](#) () const
- unsigned int [noffspring](#) () const noexcept
- bool [is\\_leaf](#) () const noexcept

#### Construct a new Node object

- [Node](#) ()
- [Node](#) (unsigned int id\_, unsigned int ord\_, bool duplication\_)
- [Node](#) (unsigned int id\_, unsigned int ord\_, std::vector< unsigned int > annotations\_, bool duplication\_)
- [Node](#) ([Node](#) &&x) noexcept
- [Node](#) (const [Node](#) &x)

## Public Attributes

- unsigned int [id](#)  
*Id of the node (as specified in the input)*
- unsigned int [ord](#)  
*Order in which the node was created.*
- [phylocounters::PhyloArray](#) array
- `std::vector< unsigned int >` [annotations](#)  
*Observed annotations (only defined for [Geese](#))*
- bool [duplication](#)
- `std::vector< phylocounters::PhyloArray >` [arrays](#) = {}  
*Arrays given all possible states.*
- [Node](#) \* [parent](#) = nullptr  
*Parent node.*
- `std::vector< Node * >` [offspring](#) = {}  
*Offspring nodes.*
- `std::vector< unsigned int >` [narray](#) = {}  
*ID of the array in the model.*
- bool [visited](#) = false
- `std::vector< double >` [subtree\\_prob](#)  
*Induced subtree probabilities.*
- `std::vector< double >` [probability](#)  
*The probability of observing each state.*

### 8.32.1 Detailed Description

A single node for the model.

Each node contains all the information to compute the conditional probability of the pruning algorithm at that node.

Definition at line 11 of file `geese-node-bones.hpp`.

### 8.32.2 Constructor & Destructor Documentation

#### 8.32.2.1 Node() [1/5]

```
Node::Node ( ) [inline]
```

Definition at line 36 of file `geese-node-bones.hpp`.

### 8.32.2.2 Node() [2/5]

```
Node::Node (
    unsigned int id_,
    unsigned int ord_,
    bool duplication_ ) [inline]
```

Definition at line 56 of file geese-node-bones.hpp.

### 8.32.2.3 Node() [3/5]

```
Node::Node (
    unsigned int id_,
    unsigned int ord_,
    std::vector< unsigned int > annotations_,
    bool duplication_ ) [inline]
```

Definition at line 62 of file geese-node-bones.hpp.

### 8.32.2.4 Node() [4/5]

```
Node::Node (
    Node && x ) [inline], [noexcept]
```

Definition at line 69 of file geese-node-bones.hpp.

### 8.32.2.5 Node() [5/5]

```
Node::Node (
    const Node & x ) [inline]
```

Definition at line 83 of file geese-node-bones.hpp.

### 8.32.2.6 ~Node()

```
Node::~Node ( ) [inline]
```

Definition at line 47 of file geese-node-bones.hpp.

## 8.32.3 Member Function Documentation



### 8.32.3.1 get\_parent()

```
int Node::get_parent ( ) const [inline]
```

Definition at line 97 of file geese-node-bones.hpp.

### 8.32.3.2 is\_leaf()

```
bool Node::is_leaf ( ) const [inline], [noexcept]
```

Definition at line 109 of file geese-node-bones.hpp.

### 8.32.3.3 noffspring()

```
unsigned int Node::noffspring ( ) const [inline], [noexcept]
```

Definition at line 103 of file geese-node-bones.hpp.

## 8.32.4 Member Data Documentation

### 8.32.4.1 annotations

```
std::vector< unsigned int > Node::annotations
```

Observed annotations (only defined for [Geese](#))

Definition at line 18 of file geese-node-bones.hpp.

### 8.32.4.2 array

```
phylocounters::PhyloArray Node::array
```

Definition at line 17 of file geese-node-bones.hpp.

### 8.32.4.3 arrays

```
std::vector< phylocounters::PhyloArray > Node::arrays = {}
```

Arrays given all possible states.

Definition at line 21 of file geese-node-bones.hpp.

### 8.32.4.4 duplication

```
bool Node::duplication
```

Definition at line 19 of file geese-node-bones.hpp.

### 8.32.4.5 id

```
unsigned int Node::id
```

Id of the node (as specified in the input)

Definition at line 14 of file geese-node-bones.hpp.

### 8.32.4.6 narray

```
std::vector< unsigned int > Node::narray = {}
```

ID of the array in the model.

Definition at line 24 of file geese-node-bones.hpp.

### 8.32.4.7 offspring

```
std::vector< Node* > Node::offspring = {}
```

Offspring nodes.

Definition at line 23 of file geese-node-bones.hpp.

#### 8.32.4.8 ord

```
unsigned int Node::ord
```

Order in which the node was created.

Definition at line 15 of file geese-node-bones.hpp.

#### 8.32.4.9 parent

```
Node* Node::parent = nullptr
```

Parent node.

Definition at line 22 of file geese-node-bones.hpp.

#### 8.32.4.10 probability

```
std::vector< double > Node::probability
```

The probability of observing each state.

Definition at line 28 of file geese-node-bones.hpp.

#### 8.32.4.11 subtree\_prob

```
std::vector< double > Node::subtree_prob
```

Induced subtree probabilities.

Definition at line 27 of file geese-node-bones.hpp.

#### 8.32.4.12 visited

```
bool Node::visited = false
```

Definition at line 25 of file geese-node-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/models/geese/geese-node-bones.hpp](#)

## 8.33 NodeData Class Reference

Data definition for the `PhyloArray` class.

```
#include <phylo.hpp>
```

### Public Member Functions

- `NodeData` (`const` `std::vector< double >` &`blengths_`, `const` `std::vector< bool >` &`states_`, `bool` `duplication_`↵  
=true)

### Public Attributes

- `std::vector< double >` `blengths` = {}
- `std::vector< bool >` `states` = {}
- `bool` `duplication` = true

### 8.33.1 Detailed Description

Data definition for the `PhyloArray` class.

Details about the available counters for `PhyloArray` objects can be found in the [Phylo counters](#) section.

This holds basic information about a given node.

Definition at line 38 of file `phylo.hpp`.

### 8.33.2 Constructor & Destructor Documentation

#### 8.33.2.1 NodeData()

```
NodeData::NodeData (
    const std::vector< double > & blengths_,
    const std::vector< bool > & states_,
    bool duplication_ = true ) [inline]
```

Definition at line 58 of file `phylo.hpp`.

### 8.33.3 Member Data Documentation

### 8.33.3.1 blengths

```
std::vector< double > NodeData::blengths = {}
```

Branch length.

Definition at line 44 of file phylo.hpp.

### 8.33.3.2 duplication

```
bool NodeData::duplication = true
```

Definition at line 54 of file phylo.hpp.

### 8.33.3.3 states

```
std::vector< bool > NodeData::states = {}
```

State of the parent node.

Definition at line 49 of file phylo.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[phylo.hpp](#)

## 8.34 PhyloCounterData Class Reference

```
#include <phylo.hpp>
```

### Public Member Functions

- [PhyloCounterData](#) (std::vector< [uint](#) > [data\\_](#), std::vector< double > \*[counters\\_](#)=nullptr)
- [PhyloCounterData](#) ()
- [uint at](#) ([uint d](#))
- [uint operator\(\)](#) ([uint d](#))
- [uint operator\[\]](#) ([uint d](#))
- void [reserve](#) ([uint x](#))
- void [push\\_back](#) ([uint x](#))
- void [shrink\\_to\\_fit](#) ()
- [uint size](#) ()
- std::vector< [uint](#) >::iterator [begin](#) ()
- std::vector< [uint](#) >::iterator [end](#) ()
- bool [empty](#) ()
- std::vector< double > \* [get\\_counters](#) ()

### 8.34.1 Detailed Description

Definition at line 69 of file phylo.hpp.

### 8.34.2 Constructor & Destructor Documentation

#### 8.34.2.1 PhyloCounterData() [1/2]

```
PhyloCounterData::PhyloCounterData (
    std::vector< uint > data_,
    std::vector< double > * counters_ = nullptr ) [inline]
```

Definition at line 75 of file phylo.hpp.

#### 8.34.2.2 PhyloCounterData() [2/2]

```
PhyloCounterData::PhyloCounterData ( ) [inline]
```

Definition at line 80 of file phylo.hpp.

### 8.34.3 Member Function Documentation

#### 8.34.3.1 at()

```
uint PhyloCounterData::at (
    uint d ) [inline]
```

Definition at line 82 of file phylo.hpp.

#### 8.34.3.2 begin()

```
std::vector< uint >::iterator PhyloCounterData::begin ( ) [inline]
```

Definition at line 90 of file phylo.hpp.

### 8.34.3.3 empty()

```
bool PhyloCounterData::empty ( ) [inline]
```

Definition at line 93 of file phylo.hpp.

### 8.34.3.4 end()

```
std::vector< uint >::iterator PhyloCounterData::end ( ) [inline]
```

Definition at line 91 of file phylo.hpp.

### 8.34.3.5 get\_counters()

```
std::vector< double >* PhyloCounterData::get_counters ( ) [inline]
```

Definition at line 94 of file phylo.hpp.

### 8.34.3.6 operator()()

```
uint PhyloCounterData::operator() (
    uint d ) [inline]
```

Definition at line 83 of file phylo.hpp.

### 8.34.3.7 operator[]()

```
uint PhyloCounterData::operator[] (
    uint d ) [inline]
```

Definition at line 84 of file phylo.hpp.

### 8.34.3.8 push\_back()

```
void PhyloCounterData::push_back (
    uint x ) [inline]
```

Definition at line 86 of file phylo.hpp.

#### 8.34.3.9 reserve()

```
void PhyloCounterData::reserve (
    uint x ) [inline]
```

Definition at line 85 of file phylo.hpp.

#### 8.34.3.10 shrink\_to\_fit()

```
void PhyloCounterData::shrink_to_fit ( ) [inline]
```

Definition at line 87 of file phylo.hpp.

#### 8.34.3.11 size()

```
uint PhyloCounterData::size ( ) [inline]
```

Definition at line 88 of file phylo.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[phylo.hpp](#)

## 8.35 PhyloRuleDynData Class Reference

```
#include <phylo.hpp>
```

### Public Member Functions

- [PhyloRuleDynData](#) ([const](#) std::vector< double > \*counts\_, [uint](#) pos\_, [uint](#) lb\_, [uint](#) ub\_, [uint](#) duplication\_)
- [~PhyloRuleDynData](#) ()

### Public Attributes

- [const](#) std::vector< double > \* [counts](#)
- [uint](#) [pos](#)
- [uint](#) [lb](#)
- [uint](#) [ub](#)
- [uint](#) [duplication](#)

#### 8.35.1 Detailed Description

Definition at line 2147 of file phylo.hpp.



## 8.35.2 Constructor & Destructor Documentation

### 8.35.2.1 PhyloRuleDynData()

```
PhyloRuleDynData::PhyloRuleDynData (
    const std::vector< double > * counts_,
    uint pos_,
    uint lb_,
    uint ub_,
    uint duplication_ ) [inline]
```

Definition at line 2155 of file phylo.hpp.

### 8.35.2.2 ~PhyloRuleDynData()

```
PhyloRuleDynData::~PhyloRuleDynData ( ) [inline]
```

Definition at line 2164 of file phylo.hpp.

## 8.35.3 Member Data Documentation

### 8.35.3.1 counts

```
const std::vector< double >* PhyloRuleDynData::counts
```

Definition at line 2149 of file phylo.hpp.

### 8.35.3.2 duplication

```
uint PhyloRuleDynData::duplication
```

Definition at line 2153 of file phylo.hpp.

### 8.35.3.3 lb

```
uint PhyloRuleDynData::lb
```

Definition at line 2151 of file phylo.hpp.

### 8.35.3.4 pos

```
uint PhyloRuleDynData::pos
```

Definition at line 2150 of file phylo.hpp.

### 8.35.3.5 ub

```
uint PhyloRuleDynData::ub
```

Definition at line 2152 of file phylo.hpp.

The documentation for this class was generated from the following file:


- include/barry/counters/[phylo.hpp](#)

## 8.36 PowerSet< Array\_Type, Data\_Rule\_Type > Class Template Reference

Powerset of a binary array.

```
#include <powerset-bones.hpp>
```

Collaboration diagram for PowerSet< Array\_Type, Data\_Rule\_Type >:



## Public Member Functions

- void [init\\_support](#) ()
- void [calc](#) ()
- void [reset](#) (uint N\_, uint M\_)

### Construct and destroy a PowerSet object

- [PowerSet](#) ()
- [PowerSet](#) (uint N\_, uint M\_)
- [PowerSet](#) (const Array\_Type &array)
- [~PowerSet](#) ()

### Wrappers for the `<tt>Rules</tt>` member.

*These will add rules to the model, which are shared by the support and the actual counter function.*

- void [add\\_rule](#) (Rule< Array\_Type, Data\_Rule\_Type > rule)
- void [add\\_rule](#) (Rule\_fun\_type< Array\_Type, Data\_Rule\_Type > count\_fun\_, Data\_Rule\_Type data\_)

### Getter functions

- const std::vector< Array\_Type > \* [get\\_data\\_ptr](#) () const
- std::vector< Array\_Type > [get\\_data](#) () const
- std::vector< Array\_Type >::iterator [begin](#) ()
- std::vector< Array\_Type >::iterator [end](#) ()
- std::size\_t [size](#) () const noexcept
- const Array\_Type & [operator\[\]](#) (const unsigned int &i) const

## Public Attributes

- Array\_Type [EmptyArray](#)
- std::vector< Array\_Type > [data](#)
- Rules< Array\_Type, Data\_Rule\_Type > \* [rules](#)
- uint [N](#)
- uint [M](#)
- bool [rules\\_deleted](#) = false
- std::vector< size\_t > [coordinates\\_free](#)
- std::vector< size\_t > [coordinates\\_locked](#)
- size\_t [n\\_free](#)
- size\_t [n\\_locked](#)

### 8.36.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
class PowerSet< Array_Type, Data_Rule_Type >
```

Powerset of a binary array.

#### Template Parameters

<i>Array_Type</i>	
<i>Data_Rule_Type</i>	

Definition at line 11 of file powerset-bones.hpp.

## 8.36.2 Constructor & Destructor Documentation

### 8.36.2.1 PowerSet() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet ( ) [inline]
```

Definition at line 36 of file powerset-bones.hpp.

### 8.36.2.2 PowerSet() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    uint N_,
    uint M_ ) [inline]
```

Definition at line 38 of file powerset-bones.hpp.

### 8.36.2.3 PowerSet() [3/3]

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    const Array_Type & array ) [inline]
```

Definition at line 5 of file powerset-meat.hpp.

### 8.36.2.4 ~PowerSet()

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::~~PowerSet [inline]
```

Definition at line 13 of file powerset-meat.hpp.

## 8.36.3 Member Function Documentation

#### 8.36.3.1 add\_rule() [1/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > rule ) [inline]
```

Definition at line 173 of file powerset-meat.hpp.

#### 8.36.3.2 add\_rule() [2/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ ) [inline]
```

Definition at line 182 of file powerset-meat.hpp.

#### 8.36.3.3 begin()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::begin ( ) [inline]
```

Definition at line 68 of file powerset-bones.hpp.

#### 8.36.3.4 calc()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::calc [inline]
```

Definition at line 144 of file powerset-meat.hpp.

#### 8.36.3.5 end()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::end ( ) [inline]
```

Definition at line 69 of file powerset-bones.hpp.

### 8.36.3.6 get\_data()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::get_data ( ) const [inline]
```

Definition at line 67 of file powerset-bones.hpp.

### 8.36.3.7 get\_data\_ptr()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const std::vector< Array_Type >* PowerSet< Array_Type, Data_Rule_Type >::get_data_ptr ( )
const [inline]
```

Definition at line 66 of file powerset-bones.hpp.

### 8.36.3.8 init\_support()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::init_support [inline]
```

Definition at line 19 of file powerset-meat.hpp.

### 8.36.3.9 operator[]()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const Array_Type& PowerSet< Array_Type, Data_Rule_Type >::operator[] (
    const unsigned int & i ) const [inline]
```

Definition at line 71 of file powerset-bones.hpp.

### 8.36.3.10 reset()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::reset (
    uint N_,
    uint M_ ) [inline]
```

Definition at line 160 of file powerset-meat.hpp.

### 8.36.3.11 size()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::size_t PowerSet< Array_Type, Data_Rule_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 70 of file powerset-bones.hpp.

## 8.36.4 Member Data Documentation

### 8.36.4.1 coordinates\_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_free
```

Definition at line 26 of file powerset-bones.hpp.

### 8.36.4.2 coordinates\_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_locked
```

Definition at line 27 of file powerset-bones.hpp.

### 8.36.4.3 data

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::data
```

Definition at line 19 of file powerset-bones.hpp.

### 8.36.4.4 EmptyArray

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Array_Type PowerSet< Array_Type, Data_Rule_Type >::EmptyArray
```

Definition at line 18 of file powerset-bones.hpp.

#### 8.36.4.5 M

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
uint PowerSet< Array_Type, Data_Rule_Type >::M
```

Definition at line 22 of file powerset-bones.hpp.

#### 8.36.4.6 N

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
uint PowerSet< Array_Type, Data_Rule_Type >::N
```

Definition at line 22 of file powerset-bones.hpp.

#### 8.36.4.7 n\_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_free
```

Definition at line 28 of file powerset-bones.hpp.

#### 8.36.4.8 n\_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_locked
```

Definition at line 29 of file powerset-bones.hpp.

#### 8.36.4.9 rules

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Rules<Array_Type,Data_Rule_Type>* PowerSet< Array_Type, Data_Rule_Type >::rules
```

Definition at line 20 of file powerset-bones.hpp.



#### 8.36.4.10 rules\_deleted

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
bool PowerSet< Array_Type, Data_Rule_Type >::rules_deleted = false
```

Definition at line 23 of file powerset-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/powerset-bones.hpp
- include/barry/powerset-meat.hpp

## 8.37 Progress Class Reference

A simple progress bar.

```
#include <progress.hpp>
```

### Public Member Functions

- [Progress](#) (int n\_, int width\_)
- [~Progress](#) ()
- void [next](#) ()
- void [end](#) ()

#### 8.37.1 Detailed Description

A simple progress bar.

Definition at line 11 of file progress.hpp.

#### 8.37.2 Constructor & Destructor Documentation

##### 8.37.2.1 Progress()

```
Progress::Progress (
    int n_,
    int width_ ) [inline]
```

Definition at line 30 of file progress.hpp.

### 8.37.2.2 ~Progress()

```
Progress::~~Progress ( ) [inline]
```

Definition at line 23 of file progress.hpp.

## 8.37.3 Member Function Documentation

### 8.37.3.1 end()

```
void Progress::end ( ) [inline]
```

Definition at line 52 of file progress.hpp.

### 8.37.3.2 next()

```
void Progress::next ( ) [inline]
```

Definition at line 41 of file progress.hpp.

The documentation for this class was generated from the following file:

- [include/barry/progress.hpp](#)

## 8.38 Rule< Array\_Type, Data\_Type > Class Template Reference

[Rule](#) for determining if a cell should be included in a sequence.

```
#include <rules-bones.hpp>
```

### Public Member Functions

- [~Rule](#) ()
- Data\_Type & [D](#) ()  
*Read/Write access to the data.*
- bool [operator\(\)](#) (const Array\_Type &a, uint i, uint j)
- std::string & [get\\_name](#) ()
- std::string & [get\\_description](#) ()
- std::string [get\\_name](#) () const
- std::string [get\\_description](#) () const

#### Construct a new Rule object

Construct a new [Rule](#) object

**Parameters**

<code>fun_</code>	<i>A function of type <code>Rule_fun_type</code>.</i>
<code>dat_</code>	<i>Data pointer to be passed to <code>fun_</code></i>
<code>delete_↔ dat_</code>	<i>When <code>true</code>, the <code>Rule</code> destructor will delete the pointer, if defined.</i>

- `Rule()`
- `Rule(Rule_fun_type< Array_Type, Data_Type > fun_, Data_Type dat_, std::string name_="", std::string desc_="")`

**8.38.1 Detailed Description**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Rule< Array_Type, Data_Type >
```

`Rule` for determining if a cell should be included in a sequence.

`Rules` can be used together with `Support` and `PowerSet` to determine which cells should be included when enumerating all possible realizations of a binary array.

**Template Parameters**

<i>Array_Type</i>	An object of class <code>BArray</code> .
<i>Data_Type</i>	Any type.

Definition at line 20 of file `rules-bones.hpp`.

**8.38.2 Constructor & Destructor Documentation****8.38.2.1 Rule() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule ( ) [inline]
```

Definition at line 41 of file `rules-bones.hpp`.

**8.38.2.2 Rule() [2/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule (
    Rule_fun_type< Array_Type, Data_Type > fun_,
    Data_Type dat_,
    std::string name_ = "",
    std::string desc_ = "" ) [inline]
```

Definition at line 42 of file `rules-bones.hpp`.

### 8.38.2.3 ~Rule()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::~~Rule ( ) [inline]
```

Definition at line 50 of file rules-bones.hpp.

## 8.38.3 Member Function Documentation

### 8.38.3.1 D()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Data_Type& Rule< Array_Type, Data_Type >::D ( )
```

Read/Write access to the data.

### 8.38.3.2 get\_description() [1/2]

```
template<typename Array_Type , typename Data_Type >
std::string & Rule< Array_Type, Data_Type >::get_description [inline]
```

Definition at line 48 of file rules-meat.hpp.

### 8.38.3.3 get\_description() [2/2]

```
template<typename Array_Type , typename Data_Type >
std::string Rule< Array_Type, Data_Type >::get_description [inline]
```

Definition at line 60 of file rules-meat.hpp.

### 8.38.3.4 get\_name() [1/2]

```
template<typename Array_Type , typename Data_Type >
std::string & Rule< Array_Type, Data_Type >::get_name [inline]
```

Definition at line 42 of file rules-meat.hpp.

**8.38.3.5** `get_name()` [2/2]

```
template<typename Array_Type , typename Data_Type >
std::string Rule< Array_Type, Data_Type >::get_name  [inline]
```

Definition at line 54 of file rules-meat.hpp.

**8.38.3.6** `operator()`

```
template<typename Array_Type , typename Data_Type >
bool Rule< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    uint i,
    uint j ) [inline]
```

Definition at line 37 of file rules-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/rules-bones.hpp
- include/barry/rules-meat.hpp

**8.39** Rules< Array\_Type, Data\_Type > Class Template Reference

Vector of objects of class [Rule](#).

```
#include <rules-bones.hpp>
```

**Public Member Functions**

- [Rules](#) ()
- [Rules](#) (const [Rules](#)< Array\_Type, Data\_Type > &rules\_)
- [Rules](#)< Array\_Type, Data\_Type > [operator=](#) (const [Rules](#)< Array\_Type, Data\_Type > &rules\_)
- [~Rules](#) ()
- [uint size](#) () const noexcept
- bool [operator\(\)](#) (const Array\_Type &a, uint i, uint j)  
*Check whether a given cell is free or locked.*
- void [get\\_seq](#) (const Array\_Type &a, std::vector< size\_t > \*free, std::vector< size\_t > \*locked=nullptr)  
*Computes the sequence of free and locked cells in an [BArray](#).*
- std::vector< std::string > [get\\_names](#) () const
- std::vector< std::string > [get\\_descriptions](#) () const

**Rule adding***Parameters*

rule	
------	--

- void `add_rule` (`Rule`< `Array_Type`, `Data_Type` > rule)
- void `add_rule` (`Rule_fun_type`< `Array_Type`, `Data_Type` > rule\_, `Data_Type` `data_`, `std::string` `name_`="", `std::string` `description_`="")

### 8.39.1 Detailed Description

```
template<typename Array_Type, typename Data_Type>
class Rules< Array_Type, Data_Type >
```

Vector of objects of class `Rule`.

Template Parameters

<i>Array_Type</i>	An object of class <code>BArray</code>
<i>Data_Type</i>	Any type.

Definition at line 71 of file `rules-bones.hpp`.

### 8.39.2 Constructor & Destructor Documentation

#### 8.39.2.1 Rules() [1/2]

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules ( ) [inline]
```

Definition at line 77 of file `rules-bones.hpp`.

#### 8.39.2.2 Rules() [2/2]

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules (
    const Rules< Array_Type, Data_Type > & rules_ ) [inline]
```

Definition at line 5 of file `rules-meat.hpp`.

#### 8.39.2.3 ~Rules()

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::~Rules ( ) [inline]
```

Definition at line 82 of file `rules-bones.hpp`.

### 8.39.3 Member Function Documentation

#### 8.39.3.1 add\_rule() [1/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule< Array_Type, Data_Type > rule ) [inline]
```

Definition at line 66 of file rules-meat.hpp.

#### 8.39.3.2 add\_rule() [2/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Type > rule_,
    Data_Type data_,
    std::string name_ = "",
    std::string description_ = "" ) [inline]
```

Definition at line 76 of file rules-meat.hpp.

#### 8.39.3.3 get\_descriptions()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > Rules< Array_Type, Data_Type >::get_descriptions [inline]
```

Definition at line 173 of file rules-meat.hpp.

#### 8.39.3.4 get\_names()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > Rules< Array_Type, Data_Type >::get_names [inline]
```

Definition at line 161 of file rules-meat.hpp.

#### 8.39.3.5 get\_seq()

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::get_seq (
    const Array_Type & a,
    std::vector< size_t > * free,
    std::vector< size_t > * locked = nullptr ) [inline]
```

Computes the sequence of free and locked cells in an [BArray](#).

## Parameters

<i>a</i>	An object of class <a href="#">BArray</a> .
<i>free</i>	Pointer to a vector of pairs (i, j) listing the free cells.
<i>locked</i>	(optional) Pointer to a vector of pairs (i, j) listing the locked cells.

## Returns

Nothing.

Definition at line 111 of file rules-meat.hpp.

**8.39.3.6 operator()**

```
template<typename Array_Type , typename Data_Type >
bool Rules< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    uint i,
    uint j ) [inline]
```

Check whether a given cell is free or locked.

## Parameters

<i>a</i>	A <a href="#">BArray</a> object
<i>i</i>	row position
<i>j</i>	col position

## Returns

true If the cell is locked  
false If the cell is free

Definition at line 95 of file rules-meat.hpp.

**8.39.3.7 operator=()**

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type > Rules< Array_Type, Data_Type >::operator= (
    const Rules< Array_Type, Data_Type > & rules_ )
```

Definition at line 19 of file rules-meat.hpp.



## 8.39.3.8 size()

```
template<typename Array_Type , typename Data_Type >
uint Rules< Array_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 84 of file rules-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/rules-bones.hpp](#)
- [include/barry/rules-meat.hpp](#)

## 8.40 StatsCounter&lt; Array\_Type, Data\_Type &gt; Class Template Reference

Count stats for a single Array.

```
#include <statscounter-bones.hpp>
```

## Public Member Functions

- [StatsCounter](#) (const Array\_Type \*Array\_)  
*Creator of a [StatsCounter](#)*
- [StatsCounter](#) (const StatsCounter< Array\_Type, Data\_Type > &counter)  
*Copy constructor.*
- [StatsCounter](#) ()  
*Can be created without setting the array.*
- [~StatsCounter](#) ()
- void [reset\\_array](#) (const Array\_Type \*Array\_)  
*Changes the reference array for the counting.*
- void [add\\_counter](#) (Counter< Array\_Type, Data\_Type > f\_)
- void [set\\_counters](#) (Counters< Array\_Type, Data\_Type > \*counters\_)
- void [count\\_init](#) (uint i, uint j)  
*Counter functions This function recurses through the entries of Array and at each step of adding a new cell it uses the functions to list the statistics.*
- void [count\\_current](#) (uint i, uint j)
- std::vector< double > [count\\_all](#) ()
- Counters< Array\_Type, Data\_Type > \* [get\\_counters](#) ()
- std::vector< std::string > [get\\_names](#) () const
- std::vector< std::string > [get\\_descriptions](#) () const
- size\_t [size](#) () const

## 8.40.1 Detailed Description

```
template<typename Array_Type, typename Data_Type>
class StatsCounter< Array_Type, Data_Type >
```

Count stats for a single Array.

Users can a list of functions that can be used with this. The baseline set of arguments is a pointer to a binary array and a dataset to add the counts to.

Definition at line 14 of file statscounter-bones.hpp.

## 8.40.2 Constructor & Destructor Documentation

### 8.40.2.1 StatsCounter() [1/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const Array_Type * Array_ ) [inline]
```

Creator of a [StatsCounter](#)

#### Parameters

<a href="#">Array</a> ↔	A const pointer to a <a href="#">BArray</a> .
—	

Definition at line 37 of file statscounter-bones.hpp.

### 8.40.2.2 StatsCounter() [2/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const StatsCounter< Array_Type, Data_Type > & counter )
```

Copy constructor.

#### Parameters

<a href="#">counter</a>	
-------------------------	--

### 8.40.2.3 StatsCounter() [3/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter ( ) [inline]
```

Can be created without setting the array.

Definition at line 59 of file statscounter-bones.hpp.

### 8.40.2.4 ~StatsCounter()

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::~StatsCounter ( )
```

### 8.40.3 Member Function Documentation

#### 8.40.3.1 add\_counter()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > f_ )
```

#### 8.40.3.2 count\_all()

```
template<typename Array_Type , typename Data_Type >
std::vector< double > StatsCounter< Array_Type, Data_Type >::count_all [inline]
```

Definition at line 99 of file statscounter-meat.hpp.

#### 8.40.3.3 count\_current()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_current (
    uint i,
    uint j )
```

#### 8.40.3.4 count\_init()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_init (
    uint i,
    uint j )
```

**Counter** functions This function recurses through the entries of `Array` and at each step of adding a new cell it uses the functions to list the statistics.

#### 8.40.3.5 get\_counters()

```
template<typename Array_Type , typename Data_Type >
Counters<Array_Type,Data_Type>* StatsCounter< Array_Type, Data_Type >::get_counters ( )
```

**8.40.3.6 get\_descriptions()**

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_descriptions ( ) const
```

**8.40.3.7 get\_names()**

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_names ( ) const
```

**8.40.3.8 reset\_array()**

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::reset_array (
    const Array_Type * Array_ )
```

Changes the reference array for the counting.

**Parameters**

<i>Array_↔</i> —	A pointer to an array of class Array_Type.
---------------------	--

**8.40.3.9 set\_counters()**

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::set_counters (
    Counters< Array_Type, Data_Type > * counters_ )
```

**8.40.3.10 size()**

```
template<typename Array_Type , typename Data_Type >
size_t StatsCounter< Array_Type, Data_Type >::size ( ) const [inline]
```

Definition at line 86 of file statscounter-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/statscounter-bones.hpp
- include/barry/statscounter-meat.hpp

## 8.41 Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type > Class Template Reference

Compute the support of sufficient statistics.

```
#include <support-bones.hpp>
```

### Public Member Functions

- [Support](#) ([const](#) Array\_Type &[Array\\_](#))  
*Constructor passing a reference Array.*
- [Support](#) ([uint](#) N\_, [uint](#) M\_)  
*Constructor specifying the dimensions of the array (empty).*
- [Support](#) ()
- [~Support](#) ()
- void [init\\_support](#) (std::vector< Array\_Type > \*[array\\_bank](#)=nullptr, std::vector< double > \*[stats\\_bank](#)=nullptr)
- void [calc](#) (std::vector< Array\_Type > \*[array\\_bank](#)=nullptr, std::vector< double > \*[stats\\_bank](#)=nullptr, unsigned int max\_num\_elements\_=0u)  
*Computes the entire support.*
- std::vector< double > [get\\_counts](#) () [const](#)
- std::vector< double > \* [get\\_current\\_stats](#) ()  
*List current statistics.*
- void [print](#) () [const](#)
- [const](#) FreqTable< double > & [get\\_data](#) () [const](#)
- [Counters](#)< Array\_Type, Data\_Counter\_Type > \* [get\\_counters](#) ()  
*Vector of counter functions.*
- [Rules](#)< Array\_Type, Data\_Rule\_Type > \* [get\\_rules](#) ()  
*Vector of static rules (cells to iterate).*
- [Rules](#)< Array\_Type, Data\_Rule\_Dyn\_Type > \* [get\\_rules\\_dyn](#) ()  
*Vector of dynamic rules (to include/exclude a realization).*

### Resets the support calculator

*If needed, the counters of a support object can be reused.*

#### Parameters

Array↔ _	New array over which the support will be computed.
-------------	--

- void [reset\\_array](#) ()
- void [reset\\_array](#) ([const](#) Array\_Type &[Array\\_](#))

### Manage counters

#### Parameters

f_ _	A counter to be added.
counters↔ _	A vector of counters to be added.

- void [add\\_counter](#) ([Counter](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#) > [f\\_](#))
- void [set\\_counters](#) ([Counters](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#) > [\\*counters\\_](#))

## Manage rules

### Parameters

<a href="#">f_</a>	<i>A rule to be added.</i>
<a href="#">counters_</a>	<i>A vector of rules to be added.</i>

- void [add\\_rule](#) ([Rule](#)< [Array\\_Type](#), [Data\\_Rule\\_Type](#) > [\\*f\\_](#))
- void [add\\_rule](#) ([Rule](#)< [Array\\_Type](#), [Data\\_Rule\\_Type](#) > [f\\_](#))
- void [set\\_rules](#) ([Rules](#)< [Array\\_Type](#), [Data\\_Rule\\_Type](#) > [\\*rules\\_](#))
- void [add\\_rule\\_dyn](#) ([Rule](#)< [Array\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > [\\*f\\_](#))
- void [add\\_rule\\_dyn](#) ([Rule](#)< [Array\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > [f\\_](#))
- void [set\\_rules\\_dyn](#) ([Rules](#)< [Array\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) > [\\*rules\\_](#))
- bool [eval\\_rules\\_dyn](#) ([const](#) [std::vector](#)< [double](#) > &[counts](#), [const](#) [uint](#) &[i](#), [const](#) [uint](#) &[j](#))

## Public Attributes

- [uint](#) [N](#)
- [uint](#) [M](#)
- bool [delete\\_counters](#) = true
- bool [delete\\_rules](#) = true
- bool [delete\\_rules\\_dyn](#) = true
- [uint](#) [max\\_num\\_elements](#) = [BARRY\\_MAX\\_NUM\\_ELEMENTS](#)
- [std::vector](#)< [double](#) > [current\\_stats](#)
- [std::vector](#)< [size\\_t](#) > [coordinates\\_free](#)
- [std::vector](#)< [size\\_t](#) > [coordinates\\_locked](#)
- [size\\_t](#) [cooriantes\\_n\\_free](#)
- [size\\_t](#) [cooriantes\\_n\\_locked](#)
- [std::vector](#)< [double](#) > [change\\_stats](#)
- [std::vector](#)< [size\\_t](#) > [hashes](#)
- [std::vector](#)< bool > [hashes\\_initialized](#)
- [size\\_t](#) [n\\_counters](#)

### 8.41.1 Detailed Description

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool,
typename Data_Rule_Dyn_Type = bool>
class Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

Compute the support of sufficient statistics.

Given an array and a set of counters, this object iterates throughout the support set of the Array while at the same time computing the support of the sufficient statitics.

The members `rule` and `rule_dyn` allow constraining the support. The first will establish which cells of the array will be used to iterate, for example, in the case of social networks, self-loops are not allowed, so the entire diagonal would be fixed to zero, reducing the size of the support.

In the case of `rule_dyn`, the function will stablish dynamically whether the current state will be included in the counts or not. For example, this set of rules can be used to constrain the support to networks that have a prescribed degree sequence.

Definition at line 42 of file support-bones.hpp.

## 8.41.2 Constructor & Destructor Documentation

### 8.41.2.1 Support() [1/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    const Array_Type & Array_ ) [inline]
```

Constructor passing a reference Array.

Definition at line 87 of file support-bones.hpp.

### 8.41.2.2 Support() [2/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    uint N_,
    uint M_ ) [inline]
```

Constructor specifying the dimensions of the array (empty).

Definition at line 96 of file support-bones.hpp.

### 8.41.2.3 Support() [3/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support ( )
[inline]
```

Definition at line 103 of file support-bones.hpp.

### 8.41.2.4 ~Support()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~Support ( )
[inline]
```

Definition at line 110 of file support-bones.hpp.

## 8.41.3 Member Function Documentation

### 8.41.3.1 add\_counter()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter
(
    Counter< Array_Type, Data_Counter_Type > f_ )
```

### 8.41.3.2 add\_rule() [1/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > * f_ )
```

### 8.41.3.3 add\_rule() [2/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > f_ )
```

### 8.41.3.4 add\_rule\_dyn() [1/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > * f_ )
```

### 8.41.3.5 add\_rule\_dyn() [2/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > f_ )
```



### 8.41.3.6 calc()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::calc (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr,
    unsigned int max_num_elements_ = 0u )
```

Computes the entire support.

Not to be used by the user. Sets the starting point in the array (column-major).

#### Parameters

<i>array_bank</i>	If specified, the counter will add to the vector each possible state of the array, as it counts.
<i>stats_bank</i>	If specified, the counter will add to the vector each possible set of statistics, as it counts.

### 8.41.3.7 eval\_rules\_dyn()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::eval_↵
rules_dyn (
    const std::vector< double > & counts,
    const uint & i,
    const uint & j )
```

### 8.41.3.8 get\_counters()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Counters<Array_Type,Data_Counter_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_counters ( )
```

Vector of couter functions.

### 8.41.3.9 get\_counts()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::get_counts ( ) const
```

#### 8.41.3.10 get\_current\_stats()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double >* Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_↵
Dyn_Type >::get_current_stats ( )
```

List current statistics.

#### 8.41.3.11 get\_data()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const FreqTable< double >& Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::get_data ( ) const
```

#### 8.41.3.12 get\_rules()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules ( )
```

Vector of static rules (cells to iterate).

#### 8.41.3.13 get\_rules\_dyn()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Dyn_Type>* Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn ( )
```

Vector of dynamic rules (to include/exclude a realization).

#### 8.41.3.14 init\_support()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::init_↵
support (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr )
```

### 8.41.3.15 print()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print ( )
const
```

### 8.41.3.16 reset\_array() [1/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
( )
```

### 8.41.3.17 reset\_array() [2/2]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
(
    const Array_Type & Array_ )
```

### 8.41.3.18 set\_counters()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_↵
counters (
    Counters< Array_Type, Data_Counter_Type > * counters_ )
```

### 8.41.3.19 set\_rules()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ )
```

### 8.41.3.20 set\_rules\_dyn()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules←
_dyn (
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ )
```

## 8.41.4 Member Data Documentation

### 8.41.4.1 change\_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn←
_Type >::change_stats
```

Definition at line 80 of file support-bones.hpp.

### 8.41.4.2 coordiantes\_n\_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes←
_n_free
```

Definition at line 78 of file support-bones.hpp.

### 8.41.4.3 coordiantes\_n\_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes←
_n_locked
```

Definition at line 79 of file support-bones.hpp.

#### 8.41.4.4 coordinates\_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordinates_free
```

Definition at line 76 of file support-bones.hpp.

#### 8.41.4.5 coordinates\_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordinates_locked
```

Definition at line 77 of file support-bones.hpp.

#### 8.41.4.6 current\_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::current_stats
```

Definition at line 75 of file support-bones.hpp.

#### 8.41.4.7 delete\_counters

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_counters = true
```

Definition at line 69 of file support-bones.hpp.

#### 8.41.4.8 delete\_rules

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rules = true
```

Definition at line 70 of file support-bones.hpp.

#### 8.41.4.9 delete\_rules\_dyn

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
rules_dyn = true
```

Definition at line 71 of file support-bones.hpp.

#### 8.41.4.10 hashes

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::hashes
```

Definition at line 81 of file support-bones.hpp.

#### 8.41.4.11 hashes\_initialized

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< bool > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::hashes_initialized
```

Definition at line 82 of file support-bones.hpp.

#### 8.41.4.12 M

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::M
```

Definition at line 68 of file support-bones.hpp.

#### 8.41.4.13 max\_num\_elements

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::max_num_↵
elements = BARRY_MAX_NUM_ELEMENTS
```

Definition at line 72 of file support-bones.hpp.

**8.41.4.14 N**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
uint Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >:N
```

Definition at line 68 of file support-bones.hpp.

**8.41.4.15 n\_counters**

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >:n↵
counters
```

Definition at line 83 of file support-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/support-bones.hpp](#)

**8.42 vecHasher< T > Struct Template Reference**

```
#include <typedefs.hpp>
```

**Public Member Functions**

- `std::size_t operator() (std::vector< T > const &dat) const noexcept`

**8.42.1 Detailed Description**

```
template<typename T>
struct vecHasher< T >
```

Definition at line 106 of file typedefs.hpp.

**8.42.2 Member Function Documentation****8.42.2.1 operator()()**

```
template<typename T >
std::size_t vecHasher< T >:operator() (
    std::vector< T > const & dat ) const [inline], [noexcept]
```

Definition at line 109 of file typedefs.hpp.

The documentation for this struct was generated from the following file:

- [include/barry/typedefs.hpp](#)






## Chapter 9

# File Documentation

### 9.1 `include/barry/barray-bones.hpp` File Reference

This graph shows which files directly or indirectly include this file:



#### Classes

- class `BArray< Cell_Type, Data_Type >`  
*Baseline class for binary arrays.*


### 9.2 `include/barry/barray-iterator.hpp` File Reference

#### Classes

- class `ConstBArrayRowIter< Cell_Type, Data_Type >`

## 9.3 include/barry/barray-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define BARRAY_TYPE() BArray<Cell_Type, Data_Type>`
- `#define BARRAY_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BARRAY_TEMPLATE(a, b) template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`

### Functions

- `template BARRAY_TEMPLATE_ARGS () inline void checkdim_(const BARRAY_TYPE() &lhs`
- `template const BARRAY_TYPE () &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+)(const BArray< Cell_Type`
- `for (uint i=0u;i< nrow();++i) for(uint j=0u = el[POS(i, j)]`
- `j< ncol();++j) this-> operator() (i, j)+`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-)(const BArray< Cell_Type`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator*=(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator/=(const Cell_Type &rhs)`

### Variables

- `Data_Type & rhs`
- `return * this`

#### 9.3.1 Macro Definition Documentation

#### 9.3.1.1 BARRAY\_TEMPLATE

```
#define BARRAY_TEMPLATE(  
    a,  
    b )  template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b
```

Definition at line 11 of file barray-meat-operators.hpp.

#### 9.3.1.2 BARRAY\_TEMPLATE\_ARGS

```
template BARRAY_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file barray-meat-operators.hpp.

#### 9.3.1.3 BARRAY\_TYPE

```
template Data_Type BARRAY_TYPE( ) BArray<Cell_Type, Data_Type>
```

Definition at line 7 of file barray-meat-operators.hpp.

#### 9.3.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 15 of file barray-meat-operators.hpp.

#### 9.3.1.5 ROW

```
#define ROW(  
    a )  this->el_ij[a]
```

Definition at line 14 of file barray-meat-operators.hpp.

### 9.3.2 Function Documentation

### 9.3.2.1 BARRAY\_TEMPLATE() [1/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator* ) const &
```

Definition at line 88 of file barray-meat-operators.hpp.

### 9.3.2.2 BARRAY\_TEMPLATE() [2/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const
```

### 9.3.2.3 BARRAY\_TEMPLATE() [3/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const &
```

Definition at line 46 of file barray-meat-operators.hpp.

### 9.3.2.4 BARRAY\_TEMPLATE() [4/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const
```

### 9.3.2.5 BARRAY\_TEMPLATE() [5/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const &
```

Definition at line 75 of file barray-meat-operators.hpp.

### 9.3.2.6 BARRAY\_TEMPLATE() [6/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator/ ) const &
```

Definition at line 105 of file barray-meat-operators.hpp.

### 9.3.2.7 BARRAY\_TEMPLATE\_ARGS()

```
template BARRAY_TEMPLATE_ARGS ( ) const &
```

### 9.3.2.8 BARRAY\_TYPE()

```
template const BARRAY_TYPE ( ) &
```

Definition at line 20 of file barray-meat-operators.hpp.

### 9.3.2.9 for()

```
for ( ) = el[POS(i, j)] [pure virtual]
```

Definition at line 66 of file barray-meat-operators.hpp.

### 9.3.2.10 operator()()

```
j< ncol(); ++j) this-> operator() (
    i ,
    j )
```

## 9.3.3 Variable Documentation

### 9.3.3.1 rhs

Data\_Type & rhs

#### Initial value:

```
{
    checkdim_(*this, rhs)
```

Definition at line 33 of file `barray-meat-operators.hpp`.


### 9.3.3.2 this

```
return * this
```

Definition at line 43 of file `barray-meat-operators.hpp`.

## 9.4 include/barry/barray-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- #define `BARRAY_TYPE()` `BArray<Cell_Type, Data_Type>`
- #define `BARRAY_TEMPLATE_ARGS()` `<typename Cell_Type, typename Data_Type>`
- #define `BARRAY_TEMPLATE(a, b)` `template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b`
- #define `ROW(a) this->el_ij[a]`
- #define `COL(a) this->el_ji[a]`

## Functions

- [BARRAY\\_TEMPLATE](#) (, BArray)(uint N\_
- [el\\_ij](#) [resize](#) (N)
- [el\\_ji](#) [resize](#) (M)
- [for](#) (uint i=0u;i< [source.size](#)();++i)
- Data\_Type bool [M](#) (Array\_.M)
- [BARRAY\\_TEMPLATE](#) (BARRAY\_TYPE() &, operator=)(const BArray< Cell\_Type
- [BARRAY\\_TEMPLATE](#) (, BArray)(BARRAY\_TYPE() &&x) [noexcept](#)
- [BARRAY\\_TEMPLATE](#) (BARRAY\_TYPE() &, operator=)(BARRAY\_TYPE() &&x) [noexcept](#)
- [BARRAY\\_TEMPLATE](#) (bool, operator=)(const BARRAY\_TYPE() &Array\_)
- [BARRAY\\_TEMPLATE](#) (,~BArray)()
- [BARRAY\\_TEMPLATE](#) (void, set\_data)(Data\_Type \*data\_
- [BARRAY\\_TEMPLATE](#) (Data\_Type \*, D\_ptr)()
- [BARRAY\\_TEMPLATE](#) (Data\_Type &, D)()
- [BARRAY\\_TEMPLATE](#) (void, out\_of\_range)(uint i
- [BARRAY\\_TEMPLATE](#) (Cell\_Type, get\_cell)(uint i
- [if](#) ([ROW](#)(i).size()==0u) [return](#)(Cell\_Type) 0.0
- [if](#) ([search](#) !=[ROW](#)(i).end()) [return](#) [search](#) -> [second.value](#)
- [return](#) (Cell\_Type) 0.0
- [BARRAY\\_TEMPLATE](#) (std::vector< Cell\_Type >, get\_row\_vec)(uint i
- std::vector< Cell\_Type > [ans](#) ([ncol](#)(),(Cell\_Type) [false](#))
- [for](#) (const auto &iter :[row](#)(i, [false](#))) [ans](#)[iter.first]
- [BARRAY\\_TEMPLATE](#) (void, get\_row\_vec)(std
- [BARRAY\\_TEMPLATE](#) (BARRAY\_TYPE() &, operator-)(const std
- [BARRAY\\_TEMPLATE](#) (void, [insert\\_cell](#))(uint i
- [if](#) ([check\\_exists](#))
- [COL](#) (j).emplace(i
- & [ROW](#) (i)[j])
- [BARRAY\\_TEMPLATE](#) (void, swap\_cells)(uint i0
- [if](#) ([report](#) !=nullptr)(\*[report](#))
- [if](#) ([check0](#) &[check1](#))
- [else if](#) (![check0](#) &[check1](#))
- [else if](#) ([check0](#) &![check1](#))
- [BARRAY\\_TEMPLATE](#) (void, toggle\_cell)(uint i
- [BARRAY\\_TEMPLATE](#) (void, swap\_rows)(uint i0
- [if](#) ([ROW](#)(i0).size()==0u) [move0](#)
- [if](#) ([ROW](#)(i1).size()==0u) [move1](#)
- [if](#) (![move0](#) &&![move1](#)) [return](#)
- [ROW](#) (i0).swap([ROW](#)(i1))
- [BARRAY\\_TEMPLATE](#) (void, swap\_cols)(uint j0
- [if](#) ([COL](#)(j0).size()==0u) [check0](#)
- [if](#) ([COL](#)(j1).size()==0u) [check1](#)
- [if](#) ([check0](#) &&[check1](#))
- [else if](#) ([check0](#) &&![check1](#))
- [else if](#) (![check0](#) &&[check1](#))
- [BARRAY\\_TEMPLATE](#) (void, zero\_row)(uint i
- [for](#) (auto row=[row0](#).begin();row !=[row0](#).end();++row) [rm\\_cell](#)(i
- [BARRAY\\_TEMPLATE](#) (void, zero\_col)(uint j
- [if](#) ([COL](#)(j).size()==0u) [return](#)
- [BARRAY\\_TEMPLATE](#) (void, transpose)()
- [BARRAY\\_TEMPLATE](#) (void, [clear](#))(bool hard)
- [BARRAY\\_TEMPLATE](#) (void, [resize](#))(uint N\_
- [if](#) (M\_< M) [for](#)(uint j = N\_

## Variables

- `uint M_`
- `uint const std::vector< uint > & source`
- `uint const std::vector< uint > const std::vector< uint > & target`
- `uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type > & value`
- `uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type > bool add`
- `if(source.size() !=value.size()) throw std N = N_`
- `M = M_`
- `return`
- `Data_Type & Array_`
- `Data_Type bool copy_data`
- `bool delete_data_`
- `data = data_`
- `delete_data = delete_data_`
- `uint j const`
- `uint j`
- `auto search = ROW(i).find(j)`
- `return ans`
- `uint const Cell< Cell_Type > & v`
- `uint const Cell< Cell_Type > bool check_bounds`
- `uint const Cell< Cell_Type > bool bool check_exists`
- `else`
- `NCells`
- `uint j0`
- `uint uint i1`
- `uint uint uint j1`
- `uint uint uint bool int int * report`
- `auto row0 = ROW(i)`
- `row first`
- `row false`
- `auto col0 = COL(j)`

## 9.4.1 Macro Definition Documentation

### 9.4.1.1 BARRAY\_TEMPLATE

```
#define BARRAY_TEMPLATE(
    a,
    b )  template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b
```

Definition at line 17 of file `barray-meat.hpp`.

### 9.4.1.2 BARRAY\_TEMPLATE\_ARGS

```
#define BARRAY_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 15 of file `barray-meat.hpp`.



### 9.4.1.3 BARRAY\_TYPE

```
#define BARRAY_TYPE( ) BArray<Cell_Type, Data_Type>
```

Definition at line 13 of file barray-meat.hpp.

### 9.4.1.4 COL

```
#define COL(  
    a ) this->el_ji[a]
```

Definition at line 21 of file barray-meat.hpp.

### 9.4.1.5 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 20 of file barray-meat.hpp.

## 9.4.2 Function Documentation

### 9.4.2.1 ans()

```
std::vector< Cell_Type > ans (  
    ncol() ,  
    (Cell_Type) false )
```

### 9.4.2.2 BARRAY\_TEMPLATE() [1/24]

```
BARRAY_TEMPLATE (  
    BArray ) && [noexcept]
```

Definition at line 230 of file barray-meat.hpp.

#### 9.4.2.3 BARRAY\_TEMPLATE() [2/24]

```
BARRAY_TEMPLATE (
    BArray )
```

#### 9.4.2.4 BARRAY\_TEMPLATE() [3/24]

```
BARRAY_TEMPLATE (
    ~ BArray )
```

Definition at line 339 of file barray-meat.hpp.

#### 9.4.2.5 BARRAY\_TEMPLATE() [4/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const
```

Definition at line 597 of file barray-meat.hpp.

#### 9.4.2.6 BARRAY\_TEMPLATE() [5/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator ) && [noexcept]
```

Definition at line 272 of file barray-meat.hpp.

#### 9.4.2.7 BARRAY\_TEMPLATE() [6/24]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator ) const
```

#### 9.4.2.8 BARRAY\_TEMPLATE() [7/24]

```
BARRAY_TEMPLATE (
    bool ,
    operator == ) const &
```

Definition at line 321 of file barray-meat.hpp.

#### 9.4.2.9 BARRAY\_TEMPLATE() [8/24]

```
BARRAY_TEMPLATE (
    Cell_Type ,
    get_cell )
```

#### 9.4.2.10 BARRAY\_TEMPLATE() [9/24]

```
BARRAY_TEMPLATE (
    Data_Type & ,
    D )
```

Definition at line 372 of file barray-meat.hpp.

#### 9.4.2.11 BARRAY\_TEMPLATE() [10/24]

```
BARRAY_TEMPLATE (
    Data_Type * ,
    D_ptr )
```

Definition at line 361 of file barray-meat.hpp.

#### 9.4.2.12 BARRAY\_TEMPLATE() [11/24]

```
BARRAY_TEMPLATE (
    std::vector< Cell_Type > ,
    get_row_vec )
```

#### 9.4.2.13 BARRAY\_TEMPLATE() [12/24]

```
BARRAY_TEMPLATE (
    void ,
    clear )
```

Definition at line 1130 of file barray-meat.hpp.

**9.4.2.14 BARRAY\_TEMPLATE()** [13/24]

```
BARRAY_TEMPLATE (
    void ,
    get_row_vec )
```

Definition at line 452 of file barray-meat.hpp.

**9.4.2.15 BARRAY\_TEMPLATE()** [14/24]

```
BARRAY_TEMPLATE (
    void ,
    insert_cell )
```

**9.4.2.16 BARRAY\_TEMPLATE()** [15/24]

```
BARRAY_TEMPLATE (
    void ,
    out_of_range )
```

**9.4.2.17 BARRAY\_TEMPLATE()** [16/24]

```
BARRAY_TEMPLATE (
    void ,
    resize )
```

**9.4.2.18 BARRAY\_TEMPLATE()** [17/24]

```
BARRAY_TEMPLATE (
    void ,
    set_data )
```

**9.4.2.19 BARRAY\_TEMPLATE()** [18/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_cells )
```

**9.4.2.20 BARRAY\_TEMPLATE()** [19/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_cols )
```

**9.4.2.21 BARRAY\_TEMPLATE()** [20/24]

```
BARRAY_TEMPLATE (
    void ,
    swap_rows )
```

**9.4.2.22 BARRAY\_TEMPLATE()** [21/24]

```
BARRAY_TEMPLATE (
    void ,
    toggle_cell )
```

**9.4.2.23 BARRAY\_TEMPLATE()** [22/24]

```
BARRAY_TEMPLATE (
    void ,
    transpose )
```

Definition at line 1069 of file barray-meat.hpp.

**9.4.2.24 BARRAY\_TEMPLATE()** [23/24]

```
BARRAY_TEMPLATE (
    void ,
    zero_col )
```

**9.4.2.25 BARRAY\_TEMPLATE()** [24/24]

```
BARRAY_TEMPLATE (
    void ,
    zero_row )
```

#### 9.4.2.26 COL()

```
COL (
    j )
```

#### 9.4.2.27 for() [1/3]

```
for (
    auto row = row0.begin(); row != row0.end(); ++row )
```

#### 9.4.2.28 for() [2/3]

```
for (
    const auto &iter : rowi, false )
```

#### 9.4.2.29 for() [3/3]

```
for ( )
```

Definition at line 51 of file barray-meat.hpp.

#### 9.4.2.30 if() [1/17]

```
else if (
    !check0 && check1 )
```

Definition at line 1008 of file barray-meat.hpp.

#### 9.4.2.31 if() [2/17]

```
else if (
    !check0 & check1 )
```

Definition at line 856 of file barray-meat.hpp.

**9.4.2.32 if() [3/17]**

```
if (
    !move0 &&!  move1 )
```

**9.4.2.33 if() [4/17]**

```
else if (
    check0 &!  check1 )
```

Definition at line 864 of file barray-meat.hpp.

**9.4.2.34 if() [5/17]**

```
else if (
    check0 &&!  check1 )
```

Definition at line 999 of file barray-meat.hpp.

**9.4.2.35 if() [6/17]**

```
if (
    check0 &&  check1 )
```

Definition at line 972 of file barray-meat.hpp.

**9.4.2.36 if() [7/17]**

```
if (
    check0 &  check1 )
```

Definition at line 838 of file barray-meat.hpp.

**9.4.2.37 if() [8/17]**

```
else if (
    check_exists  == CHECK::BOTH )
```

Definition at line 679 of file barray-meat.hpp.

**9.4.2.38 if()** [9/17]

```
if (
    COL(j).size() == 0u )
```

**9.4.2.39 if()** [10/17]

```
if (
    COL(j0).size() == 0u )
```

**9.4.2.40 if()** [11/17]

```
if (
    COL(j1).size() == 0u )
```

**9.4.2.41 if()** [12/17]

```
else if ( ) = N_
```

Definition at line 86 of file barray-meat.hpp.

**9.4.2.42 if()** [13/17]

```
if (
    report ! == nullptr )
```

**9.4.2.43 if()** [14/17]

```
if (
    ROW(i).size() == 0u )
```

**9.4.2.44 if()** [15/17]

```
if (
    ROW(i0).size() == 0u )
```



**9.4.2.45 if() [16/17]**

```
if (
    ROW(i1).size() == 0u )
```

**9.4.2.46 if() [17/17]**

```
if (
    search ! = ROW(i).end() ) -> second.value
```

**9.4.2.47 M()**

```
Data_Type bool M (
    Array_ M )
```

Definition at line 136 of file barray-meat.hpp.

**9.4.2.48 resize() [1/2]**

```
el_ji resize (
    M )
```

**9.4.2.49 resize() [2/2]**

```
el_ij resize (
    N )
```

**9.4.2.50 return()**

```
return (
    Cell_Type )
```

**9.4.2.51 ROW() [1/2]**

```
& ROW (
    i )
```

**9.4.2.52 ROW() [2/2]**

```
ROW (
    i0 )
```

**9.4.3 Variable Documentation****9.4.3.1 add**

```
uint const std::vector< uint > const std::vector< uint > bool add
```

**Initial value:**

```
{
    if (source.size() != target.size())
        throw std::length_error("-source- and -target- don't match on length.")
```

Definition at line 34 of file barray-meat.hpp.

**9.4.3.2 ans**

```
return ans
```

Definition at line 449 of file barray-meat.hpp.

**9.4.3.3 Array\_**

```
Data_Type & Array_
```

Definition at line 134 of file barray-meat.hpp.

#### 9.4.3.4 check\_bounds

bool check\_bounds

##### Initial value:

```
{  
    if (check_bounds) {  
        out_of_range(i0,0u);  
        out_of_range(i1,0u);  
    }  
  
    bool move0=true, move1=true
```

Definition at line 672 of file barray-meat.hpp.

#### 9.4.3.5 check\_exists

uint bool int check\_exists

##### Initial value:

```
{  
    if (check_bounds)  
        out_of_range(i,j)
```

Definition at line 673 of file barray-meat.hpp.

#### 9.4.3.6 col0

auto col0 = COL(j)

Definition at line 1061 of file barray-meat.hpp.

#### 9.4.3.7 const

uint bool check\_bounds const

##### Initial value:

```
{  
    if (i >= N)  
        throw std::range_error("The row is out of range.")
```

Definition at line 402 of file barray-meat.hpp.

#### 9.4.3.8 copy\_data

```
Data_Type bool copy_data
```

Definition at line 135 of file barray-meat.hpp.

#### 9.4.3.9 data

```
data = data_
```

Definition at line 354 of file barray-meat.hpp.

#### 9.4.3.10 delete\_data

```
delete_data = delete_data_
```

Definition at line 355 of file barray-meat.hpp.

#### 9.4.3.11 delete\_data\_

```
bool delete_data_
```

##### Initial value:

```
{  
    if ((data != nullptr) && delete_data)  
        delete data
```

Definition at line 348 of file barray-meat.hpp.

#### 9.4.3.12 else

```
else (  
    void )
```

##### Initial value:

```
{  
    ROW(i).insert(std::pair< uint, Cell<Cell_Type>>(j, v))
```

Definition at line 703 of file barray-meat.hpp.

#### 9.4.3.13 false

```
row false
```

Definition at line 1042 of file barray-meat.hpp.

#### 9.4.3.14 first

```
row first
```

Definition at line 1042 of file barray-meat.hpp.

#### 9.4.3.15 i1

```
uint i1
```

Definition at line 776 of file barray-meat.hpp.

#### 9.4.3.16 j

```
uint j
```

##### Initial value:

```
{  
    if (init_fun == nullptr)  
        return 0.0
```

Definition at line 414 of file barray-meat.hpp.

#### 9.4.3.17 j0

```
uint j0
```

Definition at line 775 of file barray-meat.hpp.

#### 9.4.3.18 j1

```
uint j1
```

Definition at line 776 of file barray-meat.hpp.

#### 9.4.3.19 M

M = M\_

Definition at line 44 of file barray-meat.hpp.

#### 9.4.3.20 M\_

uint M\_

##### Initial value:

```
{  
  
    if (N_ < N)  
        for (uint i = N_; i < N; ++i)  
            zero_row(i, false)
```

Definition at line 30 of file barray-meat.hpp.

#### 9.4.3.21 N

```
if (source.size() != target.size()) throw std::if (source.size() != value.size()) throw std::N =  
N_
```

Definition at line 43 of file barray-meat.hpp.

#### 9.4.3.22 NCells

NCells

Definition at line 707 of file barray-meat.hpp.

#### 9.4.3.23 report

uint uint uint bool int int\* report

Definition at line 779 of file barray-meat.hpp.

#### 9.4.3.24 return

```
return
```

Definition at line 66 of file barray-meat.hpp.

#### 9.4.3.25 row0

```
auto row0 = ROW(i)
```

Definition at line 1040 of file barray-meat.hpp.

#### 9.4.3.26 search

```
auto search = ROW(i).find(j)
```

Definition at line 426 of file barray-meat.hpp.

#### 9.4.3.27 source

```
uint const std::vector< uint > & source
```

Definition at line 31 of file barray-meat.hpp.

#### 9.4.3.28 target

```
uint const std::vector< uint > const std::vector< uint > & target
```

Definition at line 32 of file barray-meat.hpp.

#### 9.4.3.29 v

```
uint Cell_Type v
```

Definition at line 671 of file barray-meat.hpp.


#### 9.4.3.30 value

```
uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type >&  
value
```

Definition at line 33 of file barray-meat.hpp.

## 9.5 include/barry/barraycell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [BArrayCell< Cell\\_Type, Data\\_Type >](#)
- class [BArrayCell\\_const< Cell\\_Type, Data\\_Type >](#)

## 9.6 include/barry/barraycell-meat.hpp File Reference


This graph shows which files directly or indirectly include this file:





## 9.7 include/barry/barraydense-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [BArrayDense< Cell\\_Type, Data\\_Type >](#)  
*Baseline class for binary arrays.*

## 9.8 include/barry/barraydense-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define [BDENSE\\_TYPE\(\)](#) [BArrayDense<Cell\\_Type, Data\\_Type>](#)
- #define [BDENSE\\_TEMPLATE\\_ARGS\(\)](#) [<typename Cell\\_Type, typename Data\\_Type>](#)
- #define [BDENSE\\_TEMPLATE\(a, b\)](#) [template BDENSE\\_TEMPLATE\\_ARGS\(\) inline a BDENSE\\_TYPE\(\)::b](#)
- #define [ROW\(a\)](#) [this->el\\_ij\[a\]](#)
- #define [COL\(a\)](#) [this->el\\_ji\[a\]](#)
- #define [POS\(a, b\)](#) [\(b\)\\*N + \(a\)](#)
- #define [POS\\_N\(a, b, c\)](#) [\(b\)\\*\(c\) + \(a\)](#)

## Functions

- template `BDENSE_TEMPLATE_ARGS` () inline void `checkdim_(const BDENSE_TYPE) &lhs`
- template `const BDENSE_TYPE` () &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator+=)(`const BDENSE_TYPE`() &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator-=)(`const BDENSE_TYPE`() &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator\*=)(`const Cell_Type` &rhs)
- `BDENSE_TEMPLATE` (`BDENSE_TYPE`()&, operator/=(`const Cell_Type` &rhs)

## 9.8.1 Macro Definition Documentation

### 9.8.1.1 BDENSE\_TEMPLATE

```
#define BDENSE_TEMPLATE(  
    a,  
    b )  template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE()::b
```

Definition at line 11 of file `barraydense-meat-operators.hpp`.

### 9.8.1.2 BDENSE\_TEMPLATE\_ARGS

```
template BDENSE_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file `barraydense-meat-operators.hpp`.

### 9.8.1.3 BDENSE\_TYPE

```
template Data_Type BDENSE_TYPE( ) BArrayDense<Cell_Type, Data_Type>
```

Definition at line 7 of file `barraydense-meat-operators.hpp`.

### 9.8.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 15 of file `barraydense-meat-operators.hpp`.

### 9.8.1.5 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 16 of file barraydense-meat-operators.hpp.

### 9.8.1.6 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 17 of file barraydense-meat-operators.hpp.

### 9.8.1.7 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 14 of file barraydense-meat-operators.hpp.

## 9.8.2 Function Documentation

### 9.8.2.1 BDENSE\_TEMPLATE() [1/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator* ) const &
```

Definition at line 90 of file barraydense-meat-operators.hpp.

### 9.8.2.2 BDENSE\_TEMPLATE() [2/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator+ ) const &
```

Definition at line 34 of file barraydense-meat-operators.hpp.

### 9.8.2.3 BDENSE\_TEMPLATE() [3/4]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator- ) const &
```

Definition at line 61 of file barrydense-meat-operators.hpp.

### 9.8.2.4 BDENSE\_TEMPLATE() [4/4]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator/ ) const &
```

Definition at line 101 of file barrydense-meat-operators.hpp.

### 9.8.2.5 BDENSE\_TEMPLATE\_ARGS()

```
template BDENSE_TEMPLATE_ARGS ( ) const &
```


### 9.8.2.6 BDENSE\_TYPE()

```
template const BDENSE_TYPE ( ) &
```

Definition at line 22 of file barrydense-meat-operators.hpp.

## 9.9 include/barry/barrydense-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- `#define BDENSE_TYPE() BArrayDense<Cell_Type, Data_Type>`
- `#define BDENSE_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BDENSE_TEMPLATE(a, b) template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE():b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`
- `#define POS(a, b) (b)*N + (a)`
- `#define POS_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO_CELL static_cast<Cell_Type>(0.0)`

## Functions

- `BDENSE_TEMPLATE (, BArrayDense)(uint N_`
- `el resize (N *M, ZERO_CELL)`
- `el_rowsums resize (N, ZERO_CELL)`
- `el_colsums resize (M, ZERO_CELL)`
- `for (uint i=0u;i< source.size();++i)`
- `BDENSE_TEMPLATE (, BArrayDense)(const BDENSE_TYPE() &Array_`
- `bool M (Array_.M)`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator=)(const BDENSE_TYPE() &Array_)`
- `BDENSE_TEMPLATE (, BArrayDense)(BDENSE_TYPE() &&x) noexcept`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator=)(BDENSE_TYPE() &&x) noexcept`
- `BDENSE_TEMPLATE (bool, operator==)(const BDENSE_TYPE() &Array_)`
- `BDENSE_TEMPLATE (, ~BArrayDense)()`
- `BDENSE_TEMPLATE (void, set_data)(Data_Type *data_`
- `BDENSE_TEMPLATE (Data_Type *, D_ptr)()`
- `BDENSE_TEMPLATE (const Data_Type *, D_ptr)() const`
- `BDENSE_TEMPLATE (Data_Type &, D)()`
- `BDENSE_TEMPLATE (const Data_Type &, D)() const`
- `BDENSE_TEMPLATE (void, out_of_range)(uint i`
- `BDENSE_TEMPLATE (Cell_Type, get_cell)(uint i`
- `BDENSE_TEMPLATE (std::vector< Cell_Type >, get_row_vec)(uint i`
- `std::vector< Cell_Type > ans (ncol(), static_cast< Cell_Type >(false))`
- `BDENSE_TEMPLATE (void, get_row_vec)(std`
- `BDENSE_TEMPLATE (Entries< Cell_Type >, get_entries)() const`
- `BDENSE_TEMPLATE (bool, is_empty)(uint i`
- `BDENSE_TEMPLATE (unsigned int, nrow)() const noexcept`
- `BDENSE_TEMPLATE (unsigned int, ncol)() const noexcept`
- `BDENSE_TEMPLATE (unsigned int, nnonzero)() const noexcept`
- `BDENSE_TEMPLATE (Cell< Cell_Type >, default_val)() const`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator+=)(const std`
- `BDENSE_TEMPLATE (BDENSE_TYPE() &, operator-=)(const std`
- `BDENSE_TEMPLATE (void, insert_cell)(uint i`
- `if (el[POS(i, j)]==BARRY_ZERO_DENSE)`
- `BDENSE_TEMPLATE (void, swap_cells)(uint i0`
- `if ((i0==i1) &&(j0==j1)) return`
- `rm_cell (i0, j0, false, false)`
- `rm_cell (i1, j1, false, false)`
- `insert_cell (i0, j0, val1, false, false)`
- `insert_cell (i1, j1, val0, false, false)`
- `BDENSE_TEMPLATE (void, toggle_cell)(uint i`
- `else rm_cell (i, j, false, false)`
- `BDENSE_TEMPLATE (void, swap_rows)(uint i0`

- `BDENSE_TEMPLATE` (void, swap\_cols)(uint j0
- `BDENSE_TEMPLATE` (void, zero\_row)(uint i
- `if` (el\_rowsums[i]==ZERO\_CELL) `return`
- `BDENSE_TEMPLATE` (void, zero\_col)(uint j
- `if` (el\_colsums[j]==ZERO\_CELL) `return`
- `BDENSE_TEMPLATE` (void, transpose)()
- `BDENSE_TEMPLATE` (void, clear)(bool hard)
- `BDENSE_TEMPLATE` (void, resize)(uint N\_
- `el` `resize` (N\_\*M\_, ZERO\_CELL)
- `el_rowsums` `resize` (N\_, ZERO\_CELL)
- `el_colsums` `resize` (M\_, ZERO\_CELL)
- `BDENSE_TEMPLATE` (void, reserve)()
- `BDENSE_TEMPLATE` (void, print)(const char \*fmt
- `va_start` (args, fmt)
- `vprintf` (fmt, args)
- `va_end` (args)
- `BDENSE_TEMPLATE` (const std::vector< Cell\_Type > &, get\_data)() `const`
- `BDENSE_TEMPLATE` (const Cell\_Type, rowsum)(unsigned int i) `const`
- `BDENSE_TEMPLATE` (const Cell\_Type, colsum)(unsigned int j) `const`

## Variables

- `uint` `M_`
- `uint` `const` `std::vector< uint > & source`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > & target`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > const` `std::vector< Cell_Type > & value`
- `uint` `const` `std::vector< uint > const` `std::vector< uint > const` `std::vector< Cell_Type > bool add`
- `if`(source.size() !=value.size()) `throw` `std` `N` = `N_`
- `M` = `M_`
- `return`
- `bool` `copy_data`
- `bool` `delete_data_`
- `data` = `data_`
- `delete_data` = `delete_data_`
- `uint` `j` `const`
- `uint` `j`
- `return` `el` [`POS`(i, j)] == `ZERO_CELL`
- `return` `ans`
- `uint` `const` `Cell`< `Cell_Type` > & `v`
- `uint` `const` `Cell`< `Cell_Type` > `bool` `check_bounds`
- `uint` `const` `Cell`< `Cell_Type` > `bool` `bool` `check_exists`
- `else`
- `el_rowsums` [`i`] = (`v.value` - `old`)
- `el_colsums` [`j`] = (`v.value` - `old`)
- `uint` `j0`
- `uint` `uint` `i1`
- `uint` `uint` `uint` `j1`
- `uint` `uint` `uint` `bool` `int` `int` \* `report`
- `Cell_Type` `val0` = `el`[`POS`(i0,j0)]
- `Cell_Type` `val1` = `el`[`POS`(i1,j1)]
- `false`
- `col`

## 9.9.1 Macro Definition Documentation

### 9.9.1.1 BDENSE\_TEMPLATE

```
#define BDENSE_TEMPLATE(  
    a,  
    b )  template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE()::b
```

Definition at line 27 of file barraydense-meat.hpp.

### 9.9.1.2 BDENSE\_TEMPLATE\_ARGS

```
#define BDENSE_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 25 of file barraydense-meat.hpp.

### 9.9.1.3 BDENSE\_TYPE

```
#define BDENSE_TYPE( ) BArrayDense<Cell_Type, Data_Type>
```

Definition at line 23 of file barraydense-meat.hpp.

### 9.9.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 31 of file barraydense-meat.hpp.

### 9.9.1.5 POS

```
#define POS(  
    a,  
    b )  (b)*N + (a)
```

Definition at line 32 of file barraydense-meat.hpp.

### 9.9.1.6 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 33 of file bararraydense-meat.hpp.

### 9.9.1.7 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 30 of file bararraydense-meat.hpp.

### 9.9.1.8 ZERO\_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 38 of file bararraydense-meat.hpp.

## 9.9.2 Function Documentation

### 9.9.2.1 ans()

```
std::vector< Cell_Type > ans (  
    ncol() ,  
    static_cast< Cell_Type > false )
```

### 9.9.2.2 BDENSE\_TEMPLATE() [1/39]

```
BDENSE_TEMPLATE (  
    BArrayDense ) && [noexcept]
```

Definition at line 240 of file bararraydense-meat.hpp.



### 9.9.2.3 BDENSE\_TEMPLATE() [2/39]

```
BDENSE_TEMPLATE (
    BArrayDense ) const &
```

### 9.9.2.4 BDENSE\_TEMPLATE() [3/39]

```
BDENSE_TEMPLATE (
    BArrayDense )
```

### 9.9.2.5 BDENSE\_TEMPLATE() [4/39]

```
BDENSE_TEMPLATE (
    ~ BArrayDense )
```

Definition at line 318 of file barraydense-meat.hpp.

### 9.9.2.6 BDENSE\_TEMPLATE() [5/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator+ ) const
```

Definition at line 566 of file barraydense-meat.hpp.

### 9.9.2.7 BDENSE\_TEMPLATE() [6/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator- ) const
```

Definition at line 584 of file barraydense-meat.hpp.

### 9.9.2.8 BDENSE\_TEMPLATE() [7/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator ) && [noexcept]
```

Definition at line 257 of file barraydense-meat.hpp.

#### 9.9.2.9 BDENSE\_TEMPLATE() [8/39]

```
BDENSE_TEMPLATE (
    BDENSE_TYPE() & ,
    operator ) const &
```

Definition at line 194 of file bararraydense-meat.hpp.

#### 9.9.2.10 BDENSE\_TEMPLATE() [9/39]

```
BDENSE_TEMPLATE (
    bool ,
    is_empty )
```

#### 9.9.2.11 BDENSE\_TEMPLATE() [10/39]

```
BDENSE_TEMPLATE (
    bool ,
    operator == ) const &
```

Definition at line 300 of file bararraydense-meat.hpp.

#### 9.9.2.12 BDENSE\_TEMPLATE() [11/39]

```
BDENSE_TEMPLATE (
    Cell< Cell_Type > ,
    default_val ) const
```

Definition at line 562 of file bararraydense-meat.hpp.

#### 9.9.2.13 BDENSE\_TEMPLATE() [12/39]

```
BDENSE_TEMPLATE (
    Cell_Type ,
    get_cell )
```

**9.9.2.14 BDENSE\_TEMPLATE() [13/39]**

```
BDENSE_TEMPLATE (
    const Cell_Type,
    colsum ) const
```

Definition at line 999 of file barraydense-meat.hpp.

**9.9.2.15 BDENSE\_TEMPLATE() [14/39]**

```
BDENSE_TEMPLATE (
    const Cell_Type,
    rowsum ) const
```

Definition at line 994 of file barraydense-meat.hpp.

**9.9.2.16 BDENSE\_TEMPLATE() [15/39]**

```
BDENSE_TEMPLATE (
    const Data_Type & ,
    D ) const
```

Definition at line 353 of file barraydense-meat.hpp.

**9.9.2.17 BDENSE\_TEMPLATE() [16/39]**

```
BDENSE_TEMPLATE (
    const Data_Type * ,
    D_ptr ) const
```

Definition at line 345 of file barraydense-meat.hpp.

**9.9.2.18 BDENSE\_TEMPLATE() [17/39]**

```
BDENSE_TEMPLATE (
    const std::vector< Cell_Type > & ,
    get_data ) const
```

Definition at line 989 of file barraydense-meat.hpp.

**9.9.2.19 BDENSE\_TEMPLATE() [18/39]**

```
BDENSE_TEMPLATE (
    Data_Type & ,
    D )
```

Definition at line 349 of file bararraydense-meat.hpp.

**9.9.2.20 BDENSE\_TEMPLATE() [19/39]**

```
BDENSE_TEMPLATE (
    Data_Type * ,
    D_ptr )
```

Definition at line 341 of file bararraydense-meat.hpp.

**9.9.2.21 BDENSE\_TEMPLATE() [20/39]**

```
BDENSE_TEMPLATE (
    Entries< Cell_Type > ,
    get_entries ) const
```

Definition at line 502 of file bararraydense-meat.hpp.

**9.9.2.22 BDENSE\_TEMPLATE() [21/39]**

```
BDENSE_TEMPLATE (
    std::vector< Cell_Type > ,
    get_row_vec )
```

**9.9.2.23 BDENSE\_TEMPLATE() [22/39]**

```
BDENSE_TEMPLATE (
    unsigned int ,
    ncol ) const [noexcept]
```

Definition at line 548 of file bararraydense-meat.hpp.

**9.9.2.24 BDENSE\_TEMPLATE()** [23/39]

```
BDENSE_TEMPLATE (
    unsigned int ,
    nnozero ) const [noexcept]
```

Definition at line 552 of file barraydense-meat.hpp.

**9.9.2.25 BDENSE\_TEMPLATE()** [24/39]

```
BDENSE_TEMPLATE (
    unsigned int ,
    nrow ) const [noexcept]
```

Definition at line 544 of file barraydense-meat.hpp.

**9.9.2.26 BDENSE\_TEMPLATE()** [25/39]

```
BDENSE_TEMPLATE (
    void ,
    clear )
```

Definition at line 896 of file barraydense-meat.hpp.

**9.9.2.27 BDENSE\_TEMPLATE()** [26/39]

```
BDENSE_TEMPLATE (
    void ,
    get_row_vec )
```

Definition at line 402 of file barraydense-meat.hpp.

**9.9.2.28 BDENSE\_TEMPLATE()** [27/39]

```
BDENSE_TEMPLATE (
    void ,
    insert_cell )
```

**9.9.2.29 BDENSE\_TEMPLATE()** [28/39]

```
BDENSE_TEMPLATE (
    void ,
    out_of_range )
```

**9.9.2.30 BDENSE\_TEMPLATE()** [29/39]

```
BDENSE_TEMPLATE (
    void ,
    print ) const
```

**9.9.2.31 BDENSE\_TEMPLATE()** [30/39]

```
BDENSE_TEMPLATE (
    void ,
    reserve )
```

Definition at line 946 of file `barraydense-meat.hpp`.

**9.9.2.32 BDENSE\_TEMPLATE()** [31/39]

```
BDENSE_TEMPLATE (
    void ,
    resize )
```

**9.9.2.33 BDENSE\_TEMPLATE()** [32/39]

```
BDENSE_TEMPLATE (
    void ,
    set_data )
```

**9.9.2.34 BDENSE\_TEMPLATE()** [33/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_cells )
```

**9.9.2.35 BDENSE\_TEMPLATE()** [34/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_cols )
```

**9.9.2.36 BDENSE\_TEMPLATE()** [35/39]

```
BDENSE_TEMPLATE (
    void ,
    swap_rows )
```

**9.9.2.37 BDENSE\_TEMPLATE()** [36/39]

```
BDENSE_TEMPLATE (
    void ,
    toggle_cell )
```

**9.9.2.38 BDENSE\_TEMPLATE()** [37/39]

```
BDENSE_TEMPLATE (
    void ,
    transpose )
```

Definition at line 868 of file barraydense-meat.hpp.

**9.9.2.39 BDENSE\_TEMPLATE()** [38/39]

```
BDENSE_TEMPLATE (
    void ,
    zero_col )
```

**9.9.2.40 BDENSE\_TEMPLATE()** [39/39]

```
BDENSE_TEMPLATE (
    void ,
    zero_row )
```

#### 9.9.2.41 for()

```
for ( )
```

Definition at line 64 of file bararraydense-meat.hpp.

#### 9.9.2.42 if() [1/4]

```
if (
    (i0==i1) && (j0==j1) )
```

#### 9.9.2.43 if() [2/4]

```
if (
    el [POS(i, j)] == BARRY_ZERO_DENSE )
```

Definition at line 663 of file bararraydense-meat.hpp.

#### 9.9.2.44 if() [3/4]

```
if (
    el_colsums [j] == ZERO_CELL )
```

#### 9.9.2.45 if() [4/4]

```
if (
    el_rowsums [i] == ZERO_CELL )
```

#### 9.9.2.46 insert\_cell() [1/2]

```
insert_cell (
    i0 ,
    j0 ,
    val ,
    false ,
    false )
```



**9.9.2.47 insert\_cell()** [2/2]

```
insert_cell (
    i1 ,
    j1 ,
    val0 ,
    false ,
    false )
```

**9.9.2.48 M()**

```
bool M (
    Array_. M )
```

Definition at line 157 of file barraydense-meat.hpp.

**9.9.2.49 resize()** [1/6]

```
el_colsums resize (
    M ,
    ZERO_CELL )
```

**9.9.2.50 resize()** [2/6]

```
el_colsums resize (
    M_ ,
    ZERO_CELL )
```

**9.9.2.51 resize()** [3/6]

```
el resize (
    N * M,
    ZERO_CELL )
```

**9.9.2.52 resize()** [4/6]

```
el_rowsums resize (
    N ,
    ZERO_CELL )
```

**9.9.2.53** `resize()` [5/6]

```
el resize (
    N_ * M_,
    ZERO_CELL )
```

**9.9.2.54** `resize()` [6/6]

```
el_rowsums resize (
    N_ ,
    ZERO_CELL )
```

**9.9.2.55** `rm_cell()` [1/3]

```
else rm_cell (
    i ,
    j ,
    false ,
    false )
```

**9.9.2.56** `rm_cell()` [2/3]

```
rm_cell (
    i0 ,
    j0 ,
    false ,
    false )
```

**9.9.2.57** `rm_cell()` [3/3]

```
rm_cell (
    i1 ,
    j1 ,
    false ,
    false )
```

**9.9.2.58** `va_end()`

```
va_end (
    args )
```

### 9.9.2.59 va\_start()

```
va_start (
    args ,
    fmt )
```

### 9.9.2.60 vprintf()

```
vprintf (
    fmt ,
    args )
```

## 9.9.3 Variable Documentation

### 9.9.3.1 add

```
uint const std::vector< uint > const std::vector< uint > bool add
```

#### Initial value:

```
{
    if (source.size() != target.size())
        throw std::length_error("-source- and -target- don't match on length.")
```

Definition at line 47 of file barraydense-meat.hpp.

### 9.9.3.2 ans

```
return ans
```

Definition at line 398 of file barraydense-meat.hpp.

### 9.9.3.3 check\_bounds

```
bool check_bounds
```

#### Initial value:

```
{
    if (check_bounds)
    {
        out_of_range(i0,0u);
        out_of_range(i1,0u);
    }

    for (uint j = 0u; j < M; ++j)
        std::swap(el[POS(i0, j)], el[POS(i1, j)])
```

Definition at line 654 of file barraydense-meat.hpp.

#### 9.9.3.4 check\_exists

```
uint bool int check_exists
```

##### Initial value:

```
{  
    if (check_bounds)  
        out_of_range(i, j)
```

Definition at line 655 of file bararraydense-meat.hpp.

#### 9.9.3.5 col

```
col
```

Definition at line 843 of file bararraydense-meat.hpp.

#### 9.9.3.6 const

```
const
```

##### Initial value:

```
{  
    if (i >= N)  
        throw std::range_error("The row is out of range.")
```

Definition at line 360 of file bararraydense-meat.hpp.

#### 9.9.3.7 copy\_data

```
bool copy_data
```

Definition at line 156 of file bararraydense-meat.hpp.

#### 9.9.3.8 data

```
data = data_
```

Definition at line 334 of file bararraydense-meat.hpp.

### 9.9.3.9 delete\_data

```
delete_data = delete_data_
```

Definition at line 335 of file barraydense-meat.hpp.

### 9.9.3.10 delete\_data\_

```
bool delete_data_
```

#### Initial value:

```
{  
    if ((data != nullptr) && delete_data)  
        delete data
```

Definition at line 328 of file barraydense-meat.hpp.

### 9.9.3.11 el

```
return el == ZERO_CELL
```

Definition at line 381 of file barraydense-meat.hpp.

### 9.9.3.12 el\_colsums

```
el_colsums[j] = (v.value - old)
```

Definition at line 675 of file barraydense-meat.hpp.

### 9.9.3.13 el\_rowsums

```
el_rowsums[i] = (v.value - old)
```

Definition at line 674 of file barraydense-meat.hpp.

**9.9.3.14 else**

```
else (
    void )
```

**Initial value:**

```
{
    Cell_Type old = el[POS(i,j)]
```

Definition at line 670 of file baraydense-meat.hpp.

**9.9.3.15 false**

```
false
```

Definition at line 767 of file baraydense-meat.hpp.

**9.9.3.16 i1**

```
uint i1
```

Definition at line 721 of file baraydense-meat.hpp.

**9.9.3.17 j**

```
j
```

Definition at line 373 of file baraydense-meat.hpp.

**9.9.3.18 j0**

```
uint j0
```

Definition at line 720 of file baraydense-meat.hpp.

**9.9.3.19 j1**

```
uint j1
```

Definition at line 721 of file baraydense-meat.hpp.

### 9.9.3.20 M

M = M\_

Definition at line 57 of file barraydense-meat.hpp.

### 9.9.3.21 M\_

uint M\_

#### Initial value:

```
{  
    std::vector< Cell_Type > el_tmp(e1)
```

Definition at line 43 of file barraydense-meat.hpp.

### 9.9.3.22 N

N = N\_

Definition at line 56 of file barraydense-meat.hpp.

### 9.9.3.23 report

uint uint uint bool int int\* report

#### Initial value:

```
{  
    if (check_bounds) {  
        out_of_range(i0,j0);  
        out_of_range(i1,j1);  
    }  
  
    if (report != nullptr)  
        (*report) = EXISTS::BOTH
```

Definition at line 724 of file barraydense-meat.hpp.

### 9.9.3.24 return

return

Definition at line 94 of file barraydense-meat.hpp.

### 9.9.3.25 source

```
uint const std::vector< uint >& source
```

Definition at line 44 of file bararraydense-meat.hpp.

### 9.9.3.26 target

```
uint const std::vector< uint > const std::vector< uint >& target
```

Definition at line 45 of file bararraydense-meat.hpp.

### 9.9.3.27 v

```
uint Cell_Type v
```

Definition at line 653 of file bararraydense-meat.hpp.

### 9.9.3.28 val0

```
Cell_Type val0 = el[POS(i0,j0)]
```

Definition at line 742 of file bararraydense-meat.hpp.

### 9.9.3.29 val1

```
Cell_Type val1 = el[POS(i1,j1)]
```

Definition at line 743 of file bararraydense-meat.hpp.

### 9.9.3.30 value


```
uint const std::vector< uint > const std::vector< uint > const std::vector< Cell_Type >&  
value
```

Definition at line 46 of file bararraydense-meat.hpp.



## 9.10 include/barry/barraydensecell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [BArrayDenseCell< Cell\\_Type, Data\\_Type >](#)

### Macros

- `#define POS\(a, b\) (a) + (b) * N`

### 9.10.1 Macro Definition Documentation


#### 9.10.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * N
```

Definition at line 6 of file barraydensecell-bones.hpp.

## 9.11 include/barry/barraydensecell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define POS(a, b) (a) + (b) \* dat->N

#### 9.11.1 Macro Definition Documentation


##### 9.11.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * dat->N
```

Definition at line 6 of file barraydensecell-meat.hpp.

## 9.12 include/barry/barraydensecol-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Classes

- class [BArrayDenseCol< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseCol\\_const< Cell\\_Type, Data\\_Type >](#)

## Macros

- `#define POS(a, b) (b)*N + (a)`
- `#define POS\_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO\_CELL static_cast<Cell_Type>(0.0)`

### 9.12.1 Macro Definition Documentation

#### 9.12.1.1 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 4 of file `barraydensecol-bones.hpp`.

#### 9.12.1.2 POS\_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 5 of file `barraydensecol-bones.hpp`.


#### 9.12.1.3 ZERO\_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 6 of file `barraydensecol-bones.hpp`.

## 9.13 include/barry/barraydenserow-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [BArrayDenseRow< Cell\\_Type, Data\\_Type >](#)
- class [BArrayDenseRow\\_const< Cell\\_Type, Data\\_Type >](#)

### Macros

- #define [POS\(a, b\)](#) (b) \* [N](#) + (a)
- #define [POS\\_N\(a, b, c\)](#) (b)\*(c) + (a)
- #define [ZERO\\_CELL](#) static\_cast< Cell\_Type >(0.0)

### 9.13.1 Macro Definition Documentation

#### 9.13.1.1 POS

```
#define POS(  
    a,  
    b ) (b) * N + (a)
```

Definition at line 4 of file barraydenserow-bones.hpp.

### 9.13.1.2 POS\_N

```
#define POS_N(
    a,
    b,
    c ) (b)*(c) + (a)
```

Definition at line 5 of file barraydenserow-bones.hpp.

### 9.13.1.3 ZERO\_CELL

```
#define ZERO_CELL static_cast< Cell_Type >(0.0)
```

Definition at line 6 of file barraydenserow-bones.hpp.

## 9.14 include/barry/barrayrow-bones.hpp File Reference

### Classes

- class [BArrayRow< Cell\\_Type, Data\\_Type >](#)
- class [BArrayRow\\_const< Cell\\_Type, Data\\_Type >](#)

## 9.15 include/barry/barrayrow-meat.hpp File Reference

### Macros

- #define [BROW\\_TYPE\(\)](#) [BArrayRow<Cell\\_Type, Data\\_Type>](#)
- #define [BROW\\_TEMPLATE\\_ARGS\(\)](#) <typename Cell\_Type, typename Data\_Type>
- #define [BROW\\_TEMPLATE\(a, b\)](#) template [BROW\\_TEMPLATE\\_ARGS\(\)](#) inline a [BROW\\_TYPE\(\)](#)::b

### Functions

- [BROW\\_TEMPLATE](#) (void, operator=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator+=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator-=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator\*=)(const [BROW\\_TYPE\(\)](#) &val)
- [BROW\\_TEMPLATE](#) (void, operator/=)(const [BROW\\_TYPE\(\)](#) &val)

### 9.15.1 Macro Definition Documentation

### 9.15.1.1 BROW\_TEMPLATE

```
#define BROW_TEMPLATE(  
    a,  
    b )  template BROW_TEMPLATE_ARGS() inline a BROW_TYPE():b
```

Definition at line 8 of file bararrayrow-meat.hpp.

### 9.15.1.2 BROW\_TEMPLATE\_ARGS

```
#define BROW_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 6 of file bararrayrow-meat.hpp.

### 9.15.1.3 BROW\_TYPE

```
#define BROW_TYPE( ) BArrayRow<Cell_Type, Data_Type>
```

Definition at line 4 of file bararrayrow-meat.hpp.

## 9.15.2 Function Documentation

### 9.15.2.1 BROW\_TEMPLATE() [1/5]

```
BROW_TEMPLATE (  
    void ,  
    operator* ) const &
```

Definition at line 45 of file bararrayrow-meat.hpp.

### 9.15.2.2 BROW\_TEMPLATE() [2/5]

```
BROW_TEMPLATE (  
    void ,  
    operator+ ) const &
```

Definition at line 25 of file bararrayrow-meat.hpp.

### 9.15.2.3 BROW\_TEMPLATE() [3/5]

```
BROW_TEMPLATE (
    void ,
    operator- ) const &
```

Definition at line 34 of file barrayrow-meat.hpp.

### 9.15.2.4 BROW\_TEMPLATE() [4/5]

```
BROW_TEMPLATE (
    void ,
    operator/ ) const &
```

Definition at line 55 of file barrayrow-meat.hpp.

### 9.15.2.5 BROW\_TEMPLATE() [5/5]

```
BROW_TEMPLATE (
    void ,
    operator ) const &
```

Definition at line 11 of file barrayrow-meat.hpp.

## 9.16 include/barry/barrayvector-bones.hpp File Reference


### Classes

- class [BArrayVector< Cell\\_Type, Data\\_Type >](#)  
*Row or column of a [BArray](#)*
- class [BArrayVector\\_const< Cell\\_Type, Data\\_Type >](#)

## 9.17 include/barry/barrayvector-meat.hpp File Reference

## 9.18 include/barry/barry-configuration.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Configuration MACROS

These are mostly related to performance. The definitions follow:

- `BARRY_USE_UNORDERED_MAP` If specified, then barry is compiled using `std::unordered_map`. Otherwise it will use `std::map` for the arrays.
  - `BARRY_USE_SAFE_EXP` When specified, it will multiply all likelihoods in [Model](#) by  $(1/100)/(1/100)$  so that numerical overflows are avoided.
  - `BARRY_USE_ISFINITE` When specified, it will introduce a macro that checks whether the likelihood is finite or not.
  - `printf_barry` If not specified, will be defined as `printf`.
  - `BARRY_DEBUG_LEVEL`, when defined, will make things verbose.
- 
- `#define BARRY_SAFE_EXP -100.0`
  - `#define BARRY_ISFINITE(a)`
  - `#define BARRY_CHECK_SUPPORT(x, maxs)`
  - `#define printf_barry printf`
  - `#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t >(UINT_MAX/2u)`
  - `template<typename Ta, typename Tb >`  
`using Map = std::map< Ta, Tb >`



## 9.18.1 Macro Definition Documentation

### 9.18.1.1 BARRY\_CHECK\_SUPPORT

```
#define BARRY_CHECK_SUPPORT(  
    x,  
    maxs )
```

Definition at line 47 of file barry-configuration.hpp.

### 9.18.1.2 BARRY\_ISFINITE

```
#define BARRY_ISFINITE(  
    a )
```

Definition at line 40 of file barry-configuration.hpp.

### 9.18.1.3 BARRY\_MAX\_NUM\_ELEMENTS

```
#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t > (UINT_MAX/2u)
```

Definition at line 55 of file barry-configuration.hpp.

### 9.18.1.4 BARRY\_SAFE\_EXP

```
#define BARRY_SAFE_EXP -100.0
```

Definition at line 33 of file barry-configuration.hpp.

### 9.18.1.5 printf\_barry

```
#define printf_barry printf
```

Definition at line 51 of file barry-configuration.hpp.

## 9.18.2 Typedef Documentation


### 9.18.2.1 Map

```
template<typename Ta , typename Tb >  
using Map = std::map<Ta,Tb>
```

Definition at line 27 of file barry-configuration.hpp.

## 9.19 include/barry/barry-debug.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define `BARRY_DEBUG_LEVEL` 0

### 9.19.1 Macro Definition Documentation


#### 9.19.1.1 BARRY\_DEBUG\_LEVEL

```
#define BARRY_DEBUG_LEVEL 0
```

Definition at line 5 of file barry-debug.hpp.

## 9.20 include/barry/barry-macros.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define BARRY_ZERO Cell<Cell_Type>(0.0)`
- `#define BARRY_ZERO_DENSE static_cast<Cell_Type>(0.0)`
- `#define BARRY_ONE Cell<Cell_Type>(1.0)`
- `#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)`
- `#define BARRY_UNUSED(expr) do { (void)(expr); } while (0);`

### 9.20.1 Macro Definition Documentation

#### 9.20.1.1 BARRY\_ONE

```
#define BARRY_ONE Cell<Cell_Type>(1.0)
```

Definition at line 7 of file barry-macros.hpp.

#### 9.20.1.2 BARRY\_ONE\_DENSE

```
#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)
```

Definition at line 8 of file barry-macros.hpp.

### 9.20.1.3 BARRY\_UNUSED

```
#define BARRY_UNUSED(  
    expr ) do { (void)(expr); } while (0);
```

Definition at line 10 of file barry-macros.hpp.

### 9.20.1.4 BARRY\_ZERO

```
#define BARRY_ZERO Cell<Cell_Type>(0.0)
```

Definition at line 4 of file barry-macros.hpp.

### 9.20.1.5 BARRY\_ZERO\_DENSE

```
#define BARRY_ZERO_DENSE static_cast<Cell_Type>(0.0)
```

Definition at line 5 of file barry-macros.hpp.

## 9.21 include/barry/barry.hpp File Reference

```
#include <iostream>  
#include <cstdint>  
#include <vector>  
#include <unordered_map>  
#include <functional>  
#include <stdexcept>  
#include <cmath>  
#include <map>  
#include <algorithm>  
#include <utility>  
#include <random>  
#include <climits>  
#include <cfloat>  
#include <string>  
#include <cstdint>  
#include <memory>  
#include <regex>  
#include <iterator>  
#include "typedefs.hpp"  
#include "barry-macros.hpp"  
#include "freqtable.hpp"  
#include "cell-bones.hpp"  
#include "cell-meat.hpp"  
#include "barray-bones.hpp"  
#include "barraycell-bones.hpp"  
#include "barray-meat.hpp"  
#include "barraycell-meat.hpp"
```

```
#include "barray-meat-operators.hpp"
#include "barraydense-bones.hpp"
#include "barraydensecell-bones.hpp"
#include "barraydenserow-bones.hpp"
#include "barraydensecol-bones.hpp"
#include "barraydense-meat.hpp"
#include "barraydensecell-meat.hpp"
#include "barraydense-meat-operators.hpp"
#include "counters-bones.hpp"
#include "counters-meat.hpp"
#include "statscounter-bones.hpp"
#include "statscounter-meat.hpp"
#include "support-bones.hpp"
#include "support-meat.hpp"
#include "powerset-bones.hpp"
#include "powerset-meat.hpp"
#include "model-bones.hpp"
#include "model-meat.hpp"
#include "rules-bones.hpp"
#include "rules-meat.hpp"
#include "counters/network.hpp"
#include "counters/phylo.hpp"
#include "counters/defm.hpp"
```

## Namespaces

- [barry](#)  
*barry: Your go-to motif accountant*
- [barry::counters](#)  
*Tree class and Treeliterator class.*
- [barry::counters::network](#)
- [barry::counters::phylo](#)
- [barry::counters::defm](#)

## Macros

- `#define BARRY_HPP`
- `#define BARRY_VERSION_MAYOR 0`
- `#define BARRY_VERSION_MINOR 1`
- `#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR`
- `#define COUNTER_FUNCTION(a)`
- `#define COUNTER_LAMBDA(a)`
- `#define RULE_FUNCTION(a)`
- `#define RULE_LAMBDA(a)`

### 9.21.1 Macro Definition Documentation

#### 9.21.1.1 BARRY\_HPP

```
#define BARRY_HPP
```

Definition at line 25 of file barry.hpp.

#### 9.21.1.2 BARRY\_VERSION

```
#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR
```

Definition at line 29 of file barry.hpp.

#### 9.21.1.3 BARRY\_VERSION\_MAYOR

```
#define BARRY_VERSION_MAYOR 0
```

Definition at line 27 of file barry.hpp.

#### 9.21.1.4 BARRY\_VERSION\_MINOR

```
#define BARRY_VERSION_MINOR 1
```

Definition at line 28 of file barry.hpp.

#### 9.21.1.5 COUNTER\_FUNCTION

```
#define COUNTER_FUNCTION(  
    a )
```

**Value:**

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline double (a) (const Array_Type & Array, uint i, uint j, Data_Type & data) \  

```

Definition at line 96 of file barry.hpp.

### 9.21.1.6 COUNTER\_LAMBDA

```
#define COUNTER_LAMBDA(  
    a )
```

#### Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Counter_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, uint i, uint j, Data_Type & data)
```

Definition at line 99 of file barry.hpp.

### 9.21.1.7 RULE\_FUNCTION

```
#define RULE_FUNCTION(  
    a )
```

#### Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline bool (a) (const Array_Type & Array, uint i, uint j, Data_Type & data) \  
{
```

Definition at line 103 of file barry.hpp.

### 9.21.1.8 RULE\_LAMBDA

```
#define RULE_LAMBDA(  
    a )
```


#### Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Rule_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, uint i, uint j, Data_Type & data)
```

Definition at line 106 of file barry.hpp.

## 9.22 include/barry/cell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [Cell< Cell\\_Type >](#)  
*Entries in [BArray](#). For now, it only has two members:*

## 9.23 include/barry/cell-meat.hpp File Reference


This graph shows which files directly or indirectly include this file:



## 9.24 include/barry/col-bones.hpp File Reference

## 9.25 include/barry/counters-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Classes

- class [Counter< Array\\_Type, Data\\_Type >](#)  
*A counter function based on change statistics.*
- class [Counters< Array\\_Type, Data\\_Type >](#)  
*Vector of counters.*



## 9.26 include/barry/counters-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define COUNTER_TYPE() Counter<Array_Type,Data_Type>`
- `#define COUNTER_TEMPLATE_ARGS() <typename Array_Type, typename Data_Type>`
- `#define COUNTER_TEMPLATE(a, b) template COUNTER_TEMPLATE_ARGS() inline a COUNTER_TYPE()↔  
::b`
- `#define TMP_HASHER_CALL Hasher_fun_type<Array_Type,Data_Type>`
- `#define COUNTERS_TYPE() Counters<Array_Type,Data_Type>`
- `#define COUNTERS_TEMPLATE_ARGS() <typename Array_Type, typename Data_Type>`
- `#define COUNTERS_TEMPLATE(a, b) template COUNTERS_TEMPLATE_ARGS() inline a COUNTERS_TYPE()↔  
::b`

### Functions

- `COUNTER_TEMPLATE (, Counter)(const Counter< Array_Type`
- `Data_Type init_fun (counter_.init_fun)`
- `Data_Type hasher_fun (counter_.hasher_fun)`
- `Data_Type &&counter_.init_fun (std::move(counter_.init_fun))`
- `Data_Type &&counter_.hasher_fun (std::move(counter_.hasher_fun))`
- `Data_Type &&counter_.data (std::move(counter_.data))`
- `Data_Type &&counter_.name (std::move(counter_.name))`
- `Data_Type &&counter_.desc (std::move(counter_.desc))`
- *Move constructor.*
- `COUNTER_TEMPLATE (COUNTER_TYPE(), operator=)(const Counter< Array_Type`
- `COUNTER_TEMPLATE (COUNTER_TYPE() &, operator=)(Counter< Array_Type`
- `COUNTER_TEMPLATE (double, count)(Array_Type &Array`
- *< Move assignment*
- `return count_fun (Array, i, j, data)`
- `COUNTER_TEMPLATE (double, init)(Array_Type &Array`
- `return init_fun (Array, i, j, data)`
- `COUNTER_TEMPLATE (std::string, get_name)() const`
- `COUNTER_TEMPLATE (std::string, get_description)() const`
- `COUNTER_TEMPLATE (void, set_hasher)(Hasher_fun_type< Array_Type`

- [COUNTER\\_TEMPLATE](#) ([TMP\\_HASHER\\_CALL](#), [get\\_hasher](#)())
- [COUNTERS\\_TEMPLATE](#) (, [Counters](#)())
- [COUNTERS\\_TEMPLATE](#) ([COUNTER\\_TYPE](#)() &, [operator\[\]](#))([uint](#) idx)
- [Data\\_Type](#) [hasher](#) ([counter\\_.hasher](#))
- [Data\\_Type](#) &&[counters\\_.hasher](#) ([std::move](#)([counters\\_.hasher](#)))
- [COUNTERS\\_TEMPLATE](#) ([COUNTERS\\_TYPE](#)(), [operator=](#))([const Counters](#)< [Array\\_Type](#)
- [COUNTERS\\_TEMPLATE](#) ([COUNTERS\\_TYPE](#)() &, [operator=](#))([Counters](#)< [Array\\_Type](#)
- [COUNTERS\\_TEMPLATE](#) ([void](#), [add\\_counter](#))([Counter](#)< [Array\\_Type](#)
- [COUNTERS\\_TEMPLATE](#) ([std::vector](#)< [std::string](#) >, [get\\_names](#)()) [const](#)
- [COUNTERS\\_TEMPLATE](#) ([std::vector](#)< [std::string](#) >, [get\\_descriptions](#)()) [const](#)
- [COUNTERS\\_TEMPLATE](#) ([std::vector](#)< [double](#) >, [gen\\_hash](#))([const](#) [Array\\_Type](#) &[array](#)
- [for](#) ([auto](#) &[c](#):[data](#))
- [if](#) ([add\\_dims](#))
- [if](#) ([hasher](#))
- [if](#) ([res.size](#)()==0u) [res.push\\_back](#)(0.0)
- [COUNTERS\\_TEMPLATE](#) ([void](#), [add\\_hash](#))([Hasher\\_fun\\_type](#)< [Array\\_Type](#)

## Variables

- [Data\\_Type](#) & [counter\\_](#)
- [Data\\_Type](#) &&[counter\\_ noexcept](#)
- [uint](#) [i](#) = [locator->](#)second
- [uint](#) [uint](#) [j](#)
- [Data\\_Type](#) [fun](#)
- [Data\\_Type](#) [counter](#)
- [return](#)
- [Data\\_Type](#) [count\\_fun\\_](#)
- [Data\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [init\\_fun\\_](#)
- [Data\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Hasher\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [hasher\\_fun\\_](#)
- [Data\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Hasher\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Data\\_Type](#) [data\\_](#)
- [Data\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Hasher\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Data\\_Type](#) [std::string](#) [name\\_](#)
- [Data\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Hasher\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Type](#) > [Data\\_Type](#) [std::string](#) [std::string](#) [desc\\_](#)
- [bool](#) [add\\_dims](#)
- [return](#) [res](#)
- [Data\\_Type](#) [fun\\_](#)

## 9.26.1 Macro Definition Documentation

### 9.26.1.1 COUNTER\_TEMPLATE

```
#define COUNTER_TEMPLATE(
    a,
    b )  template COUNTER_TEMPLATE_ARGS() inline a COUNTER_TYPE()::b
```

Definition at line 8 of file counters-meat.hpp.

### 9.26.1.2 COUNTER\_TEMPLATE\_ARGS

```
#define COUNTER_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file counters-meat.hpp.

### 9.26.1.3 COUNTER\_TYPE

```
#define COUNTER_TYPE( ) Counter<Array_Type,Data_Type>
```

Definition at line 4 of file counters-meat.hpp.

### 9.26.1.4 COUNTERS\_TEMPLATE

```
#define COUNTERS_TEMPLATE(  
    a,  
    b ) template COUNTERS_TEMPLATE_ARGS() inline a COUNTERS_TYPE()::b
```

Definition at line 129 of file counters-meat.hpp.

### 9.26.1.5 COUNTERS\_TEMPLATE\_ARGS

```
#define COUNTERS_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 127 of file counters-meat.hpp.

### 9.26.1.6 COUNTERS\_TYPE

```
#define COUNTERS_TYPE( ) Counters<Array_Type,Data_Type>
```

Definition at line 125 of file counters-meat.hpp.

### 9.26.1.7 TMP\_HASHER\_CALL

```
#define TMP_HASHER_CALL Hasher_fun_type<Array_Type,Data_Type>
```

Definition at line 115 of file counters-meat.hpp.

## 9.26.2 Function Documentation

### 9.26.2.1 count\_fun()

```
return count_fun (
    Array ,
    i ,
    j ,
    data )
```

### 9.26.2.2 COUNTER\_TEMPLATE() [1/9]

```
COUNTER_TEMPLATE (
    Counter ) const
```

### 9.26.2.3 COUNTER\_TEMPLATE() [2/9]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() & ,
    operator )
```

### 9.26.2.4 COUNTER\_TEMPLATE() [3/9]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() ,
    operator ) const
```

### 9.26.2.5 COUNTER\_TEMPLATE() [4/9]

```
COUNTER_TEMPLATE (
    double ,
    count ) &
```

< Move assignment

#### 9.26.2.6 COUNTER\_TEMPLATE() [5/9]

```
COUNTER_TEMPLATE (
    double ,
    init ) &
```

#### 9.26.2.7 COUNTER\_TEMPLATE() [6/9]

```
COUNTER_TEMPLATE (
    std::string ,
    get_description ) const
```

Definition at line 107 of file counters-meat.hpp.

#### 9.26.2.8 COUNTER\_TEMPLATE() [7/9]

```
COUNTER_TEMPLATE (
    std::string ,
    get_name ) const
```

Definition at line 103 of file counters-meat.hpp.

#### 9.26.2.9 COUNTER\_TEMPLATE() [8/9]

```
COUNTER_TEMPLATE (
    TMP_HASHER_CALL ,
    get_hasher )
```

Definition at line 116 of file counters-meat.hpp.

#### 9.26.2.10 COUNTER\_TEMPLATE() [9/9]

```
COUNTER_TEMPLATE (
    void ,
    set_hasher )
```

**9.26.2.11 COUNTERS\_TEMPLATE()** [1/9]

```
COUNTERS_TEMPLATE (
    Counters )
```

Definition at line 132 of file counters-meat.hpp.

**9.26.2.12 COUNTERS\_TEMPLATE()** [2/9]

```
COUNTERS_TEMPLATE (
    COUNTER_TYPE() & ,
    operator [ ] )
```

Definition at line 134 of file counters-meat.hpp.

**9.26.2.13 COUNTERS\_TEMPLATE()** [3/9]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() & ,
    operator )
```

**9.26.2.14 COUNTERS\_TEMPLATE()** [4/9]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() ,
    operator ) const
```

**9.26.2.15 COUNTERS\_TEMPLATE()** [5/9]

```
COUNTERS_TEMPLATE (
    std::vector< double > ,
    gen_hash ) const &
```

**9.26.2.16 COUNTERS\_TEMPLATE()** [6/9]

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 212 of file counters-meat.hpp.

**9.26.2.17 COUNTERS\_TEMPLATE() [7/9]**

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_names ) const
```

Definition at line 201 of file counters-meat.hpp.

**9.26.2.18 COUNTERS\_TEMPLATE() [8/9]**

```
COUNTERS_TEMPLATE (
    void ,
    add_counter )
```

**9.26.2.19 COUNTERS\_TEMPLATE() [9/9]**

```
COUNTERS_TEMPLATE (
    void ,
    add_hash )
```

**9.26.2.20 data()**

```
Data_Type&& counter_ data (
    std::move(counter_.data) )
```

**9.26.2.21 desc()**

```
Data_Type&& counter_ desc (
    std::move(counter_.desc) )
```

Move constructor.

Definition at line 32 of file counters-meat.hpp.

**9.26.2.22 for()**

```
for (
    auto &c:data )
```

Definition at line 231 of file counters-meat.hpp.

**9.26.2.23 hasher()** [1/2]

```
Data_Type hasher (  
    counter_.  hasher )
```

Definition at line 141 of file counters-meat.hpp.

**9.26.2.24 hasher()** [2/2]

```
Data_Type&& counters_ hasher (  
    std::move(counters_.hasher) )
```

Definition at line 144 of file counters-meat.hpp.

**9.26.2.25 hasher\_fun()** [1/2]

```
Data_Type hasher_fun (  
    counter_.  hasher_fun )
```

Definition at line 13 of file counters-meat.hpp.

**9.26.2.26 hasher\_fun()** [2/2]

```
Data_Type&& counter_ hasher_fun (  
    std::move(counter_.hasher_fun) )
```

**9.26.2.27 if()** [1/3]

```
if (  
    add_dims )
```

Definition at line 246 of file counters-meat.hpp.

**9.26.2.28 if()** [2/3]

```
if (  
    hasher )
```

Definition at line 253 of file counters-meat.hpp.



### 9.26.2.29 if() [3/3]

```
if (
    res.  size() == 0u )
```

### 9.26.2.30 init\_fun() [1/3]

```
return init_fun (
    Array ,
    i ,
    j ,
    data )
```

### 9.26.2.31 init\_fun() [2/3]

```
Data_Type init_fun (
    counter_.  init_fun )
```

### 9.26.2.32 init\_fun() [3/3]

```
Data_Type&& counter_ init_fun (
    std::move(counter_.init_fun) )
```

### 9.26.2.33 name()

```
Data_Type&& counter_ name (
    std::move(counter_.name) )
```

## 9.26.3 Variable Documentation

### 9.26.3.1 add\_dims

```
bool add_dims
```

#### Initial value:

```
{
    std::vector<double> res
```

Definition at line 225 of file counters-meat.hpp.

### 9.26.3.2 count\_fun\_

Data\_Type count\_fun\_

Definition at line 179 of file counters-meat.hpp.

### 9.26.3.3 counter

Data\_Type counter

#### Initial value:

```
{  
    data.push_back(counter)
```

Definition at line 170 of file counters-meat.hpp.

### 9.26.3.4 counter\_

Data\_Type & counter\_

#### Initial value:

```
{  
    if (this != &counter_) {  
        this->count_fun = counter_.count_fun;  
        this->init_fun = counter_.init_fun;  
        this->hasher_fun = counter_.hasher_fun;  
  
        this->data = counter_.data;  
        this->name = counter_.name;  
        this->desc = counter_.desc;  
    }  
    return *this
```

Definition at line 12 of file counters-meat.hpp.

### 9.26.3.5 data\_

Data\_Rule\_Dyn\_Type Data\_Rule\_Dyn\_Type data\_

#### Initial value:

```
{  
    rules_dyn->add_rule(  
        rule_fun_,  
        data_  
    )
```

Definition at line 182 of file counters-meat.hpp.

### 9.26.3.6 desc\_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> Data←  
_Type std::string std::string desc_
```

#### Initial value:

```
{  
    data.push_back(Counter<Array_Type,Data_Type>(  
        count_fun_,  
        init_fun_,  
        hasher_fun_,  
        data_,  
        name_,  
        desc_  
    ))
```

Definition at line 184 of file counters-meat.hpp.

### 9.26.3.7 fun

```
Data_Type fun
```

#### Initial value:

```
{  
    hasher_fun = fun
```

Definition at line 111 of file counters-meat.hpp.

### 9.26.3.8 fun\_

```
Data_Type fun_
```

#### Initial value:

```
{  
    hasher = fun_
```

Definition at line 268 of file counters-meat.hpp.

### 9.26.3.9 hasher\_fun\_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> hasher←  
_fun_
```

Definition at line 181 of file counters-meat.hpp.

**9.26.3.10 i**

```
const std::vector< double > unsigned int i = locator->second
```

Definition at line 83 of file counters-meat.hpp.

**9.26.3.11 init\_fun\_**

```
Data_Type Counter_fun_type<Array_Type,Data_Type> init_fun_
```

Definition at line 180 of file counters-meat.hpp.

**9.26.3.12 j**

```
uint uint j
```

**Initial value:**

```
{
    if (count_fun == nullptr)
        return 0.0
```

Definition at line 83 of file counters-meat.hpp.

**9.26.3.13 name\_**

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> Data↔
_Type std::string name_
```

Definition at line 183 of file counters-meat.hpp.

**9.26.3.14 noexcept**

```
Data_Type &&counters_ noexcept
```

**Initial value:**

```
{
    if (this != &counter_)
    {
        this->data = std::move(counter_.data);

        this->count_fun = std::move(counter_.count_fun);
        this->init_fun = std::move(counter_.init_fun);
        this->hasher_fun = std::move(counter_.hasher_fun);

        this->name = std::move(counter_.name);
        this->desc = std::move(counter_.desc);
    }
    return *this
```

Definition at line 26 of file counters-meat.hpp.

#### 9.26.3.15 res

```
return res
```

Definition at line 263 of file counters-meat.hpp.


#### 9.26.3.16 return

```
return
```

Definition at line 175 of file counters-meat.hpp.

## 9.27 include/barry/counters/defm-formula.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Functions

- void [defm\\_motif\\_parser](#) (std::string formula, std::vector< size\_t > &locations, std::vector< bool > &signs, size\_t m\_order, size\_t y\_ncol)  
*Parses a motif formula.*

### 9.27.1 Function Documentation

### 9.27.1.1 defm\_motif\_parser()

```
void defm_motif_parser (
    std::string formula,
    std::vector< size_t > & locations,
    std::vector< bool > & signs,
    size_t m_order,
    size_t y_ncol ) [inline]
```

Parses a motif formula.

This function will take the formula and generate the corresponding input for `defm::counter_transition()`. Formulas can be specified in the following ways:

- Intercept effect: {...} No transition, only including the current state.
- Transition effect: {...} > {...} Includes current and previous states.

The general notation is `[0]y[column id]_[row id]`. A preceeding zero means that the value of the cell is considered to be zero. The column id goes between 0 and the number of columns in the array - 1 (so it is indexed from 0,) and the row id goes from 0 to `m_order`.

#### Intercept effects

Intercept effects only involve a single set of curly brackets. Using the 'greater-than' symbol (i.e., '<') is only for transition effects. When specifying intercept effects, users can skip the `row_id`, e.g., `y0_0` is equivalent to `y0`. If the passed `row_id` is different from the Markov order, i.e., `row_id != m_order`, then the function returns with an error.

Examples:

- `"{y0, 0y1}"` is equivalent to set a motif with the first element equal to one and the second to zero.

#### Transition effects

Transition effects can be specified using two sets of curly brackets and an greater-than symbol, i.e., `{...} > {...}`. The first set of brackets, which we call LHS, can only hold `row_id` that are less than `m_order`.

#### Parameters


<i>formula</i>	
<i>locations</i>	
<i>signs</i>	
<i>m_order</i>	
<i>y_ncol</i>	

Definition at line 46 of file `defm-formula.hpp`.


## 9.28 include/barry/counters/defm.hpp File Reference

```
#include "defm-formula.hpp"
```

Include dependency graph for defm.hpp:



This graph shows which files directly or indirectly include this file:



### Classes

- class [DEFMData](#)
- class [DEFMCounterData](#)
  - Data class used to store arbitrary uint or double vectors.*
- class [DEFMRuleData](#)
- class [DEFMRuleDynData](#)

### Macros

- `#define` [MAKE\\_DEFM\\_HASHER](#)(hasher, a, cov)
- `#define` [DEFM\\_RULEDYN\\_LAMBDA](#)(a)
- `#define` [UNI\\_SUB](#)(a)

### Macros for defining counters

- #define `DEFM_COUNTER(a)` inline double (a) (const `DEFMArray` & Array, uint i, uint j, `DEFMCounterData` & data)
- #define `DEFM_COUNTER_LAMBDA(a)`

### Macros for defining rules

- #define `DEFM_RULE(a)` inline bool (a) (const `DEFMArray` & Array, uint i, uint j, bool & data)
- #define `DEFM_RULE_LAMBDA(a)`

## Typedefs

- typedef `BArrayDense`< int, `DEFMData` > `DEFMArray`

### Convenient typedefs for network objects.

- typedef `Counter`< `DEFMArray`, `DEFMCounterData` > `DEFMCounter`
- typedef `Counters`< `DEFMArray`, `DEFMCounterData` > `DEFMCounters`
- typedef `Support`< `DEFMArray`, `DEFMCounterData`, `DEFMRuleData`, `DEFMRuleDynData` > `DEFMSupport`
- typedef `StatsCounter`< `DEFMArray`, `DEFMCounterData` > `DEFMStatsCounter`
- typedef `Model`< `DEFMArray`, `DEFMCounterData`, `DEFMRuleData`, `DEFMRuleDynData` > `DEFMModel`
- typedef `Rule`< `DEFMArray`, `DEFMRuleData` > `DEFMRule`
- typedef `Rules`< `DEFMArray`, `DEFMRuleData` > `DEFMRules`
- typedef `Rule`< `DEFMArray`, `DEFMRuleDynData` > `DEFMRuleDyn`
- typedef `Rules`< `DEFMArray`, `DEFMRuleDynData` > `DEFMRulesDyn`

## Functions

- void `counter_ones` (`DEFMCounters` \*counters, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr)  
*Prevalence of ones.*
- void `counter_logit_intercept` (`DEFMCounters` \*counters, size\_t n\_y, std::vector< size\_t > which={}, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)
- void `counter_transition` (`DEFMCounters` \*counters, std::vector< size\_t > coords, std::vector< bool > signs, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)  
*Prevalence of ones.*
- void `counter_transition_formula` (`DEFMCounters` \*counters, std::string formula, size\_t m\_order, size\_t n\_y, int covar\_index=-1, std::string vname="", const std::vector< std::string > \*x\_names=nullptr, const std::vector< std::string > \*y\_names=nullptr)  
*Prevalence of ones.*
- void `counter_fixed_effect` (`DEFMCounters` \*counters, int covar\_index, double k, std::string vname="", const std::vector< std::string > \*x\_names=nullptr)  
*Prevalence of ones.*

Returns true if the cell is free



*Parameters*

rules	A pointer to a <i>DEFMRules</i> object ( <i>Rules</i> < <i>DEFMArray</i> , <i>bool</i> >).
-------	--

- void *rules\_markov\_fixed* (*DEFMRules* \**rules*, size\_t *markov\_order*)  
Number of edges.
- void *rules\_dont\_become\_zero* (*DEFMSupport* \**support*, std::vector< size\_t > *ids*)  
Blocks switching a one to zero.

**9.28.1 Macro Definition Documentation****9.28.1.1 UNI\_SUB**

```
#define UNI_SUB(  
    a )
```

**Value:**

```
(\
  ((a) == 0) ? "\u2080" : (\
  ((a) == 1) ? "\u2081" : (\
  ((a) == 2) ? "\u2082" : (\
  ((a) == 3) ? "\u2083" : (\
  ((a) == 4) ? "\u2084" : (\
  ((a) == 5) ? "\u2085" : (\
  ((a) == 6) ? "\u2086" : (\
  ((a) == 7) ? "\u2087" : (\
  ((a) == 8) ? "\u2088" : (\
  "\u2089")))))))\
)
```


**9.28.2 Typedef Documentation****9.28.2.1 DEFMArray**

```
typedef BArrayDense<int, DEFMData> DEFMArray
```

Definition at line 25 of file defm.hpp.


## 9.29 include/barry/models/defm.hpp File Reference

```
#include <iterator>
#include <regex>
#include "defm/defm-bones.hpp"
#include "defm/defm-meat.hpp"
Include dependency graph for defm.hpp:
```



## 9.30 include/barry/counters/network-css.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define CSS_SIZE()`
- `#define CSS_CASE_TRUTH() if ((i < n) && (j < n))`
- `#define CSS_TRUE_CELLS()`
- `#define CSS_CASE_PERCEIVED() else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))`

- #define `CSS_PERCEIVED_CELLS()`
- #define `CSS_CASE_ELSE()`
- #define `CSS_CHECK_SIZE_INIT()`
- #define `CSS_CHECK_SIZE()`
- #define `CSS_APPEND(name)`
- #define `CSS_NET_COUNTER_LAMBDA_INIT()`

## Functions

- template<typename Tnet = Network>  
void `counter_css_partially_false_recip_commi` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)  
*Counts errors of commission.*
- template<typename Tnet = Network>  
void `counter_css_partially_false_recip_omiss` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)  
*Counts errors of omission.*
- template<typename Tnet = Network>  
void `counter_css_completely_false_recip_comiss` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)  
*Counts completely false reciprocity (comission)*
- template<typename Tnet = Network>  
void `counter_css_completely_false_recip_omiss` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)  
*Counts completely false reciprocity (omission)*
- template<typename Tnet = Network>  
void `counter_css_mixed_recip` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)  
*Counts mixed reciprocity errors.*
- template<typename Tnet = Network>  
void `counter_css_census01` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census02` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census03` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census04` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census05` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census06` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census07` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)
- template<typename Tnet = Network>  
void `counter_css_census08` (NetCounters< Tnet > \*counters, uint netsize, const std::vector< uint > &end\_)

- `template<typename Tnet = Network>`  
`void counter_css_census09 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_`  
`)`
- `template<typename Tnet = Network>`  
`void counter_css_census10 (NetCounters< Tnet > *counters, uint netsize, const std::vector< uint > &end_`  
`)`

## 9.30.1 Macro Definition Documentation

### 9.30.1.1 CSS\_APPEND

```
#define CSS_APPEND(  
    name )
```

#### Value:

```
std::string name_ = (name);\nfor (uint i = 0u; i < end_.size(); ++i) { \nstd::string tmpname = name_ + " (" + std::to_string(i) + ")";\ncounters->add_counter(tmp_count, tmp_init, nullptr, \n    NetCounterData({netsize, i == 0u ? netsize : end_[i-1], end_[i]}, {}),\n    tmpname);}
```

Definition at line 42 of file network-css.hpp.

### 9.30.1.2 CSS\_CASE\_ELSE

```
#define CSS_CASE_ELSE( )
```

Definition at line 27 of file network-css.hpp.

### 9.30.1.3 CSS\_CASE\_PERCEIVED

```
#define CSS_CASE_PERCEIVED( ) else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))
```

Definition at line 20 of file network-css.hpp.

### 9.30.1.4 CSS\_CASE\_TRUTH

```
#define CSS_CASE_TRUTH( ) if ((i < n) && (j < n))
```

Definition at line 13 of file network-css.hpp.

### 9.30.1.5 CSS\_CHECK\_SIZE

```
#define CSS_CHECK_SIZE( )
```

**Value:**

```
for (uint i = 0u; i < end_.size(); ++i) {\
  if (i == 0u) continue; \
  else if (end_[i] < end_[i-1u]) \
    throw std::logic_error("Endpoints should be specified in order.");}
```

Definition at line 37 of file network-css.hpp.

### 9.30.1.6 CSS\_CHECK\_SIZE\_INIT

```
#define CSS_CHECK_SIZE_INIT( )
```

**Value:**

```
/* The indices fall within the network */ \
if ((data.indices.at(0) > Array.ncol()) \
| (data.indices.at(2) > Array.ncol())) \
  throw std::range_error("The network does not match the prescribed size.");
```

Definition at line 31 of file network-css.hpp.

### 9.30.1.7 CSS\_NET\_COUNTER\_LAMBDA\_INIT

```
#define CSS_NET_COUNTER_LAMBDA_INIT( )
```

**Value:**

```
NETWORK_COUNTER_LAMBDA(tmp_init) {\
  CSS_CHECK_SIZE_INIT() \
  return 0.0; \
};
```

Definition at line 49 of file network-css.hpp.

### 9.30.1.8 CSS\_PERCEIVED\_CELLS

```
#define CSS_PERCEIVED_CELLS( )
```

**Value:**

```
double tji = static_cast<double>(Array(j - s, i - s, false)); \
double pji = static_cast<double>(Array(j, i, false)); \
double tij = static_cast<double>(Array(i - s, j - s, false));
```

Definition at line 21 of file network-css.hpp.

### 9.30.1.9 CSS\_SIZE

```
#define CSS_SIZE( )
```

**Value:**

```
uint n = data.indices[0u]; \
uint s = data.indices[1u]; \
uint e = data.indices[2u];
```

Definition at line 7 of file network-css.hpp.

### 9.30.1.10 CSS\_TRUE\_CELLS

```
#define CSS_TRUE_CELLS( )
```

**Value:**

```
double tji = static_cast<double>(Array(j, i, false)); \
double pij = static_cast<double>(Array(i + s, j + s, false)); \
double pji = static_cast<double>(Array(j + s, i + s, false));
```

Definition at line 14 of file network-css.hpp.

## 9.30.2 Function Documentation

### 9.30.2.1 counter\_css\_census01()

```
template<typename Tnet = Network>
void counter_css_census01 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 275 of file network-css.hpp.

### 9.30.2.2 counter\_css\_census02()

```
template<typename Tnet = Network>
void counter_css_census02 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 325 of file network-css.hpp.

### 9.30.2.3 counter\_css\_census03()

```
template<typename Tnet = Network>
void counter_css_census03 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 364 of file network-css.hpp.

### 9.30.2.4 counter\_css\_census04()

```
template<typename Tnet = Network>
void counter_css_census04 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 403 of file network-css.hpp.

### 9.30.2.5 counter\_css\_census05()

```
template<typename Tnet = Network>
void counter_css_census05 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 442 of file network-css.hpp.

### 9.30.2.6 counter\_css\_census06()

```
template<typename Tnet = Network>
void counter_css_census06 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 481 of file network-css.hpp.

### 9.30.2.7 counter\_css\_census07()

```
template<typename Tnet = Network>
void counter_css_census07 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 520 of file network-css.hpp.

### 9.30.2.8 counter\_css\_census08()

```
template<typename Tnet = Network>
void counter_css_census08 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 559 of file network-css.hpp.

### 9.30.2.9 counter\_css\_census09()

```
template<typename Tnet = Network>
void counter_css_census09 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 598 of file network-css.hpp.

### 9.30.2.10 counter\_css\_census10()

```
template<typename Tnet = Network>
void counter_css_census10 (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Definition at line 637 of file network-css.hpp.



#### 9.30.2.11 counter\_css\_completely\_false\_recip\_comiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_comiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts completely false reciprocity (comission)

Definition at line 154 of file network-css.hpp.

#### 9.30.2.12 counter\_css\_completely\_false\_recip\_omiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_omiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts completely false reciprocity (omission)

Definition at line 194 of file network-css.hpp.

#### 9.30.2.13 counter\_css\_mixed\_recip()

```
template<typename Tnet = Network>
void counter_css_mixed_recip (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts mixed reciprocity errors.

Definition at line 234 of file network-css.hpp.

#### 9.30.2.14 counter\_css\_partially\_false\_recip\_commi()

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_commi (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```

Counts errors of commission.

## Parameters

<i>netsize</i>	Size of the reference (true) network
<i>end_</i>	Vector indicating one past the ending index of each network. (see details)
—	

The *end\_* parameter should be of length *N* of *networks* - 1. It is assumed that the first network ends at *netsize*.

Definition at line 63 of file *network-css.hpp*.

### 9.30.2.15 counter\_css\_partially\_false\_recip\_omiss()

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_omiss (
    NetCounters< Tnet > * counters,
    uint netsize,
    const std::vector< uint > & end_ ) [inline]
```


Counts errors of omission.

Definition at line 110 of file *network-css.hpp*.


## 9.31 include/barry/counters/network.hpp File Reference

```
#include "network-css.hpp"
```

Include dependency graph for *network.hpp*:



This graph shows which files directly or indirectly include this file:



## Classes

- class [NetworkData](#)  
*Data class for Networks.*
- class [NetCounterData](#)  
*Data class used to store arbitrary uint or double vectors.*

## Macros

- #define [NET\\_C\\_DATA\\_IDX\(i\)](#) (data.indices[i])
- #define [NET\\_C\\_DATA\\_NUM\(i\)](#) (data.numbers[i])

### Macros for defining counters

- #define [NETWORK\\_COUNTER\(a\)](#)
- #define [NETWORK\\_COUNTER\\_LAMBDA\(a\)](#)
- #define [NETWORKDENSE\\_COUNTER\\_LAMBDA\(a\)](#)

### Macros for defining rules

- #define [NETWORK\\_RULE\(a\)](#)
- #define [NETWORK\\_RULE\\_LAMBDA\(a\)](#)

## Functions

- `template<typename Tnet = Network>`  
`void counter_edges (NetCounters< Tnet > *counters)`  
*Number of edges.*
- `template<typename Tnet = Network>`  
`void counter_isolates (NetCounters< Tnet > *counters)`  
*Number of isolated vertices.*
- `template<> void counter_isolates (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_mutual (NetCounters< Tnet > *counters)`  
*Number of mutual ties.*
- `template<typename Tnet = Network>`  
`void counter_istar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_istar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_ostar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_ostar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_ttriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ttriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_ctriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ctriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_density (NetCounters< Tnet > *counters)`
- `template<typename Tnet = Network>`  
`void counter_idegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_idegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_odegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_odegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`  
`void counter_absdiff (NetCounters< Tnet > *counters, uint attr_id, double alpha=1.0)`  
*Sum of absolute attribute difference between ego and alter.*
- `template<typename Tnet = Network>`  
`void counter_diff (NetCounters< Tnet > *counters, uint attr_id, double alpha=1.0, double tail_head=true)`  
*Sum of attribute difference between ego and alter to pow(alpha)*
- `NETWORK_COUNTER (init_single_attr)`
- `template<typename Tnet = Network>`  
`void counter_nodeicov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodeocov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodecov (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_nodematch (NetCounters< Tnet > *counters, uint attr_id)`
- `template<typename Tnet = Network>`  
`void counter_idegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given in-degree.*
- `template<> void counter_idegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`
- `template<typename Tnet = Network>`  
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< uint > d)`

- `template<typename Tnet = Network>`  
`void counter_degree (NetCounters< Tnet > *counters, std::vector< uint > d)`  
*Counts number of vertices with a given out-degree.*

### Rules for network models

#### Parameters

rules	A pointer to a <i>NetRules</i> object ( <i>Rules</i> < <i>Network</i> , <i>bool</i> >).
-------	---

- `template<typename Tnet = Network>`  
`void rules_zerodiag (NetRules< Tnet > *rules)`  
*Number of edges.*

### Convenient typedefs for network objects.

- `#define BARRY_ZERO_NETWORK 0.0`
- `#define BARRY_ZERO_NETWORK_DENSE 0`
- `typedef BArray< double, NetworkData > Network`
- `typedef BArrayDense< int, NetworkData > NetworkDense`
- `template<typename Tnet = Network>`  
`using NetCounter = Counter< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetCounters = Counters< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetSupport = Support< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetStatsCounter = StatsCounter< Tnet, NetCounterData >`
- `template<typename Tnet >`  
`using NetModel = Model< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`  
`using NetRule = Rule< Tnet, bool >`
- `template<typename Tnet = Network>`  
`using NetRules = Rules< Tnet, bool >`

## 9.31.1 Macro Definition Documentation

### 9.31.1.1 BARRY\_ZERO\_NETWORK

```
#define BARRY_ZERO_NETWORK 0.0
```

Definition at line 85 of file network.hpp.

### 9.31.1.2 BARRY\_ZERO\_NETWORK\_DENSE

```
#define BARRY_ZERO_NETWORK_DENSE 0
```

Definition at line 86 of file network.hpp.

### 9.31.1.3 NET\_C\_DATA\_IDX

```
#define NET_C_DATA_IDX(  
    i ) (data.indices[i])
```

Definition at line 74 of file network.hpp.

### 9.31.1.4 NET\_C\_DATA\_NUM

```
#define NET_C_DATA_NUM(  
    i ) (data.numbers[i])
```

Definition at line 75 of file network.hpp.

### 9.31.1.5 NETWORK\_COUNTER

```
#define NETWORK_COUNTER(  
    a )
```

#### Value:

```
template<typename Tnet = Network>\  
inline double (a) (const Tnet & Array, uint i, uint j, NetCounterData & data)
```

Function for definition of a network counter function

Definition at line 114 of file network.hpp.

### 9.31.1.6 NETWORK\_COUNTER\_LAMBDA

```
#define NETWORK_COUNTER_LAMBDA(  
    a )
```

#### Value:

```
Counter_fun_type<Tnet, NetCounterData> a = \  
    [] (const Tnet & Array, uint i, uint j, NetCounterData & data)
```

Lambda function for definition of a network counter function

Definition at line 119 of file network.hpp.

### 9.31.1.7 NETWORK\_RULE

```
#define NETWORK_RULE(  
    a )
```

**Value:**

```
template<typename Tnet = Network>\  
inline bool (a) (const Tnet & Array, uint i, uint j, bool & data)
```

Function for definition of a network counter function

Definition at line 133 of file network.hpp.

### 9.31.1.8 NETWORK\_RULE\_LAMBDA

```
#define NETWORK_RULE_LAMBDA(  
    a )
```

**Value:**

```
Rule_fun_type<Tnet, bool> a = \  
[] (const Tnet & Array, uint i, uint j, bool & data)
```

Lambda function for definition of a network counter function

Definition at line 138 of file network.hpp.

### 9.31.1.9 NETWORKDENSE\_COUNTER\_LAMBDA

```
#define NETWORKDENSE_COUNTER_LAMBDA(  
    a )
```

**Value:**

```
Counter_fun_type<NetworkDense, NetCounterData> a = \  
[] (const NetworkDense & Array, uint i, uint j, NetCounterData & data)
```

Definition at line 123 of file network.hpp.

## 9.31.2 Typedef Documentation

### 9.31.2.1 NetCounter

```
template<typename Tnet = Network>  
using NetCounter = Counter<Tnet, NetCounterData >
```

Definition at line 89 of file network.hpp.

### 9.31.2.2 NetCounters

```
template<typename Tnet = Network>  
using NetCounters = Counters<Tnet, NetCounterData>
```

Definition at line 92 of file network.hpp.

### 9.31.2.3 NetModel

```
template<typename Tnet >  
using NetModel = Model<Tnet, NetCounterData>
```

Definition at line 101 of file network.hpp.

### 9.31.2.4 NetRule

```
template<typename Tnet = Network>  
using NetRule = Rule<Tnet, bool>
```

Definition at line 104 of file network.hpp.

### 9.31.2.5 NetRules

```
template<typename Tnet = Network>  
using NetRules = Rules<Tnet, bool>
```

Definition at line 107 of file network.hpp.

### 9.31.2.6 NetStatsCounter

```
template<typename Tnet = Network>  
using NetStatsCounter = StatsCounter<Tnet, NetCounterData>
```

Definition at line 98 of file network.hpp.

### 9.31.2.7 NetSupport

```
template<typename Tnet = Network>  
using NetSupport = Support<Tnet, NetCounterData >
```

Definition at line 95 of file network.hpp.



### 9.31.2.8 Network

```
typedef BArray<double, NetworkData> Network
```

Definition at line 82 of file network.hpp.

### 9.31.2.9 NetworkDense

```
typedef BArrayDense<int, NetworkData> NetworkDense
```

Definition at line 83 of file network.hpp.

## 9.31.3 Function Documentation

### 9.31.3.1 rules\_zerodiag()


```
template<typename Tnet = Network>
void rules_zerodiag (
    NetRules< Tnet > * rules ) [inline]
```

Number of edges.

Definition at line 1383 of file network.hpp.

## 9.32 include/barry/counters/phylo.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Classes

- class [NodeData](#)  
*Data definition for the `PhyloArray` class.*
- class [PhyloCounterData](#)
- class [PhyloRuleDynData](#)

## Macros

- `#define` [DEFAULT\\_DUPLICATION](#) 1u
- `#define` [DUPL\\_SPEC](#) 0u
- `#define` [DUPL\\_DUPL](#) 1u
- `#define` [DUPL\\_EITH](#) 2u
- `#define` [MAKE\\_DUPL\\_VARS](#)()
- `#define` [IS\\_EITHER](#)() (DATA\_AT == [DUPL\\_EITH](#))
- `#define` [IS\\_DUPLICATION](#)() ((DATA\_AT == [DUPL\\_DUPL](#)) & (DPL))
- `#define` [IS\\_SPECIATION](#)() ((DATA\_AT == [DUPL\\_SPEC](#)) & (!DPL))
- `#define` [IF\\_MATCHES](#)()
- `#define` [IF\\_NOTMATCHES](#)()
- `#define` [PHYLO\\_COUNTER\\_LAMBDA](#)(a)  
*Extension of a simple counter.*
- `#define` [PHYLO\\_RULE\\_DYN\\_LAMBDA](#)(a)
- `#define` [PHYLO\\_CHECK\\_MISSING](#)()

## Typedefs

- `typedef` `std::vector< std::pair< uint, uint > >` [PhyloRuleData](#)

### Convenient typedefs for Node objects.

- `typedef` [BArrayDense](#)< [uint](#), [NodeData](#) > [PhyloArray](#)
- `typedef` [Counter](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounter](#)
- `typedef` [Counters](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounters](#)
- `typedef` [Rule](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRule](#)
- `typedef` [Rules](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRules](#)
- `typedef` [Rule](#)< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRuleDyn](#)
- `typedef` [Rules](#)< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRulesDyn](#)
- `typedef` [Support](#)< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloSupport](#)
- `typedef` [StatsCounter](#)< [PhyloArray](#), [PhyloCounterData](#) > [PhyloStatsCounter](#)
- `typedef` [Model](#)< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloModel](#)
- `typedef` [PowerSet](#)< [PhyloArray](#), [PhyloRuleData](#) > [PhyloPowerSet](#)

## Functions

- `std::string get_last_name` (unsigned int d)
- `void counter_overall_gains` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Overall functional gains.*
- `void counter_gains` (PhyloCounters \*counters, std::vector< uint > nfun, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Functional gains for a specific function (nfun).*
- `void counter_gains_k_offspring` (PhyloCounters \*counters, std::vector< uint > nfun, uint k=1u, unsigned int duplication=DEFAULT\_DUPLICATION)  
*k genes gain function nfun*
- `void counter_genes_changing` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- `void counter_preserve_pseudogene` (PhyloCounters \*counters, unsigned int nfunA, unsigned int nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Keeps track of how many pairs of genes preserve pseudostate.*
- `void counter_prop_genes_changing` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)*
- `void counter_overall_loss` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Overall functional loss.*
- `void counter_maxfuns` (PhyloCounters \*counters, uint lb, uint ub, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Cap the number of functions per gene.*
- `void counter_loss` (PhyloCounters \*counters, std::vector< uint > nfun, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total count of losses for an specific function.*
- `void counter_overall_changes` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total number of changes. Use this statistic to account for "preservation".*
- `void counter_subfun` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total count of Sub-functionalization events.*
- `void counter_cogain` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Co-evolution (joint gain or loss)*
- `void counter_longest` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Longest branch mutates (either by gain or by loss)*
- `void counter_neofun` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total number of neofunctionalization events.*
- `void counter_pairwise_neofun_singlefun` (PhyloCounters \*counters, uint nfunA, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total number of neofunctionalization events  $\sum_u \sum_{w < u} [x(u,a)*(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$  change  
stat:  $\delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- `void counter_neofun_a2b` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Total number of neofunctionalization events.*
- `void counter_co_opt` (PhyloCounters \*counters, uint nfunA, uint nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Function co-opting.*
- `void counter_k_genes_changing` (PhyloCounters \*counters, unsigned int k, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Indicator function. Equals to one if k genes changed and zero otherwise.*
- `void counter_less_than_p_prop_genes_changing` (PhyloCounters \*counters, double p, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Indicator function. Equals to one if k genes changed and zero otherwise.*
- `void counter_gains_from_0` (PhyloCounters \*counters, std::vector< uint > nfun, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Used when all the functions are in 0 (like the root node prob.)*
- `void counter_overall_gains_from_0` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Used when all the functions are in 0 (like the root node prob.)*
- `void counter_pairwise_overall_change` (PhyloCounters \*counters, unsigned int duplication=DEFAULT\_DUPLICATION)  
*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_pairwise_preserving` (`PhyloCounters` \*counters, `uint` nfunA, `uint` nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `counter_pairwise_first_gain` (`PhyloCounters` \*counters, `uint` nfunA, `uint` nfunB, unsigned int duplication=DEFAULT\_DUPLICATION)

*Used when all the functions are in 0 (like the root node prob.)*

- void `rule_dyn_limit_changes` (`PhyloSupport` \*support, `uint` pos, `uint` lb, `uint` ub, unsigned int duplication=DEFAULT\_DUPLICATION)

*Overall functional gains.*

## 9.32.1 Macro Definition Documentation

### 9.32.1.1 DEFAULT\_DUPLICATION

```
#define DEFAULT_DUPLICATION 1u
```

Definition at line 5 of file phylo.hpp.

### 9.32.1.2 DUPL\_DUPL

```
#define DUPL_DUPL 1u
```

Definition at line 7 of file phylo.hpp.

### 9.32.1.3 DUPL\_EITH

```
#define DUPL_EITH 2u
```

Definition at line 8 of file phylo.hpp.

### 9.32.1.4 DUPL\_SPEC

```
#define DUPL_SPEC 0u
```

Definition at line 6 of file phylo.hpp.

### 9.32.1.5 IF\_MATCHES

```
#define IF_MATCHES( )
```

**Value:**

```
MAKE_DUPL_VARS() \
if (IS_EITHER() | IS_DUPLICATION() | IS_SPECIATION())
```

Definition at line 19 of file phylo.hpp.

### 9.32.1.6 IF\_NOTMATCHES

```
#define IF_NOTMATCHES( )
```

**Value:**

```
MAKE_DUPL_VARS() \
if (!IS_EITHER() & !IS_DUPLICATION() & !IS_SPECIATION())
```

Definition at line 21 of file phylo.hpp.

### 9.32.1.7 IS\_DUPLICATION

```
#define IS_DUPLICATION( ) ((DATA_AT == DUPL_DUPL) & (DPL))
```

Definition at line 16 of file phylo.hpp.

### 9.32.1.8 IS\_EITHER

```
#define IS_EITHER( ) (DATA_AT == DUPL_EITH)
```

Definition at line 15 of file phylo.hpp.

### 9.32.1.9 IS\_SPECIATION

```
#define IS_SPECIATION( ) ((DATA_AT == DUPL_SPEC) & (!DPL))
```

Definition at line 17 of file phylo.hpp.

### 9.32.1.10 MAKE\_DUPL\_VARS

```
#define MAKE_DUPL_VARS( )
```

**Value:**

```
bool DPL = Array.D_ptr()->duplication; \
unsigned int DATA_AT = data[0u];
```

Definition at line 11 of file phylo.hpp.

### 9.32.1.11 PHYLO\_CHECK\_MISSING

```
#define PHYLO_CHECK_MISSING( )
```

**Value:**

```
if (Array.D_ptr() == nullptr) \
throw std::logic_error("The array data is nullptr."); \
```

Definition at line 139 of file phylo.hpp.

### 9.32.1.12 PHYLO\_COUNTER\_LAMBDA

```
#define PHYLO_COUNTER_LAMBDA(
    a )
```

**Value:**

```
Counter_fun_type<PhyloArray, PhyloCounterData> a = \
[] (const PhyloArray & Array, uint i, uint j, PhyloCounterData & data)
```

Extension of a simple counter.

It allows specifying extra arguments, in particular, the corresponding sets of rows to which this statistic may be relevant. This could be important in the case of, for example, counting correlation type statistics between function 1 and 2, and between function 1 and 3.

Definition at line 133 of file phylo.hpp.

### 9.32.1.13 PHYLO\_RULE\_DYN\_LAMBDA

```
#define PHYLO_RULE_DYN_LAMBDA(
    a )
```

**Value:**

```
Rule_fun_type<PhyloArray, PhyloRuleDynData> a = \
[] (const PhyloArray & Array, uint i, uint j, PhyloRuleDynData & data)
```

Definition at line 136 of file phylo.hpp.

## 9.32.2 Typedef Documentation

### 9.32.2.1 PhyloArray

```
typedef BArrayDense<uint, NodeData> PhyloArray
```

Definition at line 106 of file phylo.hpp.

### 9.32.2.2 PhyloCounter

```
typedef Counter<PhyloArray, PhyloCounterData > PhyloCounter
```

Definition at line 107 of file phylo.hpp.

### 9.32.2.3 PhyloCounters

```
typedef Counters< PhyloArray, PhyloCounterData> PhyloCounters
```

Definition at line 108 of file phylo.hpp.

### 9.32.2.4 PhyloModel

```
typedef Model<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloModel
```

Definition at line 118 of file phylo.hpp.

### 9.32.2.5 PhyloPowerSet

```
typedef PowerSet<PhyloArray, PhyloRuleData> PhyloPowerSet
```

Definition at line 119 of file phylo.hpp.

#### 9.32.2.6 PhyloRule

```
typedef Rule<PhyloArray,PhyloRuleData> PhyloRule
```

Definition at line 110 of file phylo.hpp.

#### 9.32.2.7 PhyloRuleData

```
typedef std::vector< std::pair< uint, uint > > PhyloRuleData
```

Definition at line 99 of file phylo.hpp.

#### 9.32.2.8 PhyloRuleDyn

```
typedef Rule<PhyloArray,PhyloRuleDynData> PhyloRuleDyn
```

Definition at line 113 of file phylo.hpp.

#### 9.32.2.9 PhyloRules

```
typedef Rules<PhyloArray,PhyloRuleData> PhyloRules
```

Definition at line 111 of file phylo.hpp.

#### 9.32.2.10 PhyloRulesDyn

```
typedef Rules<PhyloArray,PhyloRuleDynData> PhyloRulesDyn
```

Definition at line 114 of file phylo.hpp.

#### 9.32.2.11 PhyloStatsCounter

```
typedef StatsCounter<PhyloArray, PhyloCounterData> PhyloStatsCounter
```

Definition at line 117 of file phylo.hpp.



### 9.32.2.12 PhyloSupport

```
typedef Support<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloSupport
```

Definition at line 116 of file phylo.hpp.

## 9.32.3 Function Documentation


### 9.32.3.1 get\_last\_name()

```
std::string get_last_name (
    unsigned int d ) [inline]
```

Definition at line 142 of file phylo.hpp.

## 9.33 include/barry/freqtable.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class `FreqTable< T >`  
*Frequency table of vectors.*

## 9.34 include/barry/model-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [Model< Array\\_Type, Data\\_Counter\\_Type, Data\\_Rule\\_Type, Data\\_Rule\\_Dyn\\_Type >](#)

*General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:*

## 9.35 include/barry/model-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- #define [MODEL\\_TYPE\(\)](#)
- #define [MODEL\\_TEMPLATE\\_ARGS\(\)](#)
- #define [MODEL\\_TEMPLATE\(a, b\)](#) template [MODEL\\_TEMPLATE\\_ARGS\(\)](#) inline [a MODEL\\_TYPE\(\)](#)::b

## Functions

- double [update\\_normalizing\\_constant](#) (const double \*params, const double \*support, size\_t k, size\_t n)
- double [likelihood\\_](#) (const double \*stats\_target, const std::vector< double > &params, const double normalizing\_constant, size\_t n\_params, bool log\_<sub>default</sub>=false)
- [MODEL\\_TEMPLATE](#) (void, store\_psets)() noexcept
- [MODEL\\_TEMPLATE](#) (std::vector< double >, gen\_key)(const Array\_Type &Array\_)
- [MODEL\\_TEMPLATE](#) (void, add\_counter)(Counter< Array\_Type
- [MODEL\\_TEMPLATE](#) (void, set\_counters)(Counters< Array\_Type
- support\_fun [set\\_counters](#) (counters)
- [MODEL\\_TEMPLATE](#) (void, add\_hasher)(Hasher\_fun\_type< Array\_Type
- [MODEL\\_TEMPLATE](#) (void, add\_rule)(Rule< Array\_Type
- [MODEL\\_TEMPLATE](#) (void, set\_rules)(Rules< Array\_Type
- support\_fun [set\\_rules](#) (rules)
- [MODEL\\_TEMPLATE](#) (void, add\_rule\_dyn)(Rule< Array\_Type
- [MODEL\\_TEMPLATE](#) (void, set\_rules\_dyn)(Rules< Array\_Type
- support\_fun [set\\_rules\\_dyn](#) (rules\_dyn)
- [MODEL\\_TEMPLATE](#) (uint, add\_array)(const Array\_Type &Array\_
- if (transform\_model\_fun) = transform\_model\_fun(&tmp\_counts[0u], tmp\_counts.size())
- else stats\_target [push\\_back](#) (counter\_fun.count\_all())
- if (force\_new|(locator==keys2support.end()))
- arrays2support [push\\_back](#) (locator->second)
- return arrays2support [size](#) () - 1u
- [MODEL\\_TEMPLATE](#) (double, likelihood)(const std
- [MODEL\\_TEMPLATE](#) (double, likelihood\_total)(const std
- [MODEL\\_TEMPLATE](#) (double, get\_norm\_const)(const std
- [MODEL\\_TEMPLATE](#) (const std::vector< Array\_Type > \*, get\_pset)(const uint &i)
- [MODEL\\_TEMPLATE](#) (const std::vector< double > \*, get\_pset\_stats)(const uint &i)
- [MODEL\\_TEMPLATE](#) (void, print\_stats)(uint i) const
- [MODEL\\_TEMPLATE](#) (uint, size)() const noexcept
- [MODEL\\_TEMPLATE](#) (uint, size\_unique)() const noexcept
- [MODEL\\_TEMPLATE](#) (uint, nterms)() const noexcept
- [MODEL\\_TEMPLATE](#) (uint, nrules)() const noexcept
- [MODEL\\_TEMPLATE](#) (uint, nrules\_dyn)() const noexcept
- [MODEL\\_TEMPLATE](#) (uint, support\_size)() const noexcept
- [MODEL\\_TEMPLATE](#) (std::vector< std::string >, colnames)() const
- [MODEL\\_TEMPLATE](#) (Array\_Type, sample)(const Array\_Type &Array\_
- if (locator==keys2support.end())
- std::uniform\_real\_distribution [urand](#) (0, 1)
- if ((probs.size() > 0u) &&(vec\_equal\_approx(params, params\_last[a])))
- std::vector< double > [temp\\_stats](#) (params.size())
- for (size\_t array=0u;array< [probs.size](#)();++array)
- [MODEL\\_TEMPLATE](#) (double, conditional\_prob)(const Array\_Type &Array\_
- A [insert\\_cell](#) (i, j, A.default\_val(), true, false)
- std::vector< double > [tmp\\_counts](#) (counters->size())
- return (1.0+std::exp(-vec\_inner\_prod< double > (&params[0u], &tmp\_counts[0u], params.size())))
- [MODEL\\_TEMPLATE](#) (const std::mt19937 \*, get\_engine)() const
- [MODEL\\_TEMPLATE](#) (std::vector< std::vector< double > > \*, get\_stats\_target)()
- [MODEL\\_TEMPLATE](#) (std::vector< std::vector< double > > \*, get\_stats\_support)()
- [MODEL\\_TEMPLATE](#) (std::vector< unsigned int > \*, get\_arrays2support)()
- [MODEL\\_TEMPLATE](#) (std::vector< std::vector< Array\_Type > > \*, get\_pset\_arrays)()
- [MODEL\\_TEMPLATE](#) (std::vector< std::vector< double > > \*, get\_pset\_stats)()
- [MODEL\\_TEMPLATE](#) (std::vector< std::vector< double > > \*, get\_pset\_probs)()
- [MODEL\\_TEMPLATE](#) (void, set\_transform\_model)(std

## Variables

- [Data\\_Counter\\_Type](#) & [counter](#)
- [return](#)
- [Data\\_Counter\\_Type](#) [count\\_fun\\_](#)
- [Data\\_Counter\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#) > [init\\_fun\\_](#)
- [Data\\_Counter\\_Type](#) [Counter\\_fun\\_type](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#) > [Data\\_Counter\\_Type](#) [data\\_](#)
- [Data\\_Counter\\_Type](#) \* [counters\\_](#)
- [Data\\_Counter\\_Type](#) [fun\\_](#)
- [Data\\_Rule\\_Type](#) & [rules](#)
- [Data\\_Rule\\_Type](#) \* [rules\\_](#)
- [this](#) [delete\\_rules](#) = [false](#)
- [Data\\_Rule\\_Dyn\\_Type](#) [rule\\_fun\\_](#)
- [this](#) [rules\\_dyn](#) = [rules\\_](#)
- [this](#) [delete\\_rules\\_dyn](#) = [false](#)
- [bool](#) [force\\_new](#)
- [std::vector](#)< [double](#) > [key](#) = [counters](#)->[gen\\_hash](#)([Array\\_](#))
- [MapVec\\_type](#)< [double](#), [uint](#) >::const\_iterator [locator](#) = [keys2support](#).find([key](#))
- [stats\\_support\\_n\\_arrays](#) [[locator](#)->[second](#)]
- [const](#) [std::vector](#)< [double](#) > & [params](#)
- [size\\_t](#) [i](#) = [locator](#)->[second](#)
- [unsigned int](#) [a](#) = [arrays2support](#)[[i](#)]
- [double](#) [r](#) = [urand](#)(\*[engine](#))
- [double](#) [cumprob](#) = 0.0
- [size\\_t](#) [k](#) = [params.size](#)()
- [unsigned int](#) [j](#) = 0u
- [std::vector](#)< [double](#) > & [probs](#) = [pset\\_probs](#)[[a](#)]
- [else](#)
- [const](#) [std::vector](#)< [double](#) > & [stats](#) = [pset\\_stats](#)[[a](#)]
- [int](#) [i\\_matches](#) = -1
- [return](#) [this](#) [pset\\_arrays](#) [[a](#)][[j](#)]
- [template](#) [Data\\_Counter\\_Type](#)
- [template](#) [Data\\_Rule\\_Type](#)

## 9.35.1 Macro Definition Documentation

### 9.35.1.1 MODEL\_TEMPLATE

```
#define MODEL_TEMPLATE(
    a,
    b )  template MODEL_TEMPLATE_ARGS() inline a MODEL_TYPE()::b
```

Definition at line 87 of file `model-meat.hpp`.

### 9.35.1.2 MODEL\_TEMPLATE\_ARGS

```
template MODEL_TEMPLATE_ARGS( )
```

**Value:**

```
<typename Array_Type, typename Data_Counter_Type,\
  typename Data_Rule_Type, typename Data_Rule_Dyn_Type>
```

Definition at line 84 of file model-meat.hpp.

### 9.35.1.3 MODEL\_TYPE

```
template Data_Rule_Dyn_Type * MODEL_TYPE( )
```

**Value:**

```
Model<Array_Type, Data_Counter_Type, Data_Rule_Type,\
  Data_Rule_Dyn_Type>
```

Definition at line 81 of file model-meat.hpp.

## 9.35.2 Function Documentation

### 9.35.2.1 for()

```
for ( )
```

Definition at line 1234 of file model-meat.hpp.

### 9.35.2.2 if() [1/4]

```
if (
    (probs.size() > 0u) && (vec_equal_approx(params, params_last[a])) )
```

Definition at line 1218 of file model-meat.hpp.

### 9.35.2.3 if() [2/4]

```
if (
    force_new| locator==keys2support.end() )
```

When computing with the powerset, we need to grow the corresponding vectors on the fly

Definition at line 409 of file model-meat.hpp.

**9.35.2.4 if() [3/4]**

```
if (
    locator == keys2support.end() )
```

When computing with the powerset, we need to grow the corresponding vectors on the fly

Definition at line 1120 of file model-meat.hpp.

**9.35.2.5 if() [4/4]**

```
if (
    transform_model_fun ) = transform_model_fun(&tmp_counts[0u], tmp_counts.size())
```

Definition at line 398 of file model-meat.hpp.

**9.35.2.6 insert\_cell()**

```
A insert_cell (
    i ,
    j ,
    A. default_val(),
    true ,
    false )
```

**9.35.2.7 likelihood\_()**

```
double likelihood_ (
    const double * stats_target,
    const std::vector< double > & params,
    const double normalizing_constant,
    size_t n_params,
    bool log_ = false ) [inline]
```

Definition at line 45 of file model-meat.hpp.

**9.35.2.8 MODEL\_TEMPLATE() [1/33]**

```
MODEL_TEMPLATE (
    Array_Type ,
    sample ) const &
```

### 9.35.2.9 MODEL\_TEMPLATE() [2/33]

```
MODEL_TEMPLATE (
    const std::mt19937 * ,
    get_engine ) const
```

Definition at line 1288 of file model-meat.hpp.

### 9.35.2.10 MODEL\_TEMPLATE() [3/33]

```
MODEL_TEMPLATE (
    const std::vector< Array_Type > * ,
    get_pset ) const &
```

Definition at line 861 of file model-meat.hpp.

### 9.35.2.11 MODEL\_TEMPLATE() [4/33]

```
MODEL_TEMPLATE (
    const std::vector< double > * ,
    get_pset_stats ) const &
```

Definition at line 873 of file model-meat.hpp.

### 9.35.2.12 MODEL\_TEMPLATE() [5/33]

```
MODEL_TEMPLATE (
    double ,
    conditional_prob ) const &
```

### 9.35.2.13 MODEL\_TEMPLATE() [6/33]

```
MODEL_TEMPLATE (
    double ,
    get_norm_const ) const
```

Definition at line 825 of file model-meat.hpp.

**9.35.2.14 MODEL\_TEMPLATE() [7/33]**

```
MODEL_TEMPLATE (
    double ,
    likelihood ) const
```

Definition at line 521 of file model-meat.hpp.

**9.35.2.15 MODEL\_TEMPLATE() [8/33]**

```
MODEL_TEMPLATE (
    double ,
    likelihood_total ) const
```

Definition at line 755 of file model-meat.hpp.

**9.35.2.16 MODEL\_TEMPLATE() [9/33]**

```
MODEL_TEMPLATE (
    std::vector< double > ,
    gen_key ) const &
```

Definition at line 268 of file model-meat.hpp.

**9.35.2.17 MODEL\_TEMPLATE() [10/33]**

```
MODEL_TEMPLATE (
    std::vector< std::string > ,
    colnames ) const
```

Definition at line 1025 of file model-meat.hpp.

**9.35.2.18 MODEL\_TEMPLATE() [11/33]**

```
MODEL_TEMPLATE (
    std::vector< std::vector< Array_Type > > * ,
    get_pset_arrays )
```

Definition at line 1328 of file model-meat.hpp.



**9.35.2.19 MODEL\_TEMPLATE() [12/33]**

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_pset_probs )
```

Definition at line 1336 of file model-meat.hpp.

**9.35.2.20 MODEL\_TEMPLATE() [13/33]**

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_pset_stats )
```

Definition at line 1332 of file model-meat.hpp.

**9.35.2.21 MODEL\_TEMPLATE() [14/33]**

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_stats_support )
```

Definition at line 1318 of file model-meat.hpp.

**9.35.2.22 MODEL\_TEMPLATE() [15/33]**

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_stats_target )
```

Definition at line 1313 of file model-meat.hpp.

**9.35.2.23 MODEL\_TEMPLATE() [16/33]**

```
MODEL_TEMPLATE (
    std::vector< unsigned int > * ,
    get_arrays2support )
```

Definition at line 1323 of file model-meat.hpp.

**9.35.2.24 MODEL\_TEMPLATE()** [17/33]

```
MODEL_TEMPLATE (
    uint ,
    add_array ) const &
```

**9.35.2.25 MODEL\_TEMPLATE()** [18/33]

```
MODEL_TEMPLATE (
    uint ,
    nrules ) const [noexcept]
```

Definition at line 999 of file model-meat.hpp.

**9.35.2.26 MODEL\_TEMPLATE()** [19/33]

```
MODEL_TEMPLATE (
    uint ,
    nrules_dyn ) const [noexcept]
```

Definition at line 1006 of file model-meat.hpp.

**9.35.2.27 MODEL\_TEMPLATE()** [20/33]

```
MODEL_TEMPLATE (
    uint ,
    nterms ) const [noexcept]
```

Definition at line 989 of file model-meat.hpp.

**9.35.2.28 MODEL\_TEMPLATE()** [21/33]

```
MODEL_TEMPLATE (
    uint ,
    size ) const [noexcept]
```

Definition at line 974 of file model-meat.hpp.

**9.35.2.29 MODEL\_TEMPLATE()** [22/33]

```
MODEL_TEMPLATE (
    uint ,
    size_unique ) const [noexcept]
```

Definition at line 981 of file model-meat.hpp.

**9.35.2.30 MODEL\_TEMPLATE()** [23/33]

```
MODEL_TEMPLATE (
    uint ,
    support_size ) const [noexcept]
```

Definition at line 1013 of file model-meat.hpp.

**9.35.2.31 MODEL\_TEMPLATE()** [24/33]

```
MODEL_TEMPLATE (
    void ,
    add_counter )
```

**9.35.2.32 MODEL\_TEMPLATE()** [25/33]

```
MODEL_TEMPLATE (
    void ,
    add_hasher )
```

**9.35.2.33 MODEL\_TEMPLATE()** [26/33]

```
MODEL_TEMPLATE (
    void ,
    add_rule )
```

**9.35.2.34 MODEL\_TEMPLATE()** [27/33]

```
MODEL_TEMPLATE (
    void ,
    add_rule_dyn )
```

**9.35.2.35 MODEL\_TEMPLATE()** [28/33]

```
MODEL_TEMPLATE (
    void ,
    print_stats ) const
```

Definition at line 884 of file model-meat.hpp.

**9.35.2.36 MODEL\_TEMPLATE()** [29/33]

```
MODEL_TEMPLATE (
    void ,
    set_counters )
```

**9.35.2.37 MODEL\_TEMPLATE()** [30/33]

```
MODEL_TEMPLATE (
    void ,
    set_rules )
```

**9.35.2.38 MODEL\_TEMPLATE()** [31/33]

```
MODEL_TEMPLATE (
    void ,
    set_rules_dyn )
```

**9.35.2.39 MODEL\_TEMPLATE()** [32/33]

```
MODEL_TEMPLATE (
    void ,
    set_transform_model )
```

Definition at line 1340 of file model-meat.hpp.

**9.35.2.40 MODEL\_TEMPLATE()** [33/33]

```
MODEL_TEMPLATE (
    void ,
    store_psets ) [noexcept]
```

Definition at line 261 of file model-meat.hpp.

**9.35.2.41 push\_back() [1/2]**

```
else stats_target push_back (
    counter_fun. count_all() )
```

**9.35.2.42 push\_back() [2/2]**

```
arrays2support push_back (
    locator-> second )
```

**9.35.2.43 return()**

```
return (
    1.0+ std::exp-vec_inner_prod< double > (&params[0u], &tmp_counts[0u], params.↵
size()) )
```

**9.35.2.44 set\_counters()**

```
counter_fun set_counters (
    counters )
```

**9.35.2.45 set\_rules()**

```
support_fun set_rules (
    rules )
```

**9.35.2.46 set\_rules\_dyn()**

```
support_fun set_rules_dyn (
    rules_dyn )
```

**9.35.2.47 size()**

```
return arrays2support size ( )
```

#### 9.35.2.48 temp\_stats()

```
std::vector< double > temp_stats (
    params. size() )
```

#### 9.35.2.49 tmp\_counts()

```
std::vector< double > tmp_counts (
    counters-> size() )
```

#### 9.35.2.50 update\_normalizing\_constant()

```
double update_normalizing_constant (
    const double * params,
    const double * support,
    size_t k,
    size_t n ) [inline]
```

Definition at line 9 of file model-meat.hpp.

#### 9.35.2.51 urand()

```
std::uniform_real_distribution urand (
    0 ,
    1 )
```

### 9.35.3 Variable Documentation

#### 9.35.3.1 a

```
unsigned int a = arrays2support[i]
```

Definition at line 1206 of file model-meat.hpp.

### 9.35.3.2 count\_fun\_

`Data_Counter_Type` count\_fun\_

Definition at line 283 of file model-meat.hpp.

### 9.35.3.3 counter

`Data_Counter_Type&` counter

**Initial value:**

```
{  
    counters->add_counter(counter, Data_Counter_Type())
```

Definition at line 275 of file model-meat.hpp.

### 9.35.3.4 counters\_

`Data_Counter_Type*` counters\_

**Initial value:**

```
{  
    if (delete_counters) {  
        delete counters;  
        delete_counters = false;  
    }  
  
    this->counters = counters_
```

Definition at line 299 of file model-meat.hpp.

### 9.35.3.5 cumprob

`double` cumprob = 0.0

Definition at line 1211 of file model-meat.hpp.

### 9.35.3.6 data\_

`Data_Rule_Dyn_Type` Data\_Rule\_Dyn\_Type data\_

**Initial value:**

```
{  
    counters->add_counter(  
        count_fun_,  
        init_fun_,  
        data_  
    )
```

Definition at line 285 of file model-meat.hpp.

### 9.35.3.7 Data\_Counter\_Type

```
template Data_Counter_Type
```

Definition at line 1308 of file model-meat.hpp.

### 9.35.3.8 Data\_Rule\_Type

```
template Data_Rule_Type
```

Definition at line 1308 of file model-meat.hpp.

### 9.35.3.9 delete\_rules

```
this delete_rules = false
```

Definition at line 342 of file model-meat.hpp.

### 9.35.3.10 delete\_rules\_dyn

```
this delete_rules_dyn = false
```

Definition at line 381 of file model-meat.hpp.

### 9.35.3.11 else

```
else (
    void )
```

#### Initial value:

```
{
    probs.resize(pset_arrays[a].size())
```

Definition at line 1227 of file model-meat.hpp.



### 9.35.3.12 force\_new

```
bool force_new
```

#### Initial value:

```
{  
  
    counter_fun.reset_array(&Array_)
```

Definition at line 392 of file model-meat.hpp.

### 9.35.3.13 fun\_

```
Data_Counter_Type fun_
```

#### Initial value:

```
{  
    counters->add_hash(fun_)
```

Definition at line 316 of file model-meat.hpp.

### 9.35.3.14 i

```
const std::vector< double > unsigned int i = locator->second
```

Definition at line 1114 of file model-meat.hpp.

### 9.35.3.15 i\_matches

```
int i_matches = -1
```

Definition at line 1233 of file model-meat.hpp.

### 9.35.3.16 init\_fun\_

```
Data_Counter_Type Counter_fun_type<Array_Type,Data_Counter_Type> init_fun_
```

Definition at line 284 of file model-meat.hpp.

### 9.35.3.17 j

```
const std::vector< double > unsigned int unsigned int j = 0u
```

Definition at line 1216 of file model-meat.hpp.

### 9.35.3.18 k

```
size_t k = params.size()
```

Definition at line 1213 of file model-meat.hpp.

### 9.35.3.19 key

```
std::vector< double > key = counters->gen_hash(Array_)
```

Definition at line 407 of file model-meat.hpp.

### 9.35.3.20 locator

```
MapVec_type< double, uint >::const_iterator locator = keys2support.find(key)
```

Definition at line 408 of file model-meat.hpp.

### 9.35.3.21 params

```
const std::vector< double > & params
```

**Initial value:**

```
{  
    if (!this->with_pset)  
        throw std::logic_error("Sampling is only available when store_pset() is active.")  
}
```

Definition at line 1107 of file model-meat.hpp.

### 9.35.3.22 probs

```
std::vector< double >& probs = pset_probs[a]
```

Definition at line 1217 of file model-meat.hpp.

### 9.35.3.23 pset\_arrays

```
return this pset_arrays[a][j]
```

Definition at line 1253 of file model-meat.hpp.

### 9.35.3.24 r

```
double r = urand(*rengine)
```

Definition at line 1210 of file model-meat.hpp.

### 9.35.3.25 return

```
return
```

Definition at line 279 of file model-meat.hpp.

### 9.35.3.26 rule\_fun\_

```
Data_Rule_Dyn_Type rule_fun_
```

Definition at line 360 of file model-meat.hpp.

### 9.35.3.27 rules

```
this rules
```

#### Initial value:

```
{  
    rules->add_rule(rules, Data_Rule_Type())
```

Definition at line 326 of file model-meat.hpp.

### 9.35.3.28 rules\_

```
Data_Rule_Dyn_Type * rules_
```

#### Initial value:

```
{  
    if (delete_rules)  
        delete rules
```

Definition at line 335 of file model-meat.hpp.

### 9.35.3.29 rules\_dyn

```
this rules_dyn = rules_
```

Definition at line 380 of file model-meat.hpp.

### 9.35.3.30 stats

```
const std::vector< double >& stats = pset_stats[a]
```

Definition at line 1231 of file model-meat.hpp.


### 9.35.3.31 stats\_support\_n\_arrays

```
stats_support_n_arrays[locator->second]
```

Definition at line 512 of file model-meat.hpp.

## 9.36 include/barry/models/defm/defm-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [DEFM](#)

## 9.37 include/barry/models/defm/defm-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- `#define DEFM\_RANGES(a)`
- `#define DEFM\_LOOP\_ARRAYS(a) for (size_t a = 0u; a < (nobs_i - M_order); ++a)`

## Functions

- `std::vector< double > keygen\_defm (const defmcounters::DEFMArray &Array\_, defmcounters::DEFMCounterData *data)`

### 9.37.1 Macro Definition Documentation

#### 9.37.1.1 DEFM\_LOOP\_ARRAYS

```
#define DEFM_LOOP_ARRAYS(
    a ) for (size_t a = 0u; a < (nobs_i - M_order); ++a)
```

Definition at line 35 of file defm-meat.hpp.

### 9.37.1.2 DEFM\_RANGES

```
#define DEFM_RANGES(  
    a )
```

#### Value:

```
size_t __CONCAT(start_,a) = start_end[a * 2u];\  
size_t __CONCAT(end_,a)   = start_end[a * 2u + 1u];\  
size_t __CONCAT(nobs_,a)  = __CONCAT(end_,i) - __CONCAT(start_,i) + 1u;
```

Definition at line 30 of file defm-meat.hpp.

## 9.37.2 Function Documentation

### 9.37.2.1 keygen\_defm()

```
std::vector< double > keygen_defm (  
    const defmcounters::DEFMArray & Array_,  
    defmcounters::DEFMCounterData * data ) [inline]
```

Definition at line 4 of file defm-meat.hpp.

## 9.38 include/barry/models/geese.hpp File Reference


```
#include "geese/geese-node-bones.hpp"  
#include "geese/geese-bones.hpp"  
#include "geese/geese-meat.hpp"  
#include "geese/geese-meat-constructors.hpp"  
#include "geese/geese-meat-likelihood.hpp"  
#include "geese/geese-meat-likelihood_exhaust.hpp"  
#include "geese/geese-meat-simulate.hpp"  
#include "geese/geese-meat-predict.hpp"  
#include "geese/geese-meat-predict_exhaust.hpp"  
#include "geese/geese-meat-predict_sim.hpp"  
#include "geese/flock-bones.hpp"  
#include "geese/flock-meat.hpp"
```

Include dependency graph for geese.hpp:



## 9.39 include/barry/models/geese/flock-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [Flock](#)  
*A [Flock](#) is a group of [Geese](#).*

## 9.40 include/barry/models/geese/flock-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 9.41 include/barry/models/geese/geese-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [Geese](#)  
*Annotated Phylo [Model](#).*

### Macros

- #define [INITIALIZED\(\)](#)

### Functions

- template<typename Ta , typename Tb >  
std::vector< Ta > [vector\\_caster](#) (const std::vector< Tb > &x)
- [RULE\\_FUNCTION](#) (rule\_empty\_free)
- std::vector< double > [keygen\\_full](#) (const phylocounters::PhyloArray &array, const phylocounters::PhyloCounterData \*d)
- bool [vec\\_diff](#) (const std::vector< unsigned int > &s, const std::vector< unsigned int > &a)

#### 9.41.1 Macro Definition Documentation



### 9.41.1.1 INITIALIZED

```
#define INITIALIZED( )
```

#### Value:

```
if (!this->initialized) \  
    throw std::logic_error("The model has not been initialized yet.");
```

Definition at line 22 of file geese-bones.hpp.

## 9.41.2 Function Documentation

### 9.41.2.1 keygen\_full()

```
std::vector< double > keygen_full (   
    const phylocounters::PhyloArray & array,   
    const phylocounters::PhyloCounterData * d ) [inline]
```

Definition at line 36 of file geese-bones.hpp.

### 9.41.2.2 RULE\_FUNCTION()

```
RULE_FUNCTION (   
    rule_empty_free )
```

Definition at line 26 of file geese-bones.hpp.

### 9.41.2.3 vec\_diff()

```
bool vec_diff (   
    const std::vector< unsigned int > & s,   
    const std::vector< unsigned int > & a ) [inline]
```

Definition at line 61 of file geese-bones.hpp.


### 9.41.2.4 vector\_caster()

```
template<typename Ta , typename Tb >   
std::vector< Ta > vector_caster (   
    const std::vector< Tb > & x ) [inline]
```

Definition at line 10 of file geese-bones.hpp.

## 9.42 include/barry/models/geese/geese-meat-constructors.hpp File Reference


This graph shows which files directly or indirectly include this file:




## 9.43 include/barry/models/geese/geese-meat-likelihood.hpp File Reference

```
#include "geese-bones.hpp"
```

Include dependency graph for geese-meat-likelihood.hpp:




This graph shows which files directly or indirectly include this file:




## 9.44 include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 9.45 include/barry/models/geese/geese-meat-predict.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 9.46 include/barry/models/geese/geese-meat-predict\_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 9.47 include/barry/models/geese/geese-meat-predict\_sim.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 9.48 include/barry/models/geese/geese-meat-simulate.hpp File Reference

This graph shows which files directly or indirectly include this file:




## 9.49 include/barry/models/geese/geese-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 9.50 include/barry/models/geese/geese-node-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [Node](#)  
*A single node for the model.*

## 9.51 include/barry/powerset-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




### Classes

- class [PowerSet< Array\\_Type, Data\\_Rule\\_Type >](#)  
*Powerset of a binary array.*


## 9.52 include/barry/powerset-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 9.53 include/barry/progress.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [Progress](#)  
*A simple progress bar.*

### Macros

- `#define BARRY\_PROGRESS\_BAR\_WIDTH 80`

#### 9.53.1 Macro Definition Documentation

##### 9.53.1.1 BARRY\_PROGRESS\_BAR\_WIDTH


```
#define BARRY_PROGRESS_BAR_WIDTH 80
```

Definition at line 5 of file progress.hpp.



## 9.54 include/barry/rules-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Classes

- class [Rule< Array\\_Type, Data\\_Type >](#)  
*Rule for determining if a cell should be included in a sequence.*
- class [Rules< Array\\_Type, Data\\_Type >](#)  
*Vector of objects of class [Rule](#).*

### Functions

- `template<typename Array_Type , typename Data_Type >`  
`bool rule\_fun\_default (const Array_Type *array, uint i, uint j, Data_Type *dat)`

#### 9.54.1 Function Documentation


##### 9.54.1.1 `rule_fun_default()`

```
template<typename Array_Type , typename Data_Type >
bool rule_fun_default (
    const Array_Type * array,
    uint i,
    uint j,
    Data_Type * dat )
```

Definition at line 5 of file rules-bones.hpp.


## 9.55 include/barry/rules-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## 9.56 include/barry/statscounter-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




## Classes

- class [StatsCounter< Array\\_Type, Data\\_Type >](#)  
*Count stats for a single Array.*

## 9.57 include/barry/statscounter-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



### Macros

- `#define STATSCOUNTER_TYPE() StatsCounter<Array_Type,Data_Type>`
- `#define STATSCOUNTER_TEMPLATE_ARGS() <typename Array_Type, typename Data_Type>`
- `#define STATSCOUNTER_TEMPLATE(a, b) template STATSCOUNTER_TEMPLATE_ARGS() inline a STATSCOUNTER_TYPE():b`

### Functions

- `STATSCOUNTER_TEMPLATE (, StatsCounter)(const StatsCounter< Array_Type`
- `EmptyArray clear ()`
- `STATSCOUNTER_TEMPLATE (,~StatsCounter)()`
- `STATSCOUNTER_TEMPLATE (void, reset_array)(const Array_Type *Array_)`
- `STATSCOUNTER_TEMPLATE (void, add_counter)(Counter< Array_Type`
- `STATSCOUNTER_TEMPLATE (void, set_counters)(Counters< Array_Type`
- `STATSCOUNTER_TEMPLATE (void, count_init)(uint i`
- `current_stats resize (counters->size(), 0.0)`
- `for (uint n=0u;n< counters->size();++n) current_stats[n]`
- `STATSCOUNTER_TEMPLATE (void, count_current)(uint i`
- `STATSCOUNTER_TEMPLATE (std::vector< std::string >, get_names)() const`
- `STATSCOUNTER_TEMPLATE (std::vector< std::string >, get_descriptions)() const`

### Variables

- `Data_Type & counter`
- `EmptyArray = *Array`
- `current_stats = counter.current_stats`
- `counters = new Counters<Array_Type,Data_Type>((*counter.counters))`
- `counter_deleted = false`
- `Data_Type f_`
- `return`
- `Data_Type * counters_`
- `uint j`

## 9.57.1 Macro Definition Documentation

### 9.57.1.1 STATSCOUNTER\_TEMPLATE

```
#define STATSCOUNTER_TEMPLATE(  
    a,  
    b )  template STATSCOUNTER_TEMPLATE_ARGS() inline a STATSCOUNTER_TYPE()::b
```

Definition at line 8 of file statscounter-meat.hpp.

### 9.57.1.2 STATSCOUNTER\_TEMPLATE\_ARGS

```
template STATSCOUNTER_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file statscounter-meat.hpp.

### 9.57.1.3 STATSCOUNTER\_TYPE

```
template Data_Type * STATSCOUNTER_TYPE( ) StatsCounter<Array_Type, Data_Type>
```

Definition at line 4 of file statscounter-meat.hpp.

## 9.57.2 Function Documentation

### 9.57.2.1 clear()

```
EmptyArray clear ( )
```

### 9.57.2.2 for()

```
for (   
    uint n = 0u; n< counters->size(); ++n )
```

### 9.57.2.3 `resize()`

```
current_stats resize (
    counters-> size(),
    0. 0 )
```

### 9.57.2.4 `STATSCOUNTER_TEMPLATE()` [1/9]

```
STATSCOUNTER_TEMPLATE (
    StatsCounter ) const
```

### 9.57.2.5 `STATSCOUNTER_TEMPLATE()` [2/9]

```
STATSCOUNTER_TEMPLATE (
    ~ StatsCounter )
```

Definition at line 27 of file statscounter-meat.hpp.

### 9.57.2.6 `STATSCOUNTER_TEMPLATE()` [3/9]

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 256 of file statscounter-meat.hpp.

### 9.57.2.7 `STATSCOUNTER_TEMPLATE()` [4/9]

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_names ) const
```

Definition at line 251 of file statscounter-meat.hpp.

### 9.57.2.8 `STATSCOUNTER_TEMPLATE()` [5/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    add_counter )
```

### 9.57.2.9 STATSCOUNTER\_TEMPLATE() [6/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_current )
```

### 9.57.2.10 STATSCOUNTER\_TEMPLATE() [7/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_init )
```

### 9.57.2.11 STATSCOUNTER\_TEMPLATE() [8/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    reset_array ) const
```

Definition at line 34 of file statscounter-meat.hpp.

### 9.57.2.12 STATSCOUNTER\_TEMPLATE() [9/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    set_counters )
```

## 9.57.3 Variable Documentation

### 9.57.3.1 counter

Data\_Type& counter

#### Initial value:

```
{
    Array      = counter.Array
```

Definition at line 12 of file statscounter-meat.hpp.

### 9.57.3.2 counter\_deleted

```
counter_deleted = false
```

Definition at line 23 of file statscounter-meat.hpp.

### 9.57.3.3 counters

```
counters = new Counters<Array_Type,Data_Type>((*counter.counters))
```

Definition at line 22 of file statscounter-meat.hpp.

### 9.57.3.4 counters\_

```
Data_Type* counters_
```

#### Initial value:

```
{  
  
    if (!counter_deleted)  
        delete counters
```

Definition at line 53 of file statscounter-meat.hpp.

### 9.57.3.5 current\_stats

```
current_stats = counter.current_stats
```

Definition at line 19 of file statscounter-meat.hpp.

### 9.57.3.6 EmptyArray

```
EmptyArray = *Array
```

Definition at line 17 of file statscounter-meat.hpp.

### 9.57.3.7 f\_

Data\_Rule\_Dyn\_Type f\_

#### Initial value:

```
{  
    counters->add_counter(f_)
```

Definition at line 44 of file statscounter-meat.hpp.

### 9.57.3.8 j

uint j

#### Initial value:

```
{  
  
    if (counters->size() == 0u)  
        throw std::logic_error("No counters added: Cannot count without knowing what to count!")
```

Definition at line 66 of file statscounter-meat.hpp.


### 9.57.3.9 return

return

Definition at line 49 of file statscounter-meat.hpp.

## 9.58 include/barry/support-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:






## Classes

- class [Support](#)< [Array\\_Type](#), [Data\\_Counter\\_Type](#), [Data\\_Rule\\_Type](#), [Data\\_Rule\\_Dyn\\_Type](#) >  
*Compute the support of sufficient statistics.*

## 9.59 include/barry/support-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



## Macros

- `#define BARRY_SUPPORT_MEAT_HPP 1`
- `#define SUPPORT_TEMPLATE_ARGS()`
- `#define SUPPORT_TYPE()`
- `#define SUPPORT_TEMPLATE(a, b)`

## Functions

- `SUPPORT_TEMPLATE` (void, init\_support)(std
- `SUPPORT_TEMPLATE` (void, reset\_array)()
- `SUPPORT_TEMPLATE` (void, reset\_array)(const [Array\\_Type](#) &[Array\\_](#))
- `SUPPORT_TEMPLATE` (void, calc\_backend\_sparse)(uint pos
- `calc_backend_sparse` (pos+1u, [array\\_bank](#), [stats\\_bank](#))
- `EmptyArray insert_cell` ([coord\\_i](#), [coord\\_j](#), `EmptyArray.default_val().value`, false, false)
- `for` (uint n=0u;n< n\_counters;++n)
- `if` ([rules\\_dyn](#)->size() > 0u)
- `if` ([array\\_bank](#) !=nullptr) [array\\_bank](#) -> push\_back(`EmptyArray`)
- `EmptyArray rm_cell` ([coord\\_i](#), [coord\\_j](#), false, false)
- `if` ([change\\_stats\\_different](#) > 0u)
- `SUPPORT_TEMPLATE` (void, calc\_backend\_dense)(uint pos
- `calc_backend_dense` (pos+1u, [array\\_bank](#), [stats\\_bank](#))
- `EmptyArray insert_cell` ([coord\\_i](#), [coord\\_j](#), 1, false, false)
- `SUPPORT_TEMPLATE` (void, calc)(std
- `SUPPORT_TEMPLATE` (void, add\_counter)([Counter](#)< [Array\\_Type](#)
- `SUPPORT_TEMPLATE` (void, set\_counters)([Counters](#)< [Array\\_Type](#)

- `SUPPORT_TEMPLATE` (void, add\_rule)(Rule< Array\_Type
- `SUPPORT_TEMPLATE` (void, set\_rules)(Rules< Array\_Type
- `SUPPORT_TEMPLATE` (void, add\_rule\_dyn)(Rule< Array\_Type
- `SUPPORT_TEMPLATE` (void, set\_rules\_dyn)(Rules< Array\_Type
- `SUPPORT_TEMPLATE` (bool, eval\_rules\_dyn)(const std
- `SUPPORT_TEMPLATE` (std::vector< double >, get\_counts)() const
- `SUPPORT_TEMPLATE` (std::vector< double > \*, get\_current\_stats)()
- `SUPPORT_TEMPLATE` (void, print)() const
- `SUPPORT_TEMPLATE` (const FreqTable< double > &, get\_data)() const

## Variables

- std::vector< Array\_Type > \* `array_bank`
- std::vector< Array\_Type > std::vector< double > \* `stats_bank`
- const size\_t & `coord_i` = coordinates\_free[pos \* 2u]
- const size\_t & `coord_j` = coordinates\_free[pos \* 2u + 1u]
- double `tmp_chng`
- unsigned int `change_stats_different` = hashes\_initialized[pos] ? 0u : 1u
- else
- & `hashes` [pos]
- return
- Data\_Counter\_Type f\_
- Data\_Counter\_Type \* `counters_`
- delete\_counters = false
- counters = counters\_
- Data\_Rule\_Type \* `rules_`
- delete\_rules = false
- rules = rules\_
- delete\_rules\_dyn = false
- rules\_dyn = rules\_

## 9.59.1 Macro Definition Documentation

### 9.59.1.1 BARRY\_SUPPORT\_MEAT\_HPP

```
#define BARRY_SUPPORT_MEAT_HPP 1
```

Definition at line 2 of file support-meat.hpp.

### 9.59.1.2 SUPPORT\_TEMPLATE

```
#define SUPPORT_TEMPLATE(
    a,
    b )
```

#### Value:

```
template SUPPORT_TEMPLATE_ARGS() \
inline a SUPPORT_TYPE()::b
```

Definition at line 10 of file support-meat.hpp.

### 9.59.1.3 SUPPORT\_TEMPLATE\_ARGS

```
template SUPPORT_TEMPLATE_ARGS( )
```

**Value:**

```
<typename Array_Type, typename \  
Data_Counter_Type, typename Data_Rule_Type, typename Data_Rule_Dyn_Type>
```

Definition at line 4 of file support-meat.hpp.

### 9.59.1.4 SUPPORT\_TYPE

```
template Data_Rule_Dyn_Type * SUPPORT_TYPE( )
```

**Value:**

```
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, \  
Data_Rule_Dyn_Type>
```

Definition at line 7 of file support-meat.hpp.

## 9.59.2 Function Documentation

### 9.59.2.1 calc\_backend\_dense()

```
calc_backend_dense (   
    pos+ 1u,   
    array_bank ,   
    stats_bank )
```

### 9.59.2.2 calc\_backend\_sparse()

```
calc_backend_sparse (   
    pos+ 1u,   
    array_bank ,   
    stats_bank )
```

### 9.59.2.3 for()

```
for ( )
```

Definition at line 159 of file support-meat.hpp.

**9.59.2.4 if() [1/3]**

```
if (
    array_bank !    = nullptr ) -> push_back(EmptyArray)
```

**9.59.2.5 if() [2/3]**

```
if (
    change_stats_different ,
    Ou )
```

Definition at line 239 of file support-meat.hpp.

**9.59.2.6 if() [3/3]**

```
if (
    rules_dyn-> size(),
    Ou )
```

Definition at line 187 of file support-meat.hpp.

**9.59.2.7 insert\_cell() [1/2]**

```
EmptyArray insert_cell (
    coord_i ,
    coord_j ,
    1 ,
    false ,
    false )
```

**9.59.2.8 insert\_cell() [2/2]**

```
EmptyArray insert_cell (
    coord_i ,
    coord_j ,
    EmptyArray.default_val(). value,
    false ,
    false )
```

### 9.59.2.9 rm\_cell()

```
EmptyArray rm_cell (
    coord_i ,
    coord_j ,
    false ,
    false )
```

### 9.59.2.10 SUPPORT\_TEMPLATE() [1/17]

```
SUPPORT_TEMPLATE (
    bool ,
    eval_rules_dyn ) const
```

Definition at line 493 of file support-meat.hpp.

### 9.59.2.11 SUPPORT\_TEMPLATE() [2/17]

```
SUPPORT_TEMPLATE (
    const FreqTable< double > & ,
    get_data ) const
```

Definition at line 562 of file support-meat.hpp.

### 9.59.2.12 SUPPORT\_TEMPLATE() [3/17]

```
SUPPORT_TEMPLATE (
    std::vector< double > * ,
    get_current_stats )
```

Definition at line 547 of file support-meat.hpp.

### 9.59.2.13 SUPPORT\_TEMPLATE() [4/17]

```
SUPPORT_TEMPLATE (
    std::vector< double > ,
    get_counts ) const
```

Definition at line 535 of file support-meat.hpp.

**9.59.2.14 SUPPORT\_TEMPLATE()** [5/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_counter )
```

**9.59.2.15 SUPPORT\_TEMPLATE()** [6/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_rule )
```

**9.59.2.16 SUPPORT\_TEMPLATE()** [7/17]

```
SUPPORT_TEMPLATE (
    void ,
    add_rule_dyn )
```

**9.59.2.17 SUPPORT\_TEMPLATE()** [8/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc )
```

Definition at line 371 of file support-meat.hpp.

**9.59.2.18 SUPPORT\_TEMPLATE()** [9/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc_backend_dense )
```

**9.59.2.19 SUPPORT\_TEMPLATE()** [10/17]

```
SUPPORT_TEMPLATE (
    void ,
    calc_backend_sparse )
```

**9.59.2.20 SUPPORT\_TEMPLATE()** [11/17]

```
SUPPORT_TEMPLATE (
    void ,
    init_support )
```

Definition at line 13 of file support-meat.hpp.

**9.59.2.21 SUPPORT\_TEMPLATE()** [12/17]

```
SUPPORT_TEMPLATE (
    void ,
    print ) const
```

Definition at line 551 of file support-meat.hpp.

**9.59.2.22 SUPPORT\_TEMPLATE()** [13/17]

```
SUPPORT_TEMPLATE (
    void ,
    reset_array )
```

Definition at line 114 of file support-meat.hpp.

**9.59.2.23 SUPPORT\_TEMPLATE()** [14/17]

```
SUPPORT_TEMPLATE (
    void ,
    reset_array ) const &
```

Definition at line 120 of file support-meat.hpp.

**9.59.2.24 SUPPORT\_TEMPLATE()** [15/17]

```
SUPPORT_TEMPLATE (
    void ,
    set_counters )
```

#### 9.59.2.25 SUPPORT\_TEMPLATE() [16/17]

```
SUPPORT_TEMPLATE (
    void ,
    set_rules )
```

#### 9.59.2.26 SUPPORT\_TEMPLATE() [17/17]

```
SUPPORT_TEMPLATE (
    void ,
    set_rules_dyn )
```

### 9.59.3 Variable Documentation

#### 9.59.3.1 array\_bank

```
std::vector< Array_Type > * array_bank
```

Definition at line 131 of file support-meat.hpp.

#### 9.59.3.2 change\_stats\_different

```
unsigned int change_stats_different = hashes_initialized[pos] ? 0u : 1u
```

Definition at line 158 of file support-meat.hpp.

#### 9.59.3.3 coord\_i

```
const size_t & coord_i = coordinates_free[pos * 2u]
```

Definition at line 144 of file support-meat.hpp.

#### 9.59.3.4 coord\_j

```
const size_t & coord_j = coordinates_free[pos * 2u + 1u]
```

Definition at line 145 of file support-meat.hpp.



### 9.59.3.5 counters

```
counters = counters_
```

Definition at line 421 of file support-meat.hpp.

### 9.59.3.6 counters\_

```
Data_Counter_Type* counters_
```

**Initial value:**

```
{  
  
    if (delete_counters)  
        delete counters
```

Definition at line 414 of file support-meat.hpp.

### 9.59.3.7 delete\_counters

```
delete_counters = false
```

Definition at line 420 of file support-meat.hpp.

### 9.59.3.8 delete\_rules

```
delete_rules = false
```

Definition at line 454 of file support-meat.hpp.

### 9.59.3.9 delete\_rules\_dyn

```
delete_rules_dyn = false
```

Definition at line 486 of file support-meat.hpp.

#### 9.59.3.10 else

```
else (  
    void )
```

##### Initial value:

```
{  
    if (change_stats_different > 0u)  
        hashes[pos] = data.add(current_stats, nullptr)
```

Definition at line 212 of file support-meat.hpp.

#### 9.59.3.11 f\_

```
Data_Rule_Dyn_Type f_
```

##### Initial value:

```
{  
    counters->add_counter(f_)
```

Definition at line 405 of file support-meat.hpp.

#### 9.59.3.12 hashes

```
& hashes
```

Definition at line 217 of file support-meat.hpp.

#### 9.59.3.13 return

```
return
```

Definition at line 251 of file support-meat.hpp.

#### 9.59.3.14 rules

```
rules = rules_
```

Definition at line 455 of file support-meat.hpp.

### 9.59.3.15 rules\_

Data\_Rule\_Dyn\_Type\* rules\_

#### Initial value:

```
{  
  
    if (delete_rules)  
        delete rules
```

Definition at line 448 of file support-meat.hpp.

### 9.59.3.16 rules\_dyn

rules\_dyn = rules\_

Definition at line 487 of file support-meat.hpp.

### 9.59.3.17 stats\_bank

std::vector< Array\_Type > std::vector< double > \* stats\_bank

#### Initial value:

```
{  
  
    if (pos >= coordiantes_n_free)  
        return
```

Definition at line 132 of file support-meat.hpp.

### 9.59.3.18 tmp\_chng


double tmp\_chng

Definition at line 157 of file support-meat.hpp.


## 9.60 include/barry/typedefs.hpp File Reference

```
#include "barry-configuration.hpp"  
#include "barry-debug.hpp"  
#include "progress.hpp"
```

Include dependency graph for typedefs.hpp:



This graph shows which files directly or indirectly include this file:



### Classes

- class [Entries< Cell\\_Type >](#)  
*A wrapper class to store source, target, val from a [BArray](#) object.*
- struct [vecHasher< T >](#)

### Namespaces

- [CHECK](#)  
*Integer constants used to specify which cell should be check.*
- [EXISTS](#)  
*Integer constants used to specify which cell should be check to exist or not.*

## Typedefs

- typedef unsigned int [uint](#)
- typedef std::vector< std::pair< std::vector< double >, [uint](#) > > [Counts\\_type](#)
- template<typename Cell\_Type >  
using [Row\\_type](#) = [Map](#)< [uint](#), [Cell](#)< Cell\_Type > >
- template<typename Cell\_Type >  
using [Col\\_type](#) = [Map](#)< [uint](#), [Cell](#)< Cell\_Type > \* >
- template<typename Ta = double, typename Tb = uint>  
using [MapVec\\_type](#) = std::unordered\_map< std::vector< Ta >, Tb, [vecHasher](#)< Ta > >
- template<typename Array\_Type , typename Data\_Type >  
using [Hasher\\_fun\\_type](#) = std::function< std::vector< double >([const](#) Array\_Type &, Data\_Type \*)>  
*Hasher function used by the counter.*
- template<typename Array\_Type , typename Data\_Type >  
using [Counter\\_fun\\_type](#) = std::function< double([const](#) Array\_Type &, [uint](#), [uint](#), Data\_Type &)>  
*Counter and rule functions.*
- template<typename Array\_Type , typename Data\_Type >  
using [Rule\\_fun\\_type](#) = std::function< bool([const](#) Array\_Type &, [uint](#), [uint](#), Data\_Type &)>

## Functions

- std::vector< size\_t > [sort\\_array](#) ([const](#) double \*v, size\_t start, size\_t ncols, size\_t nrows)  
*Ascending sorting an array.*
- template<typename T >  
T [vec\\_inner\\_prod](#) ([const](#) T \*a, [const](#) T \*b, size\_t n)
- template<> double [vec\\_inner\\_prod](#) ([const](#) double \*a, [const](#) double \*b, size\_t n)
- template<typename T >  
bool [vec\\_equal](#) ([const](#) std::vector< T > &a, [const](#) std::vector< T > &b)  
*Compares if -a- and -b- are equal.*
- template<typename T >  
bool [vec\\_equal\\_approx](#) ([const](#) std::vector< T > &a, [const](#) std::vector< T > &b, double eps=1e-100)

## Variables

- [const](#) int [CHECK::BOTH](#) = -1
- [const](#) int [CHECK::NONE](#) = 0
- [const](#) int [CHECK::ONE](#) = 1
- [const](#) int [CHECK::TWO](#) = 2
- [const](#) int [EXISTS::BOTH](#) = -1
- [const](#) int [EXISTS::NONE](#) = 0
- [const](#) int [EXISTS::ONE](#) = 1
- [const](#) int [EXISTS::TWO](#) = 1
- [const](#) int [EXISTS::UNKNOWN](#) = -1
- [const](#) int [EXISTS::AS\\_ZERO](#) = 0
- [const](#) int [EXISTS::AS\\_ONE](#) = 1

## 9.60.1 Typedef Documentation

### 9.60.1.1 Col\_type

```
template<typename Cell_Type >
using Col_type = Map< uint, Cell<Cell_Type>*>
```

Definition at line 71 of file typedefs.hpp.

### 9.60.1.2 Counter\_fun\_type

```
template<typename Array_Type , typename Data_Type >
using Counter_fun_type = std::function<double(const Array_Type &, uint, uint, Data_Type &)>
```

[Counter](#) and rule functions.

#### Parameters

<i>Array_Type</i>	a <a href="#">BArray</a>
<i>unit,uint</i>	Focal cell
<i>Data_Type</i>	Data associated with the function, for example, id of the attribute in the Array.

#### Returns

`Counter_fun_type` a double (the change statistic)

`Rule_fun_type` a bool. True if the cell is blocked.

Definition at line 188 of file typedefs.hpp.

### 9.60.1.3 Counts\_type

```
typedef std::vector< std::pair< std::vector<double>, uint > > Counts_type
```

Definition at line 52 of file typedefs.hpp.

### 9.60.1.4 Hasher\_fun\_type

```
template<typename Array_Type , typename Data_Type >
using Hasher_fun_type = std::function<std::vector<double>(const Array_Type &, Data_Type *)>
```

Hasher function used by the counter.

Used to characterize the support of the array.

## Template Parameters

<i>Array_Type</i>	
-------------------	--

Definition at line 201 of file typedefs.hpp.

**9.60.1.5 MapVec\_type**

```
template<typename Ta = double, typename Tb = uint>
using MapVec_type = std::unordered_map< std::vector< Ta >, Tb, vecHasher<Ta> >
```

Definition at line 129 of file typedefs.hpp.

**9.60.1.6 Row\_type**

```
template<typename Cell_Type >
using Row_type = Map< uint, Cell<Cell_Type> >
```

Definition at line 68 of file typedefs.hpp.

**9.60.1.7 Rule\_fun\_type**

```
template<typename Array_Type , typename Data_Type >
using Rule_fun_type = std::function<bool(const Array_Type &, uint, uint, Data_Type &)>
```

Definition at line 191 of file typedefs.hpp.

**9.60.1.8 uint**

```
typedef unsigned int uint
```

Definition at line 18 of file typedefs.hpp.

**9.60.2 Function Documentation****9.60.2.1 sort\_array()**

```
std::vector< size_t > sort_array (
    const double * v,
    size_t start,
    size_t ncols,
    size_t nrows ) [inline]
```

Ascending sorting an array.

It will sort an array solving ties using the next column. Data is stored column-wise.

## Template Parameters

<i>T</i>	
----------	--

## Parameters

<i>v</i>	
<i>nrows</i>	

## Returns

`std::vector<size_t>` The sorting index.

Definition at line 142 of file `typedefs.hpp`.

9.60.2.2 `vec_equal()`

```
template<typename T >
bool vec_equal (
    const std::vector< T > & a,
    const std::vector< T > & b ) [inline]
```

Compares if -a- and -b- are equal.

## Parameters

<i>a,b</i>	Two vectors of the same length
------------	--------------------------------

## Returns

`true` if all elements are equal.

Definition at line 211 of file `typedefs.hpp`.

9.60.2.3 `vec_equal_approx()`

```
template<typename T >
bool vec_equal_approx (
    const std::vector< T > & a,
    const std::vector< T > & b,
    double eps = 1e-100 ) [inline]
```

Definition at line 229 of file `typedefs.hpp`.



#### 9.60.2.4 `vec_inner_prod()` [1/2]

```
template<>
double vec_inner_prod (
    const double * a,
    const double * b,
    size_t n ) [inline]
```

Definition at line 275 of file typedefs.hpp.

#### 9.60.2.5 `vec_inner_prod()` [2/2]

```
template<typename T >
T vec_inner_prod (
    const T * a,
    const T * b,
    size_t n ) [inline]
```

Definition at line 252 of file typedefs.hpp.

## 9.61 README.md File Reference



# Index

- ~BArray
  - BArray< Cell\_Type, Data\_Type >, [47](#)
- ~BArrayCell
  - BArrayCell< Cell\_Type, Data\_Type >, [58](#)
- ~BArrayCell\_const
  - BArrayCell\_const< Cell\_Type, Data\_Type >, [60](#)
- ~BArrayDense
  - BArrayDense< Cell\_Type, Data\_Type >, [66](#)
- ~BArrayDenseCell
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [79](#)
- ~BArrayRow
  - BArrayRow< Cell\_Type, Data\_Type >, [92](#)
- ~BArrayRow\_const
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [94](#)
- ~BArrayVector
  - BArrayVector< Cell\_Type, Data\_Type >, [97](#)
- ~BArrayVector\_const
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [100](#)
- ~Cell
  - Cell< Cell\_Type >, [104](#)
- ~ConstBArrayRowIter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, [109](#)
- ~Counter
  - Counter< Array\_Type, Data\_Type >, [112](#)
- ~Counters
  - Counters< Array\_Type, Data\_Type >, [117](#)
- ~DEFM
  - DEFM, [122](#)
- ~DEFMCounterData
  - DEFMCounterData, [126](#)
- ~DEFMData
  - DEFMData, [130](#)
- ~DEFMRuleDynData
  - DEFMRuleDynData, [136](#)
- ~Entries
  - Entries< Cell\_Type >, [137](#)
- ~Flock
  - Flock, [140](#)
- ~FreqTable
  - FreqTable< T >, [146](#)
- ~Geese
  - Geese, [153](#)
- ~Model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [167](#)
- ~NetCounterData
  - NetCounterData, [185](#)
- ~NetworkData
  - NetworkData, [187](#)
- ~Node
  - Node, [190](#)
- ~PhyloRuleDynData
  - PhyloRuleDynData, [199](#)
- ~PowerSet
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [202](#)
- ~Progress
  - Progress, [207](#)
- ~Rule
  - Rule< Array\_Type, Data\_Type >, [209](#)
- ~Rules
  - Rules< Array\_Type, Data\_Type >, [212](#)
- ~StatsCounter
  - StatsCounter< Array\_Type, Data\_Type >, [216](#)
- ~Support
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [221](#)
- a
  - model-meat.hpp, [348](#)
- active
  - Cell< Cell\_Type >, [107](#)
- add
  - barray-meat.hpp, [248](#)
  - barraydense-meat.hpp, [273](#)
  - Cell< Cell\_Type >, [105](#), [106](#)
  - FreqTable< T >, [147](#)
- add\_array
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [167](#)
- add\_counter
  - Counters< Array\_Type, Data\_Type >, [117](#), [118](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [168](#)
  - StatsCounter< Array\_Type, Data\_Type >, [217](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [222](#)
- add\_data
  - Flock, [140](#)
- add\_dims
  - counters-meat.hpp, [303](#)
- add\_hash
  - Counters< Array\_Type, Data\_Type >, [118](#)

- add\_hasher
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 168
- add\_rule
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 168
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 202, 203
  - Rules< Array\_Type, Data\_Type >, 213
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 222
- add\_rule\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 169
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 222
- annotations
  - Node, 191
- ans
  - barray-meat.hpp, 239, 248
  - barraydense-meat.hpp, 262, 273
- Array
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 109
- array
  - DEFMData, 130
  - Node, 191
- Array\_
  - barray-meat.hpp, 248
- array\_bank
  - support-meat.hpp, 382
- arrays
  - Node, 191
- arrays2support
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 178
- AS\_ONE
  - EXISTS, 41
- as\_vector
  - FreqTable< T >, 147
- AS\_ZERO
  - EXISTS, 41
- at
  - DEFMData, 130
  - PhyloCounterData, 196
- BArray
  - BArray< Cell\_Type, Data\_Type >, 46, 47
- BArray< Cell\_Type, Data\_Type >, 43
  - ~BArray, 47
  - BArray, 46, 47
  - BArrayCell< Cell\_Type, Data\_Type >, 56
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 56
- clear, 47
- col, 47
- D, 48
- D\_ptr, 48
- default\_val, 48
- flush\_data, 48
- get\_cell, 48
- get\_col\_vec, 49
- get\_entries, 49
- get\_row\_vec, 49
- insert\_cell, 50
- is\_dense, 50
- is\_empty, 50
- ncol, 51
- nnozero, 51
- nrow, 51
- operator\*=: 51
- operator(), 51
- operator+=, 52
- operator-=, 52
- operator/=: 53
- operator=, 53
- operator==, 53
- out\_of\_range, 53
- print, 53
- reserve, 54
- resize, 54
- rm\_cell, 54
- row, 54
- set\_data, 54
- swap\_cells, 55
- swap\_cols, 55
- swap\_rows, 55
- toggle\_cell, 55
- toggle\_lock, 55
- transpose, 56
- visited, 57
- zero\_col, 56
- zero\_row, 56
- barray-meat-operators.hpp
  - BARRAY\_TEMPLATE, 232–234
  - BARRAY\_TEMPLATE\_ARGS, 233, 235
  - BARRAY\_TYPE, 233, 235
  - COL, 233
  - for, 235
  - operator(), 235
  - rhs, 235
  - ROW, 233
  - this, 236
- barray-meat.hpp
  - add, 248
  - ans, 239, 248
  - Array\_, 248
  - BARRAY\_TEMPLATE, 238–243
  - BARRAY\_TEMPLATE\_ARGS, 238
  - BARRAY\_TYPE, 238
  - check\_bounds, 248
  - check\_exists, 249

- COL, 239, 243
- col0, 249
- const, 249
- copy\_data, 249
- data, 250
- delete\_data, 250
- delete\_data\_, 250
- else, 250
- false, 250
- first, 251
- for, 244
- i1, 251
- if, 244–247
- j, 251
- j0, 251
- j1, 251
- M, 247, 251
- M\_, 252
- N, 252
- NCells, 252
- report, 252
- resize, 247
- return, 247, 252
- ROW, 239, 247, 248
- row0, 253
- search, 253
- source, 253
- target, 253
- v, 253
- value, 253
- BARRAY\_TEMPLATE
  - barray-meat-operators.hpp, 232–234
  - barray-meat.hpp, 238–243
- BARRAY\_TEMPLATE\_ARGS
  - barray-meat-operators.hpp, 233, 235
  - barray-meat.hpp, 238
- BARRAY\_TYPE
  - barray-meat-operators.hpp, 233, 235
  - barray-meat.hpp, 238
- BArrayCell
  - BArrayCell< Cell\_Type, Data\_Type >, 58
- BArrayCell< Cell\_Type, Data\_Type >, 57
  - ~BArrayCell, 58
  - BArray< Cell\_Type, Data\_Type >, 56
  - BArrayCell, 58
  - operator Cell\_Type, 58
  - operator\*=, 58
  - operator+=, 58
  - operator-=, 59
  - operator/=: 59
  - operator=, 59
  - operator==, 59
- BArrayCell\_const
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 60
- BArrayCell\_const< Cell\_Type, Data\_Type >, 60
  - ~BArrayCell\_const, 60
  - BArray< Cell\_Type, Data\_Type >, 56
  - BArrayCell\_const, 60
- operator Cell\_Type, 61
- operator!=, 61
- operator<, 61
- operator<=, 61
- operator>, 61
- operator>=, 62
- operator==, 61
- BArrayDense
  - BArrayDense< Cell\_Type, Data\_Type >, 65, 66
- BArrayDense< Cell\_Type, Data\_Type >, 62
  - ~BArrayDense, 66
  - BArrayDense, 65, 66
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 76, 81
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 77, 84
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 77
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 77, 88
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 77
  - clear, 67
  - col, 67
  - colsum, 67
  - D, 67, 68
  - D\_ptr, 68
  - default\_val, 68
  - get\_cell, 68
  - get\_col\_vec, 68, 69
  - get\_data, 69
  - get\_entries, 69
  - get\_row\_vec, 69
  - insert\_cell, 70
  - is\_dense, 70
  - is\_empty, 70
  - ncol, 70
  - nnozero, 71
  - nrow, 71
  - operator\*=, 71
  - operator(), 71
  - operator+=, 71, 72
  - operator-=, 72
  - operator/=: 72
  - operator=, 73
  - operator==, 73
  - out\_of\_range, 73
  - print, 73
  - reserve, 73
  - resize, 74
  - rm\_cell, 74
  - row, 74
  - rowsum, 74
  - set\_data, 74
  - swap\_cells, 75
  - swap\_cols, 75
  - swap\_rows, 75
  - toggle\_cell, 75
  - toggle\_lock, 76

- transpose, 76
- visited, 77
- zero\_col, 76
- zero\_row, 76
- barraydense-meat-operators.hpp
  - BDENSE\_TEMPLATE, 256–258
  - BDENSE\_TEMPLATE\_ARGS, 256, 258
  - BDENSE\_TYPE, 256, 258
  - COL, 256
  - POS, 256
  - POS\_N, 257
  - ROW, 257
- barraydense-meat.hpp
  - add, 273
  - ans, 262, 273
  - BDENSE\_TEMPLATE, 261–269
  - BDENSE\_TEMPLATE\_ARGS, 261
  - BDENSE\_TYPE, 261
  - check\_bounds, 273
  - check\_exists, 273
  - COL, 261
  - col, 274
  - const, 274
  - copy\_data, 274
  - data, 274
  - delete\_data, 274
  - delete\_data\_, 275
  - el, 275
  - el\_colsums, 275
  - el\_rowsums, 275
  - else, 275
  - false, 276
  - for, 269
  - i1, 276
  - if, 270
  - insert\_cell, 270
  - j, 276
  - j0, 276
  - j1, 276
  - M, 271, 276
  - M\_, 277
  - N, 277
  - POS, 261
  - POS\_N, 261
  - report, 277
  - resize, 271, 272
  - return, 277
  - rm\_cell, 272
  - ROW, 262
  - source, 277
  - target, 278
  - v, 278
  - va\_end, 272
  - va\_start, 272
  - val0, 278
  - val1, 278
  - value, 278
  - vprintf, 273
  - ZERO\_CELL, 262
- BArrayDenseCell
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 79
- BArrayDenseCell< Cell\_Type, Data\_Type >, 78
  - ~BArrayDenseCell, 79
  - BArrayDense< Cell\_Type, Data\_Type >, 76, 81
  - BArrayDenseCell, 79
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 81, 84
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 81, 86
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 88
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 91
  - operator Cell\_Type, 79
  - operator\*=: 79
  - operator+=, 79
  - operator-=, 80
  - operator/=: 80
  - operator=, 80
  - operator==, 80
- barraydensecell-bones.hpp
  - POS, 279
- barraydensecell-meat.hpp
  - POS, 280
- BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 82
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 84
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 86
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 88
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 91
- BArrayDenseCol
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 82
- BArrayDenseCol< Cell\_Type, Data\_Type >, 82
  - BArrayDense< Cell\_Type, Data\_Type >, 77, 84
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 81, 84
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 84
  - BArrayDenseCol, 82
  - begin, 83
  - end, 83
  - operator(), 83
  - size, 83
- barraydensecol-bones.hpp
  - POS, 281
  - POS\_N, 281
  - ZERO\_CELL, 281
- BArrayDenseCol\_const
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 85
- BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 84
  - BArrayDense< Cell\_Type, Data\_Type >, 77
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 81, 86
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, 86
  - BArrayDenseCol\_const, 85

- begin, [85](#)
- end, [85](#)
- operator(), [85](#)
- size, [86](#)
- BArrayDenseRow
  - BArrayDenseRow< Cell\_Type, Data\_Type >, [87](#)
- BArrayDenseRow< Cell\_Type, Data\_Type >, [86](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [77](#), [88](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [88](#)
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, [88](#)
  - BArrayDenseRow, [87](#)
  - begin, [87](#)
  - end, [87](#)
  - operator(), [88](#)
  - size, [88](#)
- barraydenserow-bones.hpp
  - POS, [282](#)
  - POS\_N, [282](#)
  - ZERO\_CELL, [283](#)
- BArrayDenseRow\_const
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, [89](#)
- BArrayDenseRow\_const< Cell\_Type, Data\_Type >, [89](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [77](#)
  - BArrayDenseCell< Cell\_Type, Data\_Type >, [91](#)
  - BArrayDenseCell\_const< Cell\_Type, Data\_Type >, [91](#)
  - BArrayDenseRow\_const, [89](#)
  - begin, [90](#)
  - end, [90](#)
  - operator(), [90](#)
  - size, [90](#)
- BArrayRow
  - BArrayRow< Cell\_Type, Data\_Type >, [92](#)
- BArrayRow< Cell\_Type, Data\_Type >, [91](#)
  - ~BArrayRow, [92](#)
  - BArrayRow, [92](#)
  - operator BArrayRow< Cell\_Type, Data\_Type >, [92](#)
  - operator\*=[92](#)
  - operator+=[92](#)
  - operator-=[92](#)
  - operator/=, [93](#)
  - operator=, [93](#)
  - operator==, [93](#)
- barrayrow-meat.hpp
  - BROW\_TEMPLATE, [283–285](#)
  - BROW\_TEMPLATE\_ARGS, [284](#)
  - BROW\_TYPE, [284](#)
- BArrayRow\_const
  - BArrayRow\_const< Cell\_Type, Data\_Type >, [94](#)
- BArrayRow\_const< Cell\_Type, Data\_Type >, [93](#)
  - ~BArrayRow\_const, [94](#)
  - BArrayRow\_const, [94](#)
  - operator BArrayRow\_const< Cell\_Type, Data\_Type >, [94](#)
  - operator!=, [94](#)
  - operator<, [94](#)
- operator<=, [95](#)
- operator>, [95](#)
- operator>=, [95](#)
- operator==, [95](#)
- BArrayVector
  - BArrayVector< Cell\_Type, Data\_Type >, [96](#)
- BArrayVector< Cell\_Type, Data\_Type >, [95](#)
  - ~BArrayVector, [97](#)
  - BArrayVector, [96](#)
  - begin, [97](#)
  - end, [97](#)
  - is\_col, [97](#)
  - is\_row, [97](#)
  - operator std::vector< Cell\_Type >, [98](#)
  - operator\*=[98](#)
  - operator+=, [98](#)
  - operator-=, [98](#)
  - operator/=, [98](#)
  - operator=, [99](#)
  - operator==, [99](#)
  - size, [99](#)
- BArrayVector\_const
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [100](#)
- BArrayVector\_const< Cell\_Type, Data\_Type >, [99](#)
  - ~BArrayVector\_const, [100](#)
  - BArrayVector\_const, [100](#)
  - begin, [101](#)
  - end, [101](#)
  - is\_col, [101](#)
  - is\_row, [101](#)
  - operator std::vector< Cell\_Type >, [101](#)
  - operator!=, [101](#)
  - operator<, [102](#)
  - operator<=, [102](#)
  - operator>, [102](#)
  - operator>=, [102](#)
  - operator==, [102](#)
  - size, [103](#)
- barry, [39](#)
- barry-configuration.hpp
  - BARRY\_CHECK\_SUPPORT, [287](#)
  - BARRY\_ISFINITE, [287](#)
  - BARRY\_MAX\_NUM\_ELEMENTS, [287](#)
  - BARRY\_SAFE\_EXP, [287](#)
  - Map, [287](#)
  - printf\_barry, [287](#)
- barry-debug.hpp
  - BARRY\_DEBUG\_LEVEL, [288](#)
- barry-macros.hpp
  - BARRY\_ONE, [289](#)
  - BARRY\_ONE\_DENSE, [289](#)
  - BARRY\_UNUSED, [289](#)
  - BARRY\_ZERO, [290](#)
  - BARRY\_ZERO\_DENSE, [290](#)
- barry.hpp
  - BARRY\_HPP, [291](#)
  - BARRY\_VERSION, [292](#)

- BARRY\_VERSION\_MAYOR, 292
- BARRY\_VERSION\_MINOR, 292
- COUNTER\_FUNCTION, 292
- COUNTER\_LAMBDA, 292
- RULE\_FUNCTION, 293
- RULE\_LAMBDA, 293
- barry::counters, 39
- barry::counters::defm, 40
- barry::counters::network, 40
- barry::counters::phylo, 40
- BARRY\_CHECK\_SUPPORT
  - barry-configuration.hpp, 287
- BARRY\_DEBUG\_LEVEL
  - barry-debug.hpp, 288
- BARRY\_HPP
  - barry.hpp, 291
- BARRY\_ISFINITE
  - barry-configuration.hpp, 287
- BARRY\_MAX\_NUM\_ELEMENTS
  - barry-configuration.hpp, 287
- BARRY\_ONE
  - barry-macros.hpp, 289
- BARRY\_ONE\_DENSE
  - barry-macros.hpp, 289
- BARRY\_PROGRESS\_BAR\_WIDTH
  - progress.hpp, 366
- BARRY\_SAFE\_EXP
  - barry-configuration.hpp, 287
- BARRY\_SUPPORT\_MEAT\_HPP
  - support-meat.hpp, 376
- BARRY\_UNUSED
  - barry-macros.hpp, 289
- BARRY\_VERSION
  - barry.hpp, 292
- BARRY\_VERSION\_MAYOR
  - barry.hpp, 292
- BARRY\_VERSION\_MINOR
  - barry.hpp, 292
- BARRY\_ZERO
  - barry-macros.hpp, 290
- BARRY\_ZERO\_DENSE
  - barry-macros.hpp, 290
- BARRY\_ZERO\_NETWORK
  - network.hpp, 323
- BARRY\_ZERO\_NETWORK\_DENSE
  - network.hpp, 323
- BDENSE\_TEMPLATE
  - barraydense-meat-operators.hpp, 256–258
  - barraydense-meat.hpp, 261–269
- BDENSE\_TEMPLATE\_ARGS
  - barraydense-meat-operators.hpp, 256, 258
  - barraydense-meat.hpp, 261
- BDENSE\_TYPE
  - barraydense-meat-operators.hpp, 256, 258
  - barraydense-meat.hpp, 261
- begin
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 83
- BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 85
- BArrayDenseRow< Cell\_Type, Data\_Type >, 87
- BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 90
- BArrayVector< Cell\_Type, Data\_Type >, 97
- BArrayVector\_const< Cell\_Type, Data\_Type >, 101
- PhyloCounterData, 196
- PowerSet< Array\_Type, Data\_Rule\_Type >, 203
- lengths
  - NodeData, 194
- BOTH
  - CHECK, 40
  - EXISTS, 42
- BROW\_TEMPLATE
  - barrayrow-meat.hpp, 283–285
- BROW\_TEMPLATE\_ARGS
  - barrayrow-meat.hpp, 284
- BROW\_TYPE
  - barrayrow-meat.hpp, 284
- calc
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 203
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 222
- calc\_backend\_dense
  - support-meat.hpp, 377
- calc\_backend\_sparse
  - support-meat.hpp, 377
- calc\_reduced\_sequence
  - Geese, 153
- calc\_sequence
  - Geese, 153
- Cell
  - Cell< Cell\_Type >, 104, 105
- Cell< Cell\_Type >, 103
  - ~Cell, 104
  - active, 107
  - add, 105, 106
  - Cell, 104, 105
  - operator Cell\_Type, 106
  - operator!=, 106
  - operator=, 106, 107
  - operator==, 107
  - value, 107
  - visited, 107
- Cell\_const< Cell\_Type >, 108
- change\_stats
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 226
- change\_stats\_different
  - support-meat.hpp, 382
- CHECK, 40
  - BOTH, 40
  - NONE, 40
  - ONE, 40



- TWO, [41](#)
- check\_bounds
  - barray-meat.hpp, [248](#)
  - barraydense-meat.hpp, [273](#)
- check\_exists
  - barray-meat.hpp, [249](#)
  - barraydense-meat.hpp, [273](#)
- clear
  - BArray< Cell\_Type, Data\_Type >, [47](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [67](#)
  - FreqTable< T >, [147](#)
  - statscounter-meat.hpp, [370](#)
- COL
  - barray-meat-operators.hpp, [233](#)
  - barray-meat.hpp, [239](#), [243](#)
  - barraydense-meat-operators.hpp, [256](#)
  - barraydense-meat.hpp, [261](#)
- col
  - BArray< Cell\_Type, Data\_Type >, [47](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [67](#)
  - barraydense-meat.hpp, [274](#)
- col0
  - barray-meat.hpp, [249](#)
- Col\_type
  - typedefs.hpp, [388](#)
- colnames
  - Flock, [141](#)
  - Geese, [154](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [169](#)
- colsum
  - BArrayDense< Cell\_Type, Data\_Type >, [67](#)
- conditional\_prob
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [169](#)
- const
  - barray-meat.hpp, [249](#)
  - barraydense-meat.hpp, [274](#)
- ConstBArrayRowIter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, [109](#)
- ConstBArrayRowIter< Cell\_Type, Data\_Type >, [108](#)
  - ~ConstBArrayRowIter, [109](#)
  - Array, [109](#)
  - ConstBArrayRowIter, [109](#)
  - current\_col, [110](#)
  - current\_row, [110](#)
  - iter, [110](#)
- coord\_i
  - support-meat.hpp, [382](#)
- coord\_j
  - support-meat.hpp, [382](#)
- cooriantes\_n\_free
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [226](#)
- cooriantes\_n\_locked
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [226](#)
- coordinates\_free
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [205](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [226](#)
- coordinates\_locked
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [205](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [227](#)
- copy\_data
  - barray-meat.hpp, [249](#)
  - barraydense-meat.hpp, [274](#)
- count
  - Counter< Array\_Type, Data\_Type >, [113](#)
- count\_all
  - StatsCounter< Array\_Type, Data\_Type >, [217](#)
- count\_current
  - StatsCounter< Array\_Type, Data\_Type >, [217](#)
- count\_fun
  - Counter< Array\_Type, Data\_Type >, [114](#)
  - counters-meat.hpp, [298](#)
- count\_fun\_
  - counters-meat.hpp, [303](#)
  - model-meat.hpp, [348](#)
- count\_init
  - StatsCounter< Array\_Type, Data\_Type >, [217](#)
- Counter
  - Counter< Array\_Type, Data\_Type >, [112](#)
- counter
  - counters-meat.hpp, [304](#)
  - model-meat.hpp, [349](#)
  - statscounter-meat.hpp, [372](#)
- Counter< Array\_Type, Data\_Type >, [110](#)
  - ~Counter, [112](#)
  - count, [113](#)
  - count\_fun, [114](#)
  - Counter, [112](#)
  - data, [114](#)
  - desc, [115](#)
  - get\_description, [113](#)
  - get\_hasher, [113](#)
  - get\_name, [113](#)
  - hasher\_fun, [115](#)
  - init, [113](#)
  - init\_fun, [115](#)
  - name, [115](#)
  - operator=, [113](#), [114](#)
  - set\_hasher, [114](#)
- counter\_
  - counters-meat.hpp, [304](#)
- counter\_absdiff
  - DEFMArray counters, [21](#)
- counter\_co\_opt

- Phylo counters, [32](#)
- counter\_cogain
  - Phylo counters, [32](#)
- counter\_css\_census01
  - network-css.hpp, [316](#)
- counter\_css\_census02
  - network-css.hpp, [316](#)
- counter\_css\_census03
  - network-css.hpp, [316](#)
- counter\_css\_census04
  - network-css.hpp, [317](#)
- counter\_css\_census05
  - network-css.hpp, [317](#)
- counter\_css\_census06
  - network-css.hpp, [317](#)
- counter\_css\_census07
  - network-css.hpp, [317](#)
- counter\_css\_census08
  - network-css.hpp, [318](#)
- counter\_css\_census09
  - network-css.hpp, [318](#)
- counter\_css\_census10
  - network-css.hpp, [318](#)
- counter\_css\_completely\_false\_recip\_comiss
  - network-css.hpp, [318](#)
- counter\_css\_completely\_false\_recip\_omiss
  - network-css.hpp, [319](#)
- counter\_css\_mixed\_recip
  - network-css.hpp, [319](#)
- counter\_css\_partially\_false\_recip\_commi
  - network-css.hpp, [319](#)
- counter\_css\_partially\_false\_recip\_omiss
  - network-css.hpp, [320](#)
- counter\_ctriads
  - DEFMArray counters, [22](#)
- counter\_degree
  - DEFMArray counters, [22](#)
- counter\_deleted
  - statscounter-meat.hpp, [372](#)
- counter\_density
  - DEFMArray counters, [22](#)
- counter\_diff
  - DEFMArray counters, [23](#)
- counter\_edges
  - DEFMArray counters, [23](#)
- counter\_fixed\_effect
  - DEFMArray counters, [23](#)
- counter\_fun
  - Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
[178](#)
- Counter\_fun\_type
  - typedefs.hpp, [388](#)
- COUNTER\_FUNCTION
  - barry.hpp, [292](#)
- counter\_gains
  - Phylo counters, [32](#)
- counter\_gains\_from\_0
  - Phylo counters, [32](#)
- counter\_gains\_k\_offspring
  - Phylo counters, [33](#)
- counter\_genes\_changing
  - Phylo counters, [33](#)
- counter\_idegree
  - DEFMArray counters, [24](#)
- counter\_idegree15
  - DEFMArray counters, [24](#)
- counter\_isolates
  - DEFMArray counters, [24](#), [25](#)
- counter\_istar2
  - DEFMArray counters, [25](#)
- counter\_k\_genes\_changing
  - Phylo counters, [33](#)
- COUNTER\_LAMBDA
  - barry.hpp, [292](#)
- counter\_less\_than\_p\_prop\_genes\_changing
  - Phylo counters, [33](#)
- counter\_logit\_intercept
  - DEFMArray counters, [25](#)
- counter\_longest
  - Phylo counters, [34](#)
- counter\_loss
  - Phylo counters, [34](#)
- counter\_maxfun
  - Phylo counters, [34](#)
- counter\_mutual
  - DEFMArray counters, [25](#)
- counter\_neofun
  - Phylo counters, [34](#)
- counter\_neofun\_a2b
  - Phylo counters, [35](#)
- counter\_nodecov
  - DEFMArray counters, [26](#)
- counter\_nodeicov
  - DEFMArray counters, [26](#)
- counter\_nodematch
  - DEFMArray counters, [26](#)
- counter\_nodeocov
  - DEFMArray counters, [26](#)
- counter\_odegree
  - DEFMArray counters, [26](#), [27](#)
- counter\_odegree15
  - DEFMArray counters, [27](#)
- counter\_ones
  - DEFMArray counters, [27](#)
- counter\_ostar2
  - DEFMArray counters, [28](#)
- counter\_overall\_changes
  - Phylo counters, [35](#)
- counter\_overall\_gains
  - Phylo counters, [35](#)
- counter\_overall\_gains\_from\_0
  - Phylo counters, [35](#)
- counter\_overall\_loss
  - Phylo counters, [36](#)
- counter\_pairwise\_first\_gain

- Phylo counters, [36](#)
- counter\_pairwise\_neofun\_singlefun
  - Phylo counters, [36](#)
- counter\_pairwise\_overall\_change
  - Phylo counters, [36](#)
- counter\_pairwise\_preserving
  - Phylo counters, [37](#)
- counter\_preserve\_pseudogene
  - Phylo counters, [37](#)
- counter\_prop\_genes\_changing
  - Phylo counters, [37](#)
- counter\_subfun
  - Phylo counters, [37](#)
- COUNTER\_TEMPLATE
  - counters-meat.hpp, [296](#), [298](#), [299](#)
- COUNTER\_TEMPLATE\_ARGS
  - counters-meat.hpp, [296](#)
- counter\_transition
  - DEFMArray counters, [28](#)
- counter\_transition\_formula
  - DEFMArray counters, [29](#)
- counter\_ttriads
  - DEFMArray counters, [29](#)
- COUNTER\_TYPE
  - counters-meat.hpp, [297](#)
- Counters
  - Counters< Array\_Type, Data\_Type >, [116](#), [117](#)
- counters
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [178](#)
  - statscounter-meat.hpp, [373](#)
  - support-meat.hpp, [382](#)
- Counters< Array\_Type, Data\_Type >, [116](#)
  - ~Counters, [117](#)
  - add\_counter, [117](#), [118](#)
  - add\_hash, [118](#)
  - Counters, [116](#), [117](#)
  - gen\_hash, [118](#)
  - get\_descriptions, [118](#)
  - get\_names, [119](#)
  - operator=, [119](#)
  - operator[], [120](#)
  - size, [120](#)
- counters-meat.hpp
  - add\_dims, [303](#)
  - count\_fun, [298](#)
  - count\_fun\_, [303](#)
  - counter, [304](#)
  - counter\_, [304](#)
  - COUNTER\_TEMPLATE, [296](#), [298](#), [299](#)
  - COUNTER\_TEMPLATE\_ARGS, [296](#)
  - COUNTER\_TYPE, [297](#)
  - COUNTERS\_TEMPLATE, [297](#), [299–301](#)
  - COUNTERS\_TEMPLATE\_ARGS, [297](#)
  - COUNTERS\_TYPE, [297](#)
  - data, [301](#)
  - data\_, [304](#)
  - desc, [301](#)
  - desc\_, [304](#)
  - for, [301](#)
  - fun, [305](#)
  - fun\_, [305](#)
  - hasher, [301](#), [302](#)
  - hasher\_fun, [302](#)
  - hasher\_fun\_, [305](#)
  - i, [305](#)
  - if, [302](#)
  - init\_fun, [303](#)
  - init\_fun\_, [306](#)
  - j, [306](#)
  - name, [303](#)
  - name\_, [306](#)
  - noexcept, [306](#)
  - res, [306](#)
  - return, [307](#)
  - TMP\_HASHER\_CALL, [297](#)
- counters\_
  - model-meat.hpp, [349](#)
  - statscounter-meat.hpp, [373](#)
  - support-meat.hpp, [383](#)
- COUNTERS\_TEMPLATE
  - counters-meat.hpp, [297](#), [299–301](#)
- COUNTERS\_TEMPLATE\_ARGS
  - counters-meat.hpp, [297](#)
- COUNTERS\_TYPE
  - counters-meat.hpp, [297](#)
- Counting, [13](#)
- counts
  - DEFMRuleDynData, [136](#)
  - PhyloRuleDynData, [199](#)
- Counts\_type
  - typedefs.hpp, [388](#)
- covar\_sort
  - DEFMData, [130](#)
- covar\_used
  - DEFMData, [130](#)
- covariates
  - DEFMData, [130](#)
- CSS\_APPEND
  - network-css.hpp, [314](#)
- CSS\_CASE\_ELSE
  - network-css.hpp, [314](#)
- CSS\_CASE\_PERCEIVED
  - network-css.hpp, [314](#)
- CSS\_CASE\_TRUTH
  - network-css.hpp, [314](#)
- CSS\_CHECK\_SIZE
  - network-css.hpp, [314](#)
- CSS\_CHECK\_SIZE\_INIT
  - network-css.hpp, [315](#)
- CSS\_NET\_COUNTER\_LAMBDA\_INIT
  - network-css.hpp, [315](#)
- CSS\_PERCEIVED\_CELLS
  - network-css.hpp, [315](#)
- CSS\_SIZE

- network-css.hpp, 315
- CSS\_TRUE\_CELLS
  - network-css.hpp, 316
- cumprob
  - model-meat.hpp, 349
- current\_col
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 110
- current\_row
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, 110
- current\_stats
  - statscounter-meat.hpp, 373
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 227
- D
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayDense< Cell\_Type, Data\_Type >, 67, 68
  - Rule< Array\_Type, Data\_Type >, 210
- D\_ptr
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayDense< Cell\_Type, Data\_Type >, 68
- dat
  - Flock, 144
- data
  - barray-meat.hpp, 250
  - barraydense-meat.hpp, 274
  - Counter< Array\_Type, Data\_Type >, 114
  - counters-meat.hpp, 301
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 205
- data\_
  - counters-meat.hpp, 304
  - model-meat.hpp, 349
- Data\_Counter\_Type
  - model-meat.hpp, 349
- Data\_Rule\_Type
  - model-meat.hpp, 350
- DEFAULT\_DUPLICATION
  - phylo.hpp, 330
- default\_val
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayDense< Cell\_Type, Data\_Type >, 68
- DEFM, 121
  - ~DEFM, 122
  - DEFM, 122
  - get\_ID, 122
  - get\_m\_order, 122
  - get\_model, 123
  - get\_n\_covars, 123
  - get\_n\_obs, 123
  - get\_n\_rows, 123
  - get\_n\_y, 123
  - get\_X, 123
  - get\_X\_names, 124
  - get\_Y, 124
  - get\_Y\_names, 124
  - init, 124
  - likelihood, 124
  - logodds, 124
  - motif\_census, 125
  - set\_names, 125
  - simulate, 125
- defm-formula.hpp
  - defm\_motif\_parser, 307
- defm-meat.hpp
  - DEFM\_LOOP\_ARRAYS, 355
  - DEFM\_RANGES, 355
  - keygen\_defm, 356
- defm.hpp
  - DEFMArray, 311
  - UNI\_SUB, 311
- DEFM\_COUNTER
  - Phylo rules, 15
- DEFM\_COUNTER\_LAMBDA
  - Phylo rules, 15
- DEFM\_LOOP\_ARRAYS
  - defm-meat.hpp, 355
- defm\_motif\_parser
  - defm-formula.hpp, 307
- DEFM\_RANGES
  - defm-meat.hpp, 355
- DEFM\_RULE
  - Phylo rules, 15
- DEFM\_RULE\_LAMBDA
  - Phylo rules, 16
- DEFM\_RULEDYN\_LAMBDA
  - Phylo rules, 16
- DEFMArray
  - defm.hpp, 311
- DEFMArray counters, 19
  - counter\_absdiff, 21
  - counter\_ctriads, 22
  - counter\_degree, 22
  - counter\_density, 22
  - counter\_diff, 23
  - counter\_edges, 23
  - counter\_fixed\_effect, 23
  - counter\_idegree, 24
  - counter\_idegree15, 24
  - counter\_isolates, 24, 25
  - counter\_istar2, 25
  - counter\_logit\_intercept, 25
  - counter\_mutual, 25
  - counter\_nodecov, 26
  - counter\_nodeicov, 26
  - counter\_nodematch, 26
  - counter\_nodeocov, 26
  - counter\_odegree, 26, 27
  - counter\_odegree15, 27
  - counter\_ones, 27
  - counter\_ostar2, 28
  - counter\_transition, 28
  - counter\_transition\_formula, 29
  - counter\_ttriads, 29
  - NETWORK\_COUNTER, 29

- rules\_dont\_become\_zero, [29](#)
- rules\_markov\_fixed, [30](#)
- DEFMCounter
  - Phylo rules, [17](#)
- DEFMCounterData, [125](#)
  - ~DEFMCounterData, [126](#)
  - DEFMCounterData, [126](#)
  - idx, [127](#)
  - indices, [127](#)
  - is\_true, [127](#)
  - logical, [127](#)
  - num, [127](#)
  - numbers, [128](#)
- DEFMCounters
  - Phylo rules, [17](#)
- DEFMData, [128](#)
  - ~DEFMData, [130](#)
  - array, [130](#)
  - at, [130](#)
  - covar\_sort, [130](#)
  - covar\_used, [130](#)
  - covariates, [130](#)
  - DEFMData, [129](#)
  - obs\_start, [131](#)
  - X\_ncol, [131](#)
  - X\_nrow, [131](#)
- DEFMModel
  - Phylo rules, [17](#)
- DEFMRule
  - Phylo rules, [17](#)
- DEFMRuleData, [132](#)
  - DEFMRuleData, [132](#), [133](#)
  - idx, [133](#)
  - indices, [134](#)
  - init, [134](#)
  - is\_true, [133](#)
  - logical, [134](#)
  - num, [133](#)
  - numbers, [134](#)
- DEFMRuleDyn
  - Phylo rules, [17](#)
- DEFMRuleDynData, [135](#)
  - ~DEFMRuleDynData, [136](#)
  - counts, [136](#)
  - DEFMRuleDynData, [136](#)
- DEFMRules
  - Phylo rules, [17](#)
- DEFMRulesDyn
  - Phylo rules, [18](#)
- DEFMStatsCounter
  - Phylo rules, [18](#)
- DEFMSupport
  - Phylo rules, [18](#)
- delete\_counters
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [178](#)
  - Support< Array\_Type, Data\_Counter\_Type,
- Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [227](#)
- support-meat.hpp, [383](#)
- delete\_data
  - barray-meat.hpp, [250](#)
  - barraydense-meat.hpp, [274](#)
- delete\_data\_
  - barray-meat.hpp, [250](#)
  - barraydense-meat.hpp, [275](#)
- delete\_rengine
  - Geese, [160](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [179](#)
- delete\_rules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [179](#)
  - model-meat.hpp, [350](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [227](#)
  - support-meat.hpp, [383](#)
- delete\_rules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [179](#)
  - model-meat.hpp, [350](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [227](#)
  - support-meat.hpp, [383](#)
- delete\_support
  - Geese, [160](#)
- desc
  - Counter< Array\_Type, Data\_Type >, [115](#)
  - counters-meat.hpp, [301](#)
- desc\_
  - counters-meat.hpp, [304](#)
- directed
  - NetworkData, [187](#)
- DUPL\_DUPL
  - phylo.hpp, [330](#)
- DUPL\_EITH
  - phylo.hpp, [330](#)
- DUPL\_SPEC
  - phylo.hpp, [330](#)
- duplication
  - Node, [192](#)
  - NodeData, [195](#)
  - PhyloRuleDynData, [199](#)
- el
  - barraydense-meat.hpp, [275](#)
- el\_colsums
  - barraydense-meat.hpp, [275](#)
- el\_rowsums
  - barraydense-meat.hpp, [275](#)
- else

- barray-meat.hpp, 250
  - barraydense-meat.hpp, 275
  - model-meat.hpp, 350
  - support-meat.hpp, 383
- empty
  - PhyloCounterData, 196
- EmptyArray
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 205
  - statscounter-meat.hpp, 373
- end
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 83
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 85
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 87
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 90
  - BArrayVector< Cell\_Type, Data\_Type >, 97
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 101
  - PhyloCounterData, 197
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 203
  - Progress, 208
- Entries
  - Entries< Cell\_Type >, 137
- Entries< Cell\_Type >, 136
  - ~Entries, 137
  - Entries, 137
  - resize, 138
  - source, 138
  - target, 138
  - val, 138
- eval\_rules\_dyn
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 223
- EXISTS, 41
  - AS\_ONE, 41
  - AS\_ZERO, 41
  - BOTH, 42
  - NONE, 42
  - ONE, 42
  - TWO, 42
  - UNKNOWN, 42
- f\_
  - statscounter-meat.hpp, 373
  - support-meat.hpp, 384
- false
  - barray-meat.hpp, 250
  - barraydense-meat.hpp, 276
- first
  - barray-meat.hpp, 251
- first\_calc\_done
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 179
- Flock, 139
  - ~Flock, 140
  - add\_data, 140
  - colnames, 141
  - dat, 144
  - Flock, 140
  - get\_counters, 141
  - get\_model, 141
  - get\_stats\_support, 141
  - get\_stats\_target, 141
  - get\_support\_fun, 141
  - init, 142
  - initialized, 145
  - likelihood\_joint, 142
  - model, 145
  - nfunctions, 145
  - nfuncs, 142
  - nleaves, 142
  - nnodes, 143
  - nterms, 143
  - ntrees, 143
  - operator(), 143
  - parse\_polytomies, 144
  - print, 144
  - rengine, 145
  - set\_seed, 144
  - support\_size, 144
- flush\_data
  - BArray< Cell\_Type, Data\_Type >, 48
- for
  - barray-meat-operators.hpp, 235
  - barray-meat.hpp, 244
  - barraydense-meat.hpp, 269
  - counters-meat.hpp, 301
  - model-meat.hpp, 339
  - statscounter-meat.hpp, 370
  - support-meat.hpp, 377
- force\_new
  - model-meat.hpp, 350
- FreqTable
  - FreqTable< T >, 146
- FreqTable< T >, 145
  - ~FreqTable, 146
  - add, 147
  - as\_vector, 147
  - clear, 147
  - FreqTable, 146
  - get\_data, 147
  - get\_index, 147
  - make\_hash, 148
  - print, 148
  - reserve, 148
  - size, 148
- fun
  - counters-meat.hpp, 305
- fun\_
  - counters-meat.hpp, 305
  - model-meat.hpp, 351
- Geese, 149
  - ~Geese, 153
  - calc\_reduced\_sequence, 153

- calc\_sequence, 153
- colnames, 154
- delete\_rengine, 160
- delete\_support, 160
- Geese, 152, 153
- get\_annotated\_nodes, 154
- get\_counters, 154
- get\_model, 154
- get\_probabilities, 154
- get\_rengine, 154
- get\_states, 155
- get\_support\_fun, 155
- inherit\_support, 155
- init, 155
- init\_node, 155
- initialized, 160
- likelihood, 156
- likelihood\_exhaust, 156
- map\_to\_nodes, 161
- nannotations, 156
- nfunctions, 161
- nfuns, 156
- nleaves, 156
- nnodes, 157
- nodes, 161
- nterms, 157
- observed\_counts, 157
- operator=, 157
- parse\_polytomies, 157
- predict, 158
- predict\_backend, 158
- predict\_exhaust, 158
- predict\_exhaust\_backend, 158
- predict\_sim, 159
- print, 159
- print\_observed\_counts, 159
- pset\_loc, 161
- reduced\_sequence, 161
- sequence, 161
- set\_seed, 159
- simulate, 159
- support\_size, 160
- update\_annotations, 160
- geese-bones.hpp
  - INITIALIZED, 358
  - keygen\_full, 359
  - RULE\_FUNCTION, 359
  - vec\_diff, 359
  - vector\_caster, 359
- gen\_hash
  - Counters< Array\_Type, Data\_Type >, 118
- gen\_key
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 170
- get\_annotated\_nodes
  - Geese, 154
- get\_arrays2support
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 170
- get\_cell
  - BArray< Cell\_Type, Data\_Type >, 48
  - BArrayDense< Cell\_Type, Data\_Type >, 68
- get\_col\_vec
  - BArray< Cell\_Type, Data\_Type >, 49
  - BArrayDense< Cell\_Type, Data\_Type >, 68, 69
- get\_counters
  - Flock, 141
  - Geese, 154
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 170
  - PhyloCounterData, 197
  - StatsCounter< Array\_Type, Data\_Type >, 217
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 223
- get\_counts
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 223
- get\_current\_stats
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 223
- get\_data
  - BArrayDense< Cell\_Type, Data\_Type >, 69
  - FreqTable< T >, 147
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 203
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 224
- get\_data\_ptr
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 204
- get\_description
  - Counter< Array\_Type, Data\_Type >, 113
  - Rule< Array\_Type, Data\_Type >, 210
- get\_descriptions
  - Counters< Array\_Type, Data\_Type >, 118
  - Rules< Array\_Type, Data\_Type >, 213
  - StatsCounter< Array\_Type, Data\_Type >, 217
- get\_entries
  - BArray< Cell\_Type, Data\_Type >, 49
  - BArrayDense< Cell\_Type, Data\_Type >, 69
- get\_hasher
  - Counter< Array\_Type, Data\_Type >, 113
- get\_ID
  - DEFM, 122
- get\_index
  - FreqTable< T >, 147
- get\_last\_name
  - phylo.hpp, 335
- get\_m\_order
  - DEFM, 122
- get\_model

- DEFM, [123](#)
- Flock, [141](#)
- Geese, [154](#)
- get\_n\_covars
  - DEFM, [123](#)
- get\_n\_obs
  - DEFM, [123](#)
- get\_n\_rows
  - DEFM, [123](#)
- get\_n\_y
  - DEFM, [123](#)
- get\_name
  - Counter< Array\_Type, Data\_Type >, [113](#)
  - Rule< Array\_Type, Data\_Type >, [210](#)
- get\_names
  - Counters< Array\_Type, Data\_Type >, [119](#)
  - Rules< Array\_Type, Data\_Type >, [213](#)
  - StatsCounter< Array\_Type, Data\_Type >, [218](#)
- get\_norm\_const
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [170](#)
- get\_parent
  - Node, [190](#)
- get\_probabilities
  - Geese, [154](#)
- get\_pset
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [170](#)
- get\_pset\_arrays
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [171](#)
- get\_pset\_probs
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [171](#)
- get\_pset\_stats
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [171](#)
- get\_rengine
  - Geese, [154](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [171](#)
- get\_row\_vec
  - BArray< Cell\_Type, Data\_Type >, [49](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [69](#)
- get\_rules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [172](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [224](#)
- get\_rules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [172](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [224](#)
- get\_seq
  - Rules< Array\_Type, Data\_Type >, [213](#)
- get\_states
  - Geese, [155](#)
- get\_stats\_support
  - Flock, [141](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [172](#)
- get\_stats\_target
  - Flock, [141](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [172](#)
- get\_support\_fun
  - Flock, [141](#)
  - Geese, [155](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [172](#)
- get\_X
  - DEFM, [123](#)
- get\_X\_names
  - DEFM, [124](#)
- get\_Y
  - DEFM, [124](#)
- get\_Y\_names
  - DEFM, [124](#)
- hasher
  - counters-meat.hpp, [301](#), [302](#)
- hasher\_fun
  - Counter< Array\_Type, Data\_Type >, [115](#)
  - counters-meat.hpp, [302](#)
- hasher\_fun\_
  - counters-meat.hpp, [305](#)
- Hasher\_fun\_type
  - typedefs.hpp, [388](#)
- hashes
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [228](#)
  - support-meat.hpp, [384](#)
- hashes\_initialized
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [228](#)
- i
  - counters-meat.hpp, [305](#)
  - model-meat.hpp, [351](#)
- i1
  - barray-meat.hpp, [251](#)



- barraydense-meat.hpp, 276
- i\_matches
  - model-meat.hpp, 351
- id
  - Node, 192
- idx
  - DEFMCounterData, 127
  - DEFMRuleData, 133
- if
  - barray-meat.hpp, 244–247
  - barraydense-meat.hpp, 270
  - counters-meat.hpp, 302
  - model-meat.hpp, 339, 340
  - support-meat.hpp, 377, 378
- IF\_MATCHES
  - phylo.hpp, 330
- IF\_NOTMATCHES
  - phylo.hpp, 331
- include/barry/barray-bones.hpp, 231
- include/barry/barray-iterator.hpp, 231
- include/barry/barray-meat-operators.hpp, 232
- include/barry/barray-meat.hpp, 236
- include/barry/barraycell-bones.hpp, 254
- include/barry/barraycell-meat.hpp, 254
- include/barry/barraydense-bones.hpp, 255
- include/barry/barraydense-meat-operators.hpp, 255
- include/barry/barraydense-meat.hpp, 258
- include/barry/barraydensecell-bones.hpp, 279
- include/barry/barraydensecell-meat.hpp, 280
- include/barry/barraydensecol-bones.hpp, 280
- include/barry/barraydenserow-bones.hpp, 282
- include/barry/barrayrow-bones.hpp, 283
- include/barry/barrayrow-meat.hpp, 283
- include/barry/barrayvector-bones.hpp, 285
- include/barry/barrayvector-meat.hpp, 286
- include/barry/barry-configuration.hpp, 286
- include/barry/barry-debug.hpp, 288
- include/barry/barry-macros.hpp, 289
- include/barry/barry.hpp, 290
- include/barry/cell-bones.hpp, 293
- include/barry/cell-meat.hpp, 294
- include/barry/col-bones.hpp, 294
- include/barry/counters-bones.hpp, 294
- include/barry/counters-meat.hpp, 295
- include/barry/counters/defm-formula.hpp, 307
- include/barry/counters/defm.hpp, 309
- include/barry/counters/network-css.hpp, 312
- include/barry/counters/network.hpp, 320
- include/barry/counters/phylo.hpp, 327
- include/barry/freqtable.hpp, 335
- include/barry/model-bones.hpp, 336
- include/barry/model-meat.hpp, 336
- include/barry/models/defm.hpp, 312
- include/barry/models/defm/defm-bones.hpp, 354
- include/barry/models/defm/defm-meat.hpp, 355
- include/barry/models/geese.hpp, 356
- include/barry/models/geese/flock-bones.hpp, 357
- include/barry/models/geese/flock-meat.hpp, 357
- include/barry/models/geese/geese-bones.hpp, 358
- include/barry/models/geese/geese-meat-constructors.hpp, 360
- include/barry/models/geese/geese-meat-likelihood.hpp, 360
- include/barry/models/geese/geese-meat-likelihood\_exhaust.hpp, 361
- include/barry/models/geese/geese-meat-predict.hpp, 362
- include/barry/models/geese/geese-meat-predict\_exhaust.hpp, 362
- include/barry/models/geese/geese-meat-predict\_sim.hpp, 363
- include/barry/models/geese/geese-meat-simulate.hpp, 363
- include/barry/models/geese/geese-meat.hpp, 364
- include/barry/models/geese/geese-node-bones.hpp, 364
- include/barry/powerset-bones.hpp, 365
- include/barry/powerset-meat.hpp, 365
- include/barry/progress.hpp, 366
- include/barry/rules-bones.hpp, 367
- include/barry/rules-meat.hpp, 368
- include/barry/statscounter-bones.hpp, 368
- include/barry/statscounter-meat.hpp, 369
- include/barry/support-bones.hpp, 374
- include/barry/support-meat.hpp, 375
- include/barry/typedefs.hpp, 386
- indices
  - DEFMCounterData, 127
  - DEFMRuleData, 134
  - NetCounterData, 185
- inherit\_support
  - Geese, 155
- init
  - Counter< Array\_Type, Data\_Type >, 113
  - DEFM, 124
  - DEFMRuleData, 134
  - Flock, 142
  - Geese, 155
- init\_fun
  - Counter< Array\_Type, Data\_Type >, 115
  - counters-meat.hpp, 303
- init\_fun\_
  - counters-meat.hpp, 306
  - model-meat.hpp, 351
- init\_node
  - Geese, 155
- init\_support
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 204
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 224
- INITIALIZED
  - geese-bones.hpp, 358
- initialized
  - Flock, 145
  - Geese, 160

- insert\_cell
  - BArray< Cell\_Type, Data\_Type >, [50](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [70](#)
  - barraydense-meat.hpp, [270](#)
  - model-meat.hpp, [340](#)
  - support-meat.hpp, [378](#)
- is\_col
  - BArrayVector< Cell\_Type, Data\_Type >, [97](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [101](#)
- is\_dense
  - BArray< Cell\_Type, Data\_Type >, [50](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [70](#)
- IS\_DUPLICATION
  - phylo.hpp, [331](#)
- IS\_EITHER
  - phylo.hpp, [331](#)
- is\_empty
  - BArray< Cell\_Type, Data\_Type >, [50](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [70](#)
- is\_leaf
  - Node, [191](#)
- is\_row
  - BArrayVector< Cell\_Type, Data\_Type >, [97](#)
  - BArrayVector\_const< Cell\_Type, Data\_Type >, [101](#)
- IS\_SPECIATION
  - phylo.hpp, [331](#)
- is\_true
  - DEFMCounterData, [127](#)
  - DEFMRuleData, [133](#)
- iter
  - ConstBArrayRowIter< Cell\_Type, Data\_Type >, [110](#)
- j
  - barray-meat.hpp, [251](#)
  - barraydense-meat.hpp, [276](#)
  - counters-meat.hpp, [306](#)
  - model-meat.hpp, [351](#)
  - statscounter-meat.hpp, [374](#)
- j0
  - barray-meat.hpp, [251](#)
  - barraydense-meat.hpp, [276](#)
- j1
  - barray-meat.hpp, [251](#)
  - barraydense-meat.hpp, [276](#)
- k
  - model-meat.hpp, [352](#)
- key
  - model-meat.hpp, [352](#)
- keygen\_defm
  - defm-meat.hpp, [356](#)
- keygen\_full
  - geese-bones.hpp, [359](#)
- keys2support
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [179](#)
- lb
  - PhyloRuleDynData, [199](#)
- likelihood
  - DEFM, [124](#)
  - Geese, [156](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [173](#)
- likelihood\_
  - model-meat.hpp, [340](#)
- likelihood\_exhaust
  - Geese, [156](#)
- likelihood\_joint
  - Flock, [142](#)
- likelihood\_total
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [174](#)
- locator
  - model-meat.hpp, [352](#)
- logical
  - DEFMCounterData, [127](#)
  - DEFMRuleData, [134](#)
- logodds
  - DEFM, [124](#)
- M
  - barray-meat.hpp, [247](#), [251](#)
  - barraydense-meat.hpp, [271](#), [276](#)
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [205](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [228](#)
- M\_
  - barray-meat.hpp, [252](#)
  - barraydense-meat.hpp, [277](#)
- MAKE\_DEFM\_HASHER
  - Phylo rules, [16](#)
- MAKE\_DUPL\_VARS
  - phylo.hpp, [331](#)
- make\_hash
  - FreqTable< T >, [148](#)
- Map
  - barry-configuration.hpp, [287](#)
- map\_to\_nodes
  - Geese, [161](#)
- MapVec\_type
  - typedefs.hpp, [389](#)
- max\_num\_elements
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [228](#)
- Model

- Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
166, 167
- model
  - Flock, 145
- Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type,  
Data\_Rule\_Dyn\_Type >, 162
  - ~Model, 167
  - add\_array, 167
  - add\_counter, 168
  - add\_hasher, 168
  - add\_rule, 168
  - add\_rule\_dyn, 169
  - arrays2support, 178
  - colnames, 169
  - conditional\_prob, 169
  - counter\_fun, 178
  - counters, 178
  - delete\_counters, 178
  - delete\_rengine, 179
  - delete\_rules, 179
  - delete\_rules\_dyn, 179
  - first\_calc\_done, 179
  - gen\_key, 170
  - get\_arrays2support, 170
  - get\_counters, 170
  - get\_norm\_const, 170
  - get\_pset, 170
  - get\_pset\_arrays, 171
  - get\_pset\_probs, 171
  - get\_pset\_stats, 171
  - get\_rengine, 171
  - get\_rules, 172
  - get\_rules\_dyn, 172
  - get\_stats\_support, 172
  - get\_stats\_target, 172
  - get\_support\_fun, 172
  - keys2support, 179
  - likelihood, 173
  - likelihood\_total, 174
  - Model, 166, 167
  - normalizing\_constants, 180
  - nrules, 174
  - nrules\_dyn, 174
  - nterms, 174
  - operator=, 174
  - params\_last, 180
  - print, 175
  - print\_stats, 175
  - pset\_arrays, 180
  - pset\_probs, 180
  - pset\_stats, 181
  - rengine, 181
  - rules, 181
  - rules\_dyn, 181
  - sample, 175
  - set\_counters, 175
  - set\_rengine, 176
  - set\_rules, 176
  - set\_rules\_dyn, 176
  - set\_seed, 176
  - set\_transform\_model, 176
  - size, 177
  - size\_unique, 177
  - stats\_support, 182
  - stats\_support\_n\_arrays, 182
  - stats\_target, 182
  - store\_psets, 177
  - support\_fun, 182
  - support\_size, 177
  - transform\_model, 178
  - transform\_model\_fun, 183
  - transform\_model\_term\_names, 183
  - with\_pset, 183
- model-meat.hpp
  - a, 348
  - count\_fun\_, 348
  - counter, 349
  - counters\_, 349
  - cumprob, 349
  - data\_, 349
  - Data\_Counter\_Type, 349
  - Data\_Rule\_Type, 350
  - delete\_rules, 350
  - delete\_rules\_dyn, 350
  - else, 350
  - for, 339
  - force\_new, 350
  - fun\_, 351
  - i, 351
  - i\_matches, 351
  - if, 339, 340
  - init\_fun\_, 351
  - insert\_cell, 340
  - j, 351
  - k, 352
  - key, 352
  - likelihood\_, 340
  - locator, 352
  - MODEL\_TEMPLATE, 338, 340–346
  - MODEL\_TEMPLATE\_ARGS, 338
  - MODEL\_TYPE, 339
  - params, 352
  - probs, 352
  - pset\_arrays, 352
  - push\_back, 346, 347
  - r, 353
  - return, 347, 353
  - rule\_fun\_, 353
  - rules, 353
  - rules\_, 353
  - rules\_dyn, 354
  - set\_counters, 347
  - set\_rules, 347
  - set\_rules\_dyn, 347
  - size, 347

- stats, [354](#)
- stats\_support\_n\_arrays, [354](#)
- temp\_stats, [347](#)
- tmp\_counts, [348](#)
- update\_normalizing\_constant, [348](#)
- urand, [348](#)
- MODEL\_TEMPLATE
  - model-meat.hpp, [338](#), [340–346](#)
- MODEL\_TEMPLATE\_ARGS
  - model-meat.hpp, [338](#)
- MODEL\_TYPE
  - model-meat.hpp, [339](#)
- motif\_census
  - DEFM, [125](#)
- N
  - barray-meat.hpp, [252](#)
  - barraydense-meat.hpp, [277](#)
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [206](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [228](#)
- n\_counters
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [229](#)
- n\_free
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [206](#)
- n\_locked
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [206](#)
- name
  - Counter< Array\_Type, Data\_Type >, [115](#)
  - counters-meat.hpp, [303](#)
- name\_
  - counters-meat.hpp, [306](#)
- nannotations
  - Geese, [156](#)
- narray
  - Node, [192](#)
- NCells
  - barray-meat.hpp, [252](#)
- ncol
  - BArray< Cell\_Type, Data\_Type >, [51](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [70](#)
  - Phylo rules, [18](#)
- NET\_C\_DATA\_IDX
  - network.hpp, [324](#)
- NET\_C\_DATA\_NUM
  - network.hpp, [324](#)
- NetCounter
  - network.hpp, [325](#)
- NetCounterData, [184](#)
  - ~NetCounterData, [185](#)
  - indices, [185](#)
  - NetCounterData, [184](#)
  - numbers, [185](#)
- NetCounters
  - network.hpp, [325](#)
- NetModel
  - network.hpp, [326](#)
- NetRule
  - network.hpp, [326](#)
- NetRules
  - network.hpp, [326](#)
- NetStatsCounter
  - network.hpp, [326](#)
- NetSupport
  - network.hpp, [326](#)
- Network
  - network.hpp, [326](#)
- network-css.hpp
  - counter\_css\_census01, [316](#)
  - counter\_css\_census02, [316](#)
  - counter\_css\_census03, [316](#)
  - counter\_css\_census04, [317](#)
  - counter\_css\_census05, [317](#)
  - counter\_css\_census06, [317](#)
  - counter\_css\_census07, [317](#)
  - counter\_css\_census08, [318](#)
  - counter\_css\_census09, [318](#)
  - counter\_css\_census10, [318](#)
  - counter\_css\_completely\_false\_recip\_commiss, [318](#)
  - counter\_css\_completely\_false\_recip\_omiss, [319](#)
  - counter\_css\_mixed\_recip, [319](#)
  - counter\_css\_partially\_false\_recip\_commi, [319](#)
  - counter\_css\_partially\_false\_recip\_omiss, [320](#)
  - CSS\_APPEND, [314](#)
  - CSS\_CASE\_ELSE, [314](#)
  - CSS\_CASE\_PERCEIVED, [314](#)
  - CSS\_CASE\_TRUTH, [314](#)
  - CSS\_CHECK\_SIZE, [314](#)
  - CSS\_CHECK\_SIZE\_INIT, [315](#)
  - CSS\_NET\_COUNTER\_LAMBDA\_INIT, [315](#)
  - CSS\_PERCEIVED\_CELLS, [315](#)
  - CSS\_SIZE, [315](#)
  - CSS\_TRUE\_CELLS, [316](#)
- network.hpp
  - BARRY\_ZERO\_NETWORK, [323](#)
  - BARRY\_ZERO\_NETWORK\_DENSE, [323](#)
  - NET\_C\_DATA\_IDX, [324](#)
  - NET\_C\_DATA\_NUM, [324](#)
  - NetCounter, [325](#)
  - NetCounters, [325](#)
  - NetModel, [326](#)
  - NetRule, [326](#)
  - NetRules, [326](#)
  - NetStatsCounter, [326](#)
  - NetSupport, [326](#)
  - Network, [326](#)
  - NETWORK\_COUNTER, [324](#)
  - NETWORK\_COUNTER\_LAMBDA, [324](#)
  - NETWORK\_RULE, [324](#)
  - NETWORK\_RULE\_LAMBDA, [325](#)
  - NetworkDense, [327](#)
  - NETWORKDENSE\_COUNTER\_LAMBDA, [325](#)
  - rules\_zerodiag, [327](#)
- NETWORK\_COUNTER

- DEFMArray counters, 29
- network.hpp, 324
- NETWORK\_COUNTER\_LAMBDA
  - network.hpp, 324
- NETWORK\_RULE
  - network.hpp, 324
- NETWORK\_RULE\_LAMBDA
  - network.hpp, 325
- NetworkData, 185
  - ~NetworkData, 187
  - directed, 187
  - NetworkData, 186, 187
  - vertex\_attr, 187
- NetworkDense
  - network.hpp, 327
- NETWORKDENSE\_COUNTER\_LAMBDA
  - network.hpp, 325
- next
  - Progress, 208
- nfunctions
  - Flock, 145
  - Geese, 161
- nfuns
  - Flock, 142
  - Geese, 156
- nleaves
  - Flock, 142
  - Geese, 156
- nnodes
  - Flock, 143
  - Geese, 157
- nnozero
  - BArray< Cell\_Type, Data\_Type >, 51
  - BArrayDense< Cell\_Type, Data\_Type >, 71
- Node, 188
  - ~Node, 190
  - annotations, 191
  - array, 191
  - arrays, 191
  - duplication, 192
  - get\_parent, 190
  - id, 192
  - is\_leaf, 191
  - narray, 192
  - Node, 189, 190
  - noffspring, 191
  - offspring, 192
  - ord, 192
  - parent, 193
  - probability, 193
  - subtree\_prob, 193
  - visited, 193
- NodeData, 194
  - blengths, 194
  - duplication, 195
  - NodeData, 194
  - states, 195
- nodes
  - Geese, 161
- noexcept
  - counters-meat.hpp, 306
- noffspring
  - Node, 191
- NONE
  - CHECK, 40
  - EXISTS, 42
- normalizing\_constants
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 180
- nrow
  - BArray< Cell\_Type, Data\_Type >, 51
  - BArrayDense< Cell\_Type, Data\_Type >, 71
  - Phylo rules, 18
- nrules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 174
- nrules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 174
- nterms
  - Flock, 143
  - Geese, 157
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 174
- ntrees
  - Flock, 143
- num
  - DEFMCounterData, 127
  - DEFMRuleData, 133
- numbers
  - DEFMCounterData, 128
  - DEFMRuleData, 134
  - NetCounterData, 185
- obs\_start
  - DEFMData, 131
- observed\_counts
  - Geese, 157
- offspring
  - Node, 192
- ONE
  - CHECK, 40
  - EXISTS, 42
- operator BArrayRow< Cell\_Type, Data\_Type >
  - BArrayRow< Cell\_Type, Data\_Type >, 92
- operator BArrayRow\_const< Cell\_Type, Data\_Type >
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 94
- operator Cell\_Type
  - BArrayCell< Cell\_Type, Data\_Type >, 58
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 79
  - Cell< Cell\_Type >, 106
- operator std::vector< Cell\_Type >

- BArrayVector< Cell\_Type, Data\_Type >, 98
- BArrayVector\_const< Cell\_Type, Data\_Type >, 101
- operator!=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 94
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 101
  - Cell< Cell\_Type >, 106
- operator<
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 94
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 102
- operator<=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 95
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 102
- operator>
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 95
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 102
- operator>=
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 62
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 95
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 102
- operator\*=
  - BArray< Cell\_Type, Data\_Type >, 51
  - BArrayCell< Cell\_Type, Data\_Type >, 58
  - BArrayDense< Cell\_Type, Data\_Type >, 71
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 79
  - BArrayRow< Cell\_Type, Data\_Type >, 92
  - BArrayVector< Cell\_Type, Data\_Type >, 98
- operator()
  - BArray< Cell\_Type, Data\_Type >, 51
  - barray-meat-operators.hpp, 235
  - BArrayDense< Cell\_Type, Data\_Type >, 71
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 83
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 85
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 88
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 90
  - Flock, 143
  - Phylo rules, 18
  - PhyloCounterData, 197
  - Rule< Array\_Type, Data\_Type >, 211
  - Rules< Array\_Type, Data\_Type >, 214
  - vecHasher< T >, 229
- operator+=
  - BArray< Cell\_Type, Data\_Type >, 52
  - BArrayCell< Cell\_Type, Data\_Type >, 58
  - BArrayDense< Cell\_Type, Data\_Type >, 71, 72
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 79
  - BArrayRow< Cell\_Type, Data\_Type >, 92
- BArrayVector< Cell\_Type, Data\_Type >, 98
- operator=
  - BArray< Cell\_Type, Data\_Type >, 52
  - BArrayCell< Cell\_Type, Data\_Type >, 59
  - BArrayDense< Cell\_Type, Data\_Type >, 72
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 80
  - BArrayRow< Cell\_Type, Data\_Type >, 92
  - BArrayVector< Cell\_Type, Data\_Type >, 98
- operator/=
  - BArray< Cell\_Type, Data\_Type >, 53
  - BArrayCell< Cell\_Type, Data\_Type >, 59
  - BArrayDense< Cell\_Type, Data\_Type >, 72
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 80
  - BArrayRow< Cell\_Type, Data\_Type >, 93
  - BArrayVector< Cell\_Type, Data\_Type >, 98
- operator=
  - BArray< Cell\_Type, Data\_Type >, 53
  - BArrayCell< Cell\_Type, Data\_Type >, 59
  - BArrayDense< Cell\_Type, Data\_Type >, 73
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 80
  - BArrayRow< Cell\_Type, Data\_Type >, 93
  - BArrayVector< Cell\_Type, Data\_Type >, 99
  - Cell< Cell\_Type >, 106, 107
  - Counter< Array\_Type, Data\_Type >, 113, 114
  - Counters< Array\_Type, Data\_Type >, 119
  - Geese, 157
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 174
  - Rules< Array\_Type, Data\_Type >, 214
- operator==
  - BArray< Cell\_Type, Data\_Type >, 53
  - BArrayCell< Cell\_Type, Data\_Type >, 59
  - BArrayCell\_const< Cell\_Type, Data\_Type >, 61
  - BArrayDense< Cell\_Type, Data\_Type >, 73
  - BArrayDenseCell< Cell\_Type, Data\_Type >, 80
  - BArrayRow< Cell\_Type, Data\_Type >, 93
  - BArrayRow\_const< Cell\_Type, Data\_Type >, 95
  - BArrayVector< Cell\_Type, Data\_Type >, 99
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 102
  - Cell< Cell\_Type >, 107
- operator[]
  - Counters< Array\_Type, Data\_Type >, 120
  - PhyloCounterData, 197
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 204
- ord
  - Node, 192
- out\_of\_range
  - BArray< Cell\_Type, Data\_Type >, 53
  - BArrayDense< Cell\_Type, Data\_Type >, 73
- params
  - model-meat.hpp, 352
- params\_last
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 180
- parent

- Node, [193](#)
- parse\_polytomies
  - Flock, [144](#)
  - Geese, [157](#)
- Phylo counters, [30](#)
  - counter\_co\_opt, [32](#)
  - counter\_cogain, [32](#)
  - counter\_gains, [32](#)
  - counter\_gains\_from\_0, [32](#)
  - counter\_gains\_k\_offspring, [33](#)
  - counter\_genes\_changing, [33](#)
  - counter\_k\_genes\_changing, [33](#)
  - counter\_less\_than\_p\_prop\_genes\_changing, [33](#)
  - counter\_longest, [34](#)
  - counter\_loss, [34](#)
  - counter\_maxfun, [34](#)
  - counter\_neofun, [34](#)
  - counter\_neofun\_a2b, [35](#)
  - counter\_overall\_changes, [35](#)
  - counter\_overall\_gains, [35](#)
  - counter\_overall\_gains\_from\_0, [35](#)
  - counter\_overall\_loss, [36](#)
  - counter\_pairwise\_first\_gain, [36](#)
  - counter\_pairwise\_neofun\_singlefun, [36](#)
  - counter\_pairwise\_overall\_change, [36](#)
  - counter\_pairwise\_preserving, [37](#)
  - counter\_preserve\_pseudogene, [37](#)
  - counter\_prop\_genes\_changing, [37](#)
  - counter\_subfun, [37](#)
- Phylo rules, [14](#)
  - DEFM\_COUNTER, [15](#)
  - DEFM\_COUNTER\_LAMBDA, [15](#)
  - DEFM\_RULE, [15](#)
  - DEFM\_RULE\_LAMBDA, [16](#)
  - DEFM\_RULEDYN\_LAMBDA, [16](#)
  - DEFMCounter, [17](#)
  - DEFMCounters, [17](#)
  - DEFMModel, [17](#)
  - DEFMRule, [17](#)
  - DEFMRuleDyn, [17](#)
  - DEFMRules, [17](#)
  - DEFMRulesDyn, [18](#)
  - DEFMStatsCounter, [18](#)
  - DEFMSupport, [18](#)
  - MAKE\_DEFM\_HASHER, [16](#)
  - ncol, [18](#)
  - nrow, [18](#)
  - operator(), [18](#)
  - print, [19](#)
  - rule\_dyn\_limit\_changes, [19](#)
- phylo.hpp
  - DEFAULT\_DUPLICATION, [330](#)
  - DUPL\_DUPL, [330](#)
  - DUPL\_EITH, [330](#)
  - DUPL\_SPEC, [330](#)
  - get\_last\_name, [335](#)
  - IF\_MATCHES, [330](#)
  - IF\_NOTMATCHES, [331](#)
  - IS\_DUPLICATION, [331](#)
  - IS\_EITHER, [331](#)
  - IS\_SPECIATION, [331](#)
  - MAKE\_DUPL\_VARS, [331](#)
  - PHYLO\_CHECK\_MISSING, [332](#)
  - PHYLO\_COUNTER\_LAMBDA, [332](#)
  - PHYLO\_RULE\_DYN\_LAMBDA, [332](#)
  - PhyloArray, [333](#)
  - PhyloCounter, [333](#)
  - PhyloCounters, [333](#)
  - PhyloModel, [333](#)
  - PhyloPowerSet, [333](#)
  - PhyloRule, [333](#)
  - PhyloRuleData, [334](#)
  - PhyloRuleDyn, [334](#)
  - PhyloRules, [334](#)
  - PhyloRulesDyn, [334](#)
  - PhyloStatsCounter, [334](#)
  - PhyloSupport, [334](#)
  - PHYLO\_CHECK\_MISSING
    - phylo.hpp, [332](#)
  - PHYLO\_COUNTER\_LAMBDA
    - phylo.hpp, [332](#)
  - PHYLO\_RULE\_DYN\_LAMBDA
    - phylo.hpp, [332](#)
  - PhyloArray
    - phylo.hpp, [333](#)
  - PhyloCounter
    - phylo.hpp, [333](#)
  - PhyloCounterData, [195](#)
    - at, [196](#)
    - begin, [196](#)
    - empty, [196](#)
    - end, [197](#)
    - get\_counters, [197](#)
    - operator(), [197](#)
    - operator[], [197](#)
    - PhyloCounterData, [196](#)
    - push\_back, [197](#)
    - reserve, [197](#)
    - shrink\_to\_fit, [198](#)
    - size, [198](#)
  - PhyloCounters
    - phylo.hpp, [333](#)
  - PhyloModel
    - phylo.hpp, [333](#)
  - PhyloPowerSet
    - phylo.hpp, [333](#)
  - PhyloRule
    - phylo.hpp, [333](#)
  - PhyloRuleData
    - phylo.hpp, [334](#)
  - PhyloRuleDyn
    - phylo.hpp, [334](#)
  - PhyloRuleDynData, [198](#)
    - ~PhyloRuleDynData, [199](#)
    - counts, [199](#)
    - duplication, [199](#)



- lb, 199
- PhyloRuleDynData, 199
- pos, 199
- ub, 200
- PhyloRules
  - phylo.hpp, 334
- PhyloRulesDyn
  - phylo.hpp, 334
- PhyloStatsCounter
  - phylo.hpp, 334
- PhyloSupport
  - phylo.hpp, 334
- POS
  - barraydense-meat-operators.hpp, 256
  - barraydense-meat.hpp, 261
  - barraydensecell-bones.hpp, 279
  - barraydensecell-meat.hpp, 280
  - barraydensecol-bones.hpp, 281
  - barraydenserow-bones.hpp, 282
- pos
  - PhyloRuleDynData, 199
- POS\_N
  - barraydense-meat-operators.hpp, 257
  - barraydense-meat.hpp, 261
  - barraydensecol-bones.hpp, 281
  - barraydenserow-bones.hpp, 282
- PowerSet
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 202
- PowerSet< Array\_Type, Data\_Rule\_Type >, 200
  - ~PowerSet, 202
  - add\_rule, 202, 203
  - begin, 203
  - calc, 203
  - coordinates\_free, 205
  - coordinates\_locked, 205
  - data, 205
  - EmptyArray, 205
  - end, 203
  - get\_data, 203
  - get\_data\_ptr, 204
  - init\_support, 204
  - M, 205
  - N, 206
  - n\_free, 206
  - n\_locked, 206
  - operator[], 204
  - PowerSet, 202
  - reset, 204
  - rules, 206
  - rules\_deleted, 206
  - size, 204
- predict
  - Geese, 158
- predict\_backend
  - Geese, 158
- predict\_exhaust
  - Geese, 158
- predict\_exhaust\_backend
  - Geese, 158
- predict\_sim
  - Geese, 159
- print
  - BArray< Cell\_Type, Data\_Type >, 53
  - BArrayDense< Cell\_Type, Data\_Type >, 73
  - Flock, 144
  - FreqTable< T >, 148
  - Geese, 159
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 175
  - Phylo rules, 19
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 224
- print\_observed\_counts
  - Geese, 159
- print\_stats
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 175
- printf\_barry
  - barry-configuration.hpp, 287
- probability
  - Node, 193
- probs
  - model-meat.hpp, 352
- Progress, 207
  - ~Progress, 207
  - end, 208
  - next, 208
  - Progress, 207
- progress.hpp
  - BARRY\_PROGRESS\_BAR\_WIDTH, 366
- pset\_arrays
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 180
  - model-meat.hpp, 352
- pset\_loc
  - Geese, 161
- pset\_probs
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 180
- pset\_stats
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 181
- push\_back
  - model-meat.hpp, 346, 347
  - PhyloCounterData, 197
- r
  - model-meat.hpp, 353
- README.md, 391
- reduced\_sequence
  - Geese, 161



- engine
  - Flock, [145](#)
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [181](#)
- report
  - barray-meat.hpp, [252](#)
  - barraydense-meat.hpp, [277](#)
- res
  - counters-meat.hpp, [306](#)
- reserve
  - BArray< Cell\_Type, Data\_Type >, [54](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [73](#)
  - FreqTable< T >, [148](#)
  - PhyloCounterData, [197](#)
- reset
  - PowerSet< Array\_Type, Data\_Rule\_Type >, [204](#)
- reset\_array
  - StatsCounter< Array\_Type, Data\_Type >, [218](#)
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [225](#)
- resize
  - BArray< Cell\_Type, Data\_Type >, [54](#)
  - barray-meat.hpp, [247](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [74](#)
  - barraydense-meat.hpp, [271](#), [272](#)
  - Entries< Cell\_Type >, [138](#)
  - statscounter-meat.hpp, [370](#)
- return
  - barray-meat.hpp, [247](#), [252](#)
  - barraydense-meat.hpp, [277](#)
  - counters-meat.hpp, [307](#)
  - model-meat.hpp, [347](#), [353](#)
  - statscounter-meat.hpp, [374](#)
  - support-meat.hpp, [384](#)
- rhs
  - barray-meat-operators.hpp, [235](#)
- rm\_cell
  - BArray< Cell\_Type, Data\_Type >, [54](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [74](#)
  - barraydense-meat.hpp, [272](#)
  - support-meat.hpp, [378](#)
- ROW
  - barray-meat-operators.hpp, [233](#)
  - barray-meat.hpp, [239](#), [247](#), [248](#)
  - barraydense-meat-operators.hpp, [257](#)
  - barraydense-meat.hpp, [262](#)
- row
  - BArray< Cell\_Type, Data\_Type >, [54](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [74](#)
- row0
  - barray-meat.hpp, [253](#)
- Row\_type
  - typedefs.hpp, [389](#)
- rowsum
  - BArrayDense< Cell\_Type, Data\_Type >, [74](#)
- Rule
  - Rule< Array\_Type, Data\_Type >, [209](#)
  - Rule< Array\_Type, Data\_Type >, [208](#)
  - ~Rule, [209](#)
  - D, [210](#)
  - get\_description, [210](#)
  - get\_name, [210](#)
  - operator(), [211](#)
  - Rule, [209](#)
  - rule\_dyn\_limit\_changes
    - Phylo rules, [19](#)
  - rule\_fun\_
    - model-meat.hpp, [353](#)
  - rule\_fun\_default
    - rules-bones.hpp, [367](#)
  - Rule\_fun\_type
    - typedefs.hpp, [389](#)
  - RULE\_FUNCTION
    - barry.hpp, [293](#)
    - geese-bones.hpp, [359](#)
  - RULE\_LAMBDA
    - barry.hpp, [293](#)
  - Rules
    - Rules< Array\_Type, Data\_Type >, [212](#)
  - rules
    - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [181](#)
    - model-meat.hpp, [353](#)
    - PowerSet< Array\_Type, Data\_Rule\_Type >, [206](#)
    - support-meat.hpp, [384](#)
    - Rules< Array\_Type, Data\_Type >, [211](#)
    - ~Rules, [212](#)
    - add\_rule, [213](#)
    - get\_descriptions, [213](#)
    - get\_names, [213](#)
    - get\_seq, [213](#)
    - operator(), [214](#)
    - operator=, [214](#)
    - Rules, [212](#)
    - size, [214](#)
    - rules-bones.hpp
      - rule\_fun\_default, [367](#)
    - rules\_
      - model-meat.hpp, [353](#)
      - support-meat.hpp, [384](#)
    - rules\_deleted
      - PowerSet< Array\_Type, Data\_Rule\_Type >, [206](#)
    - rules\_dont\_become\_zero
      - DEFMArray counters, [29](#)
    - rules\_dyn
      - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [181](#)
      - model-meat.hpp, [354](#)
      - support-meat.hpp, [385](#)
    - rules\_markov\_fixed
      - DEFMArray counters, [30](#)
    - rules\_zerodiag

- network.hpp, 327
- sample
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 175
- search
  - barray-meat.hpp, 253
- sequence
  - Geese, 161
- set\_counters
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 175
  - model-meat.hpp, 347
  - StatsCounter< Array\_Type, Data\_Type >, 218
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 225
- set\_data
  - BArray< Cell\_Type, Data\_Type >, 54
  - BArrayDense< Cell\_Type, Data\_Type >, 74
- set\_hasher
  - Counter< Array\_Type, Data\_Type >, 114
- set\_names
  - DEFM, 125
- set\_engine
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 176
- set\_rules
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 176
  - model-meat.hpp, 347
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 225
- set\_rules\_dyn
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 176
  - model-meat.hpp, 347
  - Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 225
- set\_seed
  - Flock, 144
  - Geese, 159
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 176
- set\_transform\_model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 176
- shrink\_to\_fit
  - PhyloCounterData, 198
- simulate
  - DEFM, 125
  - Geese, 159
- size
  - BArrayDenseCol< Cell\_Type, Data\_Type >, 83
  - BArrayDenseCol\_const< Cell\_Type, Data\_Type >, 86
  - BArrayDenseRow< Cell\_Type, Data\_Type >, 88
  - BArrayDenseRow\_const< Cell\_Type, Data\_Type >, 90
  - BArrayVector< Cell\_Type, Data\_Type >, 99
  - BArrayVector\_const< Cell\_Type, Data\_Type >, 103
  - Counters< Array\_Type, Data\_Type >, 120
  - FreqTable< T >, 148
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 177
  - model-meat.hpp, 347
  - PhyloCounterData, 198
  - PowerSet< Array\_Type, Data\_Rule\_Type >, 204
  - Rules< Array\_Type, Data\_Type >, 214
  - StatsCounter< Array\_Type, Data\_Type >, 218
- size\_unique
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 177
- sort\_array
  - typedefs.hpp, 389
- source
  - barray-meat.hpp, 253
  - barraydense-meat.hpp, 277
  - Entries< Cell\_Type >, 138
- states
  - NodeData, 195
- Statistical Models, 13
- stats
  - model-meat.hpp, 354
- stats\_bank
  - support-meat.hpp, 385
- stats\_support
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 182
- stats\_support\_n\_arrays
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 182
  - model-meat.hpp, 354
- stats\_target
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, 182
- StatsCounter
  - StatsCounter< Array\_Type, Data\_Type >, 216
- StatsCounter< Array\_Type, Data\_Type >, 215
  - ~StatsCounter, 216
  - add\_counter, 217
  - count\_all, 217

- count\_current, 217
- count\_init, 217
- get\_counters, 217
- get\_descriptions, 217
- get\_names, 218
- reset\_array, 218
- set\_counters, 218
- size, 218
- StatsCounter, 216
- statscounter-meat.hpp
  - clear, 370
  - counter, 372
  - counter\_deleted, 372
  - counters, 373
  - counters\_, 373
  - current\_stats, 373
  - EmptyArray, 373
  - f\_, 373
  - for, 370
  - j, 374
  - resize, 370
  - return, 374
  - STATSCOUNTER\_TEMPLATE, 370–372
  - STATSCOUNTER\_TEMPLATE\_ARGS, 370
  - STATSCOUNTER\_TYPE, 370
- STATSCOUNTER\_TEMPLATE
  - statscounter-meat.hpp, 370–372
- STATSCOUNTER\_TEMPLATE\_ARGS
  - statscounter-meat.hpp, 370
- STATSCOUNTER\_TYPE
  - statscounter-meat.hpp, 370
- store\_psets
  - Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
177
- subtree\_prob
  - Node, 193
- Support
  - Support< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
221
- Support< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type,  
Data\_Rule\_Dyn\_Type >, 219
  - ~Support, 221
  - add\_counter, 222
  - add\_rule, 222
  - add\_rule\_dyn, 222
  - calc, 222
  - change\_stats, 226
  - coordiantes\_n\_free, 226
  - coordiantes\_n\_locked, 226
  - coordinates\_free, 226
  - coordinates\_locked, 227
  - current\_stats, 227
  - delete\_counters, 227
  - delete\_rules, 227
  - delete\_rules\_dyn, 227
  - eval\_rules\_dyn, 223
  - get\_counters, 223
  - get\_counts, 223
  - get\_current\_stats, 223
  - get\_data, 224
  - get\_rules, 224
  - get\_rules\_dyn, 224
  - hashes, 228
  - hashes\_initialized, 228
  - init\_support, 224
  - M, 228
  - max\_num\_elements, 228
  - N, 228
  - n\_counters, 229
  - print, 224
  - reset\_array, 225
  - set\_counters, 225
  - set\_rules, 225
  - set\_rules\_dyn, 225
  - Support, 221
- support-meat.hpp
  - array\_bank, 382
  - BARRY\_SUPPORT\_MEAT\_HPP, 376
  - calc\_backend\_dense, 377
  - calc\_backend\_sparse, 377
  - change\_stats\_different, 382
  - coord\_i, 382
  - coord\_j, 382
  - counters, 382
  - counters\_, 383
  - delete\_counters, 383
  - delete\_rules, 383
  - delete\_rules\_dyn, 383
  - else, 383
  - f\_, 384
  - for, 377
  - hashes, 384
  - if, 377, 378
  - insert\_cell, 378
  - return, 384
  - rm\_cell, 378
  - rules, 384
  - rules\_, 384
  - rules\_dyn, 385
  - stats\_bank, 385
  - SUPPORT\_TEMPLATE, 376, 379–382
  - SUPPORT\_TEMPLATE\_ARGS, 376
  - SUPPORT\_TYPE, 377
  - tmp\_chng, 385
- support\_fun
  - Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
182
- support\_size
  - Flock, 144
  - Geese, 160
  - Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
177

- SUPPORT\_TEMPLATE
  - support-meat.hpp, [376](#), [379–382](#)
- SUPPORT\_TEMPLATE\_ARGS
  - support-meat.hpp, [376](#)
- SUPPORT\_TYPE
  - support-meat.hpp, [377](#)
- swap\_cells
  - BArray< Cell\_Type, Data\_Type >, [55](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [75](#)
- swap\_cols
  - BArray< Cell\_Type, Data\_Type >, [55](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [75](#)
- swap\_rows
  - BArray< Cell\_Type, Data\_Type >, [55](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [75](#)
- target
  - barray-meat.hpp, [253](#)
  - barraydense-meat.hpp, [278](#)
  - Entries< Cell\_Type >, [138](#)
- temp\_stats
  - model-meat.hpp, [347](#)
- this
  - barray-meat-operators.hpp, [236](#)
- tmp\_chng
  - support-meat.hpp, [385](#)
- tmp\_counts
  - model-meat.hpp, [348](#)
- TMP\_HASHER\_CALL
  - counters-meat.hpp, [297](#)
- toggle\_cell
  - BArray< Cell\_Type, Data\_Type >, [55](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [75](#)
- toggle\_lock
  - BArray< Cell\_Type, Data\_Type >, [55](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [76](#)
- transform\_model
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [178](#)
- transform\_model\_fun
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [183](#)
- transform\_model\_term\_names
  - Model< Array\_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >, [183](#)
- transpose
  - BArray< Cell\_Type, Data\_Type >, [56](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [76](#)
- TWO
  - CHECK, [41](#)
  - EXISTS, [42](#)
- typedefs.hpp
  - Col\_type, [388](#)
  - Counter\_fun\_type, [388](#)
  - Counts\_type, [388](#)
  - Hasher\_fun\_type, [388](#)
  - MapVec\_type, [389](#)
  - Row\_type, [389](#)
  - Rule\_fun\_type, [389](#)
  - sort\_array, [389](#)
  - uint, [389](#)
  - vec\_equal, [390](#)
  - vec\_equal\_approx, [390](#)
  - vec\_inner\_prod, [390](#), [391](#)
- ub
  - PhyloRuleDynData, [200](#)
- uint
  - typedefs.hpp, [389](#)
- UNKNOWN
  - EXISTS, [42](#)
- UNI\_SUB
  - defm.hpp, [311](#)
- update\_annotations
  - Geese, [160](#)
- update\_normalizing\_constant
  - model-meat.hpp, [348](#)
- urand
  - model-meat.hpp, [348](#)
- v
  - barray-meat.hpp, [253](#)
  - barraydense-meat.hpp, [278](#)
- va\_end
  - barraydense-meat.hpp, [272](#)
- va\_start
  - barraydense-meat.hpp, [272](#)
- val
  - Entries< Cell\_Type >, [138](#)
- val0
  - barraydense-meat.hpp, [278](#)
- val1
  - barraydense-meat.hpp, [278](#)
- value
  - barray-meat.hpp, [253](#)
  - barraydense-meat.hpp, [278](#)
  - Cell< Cell\_Type >, [107](#)
- vec\_diff
  - geese-bones.hpp, [359](#)
- vec\_equal
  - typedefs.hpp, [390](#)
- vec\_equal\_approx
  - typedefs.hpp, [390](#)
- vec\_inner\_prod
  - typedefs.hpp, [390](#), [391](#)
- vecHasher< T >, [229](#)
  - operator(), [229](#)
- vector\_caster
  - geese-bones.hpp, [359](#)
- vertex\_attr
  - NetworkData, [187](#)
- visited
  - BArray< Cell\_Type, Data\_Type >, [57](#)
  - BArrayDense< Cell\_Type, Data\_Type >, [77](#)
  - Cell< Cell\_Type >, [107](#)

Node, [193](#)

vprintf  
barraydense-meat.hpp, [273](#)

with\_pset  
Model< Array\_Type, Data\_Counter\_Type,  
Data\_Rule\_Type, Data\_Rule\_Dyn\_Type >,  
[183](#)

X\_ncol  
DEFMData, [131](#)

X\_nrow  
DEFMData, [131](#)

ZERO\_CELL  
barraydense-meat.hpp, [262](#)  
barraydensecol-bones.hpp, [281](#)  
barraydenserow-bones.hpp, [283](#)

zero\_col  
BArray< Cell\_Type, Data\_Type >, [56](#)  
BArrayDense< Cell\_Type, Data\_Type >, [76](#)

zero\_row  
BArray< Cell\_Type, Data\_Type >, [56](#)  
BArrayDense< Cell\_Type, Data\_Type >, [76](#)