

barry: Your go-to motif accountant

0.0-1

Generated by Doxygen 1.9.1

1 Main Page	1
2 Module Index	5
2.1 Modules	5
3 Hierarchical Index	7
3.1 Class Hierarchy	7
4 Class Index	9
4.1 Class List	9
5 File Index	11
5.1 File List	11
6 Module Documentation	13
6.1 Counting	13
6.1.1 Detailed Description	15
6.1.2 Macro Definition Documentation	15
6.1.2.1 IF_MATCHES	15
6.1.2.2 IF_NOTMATCHES	15
6.1.2.3 IS_DUPLICATION	15
6.1.2.4 IS_EITHER	16
6.1.2.5 IS_SPECIATION	16
6.1.2.6 MAKE_DEFM_HASHER	16
6.1.2.7 MAKE_DUPL_VARS	16
6.1.2.8 PHYLO_CHECK_MISSING	17
6.1.2.9 PHYLO_COUNTER_LAMBDA	17
6.1.2.10 PHYLO_RULE_DYN_LAMBDA	17
6.1.3 Function Documentation	17
6.1.3.1 counter_co_opt()	18
6.1.3.2 counter_cogain()	18
6.1.3.3 counter_gains()	18
6.1.3.4 counter_gains_from_0()	19
6.1.3.5 counter_gains_k_offspring()	19
6.1.3.6 counter_genes_changing()	19
6.1.3.7 counter_k_genes_changing()	19
6.1.3.8 counter_less_than_p_prop_genes_changing()	20
6.1.3.9 counter_longest()	20
6.1.3.10 counter_loss()	20
6.1.3.11 counter_maxfuncs()	20
6.1.3.12 counter_neofun()	21
6.1.3.13 counter_neofun_a2b()	21
6.1.3.14 counter_overall_changes()	21
6.1.3.15 counter_overall_gains()	21

6.1.3.16 counter_overall_gains_from_0()	22
6.1.3.17 counter_overall_loss()	22
6.1.3.18 counter_pairwise_first_gain()	22
6.1.3.19 counter_pairwise_neofun_singlefun()	22
6.1.3.20 counter_pairwise_overall_change()	23
6.1.3.21 counter_pairwise_preserving()	23
6.1.3.22 counter_preserve_pseudogene()	23
6.1.3.23 counter_prop_genes_changing()	23
6.1.3.24 counter_subfun()	24
6.1.3.25 get_last_name()	24
6.2 Statistical Models	24
6.2.1 Detailed Description	24
6.3 Network counters	24
6.3.1 Detailed Description	26
6.3.2 Function Documentation	26
6.3.2.1 counter_absdiff()	27
6.3.2.2 counter_ctriads() [1/2]	27
6.3.2.3 counter_ctriads() [2/2]	27
6.3.2.4 counter_degree()	27
6.3.2.5 counter_density()	28
6.3.2.6 counter_diff()	28
6.3.2.7 counter_edges()	28
6.3.2.8 counter_fixed_effect()	28
6.3.2.9 counter_iddegree() [1/2]	29
6.3.2.10 counter_iddegree() [2/2]	29
6.3.2.11 counter_iddegree15() [1/2]	29
6.3.2.12 counter_iddegree15() [2/2]	29
6.3.2.13 counter_isolates() [1/2]	30
6.3.2.14 counter_isolates() [2/2]	30
6.3.2.15 counter_istar2() [1/2]	30
6.3.2.16 counter_istar2() [2/2]	30
6.3.2.17 counter_logit_intercept()	30
6.3.2.18 counter_mutual()	31
6.3.2.19 counter_nodecov()	31
6.3.2.20 counter_nodeicov()	31
6.3.2.21 counter_nodematch()	31
6.3.2.22 counter_nodeocov()	31
6.3.2.23 counter_odegree() [1/2]	32
6.3.2.24 counter_odegree() [2/2]	32
6.3.2.25 counter_odegree15() [1/2]	32
6.3.2.26 counter_odegree15() [2/2]	32
6.3.2.27 counter_ones()	32

6.3.2.28 counter_ostar2() [1/2]	33
6.3.2.29 counter_ostar2() [2/2]	33
6.3.2.30 counter_transition()	33
6.3.2.31 counter_transition_formula()	34
6.3.2.32 counter_ttriads() [1/2]	34
6.3.2.33 counter_ttriads() [2/2]	34
6.3.2.34 NETWORK_COUNTER()	34
6.3.2.35 rules_dont_become_zero()	35
6.3.2.36 rules_markov_fixed()	35
6.4 Phylo rules	35
6.4.1 Detailed Description	37
6.4.2 Typedef Documentation	37
6.4.2.1 DEFMCounter	37
6.4.2.2 DEFMCounters	37
6.4.2.3 DEFMModel	38
6.4.2.4 DEFMRule	38
6.4.2.5 DEFMRuleDyn	38
6.4.2.6 DEFMRules	38
6.4.2.7 DEFMRulesDyn	38
6.4.2.8 DEFMStatsCounter	38
6.4.2.9 DEFMSupport	39
6.4.3 Function Documentation	39
6.4.3.1 at()	39
6.4.3.2 DEFMCounterData() [1/2]	39
6.4.3.3 DEFMCounterData() [2/2]	39
6.4.3.4 DEFMData() [1/2]	39
6.4.3.5 DEFMData() [2/2]	39
6.4.3.6 DEFMRuleData() [1/3]	40
6.4.3.7 DEFMRuleData() [2/3]	40
6.4.3.8 DEFMRuleData() [3/3]	40
6.4.3.9 DEFMRuleDynData()	40
6.4.3.10 idx() [1/2]	41
6.4.3.11 idx() [2/2]	41
6.4.3.12 is_true() [1/2]	41
6.4.3.13 is_true() [2/2]	41
6.4.3.14 ncol()	41
6.4.3.15 nrow()	41
6.4.3.16 num() [1/2]	42
6.4.3.17 num() [2/2]	42
6.4.3.18 operator()()	42
6.4.3.19 print()	42
6.4.3.20 rule_dyn_limit_changes()	43

6.4.3.21 ~DEFMCounterData()	43
6.4.3.22 ~DEFMData()	43
6.4.3.23 ~DEFMRuleDynData()	43
6.4.4 Variable Documentation	44
6.4.4.1 array	44
6.4.4.2 counts	44
6.4.4.3 covar_sort	44
6.4.4.4 covar_used	44
6.4.4.5 covariates	44
6.4.4.6 indices [1/2]	45
6.4.4.7 indices [2/2]	45
6.4.4.8 init	45
6.4.4.9 is_motif	45
6.4.4.10 logical [1/2]	45
6.4.4.11 logical [2/2]	45
6.4.4.12 numbers [1/2]	46
6.4.4.13 numbers [2/2]	46
6.4.4.14 obs_start	46
6.4.4.15 X_ncol	46
6.4.4.16 X_nrow	46
6.5 Phylo counters	47
6.5.1 Detailed Description	48
6.5.2 Function Documentation	48
6.5.2.1 counter_co_opt()	48
6.5.2.2 counter_cogain()	49
6.5.2.3 counter_gains()	49
6.5.2.4 counter_gains_from_0()	49
6.5.2.5 counter_gains_k_offspring()	50
6.5.2.6 counter_genes_changing()	50
6.5.2.7 counter_k_genes_changing()	50
6.5.2.8 counter_less_than_p_prop_genes_changing()	50
6.5.2.9 counter_longest()	51
6.5.2.10 counter_loss()	51
6.5.2.11 counter_maxfuns()	51
6.5.2.12 counter_neofun()	51
6.5.2.13 counter_neofun_a2b()	52
6.5.2.14 counter_overall_changes()	52
6.5.2.15 counter_overall_gains()	52
6.5.2.16 counter_overall_gains_from_0()	52
6.5.2.17 counter_overall_loss()	53
6.5.2.18 counter_pairwise_first_gain()	53
6.5.2.19 counter_pairwise_neofun_singlefun()	53

6.5.2.20 counter_pairwise_overall_change()	53
6.5.2.21 counter_pairwise_preserving()	54
6.5.2.22 counter_preserve_pseudogene()	54
6.5.2.23 counter_prop_genes_changing()	54
6.5.2.24 counter_subfun()	54
7 Namespace Documentation	55
7.1 barry Namespace Reference	55
7.1.1 Detailed Description	55
7.2 barry::counters Namespace Reference	55
7.2.1 Detailed Description	55
7.3 barry::counters::network Namespace Reference	56
7.4 CHECK Namespace Reference	56
7.4.1 Detailed Description	56
7.4.2 Variable Documentation	56
7.4.2.1 BOTH	56
7.4.2.2 NONE	56
7.4.2.3 ONE	56
7.4.2.4 TWO	57
7.5 defm Namespace Reference	57
7.6 EXISTS Namespace Reference	57
7.6.1 Detailed Description	57
7.6.2 Variable Documentation	57
7.6.2.1 AS_ONE	57
7.6.2.2 AS_ZERO	57
7.6.2.3 BOTH	58
7.6.2.4 NONE	58
7.6.2.5 ONE	58
7.6.2.6 TWO	58
7.6.2.7 UNKNOWN	58
7.7 geese Namespace Reference	58
8 Class Documentation	59
8.1 BArray< Cell_Type, Data_Type > Class Template Reference	59
8.1.1 Detailed Description	61
8.1.2 Constructor & Destructor Documentation	62
8.1.2.1 BArray() [1/6]	62
8.1.2.2 BArray() [2/6]	62
8.1.2.3 BArray() [3/6]	62
8.1.2.4 BArray() [4/6]	63
8.1.2.5 BArray() [5/6]	63
8.1.2.6 BArray() [6/6]	63
8.1.2.7 ~BArray()	63

8.1.3 Member Function Documentation	63
8.1.3.1 clear()	63
8.1.3.2 col()	64
8.1.3.3 D() [1/2]	64
8.1.3.4 D() [2/2]	64
8.1.3.5 D_ptr() [1/2]	64
8.1.3.6 D_ptr() [2/2]	64
8.1.3.7 default_val()	64
8.1.3.8 flush_data()	64
8.1.3.9 get_cell()	65
8.1.3.10 get_col_vec() [1/2]	65
8.1.3.11 get_col_vec() [2/2]	65
8.1.3.12 get_entries()	65
8.1.3.13 get_row_vec() [1/2]	65
8.1.3.14 get_row_vec() [2/2]	66
8.1.3.15 insert_cell() [1/3]	66
8.1.3.16 insert_cell() [2/3]	66
8.1.3.17 insert_cell() [3/3]	66
8.1.3.18 is_dense()	66
8.1.3.19 is_empty()	67
8.1.3.20 ncol()	67
8.1.3.21 nnozero()	67
8.1.3.22 nrow()	67
8.1.3.23 operator>() [1/2]	67
8.1.3.24 operator>() [2/2]	67
8.1.3.25 operator*=()	68
8.1.3.26 operator+=() [1/3]	68
8.1.3.27 operator+=() [2/3]	68
8.1.3.28 operator+=() [3/3]	68
8.1.3.29 operator-=() [1/3]	68
8.1.3.30 operator-=() [2/3]	68
8.1.3.31 operator-=() [3/3]	69
8.1.3.32 operator/=()	69
8.1.3.33 operator=() [1/2]	69
8.1.3.34 operator=() [2/2]	69
8.1.3.35 operator==()	69
8.1.3.36 out_of_range()	69
8.1.3.37 print()	70
8.1.3.38 print_n()	70
8.1.3.39 reserve()	70
8.1.3.40 resize()	70
8.1.3.41 rm_cell()	70

8.1.3.42 row()	71
8.1.3.43 set_data()	71
8.1.3.44 swap_cells()	71
8.1.3.45 swap_cols()	71
8.1.3.46 swap_rows()	72
8.1.3.47 toggle_cell()	72
8.1.3.48 toggle_lock()	72
8.1.3.49 transpose()	72
8.1.3.50 zero_col()	72
8.1.3.51 zero_row()	73
8.1.4 Friends And Related Function Documentation	73
8.1.4.1 BArrayCell< Cell_Type, Data_Type >	73
8.1.4.2 BArrayCell_const< Cell_Type, Data_Type >	73
8.1.5 Member Data Documentation	73
8.1.5.1 visited	73
8.2 BArrayCell< Cell_Type, Data_Type > Class Template Reference	74
8.2.1 Detailed Description	74
8.2.2 Constructor & Destructor Documentation	74
8.2.2.1 BArrayCell()	74
8.2.2.2 ~BArrayCell()	74
8.2.3 Member Function Documentation	75
8.2.3.1 operator Cell_Type()	75
8.2.3.2 operator*=()	75
8.2.3.3 operator+=()	75
8.2.3.4 operator-=()	75
8.2.3.5 operator/=()	75
8.2.3.6 operator=()	76
8.2.3.7 operator==()	76
8.3 BArrayCell_const< Cell_Type, Data_Type > Class Template Reference	76
8.3.1 Detailed Description	76
8.3.2 Constructor & Destructor Documentation	77
8.3.2.1 BArrayCell_const()	77
8.3.2.2 ~BArrayCell_const()	77
8.3.3 Member Function Documentation	77
8.3.3.1 operator Cell_Type()	77
8.3.3.2 operator!=()	77
8.3.3.3 operator<()	78
8.3.3.4 operator<=()	78
8.3.3.5 operator==()	78
8.3.3.6 operator>()	78
8.3.3.7 operator>=()	78
8.4 BArrayDense< Cell_Type, Data_Type > Class Template Reference	79

8.4.1 Detailed Description	81
8.4.2 Constructor & Destructor Documentation	82
8.4.2.1 BArrayDense() [1/6]	82
8.4.2.2 BArrayDense() [2/6]	82
8.4.2.3 BArrayDense() [3/6]	82
8.4.2.4 BArrayDense() [4/6]	83
8.4.2.5 BArrayDense() [5/6]	83
8.4.2.6 BArrayDense() [6/6]	83
8.4.2.7 ~BArrayDense()	83
8.4.3 Member Function Documentation	83
8.4.3.1 clear()	84
8.4.3.2 col() [1/2]	84
8.4.3.3 col() [2/2]	84
8.4.3.4 colsum()	84
8.4.3.5 D() [1/2]	84
8.4.3.6 D() [2/2]	85
8.4.3.7 D_ptr() [1/2]	85
8.4.3.8 D_ptr() [2/2]	85
8.4.3.9 default_val()	85
8.4.3.10 get_cell()	85
8.4.3.11 get_col_vec() [1/2]	86
8.4.3.12 get_col_vec() [2/2]	86
8.4.3.13 get_data()	86
8.4.3.14 get_entries()	86
8.4.3.15 get_row_vec() [1/2]	87
8.4.3.16 get_row_vec() [2/2]	87
8.4.3.17 insert_cell() [1/2]	87
8.4.3.18 insert_cell() [2/2]	87
8.4.3.19 is_dense()	88
8.4.3.20 is_empty()	88
8.4.3.21 ncol()	88
8.4.3.22 nnozero()	88
8.4.3.23 nrow()	88
8.4.3.24 operator>() [1/2]	89
8.4.3.25 operator>() [2/2]	89
8.4.3.26 operator*=()	89
8.4.3.27 operator+=() [1/3]	89
8.4.3.28 operator+=() [2/3]	89
8.4.3.29 operator+=() [3/3]	90
8.4.3.30 operator-=() [1/3]	90
8.4.3.31 operator-=() [2/3]	90
8.4.3.32 operator-=() [3/3]	90

8.4.3.33 operator/=()	90
8.4.3.34 operator=() [1/2]	91
8.4.3.35 operator=() [2/2]	91
8.4.3.36 operator==()	91
8.4.3.37 out_of_range()	91
8.4.3.38 print()	91
8.4.3.39 reserve()	92
8.4.3.40 resize()	92
8.4.3.41 rm_cell()	92
8.4.3.42 row() [1/2]	92
8.4.3.43 row() [2/2]	92
8.4.3.44 rowsum()	93
8.4.3.45 set_data()	93
8.4.3.46 swap_cells()	93
8.4.3.47 swap_cols()	93
8.4.3.48 swap_rows()	94
8.4.3.49 toggle_cell()	94
8.4.3.50 toggle_lock()	94
8.4.3.51 transpose()	94
8.4.3.52 zero_col()	94
8.4.3.53 zero_row()	95
8.4.4 Friends And Related Function Documentation	95
8.4.4.1 BArrayDenseCell< Cell_Type, Data_Type >	95
8.4.4.2 BArrayDenseCol< Cell_Type, Data_Type >	95
8.4.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >	95
8.4.4.4 BArrayDenseRow< Cell_Type, Data_Type >	95
8.4.4.5 BArrayDenseRow_const< Cell_Type, Data_Type >	96
8.4.5 Member Data Documentation	96
8.4.5.1 visited	96
8.5 BArrayDenseCell< Cell_Type, Data_Type > Class Template Reference	96
8.5.1 Detailed Description	97
8.5.2 Constructor & Destructor Documentation	97
8.5.2.1 BArrayDenseCell()	97
8.5.2.2 ~BArrayDenseCell()	97
8.5.3 Member Function Documentation	97
8.5.3.1 operator Cell_Type()	97
8.5.3.2 operator*=()	98
8.5.3.3 operator+=()	98
8.5.3.4 operator-=()	98
8.5.3.5 operator/=()	98
8.5.3.6 operator=() [1/2]	98
8.5.3.7 operator=() [2/2]	99

8.5.3.8 operator==()	99
8.5.4 Friends And Related Function Documentation	99
8.5.4.1 BArrayDense< Cell_Type, Data_Type >	99
8.5.4.2 BArrayDenseCol< Cell_Type, Data_Type >	99
8.5.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >	99
8.6 BArrayDenseCell_const< Cell_Type, Data_Type > Class Template Reference	100
8.6.1 Detailed Description	100
8.7 BArrayDenseCol< Cell_Type, Data_Type > Class Template Reference	100
8.7.1 Detailed Description	100
8.7.2 Constructor & Destructor Documentation	100
8.7.2.1 BArrayDenseCol()	101
8.7.3 Member Function Documentation	101
8.7.3.1 begin()	101
8.7.3.2 end()	101
8.7.3.3 operator()()	101
8.7.3.4 size()	101
8.7.4 Friends And Related Function Documentation	102
8.7.4.1 BArrayDense< Cell_Type, Data_Type >	102
8.7.4.2 BArrayDenseCell< Cell_Type, Data_Type >	102
8.7.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >	102
8.8 BArrayDenseCol_const< Cell_Type, Data_Type > Class Template Reference	102
8.8.1 Detailed Description	103
8.8.2 Constructor & Destructor Documentation	103
8.8.2.1 BArrayDenseCol_const()	103
8.8.3 Member Function Documentation	103
8.8.3.1 begin()	103
8.8.3.2 end()	103
8.8.3.3 operator()()	104
8.8.3.4 size()	104
8.8.4 Friends And Related Function Documentation	104
8.8.4.1 BArrayDenseCell< Cell_Type, Data_Type >	104
8.8.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	104
8.9 BArrayDenseRow< Cell_Type, Data_Type > Class Template Reference	104
8.9.1 Detailed Description	105
8.9.2 Constructor & Destructor Documentation	105
8.9.2.1 BArrayDenseRow()	105
8.9.3 Member Function Documentation	105
8.9.3.1 begin()	105
8.9.3.2 end()	106
8.9.3.3 operator()()	106
8.9.3.4 size()	106
8.9.4 Friends And Related Function Documentation	106

8.9.4.1 BArrayDense< Cell_Type, Data_Type >	106
8.9.4.2 BArrayDenseCell< Cell_Type, Data_Type >	106
8.9.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >	107
8.10 BArrayDenseRow_const< Cell_Type, Data_Type > Class Template Reference	107
8.10.1 Detailed Description	107
8.10.2 Constructor & Destructor Documentation	107
8.10.2.1 BArrayDenseRow_const()	108
8.10.3 Member Function Documentation	108
8.10.3.1 begin()	108
8.10.3.2 end()	108
8.10.3.3 operator>()	108
8.10.3.4 size()	108
8.10.4 Friends And Related Function Documentation	109
8.10.4.1 BArrayDenseCell< Cell_Type, Data_Type >	109
8.10.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >	109
8.11 BArrayRow< Cell_Type, Data_Type > Class Template Reference	109
8.11.1 Detailed Description	109
8.11.2 Constructor & Destructor Documentation	110
8.11.2.1 BArrayRow()	110
8.11.2.2 ~BArrayRow()	110
8.11.3 Member Function Documentation	110
8.11.3.1 operator BArrayRow< Cell_Type, Data_Type >()	110
8.11.3.2 operator*=()	110
8.11.3.3 operator+=()	110
8.11.3.4 operator-=()	111
8.11.3.5 operator/=()	111
8.11.3.6 operator=()	111
8.11.3.7 operator==()	111
8.12 BArrayRow_const< Cell_Type, Data_Type > Class Template Reference	111
8.12.1 Detailed Description	112
8.12.2 Constructor & Destructor Documentation	112
8.12.2.1 BArrayRow_const()	112
8.12.2.2 ~BArrayRow_const()	112
8.12.3 Member Function Documentation	112
8.12.3.1 operator BArrayRow_const< Cell_Type, Data_Type >()	112
8.12.3.2 operator"!=()	112
8.12.3.3 operator<()	113
8.12.3.4 operator<=()	113
8.12.3.5 operator==()	113
8.12.3.6 operator>()	113
8.12.3.7 operator>=()	113
8.13 BArrayVector< Cell_Type, Data_Type > Class Template Reference	113

8.13.1 Detailed Description	114
8.13.2 Constructor & Destructor Documentation	114
8.13.2.1 BArrayVector()	114
8.13.2.2 ~BArrayVector()	115
8.13.3 Member Function Documentation	115
8.13.3.1 begin()	115
8.13.3.2 end()	115
8.13.3.3 is_col()	115
8.13.3.4 is_row()	116
8.13.3.5 operator std::vector< Cell_Type >()	116
8.13.3.6 operator*=()	116
8.13.3.7 operator+=()	116
8.13.3.8 operator-=()	116
8.13.3.9 operator/=()	117
8.13.3.10 operator=()	117
8.13.3.11 operator==()	117
8.13.3.12 size()	117
8.14 BArrayVector_const< Cell_Type, Data_Type > Class Template Reference	117
8.14.1 Detailed Description	118
8.14.2 Constructor & Destructor Documentation	118
8.14.2.1 BArrayVector_const()	118
8.14.2.2 ~BArrayVector_const()	118
8.14.3 Member Function Documentation	119
8.14.3.1 begin()	119
8.14.3.2 end()	119
8.14.3.3 is_col()	119
8.14.3.4 is_row()	119
8.14.3.5 operator std::vector< Cell_Type >()	119
8.14.3.6 operator"!=()	120
8.14.3.7 operator<()	120
8.14.3.8 operator<=()	120
8.14.3.9 operator==()	120
8.14.3.10 operator>()	120
8.14.3.11 operator>=()	121
8.14.3.12 size()	121
8.15 Cell< Cell_Type > Class Template Reference	121
8.15.1 Detailed Description	122
8.15.2 Constructor & Destructor Documentation	122
8.15.2.1 Cell() [1/7]	122
8.15.2.2 Cell() [2/7]	122
8.15.2.3 ~Cell()	122
8.15.2.4 Cell() [3/7]	123

8.15.2.5 Cell() [4/7]	123
8.15.2.6 Cell() [5/7]	123
8.15.2.7 Cell() [6/7]	123
8.15.2.8 Cell() [7/7]	123
8.15.3 Member Function Documentation	123
8.15.3.1 add() [1/4]	124
8.15.3.2 add() [2/4]	124
8.15.3.3 add() [3/4]	124
8.15.3.4 add() [4/4]	124
8.15.3.5 operator Cell_Type()	124
8.15.3.6 operator!=()	124
8.15.3.7 operator=() [1/2]	125
8.15.3.8 operator=() [2/2]	125
8.15.3.9 operator==()	125
8.15.4 Member Data Documentation	125
8.15.4.1 active	125
8.15.4.2 value	125
8.15.4.3 visited	126
8.16 Cell_const< Cell_Type > Class Template Reference	126
8.16.1 Detailed Description	126
8.17 ConstBArrayRowIter< Cell_Type, Data_Type > Class Template Reference	126
8.17.1 Detailed Description	127
8.17.2 Constructor & Destructor Documentation	127
8.17.2.1 ConstBArrayRowIter()	127
8.17.2.2 ~ConstBArrayRowIter()	127
8.17.3 Member Data Documentation	127
8.17.3.1 Array	128
8.17.3.2 current_col	128
8.17.3.3 current_row	128
8.17.3.4 iter	128
8.18 Counter< Array_Type, Data_Type > Class Template Reference	128
8.18.1 Detailed Description	129
8.18.2 Constructor & Destructor Documentation	130
8.18.2.1 Counter() [1/4]	130
8.18.2.2 Counter() [2/4]	130
8.18.2.3 Counter() [3/4]	130
8.18.2.4 Counter() [4/4]	130
8.18.2.5 ~Counter()	131
8.18.3 Member Function Documentation	131
8.18.3.1 count()	131
8.18.3.2 get_description()	131
8.18.3.3 get_hasher()	131

8.18.3.4 get_name()	131
8.18.3.5 init()	131
8.18.3.6 operator=() [1/2]	132
8.18.3.7 operator=() [2/2]	132
8.18.3.8 set_hasher()	132
8.18.4 Member Data Documentation	132
8.18.4.1 count_fun	132
8.18.4.2 data	133
8.18.4.3 desc	133
8.18.4.4 hasher_fun	133
8.18.4.5 init_fun	133
8.18.4.6 name	133
8.19 Counters< Array_Type, Data_Type > Class Template Reference	134
8.19.1 Detailed Description	134
8.19.2 Constructor & Destructor Documentation	134
8.19.2.1 Counters() [1/3]	135
8.19.2.2 ~Counters()	135
8.19.2.3 Counters() [2/3]	135
8.19.2.4 Counters() [3/3]	135
8.19.3 Member Function Documentation	135
8.19.3.1 add_counter() [1/2]	136
8.19.3.2 add_counter() [2/2]	136
8.19.3.3 add_hash()	136
8.19.3.4 gen_hash()	136
8.19.3.5 get_descriptions()	137
8.19.3.6 get_names()	137
8.19.3.7 operator=() [1/2]	137
8.19.3.8 operator=() [2/2]	137
8.19.3.9 operator[]()	138
8.19.3.10 size()	138
8.20 DEFM Class Reference	139
8.20.1 Detailed Description	140
8.20.2 Constructor & Destructor Documentation	140
8.20.2.1 DEFM()	140
8.20.3 Member Function Documentation	140
8.20.3.1 get_column_major()	140
8.20.3.2 get_ID()	140
8.20.3.3 get_m_order()	141
8.20.3.4 get_model()	141
8.20.3.5 get_n_covars()	141
8.20.3.6 get_n_obs()	141
8.20.3.7 get_n_rows()	141

8.20.3.8	get_n_y()	141
8.20.3.9	get_X()	142
8.20.3.10	get_X_names()	142
8.20.3.11	get_Y()	142
8.20.3.12	get_Y_names()	142
8.20.3.13	init()	142
8.20.3.14	is_motif()	142
8.20.3.15	logodds()	143
8.20.3.16	motif_census()	143
8.20.3.17	print()	143
8.20.3.18	set_names()	143
8.20.3.19	simulate()	143
8.21	DEFMCounterData Class Reference	144
8.21.1	Detailed Description	144
8.22	DEFMData Class Reference	144
8.22.1	Detailed Description	145
8.23	DEFMRuleData Class Reference	146
8.23.1	Detailed Description	146
8.24	DEFMRuleDynData Class Reference	147
8.24.1	Detailed Description	147
8.25	Entries< Cell_Type > Class Template Reference	148
8.25.1	Detailed Description	148
8.25.2	Constructor & Destructor Documentation	148
8.25.2.1	Entries() [1/2]	148
8.25.2.2	Entries() [2/2]	149
8.25.2.3	~Entries()	149
8.25.3	Member Function Documentation	149
8.25.3.1	resize()	149
8.25.4	Member Data Documentation	149
8.25.4.1	source	149
8.25.4.2	target	149
8.25.4.3	val	150
8.26	Flock Class Reference	150
8.26.1	Detailed Description	151
8.26.2	Constructor & Destructor Documentation	151
8.26.2.1	Flock()	151
8.26.2.2	~Flock()	151
8.26.3	Member Function Documentation	151
8.26.3.1	add_data()	151
8.26.3.2	colnames()	152
8.26.3.3	get_counters()	152
8.26.3.4	get_model()	152

8.26.3.5 <code>get_stats_support()</code>	152
8.26.3.6 <code>get_stats_target()</code>	153
8.26.3.7 <code>get_support_fun()</code>	153
8.26.3.8 <code>init()</code>	153
8.26.3.9 <code>likelihood_joint()</code>	153
8.26.3.10 <code>nfuncs()</code>	154
8.26.3.11 <code>nleaves()</code>	154
8.26.3.12 <code>nnodes()</code>	154
8.26.3.13 <code>nterms()</code>	154
8.26.3.14 <code>ntrees()</code>	154
8.26.3.15 <code>operator()</code>	154
8.26.3.16 <code>parse_polytomies()</code>	155
8.26.3.17 <code>print()</code>	155
8.26.3.18 <code>set_seed()</code>	155
8.26.3.19 <code>support_size()</code>	156
8.26.4 Member Data Documentation	156
8.26.4.1 <code>dat</code>	156
8.26.4.2 <code>initialized</code>	156
8.26.4.3 <code>model</code>	156
8.26.4.4 <code>nfunctions</code>	156
8.26.4.5 <code>engine</code>	157
8.27 <code>FreqTable< T ></code> Class Template Reference	157
8.27.1 Detailed Description	157
8.27.2 Constructor & Destructor Documentation	158
8.27.2.1 <code>FreqTable()</code>	158
8.27.2.2 <code>~FreqTable()</code>	158
8.27.3 Member Function Documentation	158
8.27.3.1 <code>add()</code>	158
8.27.3.2 <code>as_vector()</code>	158
8.27.3.3 <code>clear()</code>	159
8.27.3.4 <code>get_data()</code>	159
8.27.3.5 <code>get_index()</code>	159
8.27.3.6 <code>make_hash()</code>	159
8.27.3.7 <code>print()</code>	159
8.27.3.8 <code>reserve()</code>	160
8.27.3.9 <code>size()</code>	160
8.28 Geese Class Reference	160
8.28.1 Detailed Description	163
8.28.2 Constructor & Destructor Documentation	163
8.28.2.1 <code>Geese()</code> [1/4]	164
8.28.2.2 <code>Geese()</code> [2/4]	164
8.28.2.3 <code>Geese()</code> [3/4]	164

8.28.2.4 Geese() [4 / 4]	164
8.28.2.5 ~Geese()	164
8.28.3 Member Function Documentation	164
8.28.3.1 calc_reduced_sequence()	165
8.28.3.2 calc_sequence()	165
8.28.3.3 colnames()	165
8.28.3.4 get_annotated_nodes()	165
8.28.3.5 get_annotations()	165
8.28.3.6 get_counters()	166
8.28.3.7 get_model()	166
8.28.3.8 get_probabilities()	166
8.28.3.9 get_engine()	166
8.28.3.10 get_states()	166
8.28.3.11 get_support_fun()	167
8.28.3.12 inherit_support()	167
8.28.3.13 init()	167
8.28.3.14 init_node()	167
8.28.3.15 likelihood()	167
8.28.3.16 likelihood_exhaust()	168
8.28.3.17 nannotations()	168
8.28.3.18 nfuncs()	168
8.28.3.19 nleaves()	168
8.28.3.20 nnodes()	168
8.28.3.21 nterms()	169
8.28.3.22 observed_counts()	169
8.28.3.23 operator=() [1 / 2]	169
8.28.3.24 operator=() [2 / 2]	169
8.28.3.25 parse_polytomies()	169
8.28.3.26 predict()	170
8.28.3.27 predict_backend()	170
8.28.3.28 predict_exhaust()	170
8.28.3.29 predict_exhaust_backend()	170
8.28.3.30 predict_sim()	170
8.28.3.31 print()	171
8.28.3.32 print_nodes()	171
8.28.3.33 print_observed_counts()	171
8.28.3.34 set_seed()	171
8.28.3.35 simulate()	171
8.28.3.36 support_size()	171
8.28.3.37 update_annotations()	172
8.28.4 Member Data Documentation	172
8.28.4.1 delete_engine	172

8.28.4.2 delete_support	172
8.28.4.3 etype_default	172
8.28.4.4 etype_duplication	172
8.28.4.5 etype_either	173
8.28.4.6 etype_speciation	173
8.28.4.7 initialized	173
8.28.4.8 map_to_state_id	173
8.28.4.9 nfunctions	173
8.28.4.10 nodes	173
8.28.4.11 pset_loc	174
8.28.4.12 reduced_sequence	174
8.28.4.13 sequence	174
8.29 Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	175
8.29.1 Detailed Description	179
8.29.2 Constructor & Destructor Documentation	179
8.29.2.1 Model() [1/3]	179
8.29.2.2 Model() [2/3]	179
8.29.2.3 Model() [3/3]	180
8.29.2.4 ~Model()	180
8.29.3 Member Function Documentation	180
8.29.3.1 add_array()	180
8.29.3.2 add_counter() [1/2]	181
8.29.3.3 add_counter() [2/2]	181
8.29.3.4 add_hasher()	181
8.29.3.5 add_rule() [1/2]	181
8.29.3.6 add_rule() [2/2]	181
8.29.3.7 add_rule_dyn() [1/2]	182
8.29.3.8 add_rule_dyn() [2/2]	182
8.29.3.9 colnames()	182
8.29.3.10 conditional_prob()	182
8.29.3.11 gen_key()	183
8.29.3.12 get_arrays2support()	183
8.29.3.13 get_counters()	183
8.29.3.14 get_norm_const()	183
8.29.3.15 get_pset()	184
8.29.3.16 get_pset_arrays()	184
8.29.3.17 get_pset_probs()	184
8.29.3.18 get_pset_stats() [1/2]	184
8.29.3.19 get_pset_stats() [2/2]	184
8.29.3.20 get_rengine()	185
8.29.3.21 get_rules()	185

8.29.3.22	get_rules_dyn()	185
8.29.3.23	get_stats_support()	185
8.29.3.24	get_stats_target()	185
8.29.3.25	get_support_fun()	186
8.29.3.26	likelihood() [1/4]	186
8.29.3.27	likelihood() [2/4]	186
8.29.3.28	likelihood() [3/4]	186
8.29.3.29	likelihood() [4/4]	187
8.29.3.30	likelihood_total()	187
8.29.3.31	nrules()	187
8.29.3.32	nrules_dyn()	187
8.29.3.33	nterms()	187
8.29.3.34	operator=()	188
8.29.3.35	print()	188
8.29.3.36	print_stats()	188
8.29.3.37	sample() [1/2]	188
8.29.3.38	sample() [2/2]	189
8.29.3.39	set_counters()	189
8.29.3.40	set_engine()	189
8.29.3.41	set_rules()	189
8.29.3.42	set_rules_dyn()	189
8.29.3.43	set_seed()	190
8.29.3.44	set_transform_model()	190
8.29.3.45	size()	190
8.29.3.46	size_unique()	190
8.29.3.47	store_psets()	191
8.29.3.48	support_size()	191
8.29.3.49	transform_model()	191
8.29.4	Member Data Documentation	191
8.29.4.1	arrays2support	191
8.29.4.2	counter_fun	191
8.29.4.3	counters	192
8.29.4.4	delete_counters	192
8.29.4.5	delete_engine	192
8.29.4.6	delete_rules	192
8.29.4.7	delete_rules_dyn	192
8.29.4.8	first_calc_done	193
8.29.4.9	keys2support	193
8.29.4.10	normalizing_constants	193
8.29.4.11	params_last	193
8.29.4.12	pset_arrays	194
8.29.4.13	pset_probs	194

8.29.4.14 pset_stats	194
8.29.4.15 engine	194
8.29.4.16 rules	195
8.29.4.17 rules_dyn	195
8.29.4.18 stats_support	195
8.29.4.19 stats_support_n_arrays	195
8.29.4.20 stats_target	196
8.29.4.21 support_fun	196
8.29.4.22 transform_model_fun	196
8.29.4.23 transform_model_term_names	197
8.29.4.24 with_pset	197
8.30 NetCounterData Class Reference	197
8.30.1 Detailed Description	197
8.30.2 Constructor & Destructor Documentation	198
8.30.2.1 NetCounterData() [1/2]	198
8.30.2.2 NetCounterData() [2/2]	198
8.30.2.3 ~NetCounterData()	198
8.30.3 Member Data Documentation	198
8.30.3.1 indices	198
8.30.3.2 numbers	198
8.31 NetworkData Class Reference	199
8.31.1 Detailed Description	199
8.31.2 Constructor & Destructor Documentation	199
8.31.2.1 NetworkData() [1/3]	199
8.31.2.2 NetworkData() [2/3]	199
8.31.2.3 NetworkData() [3/3]	200
8.31.2.4 ~NetworkData()	200
8.31.3 Member Data Documentation	200
8.31.3.1 directed	200
8.31.3.2 vertex_attr	201
8.32 Node Class Reference	201
8.32.1 Detailed Description	202
8.32.2 Constructor & Destructor Documentation	202
8.32.2.1 Node() [1/5]	202
8.32.2.2 Node() [2/5]	203
8.32.2.3 Node() [3/5]	203
8.32.2.4 Node() [4/5]	203
8.32.2.5 Node() [5/5]	203
8.32.2.6 ~Node()	203
8.32.3 Member Function Documentation	203
8.32.3.1 get_parent()	204
8.32.3.2 is_leaf()	204

8.32.3.3 noffspring()	204
8.32.4 Member Data Documentation	204
8.32.4.1 annotations	204
8.32.4.2 array	204
8.32.4.3 arrays	205
8.32.4.4 duplication	205
8.32.4.5 id	205
8.32.4.6 narray	205
8.32.4.7 offspring	205
8.32.4.8 ord	206
8.32.4.9 parent	206
8.32.4.10 probability	206
8.32.4.11 subtree_prob	206
8.32.4.12 visited	206
8.33 NodeData Class Reference	207
8.33.1 Detailed Description	207
8.33.2 Constructor & Destructor Documentation	207
8.33.2.1 NodeData()	207
8.33.3 Member Data Documentation	207
8.33.3.1 blengths	208
8.33.3.2 duplication	208
8.33.3.3 states	208
8.34 PhyloCounterData Class Reference	208
8.34.1 Detailed Description	209
8.34.2 Constructor & Destructor Documentation	209
8.34.2.1 PhyloCounterData() [1/2]	209
8.34.2.2 PhyloCounterData() [2/2]	209
8.34.3 Member Function Documentation	209
8.34.3.1 at()	209
8.34.3.2 begin()	209
8.34.3.3 empty()	210
8.34.3.4 end()	210
8.34.3.5 get_counters()	210
8.34.3.6 operator()()	210
8.34.3.7 operator[]()	210
8.34.3.8 push_back()	210
8.34.3.9 reserve()	211
8.34.3.10 shrink_to_fit()	211
8.34.3.11 size()	211
8.35 PhyloRuleDynData Class Reference	211
8.35.1 Detailed Description	212
8.35.2 Constructor & Destructor Documentation	212

8.35.2.1 PhyloRuleDynData()	212
8.35.2.2 ~PhyloRuleDynData()	212
8.35.3 Member Function Documentation	212
8.35.3.1 operator()()	212
8.35.4 Member Data Documentation	212
8.35.4.1 counts	212
8.35.4.2 duplication	213
8.35.4.3 lb	213
8.35.4.4 pos	213
8.35.4.5 ub	213
8.36 PowerSet< Array_Type, Data_Rule_Type > Class Template Reference	213
8.36.1 Detailed Description	214
8.36.2 Constructor & Destructor Documentation	215
8.36.2.1 PowerSet() [1/3]	215
8.36.2.2 PowerSet() [2/3]	215
8.36.2.3 PowerSet() [3/3]	215
8.36.2.4 ~PowerSet()	215
8.36.3 Member Function Documentation	215
8.36.3.1 add_rule() [1/2]	216
8.36.3.2 add_rule() [2/2]	216
8.36.3.3 begin()	216
8.36.3.4 calc()	216
8.36.3.5 end()	216
8.36.3.6 get_data()	217
8.36.3.7 get_data_ptr()	217
8.36.3.8 init_support()	217
8.36.3.9 operator[]()	217
8.36.3.10 reset()	217
8.36.3.11 size()	218
8.36.4 Member Data Documentation	218
8.36.4.1 coordinates_free	218
8.36.4.2 coordinates_locked	218
8.36.4.3 data	218
8.36.4.4 EmptyArray	218
8.36.4.5 M	219
8.36.4.6 N	219
8.36.4.7 n_free	219
8.36.4.8 n_locked	219
8.36.4.9 rules	219
8.36.4.10 rules_deleted	220
8.37 Progress Class Reference	220
8.37.1 Detailed Description	220

8.37.2 Constructor & Destructor Documentation	220
8.37.2.1 Progress()	220
8.37.2.2 ~Progress()	221
8.37.3 Member Function Documentation	221
8.37.3.1 end()	221
8.37.3.2 next()	221
8.38 Rule< Array_Type, Data_Type > Class Template Reference	221
8.38.1 Detailed Description	222
8.38.2 Constructor & Destructor Documentation	222
8.38.2.1 Rule() [1/2]	222
8.38.2.2 Rule() [2/2]	222
8.38.2.3 ~Rule()	223
8.38.3 Member Function Documentation	223
8.38.3.1 D()	223
8.38.3.2 get_description() [1/2]	223
8.38.3.3 get_description() [2/2]	223
8.38.3.4 get_name() [1/2]	223
8.38.3.5 get_name() [2/2]	224
8.38.3.6 operator()()	224
8.39 Rules< Array_Type, Data_Type > Class Template Reference	224
8.39.1 Detailed Description	225
8.39.2 Constructor & Destructor Documentation	225
8.39.2.1 Rules() [1/2]	225
8.39.2.2 Rules() [2/2]	225
8.39.2.3 ~Rules()	226
8.39.3 Member Function Documentation	226
8.39.3.1 add_rule() [1/2]	226
8.39.3.2 add_rule() [2/2]	226
8.39.3.3 begin()	226
8.39.3.4 end()	226
8.39.3.5 get_descriptions()	227
8.39.3.6 get_names()	227
8.39.3.7 get_seq()	227
8.39.3.8 operator()()	227
8.39.3.9 operator=()	228
8.39.3.10 size()	228
8.40 StatsCounter< Array_Type, Data_Type > Class Template Reference	228
8.40.1 Detailed Description	229
8.40.2 Constructor & Destructor Documentation	229
8.40.2.1 StatsCounter() [1/3]	229
8.40.2.2 StatsCounter() [2/3]	230
8.40.2.3 StatsCounter() [3/3]	230

8.40.2.4 ~StatsCounter()	230
8.40.3 Member Function Documentation	230
8.40.3.1 add_counter()	230
8.40.3.2 count_all()	231
8.40.3.3 count_current()	231
8.40.3.4 count_init()	231
8.40.3.5 get_counters()	231
8.40.3.6 get_descriptions()	231
8.40.3.7 get_names()	231
8.40.3.8 reset_array()	231
8.40.3.9 set_counters()	232
8.40.3.10 size()	232
8.41 Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference	232
8.41.1 Detailed Description	234
8.41.2 Constructor & Destructor Documentation	234
8.41.2.1 Support() [1/3]	234
8.41.2.2 Support() [2/3]	235
8.41.2.3 Support() [3/3]	235
8.41.2.4 ~Support()	235
8.41.3 Member Function Documentation	235
8.41.3.1 add_counter()	235
8.41.3.2 add_rule() [1/2]	236
8.41.3.3 add_rule() [2/2]	236
8.41.3.4 add_rule_dyn() [1/2]	236
8.41.3.5 add_rule_dyn() [2/2]	236
8.41.3.6 calc()	236
8.41.3.7 eval_rules_dyn()	237
8.41.3.8 get_counters()	237
8.41.3.9 get_counts()	237
8.41.3.10 get_current_stats()	238
8.41.3.11 get_data()	238
8.41.3.12 get_rules()	238
8.41.3.13 get_rules_dyn()	238
8.41.3.14 init_support()	239
8.41.3.15 print()	239
8.41.3.16 reset_array() [1/2]	239
8.41.3.17 reset_array() [2/2]	239
8.41.3.18 set_counters()	240
8.41.3.19 set_rules()	240
8.41.3.20 set_rules_dyn()	240
8.41.4 Member Data Documentation	240

8.41.4.1 change_stats	240
8.41.4.2 coordiantes_n_free	241
8.41.4.3 coordiantes_n_locked	241
8.41.4.4 coordinates_free	241
8.41.4.5 coordinates_locked	241
8.41.4.6 current_stats	241
8.41.4.7 delete_counters	242
8.41.4.8 delete_rules	242
8.41.4.9 delete_rules_dyn	242
8.41.4.10 hashes	242
8.41.4.11 hashes_initialized	242
8.41.4.12 M	243
8.41.4.13 max_num_elements	243
8.41.4.14 N	243
8.41.4.15 n_counters	243
8.42 vecHasher< T > Struct Template Reference	243
8.42.1 Detailed Description	244
8.42.2 Member Function Documentation	244
8.42.2.1 operator()()	244
9 File Documentation	245
9.1 include/barry/barray-bones.hpp File Reference	245
9.2 include/barry/barray-iterator.hpp File Reference	245
9.3 include/barry/barray-meat-operators.hpp File Reference	246
9.3.1 Macro Definition Documentation	246
9.3.1.1 BARRAY_TEMPLATE	247
9.3.1.2 BARRAY_TEMPLATE_ARGS	247
9.3.1.3 BARRAY_TYPE	247
9.3.1.4 COL	247
9.3.1.5 ROW	247
9.3.2 Function Documentation	247
9.3.2.1 BARRAY_TEMPLATE() [1/6]	248
9.3.2.2 BARRAY_TEMPLATE() [2/6]	248
9.3.2.3 BARRAY_TEMPLATE() [3/6]	248
9.3.2.4 BARRAY_TEMPLATE() [4/6]	248
9.3.2.5 BARRAY_TEMPLATE() [5/6]	248
9.3.2.6 BARRAY_TEMPLATE() [6/6]	249
9.3.2.7 BARRAY_TEMPLATE_ARGS()	249
9.3.2.8 BARRAY_TYPE()	249
9.3.2.9 for()	249
9.3.2.10 operator()()	249
9.3.3 Variable Documentation	249

9.3.3.1 rhs	250
9.3.3.2 this	250
9.4 include/barry/barray-meat.hpp File Reference	250
9.4.1 Macro Definition Documentation	250
9.4.1.1 COL	251
9.4.1.2 ROW	251
9.5 include/barry/barraycell-bones.hpp File Reference	251
9.6 include/barry/barraycell-meat.hpp File Reference	252
9.7 include/barry/barraydense-bones.hpp File Reference	252
9.8 include/barry/barraydense-meat-operators.hpp File Reference	253
9.8.1 Macro Definition Documentation	253
9.8.1.1 BDENSE_TEMPLATE	253
9.8.1.2 BDENSE_TEMPLATE_ARGS	254
9.8.1.3 BDENSE_TYPE	254
9.8.1.4 COL	254
9.8.1.5 POS	254
9.8.1.6 POS_N	254
9.8.1.7 ROW	255
9.8.2 Function Documentation	255
9.8.2.1 BDENSE_TEMPLATE() [1/4]	255
9.8.2.2 BDENSE_TEMPLATE() [2/4]	255
9.8.2.3 BDENSE_TEMPLATE() [3/4]	255
9.8.2.4 BDENSE_TEMPLATE() [4/4]	255
9.8.2.5 BDENSE_TEMPLATE_ARGS()	256
9.8.2.6 BDENSE_TYPE()	256
9.9 include/barry/barraydense-meat.hpp File Reference	256
9.9.1 Macro Definition Documentation	256
9.9.1.1 COL	256
9.9.1.2 POS	257
9.9.1.3 POS_N	257
9.9.1.4 ROW	257
9.9.1.5 ZERO_CELL	257
9.10 include/barry/barraydensecell-bones.hpp File Reference	257
9.10.1 Macro Definition Documentation	258
9.10.1.1 POS	258
9.11 include/barry/barraydensecell-meat.hpp File Reference	258
9.11.1 Macro Definition Documentation	258
9.11.1.1 POS	259
9.12 include/barry/barraydensecol-bones.hpp File Reference	259
9.12.1 Macro Definition Documentation	259
9.12.1.1 POS	259
9.12.1.2 POS_N	260

9.12.1.3 ZERO_CELL	260
9.13 include/barry/barraydenserow-bones.hpp File Reference	260
9.13.1 Macro Definition Documentation	261
9.13.1.1 POS	261
9.13.1.2 POS_N	261
9.13.1.3 ZERO_CELL	261
9.14 include/barry/barrayrow-bones.hpp File Reference	261
9.15 include/barry/barrayrow-meat.hpp File Reference	261
9.15.1 Macro Definition Documentation	262
9.15.1.1 BROW_TEMPLATE	262
9.15.1.2 BROW_TEMPLATE_ARGS	262
9.15.1.3 BROW_TYPE	262
9.15.2 Function Documentation	262
9.15.2.1 BROW_TEMPLATE() [1/5]	262
9.15.2.2 BROW_TEMPLATE() [2/5]	263
9.15.2.3 BROW_TEMPLATE() [3/5]	263
9.15.2.4 BROW_TEMPLATE() [4/5]	263
9.15.2.5 BROW_TEMPLATE() [5/5]	263
9.16 include/barry/barrayvector-bones.hpp File Reference	263
9.17 include/barry/barrayvector-meat.hpp File Reference	264
9.18 include/barry/barry-configuration.hpp File Reference	264
9.18.1 Macro Definition Documentation	265
9.18.1.1 BARRY_CHECK_SUPPORT	265
9.18.1.2 BARRY_ISFINITE	265
9.18.1.3 BARRY_MAX_NUM_ELEMENTS	265
9.18.1.4 BARRY_SAFE_EXP	265
9.18.1.5 printf_barry	265
9.18.2 Typedef Documentation	266
9.18.2.1 Map	266
9.19 include/barry/barry-debug.hpp File Reference	266
9.19.1 Macro Definition Documentation	266
9.19.1.1 BARRY_DEBUG_LEVEL	266
9.20 include/barry/barry-macros.hpp File Reference	267
9.20.1 Macro Definition Documentation	267
9.20.1.1 BARRY_ONE	267
9.20.1.2 BARRY_ONE_DENSE	267
9.20.1.3 BARRY_UNUSED	268
9.20.1.4 BARRY_ZERO	268
9.20.1.5 BARRY_ZERO_DENSE	268
9.21 include/barry/barry.hpp File Reference	268
9.21.1 Macro Definition Documentation	269
9.21.1.1 BARRY_HPP	270

9.21.1.2 BARRY_VERSION	270
9.21.1.3 BARRY_VERSION_MAYOR	270
9.21.1.4 BARRY_VERSION_MINOR	270
9.21.1.5 COUNTER_FUNCTION	270
9.21.1.6 COUNTER_LAMBDA	271
9.21.1.7 RULE_FUNCTION	271
9.21.1.8 RULE_LAMBDA	271
9.22 include/barry/cell-bones.hpp File Reference	271
9.23 include/barry/cell-meat.hpp File Reference	272
9.24 include/barry/col-bones.hpp File Reference	272
9.25 include/barry/counters-bones.hpp File Reference	272
9.26 include/barry/counters-meat.hpp File Reference	273
9.26.1 Macro Definition Documentation	274
9.26.1.1 COUNTER_TEMPLATE	274
9.26.1.2 COUNTER_TEMPLATE_ARGS	275
9.26.1.3 COUNTER_TYPE	275
9.26.1.4 COUNTERS_TEMPLATE	275
9.26.1.5 COUNTERS_TEMPLATE_ARGS	275
9.26.1.6 COUNTERS_TYPE	275
9.26.1.7 TMP_HASHER_CALL	275
9.26.2 Function Documentation	276
9.26.2.1 count_fun()	276
9.26.2.2 COUNTER_TEMPLATE() [1/9]	276
9.26.2.3 COUNTER_TEMPLATE() [2/9]	276
9.26.2.4 COUNTER_TEMPLATE() [3/9]	276
9.26.2.5 COUNTER_TEMPLATE() [4/9]	276
9.26.2.6 COUNTER_TEMPLATE() [5/9]	277
9.26.2.7 COUNTER_TEMPLATE() [6/9]	277
9.26.2.8 COUNTER_TEMPLATE() [7/9]	277
9.26.2.9 COUNTER_TEMPLATE() [8/9]	277
9.26.2.10 COUNTER_TEMPLATE() [9/9]	277
9.26.2.11 COUNTERS_TEMPLATE() [1/9]	278
9.26.2.12 COUNTERS_TEMPLATE() [2/9]	278
9.26.2.13 COUNTERS_TEMPLATE() [3/9]	278
9.26.2.14 COUNTERS_TEMPLATE() [4/9]	278
9.26.2.15 COUNTERS_TEMPLATE() [5/9]	278
9.26.2.16 COUNTERS_TEMPLATE() [6/9]	278
9.26.2.17 COUNTERS_TEMPLATE() [7/9]	279
9.26.2.18 COUNTERS_TEMPLATE() [8/9]	279
9.26.2.19 COUNTERS_TEMPLATE() [9/9]	279
9.26.2.20 data()	279
9.26.2.21 desc()	279

9.26.2.22 for()	279
9.26.2.23 hasher() [1/2]	280
9.26.2.24 hasher() [2/2]	280
9.26.2.25 hasher_fun() [1/2]	280
9.26.2.26 hasher_fun() [2/2]	280
9.26.2.27 if() [1/3]	280
9.26.2.28 if() [2/3]	280
9.26.2.29 if() [3/3]	281
9.26.2.30 init_fun() [1/3]	281
9.26.2.31 init_fun() [2/3]	281
9.26.2.32 init_fun() [3/3]	281
9.26.2.33 name()	281
9.26.3 Variable Documentation	281
9.26.3.1 add_dims	281
9.26.3.2 count_fun_	282
9.26.3.3 counter	282
9.26.3.4 counter_	282
9.26.3.5 data_	282
9.26.3.6 desc_	283
9.26.3.7 fun	283
9.26.3.8 fun_	283
9.26.3.9 hasher_fun_	283
9.26.3.10 i	284
9.26.3.11 init_fun_	284
9.26.3.12 j	284
9.26.3.13 name_	284
9.26.3.14 noexcept	284
9.26.3.15 res	285
9.26.3.16 return	285
9.27 include/barry/counters/network-css.hpp File Reference	285
9.27.1 Macro Definition Documentation	286
9.27.1.1 CSS_APPEND	287
9.27.1.2 CSS_CASE_ELSE	287
9.27.1.3 CSS_CASE_PERCEIVED	287
9.27.1.4 CSS_CASE_TRUTH	287
9.27.1.5 CSS_CHECK_SIZE	287
9.27.1.6 CSS_CHECK_SIZE_INIT	288
9.27.1.7 CSS_MATCH_TYPE	288
9.27.1.8 CSS_NET_COUNTER_LAMBDA_INIT	288
9.27.1.9 CSS_PERCEIVED_CELLS	288
9.27.1.10 CSS_SIZE	289
9.27.1.11 CSS_TRUE_CELLS	289

9.27.2 Function Documentation	289
9.27.2.1 counter_css_census01()	289
9.27.2.2 counter_css_census02()	289
9.27.2.3 counter_css_census03()	290
9.27.2.4 counter_css_census04()	290
9.27.2.5 counter_css_census05()	290
9.27.2.6 counter_css_census06()	290
9.27.2.7 counter_css_census07()	291
9.27.2.8 counter_css_census08()	291
9.27.2.9 counter_css_census09()	291
9.27.2.10 counter_css_census10()	291
9.27.2.11 counter_css_completely_false_recip_comiss()	292
9.27.2.12 counter_css_completely_false_recip_omiss()	292
9.27.2.13 counter_css_mixed_recip()	292
9.27.2.14 counter_css_partially_false_recip_commi()	292
9.27.2.15 counter_css_partially_false_recip_omiss()	293
9.28 include/barry/counters/network.hpp File Reference	293
9.28.1 Macro Definition Documentation	296
9.28.1.1 BARRY_ZERO_NETWORK	296
9.28.1.2 BARRY_ZERO_NETWORK_DENSE	297
9.28.1.3 NET_C_DATA_IDX	297
9.28.1.4 NET_C_DATA_NUM	297
9.28.1.5 NETWORK_COUNTER	297
9.28.1.6 NETWORK_COUNTER_LAMBDA	297
9.28.1.7 NETWORK_RULE	298
9.28.1.8 NETWORK_RULE_LAMBDA	298
9.28.1.9 NETWORKDENSE_COUNTER_LAMBDA	298
9.28.2 Typedef Documentation	298
9.28.2.1 NetCounter	298
9.28.2.2 NetCounters	299
9.28.2.3 NetModel	299
9.28.2.4 NetRule	299
9.28.2.5 NetRules	299
9.28.2.6 NetStatsCounter	299
9.28.2.7 NetSupport	299
9.28.2.8 Network	300
9.28.2.9 NetworkDense	300
9.28.3 Function Documentation	300
9.28.3.1 rules_zerodiag()	300
9.29 include/barry/freqtable.hpp File Reference	300
9.30 include/barry/model-bones.hpp File Reference	301
9.31 include/barry/model-meat.hpp File Reference	301

9.31.1 Macro Definition Documentation	303
9.31.1.1 MODEL_TEMPLATE	304
9.31.1.2 MODEL_TEMPLATE_ARGS	304
9.31.1.3 MODEL_TYPE	304
9.31.2 Function Documentation	304
9.31.2.1 for() [1/2]	304
9.31.2.2 for() [2/2]	304
9.31.2.3 if() [1/4]	305
9.31.2.4 if() [2/4]	305
9.31.2.5 if() [3/4]	305
9.31.2.6 if() [4/4]	305
9.31.2.7 insert_cell()	305
9.31.2.8 likelihood_()	306
9.31.2.9 MODEL_TEMPLATE() [1/33]	306
9.31.2.10 MODEL_TEMPLATE() [2/33]	306
9.31.2.11 MODEL_TEMPLATE() [3/33]	306
9.31.2.12 MODEL_TEMPLATE() [4/33]	306
9.31.2.13 MODEL_TEMPLATE() [5/33]	307
9.31.2.14 MODEL_TEMPLATE() [6/33]	307
9.31.2.15 MODEL_TEMPLATE() [7/33]	307
9.31.2.16 MODEL_TEMPLATE() [8/33]	307
9.31.2.17 MODEL_TEMPLATE() [9/33]	307
9.31.2.18 MODEL_TEMPLATE() [10/33]	308
9.31.2.19 MODEL_TEMPLATE() [11/33]	308
9.31.2.20 MODEL_TEMPLATE() [12/33]	308
9.31.2.21 MODEL_TEMPLATE() [13/33]	308
9.31.2.22 MODEL_TEMPLATE() [14/33]	308
9.31.2.23 MODEL_TEMPLATE() [15/33]	309
9.31.2.24 MODEL_TEMPLATE() [16/33]	309
9.31.2.25 MODEL_TEMPLATE() [17/33]	309
9.31.2.26 MODEL_TEMPLATE() [18/33]	309
9.31.2.27 MODEL_TEMPLATE() [19/33]	309
9.31.2.28 MODEL_TEMPLATE() [20/33]	310
9.31.2.29 MODEL_TEMPLATE() [21/33]	310
9.31.2.30 MODEL_TEMPLATE() [22/33]	310
9.31.2.31 MODEL_TEMPLATE() [23/33]	310
9.31.2.32 MODEL_TEMPLATE() [24/33]	310
9.31.2.33 MODEL_TEMPLATE() [25/33]	311
9.31.2.34 MODEL_TEMPLATE() [26/33]	311
9.31.2.35 MODEL_TEMPLATE() [27/33]	311
9.31.2.36 MODEL_TEMPLATE() [28/33]	311
9.31.2.37 MODEL_TEMPLATE() [29/33]	311

9.31.2.38 MODEL_TEMPLATE() [30/33]	311
9.31.2.39 MODEL_TEMPLATE() [31/33]	312
9.31.2.40 MODEL_TEMPLATE() [32/33]	312
9.31.2.41 MODEL_TEMPLATE() [33/33]	312
9.31.2.42 push_back() [1/2]	312
9.31.2.43 push_back() [2/2]	312
9.31.2.44 reserve() [1/2]	312
9.31.2.45 reserve() [2/2]	313
9.31.2.46 return()	313
9.31.2.47 set_counters()	313
9.31.2.48 set_rules()	313
9.31.2.49 set_rules_dyn()	313
9.31.2.50 size()	313
9.31.2.51 update_normalizing_constant()	314
9.31.2.52 urand()	314
9.31.3 Variable Documentation	314
9.31.3.1 a	314
9.31.3.2 count_fun_	314
9.31.3.3 counter	314
9.31.3.4 counters_	315
9.31.3.5 cumprob	315
9.31.3.6 data_	315
9.31.3.7 Data_Counter_Type	315
9.31.3.8 Data_Rule_Type	315
9.31.3.9 delete_rules	316
9.31.3.10 delete_rules_dyn	316
9.31.3.11 else	316
9.31.3.12 force_new	316
9.31.3.13 fun_	316
9.31.3.14 i	317
9.31.3.15 i_matches	317
9.31.3.16 init_fun_	317
9.31.3.17 j	317
9.31.3.18 k	317
9.31.3.19 key	317
9.31.3.20 locator	318
9.31.3.21 params	318
9.31.3.22 probs	318
9.31.3.23 pset_arrays	318
9.31.3.24 r	318
9.31.3.25 return	318
9.31.3.26 rule_fun_	319

9.31.3.27 rules	319
9.31.3.28 rules_	319
9.31.3.29 rules_dyn	319
9.31.3.30 stats	319
9.31.3.31 stats_support_n_arrays	320
9.31.3.32 temp_stats	320
9.31.3.33 tmp_counts	320
9.32 include/barry/models/defm.hpp File Reference	320
9.33 include/barry/models/defm/counters.hpp File Reference	321
9.33.1 Macro Definition Documentation	322
9.33.1.1 DEFM_COUNTER	322
9.33.1.2 DEFM_COUNTER_LAMBDA	323
9.33.1.3 DEFM_RULE	323
9.33.1.4 DEFM_RULE_LAMBDA	323
9.33.1.5 DEFM RULEDYN_LAMBDA	323
9.33.1.6 UNI_SUB	324
9.34 include/barry/models/geese/counters.hpp File Reference	324
9.35 include/barry/models/defm/defm-bones.hpp File Reference	326
9.36 include/barry/models/defm/defm-meat.hpp File Reference	326
9.36.1 Macro Definition Documentation	327
9.36.1.1 DEFM_LOOP_ARRAYS	327
9.36.1.2 DEFM_RANGES	327
9.36.2 Function Documentation	327
9.36.2.1 keygen_defm()	327
9.37 include/barry/models/defm/defm-types.hpp File Reference	328
9.37.1 Typedef Documentation	328
9.37.1.1 DEFMArray	329
9.38 include/barry/models/defm/formula.hpp File Reference	329
9.38.1 Function Documentation	329
9.38.1.1 defm_motif_parser()	330
9.39 include/barry/models/geese.hpp File Reference	331
9.40 include/barry/models/geese/flock-bones.hpp File Reference	331
9.41 include/barry/models/geese/flock-meat.hpp File Reference	332
9.42 include/barry/models/geese/geese-bones.hpp File Reference	332
9.42.1 Macro Definition Documentation	333
9.42.1.1 INITIALIZED	333
9.42.2 Function Documentation	333
9.42.2.1 keygen_full()	333
9.42.2.2 RULE_FUNCTION()	333
9.42.2.3 vec_diff()	334
9.42.2.4 vector_caster()	334
9.43 include/barry/models/geese/geese-meat-constructors.hpp File Reference	334

9.44 include/barry/models/geese/geese-meat-likelihood.hpp File Reference	335
9.45 include/barry/models/geese/geese-meat-likelihood_exhaust.hpp File Reference	336
9.46 include/barry/models/geese/geese-meat-predict.hpp File Reference	336
9.47 include/barry/models/geese/geese-meat-predict_exhaust.hpp File Reference	337
9.48 include/barry/models/geese/geese-meat-predict_sim.hpp File Reference	337
9.49 include/barry/models/geese/geese-meat-simulate.hpp File Reference	338
9.50 include/barry/models/geese/geese-meat.hpp File Reference	338
9.51 include/barry/models/geese/geese-node-bones.hpp File Reference	339
9.52 include/barry/models/geese/geese-types.hpp File Reference	339
9.52.1 Typedef Documentation	340
9.52.1.1 PhyloArray	340
9.52.1.2 PhyloCounter	340
9.52.1.3 PhyloCounters	340
9.52.1.4 PhyloModel	340
9.52.1.5 PhyloPowerSet	341
9.52.1.6 PhyloRule	341
9.52.1.7 PhyloRuleData	341
9.52.1.8 PhyloRuleDyn	341
9.52.1.9 PhyloRules	341
9.52.1.10 PhyloRulesDyn	341
9.52.1.11 PhyloStatsCounter	342
9.52.1.12 PhyloSupport	342
9.53 include/barry/powerset-bones.hpp File Reference	342
9.54 include/barry/powerset-meat.hpp File Reference	343
9.55 include/barry/progress.hpp File Reference	343
9.55.1 Macro Definition Documentation	344
9.55.1.1 BARRY_PROGRESS_BAR_WIDTH	344
9.56 include/barry/rules-bones.hpp File Reference	344
9.56.1 Function Documentation	344
9.56.1.1 rule_fun_default()	345
9.57 include/barry/rules-meat.hpp File Reference	345
9.58 include/barry/statscounter-bones.hpp File Reference	345
9.59 include/barry/statscounter-meat.hpp File Reference	346
9.59.1 Macro Definition Documentation	347
9.59.1.1 STATSCOUNTER_TEMPLATE	347
9.59.1.2 STATSCOUNTER_TEMPLATE_ARGS	347
9.59.1.3 STATSCOUNTER_TYPE	347
9.59.2 Function Documentation	347
9.59.2.1 clear()	347
9.59.2.2 for()	348
9.59.2.3 resize()	348
9.59.2.4 STATSCOUNTER_TEMPLATE() [1/9]	348

9.59.2.5 STATSCOUNTER_TEMPLATE() [2/9]	348
9.59.2.6 STATSCOUNTER_TEMPLATE() [3/9]	348
9.59.2.7 STATSCOUNTER_TEMPLATE() [4/9]	348
9.59.2.8 STATSCOUNTER_TEMPLATE() [5/9]	349
9.59.2.9 STATSCOUNTER_TEMPLATE() [6/9]	349
9.59.2.10 STATSCOUNTER_TEMPLATE() [7/9]	349
9.59.2.11 STATSCOUNTER_TEMPLATE() [8/9]	349
9.59.2.12 STATSCOUNTER_TEMPLATE() [9/9]	349
9.59.3 Variable Documentation	349
9.59.3.1 counter	350
9.59.3.2 counter_deleted	350
9.59.3.3 counters	350
9.59.3.4 counters_	350
9.59.3.5 current_stats	350
9.59.3.6 EmptyArray	351
9.59.3.7 f_	351
9.59.3.8 j	351
9.59.3.9 return	351
9.60 include/barry/support-bones.hpp File Reference	351
9.61 include/barry/support-meat.hpp File Reference	352
9.61.1 Macro Definition Documentation	352
9.61.1.1 BARRY_SUPPORT_MEAT_HPP	352
9.62 include/barry/typedefs.hpp File Reference	353
9.62.1 Typedef Documentation	355
9.62.1.1 Col_type	355
9.62.1.2 Counter_fun_type	355
9.62.1.3 Counts_type	355
9.62.1.4 Hasher_fun_type	355
9.62.1.5 MapVec_type	356
9.62.1.6 Row_type	356
9.62.1.7 Rule_fun_type	356
9.62.2 Function Documentation	356
9.62.2.1 sort_array()	356
9.62.2.2 vec_equal()	357
9.62.2.3 vec_equal_approx()	357
9.62.2.4 vec_inner_prod() [1/2]	358
9.62.2.5 vec_inner_prod() [2/2]	358
9.63 README.md File Reference	358

Chapter 1

Main Page

Barry: your to-go motif accountant

This repository contains a C++ template library that essentially counts sufficient statistics on binary arrays. Its primary goal is to provide a general framework for building discrete exponential-family models. A particular example is Exponential Random Graph Models (ERGMs), but we can use `barry` to deal with non-square arrays.

Among the key features included in `barry`, we have:

- Sparse arrays.
- User-defined count statistics.
- User-defined constrain of the support set.
- Powerset generation of binary arrays.
- Discrete Exponential Family Models module (DEFMs).
- Pooled DEFMs.

To use `barry`, you can either download the entire repository or, since it is header-only, the single header version `barry.hpp`.

This library was created and maintained by Dr. George G. Vega Yon as part of his doctoral dissertation "Essays on Bioinformatics and Social Network Analysis: Statistical and Computational Methods for Complex Systems."

Examples

Counting statistics in a graph

In the following code we create an array of size 5x5 of class `Network` (available in the namespace `netcounters`), add/remove ties, print the graph, and count common statistics used in ERGMs:

```
#include <iostream>
#include <ostream>
#include "../include/barry.hpp"
typedef std::vector< unsigned int > vuint;
int main() {
    // Creating network of size six with five ties
    netcounters::Network net(
        6, 6,
        {0, 0, 4, 4, 2, 0, 1},
        {1, 2, 0, 2, 4, 0, 1}
    );

    // How does this looks like?
    net.print("Current view");

    // Adding extra ties
    net += {1, 0};
    net(2, 0) = true;

    // And removing a couple
    net(0, 0) = false;
    net -= {1, 1};
    net.print("New view");

    // Initializing the data. The program deals with freeing the memory
    net.set_data(new netcounters::NetworkData, true);
    // Creating counter object for the network and adding stats to count
    netcounters::NetStatsCounter counter(&net);
    netcounters::counter_edges(counter.counters);
    netcounters::counter_ttriads(counter.counters);
    netcounters::counter_isolates(counter.counters);
    netcounters::counter_ctriads(counter.counters);
    netcounters::counter_mutual(counter.counters);

    // Counting and printing the results
    std::vector< double > counts = counter.count_all();

    std::cout <<
        "Edges          : " << counts[0] << std::endl <<
        "Transitive triads : " << counts[1] << std::endl <<
        "Isolates         : " << counts[2] << std::endl <<
        "C triads         : " << counts[3] << std::endl <<
        "Mutuals          : " << counts[4] << std::endl;

    return 0;
}
```

Compiling this program using g++

```
g++ -std=c++11 -Wall -pedantic 08-counts.cpp -o counts && ./counts
```

Yields the following output:

```
Current view
[ 0,] 1 1 1 . . .
[ 1,] . 1 . . . .
[ 2,] . . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
New view
[ 0,] . 1 1 . . .
[ 1,] 1 . . . . .
[ 2,] 1 . . . 1 .
[ 3,] . . . . . .
[ 4,] 1 . 1 . . .
[ 5,] . . . . . .
Edges          : 7
Transitive triads : 3
Isolates       : 2
C triads       : 1
Mutuals        : 3
```


Features

Efficient memory usage

One of the key features of `barry` is that it will handle memory efficiently. In the case of pooled-data models, the module for statistical models avoids double-counting support when possible by keeping track of what datasets (networks, for instance) share the same.

Documentation

More information can be found in the Doxygen website [here](#) and in the PDF version of the documentation [here](#).

Code of Conduct

Please note that the `barry` project is released with a [Contributor Code of Conduct](#). By contributing to this project, you agree to abide by its terms.

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Counting	13
Statistical Models	24
Network counters	24
Phylo counters	47
Phylo rules	35

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

BArray< Cell_Type, Data_Type >	59
BArray< bool, bool >	59
BArray< Cell_Type, Data_Type >	59
BArrayCell< Cell_Type, Data_Type >	74
BArrayCell_const< Cell_Type, Data_Type >	76
BArrayDense< Cell_Type, Data_Type >	79
BArrayDense< bool, bool >	79
BArrayDenseCell< Cell_Type, Data_Type >	96
BArrayDenseCell_const< Cell_Type, Data_Type >	100
BArrayDenseCol< Cell_Type, Data_Type >	100
BArrayDenseCol_const< Cell_Type, Data_Type >	102
BArrayDenseRow< Cell_Type, Data_Type >	104
BArrayDenseRow_const< Cell_Type, Data_Type >	107
BArrayRow< Cell_Type, Data_Type >	109
BArrayRow_const< Cell_Type, Data_Type >	111
BArrayVector< Cell_Type, Data_Type >	113
BArrayVector_const< Cell_Type, Data_Type >	117
Cell< Cell_Type >	121
Cell< bool >	121
Cell_const< Cell_Type >	126
ConstBArrayRowIter< Cell_Type, Data_Type >	126
Counter< Array_Type, Data_Type >	128
Counters< Array_Type, Data_Type >	134
Counters< Array_Type, Data_Type >	134
Counters< BArray< bool, bool >, bool >	134
Counters< BArray<>, bool >	134
DEFMCounterData	144
DEFMData	144
DEFMModel	
DEFM	139
DEFMRuleData	146
DEFMRuleDynData	147
Entries< Cell_Type >	148
Flock	150
FreqTable< T >	157

Geese	160
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >	175
NetCounterData	197
NetworkData	199
Node	201
NodeData	207
PhyloCounterData	208
PhyloRuleDynData	211
PowerSet< Array_Type, Data_Rule_Type >	213
Progress	220
Rule< Array_Type, Data_Type >	221
Rules< Array_Type, Data_Type >	224
Rules< BArray< bool, bool >, bool >	224
Rules< BArray<>, bool >	224
StatsCounter< Array_Type, Data_Type >	228
StatsCounter< BArray<>, bool >	228
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >	232
Support< BArray<>, bool, bool, bool >	232
vecHasher< T >	243

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

BArray< Cell_Type, Data_Type >	
Baseline class for binary arrays	59
BArrayCell< Cell_Type, Data_Type >	74
BArrayCell_const< Cell_Type, Data_Type >	76
BArrayDense< Cell_Type, Data_Type >	
Baseline class for binary arrays	79
BArrayDenseCell< Cell_Type, Data_Type >	96
BArrayDenseCell_const< Cell_Type, Data_Type >	100
BArrayDenseCol< Cell_Type, Data_Type >	100
BArrayDenseCol_const< Cell_Type, Data_Type >	102
BArrayDenseRow< Cell_Type, Data_Type >	104
BArrayDenseRow_const< Cell_Type, Data_Type >	107
BArrayRow< Cell_Type, Data_Type >	109
BArrayRow_const< Cell_Type, Data_Type >	111
BArrayVector< Cell_Type, Data_Type >	
Row or column of a BArray	113
BArrayVector_const< Cell_Type, Data_Type >	117
Cell< Cell_Type >	
Entries in BArray . For now, it only has two members:	121
Cell_const< Cell_Type >	126
ConstBArrayRowIter< Cell_Type, Data_Type >	126
Counter< Array_Type, Data_Type >	
A counter function based on change statistics	128
Counters< Array_Type, Data_Type >	
Vector of counters	134
DEFM	139
DEFMCounterData	
Data class used to store arbitrary size_t or double vectors	144
DEFMData	
Data class for DEFM arrays	144
DEFMRuleData	146
DEFMRuleDynData	147
Entries< Cell_Type >	
A wrapper class to store source, target, val from a BArray object	148
Flock	
A Flock is a group of Geese	150

FreqTable< T >	
Frequency table of vectors	157
Geese	
Annotated Phylo Model	160
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >	
General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:	175
NetCounterData	
Data class used to store arbitrary size_t or double vectors	197
NetworkData	
Data class for Networks	199
Node	
A single node for the model	201
NodeData	
Data definition for the PhyloArray class	207
PhyloCounterData	208
PhyloRuleDynData	211
PowerSet< Array_Type, Data_Rule_Type >	
Powerset of a binary array	213
Progress	
A simple progress bar	220
Rule< Array_Type, Data_Type >	
Rule for determining if a cell should be included in a sequence	221
Rules< Array_Type, Data_Type >	
Vector of objects of class Rule	224
StatsCounter< Array_Type, Data_Type >	
Count stats for a single Array	228
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >	
Compute the support of sufficient statistics	232
vecHasher< T >	243

Chapter 5

File Index

5.1 File List

Here is a list of all files with brief descriptions:

include/barry/barray-bones.hpp	245
include/barry/barray-iterator.hpp	245
include/barry/barray-meat-operators.hpp	246
include/barry/barray-meat.hpp	250
include/barry/barraycell-bones.hpp	251
include/barry/barraycell-meat.hpp	252
include/barry/barraydense-bones.hpp	252
include/barry/barraydense-meat-operators.hpp	253
include/barry/barraydense-meat.hpp	256
include/barry/barraydensecell-bones.hpp	257
include/barry/barraydensecell-meat.hpp	258
include/barry/barraydensecol-bones.hpp	259
include/barry/barraydenserow-bones.hpp	260
include/barry/barrayrow-bones.hpp	261
include/barry/barrayrow-meat.hpp	261
include/barry/barrayvector-bones.hpp	263
include/barry/barrayvector-meat.hpp	264
include/barry/barray-configuration.hpp	264
include/barry/barray-debug.hpp	266
include/barry/barray-macros.hpp	267
include/barry/barray.hpp	268
include/barry/cell-bones.hpp	271
include/barry/cell-meat.hpp	272
include/barry/col-bones.hpp	272
include/barry/counters-bones.hpp	272
include/barry/counters-meat.hpp	273
include/barry/freqtable.hpp	300
include/barry/model-bones.hpp	301
include/barry/model-meat.hpp	301
include/barry/powerset-bones.hpp	342
include/barry/powerset-meat.hpp	343
include/barry/progress.hpp	343
include/barry/rules-bones.hpp	344
include/barry/rules-meat.hpp	345
include/barry/statscounter-bones.hpp	345

include/barry/statscounter-meat.hpp	346
include/barry/support-bones.hpp	351
include/barry/support-meat.hpp	352
include/barry/typedefs.hpp	353
include/barry/counters/network-css.hpp	285
include/barry/counters/network.hpp	293
include/barry/models/defm.hpp	320
include/barry/models/geese.hpp	331
include/barry/models/defm/counters.hpp	321
include/barry/models/defm/defm-bones.hpp	326
include/barry/models/defm/defm-meat.hpp	326
include/barry/models/defm/defm-types.hpp	328
include/barry/models/defm/formula.hpp	329
include/barry/models/geese/counters.hpp	324
include/barry/models/geese/flock-bones.hpp	331
include/barry/models/geese/flock-meat.hpp	332
include/barry/models/geese/geese-bones.hpp	332
include/barry/models/geese/geese-meat-constructors.hpp	334
include/barry/models/geese/geese-meat-likelihood.hpp	335
include/barry/models/geese/geese-meat-likelihood_exhaust.hpp	336
include/barry/models/geese/geese-meat-predict.hpp	336
include/barry/models/geese/geese-meat-predict_exhaust.hpp	337
include/barry/models/geese/geese-meat-predict_sim.hpp	337
include/barry/models/geese/geese-meat-simulate.hpp	338
include/barry/models/geese/geese-meat.hpp	338
include/barry/models/geese/geese-node-bones.hpp	339
include/barry/models/geese/geese-types.hpp	339

Chapter 6

Module Documentation

6.1 Counting

Classes

- class [NetworkData](#)
Data class for Networks.
- class [Counter](#)< [Array_Type](#), [Data_Type](#) >
A counter function based on change statistics.

Macros

- `#define MAKE_DEFM_HASHER(hasher, a, cov)`
- `#define MAKE_DUPL_VARS()`
- `#define IS_EITHER() ((DATA_AT == Geese::etype_either)`
- `#define IS_DUPLICATION() ((DATA_AT == Geese::etype_duplication) & (DPL))`
- `#define IS_SPECIATION() ((DATA_AT == Geese::etype_speciation) & (!DPL))`
- `#define IF_MATCHES()`
- `#define IF_NOTMATCHES()`
- `#define PHYLO_COUNTER_LAMBDA(a)`
Extension of a simple counter.
- `#define PHYLO_RULE_DYN_LAMBDA(a)`
- `#define PHYLO_CHECK_MISSING()`
- `std::string get_last_name (size_t d)`
- `void counter_overall_gains (PhyloCounters *counters, size_t duplication=Geese::etype_default)`
Overall functional gains.
- `void counter_gains (PhyloCounters *counters, std::vector< size_t > nfun, size_t duplication=Geese::etype_default)`
Functional gains for a specific function (nfun).
- `void counter_gains_k_offspring (PhyloCounters *counters, std::vector< size_t > nfun, size_t k=1u, size_t duplication=Geese::etype_default)`
k genes gain function nfun
- `void counter_genes_changing (PhyloCounters *counters, size_t duplication=Geese::etype_default)`
Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

- void `counter_preserve_pseudogene` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Keeps track of how many pairs of genes preserve pseudostate.
- void `counter_prop_genes_changing` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)
- void `counter_overall_loss` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Overall functional loss.
- void `counter_maxfuns` (`PhyloCounters *counters`, `size_t lb`, `size_t ub`, `size_t duplication=Geese::etype_default`)
Cap the number of functions per gene.
- void `counter_loss` (`PhyloCounters *counters`, `std::vector< size_t > nfun`, `size_t duplication=Geese::etype_default`)
Total count of losses for an specific function.
- void `counter_overall_changes` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Total number of changes. Use this statistic to account for "preservation".
- void `counter_subfun` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Total count of Sub-functionalization events.
- void `counter_cogain` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Co-evolution (joint gain or loss)
- void `counter_longest` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Longest branch mutates (either by gain or by loss)
- void `counter_neofun` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Total number of neofunctionalization events.
- void `counter_pairwise_neofun_singlefun` (`PhyloCounters *counters`, `size_t nfunA`, `size_t duplication=Geese::etype_default`)
Total number of neofunctionalization events $\sum_u \sum_{w < u} [x(u,a)(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$ change
stat: $\delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void `counter_neofun_a2b` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Total number of neofunctionalization events.
- void `counter_co_opt` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Function co-opting.
- void `counter_k_genes_changing` (`PhyloCounters *counters`, `size_t k`, `size_t duplication=Geese::etype_default`)
Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_less_than_p_prop_genes_changing` (`PhyloCounters *counters`, `double p`, `size_t duplication=Geese::etype_default`)
Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_gains_from_0` (`PhyloCounters *counters`, `std::vector< size_t > nfun`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_overall_gains_from_0` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_overall_change` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_preserving` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_first_gain` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)

6.1.1 Detailed Description

`barry` includes a flexible way to generate counters based on change statistics. Since most of the time we are counting many motifs in a graph, change statistics make a reasonable (and efficient) way to make such counts.

In particular, let the motif be defined as $s(y)$, with y as the binary array. The change statistic when adding cell y_{ij} , i.e. when the cell moves from being empty to have a one, is defined as

$$\delta(y_{ij}) = s_{ij}^+(y) - s_{ij}^-(y),$$

where $s_{ij}^+(y)$ and $s_{ij}^-(y)$ represent the motif statistic with and without the ij -cell. For example, in the case of networks, the change statistic for the number of edges is always 1.

To count statistics in an array, the [\[Counter\]](#) class will empty the array, initialize the counters, and then start counting while adding at each step a single cell, until matching the original array.

6.1.2 Macro Definition Documentation

6.1.2.1 IF_MATCHES

```
#define IF_MATCHES( )
```

Value:

```
MAKE_DUPL_VARS() \
if (IS_EITHER() || IS_DUPLICATION() || IS_SPECIATION())
```

Definition at line 20 of file counters.hpp.

6.1.2.2 IF_NOTMATCHES

```
#define IF_NOTMATCHES( )
```

Value:

```
MAKE_DUPL_VARS() \
if (!IS_EITHER() && !IS_DUPLICATION() && !IS_SPECIATION())
```

Definition at line 22 of file counters.hpp.

6.1.2.3 IS_DUPLICATION

```
#define IS_DUPLICATION( ) ((DATA_AT == Geese::etype_duplication) & (DPL))
```

Definition at line 17 of file counters.hpp.

6.1.2.4 IS_EITHER

```
#define IS_EITHER( ) (DATA_AT == Geese::etype_either)
```

Definition at line 16 of file counters.hpp.

6.1.2.5 IS_SPECIATION

```
#define IS_SPECIATION( ) ((DATA_AT == Geese::etype_speciation) & (!DPL))
```

Definition at line 18 of file counters.hpp.

6.1.2.6 MAKE_DEFM_HASHER

```
#define MAKE_DEFM_HASHER(  
    hasher,  
    a,  
    cov )
```

Value:

```
barry::Hasher_fun_type<DEFMArray,DEFMCounterData> \  
hasher = [cov](const DEFMArray & array, DEFMCounterData * d) { \  
    std::vector< double > res; \  
    /* Adding the column feature */ \  
    for (size_t i = 0u; i < array.nrow(); ++i) \  
        res.push_back(array.D()(i, cov)); \  
    /* Adding the fixed dims */ \  
    for (size_t i = 0u; i < (array.nrow() - 1); ++i) \  
        for (size_t j = 0u; j < array.ncol(); ++j) \  
            res.push_back(array(i, j)); \  
    return res;\  
};
```

Details on the available counters for DEFMworkData can be found in the [Network counters](#) section.

Definition at line 21 of file counters.hpp.

6.1.2.7 MAKE_DUPL_VARS

```
#define MAKE_DUPL_VARS( )
```

Value:

```
bool DPL = Array.D_ptr()->duplication; \  
size_t DATA_AT = data[0u];
```

Details about the available counters for PhyloArray objects can be found in the [Phylo counters](#) section.

Definition at line 12 of file counters.hpp.

6.1.2.8 PHYLO_CHECK_MISSING

```
#define PHYLO_CHECK_MISSING( )
```

Value:

```
if (Array.D_ptr() == nullptr) \
    throw std::logic_error("The array data is nullptr."); \
```

Definition at line 42 of file counters.hpp.

6.1.2.9 PHYLO_COUNTER_LAMBDA

```
#define PHYLO_COUNTER_LAMBDA(  
    a )
```

Value:

```
barry::Counter_fun_type<PhyloArray, PhyloCounterData> a = \
[] (const PhyloArray & Array, size_t i, size_t j, PhyloCounterData & data)
```

Extension of a simple counter.

It allows specifying extra arguments, in particular, the corresponding sets of rows to which this statistic may be relevant. This could be important in the case of, for example, counting correlation type statistics between function 1 and 2, and between function 1 and 3.

Definition at line 36 of file counters.hpp.

6.1.2.10 PHYLO_RULE_DYN_LAMBDA

```
#define PHYLO_RULE_DYN_LAMBDA(  
    a )
```

Value:

```
barry::Rule_fun_type<PhyloArray, PhyloRuleDynData> a = \
[] (const PhyloArray & Array, size_t i, size_t j, PhyloRuleDynData & data)
```

Definition at line 39 of file counters.hpp.

6.1.3 Function Documentation

6.1.3.1 counter_co_opt()

```
void counter_co_opt (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Function co-opting.

Function co-opting of functions A and B happens when, for example, function B is gained as a new featured leveraging what function A already does; without losing function A. The sufficient statistic is defined as follows:

$$x_{pa}(1 - x_{pb}) \sum_{i < j} \left[x_{ia}^p (1 - x_{ib}^p) x_{ja}^p x_{jb}^p + x_{ja}^p (1 - x_{jb}^p) x_{ia}^p x_{ib}^p \right]$$

This algorithm implements the change statistic.

Definition at line 1296 of file counters.hpp.

6.1.3.2 counter_cogain()

```
void counter_cogain (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Co-evolution (joint gain or loss)

Needs to specify pairs of functions (nfunA, nfunB).

Definition at line 791 of file counters.hpp.

6.1.3.3 counter_gains()

```
void counter_gains (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Functional gains for a specific function (nfun).

Definition at line 96 of file counters.hpp.

6.1.3.4 counter_gains_from_0()

```
void counter_gains_from_0 (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1630 of file counters.hpp.

6.1.3.5 counter_gains_k_offspring()

```
void counter_gains_k_offspring (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t k = 1u,
    size_t duplication = Geese::etype_default ) [inline]
```

k genes gain function nfun

Definition at line 156 of file counters.hpp.

6.1.3.6 counter_genes_changing()

```
void counter_genes_changing (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 228 of file counters.hpp.

6.1.3.7 counter_k_genes_changing()

```
void counter_k_genes_changing (
    PhyloCounters * counters,
    size_t k,
    size_t duplication = Geese::etype_default ) [inline]
```

Indicator function. Equals to one if k genes changed and zero otherwise.

Definition at line 1394 of file counters.hpp.

6.1.3.8 counter_less_than_p_prop_genes_changing()

```
void counter_less_than_p_prop_genes_changing (
    PhyloCounters * counters,
    double p,
    size_t duplication = Geese::etype_default ) [inline]
```

Indicator function. Equals to one if k genes changed and zero otherwise.

< How many genes diverge the parent

Definition at line 1514 of file counters.hpp.

6.1.3.9 counter_longest()

```
void counter_longest (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Longest branch mutates (either by gain or by loss)

Definition at line 848 of file counters.hpp.

6.1.3.10 counter_loss()

```
void counter_loss (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Total count of losses for an specific function.

Definition at line 591 of file counters.hpp.

6.1.3.11 counter_maxfuns()

```
void counter_maxfuns (
    PhyloCounters * counters,
    size_t lb,
    size_t ub,
    size_t duplication = Geese::etype_default ) [inline]
```

Cap the number of functions per gene.

Definition at line 529 of file counters.hpp.

6.1.3.12 counter_neofun()

```
void counter_neofun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1018 of file counters.hpp.

6.1.3.13 counter_neofun_a2b()

```
void counter_neofun_a2b (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1163 of file counters.hpp.

6.1.3.14 counter_overall_changes()

```
void counter_overall_changes (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of changes. Use this statistic to account for "preservation".

Definition at line 643 of file counters.hpp.

6.1.3.15 counter_overall_gains()

```
void counter_overall_gains (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Overall functional gains.

Total number of gains (irrespective of the function).

Definition at line 58 of file counters.hpp.

6.1.3.16 counter_overall_gains_from_0()

```
void counter_overall_gains_from_0 (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1696 of file counters.hpp.

6.1.3.17 counter_overall_loss()

```
void counter_overall_loss (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Overall functional loss.

Definition at line 481 of file counters.hpp.

6.1.3.18 counter_pairwise_first_gain()

```
void counter_pairwise_first_gain (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a. $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1948 of file counters.hpp.

6.1.3.19 counter_pairwise_neofun_singlefun()

```
void counter_pairwise_neofun_singlefun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events $\sum_u \sum_{w < u} [x(u,a)*(1-x(w,a)) + (1-x(u,a)) * x(w,a)]$ change stat: $\Delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$

Definition at line 1099 of file counters.hpp.

6.1.3.20 counter_pairwise_overall_change()

```
void counter_pairwise_overall_change (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1744 of file counters.hpp.

6.1.3.21 counter_pairwise_preserving()

```
void counter_pairwise_preserving (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a. $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1809 of file counters.hpp.

6.1.3.22 counter_preserve_pseudogene()

```
void counter_preserve_pseudogene (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many pairs of genes preserve pseudostate.

Definition at line 297 of file counters.hpp.

6.1.3.23 counter_prop_genes_changing()

```
void counter_prop_genes_changing (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 379 of file counters.hpp.

6.1.3.24 counter_subfun()

```
void counter_subfun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total count of Sub-functionalization events.

It requires to specify data = {funA, funB}

Definition at line 702 of file counters.hpp.

6.1.3.25 get_last_name()

```
std::string get_last_name (
    size_t d ) [inline]
```

Definition at line 45 of file counters.hpp.

6.2 Statistical Models

Statistical models available in `barry`.

Classes

- class [Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >](#)
General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:
- class [Flock](#)
A [Flock](#) is a group of [Geese](#).
- class [Geese](#)
Annotated Phylo [Model](#).

6.2.1 Detailed Description

Statistical models available in `barry`.

6.3 Network counters

[Counters](#) for network models.

Functions

- `template<typename Tnet = Network>`
`void counter_edges (NetCounters< Tnet > *counters)`
Number of edges.
- `template<typename Tnet = Network>`
`void counter_isolates (NetCounters< Tnet > *counters)`
Number of isolated vertices.
- `template<> void counter_isolates (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_mutual (NetCounters< Tnet > *counters)`
Number of mutual ties.
- `template<typename Tnet = Network>`
`void counter_istar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_istar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ostar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_ostar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ttriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ttriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ctriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ctriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_density (NetCounters< Tnet > *counters)`
- `template<typename Tnet = Network>`
`void counter_idegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_idegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_odegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_odegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_absdiff (NetCounters< Tnet > *counters, size_t attr_id, double alpha=1.0)`
Sum of absolute attribute difference between ego and alter.
- `template<typename Tnet = Network>`
`void counter_diff (NetCounters< Tnet > *counters, size_t attr_id, double alpha=1.0, double tail_head=true)`
Sum of attribute difference between ego and alter to pow(alpha)
- **NETWORK_COUNTER** (init_single_attr)
- `template<typename Tnet = Network>`
`void counter_nodeicov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodeocov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodcov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodematch (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_idegree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given in-degree.
- `template<> void counter_idegree (NetCounters< NetworkDense > *counters, std::vector< size_t > d)`
- `template<typename Tnet = Network>`
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given out-degree.
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< size_t > d)`

- `template<typename Tnet = Network>`
`void counter_degree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given out-degree.
- `void counter_ones (DEFMCounters *counters, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr)`
Prevalence of ones.
- `void counter_logit_intercept (DEFMCounters *counters, size_t n_y, std::vector< size_t > which={}, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)`
- `void counter_transition (DEFMCounters *counters, std::vector< size_t > coords, std::vector< bool > signs, size_t m_order, size_t n_y, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)`
Prevalence of ones.
- `void counter_transition_formula (DEFMCounters *counters, std::string formula, size_t m_order, size_t n_y, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)`
Prevalence of ones.
- `void counter_fixed_effect (DEFMCounters *counters, int covar_index, double k, std::string vname="", const std::vector< std::string > *x_names=nullptr)`
Prevalence of ones.

Returns true if the cell is free

Parameters

<i>rules</i>	A pointer to a DEFMRules object (<code>Rules<DEFMArray, bool></code>).
--------------	--

- `void rules_markov_fixed (DEFMRules *rules, size_t markov_order)`
Number of edges.
- `void rules_dont_become_zero (DEFMSupport *support, std::vector< size_t > ids)`
Blocks switching a one to zero.

6.3.1 Detailed Description

`Counters` for network models.

Parameters

<i>counters</i>	A pointer to a NetCounters object (<code>Counters<Network, NetCounterData></code>).
<i>counters</i>	A pointer to a DEFMCounters object (<code>Counters<DEFMArray, DEFMCOUNTERData></code>).

6.3.2 Function Documentation

6.3.2.1 counter_absdiff()

```
template<typename Tnet = Network>
void counter_absdiff (
    NetCounters< Tnet > * counters,
    size_t attr_id,
    double alpha = 1.0 ) [inline]
```

Sum of absolute attribute difference between ego and alter.

Definition at line 908 of file network.hpp.

6.3.2.2 counter_ctriads() [1/2]

```
template<>
void counter_ctriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 665 of file network.hpp.

6.3.2.3 counter_ctriads() [2/2]

```
template<typename Tnet = Network>
void counter_ctriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 610 of file network.hpp.

6.3.2.4 counter_degree()

```
template<typename Tnet = Network>
void counter_degree (
    NetCounters< Tnet > * counters,
    std::vector< size_t > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1326 of file network.hpp.

6.3.2.5 counter_density()

```
template<typename Tnet = Network>
void counter_density (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 729 of file network.hpp.

6.3.2.6 counter_diff()

```
template<typename Tnet = Network>
void counter_diff (
    NetCounters< Tnet > * counters,
    size_t attr_id,
    double alpha = 1.0,
    double tail_head = true ) [inline]
```

Sum of attribute difference between ego and alter to pow(alpha)

Definition at line 953 of file network.hpp.

6.3.2.7 counter_edges()

```
template<typename Tnet = Network>
void counter_edges (
    NetCounters< Tnet > * counters ) [inline]
```

Number of edges.

Definition at line 152 of file network.hpp.

6.3.2.8 counter_fixed_effect()

```
void counter_fixed_effect (
    DEFMCounters * counters,
    int covar_index,
    double k,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr ) [inline]
```

Prevalence of ones.

Parameters

<i>counters</i>	Pointer ot a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 610 of file counters.hpp.

6.3.2.9 counter_iddegree() [1/2]

```
template<>
void counter_iddegree (
    NetCounters< NetworkDense > * counters,
    std::vector< size_t > d ) [inline]
```

Definition at line 1170 of file network.hpp.

6.3.2.10 counter_iddegree() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree (
    NetCounters< Tnet > * counters,
    std::vector< size_t > d ) [inline]
```

Counts number of vertices with a given in-degree.

Definition at line 1123 of file network.hpp.

6.3.2.11 counter_iddegree15() [1/2]

```
template<>
void counter_iddegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 785 of file network.hpp.

6.3.2.12 counter_iddegree15() [2/2]

```
template<typename Tnet = Network>
void counter_iddegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 757 of file network.hpp.

6.3.2.13 counter_isolates() [1/2]

```
template<>
void counter_isolates (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 215 of file network.hpp.

6.3.2.14 counter_isolates() [2/2]

```
template<typename Tnet = Network>
void counter_isolates (
    NetCounters< Tnet > * counters ) [inline]
```

Number of isolated vertices.

Definition at line 175 of file network.hpp.

6.3.2.15 counter_istar2() [1/2]

```
template<>
void counter_istar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 338 of file network.hpp.

6.3.2.16 counter_istar2() [2/2]

```
template<typename Tnet = Network>
void counter_istar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 312 of file network.hpp.

6.3.2.17 counter_logit_intercept()

```
void counter_logit_intercept (
    DEFMCounters * counters,
    size_t n_y,
    std::vector< size_t > which = {},
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Definition at line 151 of file counters.hpp.

6.3.2.18 counter_mutual()

```
template<typename Tnet = Network>
void counter_mutual (
    NetCounters< Tnet > * counters ) [inline]
```

Number of mutual ties.

Definition at line 256 of file network.hpp.

6.3.2.19 counter_nodecov()

```
template<typename Tnet = Network>
void counter_nodecov (
    NetCounters< Tnet > * counters,
    size_t attr_id ) [inline]
```

Definition at line 1066 of file network.hpp.

6.3.2.20 counter_nodeicov()

```
template<typename Tnet = Network>
void counter_nodeicov (
    NetCounters< Tnet > * counters,
    size_t attr_id ) [inline]
```

Definition at line 1016 of file network.hpp.

6.3.2.21 counter_nodematch()

```
template<typename Tnet = Network>
void counter_nodematch (
    NetCounters< Tnet > * counters,
    size_t attr_id ) [inline]
```

Definition at line 1091 of file network.hpp.

6.3.2.22 counter_nodeocov()

```
template<typename Tnet = Network>
void counter_nodeocov (
    NetCounters< Tnet > * counters,
    size_t attr_id ) [inline]
```

Definition at line 1041 of file network.hpp.

6.3.2.23 counter_odegree() [1/2]

```
template<>
void counter_odegree (
    NetCounters< NetworkDense > * counters,
    std::vector< size_t > d ) [inline]
```

Definition at line 1271 of file network.hpp.

6.3.2.24 counter_odegree() [2/2]

```
template<typename Tnet = Network>
void counter_odegree (
    NetCounters< Tnet > * counters,
    std::vector< size_t > d ) [inline]
```

Counts number of vertices with a given out-degree.

Definition at line 1223 of file network.hpp.

6.3.2.25 counter_odegree15() [1/2]

```
template<>
void counter_odegree15 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 862 of file network.hpp.

6.3.2.26 counter_odegree15() [2/2]

```
template<typename Tnet = Network>
void counter_odegree15 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 834 of file network.hpp.

6.3.2.27 counter_ones()

```
void counter_ones (
    DEFMCounters * counters,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr ) [inline]
```

Prevalence of ones.

Parameters

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If \geq than 0, then the interaction

Definition at line 81 of file counters.hpp.

6.3.2.28 counter_ostar2() [1/2]

```
template<>
void counter_ostar2 (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 404 of file network.hpp.

6.3.2.29 counter_ostar2() [2/2]

```
template<typename Tnet = Network>
void counter_ostar2 (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 376 of file network.hpp.

6.3.2.30 counter_transition()

```
void counter_transition (
    DEFMCounters * counters,
    std::vector< size_t > coords,
    std::vector< bool > signs,
    size_t m_order,
    size_t n_y,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Prevalence of ones.

Parameters

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If \geq than 0, then the interaction

Definition at line 270 of file counters.hpp.

6.3.2.31 counter_transition_formula()

```
void counter_transition_formula (
    DEFMCounters * counters,
    std::string formula,
    size_t m_order,
    size_t n_y,
    int covar_index = -1,
    std::string vname = "",
    const std::vector< std::string > * x_names = nullptr,
    const std::vector< std::string > * y_names = nullptr ) [inline]
```

Prevalence of ones.

Parameters

<i>counters</i>	Pointer of a vector of counters
<i>covar_index</i>	If >= than 0, then the interaction

Definition at line 579 of file counters.hpp.

6.3.2.32 counter_ttriads() [1/2]

```
template<>
void counter_ttriads (
    NetCounters< NetworkDense > * counters ) [inline]
```

Definition at line 531 of file network.hpp.

6.3.2.33 counter_ttriads() [2/2]

```
template<typename Tnet = Network>
void counter_ttriads (
    NetCounters< Tnet > * counters ) [inline]
```

Definition at line 441 of file network.hpp.

6.3.2.34 NETWORK_COUNTER()

```
NETWORK_COUNTER (
    init_single_attr )
```

Definition at line 997 of file network.hpp.

6.3.2.35 rules_dont_become_zero()

```
void rules_dont_become_zero (
    DEFMSupport * support,
    std::vector< size_t > ids ) [inline]
```

Blocks switching a one to zero.

Parameters

<i>rules</i>	
<i>ids</i>	Ids of the variables that will follow this rule.

Definition at line 678 of file counters.hpp.

6.3.2.36 rules_markov_fixed()

```
void rules_markov_fixed (
    DEFMRules * rules,
    size_t markov_order ) [inline]
```


Number of edges.

Definition at line 653 of file counters.hpp.

6.4 Phylo rules

[Rules](#) for phylogenetic modeling.

Collaboration diagram for Phylo rules:

**Classes**

- class [DEFMRuleDynData](#)

Functions

- [DEFMData::DEFMData](#) ()
Vector indicating which covariates are included in the model.
- [DEFMData::DEFMData](#) ([DEFMArray](#) *array_, const double *covariates_, size_t obs_start_, size_t X_ncol_, size_t X_nrow_)
Constructor.
- double [DEFMData::operator\(\)](#) (size_t i, size_t j) const
Access to the row (i) column (j) data.
- double [DEFMData::at](#) (size_t i, size_t j) const
- size_t [DEFMData::ncol](#) () const
- size_t [DEFMData::nrow](#) () const
- void [DEFMData::print](#) () const
- [DEFMData::~DEFMData](#) ()
- [DEFMCounterData::DEFMCounterData](#) ()
- [DEFMCounterData::DEFMCounterData](#) (const std::vector< size_t > indices_, const std::vector< double > numbers_, const std::vector< bool > logical_, bool is_motif_=true)
- size_t [DEFMCounterData::idx](#) (size_t i) const
- double [DEFMCounterData::num](#) (size_t i) const
- bool [DEFMCounterData::is_true](#) (size_t i) const
- [DEFMCounterData::~DEFMCounterData](#) ()
- double [DEFMRuleData::num](#) (size_t i) const
- size_t [DEFMRuleData::idx](#) (size_t i) const
- bool [DEFMRuleData::is_true](#) (size_t i) const
- [DEFMRuleData::DEFMRuleData](#) ()
- [DEFMRuleData::DEFMRuleData](#) (std::vector< double > numbers_, std::vector< size_t > indices_, std::vector< bool > logical_)
- [DEFMRuleData::DEFMRuleData](#) (std::vector< double > numbers_, std::vector< size_t > indices_)
- [DEFMRuleDynData::DEFMRuleDynData](#) (const std::vector< double > *counts_, std::vector< double > numbers_={}, std::vector< size_t > indices_={}, std::vector< bool > logical_={})
- [DEFMRuleDynData::~DEFMRuleDynData](#) ()
- void [rule_dyn_limit_changes](#) ([PhyloSupport](#) *support, size_t pos, size_t lb, size_t ub, size_t duplication=[Geese::etype_default](#))
Overall functional gains.

Variables

- [DEFMArray](#) * [DEFMData::array](#)
- const double * [DEFMData::covariates](#)
Vector of covariates (complete vector)
- size_t [DEFMData::obs_start](#)
Index of the observation in the data.
- size_t [DEFMData::X_ncol](#)
Number of columns in the array of covariates.
- size_t [DEFMData::X_nrow](#)
Number of rows in the array of covariates.
- std::vector< size_t > [DEFMData::covar_sort](#)
- std::vector< size_t > [DEFMData::covar_used](#)
Value where the sorting of the covariates is stored.
- std::vector< size_t > [DEFMCounterData::indices](#)
- std::vector< double > [DEFMCounterData::numbers](#)
- std::vector< bool > [DEFMCounterData::logical](#)
- bool [DEFMCounterData::is_motif](#)

If false, then is a logit intercept.

- `std::vector< double > DEFMRuleData::numbers`
- `std::vector< size_t > DEFMRuleData::indices`
- `std::vector< bool > DEFMRuleData::logical`
- `bool DEFMRuleData::init = false`
- `const std::vector< double > * DEFMRuleDynData::counts`

Convenient typedefs for network objects.

- `typedef barry::Counter< DEFMArray, DEFMCounterData > DEFMCounter`
- `typedef barry::Counters< DEFMArray, DEFMCounterData > DEFMCounters`
- `typedef barry::Support< DEFMArray, DEFMCounterData, DEFMRuleData, DEFMRuleDynData > DEFMSupport`
- `typedef barry::StatsCounter< DEFMArray, DEFMCounterData > DEFMStatsCounter`
- `typedef barry::Model< DEFMArray, DEFMCounterData, DEFMRuleData, DEFMRuleDynData > DEFMModel`
- `typedef barry::Rule< DEFMArray, DEFMRuleData > DEFMRule`
- `typedef barry::Rules< DEFMArray, DEFMRuleData > DEFMRules`
- `typedef barry::Rule< DEFMArray, DEFMRuleDynData > DEFMRuleDyn`
- `typedef barry::Rules< DEFMArray, DEFMRuleDynData > DEFMRulesDyn`

6.4.1 Detailed Description

[Rules](#) for phylogenetic modeling.

Parameters

<i>rules</i>	A pointer to a <code>PhyloRules</code> object (<code>Rules<PhyloArray, PhyloRuleData></code>).
--------------	--

6.4.2 Typedef Documentation

6.4.2.1 DEFMCounter

```
typedef barry::Counter<DEFMArray, DEFMCounterData > DEFMCounter
```

Definition at line 171 of file `defm-types.hpp`.

6.4.2.2 DEFMCounters

```
typedef barry::Counters<DEFMArray, DEFMCounterData> DEFMCounters
```

Definition at line 172 of file `defm-types.hpp`.

6.4.2.3 DEFMMModel

```
typedef barry::Model<DEFMArray, DEFMCounterData, DEFMRuleData, DEFMRuleDynData> DEFMMModel
```

Definition at line 175 of file defm-types.hpp.

6.4.2.4 DEFMRule

```
typedef barry::Rule<DEFMArray, DEFMRuleData> DEFMRule
```

Definition at line 178 of file defm-types.hpp.

6.4.2.5 DEFMRuleDyn

```
typedef barry::Rule<DEFMArray, DEFMRuleDynData> DEFMRuleDyn
```

Definition at line 180 of file defm-types.hpp.

6.4.2.6 DEFMRules

```
typedef barry::Rules<DEFMArray, DEFMRuleData> DEFMRules
```

Definition at line 179 of file defm-types.hpp.

6.4.2.7 DEFMRulesDyn

```
typedef barry::Rules<DEFMArray, DEFMRuleDynData> DEFMRulesDyn
```

Definition at line 181 of file defm-types.hpp.

6.4.2.8 DEFMStatsCounter

```
typedef barry::StatsCounter<DEFMArray, DEFMCounterData> DEFMStatsCounter
```

Definition at line 174 of file defm-types.hpp.

6.4.2.9 DEFMSupport

```
typedef barry::Support<DEFMArray, DEFMCounterData, DEFMRuleData,DEFMRuleDynData> DEFMSupport
```

Definition at line 173 of file defm-types.hpp.

6.4.3 Function Documentation

6.4.3.1 at()

```
double DEFMData::at (
    size_t i,
    size_t j ) const
```

6.4.3.2 DEFMCounterData() [1/2]

```
DEFMCounterData::DEFMCounterData ( ) [inline]
```

Definition at line 72 of file defm-types.hpp.

6.4.3.3 DEFMCounterData() [2/2]

```
DEFMCounterData::DEFMCounterData (
    const std::vector< size_t > indices_,
    const std::vector< double > numbers_,
    const std::vector< bool > logical_,
    bool is_motif_ = true ) [inline]
```

Definition at line 73 of file defm-types.hpp.

6.4.3.4 DEFMDData() [1/2]

```
DEFMDData::DEFMDData ( ) [inline]
```

Vector indicating which covariates are included in the model.

Definition at line 27 of file defm-types.hpp.

6.4.3.5 DEFMDData() [2/2]

```
DEFMDData::DEFMDData (
    DEFMArray * array_,
    const double * covariates_,
    size_t obs_start_,
    size_t X_ncol_,
    size_t X_nrow_ ) [inline]
```

Constructor.

Parameters

<i>covariates</i> ↔ —	Pointer to the attribute data.
<i>obs_</i> ↔ <i>start_</i>	Location of the current observation in the covariates vector
<i>X_ncol_</i>	Number of columns (covariates.)

Definition at line 36 of file defm-types.hpp.

6.4.3.6 DEFMRuleData() [1/3]

```
DEFMRuleData::DEFMRuleData ( ) [inline]
```

Definition at line 102 of file defm-types.hpp.

6.4.3.7 DEFMRuleData() [2/3]

```
DEFMRuleData::DEFMRuleData (
    std::vector< double > numbers_,
    std::vector< size_t > indices_ ) [inline]
```

Definition at line 110 of file defm-types.hpp.

6.4.3.8 DEFMRuleData() [3/3]

```
DEFMRuleData::DEFMRuleData (
    std::vector< double > numbers_,
    std::vector< size_t > indices_,
    std::vector< bool > logical_ ) [inline]
```

Definition at line 104 of file defm-types.hpp.

6.4.3.9 DEFMRuleDynData()

```
DEFMRuleDynData::DEFMRuleDynData (
    const std::vector< double > * counts_,
    std::vector< double > numbers_ = {},
    std::vector< size_t > indices_ = {},
    std::vector< bool > logical_ = {} ) [inline]
```

Definition at line 156 of file defm-types.hpp.

6.4.3.10 idx() [1/2]

```
size_t DEFMCOUNTERData::idx (
    size_t i ) const [inline]
```

Definition at line 81 of file defm-types.hpp.

6.4.3.11 idx() [2/2]

```
size_t DEFMRULEData::idx (
    size_t i ) const [inline]
```

Definition at line 99 of file defm-types.hpp.

6.4.3.12 is_true() [1/2]

```
bool DEFMCOUNTERData::is_true (
    size_t i ) const [inline]
```

Definition at line 83 of file defm-types.hpp.

6.4.3.13 is_true() [2/2]

```
bool DEFMRULEData::is_true (
    size_t i ) const [inline]
```

Definition at line 100 of file defm-types.hpp.

6.4.3.14 ncol()

```
size_t DEFMDATA::ncol ( ) const [inline]
```

Definition at line 123 of file defm-types.hpp.

6.4.3.15 nrow()

```
size_t DEFMDATA::nrow ( ) const [inline]
```

Definition at line 127 of file defm-types.hpp.

6.4.3.16 num() [1/2]

```
double DEFMCOUNTERData::num (
    size_t i ) const [inline]
```

Definition at line 82 of file defm-types.hpp.

6.4.3.17 num() [2/2]

```
double DEFMRULEData::num (
    size_t i ) const [inline]
```

Definition at line 98 of file defm-types.hpp.

6.4.3.18 operator()()

```
double DEFMDATA::operator() (
    size_t i,
    size_t j ) const [inline]
```

Access to the row (i) column (j) data.

Parameters

<i>i</i>	
<i>j</i>	

Returns

double

Definition at line 118 of file defm-types.hpp.

6.4.3.19 print()

```
void DEFMDATA::print ( ) const [inline]
```

Definition at line 131 of file defm-types.hpp.

6.4.3.20 rule_dyn_limit_changes()

```
void rule_dyn_limit_changes (
    PhyloSupport * support,
    size_t pos,
    size_t lb,
    size_t ub,
    size_t duplication = Geese::etype_default ) [inline]
```

Overall functional gains.

Parameters

<i>support</i>	Support of a model.
<i>pos</i>	Position of the focal statistic.
<i>lb</i>	Lower bound
<i>ub</i>	Upper bound

Returns

(void) adds a rule limiting the support of the model.

Definition at line 2058 of file counters.hpp.

6.4.3.21 ~DEFMCounterData()

```
DEFMCounterData::~DEFMCounterData ( ) [inline]
```

Definition at line 85 of file defm-types.hpp.

6.4.3.22 ~DEFMData()

```
DEFMData::~DEFMData ( ) [inline]
```

Definition at line 58 of file defm-types.hpp.

6.4.3.23 ~DEFMRuleDynData()

```
DEFMRuleDynData::~DEFMRuleDynData ( ) [inline]
```

Definition at line 163 of file defm-types.hpp.

6.4.4 Variable Documentation

6.4.4.1 array

```
DEFMArray* DEFMDData::array
```

Definition at line 19 of file defm-types.hpp.

6.4.4.2 counts

```
const std::vector< double >* DEFMRuleDynData::counts
```

Definition at line 154 of file defm-types.hpp.

6.4.4.3 covar_sort

```
std::vector< size_t > DEFMDData::covar_sort
```

Definition at line 24 of file defm-types.hpp.

6.4.4.4 covar_used

```
std::vector< size_t > DEFMDData::covar_used
```

Value where the sorting of the covariates is stored.

Definition at line 25 of file defm-types.hpp.

6.4.4.5 covariates

```
const double* DEFMDData::covariates
```

Vector of covariates (complete vector)

Definition at line 20 of file defm-types.hpp.

6.4.4.6 indices [1/2]

```
std::vector< size_t > DEFMCOUNTERData::indices
```

Definition at line 67 of file defm-types.hpp.

6.4.4.7 indices [2/2]

```
std::vector< size_t > DEFMRULEData::indices
```

Definition at line 93 of file defm-types.hpp.

6.4.4.8 init

```
bool DEFMRULEData::init = false
```

Definition at line 96 of file defm-types.hpp.

6.4.4.9 is_motif

```
bool DEFMCOUNTERData::is_motif
```

If false, then is a logit intercept.

Definition at line 70 of file defm-types.hpp.

6.4.4.10 logical [1/2]

```
std::vector< bool > DEFMCOUNTERData::logical
```

Definition at line 69 of file defm-types.hpp.

6.4.4.11 logical [2/2]

```
std::vector< bool > DEFMRULEData::logical
```

Definition at line 94 of file defm-types.hpp.

6.4.4.12 numbers [1/2]

```
std::vector< double > DEFMCOUNTERData::numbers
```

Definition at line 68 of file defm-types.hpp.

6.4.4.13 numbers [2/2]

```
std::vector< double > DEFMRULEData::numbers
```

Definition at line 92 of file defm-types.hpp.

6.4.4.14 obs_start

```
size_t DEFMDData::obs_start
```

Index of the observation in the data.

Definition at line 21 of file defm-types.hpp.

6.4.4.15 X_ncol

```
size_t DEFMDData::X_ncol
```

Number of columns in the array of covariates.

Definition at line 22 of file defm-types.hpp.

6.4.4.16 X_nrow

```
size_t DEFMDData::X_nrow
```


Number of rows in the array of covariates.

Definition at line 23 of file defm-types.hpp.

6.5 Phylo counters

[Counters](#) for phylogenetic modeling.

Collaboration diagram for Phylo counters:



Modules

- [Phylo rules](#)

Rules for phylogenetic modeling.

- void [counter_overall_gains](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Overall functional gains.
- void [counter_gains](#) ([PhyloCounters](#) *counters, std::vector< size_t > nfun, size_t duplication=[Geese::etype_default](#))
Functional gains for a specific function (nfun).
- void [counter_gains_k_offspring](#) ([PhyloCounters](#) *counters, std::vector< size_t > nfun, size_t k=1u, size_t duplication=[Geese::etype_default](#))
k genes gain function nfun
- void [counter_genes_changing](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)
- void [counter_preserve_pseudogene](#) ([PhyloCounters](#) *counters, size_t nfunA, size_t nfunB, size_t duplication=[Geese::etype_default](#))
Keeps track of how many pairs of genes preserve pseudostate.
- void [counter_prop_genes_changing](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)
- void [counter_overall_loss](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Overall functional loss.
- void [counter_maxfuns](#) ([PhyloCounters](#) *counters, size_t lb, size_t ub, size_t duplication=[Geese::etype_default](#))
Cap the number of functions per gene.
- void [counter_loss](#) ([PhyloCounters](#) *counters, std::vector< size_t > nfun, size_t duplication=[Geese::etype_default](#))
Total count of losses for an specific function.
- void [counter_overall_changes](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Total number of changes. Use this statistic to account for "preservation".
- void [counter_subfun](#) ([PhyloCounters](#) *counters, size_t nfunA, size_t nfunB, size_t duplication=[Geese::etype_default](#))
Total count of Sub-functionalization events.
- void [counter_cogain](#) ([PhyloCounters](#) *counters, size_t nfunA, size_t nfunB, size_t duplication=[Geese::etype_default](#))
Co-evolution (joint gain or loss)
- void [counter_longest](#) ([PhyloCounters](#) *counters, size_t duplication=[Geese::etype_default](#))
Longest branch mutates (either by gain or by loss)
- void [counter_neofun](#) ([PhyloCounters](#) *counters, size_t nfunA, size_t nfunB, size_t duplication=[Geese::etype_default](#))
Total number of neofunctionalization events.

- void `counter_pairwise_neofun_singlefun` (`PhyloCounters *counters`, `size_t nfunA`, `size_t duplication=Geese::etype_default`)
Total number of neofunctionalization events $\sum_u \sum_{\{w < u\}} [x(u,a)(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$ change stat: $\Delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void `counter_neofun_a2b` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Total number of neofunctionalization events.
- void `counter_co_opt` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Function co-opting.
- void `counter_k_genes_changing` (`PhyloCounters *counters`, `size_t k`, `size_t duplication=Geese::etype_default`)
Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_less_than_p_prop_genes_changing` (`PhyloCounters *counters`, `double p`, `size_t duplication=Geese::etype_default`)
Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_gains_from_0` (`PhyloCounters *counters`, `std::vector< size_t > nfun`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_overall_gains_from_0` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_overall_change` (`PhyloCounters *counters`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_preserving` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_first_gain` (`PhyloCounters *counters`, `size_t nfunA`, `size_t nfunB`, `size_t duplication=Geese::etype_default`)
Used when all the functions are in 0 (like the root node prob.)

6.5.1 Detailed Description

`Counters` for phylogenetic modeling.

Parameters

<code>counters</code>	A pointer to a <code>PhyloCounters</code> object (<code>Counters<PhyloArray, PhyloCounterData></code>).
-----------------------	---

6.5.2 Function Documentation

6.5.2.1 counter_co_opt()

```
void counter_co_opt (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Function co-opting.

Function co-opting of functions A and B happens when, for example, function B is gained as a new featured leveraging what function A already does; without losing function A. The sufficient statistic is defined as follows:

$$x_{pa}(1 - x_{pb}) \sum_{i < j} \left[x_{ia}^p (1 - x_{ib}^p) x_{ja}^p x_{jb}^p + x_{ja}^p (1 - x_{jb}^p) x_{ia}^p x_{ib}^p \right]$$

This algorithm implements the change statistic.

Definition at line 1296 of file counters.hpp.

6.5.2.2 counter_cogain()

```
void counter_cogain (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Co-evolution (joint gain or loss)

Needs to specify pairs of functions (nfunA, nfunB).

Definition at line 791 of file counters.hpp.

6.5.2.3 counter_gains()

```
void counter_gains (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Functional gains for a specific function (nfun).

Definition at line 96 of file counters.hpp.

6.5.2.4 counter_gains_from_0()

```
void counter_gains_from_0 (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1630 of file counters.hpp.

6.5.2.5 counter_gains_k_offspring()

```
void counter_gains_k_offspring (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t k = 1u,
    size_t duplication = Geese::etype_default ) [inline]
```

k genes gain function nfun

Definition at line 156 of file counters.hpp.

6.5.2.6 counter_genes_changing()

```
void counter_genes_changing (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 228 of file counters.hpp.

6.5.2.7 counter_k_genes_changing()

```
void counter_k_genes_changing (
    PhyloCounters * counters,
    size_t k,
    size_t duplication = Geese::etype_default ) [inline]
```

Indicator function. Equals to one if k genes changed and zero otherwise.

Definition at line 1394 of file counters.hpp.

6.5.2.8 counter_less_than_p_prop_genes_changing()

```
void counter_less_than_p_prop_genes_changing (
    PhyloCounters * counters,
    double p,
    size_t duplication = Geese::etype_default ) [inline]
```

Indicator function. Equals to one if k genes changed and zero otherwise.

< How many genes diverge the parent

Definition at line 1514 of file counters.hpp.

6.5.2.9 counter_longest()

```
void counter_longest (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Longest branch mutates (either by gain or by loss)

Definition at line 848 of file counters.hpp.

6.5.2.10 counter_loss()

```
void counter_loss (
    PhyloCounters * counters,
    std::vector< size_t > nfun,
    size_t duplication = Geese::etype_default ) [inline]
```

Total count of losses for an specific function.

Definition at line 591 of file counters.hpp.

6.5.2.11 counter_maxfuns()

```
void counter_maxfuns (
    PhyloCounters * counters,
    size_t lb,
    size_t ub,
    size_t duplication = Geese::etype_default ) [inline]
```

Cap the number of functions per gene.

Definition at line 529 of file counters.hpp.

6.5.2.12 counter_neofun()

```
void counter_neofun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1018 of file counters.hpp.

6.5.2.13 counter_neofun_a2b()

```
void counter_neofun_a2b (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events.

Needs to specify pairs of function.

Definition at line 1163 of file counters.hpp.

6.5.2.14 counter_overall_changes()

```
void counter_overall_changes (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of changes. Use this statistic to account for "preservation".

Definition at line 643 of file counters.hpp.

6.5.2.15 counter_overall_gains()

```
void counter_overall_gains (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Overall functional gains.

Total number of gains (irrespective of the function).

Definition at line 58 of file counters.hpp.

6.5.2.16 counter_overall_gains_from_0()

```
void counter_overall_gains_from_0 (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1696 of file counters.hpp.

6.5.2.17 counter_overall_loss()

```
void counter_overall_loss (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Overall functional loss.

Definition at line 481 of file counters.hpp.

6.5.2.18 counter_pairwise_first_gain()

```
void counter_pairwise_first_gain (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a. $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1948 of file counters.hpp.

6.5.2.19 counter_pairwise_neofun_singlefun()

```
void counter_pairwise_neofun_singlefun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t duplication = Geese::etype_default ) [inline]
```

Total number of neofunctionalization events $\sum_u \sum_{w < u} [x(u,a)*(1-x(w,a)) + (1-x(u,a)) * x(w,a)]$ change stat: $\Delta x(u,a): 0 \rightarrow 1 = 1 - 2 * x(w,a)$

Definition at line 1099 of file counters.hpp.

6.5.2.20 counter_pairwise_overall_change()

```
void counter_pairwise_overall_change (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a.

Definition at line 1744 of file counters.hpp.

6.5.2.21 counter_pairwise_preserving()

```
void counter_pairwise_preserving (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Used when all the functions are in 0 (like the root node prob.)

Needs to specify function a. $\sum x(a)^3(1-x(b))^3 + x(b)^3(1-x(a))^3 + x(a)^3 * x(b)^3 + (1-x(a))^3 * (1-x(b))^3$

Definition at line 1809 of file counters.hpp.

6.5.2.22 counter_preserve_pseudogene()

```
void counter_preserve_pseudogene (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many pairs of genes preserve pseudostate.

Definition at line 297 of file counters.hpp.

6.5.2.23 counter_prop_genes_changing()

```
void counter_prop_genes_changing (
    PhyloCounters * counters,
    size_t duplication = Geese::etype_default ) [inline]
```

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)

Definition at line 379 of file counters.hpp.

6.5.2.24 counter_subfun()

```
void counter_subfun (
    PhyloCounters * counters,
    size_t nfunA,
    size_t nfunB,
    size_t duplication = Geese::etype_default ) [inline]
```

Total count of Sub-functionalization events.

It requires to specify data = {funA, funB}

Definition at line 702 of file counters.hpp.

Chapter 7

Namespace Documentation

7.1 `barry` Namespace Reference

`barry`: Your go-to motif accountant

Namespaces

- [counters](#)

Tree class and Treeliterator class.

7.1.1 Detailed Description

`barry`: Your go-to motif accountant

7.2 `barry::counters` Namespace Reference

Tree class and Treeliterator class.

Namespaces

- [network](#)

7.2.1 Detailed Description

Tree class and Treeliterator class.

7.3 barry::counters::network Namespace Reference

7.4 CHECK Namespace Reference

Integer constants used to specify which cell should be check.

Variables

- const int BOTH = -1
- const int NONE = 0
- const int ONE = 1
- const int TWO = 2

7.4.1 Detailed Description

Integer constants used to specify which cell should be check.

7.4.2 Variable Documentation

7.4.2.1 BOTH

```
const int CHECK::BOTH = -1
```

Definition at line 27 of file typedefs.hpp.

7.4.2.2 NONE

```
const int CHECK::NONE = 0
```

Definition at line 28 of file typedefs.hpp.

7.4.2.3 ONE

```
const int CHECK::ONE = 1
```

Definition at line 29 of file typedefs.hpp.

7.4.2.4 TWO

```
const int CHECK::TWO = 2
```

Definition at line 30 of file typedefs.hpp.

7.5 defm Namespace Reference

7.6 EXISTS Namespace Reference

Integer constants used to specify which cell should be check to exist or not.

Variables

- const int BOTH = -1
- const int NONE = 0
- const int ONE = 1
- const int TWO = 1
- const int UNKNOWN = -1
- const int AS_ZERO = 0
- const int AS_ONE = 1

7.6.1 Detailed Description

Integer constants used to specify which cell should be check to exist or not.

7.6.2 Variable Documentation

7.6.2.1 AS_ONE

```
const int EXISTS::AS_ONE = 1
```

Definition at line 45 of file typedefs.hpp.

7.6.2.2 AS_ZERO

```
const int EXISTS::AS_ZERO = 0
```

Definition at line 44 of file typedefs.hpp.

7.6.2.3 BOTH

```
const int EXISTS::BOTH = -1
```

Definition at line 38 of file typedefs.hpp.

7.6.2.4 NONE

```
const int EXISTS::NONE = 0
```

Definition at line 39 of file typedefs.hpp.

7.6.2.5 ONE

```
const int EXISTS::ONE = 1
```

Definition at line 40 of file typedefs.hpp.

7.6.2.6 TWO

```
const int EXISTS::TWO = 1
```

Definition at line 41 of file typedefs.hpp.

7.6.2.7 UNKNOWN

```
const int EXISTS::UNKNOWN = -1
```

Definition at line 43 of file typedefs.hpp.

7.7 geese Namespace Reference

Chapter 8

Class Documentation

8.1 BArray< Cell_Type, Data_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barray-bones.hpp>
```

Public Member Functions

- bool `operator==` (const `BArray`< `Cell_Type`, `Data_Type` > &`Array_`)
- `~BArray` ()
- void `out_of_range` (size_t `i`, size_t `j`) const
- `Cell_Type` `get_cell` (size_t `i`, size_t `j`, bool `check_bounds=true`) const
- std::vector< `Cell_Type` > `get_col_vec` (size_t `i`, bool `check_bounds=true`) const
- std::vector< `Cell_Type` > `get_row_vec` (size_t `i`, bool `check_bounds=true`) const
- void `get_col_vec` (std::vector< `Cell_Type` > *`x`, size_t `i`, bool `check_bounds=true`) const
- void `get_row_vec` (std::vector< `Cell_Type` > *`x`, size_t `i`, bool `check_bounds=true`) const
- const `Row_type`< `Cell_Type` > & `row` (size_t `i`, bool `check_bounds=true`) const
- const `Col_type`< `Cell_Type` > & `col` (size_t `i`, bool `check_bounds=true`) const
- `Entries`< `Cell_Type` > `get_entries` () const
 - Get the edgelist.*
- void `transpose` ()
- void `clear` (bool `hard=true`)
- void `resize` (size_t `N_`, size_t `M_`)
- void `reserve` ()
- void `print` (const char *`fmt=nullptr`,...) const
- void `print_n` (size_t `nrow`, size_t `ncol`, const char *`fmt=nullptr`,...) const
- bool `is_dense` () const `noexcept`

Constructors

Parameters

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An size_t vector ranging from 0 to M_
target	When true tries to add repeated observations.

- **BArray** ()
Zero-size array.
 - **BArray** (size_t N_, size_t M_)
Empty array.
 - **BArray** (size_t N_, size_t M_, const std::vector< size_t > &source, const std::vector< size_t > &target, const std::vector< Cell_Type > &value, bool add=true)
Edgelist with data.
 - **BArray** (size_t N_, size_t M_, const std::vector< size_t > &source, const std::vector< size_t > &target, bool add=true)
Edgelist with no data (simpler)
 - **BArray** (const **BArray**< Cell_Type, Data_Type > &Array_, bool copy_data=false)
Copy constructor.
 - **BArray**< Cell_Type, Data_Type > & **operator=** (const **BArray**< Cell_Type, Data_Type > &Array_)
Assignment constructor.
 - **BArray** (**BArray**< Cell_Type, Data_Type > &&x) **noexcept**
Move operator.
 - **BArray**< Cell_Type, Data_Type > & **operator=** (**BArray**< Cell_Type, Data_Type > &&x) **noexcept**
Move assignment.
-
- void **set_data** (Data_Type *data_, bool delete_data_=false)
Set the data object.
 - Data_Type * **D_ptr** ()
 - const Data_Type * **D_ptr** () const
 - Data_Type & **D** ()
 - const Data_Type & **D** () const
 - void **flush_data** ()

Queries

is_empty queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

Parameters

i,j	<i>Coordinates</i>
check_bounds	<i>If false avoids checking bounds.</i>

- bool **is_empty** (size_t i, size_t j, bool check_bounds=true) const
- size_t **nrow** () const **noexcept**
- size_t **ncol** () const **noexcept**
- size_t **nnozero** () const **noexcept**
- **Cell**< Cell_Type > **default_val** () const

Cell-wise insertion/deletion

Parameters

i,j	<i>Row,column</i>
check_bounds	<i>When true and out of range, the function throws an error.</i>
check_exists	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of swap_cells, check if either of both cells exists/don't exist.</i>

- `BArray< Cell_Type, Data_Type > & operator+=` (const std::pair< size_t, size_t > &coords)
- `BArray< Cell_Type, Data_Type > & operator-=` (const std::pair< size_t, size_t > &coords)
- `BArrayCell< Cell_Type, Data_Type > operator()` (size_t i, size_t j, bool check_bounds=true)
- `const Cell_Type operator()` (size_t i, size_t j, bool check_bounds=true) const
- `void rm_cell` (size_t i, size_t j, bool check_bounds=true, bool check_exists=true)
- `void insert_cell` (size_t i, size_t j, const Cell< Cell_Type > &v, bool check_bounds, bool check_exists)
- `void insert_cell` (size_t i, size_t j, Cell< Cell_Type > &&v, bool check_bounds, bool check_exists)
- `void insert_cell` (size_t i, size_t j, Cell_Type v, bool check_bounds, bool check_exists)
- `void swap_cells` (size_t i0, size_t j0, size_t i1, size_t j1, bool check_bounds=true, int check_exists=CHECK::BOTH, int *report=nullptr)
- `void toggle_cell` (size_t i, size_t j, bool check_bounds=true, int check_exists=EXISTS::UNKNOWN)
- `void toggle_lock` (size_t i, size_t j, bool check_bounds=true)

Column/row wise interchange

- `void swap_rows` (size_t i0, size_t i1, bool check_bounds=true)
- `void swap_cols` (size_t j0, size_t j1, bool check_bounds=true)
- `void zero_row` (size_t i, bool check_bounds=true)
- `void zero_col` (size_t j, bool check_bounds=true)

Arithmetic operators

- `BArray< Cell_Type, Data_Type > & operator+=` (const BArray< Cell_Type, Data_Type > &rhs)
- `BArray< Cell_Type, Data_Type > & operator+=` (const Cell_Type &rhs)
- `BArray< Cell_Type, Data_Type > & operator-=` (const BArray< Cell_Type, Data_Type > &rhs)
- `BArray< Cell_Type, Data_Type > & operator-=` (const Cell_Type &rhs)
- `BArray< Cell_Type, Data_Type > & operator/=` (const Cell_Type &rhs)
- `BArray< Cell_Type, Data_Type > & operator*=` (const Cell_Type &rhs)

Public Attributes

- bool `visited` = false

Friends

- class `BArrayCell< Cell_Type, Data_Type >`
- class `BArrayCell_const< Cell_Type, Data_Type >`

8.1.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArray< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

`BArray` class objects are arbitrary arrays in which non-empty cells hold data of type `Cell_Type`. The non-empty cells are stored by row and indexed using `unordered_maps`, i.e. `std::vector< std::unordered_map<size_t, Cell_Type> >`.

Template Parameters

<code>Cell_Type</code>	Type of cell (any type).
<code>Data_Type</code>	Data type of the array (bool default).

Definition at line 28 of file `barray-bones.hpp`.

8.1.2 Constructor & Destructor Documentation

8.1.2.1 BArray() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray ( ) [inline]
```

Zero-size array.

Definition at line 69 of file `barray-bones.hpp`.

8.1.2.2 BArray() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    size_t N_,
    size_t M_ ) [inline]
```

Empty array.

Definition at line 72 of file `barray-bones.hpp`.

8.1.2.3 BArray() [3/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    size_t N_,
    size_t M_,
    const std::vector< size_t > & source,
    const std::vector< size_t > & target,
    const std::vector< Cell_Type > & value,
    bool add = true )
```

Edgelist with data.

8.1.2.4 BArray() [4/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    size_t N_,
    size_t M_,
    const std::vector< size_t > & source,
    const std::vector< size_t > & target,
    bool add = true )
```

Edgelist with no data (simpler)

8.1.2.5 BArray() [5/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    const BArray< Cell_Type, Data_Type > & Array_,
    bool copy_data = false )
```

Copy constructor.

8.1.2.6 BArray() [6/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::BArray (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move operator.

8.1.2.7 ~BArray()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray< Cell_Type, Data_Type >::~~BArray ( )
```

8.1.3 Member Function Documentation

8.1.3.1 clear()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::clear (
    bool hard = true )
```

8.1.3.2 col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Col_type< Cell_Type >& BArray< Cell_Type, Data_Type >::col (
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.3 D() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type& BArray< Cell_Type, Data_Type >::D ( )
```

8.1.3.4 D() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type& BArray< Cell_Type, Data_Type >::D ( ) const
```

8.1.3.5 D_ptr() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( )
```

8.1.3.6 D_ptr() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Data_Type* BArray< Cell_Type, Data_Type >::D_ptr ( ) const
```

8.1.3.7 default_val()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell<Cell_Type> BArray< Cell_Type, Data_Type >::default_val ( ) const
```

8.1.3.8 flush_data()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::flush_data ( )
```

8.1.3.9 get_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Cell_Type BArray< Cell_Type, Data_Type >::get_cell (
    size_t i,
    size_t j,
    bool check_bounds = true ) const
```

8.1.3.10 get_col_vec() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_col_vec (
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.11 get_col_vec() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.12 get_entries()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Entries<Cell_Type> BArray< Cell_Type, Data_Type >::get_entries ( ) const
```

Get the edgelist.

[Entries](#) is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

Returns

`Entries<Cell_Type>`

8.1.3.13 get_row_vec() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type > BArray< Cell_Type, Data_Type >::get_row_vec (
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.14 get_row_vec() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.15 insert_cell() [1/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    size_t i,
    size_t j,
    Cell< Cell_Type > && v,
    bool check_bounds,
    bool check_exists )
```

8.1.3.16 insert_cell() [2/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    size_t i,
    size_t j,
    Cell_Type v,
    bool check_bounds,
    bool check_exists )
```

8.1.3.17 insert_cell() [3/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::insert_cell (
    size_t i,
    size_t j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool check_exists )
```

8.1.3.18 is_dense()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 241 of file `barray-bones.hpp`.

8.1.3.19 is_empty()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::is_empty (
    size_t i,
    size_t j,
    bool check_bounds = true ) const
```

8.1.3.20 ncol()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArray< Cell_Type, Data_Type >::ncol ( ) const [noexcept]
```

8.1.3.21 nnozero()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArray< Cell_Type, Data_Type >::nnozero ( ) const [noexcept]
```

8.1.3.22 nrow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArray< Cell_Type, Data_Type >::nrow ( ) const [noexcept]
```

8.1.3.23 operator()() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell<Cell_Type,Data_Type> BArray< Cell_Type, Data_Type >::operator() (
    size_t i,
    size_t j,
    bool check_bounds = true )
```

8.1.3.24 operator()() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Cell_Type BArray< Cell_Type, Data_Type >::operator() (
    size_t i,
    size_t j,
    bool check_bounds = true ) const
```

8.1.3.25 operator*=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

8.1.3.26 operator+=() [1/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

8.1.3.27 operator+=() [2/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & rhs )
```

8.1.3.28 operator+=() [3/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator+= (
    const std::pair< size_t, size_t > & coords )
```

8.1.3.29 operator-=() [1/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const BArray< Cell_Type, Data_Type > & rhs )
```

8.1.3.30 operator-=() [2/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & rhs )
```

8.1.3.31 operator-=() [3/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator-= (
    const std::pair< size_t, size_t > & coords )
```

8.1.3.32 operator/=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & rhs )
```

8.1.3.33 operator=() [1/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    BArray< Cell_Type, Data_Type > && x ) [noexcept]
```

Move assignment.

8.1.3.34 operator=() [2/2]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArray<Cell_Type,Data_Type>& BArray< Cell_Type, Data_Type >::operator= (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

Assignment constructor.

8.1.3.35 operator==()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::operator== (
    const BArray< Cell_Type, Data_Type > & Array_ )
```

8.1.3.36 out_of_range()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::out_of_range (
    size_t i,
    size_t j ) const
```

8.1.3.37 print()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const
```

8.1.3.38 print_n()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::print_n (
    size_t nrow,
    size_t ncol,
    const char * fmt = nullptr,
    ... ) const
```

8.1.3.39 reserve()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::reserve ( )
```

8.1.3.40 resize()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::resize (
    size_t N_,
    size_t M_ )
```

8.1.3.41 rm_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::rm_cell (
    size_t i,
    size_t j,
    bool check_bounds = true,
    bool check_exists = true )
```

8.1.3.42 row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const Row_type< Cell_Type >& BArray< Cell_Type, Data_Type >::row (
    size_t i,
    bool check_bounds = true ) const
```

8.1.3.43 set_data()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false )
```

Set the data object.

Parameters

<i>data_</i>	
<i>delete_ ↔ data_</i>	

8.1.3.44 swap_cells()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cells (
    size_t i0,
    size_t j0,
    size_t i1,
    size_t j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr )
```

8.1.3.45 swap_cols()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_cols (
    size_t j0,
    size_t j1,
    bool check_bounds = true )
```

8.1.3.46 swap_rows()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::swap_rows (
    size_t i0,
    size_t i1,
    bool check_bounds = true )
```

8.1.3.47 toggle_cell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_cell (
    size_t i,
    size_t j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN )
```

8.1.3.48 toggle_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::toggle_lock (
    size_t i,
    size_t j,
    bool check_bounds = true )
```

8.1.3.49 transpose()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::transpose ( )
```

8.1.3.50 zero_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_col (
    size_t j,
    bool check_bounds = true )
```

8.1.3.51 zero_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArray< Cell_Type, Data_Type >::zero_row (
    size_t i,
    bool check_bounds = true )
```

8.1.4 Friends And Related Function Documentation

8.1.4.1 BArrayCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barray-bones.hpp.

8.1.4.2 BArrayCell_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barray-bones.hpp.

8.1.5 Member Data Documentation

8.1.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArray< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if cell.visited = true and visited = true, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 54 of file barray-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/barray-bones.hpp](#)

8.2 BArrayCell< Cell_Type, Data_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

Public Member Functions

- [BArrayCell](#) ([BArray](#)< Cell_Type, Data_Type > *Array_, size_t i_, size_t j_, bool check_bounds=true)
- [~BArrayCell](#) ()
- void [operator=](#) (const Cell_Type &val)
- void [operator+=](#) (const Cell_Type &val)
- void [operator-=](#) (const Cell_Type &val)
- void [operator*=](#) (const Cell_Type &val)
- void [operator/=](#) (const Cell_Type &val)
- [operator Cell_Type](#) () const
- bool [operator==](#) (const Cell_Type &val) const

8.2.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell< Cell_Type, Data_Type >
```

Definition at line 7 of file barraycell-bones.hpp.

8.2.2 Constructor & Destructor Documentation

8.2.2.1 BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::BArrayCell (
    BArray< Cell_Type, Data_Type > * Array_,
    size_t i_,
    size_t j_,
    bool check_bounds = true ) [inline]
```

Definition at line 16 of file barraycell-bones.hpp.

8.2.2.2 ~BArrayCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell< Cell_Type, Data_Type >::~BArrayCell ( ) [inline]
```

Definition at line 31 of file barraycell-bones.hpp.

8.2.3 Member Function Documentation

8.2.3.1 operator Cell_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 58 of file barraycell-meat.hpp.

8.2.3.2 operator*=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 40 of file barraycell-meat.hpp.

8.2.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 18 of file barraycell-meat.hpp.

8.2.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 29 of file barraycell-meat.hpp.

8.2.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 49 of file barraycell-meat.hpp.

8.2.3.6 operator=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 7 of file barraycell-meat.hpp.

8.2.3.7 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 63 of file barraycell-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/barray-bones.hpp
- include/barry/barraycell-bones.hpp
- include/barry/barraycell-meat.hpp
- include/barry/barrayrow-meat.hpp

8.3 BArrayCell_const< Cell_Type, Data_Type > Class Template Reference

```
#include <barraycell-bones.hpp>
```

Public Member Functions

- [BArrayCell_const](#) (const [BArray](#)< Cell_Type, Data_Type > *Array_, size_t i_, size_t j_, bool check_↔ bounds=true)
- [~BArrayCell_const](#) ()
- [operator Cell_Type](#) () const
- bool [operator==](#) (const Cell_Type &val) const
- bool [operator!=](#) (const Cell_Type &val) const
- bool [operator<](#) (const Cell_Type &val) const
- bool [operator>](#) (const Cell_Type &val) const
- bool [operator<=](#) (const Cell_Type &val) const
- bool [operator>=](#) (const Cell_Type &val) const

8.3.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayCell_const< Cell_Type, Data_Type >
```

Definition at line 46 of file barraycell-bones.hpp.

8.3.2 Constructor & Destructor Documentation

8.3.2.1 BArrayCell_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::BArrayCell_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    size_t i_,
    size_t j_,
    bool check_bounds = true ) [inline]
```

Definition at line 55 of file barraycell-bones.hpp.

8.3.2.2 ~BArrayCell_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayCell_const< Cell_Type, Data_Type >::~~BArrayCell_const ( ) [inline]
```

Definition at line 67 of file barraycell-bones.hpp.

8.3.3 Member Function Documentation

8.3.3.1 operator Cell_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayCell_const< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 68 of file barraycell-meat.hpp.

8.3.3.2 operator"!=(

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator!=(
    const Cell_Type & val ) const [inline]
```

Definition at line 78 of file barraycell-meat.hpp.

8.3.3.3 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 83 of file barraycell-meat.hpp.

8.3.3.4 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 93 of file barraycell-meat.hpp.

8.3.3.5 operator==(())

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator==(
    const Cell_Type & val ) const [inline]
```

Definition at line 73 of file barraycell-meat.hpp.

8.3.3.6 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 88 of file barraycell-meat.hpp.

8.3.3.7 operator>=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayCell_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 98 of file barraycell-meat.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barray-bones.hpp](#)
- [include/barry/barraycell-bones.hpp](#)
- [include/barry/barraycell-meat.hpp](#)
- [include/barry/barrayrow-meat.hpp](#)

8.4 BArrayDense< Cell_Type, Data_Type > Class Template Reference

Baseline class for binary arrays.

```
#include <barraydense-bones.hpp>
```

Public Member Functions

- bool `operator==` (const BArrayDense< Cell_Type, Data_Type > &Array_)
 - `~BArrayDense` ()
 - void `out_of_range` (size_t i, size_t j) const
 - Cell_Type `get_cell` (size_t i, size_t j, bool check_bounds=true) const
 - std::vector< Cell_Type > `get_col_vec` (size_t i, bool check_bounds=true) const
 - std::vector< Cell_Type > `get_row_vec` (size_t i, bool check_bounds=true) const
 - void `get_col_vec` (std::vector< Cell_Type > *x, size_t i, bool check_bounds=true) const
 - void `get_row_vec` (std::vector< Cell_Type > *x, size_t i, bool check_bounds=true) const
 - BArrayDenseRow< Cell_Type, Data_Type > & `row` (size_t i, bool check_bounds=true)
 - const BArrayDenseRow_const< Cell_Type, Data_Type > `row` (size_t i, bool check_bounds=true) const
 - BArrayDenseCol< Cell_Type, Data_Type > & `col` (size_t j, bool check_bounds=true)
 - const BArrayDenseCol_const< Cell_Type, Data_Type > `col` (size_t j, bool check_bounds=true) const
 - Entries< Cell_Type > `get_entries` () const
- Get the edgelist.*
- void `transpose` ()
 - void `clear` (bool hard=true)
 - void `resize` (size_t N_, size_t M_)
 - void `reserve` ()
 - void `print` (const char *fmt=nullptr,...) const
 - bool `is_dense` () const noexcept
 - const std::vector< Cell_Type > & `get_data` () const
 - const Cell_Type `rowsum` (size_t i) const
 - const Cell_Type `colsum` (size_t i) const

Constructors

Parameters

N_	Number of rows
M_	Number of columns
source	An unsigned vector ranging from 0 to N_
target	An size_t vector ranging from 0 to M_
target	When <code>true</code> tries to add repeated observations.
value	Cell_Type default fill-in value (zero, by default.)

- BArrayDense ()
- *Zero-size array.*
- BArrayDense (size_t N_, size_t M_, Cell_Type value=static_cast< Cell_Type >(0))
- *Empty array.*
- BArrayDense (size_t N_, size_t M_, const std::vector< size_t > &source, const std::vector< size_t > &target, const std::vector< Cell_Type > &value, bool add=true)
- *Edgelist with data.*
- BArrayDense (size_t N_, size_t M_, const std::vector< size_t > &source, const std::vector< size_t > &target, bool add=true)

Edgelist with no data (simpler)

- `BArrayDense` (const `BArrayDense`< Cell_Type, Data_Type > &Array_, bool copy_data=false)
Copy constructor.
- `BArrayDense`< Cell_Type, Data_Type > & `operator=` (const `BArrayDense`< Cell_Type, Data_Type > &Array_)
Assignment constructor.
- `BArrayDense` (`BArrayDense`< Cell_Type, Data_Type > &&x) `noexcept`
Move operator.
- `BArrayDense`< Cell_Type, Data_Type > & `operator=` (`BArrayDense`< Cell_Type, Data_Type > &&x) `noexcept`
Move assignment.

- void `set_data` (Data_Type *data_, bool delete_data_=false)

Set the data object.

- Data_Type * `D_ptr` ()
- const Data_Type * `D_ptr` () const
- Data_Type & `D` ()
- const Data_Type & `D` () const

Queries

is_empty queries a single cell. *nrow*, *ncol*, and *nnozero* return the number of rows, columns, and non-zero cells respectively.

Parameters

i,j	<i>Coordinates</i>
check_bounds	<i>If false avoids checking bounds.</i>

- bool `is_empty` (size_t i, size_t j, bool check_bounds=true) const
- size_t `nrow` () const `noexcept`
- size_t `ncol` () const `noexcept`
- size_t `nnozero` () const `noexcept`
- `Cell`< Cell_Type > `default_val` () const

Cell-wise insertion/deletion

Parameters

i,j	<i>Row,column</i>
check_bounds	<i>When true and out of range, the function throws an error.</i>
check_exists	<i>Wither check if the cell exists (before trying to delete/add), or, in the case of swap_cells, check if either of both cells exists/don't exist.</i>

- `BArrayDense`< Cell_Type, Data_Type > & `operator+=` (const std::pair< size_t, size_t > &coords)
- `BArrayDense`< Cell_Type, Data_Type > & `operator-=` (const std::pair< size_t, size_t > &coords)
- `BArrayDenseCell`< Cell_Type, Data_Type > `operator()` (size_t i, size_t j, bool check_bounds=true)
- const Cell_Type `operator()` (size_t i, size_t j, bool check_bounds=true) const
- void `rm_cell` (size_t i, size_t j, bool check_bounds=true, bool check_exists=true)
- void `insert_cell` (size_t i, size_t j, const `Cell`< Cell_Type > &v, bool check_bounds, bool)
- void `insert_cell` (size_t i, size_t j, Cell_Type v, bool check_bounds, bool)

- void `swap_cells` (size_t i0, size_t j0, size_t i1, size_t j1, bool check_bounds=true, int check_exists=CHECK::BOTH, int *report=nullptr)
- void `toggle_cell` (size_t i, size_t j, bool check_bounds=true, int check_exists=EXISTS::UNKNOWN)
- void `toggle_lock` (size_t i, size_t j, bool check_bounds=true)

Column/row wise interchange

- void `swap_rows` (size_t i0, size_t i1, bool check_bounds=true)
- void `swap_cols` (size_t j0, size_t j1, bool check_bounds=true)
- void `zero_row` (size_t i, bool check_bounds=true)
- void `zero_col` (size_t j, bool check_bounds=true)

Arithmetic operators

- `BArrayDense< Cell_Type, Data_Type > & operator+=` (const `BArrayDense< Cell_Type, Data_Type >` &rhs)
- `BArrayDense< Cell_Type, Data_Type > & operator+=` (const Cell_Type &rhs)
- `BArrayDense< Cell_Type, Data_Type > & operator-=` (const `BArrayDense< Cell_Type, Data_Type >` &rhs)
- `BArrayDense< Cell_Type, Data_Type > & operator-=` (const Cell_Type &rhs)
- `BArrayDense< Cell_Type, Data_Type > & operator/=` (const Cell_Type &rhs)
- `BArrayDense< Cell_Type, Data_Type > & operator*=` (const Cell_Type &rhs)

Public Attributes

- bool `visited` = false

Friends

- class `BArrayDenseCell< Cell_Type, Data_Type >`
- class `BArrayDenseCol< Cell_Type, Data_Type >`
- class `BArrayDenseCol_const< Cell_Type, Data_Type >`
- class `BArrayDenseRow< Cell_Type, Data_Type >`
- class `BArrayDenseRow_const< Cell_Type, Data_Type >`

8.4.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDense< Cell_Type, Data_Type >
```

Baseline class for binary arrays.

`BArrayDense` class objects are arbitrary dense-arrays. The data is stored internally in the `el` member, which can be accessed using the member function `get_data()`, by column.

Template Parameters

<i>Cell_Type</i>	Type of cell (any type).
<i>Data_Type</i>	Data type of the array (bool default).

Definition at line 33 of file `barraydense-bones.hpp`.

8.4.2 Constructor & Destructor Documentation

8.4.2.1 BArrayDense() [1/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense ( ) [inline]
```

Zero-size array.

Definition at line 79 of file `barraydense-bones.hpp`.

8.4.2.2 BArrayDense() [2/6]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    size_t N_,
    size_t M_,
    Cell_Type value = static_cast<Cell_Type>(0) ) [inline]
```

Empty array.

Definition at line 82 of file `barraydense-bones.hpp`.

8.4.2.3 BArrayDense() [3/6]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    size_t N_,
    size_t M_,
    const std::vector< size_t > & source,
    const std::vector< size_t > & target,
    const std::vector< Cell_Type > & value,
    bool add = true ) [inline]
```

Edgelist with data.

Definition at line 35 of file `barraydense-meat.hpp`.

8.4.2.4 BArrayDense() [4/6]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    size_t N_,
    size_t M_,
    const std::vector< size_t > & source,
    const std::vector< size_t > & target,
    bool add = true ) [inline]
```

Edgelist with no data (simpler)

Definition at line 94 of file `barraydense-meat.hpp`.

8.4.2.5 BArrayDense() [5/6]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    const BArrayDense< Cell_Type, Data_Type > & Array_,
    bool copy_data = false ) [inline]
```

Copy constructor.

Definition at line 150 of file `barraydense-meat.hpp`.

8.4.2.6 BArrayDense() [6/6]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type >::BArrayDense (
    BArrayDense< Cell_Type, Data_Type > && x ) [inline], [noexcept]
```

Move operator.

Definition at line 244 of file `barraydense-meat.hpp`.

8.4.2.7 ~BArrayDense()

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type >::~~BArrayDense [inline]
```

Definition at line 325 of file `barraydense-meat.hpp`.

8.4.3 Member Function Documentation

8.4.3.1 clear()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::clear (
    bool hard = true ) [inline]
```

Definition at line 920 of file `barraydense-meat.hpp`.

8.4.3.2 col() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCol< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::col (
    size_t j,
    bool check_bounds = true ) [inline]
```

Definition at line 513 of file `barraydense-meat.hpp`.

8.4.3.3 col() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const BArrayDenseCol_const< Cell_Type, Data_Type > BArrayDense< Cell_Type, Data_Type >::col (
    size_t j,
    bool check_bounds = true ) const [inline]
```

Definition at line 499 of file `barraydense-meat.hpp`.

8.4.3.4 colsum()

```
template<typename Cell_Type , typename Data_Type >
const Cell_Type BArrayDense< Cell_Type, Data_Type >::colsum (
    size_t i ) const [inline]
```

Definition at line 1023 of file `barraydense-meat.hpp`.

8.4.3.5 D() [1/2]

```
template<typename Cell_Type , typename Data_Type >
Data_Type & BArrayDense< Cell_Type, Data_Type >::D [inline]
```

Definition at line 360 of file `barraydense-meat.hpp`.

8.4.3.6 D() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const Data_Type & BArrayDense< Cell_Type, Data_Type >::D [inline]
```

Definition at line 365 of file `barraydense-meat.hpp`.

8.4.3.7 D_ptr() [1/2]

```
template<typename Cell_Type , typename Data_Type >
Data_Type * BArrayDense< Cell_Type, Data_Type >::D_ptr [inline]
```

Definition at line 350 of file `barraydense-meat.hpp`.

8.4.3.8 D_ptr() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const Data_Type * BArrayDense< Cell_Type, Data_Type >::D_ptr [inline]
```

Definition at line 355 of file `barraydense-meat.hpp`.

8.4.3.9 default_val()

```
template<typename Cell_Type , typename Data_Type >
Cell< Cell_Type > BArrayDense< Cell_Type, Data_Type >::default_val [inline]
```

Definition at line 586 of file `barraydense-meat.hpp`.

8.4.3.10 get_cell()

```
template<typename Cell_Type , typename Data_Type >
Cell_Type BArrayDense< Cell_Type, Data_Type >::get_cell (
    size_t i,
    size_t j,
    bool check_bounds = true ) const [inline]
```

Definition at line 391 of file `barraydense-meat.hpp`.

8.4.3.11 get_col_vec() [1/2]

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    size_t i,
    bool check_bounds = true ) const [inline]
```

Definition at line 439 of file bararraydense-meat.hpp.

8.4.3.12 get_col_vec() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::get_col_vec (
    std::vector< Cell_Type > * x,
    size_t i,
    bool check_bounds = true ) const [inline]
```

Definition at line 457 of file bararraydense-meat.hpp.

8.4.3.13 get_data()

```
template<typename Cell_Type , typename Data_Type >
const std::vector< Cell_Type > & BArrayDense< Cell_Type, Data_Type >::get_data [inline]
```

Definition at line 1013 of file bararraydense-meat.hpp.

8.4.3.14 get_entries()

```
template<typename Cell_Type , typename Data_Type >
Entries< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_entries [inline]
```

Get the edgelist.

[Entries](#) is a class with three objects: Two `std::vector` with the row and column coordinates respectively, and one `std::vector` with the corresponding value of the cell.

Returns

`Entries<Cell_Type>`

Definition at line 525 of file bararraydense-meat.hpp.

8.4.3.15 get_row_vec() [1/2]

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type > BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    size_t i,
    bool check_bounds = true ) const [inline]
```

Definition at line 406 of file `barraydense-meat.hpp`.

8.4.3.16 get_row_vec() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::get_row_vec (
    std::vector< Cell_Type > * x,
    size_t i,
    bool check_bounds = true ) const [inline]
```

Definition at line 424 of file `barraydense-meat.hpp`.

8.4.3.17 insert_cell() [1/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    size_t i,
    size_t j,
    Cell_Type v,
    bool check_bounds,
    bool ) [inline]
```

Definition at line 712 of file `barraydense-meat.hpp`.

8.4.3.18 insert_cell() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::insert_cell (
    size_t i,
    size_t j,
    const Cell< Cell_Type > & v,
    bool check_bounds,
    bool ) [inline]
```

Definition at line 678 of file `barraydense-meat.hpp`.

8.4.3.19 is_dense()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::is_dense ( ) const [inline], [noexcept]
```

Definition at line 256 of file `barraydense-bones.hpp`.

8.4.3.20 is_empty()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayDense< Cell_Type, Data_Type >::is_empty (
    size_t i,
    size_t j,
    bool check_bounds = true ) const [inline]
```

Definition at line 554 of file `barraydense-meat.hpp`.

8.4.3.21 ncol()

```
template<typename Cell_Type , typename Data_Type >
size_t BArrayDense< Cell_Type, Data_Type >::ncol [inline], [noexcept]
```

Definition at line 571 of file `barraydense-meat.hpp`.

8.4.3.22 nnozero()

```
template<typename Cell_Type , typename Data_Type >
size_t BArrayDense< Cell_Type, Data_Type >::nnozero [inline], [noexcept]
```

Definition at line 575 of file `barraydense-meat.hpp`.

8.4.3.23 nrow()

```
template<typename Cell_Type , typename Data_Type >
size_t BArrayDense< Cell_Type, Data_Type >::nrow [inline], [noexcept]
```

Definition at line 567 of file `barraydense-meat.hpp`.

8.4.3.24 operator>() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type > BArrayDense< Cell_Type, Data_Type >::operator() (
    size_t i,
    size_t j,
    bool check_bounds = true ) [inline]
```

Definition at line 630 of file `barraydense-meat.hpp`.

8.4.3.25 operator>() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const Cell_Type BArrayDense< Cell_Type, Data_Type >::operator() (
    size_t i,
    size_t j,
    bool check_bounds = true ) const [inline]
```

Definition at line 641 of file `barraydense-meat.hpp`.

8.4.3.26 operator*=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & rhs )
```

8.4.3.27 operator+=() [1/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+= (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

8.4.3.28 operator+=() [2/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & rhs )
```

8.4.3.29 operator+=() [3/3]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::operator+=( (
    const std::pair< size_t, size_t > & coords ) [inline]
```

Definition at line 591 of file `barraydense-meat.hpp`.

8.4.3.30 operator-=() [1/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const BArrayDense< Cell_Type, Data_Type > & rhs )
```

8.4.3.31 operator-=() [2/3]

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const Cell_Type & rhs )
```

8.4.3.32 operator-=() [3/3]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::operator-=( (
    const std::pair< size_t, size_t > & coords ) [inline]
```

Definition at line 610 of file `barraydense-meat.hpp`.

8.4.3.33 operator/=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDense<Cell_Type,Data_Type>& BArrayDense< Cell_Type, Data_Type >::operator/=( (
    const Cell_Type & rhs )
```


8.4.3.34 operator=() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::operator= (
    BArrayDense< Cell_Type, Data_Type > && x ) [inline], [noexcept]
```

Move assignment.

Definition at line 262 of file `barraydense-meat.hpp`.

8.4.3.35 operator=() [2/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDense< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::operator= (
    const BArrayDense< Cell_Type, Data_Type > & Array_ ) [inline]
```

Assignment constructor.

Definition at line 194 of file `barraydense-meat.hpp`.

8.4.3.36 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayDense< Cell_Type, Data_Type >::operator== (
    const BArrayDense< Cell_Type, Data_Type > & Array_ ) [inline]
```

Definition at line 306 of file `barraydense-meat.hpp`.

8.4.3.37 out_of_range()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::out_of_range (
    size_t i,
    size_t j ) const [inline]
```

Definition at line 370 of file `barraydense-meat.hpp`.

8.4.3.38 print()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::print (
    const char * fmt = nullptr,
    ... ) const [inline]
```

Definition at line 979 of file `barraydense-meat.hpp`.

8.4.3.39 reserve()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::reserve [inline]
```

Definition at line 970 of file barraydense-meat.hpp.

8.4.3.40 resize()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::resize (
    size_t N_,
    size_t M_ ) [inline]
```

Definition at line 934 of file barraydense-meat.hpp.

8.4.3.41 rm_cell()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::rm_cell (
    size_t i,
    size_t j,
    bool check_bounds = true,
    bool check_exists = true ) [inline]
```

Definition at line 655 of file barraydense-meat.hpp.

8.4.3.42 row() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseRow< Cell_Type, Data_Type > & BArrayDense< Cell_Type, Data_Type >::row (
    size_t i,
    bool check_bounds = true ) [inline]
```

Definition at line 485 of file barraydense-meat.hpp.

8.4.3.43 row() [2/2]

```
template<typename Cell_Type , typename Data_Type >
const BArrayDenseRow_const< Cell_Type, Data_Type > BArrayDense< Cell_Type, Data_Type >::row (
    size_t i,
    bool check_bounds = true ) const [inline]
```

Definition at line 472 of file barraydense-meat.hpp.

8.4.3.44 rowsum()

```
template<typename Cell_Type , typename Data_Type >
const Cell_Type BArrayDense< Cell_Type, Data_Type >::rowsum (
    size_t i ) const [inline]
```

Definition at line 1018 of file barraydense-meat.hpp.

8.4.3.45 set_data()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::set_data (
    Data_Type * data_,
    bool delete_data_ = false ) [inline]
```

Set the data object.

Parameters

<i>data_</i>	
<i>delete_↔ data_</i>	

Definition at line 334 of file barraydense-meat.hpp.

8.4.3.46 swap_cells()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::swap_cells (
    size_t i0,
    size_t j0,
    size_t i1,
    size_t j1,
    bool check_bounds = true,
    int check_exists = CHECK::BOTH,
    int * report = nullptr ) [inline]
```

Definition at line 743 of file barraydense-meat.hpp.

8.4.3.47 swap_cols()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::swap_cols (
    size_t j0,
    size_t j1,
    bool check_bounds = true ) [inline]
```

Definition at line 827 of file barraydense-meat.hpp.

8.4.3.48 swap_rows()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::swap_rows (
    size_t i0,
    size_t i1,
    bool check_bounds = true ) [inline]
```

Definition at line 799 of file `barraydense-meat.hpp`.

8.4.3.49 toggle_cell()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::toggle_cell (
    size_t i,
    size_t j,
    bool check_bounds = true,
    int check_exists = EXISTS::UNKNOWN ) [inline]
```

Definition at line 780 of file `barraydense-meat.hpp`.

8.4.3.50 toggle_lock()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayDense< Cell_Type, Data_Type >::toggle_lock (
    size_t i,
    size_t j,
    bool check_bounds = true )
```

8.4.3.51 transpose()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::transpose [inline]
```

Definition at line 892 of file `barraydense-meat.hpp`.

8.4.3.52 zero_col()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::zero_col (
    size_t j,
    bool check_bounds = true ) [inline]
```

Definition at line 873 of file `barraydense-meat.hpp`.

8.4.3.53 zero_row()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDense< Cell_Type, Data_Type >::zero_row (
    size_t i,
    bool check_bounds = true ) [inline]
```

Definition at line 854 of file barraydense-meat.hpp.

8.4.4 Friends And Related Function Documentation

8.4.4.1 BArrayDenseCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

8.4.4.2 BArrayDenseCol< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

8.4.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

8.4.4.4 BArrayDenseRow< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file barraydense-bones.hpp.

8.4.4.5 BArrayDenseRow_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseRow_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydense-bones.hpp`.

8.4.5 Member Data Documentation

8.4.5.1 visited

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayDense< Cell_Type, Data_Type >::visited = false
```

This is as a reference, if we need to iterate through the cells and we need to keep track which were visited, we use this as a reference. So that if `cell.visited = true` and `visited = true`, it means that we haven't been here yet. Ideally, any routine using this->visited should switch it at the beginning of the routine.

Definition at line 63 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydense-meat.hpp`

8.5 BArrayDenseCell< Cell_Type, Data_Type > Class Template Reference

```
#include <barraydensecell-bones.hpp>
```

Public Member Functions

- `BArrayDenseCell` (`BArrayDense`< `Cell_Type`, `Data_Type` > *`Array_`, `size_t i_`, `size_t j_`, `bool check_`↵
`bounds=true`)
- `BArrayDenseCell`< `Cell_Type`, `Data_Type` > & `operator=` (const `BArrayDenseCell`< `Cell_Type`, `Data_Type` > &`other`)
- `~BArrayDenseCell` ()
- void `operator=` (const `Cell_Type` &`val`)
- void `operator+=` (const `Cell_Type` &`val`)
- void `operator-=` (const `Cell_Type` &`val`)
- void `operator*=` (const `Cell_Type` &`val`)
- void `operator/=` (const `Cell_Type` &`val`)
- `operator Cell_Type` () const
- bool `operator==` (const `Cell_Type` &`val`) const

Friends

- class [BArrayDense< Cell_Type, Data_Type >](#)
- class [BArrayDenseCol< Cell_Type, Data_Type >](#)
- class [BArrayDenseCol_const< Cell_Type, Data_Type >](#)

8.5.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCell< Cell_Type, Data_Type >
```

Definition at line 18 of file `barraydensecell-bones.hpp`.

8.5.2 Constructor & Destructor Documentation

8.5.2.1 BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::BArrayDenseCell (
    BArrayDense< Cell_Type, Data_Type > * Array_,
    size_t i_,
    size_t j_,
    bool check_bounds = true ) [inline]
```

Definition at line 30 of file `barraydensecell-bones.hpp`.

8.5.2.2 ~BArrayDenseCell()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCell< Cell_Type, Data_Type >::~~BArrayDenseCell ( ) [inline]
```

Definition at line 56 of file `barraydensecell-bones.hpp`.

8.5.3 Member Function Documentation

8.5.3.1 operator Cell_Type()

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type >::operator Cell_Type [inline]
```

Definition at line 112 of file `barraydensecell-meat.hpp`.

8.5.3.2 operator*=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 78 of file barraydensecell-meat.hpp.

8.5.3.3 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 48 of file barraydensecell-meat.hpp.

8.5.3.4 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 63 of file barraydensecell-meat.hpp.

8.5.3.5 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 95 of file barraydensecell-meat.hpp.

8.5.3.6 operator=() [1/2]

```
template<typename Cell_Type , typename Data_Type >
BArrayDenseCell< Cell_Type, Data_Type > & BArrayDenseCell< Cell_Type, Data_Type >::operator=
(
    const BArrayDenseCell< Cell_Type, Data_Type > & other ) [inline]
```

Definition at line 9 of file barraydensecell-meat.hpp.

8.5.3.7 operator=() [2/2]

```
template<typename Cell_Type , typename Data_Type >
void BArrayDenseCell< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 31 of file `barraydensecell-meat.hpp`.

8.5.3.8 operator==(

```
template<typename Cell_Type , typename Data_Type >
bool BArrayDenseCell< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 117 of file `barraydensecell-meat.hpp`.

8.5.4 Friends And Related Function Documentation**8.5.4.1 BArrayDense< Cell_Type, Data_Type >**

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

8.5.4.2 BArrayDenseCol< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

8.5.4.3 BArrayDenseCol_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCol_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecell-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecell-bones.hpp`
- `include/barry/barraydensecell-meat.hpp`

8.6 BArrayDenseCell_const< Cell_Type, Data_Type > Class Template Reference

8.6.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class BArrayDenseCell_const< Cell_Type, Data_Type >
```

Definition at line 20 of file `barraydense-bones.hpp`.

The documentation for this class was generated from the following file:

- [include/barry/barraydense-bones.hpp](#)

8.7 BArrayDenseCol< Cell_Type, Data_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

Public Member Functions

- [BArrayDenseCol](#) ([BArrayDense](#)< Cell_Type, Data_Type > &array_, size_t j)
- [Col_type](#)< Cell_Type >::iterator & [begin](#) ()
- [Col_type](#)< Cell_Type >::iterator & [end](#) ()
- size_t [size](#) () const [noexcept](#)
- std::pair< size_t, Cell_Type * > & [operator\(\)](#) (size_t i)

Friends

- class [BArrayDense](#)< Cell_Type, Data_Type >
- class [BArrayDenseCell](#)< Cell_Type, Data_Type >
- class [BArrayDenseCell_const](#)< Cell_Type, Data_Type >

8.7.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydensecol-bones.hpp`.

8.7.2 Constructor & Destructor Documentation

8.7.2.1 BArrayDenseCol()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol< Cell_Type, Data_Type >::BArrayDenseCol (
    BArrayDense< Cell_Type, Data_Type > & array_,
    size_t j ) [inline]
```

Definition at line 38 of file barraydensecol-bones.hpp.

8.7.3 Member Function Documentation

8.7.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 44 of file barraydensecol-bones.hpp.

8.7.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator& BArrayDenseCol< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 50 of file barraydensecol-bones.hpp.

8.7.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<size_t,Cell_Type*>& BArrayDenseCol< Cell_Type, Data_Type >::operator() (
    size_t i ) [inline]
```

Definition at line 62 of file barraydensecol-bones.hpp.

8.7.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 56 of file barraydensecol-bones.hpp.

8.7.4 Friends And Related Function Documentation

8.7.4.1 BArrayDense< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

8.7.4.2 BArrayDenseCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

8.7.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

8.8 BArrayDenseCol_const< Cell_Type, Data_Type > Class Template Reference

```
#include <barraydensecol-bones.hpp>
```

Public Member Functions

- `BArrayDenseCol_const` (const `BArrayDense`< `Cell_Type`, `Data_Type` > &array_, size_t j)
- `Col_type`< `Cell_Type` >::iterator `begin` ()
- `Col_type`< `Cell_Type` >::iterator `end` ()
- `size_t` `size` () const `noexcept`
- const std::pair< size_t, `Cell_Type` * > `operator()` (size_t i) const

Friends

- class [BArrayDenseCell< Cell_Type, Data_Type >](#)
- class [BArrayDenseCell_const< Cell_Type, Data_Type >](#)

8.8.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseCol_const< Cell_Type, Data_Type >
```

Definition at line 71 of file `barraydensecol-bones.hpp`.

8.8.2 Constructor & Destructor Documentation

8.8.2.1 BArrayDenseCol_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseCol_const< Cell_Type, Data_Type >::BArrayDenseCol_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    size_t j ) [inline]
```

Definition at line 80 of file `barraydensecol-bones.hpp`.

8.8.3 Member Function Documentation

8.8.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 96 of file `barraydensecol-bones.hpp`.

8.8.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Col_type<Cell_Type>::iterator BArrayDenseCol_const< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 101 of file `barraydensecol-bones.hpp`.

8.8.3.3 operator()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<size_t,Cell_Type*> BArrayDenseCol_const< Cell_Type, Data_Type >::operator() (
    size_t i ) const [inline]
```

Definition at line 112 of file `barraydensecol-bones.hpp`.

8.8.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseCol_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 107 of file `barraydensecol-bones.hpp`.

8.8.4 Friends And Related Function Documentation

8.8.4.1 BArrayDenseCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

8.8.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 62 of file `barraydensecol-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydensecol-bones.hpp`

8.9 BArrayDenseRow< Cell_Type, Data_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```

Public Member Functions

- [BArrayDenseRow](#) ([BArrayDense](#)< Cell_Type, Data_Type > &array_, size_t i)
- [Row_type](#)< Cell_Type >::iterator & [begin](#) ()
- [Row_type](#)< Cell_Type >::iterator & [end](#) ()
- size_t [size](#) () const [noexcept](#)
- std::pair< size_t, [Cell](#)< Cell_Type > > & [operator\(\)](#) (size_t i)

Friends

- class [BArrayDense](#)< Cell_Type, Data_Type >
- class [BArrayDenseCell](#)< Cell_Type, Data_Type >
- class [BArrayDenseCell_const](#)< Cell_Type, Data_Type >

8.9.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow< Cell_Type, Data_Type >
```

Definition at line 9 of file `barraydenserow-bones.hpp`.

8.9.2 Constructor & Destructor Documentation

8.9.2.1 BArrayDenseRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow< Cell_Type, Data_Type >::BArrayDenseRow (
    BArrayDense< Cell_Type, Data_Type > & array_,
    size_t i ) [inline]
```

Definition at line 40 of file `barraydenserow-bones.hpp`.

8.9.3 Member Function Documentation

8.9.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::begin ( ) [inline]
```

Definition at line 45 of file `barraydenserow-bones.hpp`.

8.9.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type<Cell_Type>::iterator& BArrayDenseRow< Cell_Type, Data_Type >::end ( ) [inline]
```

Definition at line 53 of file bararraydenserow-bones.hpp.

8.9.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::pair<size_t, Cell<Cell_Type> >& BArrayDenseRow< Cell_Type, Data_Type >::operator() (
    size_t i ) [inline]
```

Definition at line 69 of file bararraydenserow-bones.hpp.

8.9.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 61 of file bararraydenserow-bones.hpp.

8.9.4 Friends And Related Function Documentation

8.9.4.1 BArrayDense< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDense< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.

8.9.4.2 BArrayDenseCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file bararraydenserow-bones.hpp.

8.9.4.3 BArrayDenseCell_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 1 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

8.10 BArrayDenseRow_const< Cell_Type, Data_Type > Class Template Reference

```
#include <barraydenserow-bones.hpp>
```

Public Member Functions

- [BArrayDenseRow_const](#) (const [BArrayDense](#)< Cell_Type, Data_Type > &array_, size_t i)
- [Row_type](#)< Cell_Type >::const_iterator [begin](#) () const
- [Row_type](#)< Cell_Type >::const_iterator [end](#) () const
- size_t [size](#) () const [noexcept](#)
- const std::pair< size_t, [Cell](#)< Cell_Type > > [operator\(\)](#) (size_t i) const

Friends

- class [BArrayDenseCell](#)< Cell_Type, Data_Type >
- class [BArrayDenseCell_const](#)< Cell_Type, Data_Type >

8.10.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayDenseRow_const< Cell_Type, Data_Type >
```

Definition at line 80 of file `barraydenserow-bones.hpp`.

8.10.2 Constructor & Destructor Documentation

8.10.2.1 BArrayDenseRow_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayDenseRow_const< Cell_Type, Data_Type >::BArrayDenseRow_const (
    const BArrayDense< Cell_Type, Data_Type > & array_,
    size_t i ) [inline]
```

Definition at line 89 of file barraydenserow-bones.hpp.

8.10.3 Member Function Documentation

8.10.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::begin ( )
const [inline]
```

Definition at line 108 of file barraydenserow-bones.hpp.

8.10.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
Row_type< Cell_Type >::const_iterator BArrayDenseRow_const< Cell_Type, Data_Type >::end ( )
const [inline]
```

Definition at line 113 of file barraydenserow-bones.hpp.

8.10.3.3 operator()()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
const std::pair<size_t, Cell<Cell_Type>> > BArrayDenseRow_const< Cell_Type, Data_Type >↵
::operator() (
    size_t i ) const [inline]
```

Definition at line 123 of file barraydenserow-bones.hpp.

8.10.3.4 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayDenseRow_const< Cell_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 118 of file barraydenserow-bones.hpp.

8.10.4 Friends And Related Function Documentation

8.10.4.1 BArrayDenseCell< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

8.10.4.2 BArrayDenseCell_const< Cell_Type, Data_Type >

```
template<typename Cell_Type = bool, typename Data_Type = bool>
friend class BArrayDenseCell_const< Cell_Type, Data_Type > [friend]
```

Definition at line 69 of file `barraydenserow-bones.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barraydense-bones.hpp`
- `include/barry/barraydenserow-bones.hpp`

8.11 BArrayRow< Cell_Type, Data_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

Public Member Functions

- [BArrayRow](#) ([BArray](#)< Cell_Type, Data_Type > *Array_, size_t i_, bool check_bounds=true)
- [~BArrayRow](#) ()
- void [operator=](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val)
- void [operator+=](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val)
- void [operator-=](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val)
- void [operator*=](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val)
- void [operator/=](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val)
- [operator BArrayRow< Cell_Type, Data_Type > \(\)](#) const
- bool [operator==](#) (const [BArrayRow](#)< Cell_Type, Data_Type > &val) const

8.11.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow< Cell_Type, Data_Type >
```

Definition at line 5 of file `barrayrow-bones.hpp`.

8.11.2 Constructor & Destructor Documentation

8.11.2.1 BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::BArrayRow (
    BArray< Cell_Type, Data_Type > * Array_,
    size_t i_,
    bool check_bounds = true ) [inline]
```

Definition at line 13 of file bararrayrow-bones.hpp.

8.11.2.2 ~BArrayRow()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::~~BArrayRow ( ) [inline]
```

Definition at line 26 of file bararrayrow-bones.hpp.

8.11.3 Member Function Documentation

8.11.3.1 operator BArrayRow< Cell_Type, Data_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow< Cell_Type, Data_Type >::operator BArrayRow< Cell_Type, Data_Type > ( ) const
```

8.11.3.2 operator*=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator*= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

8.11.3.3 operator+=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator+= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

8.11.3.4 operator-=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator-= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

8.11.3.5 operator/=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator/= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

8.11.3.6 operator=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
void BArrayRow< Cell_Type, Data_Type >::operator= (
    const BArrayRow< Cell_Type, Data_Type > & val )
```

8.11.3.7 operator==()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow< Cell_Type, Data_Type >::operator== (
    const BArrayRow< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

8.12 BArrayRow_const< Cell_Type, Data_Type > Class Template Reference

```
#include <barrayrow-bones.hpp>
```

Public Member Functions

- [BArrayRow_const](#) (const [BArray](#)< Cell_Type, Data_Type > *Array_, size_t i_, bool check_bounds=true)
- [~BArrayRow_const](#) ()
- [operator BArrayRow_const< Cell_Type, Data_Type > \(\)](#) const
- bool [operator==](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const
- bool [operator!=](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const
- bool [operator<](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const
- bool [operator>](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const
- bool [operator<=](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const
- bool [operator>=](#) (const [BArrayRow_const](#)< Cell_Type, Data_Type > &val) const

8.12.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayRow_const< Cell_Type, Data_Type >
```

Definition at line 41 of file `barrayrow-bones.hpp`.

8.12.2 Constructor & Destructor Documentation

8.12.2.1 BArrayRow_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::BArrayRow_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    size_t i_,
    bool check_bounds = true ) [inline]
```

Definition at line 49 of file `barrayrow-bones.hpp`.

8.12.2.2 ~BArrayRow_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::~~BArrayRow_const ( ) [inline]
```

Definition at line 59 of file `barrayrow-bones.hpp`.

8.12.3 Member Function Documentation

8.12.3.1 operator BArrayRow_const< Cell_Type, Data_Type >()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayRow_const< Cell_Type, Data_Type >::operator BArrayRow_const< Cell_Type, Data_Type > ( )
const
```

8.12.3.2 operator"!="()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator!= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

8.12.3.3 operator<()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator< (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

8.12.3.4 operator<=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator<= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

8.12.3.5 operator==(())

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator==(
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

8.12.3.6 operator>()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator> (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

8.12.3.7 operator>=()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayRow_const< Cell_Type, Data_Type >::operator>= (
    const BArrayRow_const< Cell_Type, Data_Type > & val ) const
```

The documentation for this class was generated from the following file:

- [include/barry/barrayrow-bones.hpp](#)

8.13 BArrayVector< Cell_Type, Data_Type > Class Template Reference

Row or column of a [BArray](#)

```
#include <barrayvector-bones.hpp>
```

Public Member Functions

- [BArrayVector](#) ([BArray](#)< Cell_Type, Data_Type > *Array_, size_t &dim_size_t &i_, bool check_bounds=true)
Construct a new [BArrayVector](#) object.
- [~BArrayVector](#) ()
- bool [is_row](#) () const [noexcept](#)
- bool [is_col](#) () const [noexcept](#)
- size_t [size](#) () const [noexcept](#)
- std::vector< Cell_Type >::const_iterator [begin](#) () [noexcept](#)
- std::vector< Cell_Type >::const_iterator [end](#) () [noexcept](#)
- void [operator=](#) (const Cell_Type &val)
- void [operator+=](#) (const Cell_Type &val)
- void [operator-=](#) (const Cell_Type &val)
- void [operator*=](#) (const Cell_Type &val)
- void [operator/=](#) (const Cell_Type &val)
- [operator](#) std::vector< [Cell_Type](#) > () const
- bool [operator==](#) (const Cell_Type &val) const

8.13.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector< Cell_Type, Data_Type >
```

Row or column of a [BArray](#)

Template Parameters

<i>Cell_Type</i>	
<i>Data_Type</i>	

Definition at line 11 of file `barrayvector-bones.hpp`.

8.13.2 Constructor & Destructor Documentation

8.13.2.1 BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::BArrayVector (
    BArray< Cell_Type, Data_Type > * Array_,
    size_t &dim_size_t & i_,
    bool check_bounds = true ) [inline]
```

Construct a new [BArrayVector](#) object.

Parameters

<i>Array_</i>	Pointer to a BArray object
<i>dim_</i>	Dimension. 0 means row and 1 means column.
<i>i_</i>	Element to point.
<i>check_bounds</i>	When <code>true</code> , check boundaries.

Definition at line 32 of file barrayvector-bones.hpp.

8.13.2.2 ~BArrayVector()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector< Cell_Type, Data_Type >::~~BArrayVector ( ) [inline]
```

Definition at line 53 of file barrayvector-bones.hpp.

8.13.3 Member Function Documentation

8.13.3.1 begin()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::begin [inline],
[noexcept]
```

Definition at line 50 of file barrayvector-meat.hpp.

8.13.3.2 end()

```
template<typename Cell_Type , typename Data_Type >
std::vector< Cell_Type >::const_iterator BArrayVector< Cell_Type, Data_Type >::end [inline],
[noexcept]
```

Definition at line 64 of file barrayvector-meat.hpp.

8.13.3.3 is_col()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_col [inline], [noexcept]
```

Definition at line 34 of file barrayvector-meat.hpp.

8.13.3.4 is_row()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::is_row [inline], [noexcept]
```

Definition at line 29 of file barrayvector-meat.hpp.

8.13.3.5 operator std::vector< Cell_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 175 of file barrayvector-meat.hpp.

8.13.3.6 operator*=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator*= (
    const Cell_Type & val ) [inline]
```

Definition at line 133 of file barrayvector-meat.hpp.

8.13.3.7 operator+=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator+= (
    const Cell_Type & val ) [inline]
```

Definition at line 91 of file barrayvector-meat.hpp.

8.13.3.8 operator-=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator-= (
    const Cell_Type & val ) [inline]
```

Definition at line 112 of file barrayvector-meat.hpp.

8.13.3.9 operator/=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator/= (
    const Cell_Type & val ) [inline]
```

Definition at line 154 of file `barrayvector-meat.hpp`.

8.13.3.10 operator=()

```
template<typename Cell_Type , typename Data_Type >
void BArrayVector< Cell_Type, Data_Type >::operator= (
    const Cell_Type & val ) [inline]
```

Definition at line 69 of file `barrayvector-meat.hpp`.

8.13.3.11 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 185 of file `barrayvector-meat.hpp`.

8.13.3.12 size()

```
template<typename Cell_Type , typename Data_Type >
size_t BArrayVector< Cell_Type, Data_Type >::size [inline], [noexcept]
```

Definition at line 39 of file `barrayvector-meat.hpp`.

The documentation for this class was generated from the following files:

- `include/barry/barrayvector-bones.hpp`
- `include/barry/barrayvector-meat.hpp`

8.14 BArrayVector_const< Cell_Type, Data_Type > Class Template Reference

```
#include <barrayvector-bones.hpp>
```

Public Member Functions

- [BArrayVector_const](#) (const [BArray](#)< Cell_Type, Data_Type > *Array_, size_t &dim_size_t &i_, bool check↵_bounds=true)
- [~BArrayVector_const](#) ()
- bool [is_row](#) () const [noexcept](#)
- bool [is_col](#) () const [noexcept](#)
- size_t [size](#) () const [noexcept](#)
- std::vector< Cell_Type >::const_iterator [begin](#) () [noexcept](#)
- std::vector< Cell_Type >::const_iterator [end](#) () [noexcept](#)
- [operator](#) std::vector< Cell_Type > () const
- bool [operator==](#) (const Cell_Type &val) const
- bool [operator!=](#) (const Cell_Type &val) const
- bool [operator<](#) (const Cell_Type &val) const
- bool [operator>](#) (const Cell_Type &val) const
- bool [operator<=](#) (const Cell_Type &val) const
- bool [operator>=](#) (const Cell_Type &val) const

8.14.1 Detailed Description

```
template<typename Cell_Type = bool, typename Data_Type = bool>
class BArrayVector_const< Cell_Type, Data_Type >
```

Definition at line 73 of file `barrayvector-bones.hpp`.

8.14.2 Constructor & Destructor Documentation

8.14.2.1 BArrayVector_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::BArrayVector_const (
    const BArray< Cell_Type, Data_Type > * Array_,
    size_t &dim_size_t & i_,
    bool check_bounds = true ) [inline]
```

Definition at line 86 of file `barrayvector-bones.hpp`.

8.14.2.2 ~BArrayVector_const()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
BArrayVector_const< Cell_Type, Data_Type >::~BArrayVector_const ( ) [inline]
```

Definition at line 108 of file `barrayvector-bones.hpp`.

8.14.3 Member Function Documentation

8.14.3.1 begin()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::begin (
) [noexcept]
```

8.14.3.2 end()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
std::vector< Cell_Type >::const_iterator BArrayVector_const< Cell_Type, Data_Type >::end ( )
[noexcept]
```

8.14.3.3 is_col()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_col ( ) const [noexcept]
```

8.14.3.4 is_row()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
bool BArrayVector_const< Cell_Type, Data_Type >::is_row ( ) const [noexcept]
```

8.14.3.5 operator std::vector< Cell_Type >()

```
template<typename Cell_Type , typename Data_Type >
BArrayVector_const< Cell_Type, Data_Type >::operator std::vector< Cell_Type > [inline]
```

Definition at line 212 of file barrayvector-meat.hpp.

8.14.3.6 operator"!=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator!= (
    const Cell_Type & val ) const [inline]
```

Definition at line 249 of file barrayvector-meat.hpp.

8.14.3.7 operator<()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator< (
    const Cell_Type & val ) const [inline]
```

Definition at line 254 of file barrayvector-meat.hpp.

8.14.3.8 operator<=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator<= (
    const Cell_Type & val ) const [inline]
```

Definition at line 281 of file barrayvector-meat.hpp.

8.14.3.9 operator==()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator== (
    const Cell_Type & val ) const [inline]
```

Definition at line 222 of file barrayvector-meat.hpp.

8.14.3.10 operator>()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator> (
    const Cell_Type & val ) const [inline]
```

Definition at line 308 of file barrayvector-meat.hpp.

8.14.3.11 operator>=()

```
template<typename Cell_Type , typename Data_Type >
bool BArrayVector_const< Cell_Type, Data_Type >::operator>= (
    const Cell_Type & val ) const [inline]
```

Definition at line 315 of file barrayvector-meat.hpp.

8.14.3.12 size()

```
template<typename Cell_Type = bool, typename Data_Type = bool>
size_t BArrayVector_const< Cell_Type, Data_Type >::size ( ) const [noexcept]
```

The documentation for this class was generated from the following files:

- include/barry/barrayvector-bones.hpp
- include/barry/barrayvector-meat.hpp

8.15 Cell< Cell_Type > Class Template Reference

Entries in [BArray](#). For now, it only has two members:

```
#include <cell-bones.hpp>
```

Public Member Functions

- [Cell](#) ()
- [Cell](#) (Cell_Type value_, bool visited_=false, bool active_=true)
- [~Cell](#) ()
- [Cell](#) (const [Cell](#)< Cell_Type > &arg)
- [Cell](#)< Cell_Type > & [operator=](#) (const [Cell](#)< Cell_Type > &other)
- [Cell](#) ([Cell](#)< Cell_Type > &&arg) [noexcept](#)
- [Cell](#)< Cell_Type > & [operator=](#) ([Cell](#)< Cell_Type > &&other) [noexcept](#)
- void [add](#) (Cell_Type x)
- [operator Cell_Type](#) () const
- bool [operator==](#) (const [Cell](#)< Cell_Type > &rhs) const
- bool [operator!=](#) (const [Cell](#)< Cell_Type > &rhs) const
- void [add](#) (double x)
- void [add](#) (size_t x)
- void [add](#) (int x)
- [Cell](#) ()
- [Cell](#) ()
- [Cell](#) ()

Public Attributes

- Cell_Type [value](#)
- bool [visited](#)
- bool [active](#)

8.15.1 Detailed Description

```
template<class Cell_Type>
class Cell< Cell_Type >
```

[Entries](#) in [BArray](#). For now, it only has two members:

- value: the content
- visited: boolean (just a convenient)

Definition at line 10 of file cell-bones.hpp.

8.15.2 Constructor & Destructor Documentation

8.15.2.1 Cell() [1/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell ( )
```

8.15.2.2 Cell() [2/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell_Type value_,
    bool visited_ = false,
    bool active_ = true ) [inline]
```

Definition at line 16 of file cell-bones.hpp.

8.15.2.3 ~Cell()

```
template<class Cell_Type >
Cell< Cell_Type >::~Cell ( ) [inline]
```

Definition at line 18 of file cell-bones.hpp.

8.15.2.4 Cell() [3/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    const Cell< Cell_Type > & arg ) [inline]
```

Definition at line 22 of file cell-bones.hpp.

8.15.2.5 Cell() [4/7]

```
template<class Cell_Type >
Cell< Cell_Type >::Cell (
    Cell< Cell_Type > && arg ) [inline], [noexcept]
```

Definition at line 29 of file cell-bones.hpp.

8.15.2.6 Cell() [5/7]

```
Cell< double >::Cell ( ) [inline]
```

Definition at line 62 of file cell-meat.hpp.

8.15.2.7 Cell() [6/7]

```
Cell< size_t >::Cell ( ) [inline]
```

Definition at line 63 of file cell-meat.hpp.

8.15.2.8 Cell() [7/7]

```
Cell< int >::Cell ( ) [inline]
```

Definition at line 64 of file cell-meat.hpp.

8.15.3 Member Function Documentation

8.15.3.1 add() [1/4]

```
template<class Cell_Type >
void Cell< Cell_Type >::add (
    Cell_Type x )
```

8.15.3.2 add() [2/4]

```
void Cell< double >::add (
    double x ) [inline]
```

Definition at line 42 of file cell-meat.hpp.

8.15.3.3 add() [3/4]

```
void Cell< int >::add (
    int x ) [inline]
```

Definition at line 52 of file cell-meat.hpp.

8.15.3.4 add() [4/4]

```
void Cell< size_t >::add (
    size_t x ) [inline]
```

Definition at line 47 of file cell-meat.hpp.

8.15.3.5 operator Cell_Type()

```
template<class Cell_Type >
Cell< Cell_Type >::operator Cell_Type ( ) const [inline]
```

Definition at line 41 of file cell-bones.hpp.

8.15.3.6 operator"!=(

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator!= (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 31 of file cell-meat.hpp.

8.15.3.7 operator=() [1/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    Cell< Cell_Type > && other ) [noexcept]
```

Definition at line 13 of file cell-meat.hpp.

8.15.3.8 operator=() [2/2]

```
template<typename Cell_Type >
Cell< Cell_Type > & Cell< Cell_Type >::operator= (
    const Cell< Cell_Type > & other )
```

Definition at line 5 of file cell-meat.hpp.

8.15.3.9 operator==()

```
template<typename Cell_Type >
bool Cell< Cell_Type >::operator== (
    const Cell< Cell_Type > & rhs ) const
```

Definition at line 21 of file cell-meat.hpp.

8.15.4 Member Data Documentation

8.15.4.1 active

```
template<class Cell_Type >
bool Cell< Cell_Type >::active
```

Definition at line 14 of file cell-bones.hpp.

8.15.4.2 value

```
template<class Cell_Type >
Cell_Type Cell< Cell_Type >::value
```

Definition at line 12 of file cell-bones.hpp.

8.15.4.3 visited

```
template<class Cell_Type >
bool Cell< Cell_Type >::visited
```

Definition at line 13 of file cell-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/barray-meat.hpp](#)
- [include/barry/cell-bones.hpp](#)
- [include/barry/cell-meat.hpp](#)

8.16 Cell_const< Cell_Type > Class Template Reference

8.16.1 Detailed Description

```
template<typename Cell_Type>
class Cell_const< Cell_Type >
```

Definition at line 8 of file barray-meat.hpp.


The documentation for this class was generated from the following file:

- [include/barry/barray-meat.hpp](#)

8.17 ConstBArrayRowIter< Cell_Type, Data_Type > Class Template Reference

```
#include <barray-iterator.hpp>
```

Collaboration diagram for ConstBArrayRowIter< Cell_Type, Data_Type >:



Public Member Functions

- [ConstBArrayRowIter](#) (const [BArray](#)< Cell_Type, Data_Type > *Array_)
- [~ConstBArrayRowIter](#) ()

Public Attributes

- size_t [current_row](#)
- size_t [current_col](#)
- [Row_type](#)< Cell_Type >::const_iterator [iter](#)
- const [BArray](#)< Cell_Type, Data_Type > * [Array](#)

8.17.1 Detailed Description

```
template<typename Cell_Type, typename Data_Type>
class ConstBArrayRowIter< Cell_Type, Data_Type >
```

Definition at line 10 of file `barray-iterator.hpp`.

8.17.2 Constructor & Destructor Documentation

8.17.2.1 ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::ConstBArrayRowIter (
    const BArray< Cell_Type, Data_Type > * Array_ ) [inline]
```

Definition at line 17 of file `barray-iterator.hpp`.

8.17.2.2 ~ConstBArrayRowIter()

```
template<typename Cell_Type , typename Data_Type >
ConstBArrayRowIter< Cell_Type, Data_Type >::~~ConstBArrayRowIter ( ) [inline]
```

Definition at line 29 of file `barray-iterator.hpp`.

8.17.3 Member Data Documentation

8.17.3.1 Array

```
template<typename Cell_Type , typename Data_Type >
const BArray<Cell_Type,Data_Type>* ConstBArrayRowIter< Cell_Type, Data_Type >::Array
```

Definition at line 15 of file `barray-iterator.hpp`.

8.17.3.2 current_col

```
template<typename Cell_Type , typename Data_Type >
size_t ConstBArrayRowIter< Cell_Type, Data_Type >::current_col
```

Definition at line 13 of file `barray-iterator.hpp`.

8.17.3.3 current_row

```
template<typename Cell_Type , typename Data_Type >
size_t ConstBArrayRowIter< Cell_Type, Data_Type >::current_row
```

Definition at line 13 of file `barray-iterator.hpp`.

8.17.3.4 iter

```
template<typename Cell_Type , typename Data_Type >
Row_type<Cell_Type>::const_iterator ConstBArrayRowIter< Cell_Type, Data_Type >::iter
```

Definition at line 14 of file `barray-iterator.hpp`.

The documentation for this class was generated from the following file:

- `include/barry/barray-iterator.hpp`

8.18 Counter< Array_Type, Data_Type > Class Template Reference

A counter function based on change statistics.

```
#include <counters-bones.hpp>
```

Public Member Functions

- `~Counter ()`
- `double count (Array_Type &Array, size_t i, size_t j)`
- `double init (Array_Type &Array, size_t i, size_t j)`
- `std::string get_name () const`
- `std::string get_description () const`

Creator passing a counter and an initializer

Parameters

count_fun↔ _	The main counter function.
init_fun_ _	The initializer function can also be used to check if the BArray as the needed variables (see BArray::data).
data_ _	Data to be used with the counter.
delete_↔ data_ _	When <code>true</code> , the destructor will delete the pointer in the main data.

- [Counter](#) ()
- [Counter](#) ([Counter_fun_type](#)< Array_Type, Data_Type > [count_fun](#), [Counter_fun_type](#)< Array_Type, Data_Type > [init_fun](#), [Hasher_fun_type](#)< Array_Type, Data_Type > [hasher_fun](#), Data_Type [data](#), std::string [name](#)_="", std::string [desc](#)_="")
- [Counter](#) (const [Counter](#)< Array_Type, Data_Type > &[counter](#)_)
Copy constructor.
- [Counter](#) ([Counter](#)< Array_Type, Data_Type > &&[counter](#)_) **noexcept**
Move constructor.
- [Counter](#)< Array_Type, Data_Type > **operator=** (const [Counter](#)< Array_Type, Data_Type > &[counter](#)_)
Copy assignment.
- [Counter](#)< Array_Type, Data_Type > & **operator=** ([Counter](#)< Array_Type, Data_Type > &&[counter](#)_)
noexcept
Move assignment.

- void [set_hasher](#) ([Hasher_fun_type](#)< Array_Type, Data_Type > [fun](#))
Get and set the hasher function.
- [Hasher_fun_type](#)< Array_Type, Data_Type > [get_hasher](#) ()

Public Attributes

- [Counter_fun_type](#)< Array_Type, Data_Type > [count_fun](#)
- [Counter_fun_type](#)< Array_Type, Data_Type > [init_fun](#)
- [Hasher_fun_type](#)< Array_Type, Data_Type > [hasher_fun](#)
- Data_Type [data](#)
- std::string [name](#) = ""
- std::string [desc](#) = ""

8.18.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counter< Array_Type, Data_Type >
```

A counter function based on change statistics.

This class is used by `CountStats` and [StatsCounter](#) as a way to count statistics using change statistics.

Definition at line 35 of file `counters-bones.hpp`.

8.18.2 Constructor & Destructor Documentation

8.18.2.1 Counter() [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter ( ) [inline]
```

Definition at line 57 of file counters-bones.hpp.

8.18.2.2 Counter() [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Hasher_fun_type< Array_Type, Data_Type > hasher_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" ) [inline]
```

Definition at line 59 of file counters-bones.hpp.

8.18.2.3 Counter() [3/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

8.18.2.4 Counter() [4/4]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::Counter (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move constructor.

8.18.2.5 ~Counter()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter< Array_Type, Data_Type >::~~Counter ( ) [inline]
```

Definition at line 75 of file counters-bones.hpp.

8.18.3 Member Function Documentation

8.18.3.1 count()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::count (
    Array_Type & Array,
    size_t i,
    size_t j )
```

8.18.3.2 get_description()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_description ( ) const
```

8.18.3.3 get_hasher()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Hasher_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::get_hasher ( )
```

8.18.3.4 get_name()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::get_name ( ) const
```

8.18.3.5 init()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
double Counter< Array_Type, Data_Type >::init (
    Array_Type & Array,
    size_t i,
    size_t j )
```

8.18.3.6 operator=() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::operator= (
    const Counter< Array_Type, Data_Type > & counter_ )
```

Copy assignment.

8.18.3.7 operator=() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array_Type,Data_Type>& Counter< Array_Type, Data_Type >::operator= (
    Counter< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment.

8.18.3.8 set_hasher()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counter< Array_Type, Data_Type >::set_hasher (
    Hasher_fun_type< Array_Type, Data_Type > fun )
```

Get and set the hasher function.

The hasher function is used to characterize the support of the array. This way, if possible, the support enumeration is recycled.

Parameters

<i>fun</i>	
------------	--

8.18.4 Member Data Documentation**8.18.4.1 count_fun**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::count_fun
```

Definition at line 38 of file counters-bones.hpp.

8.18.4.2 data

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Data_Type Counter< Array_Type, Data_Type >::data
```

Definition at line 42 of file counters-bones.hpp.

8.18.4.3 desc

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::desc = ""
```

Definition at line 44 of file counters-bones.hpp.

8.18.4.4 hasher_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Hasher_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::hasher_fun
```

Definition at line 40 of file counters-bones.hpp.

8.18.4.5 init_fun

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter_fun_type<Array_Type,Data_Type> Counter< Array_Type, Data_Type >::init_fun
```

Definition at line 39 of file counters-bones.hpp.

8.18.4.6 name

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::string Counter< Array_Type, Data_Type >::name = ""
```

Definition at line 43 of file counters-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/counters-bones.hpp](#)

8.19 Counters< Array_Type, Data_Type > Class Template Reference

Vector of counters.

```
#include <counters-bones.hpp>
```

Public Member Functions

- [Counters](#) ()
- [~Counters](#) ()
- [Counters](#) (const [Counters](#)< Array_Type, Data_Type > &[counter_](#))
Copy constructor.
- [Counters](#) ([Counters](#)< Array_Type, Data_Type > &&[counters_](#)) **noexcept**
Move constructor.
- [Counters](#)< Array_Type, Data_Type > **operator=** (const [Counters](#)< Array_Type, Data_Type > &[counter_](#))
Copy assignment constructor.
- [Counters](#)< Array_Type, Data_Type > & **operator=** ([Counters](#)< Array_Type, Data_Type > &&[counter_](#)) **noexcept**
Move assignment constructor.
- [Counter](#)< Array_Type, Data_Type > & **operator[]** (size_t idx)
Returns a pointer to a particular counter.
- std::size_t **size** () const **noexcept**
Number of counters in the set.
- void **add_counter** ([Counter](#)< Array_Type, Data_Type > [counter](#))
- void **add_counter** ([Counter_fun_type](#)< Array_Type, Data_Type > [count_fun_](#), [Counter_fun_type](#)< Array_Type, Data_Type > [init_fun_](#), [Hasher_fun_type](#)< Array_Type, Data_Type > [hasher_fun_](#), Data_Type [data_](#), std::string [name_](#)="", std::string [desc_](#)="")
- std::vector< std::string > **get_names** () const
- std::vector< std::string > **get_descriptions** () const
- std::vector< double > **gen_hash** (const Array_Type &array, bool [add_dims](#)=true)
Generates a hash for the given array according to the counters.
- void **add_hash** ([Hasher_fun_type](#)< Array_Type, Data_Type > [fun_](#))

8.19.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Counters< Array_Type, Data_Type >
```

Vector of counters.

Various functions hold more than one counter, so this class is a helper class that allows managing multiple counters efficiently. The main data is a vector to pointers of counters.

Definition at line 108 of file counters-bones.hpp.

8.19.2 Constructor & Destructor Documentation

8.19.2.1 Counters() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters ( )
```

8.19.2.2 ~Counters()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::~~Counters ( ) [inline]
```

Definition at line 120 of file counters-bones.hpp.

8.19.2.3 Counters() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy constructor.

Parameters

<i>counter_↔</i>	
—	

8.19.2.4 Counters() [3/3]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters< Array_Type, Data_Type >::Counters (
    Counters< Array_Type, Data_Type > && counters_ ) [noexcept]
```

Move constructor.

Parameters

<i>counters_↔</i>	
—	

8.19.3 Member Function Documentation

8.19.3.1 add_counter() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > counter )
```

8.19.3.2 add_counter() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Type > init_fun_,
    Hasher_fun_type< Array_Type, Data_Type > hasher_fun_,
    Data_Type data_,
    std::string name_ = "",
    std::string desc_ = "" )
```

8.19.3.3 add_hash()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
void Counters< Array_Type, Data_Type >::add_hash (
    Hasher_fun_type< Array_Type, Data_Type > fun_ )
```

8.19.3.4 gen_hash()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< double > Counters< Array_Type, Data_Type >::gen_hash (
    const Array_Type & array,
    bool add_dims = true )
```

Generates a hash for the given array according to the counters.

Parameters

<i>array</i>	
<i>add_dims</i>	When <code>true</code> (default) the dimension of the array will be added to the hash.

Returns

`std::vector< double >` That can be hashed later.

8.19.3.5 get_descriptions()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_descriptions ( ) const
```

8.19.3.6 get_names()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::vector< std::string > Counters< Array_Type, Data_Type >::get_names ( ) const
```

8.19.3.7 operator=() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type> Counters< Array_Type, Data_Type >::operator= (
    const Counters< Array_Type, Data_Type > & counter_ )
```

Copy assignment constructor.

Parameters

<i>counter_↔</i>	
—	

Returns

[Counters<Array_Type,Data_Type>](#)

8.19.3.8 operator=() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counters<Array_Type,Data_Type>& Counters< Array_Type, Data_Type >::operator= (
    Counters< Array_Type, Data_Type > && counter_ ) [noexcept]
```

Move assignment constructor.

Parameters

<i>counter_↔</i>	
—	

Returns

[Counters](#)<[Array_Type](#),[Data_Type](#)>&

8.19.3.9 operator[]()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Counter<Array\_Type,Data\_Type>& Counters< Array\_Type, Data\_Type >::operator[] (
    size_t idx )
```

Returns a pointer to a particular counter.

Parameters

<i>idx</i>	Id of the counter
------------	-------------------

Returns

[Counter](#)<[Array_Type](#),[Data_Type](#)>*

8.19.3.10 size()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
std::size_t Counters< Array\_Type, Data\_Type >::size ( ) const [inline], [noexcept]
```

Number of counters in the set.

Returns

size_t

Definition at line 164 of file counters-bones.hpp.


The documentation for this class was generated from the following file:

- [include/barry/counters-bones.hpp](#)


8.20 DEFM Class Reference

```
#include <defm-bones.hpp>
```

Inheritance diagram for DEFM:



Collaboration diagram for DEFM:



Public Member Functions

- [DEFM](#) (int *id, int *y, double *x, size_t id_length, size_t y_ncol, size_t x_ncol, size_t m_order, bool copy_↔ data=true, bool column_major=true)
- [DEFMModel](#) & [get_model](#) ()
- void [init](#) ()
- void [simulate](#) (std::vector< double > par, int *y_out)
- size_t [get_n_y](#) () const
- size_t [get_n_obs](#) () const
- size_t [get_n_covars](#) () const
- size_t [get_m_order](#) () const
- size_t [get_n_rows](#) () const
- const int * [get_Y](#) () const
- const int * [get_ID](#) () const
- const double * [get_X](#) () const
- [barry::FreqTable](#)< int > [motif_census](#) (std::vector< size_t > idx)

- `std::vector< double > logodds` (`const std::vector< double > &par`, `size_t i`, `size_t j`)
- `void set_names` (`std::vector< std::string > Y_names_`, `std::vector< std::string > X_names_`)
- `const std::vector< std::string > & get_Y_names` () `const`
- `const std::vector< std::string > & get_X_names` () `const`
- `void print` () `const`
- `std::vector< bool > is_motif` ()
- `bool get_column_major` () `const` `noexcept`

8.20.1 Detailed Description

Definition at line 4 of file `defm-bones.hpp`.

8.20.2 Constructor & Destructor Documentation

8.20.2.1 DEFM()

```
DEFM::DEFM (
    int * id,
    int * y,
    double * x,
    size_t id_length,
    size_t y_ncol,
    size_t x_ncol,
    size_t m_order,
    bool copy_data = true,
    bool column_major = true ) [inline]
```

Definition at line 105 of file `defm-meat.hpp`.

8.20.3 Member Function Documentation

8.20.3.1 get_column_major()

```
bool DEFM::get_column_major ( ) const [inline], [noexcept]
```

Definition at line 449 of file `defm-meat.hpp`.

8.20.3.2 get_ID()

```
const int * DEFM::get_ID ( ) const [inline]
```

Definition at line 310 of file `defm-meat.hpp`.

8.20.3.3 get_m_order()

```
size_t DEFM::get_m_order ( ) const [inline]
```

Definition at line 295 of file defm-meat.hpp.

8.20.3.4 get_model()

```
DEFMModel& DEFM::get_model ( ) [inline]
```

Definition at line 49 of file defm-bones.hpp.

8.20.3.5 get_n_covars()

```
size_t DEFM::get_n_covars ( ) const [inline]
```

Definition at line 290 of file defm-meat.hpp.

8.20.3.6 get_n_obs()

```
size_t DEFM::get_n_obs ( ) const [inline]
```

Definition at line 285 of file defm-meat.hpp.

8.20.3.7 get_n_rows()

```
size_t DEFM::get_n_rows ( ) const [inline]
```

Definition at line 300 of file defm-meat.hpp.

8.20.3.8 get_n_y()

```
size_t DEFM::get_n_y ( ) const [inline]
```

Definition at line 280 of file defm-meat.hpp.

8.20.3.9 get_X()

```
const double * DEFM::get_X ( ) const [inline]
```

Definition at line 315 of file defm-meat.hpp.

8.20.3.10 get_X_names()

```
const std::vector< std::string > & DEFM::get_X_names ( ) const [inline]
```

Definition at line 422 of file defm-meat.hpp.

8.20.3.11 get_Y()

```
const int * DEFM::get_Y ( ) const [inline]
```

Definition at line 305 of file defm-meat.hpp.

8.20.3.12 get_Y_names()

```
const std::vector< std::string > & DEFM::get_Y_names ( ) const [inline]
```

Definition at line 418 of file defm-meat.hpp.

8.20.3.13 init()

```
void DEFM::init ( ) [inline]
```

Definition at line 215 of file defm-meat.hpp.

8.20.3.14 is_motif()

```
std::vector< bool > DEFM::is_motif ( ) [inline]
```

Definition at line 439 of file defm-meat.hpp.

8.20.3.15 logodds()

```
std::vector< double > DEFM::logodds (
    const std::vector< double > & par,
    size_t i,
    size_t j ) [inline]
```

Definition at line 359 of file defm-meat.hpp.

8.20.3.16 motif_census()

```
barry::FreqTable< int > DEFM::motif_census (
    std::vector< size_t > idx ) [inline]
```

Definition at line 321 of file defm-meat.hpp.

8.20.3.17 print()

```
void DEFM::print ( ) const [inline]
```

Definition at line 426 of file defm-meat.hpp.

8.20.3.18 set_names()

```
void DEFM::set_names (
    std::vector< std::string > Y_names_,
    std::vector< std::string > X_names_ ) [inline]
```

Definition at line 401 of file defm-meat.hpp.

8.20.3.19 simulate()

```
void DEFM::simulate (
    std::vector< double > par,
    int * y_out ) [inline]
```

Definition at line 39 of file defm-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/models/defm/[defm-bones.hpp](#)
- include/barry/models/defm/[defm-meat.hpp](#)

8.21 DEFMCOUNTERDATA Class Reference

Data class used to store arbitrary size_t or double vectors.

```
#include <defm-types.hpp>
```

Public Member Functions

- [DEFMCOUNTERDATA](#) ()
- [DEFMCOUNTERDATA](#) (const std::vector< size_t > indices_, const std::vector< double > numbers_, const std::vector< bool > logical_, bool is_motif_=true)
- size_t [idx](#) (size_t i) const
- double [num](#) (size_t i) const
- bool [is_true](#) (size_t i) const
- [~DEFMCOUNTERDATA](#) ()

Public Attributes

- std::vector< size_t > [indices](#)
- std::vector< double > [numbers](#)
- std::vector< bool > [logical](#)
- bool [is_motif](#)

If false, then is a logit intercept.

8.21.1 Detailed Description

Data class used to store arbitrary size_t or double vectors.

Definition at line 64 of file defm-types.hpp.

The documentation for this class was generated from the following file:

- include/barry/models/defm/[defm-types.hpp](#)

8.22 DEFMDATA Class Reference

Data class for [DEFM](#) arrays.

```
#include <defm-types.hpp>
```

Public Member Functions

- [DEFMDData](#) ()
Vector indicating which covariates are included in the model.
- [DEFMDData](#) ([DEFMArray](#) *array_, const double *covariates_, size_t obs_start_, size_t X_ncol_, size_t X_nrow_)
Constructor.
- double [operator\(\)](#) (size_t i, size_t j) const
Access to the row (i) column (j) data.
- double [at](#) (size_t i, size_t j) const
- size_t [ncol](#) () const
- size_t [nrow](#) () const
- void [print](#) () const
- [~DEFMDData](#) ()

Public Attributes

- [DEFMArray](#) * [array](#)
- const double * [covariates](#)
Vector of covariates (complete vector)
- size_t [obs_start](#)
Index of the observation in the data.
- size_t [X_ncol](#)
Number of columns in the array of covariates.
- size_t [X_nrow](#)
Number of rows in the array of covariates.
- std::vector< size_t > [covar_sort](#)
- std::vector< size_t > [covar_used](#)
Value where the sorting of the covariates is stored.

8.22.1 Detailed Description

Data class for [DEFM](#) arrays.

This holds information pointing to the data array, including information regarding the number of observations, the time slices of the observation, and the number of covariates in the data.

Definition at line 16 of file [defm-types.hpp](#).


The documentation for this class was generated from the following file:

- [include/barry/models/defm/defm-types.hpp](#)

8.23 DEFMRuleData Class Reference

```
#include <defm-types.hpp>
```

Inheritance diagram for DEFMRuleData:



Public Member Functions

- double [num](#) (size_t [i](#)) const
- size_t [idx](#) (size_t [i](#)) const
- bool [is_true](#) (size_t [i](#)) const
- [DEFMRuleData](#) ()
- [DEFMRuleData](#) (std::vector< double > [numbers_](#), std::vector< size_t > [indices_](#), std::vector< bool > [logical_](#))
- [DEFMRuleData](#) (std::vector< double > [numbers_](#), std::vector< size_t > [indices_](#))

Public Attributes

- std::vector< double > [numbers](#)
- std::vector< size_t > [indices](#)
- std::vector< bool > [logical](#)
- bool [init](#) = false

8.23.1 Detailed Description

Definition at line 89 of file [defm-types.hpp](#).


The documentation for this class was generated from the following file:

- [include/barry/models/defm/defm-types.hpp](#)


8.24 DEFMRuleDynData Class Reference

```
#include <defm-types.hpp>
```

Inheritance diagram for DEFMRuleDynData:



Collaboration diagram for DEFMRuleDynData:



Public Member Functions

- [DEFMRuleDynData](#) (const std::vector< double > *counts_, std::vector< double > numbers_={}, std::vector< size_t > indices_={}, std::vector< bool > logical_={})
- [~DEFMRuleDynData](#) ()

Public Attributes

- const std::vector< double > * [counts](#)

8.24.1 Detailed Description

Definition at line 152 of file defm-types.hpp.

The documentation for this class was generated from the following file:

- include/barry/models/defm/[defm-types.hpp](#)

8.25 Entries< Cell_Type > Class Template Reference

A wrapper class to store `source`, `target`, `val` from a `BArray` object.

```
#include <typedefs.hpp>
```

Public Member Functions

- [Entries](#) ()
- [Entries](#) (size_t n)
- [~Entries](#) ()
- void [resize](#) (size_t n)

Public Attributes

- std::vector< size_t > [source](#)
- std::vector< size_t > [target](#)
- std::vector< Cell_Type > [val](#)

8.25.1 Detailed Description

```
template<typename Cell_Type>
class Entries< Cell_Type >
```

A wrapper class to store `source`, `target`, `val` from a `BArray` object.

Template Parameters

<i>Cell_Type</i>	Any type
------------------	----------

Definition at line 78 of file `typedefs.hpp`.

8.25.2 Constructor & Destructor Documentation

8.25.2.1 Entries() [1/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries ( ) [inline]
```

Definition at line 84 of file `typedefs.hpp`.

8.25.2.2 Entries() [2/2]

```
template<typename Cell_Type >
Entries< Cell_Type >::Entries (
    size_t n ) [inline]
```

Definition at line 85 of file typedefs.hpp.

8.25.2.3 ~Entries()

```
template<typename Cell_Type >
Entries< Cell_Type >::~~Entries ( ) [inline]
```

Definition at line 92 of file typedefs.hpp.

8.25.3 Member Function Documentation

8.25.3.1 resize()

```
template<typename Cell_Type >
void Entries< Cell_Type >::resize (
    size_t n ) [inline]
```

Definition at line 94 of file typedefs.hpp.

8.25.4 Member Data Documentation

8.25.4.1 source

```
template<typename Cell_Type >
std::vector< size_t > Entries< Cell_Type >::source
```

Definition at line 80 of file typedefs.hpp.

8.25.4.2 target

```
template<typename Cell_Type >
std::vector< size_t > Entries< Cell_Type >::target
```

Definition at line 81 of file typedefs.hpp.

8.25.4.3 val

```
template<typename Cell_Type >
std::vector< Cell_Type > Entries< Cell_Type >::val
```

Definition at line 82 of file typedefs.hpp.

The documentation for this class was generated from the following file:

- include/barry/typedefs.hpp

8.26 Flock Class Reference

A [Flock](#) is a group of [Geese](#).

```
#include <flock-bones.hpp>
```

Public Member Functions

- [Flock](#) ()
- [~Flock](#) ()
- [size_t add_data](#) (std::vector< std::vector< [size_t](#) > > &annotations, std::vector< [size_t](#) > &geneid, std::vector< [int](#) > &parent, std::vector< [bool](#) > &duplication)
Add a tree to the flock.
- void [set_seed](#) (const [size_t](#) &s)
Set the seed of the model.
- void [init](#) ([size_t](#) bar_width=[BARRY_PROGRESS_BAR_WIDTH](#))
- [PhyloCounters](#) * [get_counters](#) ()
- [PhyloSupport](#) * [get_support_fun](#) ()
- std::vector< std::vector< [double](#) > > * [get_stats_support](#) ()
- std::vector< std::vector< [double](#) > > * [get_stats_target](#) ()
- [PhyloModel](#) * [get_model](#) ()
- [double likelihood_joint](#) (const std::vector< [double](#) > &par, [bool](#) as_log=false, [bool](#) use_reduced_sequence=true)
Returns the joint likelihood of the model.
- [Geese](#) * [operator\(\)](#) ([size_t](#) i, [bool](#) check_bounds=true)
Access the i-th geese element.

Information about the model

- [size_t nfuncs](#) () const [noexcept](#)
- [size_t ntrees](#) () const [noexcept](#)
- std::vector< [size_t](#) > [nnodes](#) () const [noexcept](#)
- std::vector< [size_t](#) > [nleafs](#) () const [noexcept](#)
- [size_t nterms](#) () const
- [size_t support_size](#) () const [noexcept](#)
- std::vector< std::string > [colnames](#) () const
- [size_t parse_polytomies](#) ([bool](#) verb=true, std::vector< [size_t](#) > *dist=nullptr) const [noexcept](#)
Check polytomies and return the largest.
- void [print](#) () const

Public Attributes

- `std::vector< Geese > dat`
- `size_t nfunctions = 0u`
- `bool initialized = false`
- `std::mt19937 engine`
- `PhyloModel model = PhyloModel()`

8.26.1 Detailed Description

A [Flock](#) is a group of [Geese](#).

This object builds a model with multiple trees ([Geese](#) objects), with all of these using the same [PhyloModel](#) object. Available counters (terms) can be found in `counter-phylo`.

Definition at line 14 of file `flock-bones.hpp`.

8.26.2 Constructor & Destructor Documentation

8.26.2.1 Flock()

```
Flock::Flock ( ) [inline]
```

Definition at line 25 of file `flock-bones.hpp`.

8.26.2.2 ~Flock()

```
Flock::~Flock ( ) [inline]
```

Definition at line 26 of file `flock-bones.hpp`.

8.26.3 Member Function Documentation

8.26.3.1 add_data()

```
size_t Flock::add_data (
    std::vector< std::vector< size_t > > & annotations,
    std::vector< size_t > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Add a tree to the flock.

Parameters

<i>annotations</i>	see Geese::Geese .
<i>geneid</i>	see Geese .
<i>parent</i>	see Geese .
<i>duplication</i>	see Geese .

Returns

size_t The number of tree in the model (starting from zero).

Definition at line 6 of file flock-meat.hpp.

8.26.3.2 colnames()

```
std::vector< std::string > Flock::colnames ( ) const [inline]
```

Definition at line 224 of file flock-meat.hpp.

8.26.3.3 get_counters()

```
PhyloCounters * Flock::get_counters ( ) [inline]
```

Definition at line 100 of file flock-meat.hpp.

8.26.3.4 get_model()

```
PhyloModel * Flock::get_model ( ) [inline]
```

Definition at line 131 of file flock-meat.hpp.

8.26.3.5 get_stats_support()

```
std::vector< std::vector< double > > * Flock::get_stats_support ( ) [inline]
```

Definition at line 117 of file flock-meat.hpp.

8.26.3.6 get_stats_target()

```
std::vector< std::vector< double > > * Flock::get_stats_target ( ) [inline]
```

Definition at line 124 of file flock-meat.hpp.

8.26.3.7 get_support_fun()

```
PhyloSupport * Flock::get_support_fun ( ) [inline]
```

Definition at line 110 of file flock-meat.hpp.

8.26.3.8 init()

```
void Flock::init (
    size_t bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 49 of file flock-meat.hpp.

8.26.3.9 likelihood_joint()

```
double Flock::likelihood_joint (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Returns the joint likelihood of the model.

Parameters

<i>par</i>	Vector of model parameters.
<i>as_log</i>	When <code>true</code> it will return the value as log.
<i>use_reduced_sequence</i>	When <code>true</code> (default) will compute the likelihood using the reduced sequence, which is faster.

Returns

double

Definition at line 138 of file flock-meat.hpp.

8.26.3.10 nfuncs()

```
size_t Flock::nfuncs ( ) const [inline], [noexcept]
```

Definition at line 167 of file flock-meat.hpp.

8.26.3.11 nleafs()

```
std::vector< size_t > Flock::nleafs ( ) const [inline], [noexcept]
```

Definition at line 195 of file flock-meat.hpp.

8.26.3.12 nnodes()

```
std::vector< size_t > Flock::nnodes ( ) const [inline], [noexcept]
```

Definition at line 181 of file flock-meat.hpp.

8.26.3.13 nterms()

```
size_t Flock::nterms ( ) const [inline]
```

Definition at line 209 of file flock-meat.hpp.

8.26.3.14 ntrees()

```
size_t Flock::ntrees ( ) const [inline], [noexcept]
```

Definition at line 174 of file flock-meat.hpp.

8.26.3.15 operator>()()

```
Geese * Flock::operator() (
    size_t i,
    bool check_bounds = true ) [inline]
```

Access the i-th geese element.

Parameters

<i>i</i>	Element to access
<i>check_bounds</i>	When true, it will check bounds.

Returns

Geese*

Definition at line 302 of file flock-meat.hpp.

8.26.3.16 parse_polytomies()

```
size_t Flock::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 231 of file flock-meat.hpp.

8.26.3.17 print()

```
void Flock::print ( ) const [inline]
```

Definition at line 258 of file flock-meat.hpp.

8.26.3.18 set_seed()

```
void Flock::set_seed (
    const size_t & s ) [inline]
```

Set the seed of the model.

Parameters

<i>s</i>	Passed to the <code>rengine.seed()</code> member object.
----------	--

Definition at line 42 of file flock-meat.hpp.

8.26.3.19 support_size()

```
size_t Flock::support_size ( ) const [inline], [noexcept]
```

Definition at line 217 of file flock-meat.hpp.

8.26.4 Member Data Documentation

8.26.4.1 dat

```
std::vector< Geese > Flock::dat
```

Definition at line 17 of file flock-bones.hpp.

8.26.4.2 initialized

```
bool Flock::initialized = false
```

Definition at line 19 of file flock-bones.hpp.

8.26.4.3 model

```
PhyloModel Flock::model = PhyloModel()
```

Definition at line 23 of file flock-bones.hpp.

8.26.4.4 nfunctions

```
size_t Flock::nfunctions = 0u
```

Definition at line 18 of file flock-bones.hpp.

8.26.4.5 engine

```
std::mt19937 Flock::engine
```

Definition at line 22 of file flock-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/models/geese/flock-bones.hpp
- include/barry/models/geese/flock-meat.hpp

8.27 FreqTable< T > Class Template Reference

Frequency table of vectors.

```
#include <freqtable.hpp>
```

Public Member Functions

- [FreqTable](#) ()
- [~FreqTable](#) ()
- [size_t add](#) (const std::vector< T > &x, size_t *h_precomp)
- [Counts_type as_vector](#) () const
- const std::vector< double > & [get_data](#) () const
- const std::unordered_map< size_t, size_t > & [get_index](#) () const
- void [clear](#) ()
- void [reserve](#) (size_t n, size_t k)
- void [print](#) () const
- [size_t size](#) () const [noexcept](#)
- *Number of unique elements in the table. (.*
- [size_t make_hash](#) (const std::vector< T > &x) const

8.27.1 Detailed Description

```
template<typename T = double>
class FreqTable< T >
```

Frequency table of vectors.

This is mostly used in [Support](#). The main data is contained in the `data` double vector. The matrix is stored in a row-wise fashion, where the first element is the frequency with which the vector is observed.

For example, in a model with `k` terms the first `k + 1` elements of `data` would be:

- weights
- term 1
- term 2
- ...
- term k

Definition at line 22 of file freqtable.hpp.

8.27.2 Constructor & Destructor Documentation

8.27.2.1 FreqTable()

```
template<typename T = double>
FreqTable< T >::FreqTable ( ) [inline]
```

Definition at line 34 of file freqtable.hpp.

8.27.2.2 ~FreqTable()

```
template<typename T = double>
FreqTable< T >::~~FreqTable ( ) [inline]
```

Definition at line 35 of file freqtable.hpp.

8.27.3 Member Function Documentation

8.27.3.1 add()

```
template<typename T >
size_t FreqTable< T >::add (
    const std::vector< T > & x,
    size_t * h_precomp ) [inline]
```

Definition at line 59 of file freqtable.hpp.

8.27.3.2 as_vector()

```
template<typename T >
Counts_type FreqTable< T >::as_vector [inline]
```

Definition at line 139 of file freqtable.hpp.

8.27.3.3 clear()

```
template<typename T >
void FreqTable< T >::clear [inline]
```

Definition at line 168 of file freqtable.hpp.

8.27.3.4 get_data()

```
template<typename T = double>
const std::vector< double >& FreqTable< T >::get_data ( ) const [inline]
```

Definition at line 40 of file freqtable.hpp.

8.27.3.5 get_index()

```
template<typename T = double>
const std::unordered_map<size_t,size_t>& FreqTable< T >::get_index ( ) const [inline]
```

Definition at line 41 of file freqtable.hpp.

8.27.3.6 make_hash()

```
template<typename T >
size_t FreqTable< T >::make_hash (
    const std::vector< T > & x ) const [inline]
```

Definition at line 239 of file freqtable.hpp.

8.27.3.7 print()

```
template<typename T >
void FreqTable< T >::print [inline]
```

Definition at line 204 of file freqtable.hpp.

8.27.3.8 reserve()

```
template<typename T >
void FreqTable< T >::reserve (
    size_t n,
    size_t k ) [inline]
```

Definition at line 182 of file freqtable.hpp.

8.27.3.9 size()

```
template<typename T >
size_t FreqTable< T >::size [inline], [noexcept]
```

Number of unique elements in the table. (.

Returns

size_t

Definition at line 231 of file freqtable.hpp.

The documentation for this class was generated from the following file:

- include/barry/freqtable.hpp

8.28 Geese Class Reference

Annotated Phylo [Model](#).

```
#include <geese-bones.hpp>
```

Public Member Functions

- [~Geese](#) ()
- void [init](#) (size_t bar_width=[BARRY_PROGRESS_BAR_WIDTH](#))
- void [inherit_support](#) (const [Geese](#) &model_, bool delete_support_=false)
- void [calc_sequence](#) ([Node](#) *n=nullptr)
- void [calc_reduced_sequence](#) ()
- double [likelihood](#) (const std::vector< double > &par, bool as_log=false, bool use_reduced_sequence=true)
- double [likelihood_exhaust](#) (const std::vector< double > &par)
- std::vector< double > [get_probabilities](#) () const
- void [set_seed](#) (const size_t &s)
- std::vector< std::vector< size_t > > [simulate](#) (const std::vector< double > &par)
- std::vector< std::vector< double > > [observed_counts](#) ()
- void [print_observed_counts](#) ()
- void [print](#) () const

Prints information about the GEESE.

- void `print_nodes` () const
- void `init_node` (Node &n)
- void `update_annotations` (size_t nodeid, std::vector< size_t > newann)
- std::vector< std::vector< bool > > `get_states` () const
Powerset of a gene's possible states.
- std::vector< size_t > `get_annotated_nodes` () const
Returns the ids of the nodes with at least one annotation.
- std::vector< size_t > `get_annotations` () const
Returns the annotations of the nodes with at least one annotation.

Construct a new Geese object

The model includes a total of $N + 1$ nodes, the $+ 1$ beign the root node.

Parameters

annotations	A vector of vectors with annotations. It should be of length k (number of functions). Each vector should be of length N (equal to the number of nodes, including interior). Possible values are 0, 1, and 9.
geneid	Id of the gene. It should be of length N .
parent	Id of the parent gene. Also of length N
duplication	Logical scalar indicating the type of event (true: duplication, false: speciation.)

The ordering of the entries does not matter. Passing the nodes in post order or not makes no difference to the constructor.

- `Geese` ()
- `Geese` (std::vector< std::vector< size_t > > &annotations, std::vector< size_t > &geneid, std::vector< int > &parent, std::vector< bool > &duplication)
- `Geese` (const `Geese` &model_, bool copy_data=true)
- `Geese` (`Geese` &&x) `noexcept`
- `Geese` & `operator=` (const `Geese` &model_)=delete
- `Geese` & `operator=` (`Geese` &&model_) `noexcept=delete`

Information about the model

Parameters

verb	When <code>true</code> it will print out information about the encountered polytomies.
------	--

- size_t `nfuncs` () const `noexcept`
Number of functions analyzed.
- size_t `nnodes` () const `noexcept`
Number of nodes (interior + leaf)
- size_t `nleafs` () const `noexcept`
Number of leaf.
- size_t `nterms` () const
Number of terms included.
- size_t `support_size` () const `noexcept`
Number of unique sets of sufficient stats.
- std::vector< size_t > `nannotations` () const `noexcept`
Number of annotations.
- std::vector< std::string > `colnames` () const
Names of the terms in the model.
- size_t `parse_polytomies` (bool verb=true, std::vector< size_t > *dist=nullptr) const `noexcept`

Check polytomies and return the largest.

Geese prediction

Calculate the conditional probability

Parameters

par	Vector of parameters (terms + root).
res_prob	Vector indicating each nodes' state probability.
leave_one_out	When <i>true</i> , it will compute the predictions using leave-one-out, thus the prediction will be repeated <i>nleaf</i> times.
only_annotated	When <i>true</i> , it will make the predictions only on the induced sub-tree with annotated leafs.
use_reduced_sequence	Passed to the <i>likelihood</i> method.
preorder	For the tree traversal.

When *res_prob* is specified, the function will attach the member vector *probabilities* from the [Nodes](#) objects. This contains the probability that the *i*th node has either of the possible states.

Returns

std::vector< double > Returns the posterior probability

- *std::vector< std::vector< double > >* [predict](#) (const *std::vector< double >* &par, *std::vector< std::vector< double > >* *res_prob=nullptr, bool leave_one_out=false, bool only_annotated=false, bool use_reduced_sequence=true)
- *std::vector< std::vector< double > >* [predict_backend](#) (const *std::vector< double >* &par, bool use_reduced_sequence, const *std::vector< size_t >* &preorder)
- *std::vector< std::vector< double > >* [predict_exhaust_backend](#) (const *std::vector< double >* &par, const *std::vector< size_t >* &preorder)
- *std::vector< std::vector< double > >* [predict_exhaust](#) (const *std::vector< double >* &par)
- *std::vector< std::vector< double > >* [predict_sim](#) (const *std::vector< double >* &par, bool only_annotated=false, *size_t* nsims=10000u)

Non-const pointers to shared objects in `<tt>Geese</tt>`

These functions provide direct access to some member objects that are shared by the nodes within [Geese](#).

Returns

[get_engine\(\)](#) returns the Pseudo-RNG engine used.
[get_counters\(\)](#) returns the vector of counters used.
[get_model\(\)](#) returns the [Model](#) object used.
[get_support_fun\(\)](#) returns the computed support of the model.

- *std::mt19937* * [get_engine\(\)](#)
- [PhyloCounters](#) * [get_counters\(\)](#)
- [PhyloModel](#) * [get_model\(\)](#)
- [PhyloSupport](#) * [get_support_fun\(\)](#)

Public Attributes

- *size_t* [nfunctions](#)
- *std::map< size_t, Node >* [nodes](#)
- [barry::MapVec_type< size_t >](#) [map_to_state_id](#)
- *std::vector< std::vector< std::vector< size_t > > >* [pset_loc](#)

Locations of columns.

- `std::vector< size_t >` [sequence](#)
- `std::vector< size_t >` [reduced_sequence](#)
- `bool` [initialized](#) = false
- `bool` [delete_engine](#) = false
- `bool` [delete_support](#) = false

Static Public Attributes

- static const `size_t` [etype_default](#) = 1ul
- static const `size_t` [etype_speciation](#) = 0ul
- static const `size_t` [etype_duplication](#) = 1ul
- static const `size_t` [etype_either](#) = 2ul

8.28.1 Detailed Description

Annotated Phylo [Model](#).

A list of available terms for this model can be found in the [Phylo counters](#) section.

Class representing a phylogenetic tree model with annotations.

The [Geese](#) class represents a phylogenetic tree model with annotations. It includes a total of $N + 1$ nodes, the $+ 1$ being the root node. The class provides methods for initializing the model, calculating the likelihood, simulating trees, and making predictions.

The class includes shared objects within a [Geese](#) object, such as `engine`, `model`, `states`, `n_zeros`, `n_ones`, `n_dupl_events`, and `n_spec_events`. It also includes information about the type of event, such as `etype_default`, `etype_speciation`, `etype_duplication`, and `etype_either`.

The class provides constructors, a destructor, and methods for initializing the model, inheriting support, calculating the sequence, calculating the reduced sequence, calculating the likelihood, calculating the likelihood exhaustively, getting probabilities, setting the seed, simulating trees, parsing polytomies, getting observed counts, printing observed counts, printing information about the GEESE, and making predictions.

See also

[Flock](#)

Definition at line 103 of file `geese-bones.hpp`.

8.28.2 Constructor & Destructor Documentation

8.28.2.1 Geese() [1/4]

```
Geese::Geese ( ) [inline]
```

Definition at line 6 of file geese-meat-constructors.hpp.

8.28.2.2 Geese() [2/4]

```
Geese::Geese (
    std::vector< std::vector< size_t > > & annotations,
    std::vector< size_t > & geneid,
    std::vector< int > & parent,
    std::vector< bool > & duplication ) [inline]
```

Definition at line 20 of file geese-meat-constructors.hpp.

8.28.2.3 Geese() [3/4]

```
Geese::Geese (
    const Geese & model_,
    bool copy_data = true ) [inline]
```

Definition at line 230 of file geese-meat-constructors.hpp.

8.28.2.4 Geese() [4/4]

```
Geese::Geese (
    Geese && x ) [inline], [noexcept]
```

Definition at line 309 of file geese-meat-constructors.hpp.

8.28.2.5 ~Geese()

```
Geese::~Geese ( ) [inline]
```

Definition at line 119 of file geese-meat.hpp.

8.28.3 Member Function Documentation

8.28.3.1 calc_reduced_sequence()

```
void Geese::calc_reduced_sequence ( ) [inline]
```

Definition at line 358 of file geese-meat.hpp.

8.28.3.2 calc_sequence()

```
void Geese::calc_sequence (
    Node * n = nullptr ) [inline]
```

Definition at line 314 of file geese-meat.hpp.

8.28.3.3 colnames()

```
std::vector< std::string > Geese::colnames ( ) const [inline]
```

Names of the terms in the model.

Definition at line 480 of file geese-meat.hpp.

8.28.3.4 get_annotated_nodes()

```
std::vector< size_t > Geese::get_annotated_nodes ( ) const [inline]
```

Returns the ids of the nodes with at least one annotation.

Definition at line 769 of file geese-meat.hpp.

8.28.3.5 get_annotations()

```
std::vector< size_t > Geese::get_annotations ( ) const [inline]
```

Returns the annotations of the nodes with at least one annotation.

Definition at line 792 of file geese-meat.hpp.

8.28.3.6 get_counters()

```
PhyloCounters * Geese::get_counters ( ) [inline]
```

Definition at line 752 of file geese-meat.hpp.

8.28.3.7 get_model()

```
PhyloModel * Geese::get_model ( ) [inline]
```

Definition at line 757 of file geese-meat.hpp.

8.28.3.8 get_probabilities()

```
std::vector< double > Geese::get_probabilities ( ) const [inline]
```

Definition at line 406 of file geese-meat.hpp.

8.28.3.9 get_rengine()

```
std::mt19937 * Geese::get_rengine ( ) [inline]
```

Definition at line 747 of file geese-meat.hpp.

8.28.3.10 get_states()

```
std::vector< std::vector< bool > > Geese::get_states ( ) const [inline]
```

Powerset of a gene's possible states.

This list of vectors is used throughout [Geese](#). It lists all possible combinations of functional states for any gene. Thus, for P functions, there will be 2^P possible combinations.

Returns

`std::vector< std::vector< bool > >` of length 2^P .

Definition at line 765 of file geese-meat.hpp.

8.28.3.11 get_support_fun()

```
PhyloSupport * Geese::get_support_fun ( ) [inline]
```

Definition at line 761 of file geese-meat.hpp.

8.28.3.12 inherit_support()

```
void Geese::inherit_support (
    const Geese & model_,
    bool delete_support_ = false ) [inline]
```

Definition at line 257 of file geese-meat.hpp.

8.28.3.13 init()

```
void Geese::init (
    size_t bar_width = BARRY_PROGRESS_BAR_WIDTH ) [inline]
```

Definition at line 131 of file geese-meat.hpp.

8.28.3.14 init_node()

```
void Geese::init_node (
    Node & n ) [inline]
```

Definition at line 6 of file geese-meat.hpp.

8.28.3.15 likelihood()

```
double Geese::likelihood (
    const std::vector< double > & par,
    bool as_log = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 6 of file geese-meat-likelihood.hpp.

8.28.3.16 likelihood_exhaust()

```
double Geese::likelihood_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 7 of file geese-meat-likelihood_exhaust.hpp.

8.28.3.17 nannotations()

```
std::vector< size_t > Geese::nannotations ( ) const [inline], [noexcept]
```

Number of annotations.

Definition at line 471 of file geese-meat.hpp.

8.28.3.18 nfuncs()

```
size_t Geese::nfuncs ( ) const [inline], [noexcept]
```

Number of functions analyzed.

Definition at line 427 of file geese-meat.hpp.

8.28.3.19 nleafs()

```
size_t Geese::nleafs ( ) const [inline], [noexcept]
```

Number of leaf.

Definition at line 441 of file geese-meat.hpp.

8.28.3.20 nnodes()

```
size_t Geese::nnodes ( ) const [inline], [noexcept]
```

Number of nodes (interior + leaf)

Definition at line 434 of file geese-meat.hpp.

8.28.3.21 nterms()

```
size_t Geese::nterms ( ) const [inline]
```

Number of terms included.

Definition at line 453 of file geese-meat.hpp.

8.28.3.22 observed_counts()

```
std::vector< std::vector< double > > Geese::observed_counts ( ) [inline]
```

Definition at line 522 of file geese-meat.hpp.

8.28.3.23 operator=() [1/2]

```
Geese& Geese::operator= (
    const Geese & model_ ) [delete]
```

8.28.3.24 operator=() [2/2]

```
Geese& Geese::operator= (
    Geese && model_ ) [delete], [noexcept]
```

8.28.3.25 parse_polytomies()

```
size_t Geese::parse_polytomies (
    bool verb = true,
    std::vector< size_t > * dist = nullptr ) const [inline], [noexcept]
```

Check polytomies and return the largest.

Definition at line 487 of file geese-meat.hpp.

8.28.3.26 predict()

```
std::vector< std::vector< double > > Geese::predict (
    const std::vector< double > & par,
    std::vector< std::vector< double > > * res_prob = nullptr,
    bool leave_one_out = false,
    bool only_annotated = false,
    bool use_reduced_sequence = true ) [inline]
```

Definition at line 287 of file geese-meat-predict.hpp.

8.28.3.27 predict_backend()

```
std::vector< std::vector< double > > Geese::predict_backend (
    const std::vector< double > & par,
    bool use_reduced_sequence,
    const std::vector< size_t > & preorder ) [inline]
```

< True if the array belongs to the set

Definition at line 6 of file geese-meat-predict.hpp.

8.28.3.28 predict_exhaust()

```
std::vector< std::vector< double > > Geese::predict_exhaust (
    const std::vector< double > & par ) [inline]
```

Definition at line 5 of file geese-meat-predict_exhaust.hpp.

8.28.3.29 predict_exhaust_backend()

```
std::vector< std::vector< double > > Geese::predict_exhaust_backend (
    const std::vector< double > & par,
    const std::vector< size_t > & preorder ) [inline]
```

Definition at line 47 of file geese-meat-predict_exhaust.hpp.

8.28.3.30 predict_sim()

```
std::vector< std::vector< double > > Geese::predict_sim (
    const std::vector< double > & par,
    bool only_annotated = false,
    size_t nsims = 10000u ) [inline]
```

Definition at line 6 of file geese-meat-predict_sim.hpp.

8.28.3.31 print()

```
void Geese::print ( ) const [inline]
```

Prints information about the GEESE.

Definition at line 656 of file geese-meat.hpp.

8.28.3.32 print_nodes()

```
void Geese::print_nodes ( ) const [inline]
```

Definition at line 674 of file geese-meat.hpp.

8.28.3.33 print_observed_counts()

```
void Geese::print_observed_counts ( ) [inline]
```

Definition at line 593 of file geese-meat.hpp.

8.28.3.34 set_seed()

```
void Geese::set_seed (
    const size_t & s ) [inline]
```

Definition at line 4 of file geese-meat-simulate.hpp.

8.28.3.35 simulate()

```
std::vector< std::vector< size_t > > Geese::simulate (
    const std::vector< double > & par ) [inline]
```

Definition at line 8 of file geese-meat-simulate.hpp.

8.28.3.36 support_size()

```
size_t Geese::support_size ( ) const [inline], [noexcept]
```

Number of unique sets of sufficient stats.

Definition at line 461 of file geese-meat.hpp.

8.28.3.37 update_annotations()

```
void Geese::update_annotations (
    size_t nodeid,
    std::vector< size_t > newann ) [inline]
```

Definition at line 285 of file geese-meat.hpp.

8.28.4 Member Data Documentation

8.28.4.1 delete_engine

```
bool Geese::delete_engine = false
```

Definition at line 142 of file geese-bones.hpp.

8.28.4.2 delete_support

```
bool Geese::delete_support = false
```

Definition at line 143 of file geese-bones.hpp.

8.28.4.3 etype_default

```
const size_t Geese::etype_default = 1ul [static]
```

Definition at line 156 of file geese-bones.hpp.

8.28.4.4 etype_duplication

```
const size_t Geese::etype_duplication = 1ul [static]
```

Definition at line 158 of file geese-bones.hpp.

8.28.4.5 etype_either

```
const size_t Geese::etype_either = 2ul [static]
```

Definition at line 159 of file geese-bones.hpp.

8.28.4.6 etype_speciation

```
const size_t Geese::etype_speciation = 0ul [static]
```

Definition at line 157 of file geese-bones.hpp.

8.28.4.7 initialized

```
bool Geese::initialized = false
```

Definition at line 141 of file geese-bones.hpp.

8.28.4.8 map_to_state_id

```
barry::MapVec_type< size_t > Geese::map_to_state_id
```

Definition at line 133 of file geese-bones.hpp.

8.28.4.9 nfunctions

```
size_t Geese::nfunctions
```

Definition at line 130 of file geese-bones.hpp.

8.28.4.10 nodes

```
std::map< size_t, Node > Geese::nodes
```

Definition at line 131 of file geese-bones.hpp.

8.28.4.11 pset_loc

```
std::vector< std::vector< std::vector< size_t > > > Geese::pset_loc
```

Locations of columns.

Definition at line 134 of file geese-bones.hpp.

8.28.4.12 reduced_sequence

```
std::vector< size_t > Geese::reduced_sequence
```

Definition at line 138 of file geese-bones.hpp.

8.28.4.13 sequence

```
std::vector< size_t > Geese::sequence
```

Definition at line 137 of file geese-bones.hpp.

The documentation for this class was generated from the following files:


- include/barry/models/geese/[geese-bones.hpp](#)
- include/barry/models/geese/[geese-meat-constructors.hpp](#)
- include/barry/models/geese/[geese-meat-likelihood.hpp](#)
- include/barry/models/geese/[geese-meat-likelihood_exhaust.hpp](#)
- include/barry/models/geese/[geese-meat-predict.hpp](#)
- include/barry/models/geese/[geese-meat-predict_exhaust.hpp](#)
- include/barry/models/geese/[geese-meat-predict_sim.hpp](#)
- include/barry/models/geese/[geese-meat-simulate.hpp](#)
- include/barry/models/geese/[geese-meat.hpp](#)

8.29 Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

```
#include <model-bones.hpp>
```

Collaboration diagram for Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >:



Public Member Functions

- void [set_engine](#) (std::mt19937 *engine_, bool delete_=false)
- void [set_seed](#) (size_t s)
- [Model](#) ()
- [Model](#) (size_t size_)
- [Model](#) (const [Model](#)< Array_Type, [Data_Counter_Type](#), [Data_Rule_Type](#), Data_Rule_Dyn_Type > &Model_)
- [Model](#)< Array_Type, [Data_Counter_Type](#), [Data_Rule_Type](#), Data_Rule_Dyn_Type > & [operator=](#) (const [Model](#)< Array_Type, [Data_Counter_Type](#), [Data_Rule_Type](#), Data_Rule_Dyn_Type > &Model_)
- virtual [~Model](#) ()
- void [store_psets](#) () [noexcept](#)
- std::vector< double > [gen_key](#) (const Array_Type &Array_)
- size_t [add_array](#) (const Array_Type &Array_, bool [force_new](#)=false)
Adds an array to the support of not already included.
- void [print_stats](#) (size_t i) const
- virtual void [print](#) () const
Prints information about the model.
- Array_Type [sample](#) (const Array_Type &Array_, const std::vector< double > &[params](#)={})
- Array_Type [sample](#) (const size_t &i, const std::vector< double > &[params](#))
- double [conditional_prob](#) (const Array_Type &Array_, const std::vector< double > &[params](#), size_t i, size_t j)
Conditional probability ("Gibbs sampler")
- const std::mt19937 * [get_engine](#) () const
- [Counters](#)< Array_Type, [Data_Counter_Type](#) > * [get_counters](#) ()

- [Rules](#)< Array_Type, [Data_Rule_Type](#) > * [get_rules](#) ()
- [Rules](#)< Array_Type, [Data_Rule_Dyn_Type](#) > * [get_rules_dyn](#) ()
- [Support](#)< Array_Type, [Data_Counter_Type](#), [Data_Rule_Type](#), [Data_Rule_Dyn_Type](#) > * [get_support_fun](#) ()

Wrappers for the `Counters` member.

These will add counters to the model, which are shared by the support and the actual counter function.

- void [add_counter](#) ([Counter](#)< Array_Type, [Data_Counter_Type](#) > &counter)
- void [add_counter](#) ([Counter_fun_type](#)< Array_Type, [Data_Counter_Type](#) > count_fun_, [Counter_fun_type](#)< Array_Type, [Data_Counter_Type](#) > init_fun_=nullptr, [Data_Counter_Type](#) data_=nullptr)
- void [set_counters](#) ([Counters](#)< Array_Type, [Data_Counter_Type](#) > *counters_)
- void [add_hasher](#) ([Hasher_fun_type](#)< Array_Type, [Data_Counter_Type](#) > fun_)

Wrappers for the `Rules` member.

These will add rules to the model, which are shared by the support and the actual counter function.

- void [add_rule](#) ([Rule](#)< Array_Type, [Data_Rule_Type](#) > &rule)
- void [add_rule](#) ([Rule_fun_type](#)< Array_Type, [Data_Rule_Type](#) > count_fun_, [Data_Rule_Type](#) data_)
- void [set_rules](#) ([Rules](#)< Array_Type, [Data_Rule_Type](#) > *rules_)
- void [add_rule_dyn](#) ([Rule](#)< Array_Type, [Data_Rule_Dyn_Type](#) > &rule)
- void [add_rule_dyn](#) ([Rule_fun_type](#)< Array_Type, [Data_Rule_Dyn_Type](#) > count_fun_, [Data_Rule_Dyn_Type](#) data_)
- void [set_rules_dyn](#) ([Rules](#)< Array_Type, [Data_Rule_Dyn_Type](#) > *rules_)

Likelihood functions.

Calculation of likelihood functions is done reusing normalizing constants. Before recalculating the normalizing constant, the function checks whether *params* matches the last set vector of parameters used to compute it.

Parameters

params	Vector of parameters
as_log	When <i>true</i> , the function returns the log-likelihood.

- double [likelihood](#) (const std::vector< double > ¶ms, const size_t &i, bool as_log=false)
- double [likelihood](#) (const std::vector< double > ¶ms, const Array_Type &Array_, int i=-1, bool as_log=false)
- double [likelihood](#) (const std::vector< double > ¶ms, const std::vector< double > &target_, const size_t &i, bool as_log=false)
- double [likelihood](#) (const std::vector< double > ¶ms, const double *target_, const size_t &i, bool as_log=false)
- double [likelihood_total](#) (const std::vector< double > ¶ms, bool as_log=false)

Extract elements by index

Parameters

i	Index relative to the array in the model.
params	A new vector of model parameters to compute the normalizing constant.
as_log	When <i>true</i> returns the logged version of the normalizing constant.

- double [get_norm_const](#) (const std::vector< double > ¶ms, const size_t &i, bool as_log=false)
- const std::vector< Array_Type > * [get_pset](#) (const size_t &i)
- const std::vector< double > * [get_pset_stats](#) (const size_t &i)

Size of the model

Number of different supports included in the model

This will return the size of `stats_target`.

Returns

`size()` returns the number of arrays in the model.

`size_unique()` returns the number of unique arrays (according to the hasher) in the model.

`nterms()` returns the number of terms in the model.

- `size_t size()` const noexcept
 - `size_t size_unique()` const noexcept
 - `size_t nterms()` const noexcept
 - `size_t nrules()` const noexcept
 - `size_t nrules_dyn()` const noexcept
 - `size_t support_size()` const noexcept
 - `std::vector< std::string > colnames()` const
-
- `std::vector< std::vector< double > > * get_stats_target()`
Raw pointers to the support and target statistics.
 - `std::vector< std::vector< double > > * get_stats_support()`
 - `std::vector< size_t > * get_arrays2support()`
 - `std::vector< std::vector< Array_Type > > * get_pset_arrays()`
 - `std::vector< std::vector< double > > * get_pset_stats()`
Statistics of the support(s)
 - `std::vector< std::vector< double > > * get_pset_probs()`
-
- void `set_transform_model` (std::function< std::vector< double >(double *, size_t)> fun, std::vector< std::string > names)
Set the transform_model_fun object.
 - `std::vector< double > transform_model` (double *data, size_t k)

Protected Attributes

- `MapVec_type< double, size_t > keys2support`
Map of types of arrays to support sets.
- `std::vector< std::vector< double > > params_last`
Vector of the previously used parameters.
- `std::vector< double > normalizing_constants`
- `std::vector< bool > first_calc_done`
- `bool delete_counters = false`
- `bool delete_rules = false`
- `bool delete_rules_dyn = false`
- `std::function< std::vector< double >(double *, size_t k)> transform_model_fun = nullptr`
Transformation of the model.
- `std::vector< std::string > transform_model_term_names`

Random number generation

Random number generation

- `std::mt19937 * engine = nullptr`
- `bool delete_engine = false`

Information about the arrays used in the model

stats_target holds the observed sufficient statistics for each array in the dataset. *array_↔ frequency* contains the frequency with which each of the target *stats_target* (arrays) shows in the support. *array2support* maps array indices (0, 1, ...) to the corresponding support.

Each vector of *stats_support* has the data stored in a row-wise order, with each row starting with the weights, e.g., in a model with k terms the first $k + 1$ elements of *stats_support* would be:

- *weights*
- *term 1*
- *term 2*
- ...
- *term k*
- `std::vector< std::vector< double > > stats_support`
Sufficient statistics of the model (support)
- `std::vector< size_t > stats_support_n_arrays`
Number of arrays included per support.
- `std::vector< std::vector< double > > stats_target`
Target statistics of the model.
- `std::vector< size_t > arrays2support`

Container space for the powerset (and its sufficient stats_target)

This is useful in the case of using simulations or evaluating functions that need to account for the full set of states.

- `bool with_pset = false`
- `std::vector< std::vector< Array_Type > > pset_arrays`
Arrays of the support(s)
- `std::vector< std::vector< double > > pset_stats`
Statistics of the support(s)
- `std::vector< std::vector< double > > pset_probs`
Probabilities of the support(s)

Functions to compute statistics

Arguments are recycled to save memory and computation.

- `Counters< Array_Type, Data_Counter_Type > * counters`
- `Rules< Array_Type, Data_Rule_Type > * rules`
- `Rules< Array_Type, Data_Rule_Dyn_Type > * rules_dyn`
- `Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > support_fun`
- `StatsCounter< Array_Type, Data_Counter_Type > counter_fun`

8.29.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename
Data_Rule_Dyn_Type = bool>
class Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

$$\frac{\exp\left(\theta^t c(A)\right)}{\sum_{A' \in \mathcal{A}} \exp\left(\theta^t c(A')\right)}$$

This implementation aims to reduce the number of times that the support needs to be computed. Models included here use more than a single array, and thus allow the function to recycle support sets as needed. For example, if we are looking at directed graphs all of the same size and without vertex level features, i.e. a model that only counts edges, triangles, etc. then the support needs to be fully computed only once.

Template Parameters

<i>Array_Type</i>	Class of BArray object.
<i>Data_Counter_Type</i>	Any type.
<i>Data_Rule_Type</i>	Any type.

Definition at line 34 of file model-bones.hpp.

8.29.2 Constructor & Destructor Documentation

8.29.2.1 Model() [1/3]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data_Rule_Dyn_Type >::Model [inline]
```

Definition at line 140 of file model-meat.hpp.

8.29.2.2 Model() [2/3]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data\_Counter\_Type, Data\_Rule\_Type, Data_Rule_Dyn_Type >::Model (
    size_t size_ ) [inline]
```

Definition at line 174 of file model-meat.hpp.

8.29.2.3 Model() [3/3]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Model (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
    & Model_ ) [inline]
```

Definition at line 212 of file model-meat.hpp.

8.29.2.4 ~Model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
virtual Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~~Model (
) [inline], [virtual]
```

Definition at line 159 of file model-bones.hpp.

8.29.3 Member Function Documentation

8.29.3.1 add_array()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_array (
    const Array_Type & Array_,
    bool force_new = false )
```

Adds an array to the support of not already included.

Parameters

<i>Array_</i>	array to be added
<i>force_new</i>	If false, it will use keygen to obtain a double vector and create a hash of it. If the hash has been computed earlier, the support is recycled.

Returns

The number of the array.

8.29.3.2 add_counter() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter< Array_Type, Data_Counter_Type > & counter )
```

8.29.3.3 add_counter() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter (
    Counter_fun_type< Array_Type, Data_Counter_Type > count_fun_,
    Counter_fun_type< Array_Type, Data_Counter_Type > init_fun_ = nullptr,
    Data_Counter_Type data_ = nullptr )
```

8.29.3.4 add_hasher()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_hasher (
    Hasher_fun_type< Array_Type, Data_Counter_Type > fun_ )
```

8.29.3.5 add_rule() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > & rule )
```

8.29.3.6 add_rule() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ )
```

8.29.3.7 add_rule_dyn() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule< Array_Type, Data_Rule_Dyn_Type > & rule )
```

8.29.3.8 add_rule_dyn() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_dyn
(
    Rule_fun_type< Array_Type, Data_Rule_Dyn_Type > count_fun_,
    Data_Rule_Dyn_Type data_ )
```

8.29.3.9 colnames()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::string > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_↵
Dyn_Type >::colnames ( ) const
```

8.29.3.10 conditional_prob()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::conditional↵
_prob (
    const Array_Type & Array_,
    const std::vector< double > & params,
    size_t i,
    size_t j )
```

Conditional probability ("Gibbs sampler")

Computes the conditional probability of observing $P\{Y(i,j) = Y^C, \theta\}$, i.e., the probability of observing the entry $Y(i,j)$ equal to one given the rest of the array.

Parameters

<i>Array_↵</i>	Array to check
<i>params</i>	Vector of parameters
<i>i</i>	Row entry
<i>j</i>	Column entry

Returns

double The conditional probability

8.29.3.11 gen_key()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
Type >::gen_key (
    const Array_Type & Array_ )
```

8.29.3.12 get_arrays2support()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
Type >::get_arrays2support ( )
```

8.29.3.13 get_counters()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Counters<Array_Type,Data_Counter_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_counters ( )
```

8.29.3.14 get_norm_const()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_norm_↵
const (
    const std::vector< double > & params,
    const size_t & i,
    bool as_log = false )
```

8.29.3.15 get_pset()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< Array_Type >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
_Rule_Dyn_Type >::get_pset (
    const size_t & i )
```

8.29.3.16 get_pset_arrays()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< Array_Type > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_pset_arrays ( )
```

8.29.3.17 get_pset_probs()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_pset_probs ( )
```

8.29.3.18 get_pset_stats() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_pset_stats ( )
```

Statistics of the support(s)

8.29.3.19 get_pset_stats() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::vector< double >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::get_pset_stats (
    const size_t & i )
```

8.29.3.20 get_engine()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
const std::mt19937* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::get_engine ( ) const
```

8.29.3.21 get_rules()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
_Rule_Dyn_Type >::get_rules ( )
```

8.29.3.22 get_rules_dyn()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type,Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn ( )
```

8.29.3.23 get_stats_support()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_stats_support ( )
```

8.29.3.24 get_stats_target()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > >* Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_stats_target ( )
```

Raw pointers to the support and target statistics.

The support of the model is stored as a vector of vector<double>. Each element of it contains the support for an specific type of array included. It represents an array of size $(k + 1) \times n$ unique elements, with the data stored by-row. The last element of each entry corresponds to the weights, i.e., the frequency with which such sufficient statistics are observed in the support.

8.29.3.25 get_support_fun()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type>* Model< Array_Type,
Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_support_fun ( )
```

8.29.3.26 likelihood() [1/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const Array_Type & Array_,
    int i = -1,
    bool as_log = false )
```

8.29.3.27 likelihood() [2/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const double * target_,
    const size_t & i,
    bool as_log = false )
```

8.29.3.28 likelihood() [3/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const size_t & i,
    bool as_log = false )
```


8.29.3.29 likelihood() [4/4]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood
(
    const std::vector< double > & params,
    const std::vector< double > & target_,
    const size_t & i,
    bool as_log = false )
```

8.29.3.30 likelihood_total()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
double Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::likelihood_total
(
    const std::vector< double > & params,
    bool as_log = false )
```

8.29.3.31 nrules()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nrules ( )
const [noexcept]
```

8.29.3.32 nrules_dyn()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nrules_dyn
( ) const [noexcept]
```

8.29.3.33 nterms()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::nterms ( )
const [noexcept]
```

8.29.3.34 operator=()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > & Model< Array_↵
Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::operator= (
    const Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
& Model_ ) [inline]
```

Definition at line 256 of file model-meat.hpp.

8.29.3.35 print()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print [inline],
[virtual]
```

Prints information about the model.

Definition at line 980 of file model-meat.hpp.

8.29.3.36 print_stats()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print_stats (
    size_t i ) const
```

8.29.3.37 sample() [1/2]

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample
(
    const Array_Type & Array_,
    const std::vector< double > & params = {} )
```

8.29.3.38 sample() [2/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Array_Type Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::sample
(
    const size_t & i,
    const std::vector< double > & params ) [inline]
```

Definition at line 1107 of file model-meat.hpp.

8.29.3.39 set_counters()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_counters
(
    Counters< Array_Type, Data_Counter_Type > * counters_ )
```

8.29.3.40 set_engine()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_engine (
    std::mt19937 * rengine_,
    bool delete_ = false ) [inline]
```

Definition at line 129 of file model-bones.hpp.

8.29.3.41 set_rules()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ )
```

8.29.3.42 set_rules_dyn()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules_dyn
(
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ )
```

8.29.3.43 set_seed()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_seed (
    size_t s ) [inline]
```

Definition at line 139 of file model-bones.hpp.

8.29.3.44 set_transform_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_transform_model (
    std::function< std::vector< double >(double *, size_t)> fun,
    std::vector< std::string > names )
```

Set the transform_model_fun object.

The transform_model function is used to transform the data

Parameters

<i>data</i>	
<i>target</i>	
<i>n_arrays</i>	
<i>arrays2support</i>	

8.29.3.45 size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size ( )
const [noexcept]
```

8.29.3.46 size_unique()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::size_unique
( ) const [noexcept]
```

8.29.3.47 store_psets()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
void Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::store_psets (
) [noexcept]
```

8.29.3.48 support_size()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::support_size ( ) const [noexcept]
```

8.29.3.49 transform_model()

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector<double> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::transform_model (
    double * data,
    size_t k )
```

8.29.4 Member Data Documentation

8.29.4.1 arrays2support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::arrays2support [protected]
```

Definition at line 65 of file model-bones.hpp.

8.29.4.2 counter_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
StatsCounter<Array_Type,Data_Counter_Type> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::counter_fun [protected]
```

Definition at line 95 of file model-bones.hpp.

8.29.4.3 counters

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::counters [protected]
```

Definition at line 91 of file model-bones.hpp.

8.29.4.4 delete_counters

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_counters = false [protected]
```

Definition at line 103 of file model-bones.hpp.

8.29.4.5 delete_rengine

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rengine = false [protected]
```

Definition at line 43 of file model-bones.hpp.

8.29.4.6 delete_rules

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rules = false [protected]
```

Definition at line 104 of file model-bones.hpp.

8.29.4.7 delete_rules_dyn

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_rules_dyn = false [protected]
```

Definition at line 105 of file model-bones.hpp.

8.29.4.8 first_calc_done

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< bool > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type
>::first_calc_done [protected]
```

Definition at line 101 of file model-bones.hpp.

8.29.4.9 keys2support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
MapVec_type< double, size_t > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_↵
Rule_Dyn_Type >::keys2support [protected]
```

Map of types of arrays to support sets.

This is of the same length as the vector stats_target.

Definition at line 72 of file model-bones.hpp.

8.29.4.10 normalizing_constants

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
Type >::normalizing_constants [protected]
```

Definition at line 100 of file model-bones.hpp.

8.29.4.11 params_last

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_↵
Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::params_last [protected]
```

Vector of the previously used parameters.

Definition at line 99 of file model-bones.hpp.

8.29.4.12 pset_arrays

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< Array_Type > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_arrays [protected]
```

Arrays of the support(s)

Definition at line 81 of file model-bones.hpp.

8.29.4.13 pset_probs

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_probs [protected]
```

Probabilities of the support(s)

Definition at line 83 of file model-bones.hpp.

8.29.4.14 pset_stats

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector<double> > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::pset_stats [protected]
```

Statistics of the support(s)

Definition at line 82 of file model-bones.hpp.

8.29.4.15 rengine

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::mt19937* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rengine = nullptr [protected]
```

Definition at line 42 of file model-bones.hpp.

8.29.4.16 rules

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type, Data_Rule_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rules [protected]
```

Definition at line 92 of file model-bones.hpp.

8.29.4.17 rules_dyn

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Rules<Array_Type, Data_Rule_Dyn_Type>* Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::rules_dyn [protected]
```

Definition at line 93 of file model-bones.hpp.

8.29.4.18 stats_support

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_support [protected]
```

Sufficient statistics of the model (support)

Definition at line 62 of file model-bones.hpp.

8.29.4.19 stats_support_n_arrays

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_support_n_arrays [protected]
```

Number of arrays included per support.

Definition at line 63 of file model-bones.hpp.

8.29.4.20 stats_target

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::vector< double > > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::stats_target [protected]
```

Target statistics of the model.

Definition at line 64 of file model-bones.hpp.

8.29.4.21 support_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support<Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::support_fun [protected]
```

Definition at line 94 of file model-bones.hpp.

8.29.4.22 transform_model_fun

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::function<std::vector<double>double *, size_t k)> Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::transform_model_fun = nullptr [protected]
```

Transformation of the model.

When specified, this function will update the model by modifying the linear equation. For example, if the user wanted to add interaction terms, rescale, or apply other operations of the sorts, the user can do such through this function.

The function should return `void` and receive the following arguments:

- `data` Pointer to the first element of the set of sufficient statistics
- `k` `size_t` indicating the number of sufficient statistics

Returns

Nothing, but it will modify the model data.

Definition at line 123 of file model-bones.hpp.

8.29.4.23 transform_model_term_names

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< std::string > Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::transform_model_term_names [protected]
```

Definition at line 125 of file model-bones.hpp.

8.29.4.24 with_pset

```
template<typename Array_Type = BArray<>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::with_pset = false [protected]
```

Definition at line 80 of file model-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/model-bones.hpp
- include/barry/model-meat.hpp

8.30 NetCounterData Class Reference

Data class used to store arbitrary size_t or double vectors.

```
#include <network.hpp>
```

Public Member Functions

- [NetCounterData](#) ()
- [NetCounterData](#) (const std::vector< size_t > indices_, const std::vector< double > numbers_)
- [~NetCounterData](#) ()

Public Attributes

- std::vector< size_t > [indices](#)
- std::vector< double > [numbers](#)

8.30.1 Detailed Description

Data class used to store arbitrary size_t or double vectors.

Definition at line 56 of file network.hpp.

8.30.2 Constructor & Destructor Documentation

8.30.2.1 NetCounterData() [1/2]

```
NetCounterData::NetCounterData ( ) [inline]
```

Definition at line 62 of file network.hpp.

8.30.2.2 NetCounterData() [2/2]

```
NetCounterData::NetCounterData (
    const std::vector< size_t > indices_,
    const std::vector< double > numbers_ ) [inline]
```

Definition at line 63 of file network.hpp.

8.30.2.3 ~NetCounterData()

```
NetCounterData::~~NetCounterData ( ) [inline]
```

Definition at line 68 of file network.hpp.

8.30.3 Member Data Documentation

8.30.3.1 indices

```
std::vector< size_t > NetCounterData::indices
```

Definition at line 59 of file network.hpp.

8.30.3.2 numbers

```
std::vector< double > NetCounterData::numbers
```

Definition at line 60 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

8.31 NetworkData Class Reference

Data class for Networks.

```
#include <network.hpp>
```

Public Member Functions

- [NetworkData](#) ()
- [NetworkData](#) (std::vector< double > vertex_attr_, bool directed_=true)
Constructor using a single attribute.
- [NetworkData](#) (std::vector< std::vector< double > > vertex_attr_, bool directed_=true)
Constructor using multiple attributes.
- [~NetworkData](#) ()

Public Attributes

- bool [directed](#) = true
- std::vector< std::vector< double > > [vertex_attr](#)

8.31.1 Detailed Description

Data class for Networks.

Details on the available counters for [NetworkData](#) can be found in the [Network counters](#) section.

This holds information about whether the graph is directed or not, and, if defined, vectors of node (vertex) attributes ([vertex_attr](#)).

Definition at line 19 of file [network.hpp](#).

8.31.2 Constructor & Destructor Documentation

8.31.2.1 NetworkData() [1/3]

```
NetworkData::NetworkData ( ) [inline]
```

Definition at line 25 of file [network.hpp](#).

8.31.2.2 NetworkData() [2/3]

```
NetworkData::NetworkData (
    std::vector< double > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using a single attribute.

Parameters

<i>vertex_↔ attr_</i>	Double vector of length equal to the number of vertices in the data.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 33 of file network.hpp.

8.31.2.3 NetworkData() [3/3]

```
NetworkData::NetworkData (
    std::vector< std::vector< double > > vertex_attr_,
    bool directed_ = true ) [inline]
```

Constructor using multiple attributes.

Parameters

<i>vertex_↔ attr_</i>	Vector of double vectors. The size equals to the number of attributes to be created. Each individual vector should be of length equal to the number of vertices.
<i>directed_</i>	When <code>true</code> the graph as treated as directed.

Definition at line 45 of file network.hpp.

8.31.2.4 ~NetworkData()

```
NetworkData::~NetworkData ( ) [inline]
```

Definition at line 51 of file network.hpp.

8.31.3 Member Data Documentation**8.31.3.1 directed**

```
bool NetworkData::directed = true
```

Definition at line 22 of file network.hpp.

8.31.3.2 vertex_attr

```
std::vector< std::vector< double > > NetworkData::vertex_attr
```

Definition at line 23 of file network.hpp.

The documentation for this class was generated from the following file:

- include/barry/counters/[network.hpp](#)

8.32 Node Class Reference

A single node for the model.

```
#include <geese-node-bones.hpp>
```

Collaboration diagram for Node:



Public Member Functions

- [~Node](#) ()
- int [get_parent](#) () const
- size_t [noffspring](#) () const [noexcept](#)
- bool [is_leaf](#) () const [noexcept](#)

Construct a new Node object

- [Node](#) ()
- [Node](#) (size_t id_, size_t ord_, bool duplication_)
- [Node](#) (size_t id_, size_t ord_, std::vector< size_t > annotations_, bool duplication_)
- [Node](#) ([Node](#) &&x) [noexcept](#)
- [Node](#) (const [Node](#) &x)

Public Attributes

- `size_t id`
Id of the node (as specified in the input)
- `size_t ord`
Order in which the node was created.
- `PhyloArray array`
Array of the node.
- `std::vector< size_t > annotations`
Observed annotations (only defined for [Geese](#))
- `bool duplication`
- `std::vector< PhyloArray > arrays = {}`
Arrays given all possible states.
- `Node * parent = nullptr`
Parent node.
- `std::vector< Node * > offspring = {}`
Offspring nodes.
- `std::vector< size_t > narray = {}`
ID of the array in the model.
- `bool visited = false`
- `std::vector< double > subtree_prob`
Induced subtree probabilities.
- `std::vector< double > probability`
The probability of observing each state.

8.32.1 Detailed Description

A single node for the model.

Each node contains all the information to compute the conditional probability of the pruning algorithm at that node.

Definition at line 11 of file `geese-node-bones.hpp`.

8.32.2 Constructor & Destructor Documentation

8.32.2.1 `Node()` [1/5]

```
Node::Node ( ) [inline]
```

Definition at line 37 of file `geese-node-bones.hpp`.

8.32.2.2 Node() [2/5]

```
Node::Node (
    size_t id_,
    size_t ord_,
    bool duplication_ ) [inline]
```

Definition at line 57 of file geese-node-bones.hpp.

8.32.2.3 Node() [3/5]

```
Node::Node (
    size_t id_,
    size_t ord_,
    std::vector< size_t > annotations_,
    bool duplication_ ) [inline]
```

Definition at line 63 of file geese-node-bones.hpp.

8.32.2.4 Node() [4/5]

```
Node::Node (
    Node && x ) [inline], [noexcept]
```

Definition at line 70 of file geese-node-bones.hpp.

8.32.2.5 Node() [5/5]

```
Node::Node (
    const Node & x ) [inline]
```

Definition at line 85 of file geese-node-bones.hpp.

8.32.2.6 ~Node()

```
Node::~Node ( ) [inline]
```

Definition at line 48 of file geese-node-bones.hpp.

8.32.3 Member Function Documentation

8.32.3.1 `get_parent()`

```
int Node::get_parent ( ) const [inline]
```

Definition at line 100 of file `geese-node-bones.hpp`.

8.32.3.2 `is_leaf()`

```
bool Node::is_leaf ( ) const [inline], [noexcept]
```

Definition at line 112 of file `geese-node-bones.hpp`.

8.32.3.3 `noffspring()`

```
size_t Node::noffspring ( ) const [inline], [noexcept]
```

Definition at line 106 of file `geese-node-bones.hpp`.

8.32.4 Member Data Documentation

8.32.4.1 `annotations`

```
std::vector< size_t > Node::annotations
```

Observed annotations (only defined for [Geese](#))

Definition at line 18 of file `geese-node-bones.hpp`.

8.32.4.2 `array`

```
PhyloArray Node::array
```

Array of the node.

Definition at line 17 of file `geese-node-bones.hpp`.

8.32.4.3 arrays

```
std::vector< PhyloArray > Node::arrays = {}
```

Arrays given all possible states.

Definition at line 21 of file geese-node-bones.hpp.

8.32.4.4 duplication

```
bool Node::duplication
```

Definition at line 19 of file geese-node-bones.hpp.

8.32.4.5 id

```
size_t Node::id
```

Id of the node (as specified in the input)

Definition at line 14 of file geese-node-bones.hpp.

8.32.4.6 narray

```
std::vector< size_t > Node::narray = {}
```

ID of the array in the model.

Definition at line 25 of file geese-node-bones.hpp.

8.32.4.7 offspring

```
std::vector< Node\* > Node::offspring = {}
```

Offspring nodes.

Definition at line 24 of file geese-node-bones.hpp.

8.32.4.8 ord

```
size_t Node::ord
```

Order in which the node was created.

Definition at line 15 of file geese-node-bones.hpp.

8.32.4.9 parent

```
Node* Node::parent = nullptr
```

Parent node.

Definition at line 23 of file geese-node-bones.hpp.

8.32.4.10 probability

```
std::vector< double > Node::probability
```

The probability of observing each state.

Definition at line 29 of file geese-node-bones.hpp.

8.32.4.11 subtree_prob

```
std::vector< double > Node::subtree_prob
```

Induced subtree probabilities.

Definition at line 28 of file geese-node-bones.hpp.

8.32.4.12 visited

```
bool Node::visited = false
```

Definition at line 26 of file geese-node-bones.hpp.

The documentation for this class was generated from the following file:

- [include/barry/models/geese/geese-node-bones.hpp](#)

8.33 NodeData Class Reference

Data definition for the `PhyloArray` class.

```
#include <geese-types.hpp>
```

Public Member Functions

- `NodeData` (const std::vector< double > &blengths_, const std::vector< bool > &states_, bool duplication_
_=true)

Public Attributes

- std::vector< double > `blengths` = {}
- std::vector< bool > `states` = {}
- bool `duplication` = true

8.33.1 Detailed Description

Data definition for the `PhyloArray` class.

This holds basic information about a given node.

Definition at line 12 of file `geese-types.hpp`.

8.33.2 Constructor & Destructor Documentation

8.33.2.1 NodeData()

```
NodeData::NodeData (
    const std::vector< double > & blengths_,
    const std::vector< bool > & states_,
    bool duplication_ = true ) [inline]
```

Definition at line 32 of file `geese-types.hpp`.

8.33.3 Member Data Documentation

8.33.3.1 blengths

```
std::vector< double > NodeData::blengths = {}
```

Branch length.

Definition at line 18 of file geese-types.hpp.

8.33.3.2 duplication

```
bool NodeData::duplication = true
```

Definition at line 28 of file geese-types.hpp.

8.33.3.3 states

```
std::vector< bool > NodeData::states = {}
```

State of the parent node.

Definition at line 23 of file geese-types.hpp.

The documentation for this class was generated from the following file:

- [include/barry/models/geese/geese-types.hpp](#)

8.34 PhyloCounterData Class Reference

```
#include <geese-types.hpp>
```

Public Member Functions

- [PhyloCounterData](#) (std::vector< size_t > [data_](#), std::vector< double > *[counters_](#)=nullptr)
- [PhyloCounterData](#) ()
- size_t [at](#) (size_t d)
- size_t [operator\(\)](#) (size_t d)
- size_t [operator\[\]](#) (size_t d)
- void [reserve](#) (size_t x)
- void [push_back](#) (size_t x)
- void [shrink_to_fit](#) ()
- size_t [size](#) ()
- std::vector< size_t >::iterator [begin](#) ()
- std::vector< size_t >::iterator [end](#) ()
- bool [empty](#) ()
- std::vector< double > * [get_counters](#) ()

8.34.1 Detailed Description

Definition at line 42 of file geese-types.hpp.

8.34.2 Constructor & Destructor Documentation

8.34.2.1 PhyloCounterData() [1/2]

```
PhyloCounterData::PhyloCounterData (
    std::vector< size_t > data_,
    std::vector< double > * counters_ = nullptr ) [inline]
```

Definition at line 48 of file geese-types.hpp.

8.34.2.2 PhyloCounterData() [2/2]

```
PhyloCounterData::PhyloCounterData ( ) [inline]
```

Definition at line 53 of file geese-types.hpp.

8.34.3 Member Function Documentation

8.34.3.1 at()

```
size_t PhyloCounterData::at (
    size_t d ) [inline]
```

Definition at line 55 of file geese-types.hpp.

8.34.3.2 begin()

```
std::vector< size_t >::iterator PhyloCounterData::begin ( ) [inline]
```

Definition at line 63 of file geese-types.hpp.

8.34.3.3 empty()

```
bool PhyloCounterData::empty ( ) [inline]
```

Definition at line 66 of file geese-types.hpp.

8.34.3.4 end()

```
std::vector< size_t >::iterator PhyloCounterData::end ( ) [inline]
```

Definition at line 64 of file geese-types.hpp.

8.34.3.5 get_counters()

```
std::vector< double >* PhyloCounterData::get_counters ( ) [inline]
```

Definition at line 67 of file geese-types.hpp.

8.34.3.6 operator()()

```
size_t PhyloCounterData::operator() (
    size_t d ) [inline]
```

Definition at line 56 of file geese-types.hpp.

8.34.3.7 operator[]()

```
size_t PhyloCounterData::operator[] (
    size_t d ) [inline]
```

Definition at line 57 of file geese-types.hpp.

8.34.3.8 push_back()

```
void PhyloCounterData::push_back (
    size_t x ) [inline]
```

Definition at line 59 of file geese-types.hpp.

8.34.3.9 reserve()

```
void PhyloCounterData::reserve (
    size_t x ) [inline]
```

Definition at line 58 of file geese-types.hpp.

8.34.3.10 shrink_to_fit()

```
void PhyloCounterData::shrink_to_fit ( ) [inline]
```

Definition at line 60 of file geese-types.hpp.

8.34.3.11 size()

```
size_t PhyloCounterData::size ( ) [inline]
```

Definition at line 61 of file geese-types.hpp.

The documentation for this class was generated from the following file:

- [include/barry/models/geese/geese-types.hpp](#)

8.35 PhyloRuleDynData Class Reference

```
#include <geese-types.hpp>
```

Public Member Functions

- [PhyloRuleDynData](#) (const std::vector< double > *counts_, size_t pos_, size_t lb_, size_t ub_, size_t duplication_)
- const double [operator\(\)](#) () const
- [~PhyloRuleDynData](#) ()

Public Attributes

- const std::vector< double > * [counts](#)
- size_t [pos](#)
- size_t [lb](#)
- size_t [ub](#)
- size_t [duplication](#)

8.35.1 Detailed Description

Definition at line 71 of file geese-types.hpp.

8.35.2 Constructor & Destructor Documentation

8.35.2.1 PhyloRuleDynData()

```
PhyloRuleDynData::PhyloRuleDynData (
    const std::vector< double > * counts_,
    size_t pos_,
    size_t lb_,
    size_t ub_,
    size_t duplication_ ) [inline]
```

Definition at line 79 of file geese-types.hpp.

8.35.2.2 ~PhyloRuleDynData()

```
PhyloRuleDynData::~PhyloRuleDynData ( ) [inline]
```

Definition at line 93 of file geese-types.hpp.

8.35.3 Member Function Documentation

8.35.3.1 operator()()

```
const double PhyloRuleDynData::operator() ( ) const [inline]
```

Definition at line 88 of file geese-types.hpp.

8.35.4 Member Data Documentation

8.35.4.1 counts

```
const std::vector< double >* PhyloRuleDynData::counts
```

Definition at line 73 of file geese-types.hpp.

8.35.4.2 duplication

```
size_t PhyloRuleDynData::duplication
```

Definition at line 77 of file geese-types.hpp.

8.35.4.3 lb

```
size_t PhyloRuleDynData::lb
```

Definition at line 75 of file geese-types.hpp.

8.35.4.4 pos

```
size_t PhyloRuleDynData::pos
```

Definition at line 74 of file geese-types.hpp.

8.35.4.5 ub

```
size_t PhyloRuleDynData::ub
```

Definition at line 76 of file geese-types.hpp.

The documentation for this class was generated from the following file:


- [include/barry/models/geese/geese-types.hpp](#)

8.36 PowerSet< Array_Type, Data_Rule_Type > Class Template Reference

Powerset of a binary array.

```
#include <powerset-bones.hpp>
```

Collaboration diagram for PowerSet< Array_Type, Data_Rule_Type >:



Public Member Functions

- void [init_support](#) ()
- void [calc](#) ()
- void [reset](#) (size_t N_, size_t M_)

Construct and destroy a PowerSet object

- [PowerSet](#) ()
- [PowerSet](#) (size_t N_, size_t M_)
- [PowerSet](#) (const Array_Type &array)
- [~PowerSet](#) ()

Wrappers for the `<tt>Rules</tt>` member.

These will add rules to the model, which are shared by the support and the actual counter function.

- void [add_rule](#) (Rule< Array_Type, Data_Rule_Type > rule)
- void [add_rule](#) (Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_, Data_Rule_Type data_)

Getter functions

- const std::vector< Array_Type > * [get_data_ptr](#) () const
- std::vector< Array_Type > [get_data](#) () const
- std::vector< Array_Type >::iterator [begin](#) ()
- std::vector< Array_Type >::iterator [end](#) ()
- std::size_t [size](#) () const [noexcept](#)
- const Array_Type & [operator\[\]](#) (const size_t &i) const

Public Attributes

- Array_Type [EmptyArray](#)
- std::vector< Array_Type > [data](#)
- Rules< Array_Type, Data_Rule_Type > * [rules](#)
- size_t [N](#)
- size_t [M](#)
- bool [rules_deleted](#) = false
- std::vector< size_t > [coordinates_free](#)
- std::vector< size_t > [coordinates_locked](#)
- size_t [n_free](#)
- size_t [n_locked](#)

8.36.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
class PowerSet< Array_Type, Data_Rule_Type >
```

Powerset of a binary array.

Template Parameters

<i>Array_Type</i>	
<i>Data_Rule_Type</i>	

Definition at line 11 of file powerset-bones.hpp.

8.36.2 Constructor & Destructor Documentation

8.36.2.1 PowerSet() [1/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet ( ) [inline]
```

Definition at line 36 of file powerset-bones.hpp.

8.36.2.2 PowerSet() [2/3]

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    size_t N_,
    size_t M_ ) [inline]
```

Definition at line 38 of file powerset-bones.hpp.

8.36.2.3 PowerSet() [3/3]

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::PowerSet (
    const Array_Type & array ) [inline]
```

Definition at line 5 of file powerset-meat.hpp.

8.36.2.4 ~PowerSet()

```
template<typename Array_Type , typename Data_Rule_Type >
PowerSet< Array_Type, Data_Rule_Type >::~~PowerSet [inline]
```

Definition at line 13 of file powerset-meat.hpp.

8.36.3 Member Function Documentation

8.36.3.1 add_rule() [1/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > rule ) [inline]
```

Definition at line 180 of file powerset-meat.hpp.

8.36.3.2 add_rule() [2/2]

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Rule_Type > count_fun_,
    Data_Rule_Type data_ ) [inline]
```

Definition at line 189 of file powerset-meat.hpp.

8.36.3.3 begin()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::begin ( ) [inline]
```

Definition at line 68 of file powerset-bones.hpp.

8.36.3.4 calc()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::calc [inline]
```

Definition at line 151 of file powerset-meat.hpp.

8.36.3.5 end()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type >::iterator PowerSet< Array_Type, Data_Rule_Type >::end ( ) [inline]
```

Definition at line 69 of file powerset-bones.hpp.

8.36.3.6 get_data()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::get_data ( ) const [inline]
```

Definition at line 67 of file powerset-bones.hpp.

8.36.3.7 get_data_ptr()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const std::vector< Array_Type >* PowerSet< Array_Type, Data_Rule_Type >::get_data_ptr ( )
const [inline]
```

Definition at line 66 of file powerset-bones.hpp.

8.36.3.8 init_support()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::init_support [inline]
```

Definition at line 19 of file powerset-meat.hpp.

8.36.3.9 operator[]()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
const Array_Type& PowerSet< Array_Type, Data_Rule_Type >::operator[] (
    const size_t & i ) const [inline]
```

Definition at line 71 of file powerset-bones.hpp.

8.36.3.10 reset()

```
template<typename Array_Type , typename Data_Rule_Type >
void PowerSet< Array_Type, Data_Rule_Type >::reset (
    size_t N_,
    size_t M_ ) [inline]
```

Definition at line 167 of file powerset-meat.hpp.

8.36.3.11 size()

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::size_t PowerSet< Array_Type, Data_Rule_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 70 of file powerset-bones.hpp.

8.36.4 Member Data Documentation

8.36.4.1 coordinates_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_free
```

Definition at line 26 of file powerset-bones.hpp.

8.36.4.2 coordinates_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< size_t > PowerSet< Array_Type, Data_Rule_Type >::coordinates_locked
```

Definition at line 27 of file powerset-bones.hpp.

8.36.4.3 data

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
std::vector< Array_Type > PowerSet< Array_Type, Data_Rule_Type >::data
```

Definition at line 19 of file powerset-bones.hpp.

8.36.4.4 EmptyArray

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Array_Type PowerSet< Array_Type, Data_Rule_Type >::EmptyArray
```

Definition at line 18 of file powerset-bones.hpp.

8.36.4.5 M

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::M
```

Definition at line 22 of file powerset-bones.hpp.

8.36.4.6 N

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::N
```

Definition at line 22 of file powerset-bones.hpp.

8.36.4.7 n_free

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_free
```

Definition at line 28 of file powerset-bones.hpp.

8.36.4.8 n_locked

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
size_t PowerSet< Array_Type, Data_Rule_Type >::n_locked
```

Definition at line 29 of file powerset-bones.hpp.

8.36.4.9 rules

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
Rules<Array_Type,Data_Rule_Type>* PowerSet< Array_Type, Data_Rule_Type >::rules
```

Definition at line 20 of file powerset-bones.hpp.

8.36.4.10 rules_deleted

```
template<typename Array_Type = BArray<>, typename Data_Rule_Type = bool>
bool PowerSet< Array_Type, Data_Rule_Type >::rules_deleted = false
```

Definition at line 23 of file powerset-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/powerset-bones.hpp
- include/barry/powerset-meat.hpp

8.37 Progress Class Reference

A simple progress bar.

```
#include <progress.hpp>
```

Public Member Functions

- [Progress](#) (int n_, int width_)
- [~Progress](#) ()
- void [next](#) ()
- void [end](#) ()

8.37.1 Detailed Description

A simple progress bar.

Definition at line 11 of file progress.hpp.

8.37.2 Constructor & Destructor Documentation

8.37.2.1 Progress()

```
Progress::Progress (
    int n_,
    int width_ ) [inline]
```

Definition at line 30 of file progress.hpp.

8.37.2.2 ~Progress()

```
Progress::~~Progress ( ) [inline]
```

Definition at line 23 of file progress.hpp.

8.37.3 Member Function Documentation**8.37.3.1 end()**

```
void Progress::end ( ) [inline]
```

Definition at line 52 of file progress.hpp.

8.37.3.2 next()

```
void Progress::next ( ) [inline]
```

Definition at line 41 of file progress.hpp.

The documentation for this class was generated from the following file:

- [include/barry/progress.hpp](#)

8.38 Rule< Array_Type, Data_Type > Class Template Reference

[Rule](#) for determining if a cell should be included in a sequence.

```
#include <rules-bones.hpp>
```

Public Member Functions

- [~Rule](#) ()
- Data_Type & [D](#) ()
Read/Write access to the data.
- bool [operator](#)() (const Array_Type &[a](#), size_t [i](#), size_t [j](#))
- std::string & [get_name](#) ()
- std::string & [get_description](#) ()
- std::string [get_name](#) () const
- std::string [get_description](#) () const

Construct a new Rule object

Construct a new [Rule](#) object

Parameters

<code>fun_</code>	<i>A function of type <code>Rule_fun_type</code>.</i>
<code>dat_</code>	<i>Data pointer to be passed to <code>fun_</code></i>
<code>delete_↔ dat_</code>	<i>When <code>true</code>, the <code>Rule</code> destructor will delete the pointer, if defined.</i>

- `Rule()`
- `Rule(Rule_fun_type< Array_Type, Data_Type > fun_, Data_Type dat_, std::string name_="", std::string desc_="")`

8.38.1 Detailed Description

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
class Rule< Array_Type, Data_Type >
```

`Rule` for determining if a cell should be included in a sequence.

`Rules` can be used together with `Support` and `PowerSet` to determine which cells should be included when enumerating all possible realizations of a binary array.

Template Parameters

<i>Array_Type</i>	An object of class <code>BArray</code> .
<i>Data_Type</i>	Any type.

Definition at line 20 of file `rules-bones.hpp`.

8.38.2 Constructor & Destructor Documentation**8.38.2.1 Rule() [1/2]**

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule ( ) [inline]
```

Definition at line 41 of file `rules-bones.hpp`.

8.38.2.2 Rule() [2/2]

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::Rule (
    Rule_fun_type< Array_Type, Data_Type > fun_,
    Data_Type dat_,
    std::string name_ = "",
    std::string desc_ = "" ) [inline]
```

Definition at line 42 of file `rules-bones.hpp`.

8.38.2.3 ~Rule()

```
template<typename Array_Type = BArray<>, typename Data_Type = bool>
Rule< Array_Type, Data_Type >::~~Rule ( ) [inline]
```

Definition at line 50 of file rules-bones.hpp.

8.38.3 Member Function Documentation

8.38.3.1 D()

```
template<typename Array_Type , typename Data_Type >
Data_Type & Rule< Array_Type, Data_Type >::D [inline]
```

Read/Write access to the data.

Definition at line 37 of file rules-meat.hpp.

8.38.3.2 get_description() [1/2]

```
template<typename Array_Type , typename Data_Type >
std::string & Rule< Array_Type, Data_Type >::get_description [inline]
```

Definition at line 54 of file rules-meat.hpp.

8.38.3.3 get_description() [2/2]

```
template<typename Array_Type , typename Data_Type >
std::string Rule< Array_Type, Data_Type >::get_description [inline]
```

Definition at line 66 of file rules-meat.hpp.

8.38.3.4 get_name() [1/2]

```
template<typename Array_Type , typename Data_Type >
std::string & Rule< Array_Type, Data_Type >::get_name [inline]
```

Definition at line 48 of file rules-meat.hpp.

8.38.3.5 `get_name()` [2/2]

```
template<typename Array_Type , typename Data_Type >
std::string Rule< Array_Type, Data_Type >::get_name [inline]
```

Definition at line 60 of file rules-meat.hpp.

8.38.3.6 `operator()()`

```
template<typename Array_Type , typename Data_Type >
bool Rule< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    size_t i,
    size_t j ) [inline]
```

Definition at line 43 of file rules-meat.hpp.

The documentation for this class was generated from the following files:

- include/barry/rules-bones.hpp
- include/barry/rules-meat.hpp

8.39 Rules< Array_Type, Data_Type > Class Template Reference

Vector of objects of class [Rule](#).

```
#include <rules-bones.hpp>
```

Public Member Functions

- [Rules](#) ()
- [Rules](#) (const [Rules](#)< Array_Type, Data_Type > &rules_)
- [Rules](#)< Array_Type, Data_Type > [operator=](#) (const [Rules](#)< Array_Type, Data_Type > &rules_)
- [~Rules](#) ()
- size_t [size](#) () const [noexcept](#)
- bool [operator\(\)](#) (const Array_Type &a, size_t i, size_t j)
 - Check whether a given cell is free or locked.*
- void [get_seq](#) (const Array_Type &a, std::vector< size_t > *free, std::vector< size_t > *locked=nullptr)
 - Computes the sequence of free and locked cells in an [BArray](#).*
- std::vector< std::string > [get_names](#) () const
- std::vector< std::string > [get_descriptions](#) () const
- std::vector< [Rule](#)< Array_Type, Data_Type > >::iterator [begin](#) ()
- std::vector< [Rule](#)< Array_Type, Data_Type > >::iterator [end](#) ()

Rule adding

Parameters

rule	
------	--

- void [add_rule](#) ([Rule](#)< Array_Type, Data_Type > rule)
- void [add_rule](#) ([Rule_fun_type](#)< Array_Type, Data_Type > rule_, Data_Type [data_](#), std::string [name_](#)="", std::string [description_](#)="")

8.39.1 Detailed Description

```
template<typename Array_Type, typename Data_Type>
class Rules< Array_Type, Data_Type >
```

Vector of objects of class [Rule](#).

Template Parameters

<i>Array_Type</i>	An object of class BArray
<i>Data_Type</i>	Any type.

Definition at line 71 of file rules-bones.hpp.

8.39.2 Constructor & Destructor Documentation**8.39.2.1 Rules() [1/2]**

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules ( ) [inline]
```

Definition at line 77 of file rules-bones.hpp.

8.39.2.2 Rules() [2/2]

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::Rules (
    const Rules< Array_Type, Data_Type > & rules\_ ) [inline]
```

Definition at line 5 of file rules-meat.hpp.

8.39.2.3 ~Rules()

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type >::~~Rules ( ) [inline]
```

Definition at line 82 of file rules-bones.hpp.

8.39.3 Member Function Documentation

8.39.3.1 add_rule() [1/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule< Array_Type, Data_Type > rule ) [inline]
```

Definition at line 72 of file rules-meat.hpp.

8.39.3.2 add_rule() [2/2]

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::add_rule (
    Rule_fun_type< Array_Type, Data_Type > rule_,
    Data_Type data_,
    std::string name_ = "",
    std::string description_ = "" ) [inline]
```

Definition at line 82 of file rules-meat.hpp.

8.39.3.3 begin()

```
template<typename Array_Type , typename Data_Type >
std::vector< Rule<Array_Type,Data_Type> >::iterator Rules< Array_Type, Data_Type >::begin (
) [inline]
```

Definition at line 134 of file rules-bones.hpp.

8.39.3.4 end()

```
template<typename Array_Type , typename Data_Type >
std::vector< Rule<Array_Type,Data_Type> >::iterator Rules< Array_Type, Data_Type >::end ( )
[inline]
```

Definition at line 137 of file rules-bones.hpp.

8.39.3.5 get_descriptions()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > Rules< Array_Type, Data_Type >::get_descriptions [inline]
```

Definition at line 180 of file rules-meat.hpp.

8.39.3.6 get_names()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > Rules< Array_Type, Data_Type >::get_names [inline]
```

Definition at line 167 of file rules-meat.hpp.

8.39.3.7 get_seq()

```
template<typename Array_Type , typename Data_Type >
void Rules< Array_Type, Data_Type >::get_seq (
    const Array_Type & a,
    std::vector< size_t > * free,
    std::vector< size_t > * locked = nullptr ) [inline]
```

Computes the sequence of free and locked cells in an [BArray](#).

Parameters

<i>a</i>	An object of class BArray .
<i>free</i>	Pointer to a vector of pairs (i, j) listing the free cells.
<i>locked</i>	(optional) Pointer to a vector of pairs (i, j) listing the locked cells.

Returns

Nothing.

Definition at line 117 of file rules-meat.hpp.

8.39.3.8 operator()()

```
template<typename Array_Type , typename Data_Type >
bool Rules< Array_Type, Data_Type >::operator() (
    const Array_Type & a,
    size_t i,
    size_t j ) [inline]
```

Check whether a given cell is free or locked.

Parameters

<i>a</i>	A BArray object
<i>i</i>	row position
<i>j</i>	col position

Returns

true If the cell is locked
false If the cell is free

Definition at line 101 of file rules-meat.hpp.

8.39.3.9 operator=()

```
template<typename Array_Type , typename Data_Type >
Rules< Array_Type, Data_Type > Rules< Array_Type, Data_Type >::operator= (
    const Rules< Array_Type, Data_Type > & rules_ )
```

Definition at line 19 of file rules-meat.hpp.

8.39.3.10 size()

```
template<typename Array_Type , typename Data_Type >
size_t Rules< Array_Type, Data_Type >::size ( ) const [inline], [noexcept]
```

Definition at line 84 of file rules-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/[rules-bones.hpp](#)
- include/barry/[rules-meat.hpp](#)

8.40 StatsCounter< Array_Type, Data_Type > Class Template Reference

Count stats for a single Array.

```
#include <statscounter-bones.hpp>
```

Public Member Functions

- [StatsCounter](#) (const Array_Type *Array_)
- Creator of a [StatsCounter](#)*
- [StatsCounter](#) (const [StatsCounter](#)< Array_Type, Data_Type > &counter)
- Copy constructor.*
- [StatsCounter](#) ()
- Can be created without setting the array.*
- [~StatsCounter](#) ()
- void [reset_array](#) (const Array_Type *Array_)
- Changes the reference array for the counting.*
- void [add_counter](#) ([Counter](#)< Array_Type, Data_Type > f_)
- void [set_counters](#) ([Counters](#)< Array_Type, Data_Type > *counters_)
- void [count_init](#) (size_t i, size_t j)
- [Counter](#) functions This function recurses through the entries of `Array` and at each step of adding a new cell it uses the functions to list the statistics.*
- void [count_current](#) (size_t i, size_t j)
- std::vector< double > [count_all](#) ()
- [Counters](#)< Array_Type, Data_Type > * [get_counters](#) ()
- std::vector< std::string > [get_names](#) () const
- std::vector< std::string > [get_descriptions](#) () const
- size_t [size](#) () const

8.40.1 Detailed Description

```
template<typename Array_Type, typename Data_Type>
class StatsCounter< Array_Type, Data_Type >
```

Count stats for a single Array.

Users can a list of functions that can be used with this. The baseline set of arguments is a pointer to a binary array and a dataset to add the counts to.

Definition at line 14 of file statscounter-bones.hpp.

8.40.2 Constructor & Destructor Documentation

8.40.2.1 StatsCounter() [1/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const Array_Type * Array_ ) [inline]
```

Creator of a [StatsCounter](#)

Parameters

<i>Array</i> ↔	A const pointer to a BArray .
—	

Definition at line 37 of file statscounter-bones.hpp.

8.40.2.2 StatsCounter() [2/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter (
    const StatsCounter< Array_Type, Data_Type > & counter )
```

Copy constructor.

Parameters

<i>counter</i>	
----------------	--

8.40.2.3 StatsCounter() [3/3]

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::StatsCounter ( ) [inline]
```

Can be created without setting the array.

Definition at line 59 of file statscounter-bones.hpp.

8.40.2.4 ~StatsCounter()

```
template<typename Array_Type , typename Data_Type >
StatsCounter< Array_Type, Data_Type >::~~StatsCounter ( )
```

8.40.3 Member Function Documentation

8.40.3.1 add_counter()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::add_counter (
    Counter< Array_Type, Data_Type > f_ )
```

8.40.3.2 count_all()

```
template<typename Array_Type , typename Data_Type >
std::vector< double > StatsCounter< Array_Type, Data_Type >::count_all [inline]
```

Definition at line 99 of file statscounter-meat.hpp.

8.40.3.3 count_current()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_current (
    size_t i,
    size_t j )
```

8.40.3.4 count_init()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::count_init (
    size_t i,
    size_t j )
```

Counter functions This function recurses through the entries of `Array` and at each step of adding a new cell it uses the functions to list the statistics.

8.40.3.5 get_counters()

```
template<typename Array_Type , typename Data_Type >
Counters<Array_Type,Data_Type>* StatsCounter< Array_Type, Data_Type >::get_counters ( )
```

8.40.3.6 get_descriptions()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_descriptions ( ) const
```

8.40.3.7 get_names()

```
template<typename Array_Type , typename Data_Type >
std::vector< std::string > StatsCounter< Array_Type, Data_Type >::get_names ( ) const
```

8.40.3.8 reset_array()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::reset_array (
    const Array_Type * Array_ )
```

Changes the reference array for the counting.

Parameters

<code>Array_↵</code>	A pointer to an array of class <code>Array_Type</code> .
<code>_</code>	

8.40.3.9 set_counters()

```
template<typename Array_Type , typename Data_Type >
void StatsCounter< Array_Type, Data_Type >::set_counters (
    Counters< Array_Type, Data_Type > * counters_ )
```

8.40.3.10 size()

```
template<typename Array_Type , typename Data_Type >
size_t StatsCounter< Array_Type, Data_Type >::size ( ) const [inline]
```

Definition at line 86 of file statscounter-bones.hpp.

The documentation for this class was generated from the following files:

- include/barry/statscounter-bones.hpp
- include/barry/statscounter-meat.hpp

8.41 Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type > Class Template Reference

Compute the support of sufficient statistics.

```
#include <support-bones.hpp>
```

Public Member Functions

- [Support](#) (const `Array_Type` &`Array_`)
Constructor passing a reference Array.
- [Support](#) (size_t `N_`, size_t `M_`)
Constructor specifying the dimensions of the array (empty).
- [Support](#) ()
- [~Support](#) ()
- void [init_support](#) (std::vector< `Array_Type` > *`array_bank`=nullptr, std::vector< double > *`stats_↵` bank=nullptr)
- void [calc](#) (std::vector< `Array_Type` > *`array_bank`=nullptr, std::vector< double > *`stats_bank`=nullptr, size_↵_t `max_num_elements_`=0u)
Computes the entire support.

- `std::vector< double > get_counts () const`
- `std::vector< double > * get_current_stats ()`
List current statistics.
- `void print () const`
- `const FreqTable< double > & get_data () const`
- `Counters< Array_Type, Data_Counter_Type > * get_counters ()`
Vector of counter functions.
- `Rules< Array_Type, Data_Rule_Type > * get_rules ()`
Vector of static rules (cells to iterate).
- `Rules< Array_Type, Data_Rule_Dyn_Type > * get_rules_dyn ()`
Vector of dynamic rules (to include/exclude a realization).

Resets the support calculator

If needed, the counters of a support object can be reused.

Parameters

Array↔ —	New array over which the support will be computed.
-------------	--

- `void reset_array ()`
- `void reset_array (const Array_Type &Array_)`

Manage counters

Parameters

f_ —	A counter to be added.
counters↔ —	A vector of counters to be added.

- `void add_counter (Counter< Array_Type, Data_Counter_Type > f_)`
- `void set_counters (Counters< Array_Type, Data_Counter_Type > *counters_)`

Manage rules

Parameters

f_ —	A rule to be added.
counters↔ —	A vector of rules to be added.

- `void add_rule (Rule< Array_Type, Data_Rule_Type > *f_)`
- `void add_rule (Rule< Array_Type, Data_Rule_Type > f_)`
- `void set_rules (Rules< Array_Type, Data_Rule_Type > *rules_)`
- `void add_rule_dyn (Rule< Array_Type, Data_Rule_Dyn_Type > *f_)`
- `void add_rule_dyn (Rule< Array_Type, Data_Rule_Dyn_Type > f_)`
- `void set_rules_dyn (Rules< Array_Type, Data_Rule_Dyn_Type > *rules_)`
- `bool eval_rules_dyn (const std::vector< double > &counts, const size_t &i, const size_t &j)`

Public Attributes

- `size_t N`
- `size_t M`
- `bool delete_counters = true`
- `bool delete_rules = true`
- `bool delete_rules_dyn = true`
- `size_t max_num_elements = BARRY_MAX_NUM_ELEMENTS`
- `std::vector< double > current_stats`
- `std::vector< size_t > coordinates_free`
- `std::vector< size_t > coordinates_locked`
- `size_t coordiantes_n_free`
- `size_t coordiantes_n_locked`
- `std::vector< double > change_stats`
- `std::vector< size_t > hashes`
- `std::vector< bool > hashes_initialized`
- `size_t n_counters`

8.41.1 Detailed Description

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename Data_Rule_Type = bool,
typename Data_Rule_Dyn_Type = bool>
class Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >
```

Compute the support of sufficient statistics.

Given an array and a set of counters, this object iterates throughout the support set of the Array while at the same time computing the support of the sufficient statitics.

The members `rule` and `rule_dyn` allow constraining the support. The first will establish which cells of the array will be used to iterate, for example, in the case of social networks, self-loops are not allowed, so the entire diagonal would be fixed to zero, reducing the size of the support.

In the case of `rule_dyn`, the function will stablsh dynamically whether the current state will be included in the counts or not. For example, this set of rules can be used to constrain the support to networks that have a prescribed degree sequence.

Definition at line 42 of file support-bones.hpp.

8.41.2 Constructor & Destructor Documentation

8.41.2.1 Support() [1/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    const Array_Type & Array_ ) [inline]
```

Constructor passing a reference Array.

Definition at line 89 of file support-bones.hpp.

8.41.2.2 Support() [2/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support (
    size_t N_,
    size_t M_ ) [inline]
```

Constructor specifying the dimensions of the array (empty).

Definition at line 98 of file support-bones.hpp.

8.41.2.3 Support() [3/3]

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::Support ( )
[inline]
```

Definition at line 105 of file support-bones.hpp.

8.41.2.4 ~Support()

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::~Support ( )
[inline]
```

Definition at line 112 of file support-bones.hpp.

8.41.3 Member Function Documentation

8.41.3.1 add_counter()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_counter
(
    Counter< Array_Type, Data_Counter_Type > f_ ) [inline]
```

Definition at line 416 of file support-meat.hpp.

8.41.3.2 add_rule() [1/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > * f_ ) [inline]
```

Definition at line 443 of file support-meat.hpp.

8.41.3.3 add_rule() [2/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule (
    Rule< Array_Type, Data_Rule_Type > f_ ) [inline]
```

Definition at line 453 of file support-meat.hpp.

8.41.3.4 add_rule_dyn() [1/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > * f_ ) [inline]
```

Definition at line 478 of file support-meat.hpp.

8.41.3.5 add_rule_dyn() [2/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::add_rule_↵
dyn (
    Rule< Array_Type, Data_Rule_Dyn_Type > f_ ) [inline]
```

Definition at line 488 of file support-meat.hpp.

8.41.3.6 calc()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::calc (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr,
    size_t max_num_elements_ = 0u ) [inline]
```

Computes the entire support.

Not to be used by the user. Sets the starting point in the array (column-major).

Parameters

<i>array_bank</i>	If specified, the counter will add to the vector each possible state of the array, as it counts.
<i>stats_bank</i>	If specified, the counter will add to the vector each possible set of statistics, as it counts.

Definition at line 382 of file support-meat.hpp.

8.41.3.7 eval_rules_dyn()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::eval_↵
rules_dyn (
    const std::vector< double > & counts,
    const size_t & i,
    const size_t & j ) [inline]
```

Definition at line 513 of file support-meat.hpp.

8.41.3.8 get_counters()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Counters< Array_Type, Data_Counter_Type > * Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_counters [inline]
```

Vector of couter functions.

Definition at line 593 of file support-meat.hpp.

8.41.3.9 get_counts()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::get_counts [inline]
```

Definition at line 557 of file support-meat.hpp.

8.41.3.10 get_current_stats()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
std::vector< double > * Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_current_stats [inline]
```

List current statistics.

Definition at line 571 of file support-meat.hpp.

8.41.3.11 get_data()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
const FreqTable< double > & Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::get_data [inline]
```

Definition at line 588 of file support-meat.hpp.

8.41.3.12 get_rules()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Rules< Array_Type, Data_Rule_Type > * Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules [inline]
```

Vector of static rules (cells to iterate).

Definition at line 598 of file support-meat.hpp.

8.41.3.13 get_rules_dyn()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
Rules< Array_Type, Data_Rule_Dyn_Type > * Support< Array_Type, Data_Counter_Type, Data_Rule_Type,
Data_Rule_Dyn_Type >::get_rules_dyn [inline]
```

Vector of dynamic rules (to include/exclude a realization).

Definition at line 603 of file support-meat.hpp.

8.41.3.14 init_support()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::init_↵
support (
    std::vector< Array_Type > * array_bank = nullptr,
    std::vector< double > * stats_bank = nullptr ) [inline]
```

Definition at line 5 of file support-meat.hpp.

8.41.3.15 print()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::print
[inline]
```

Definition at line 576 of file support-meat.hpp.

8.41.3.16 reset_array() [1/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
[inline]
```

Definition at line 111 of file support-meat.hpp.

8.41.3.17 reset_array() [2/2]

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::reset_array
(
    const Array_Type & Array_ ) [inline]
```

Definition at line 118 of file support-meat.hpp.

8.41.3.18 set_counters()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_↵
counters (
    Counters< Array_Type, Data_Counter_Type > * counters_ ) [inline]
```

Definition at line 426 of file support-meat.hpp.

8.41.3.19 set_rules()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules (
    Rules< Array_Type, Data_Rule_Type > * rules_ ) [inline]
```

Definition at line 463 of file support-meat.hpp.

8.41.3.20 set_rules_dyn()

```
template<typename Array_Type , typename Data_Counter_Type , typename Data_Rule_Type , typename
Data_Rule_Dyn_Type >
void Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::set_rules↵
_dyn (
    Rules< Array_Type, Data_Rule_Dyn_Type > * rules_ ) [inline]
```

Definition at line 498 of file support-meat.hpp.

8.41.4 Member Data Documentation

8.41.4.1 change_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn↵
_Type >::change_stats
```

Definition at line 82 of file support-bones.hpp.

8.41.4.2 coordiantes_n_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes←
_n_free
```

Definition at line 80 of file support-bones.hpp.

8.41.4.3 coordiantes_n_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::coordiantes←
_n_locked
```

Definition at line 81 of file support-bones.hpp.

8.41.4.4 coordinates_free

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn←
_Type >::coordinates_free
```

Definition at line 78 of file support-bones.hpp.

8.41.4.5 coordinates_locked

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn←
_Type >::coordinates_locked
```

Definition at line 79 of file support-bones.hpp.

8.41.4.6 current_stats

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< double > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn←
_Type >::current_stats
```

Definition at line 77 of file support-bones.hpp.

8.41.4.7 delete_counters

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
counters = true
```

Definition at line 71 of file support-bones.hpp.

8.41.4.8 delete_rules

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
rules = true
```

Definition at line 72 of file support-bones.hpp.

8.41.4.9 delete_rules_dyn

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
bool Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::delete_↵
rules_dyn = true
```

Definition at line 73 of file support-bones.hpp.

8.41.4.10 hashes

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< size_t > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::hashes
```

Definition at line 83 of file support-bones.hpp.

8.41.4.11 hashes_initialized

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
std::vector< bool > Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_↵
_Type >::hashes_initialized
```

Definition at line 84 of file support-bones.hpp.

8.41.4.12 M

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::M
```

Definition at line 70 of file support-bones.hpp.

8.41.4.13 max_num_elements

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::max_num←
_elements = BARRY_MAX_NUM_ELEMENTS
```

Definition at line 74 of file support-bones.hpp.

8.41.4.14 N

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::N
```

Definition at line 70 of file support-bones.hpp.

8.41.4.15 n_counters

```
template<typename Array_Type = BArray<bool, bool>, typename Data_Counter_Type = bool, typename
Data_Rule_Type = bool, typename Data_Rule_Dyn_Type = bool>
size_t Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >::n←
counters
```

Definition at line 85 of file support-bones.hpp.

The documentation for this class was generated from the following files:

- [include/barry/support-bones.hpp](#)
- [include/barry/support-meat.hpp](#)

8.42 vecHasher< T > Struct Template Reference

```
#include <typedefs.hpp>
```

Public Member Functions

- `std::size_t operator()` (`std::vector< T > const &dat`) `const` `noexcept`

8.42.1 Detailed Description

```
template<typename T>
struct vecHasher< T >
```

Definition at line 105 of file typedefs.hpp.

8.42.2 Member Function Documentation

8.42.2.1 operator()()

```
template<typename T >
std::size_t vecHasher< T >::operator() (
    std::vector< T > const & dat ) const    [inline], [noexcept]
```

Definition at line 108 of file typedefs.hpp.

The documentation for this struct was generated from the following file:

- `include/barry/typedefs.hpp`

Chapter 9

File Documentation

9.1 `include/barry/barray-bones.hpp` File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class `BArray< Cell_Type, Data_Type >`
Baseline class for binary arrays.

9.2 `include/barry/barray-iterator.hpp` File Reference

Classes

- class `ConstBArrayRowIter< Cell_Type, Data_Type >`

9.3 include/barry/barray-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define BARRAY_TYPE() BArray<Cell_Type, Data_Type>`
- `#define BARRAY_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BARRAY_TEMPLATE(a, b) template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`

Functions

- `template BARRAY_TEMPLATE_ARGS () inline void checkdim_(const BARRAY_TYPE() &lhs`
- `template const BARRAY_TYPE () &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+=)(const BArray< Cell_Type`
- `for (size_t i=0u;i< nrow();++i) for(size_t j=0u`
- `j< ncol();++j) this-> operator() (i, j)+`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator+=)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-=)(const BArray< Cell_Type`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator-=)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator*=)(const Cell_Type &rhs)`
- `BARRAY_TEMPLATE (BARRAY_TYPE()&, operator/=)(const Cell_Type &rhs)`

Variables

- `Data_Type & rhs`
- `return * this`

9.3.1 Macro Definition Documentation

9.3.1.1 BARRAY_TEMPLATE

```
#define BARRAY_TEMPLATE(  
    a,  
    b )  template BARRAY_TEMPLATE_ARGS() inline a BARRAY_TYPE()::b
```

Definition at line 11 of file barray-meat-operators.hpp.

9.3.1.2 BARRAY_TEMPLATE_ARGS

```
#define BARRAY_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file barray-meat-operators.hpp.

9.3.1.3 BARRAY_TYPE

```
#define BARRAY_TYPE( ) BArray<Cell_Type, Data_Type>
```

Definition at line 7 of file barray-meat-operators.hpp.

9.3.1.4 COL

```
#define COL(  
    a )  this->el_ji[a]
```

Definition at line 15 of file barray-meat-operators.hpp.

9.3.1.5 ROW

```
#define ROW(  
    a )  this->el_ij[a]
```

Definition at line 14 of file barray-meat-operators.hpp.

9.3.2 Function Documentation

9.3.2.1 BARRAY_TEMPLATE() [1/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator* ) const &
```

Definition at line 88 of file barray-meat-operators.hpp.

9.3.2.2 BARRAY_TEMPLATE() [2/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const
```

9.3.2.3 BARRAY_TEMPLATE() [3/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator+ ) const &
```

Definition at line 46 of file barray-meat-operators.hpp.

9.3.2.4 BARRAY_TEMPLATE() [4/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const
```

9.3.2.5 BARRAY_TEMPLATE() [5/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator- ) const &
```

Definition at line 75 of file barray-meat-operators.hpp.

9.3.2.6 BARRAY_TEMPLATE() [6/6]

```
BARRAY_TEMPLATE (
    BARRAY_TYPE() & ,
    operator/ ) const &
```

Definition at line 105 of file barray-meat-operators.hpp.

9.3.2.7 BARRAY_TEMPLATE_ARGS()

```
template BARRAY_TEMPLATE_ARGS ( ) const &
```

9.3.2.8 BARRAY_TYPE()

```
template const BARRAY_TYPE ( ) &
```

Definition at line 20 of file barray-meat-operators.hpp.

9.3.2.9 for()

```
for ( ) [pure virtual]
```

Definition at line 66 of file barray-meat-operators.hpp.

9.3.2.10 operator>()

```
j< ncol(); ++j) this-> operator() (
    i ,
    j )
```

9.3.3 Variable Documentation

9.3.3.1 rhs

Data_Type & rhs

Initial value:

```
{  
    checkdim_(*this, rhs)
```

Definition at line 33 of file barray-meat-operators.hpp.


9.3.3.2 this

```
return * this
```

Definition at line 43 of file barray-meat-operators.hpp.

9.4 include/barry/barray-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define ROW(a) this->el_ij[a]
- #define COL(a) this->el_ji[a]

9.4.1 Macro Definition Documentation

9.4.1.1 COL

```
#define COL(  
    a ) this->el_ji[a]
```

Definition at line 14 of file barray-meat.hpp.


9.4.1.2 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 13 of file barray-meat.hpp.

9.5 include/barry/barraycell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [BArrayCell< Cell_Type, Data_Type >](#)
- class [BArrayCell_const< Cell_Type, Data_Type >](#)


9.6 include/barry/barraycell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



9.7 include/barry/barraydense-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [BArrayDense< Cell_Type, Data_Type >](#)
Baseline class for binary arrays.

9.8 include/barry/barraydense-meat-operators.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define BDENSE_TYPE() BArrayDense<Cell_Type, Data_Type>`
- `#define BDENSE_TEMPLATE_ARGS() <typename Cell_Type, typename Data_Type>`
- `#define BDENSE_TEMPLATE(a, b) template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE():b`
- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`
- `#define POS(a, b) (b)*N + (a)`
- `#define POS_N(a, b, c) (b)*(c) + (a)`

Functions

- `template BDENSE_TEMPLATE_ARGS () inline void checkdim_(const BDENSE_TYPE() &lhs`
- `template const BDENSE_TYPE () &rhs)`
- `BDENSE_TEMPLATE (BDENSE_TYPE()&, operator+=)(const BDENSE_TYPE() &rhs)`
- `BDENSE_TEMPLATE (BDENSE_TYPE()&, operator-=(const BDENSE_TYPE() &rhs)`
- `BDENSE_TEMPLATE (BDENSE_TYPE()&, operator*=(const Cell_Type &rhs)`
- `BDENSE_TEMPLATE (BDENSE_TYPE()&, operator/=(const Cell_Type &rhs)`

9.8.1 Macro Definition Documentation

9.8.1.1 BDENSE_TEMPLATE

```

#define BDENSE_TEMPLATE(
    a,
    b ) template BDENSE_TEMPLATE_ARGS() inline a BDENSE_TYPE():b
  
```

Definition at line 11 of file barraydense-meat-operators.hpp.

9.8.1.2 BDENSE_TEMPLATE_ARGS

```
#define BDENSE_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 9 of file `barraydense-meat-operators.hpp`.

9.8.1.3 BDENSE_TYPE

```
#define BDENSE_TYPE( ) BArrayDense<Cell_Type, Data_Type>
```

Definition at line 7 of file `barraydense-meat-operators.hpp`.

9.8.1.4 COL

```
#define COL(  
    a ) this->el_ji[a]
```

Definition at line 15 of file `barraydense-meat-operators.hpp`.

9.8.1.5 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 16 of file `barraydense-meat-operators.hpp`.

9.8.1.6 POS_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 17 of file `barraydense-meat-operators.hpp`.

9.8.1.7 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 14 of file barraydense-meat-operators.hpp.

9.8.2 Function Documentation

9.8.2.1 BDENSE_TEMPLATE() [1/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator* ) const &
```

Definition at line 90 of file barraydense-meat-operators.hpp.

9.8.2.2 BDENSE_TEMPLATE() [2/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator+ ) const &
```

Definition at line 34 of file barraydense-meat-operators.hpp.

9.8.2.3 BDENSE_TEMPLATE() [3/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator- ) const &
```

Definition at line 61 of file barraydense-meat-operators.hpp.

9.8.2.4 BDENSE_TEMPLATE() [4/4]

```
BDENSE_TEMPLATE (  
    BDENSE_TYPE() & ,  
    operator/ ) const &
```

Definition at line 101 of file barraydense-meat-operators.hpp.

9.8.2.5 BDENSE_TEMPLATE_ARGS()

```
template BDENSE_TEMPLATE_ARGS ( ) const &
```


9.8.2.6 BDENSE_TYPE()

```
template const BDENSE_TYPE ( ) &
```

Definition at line 22 of file `barraydense-meat-operators.hpp`.

9.9 include/barry/barraydense-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define ROW(a) this->el_ij[a]`
- `#define COL(a) this->el_ji[a]`
- `#define POS(a, b) (b)*N + (a)`
- `#define POS_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO_CELL static_cast<Cell_Type>(0.0)`

9.9.1 Macro Definition Documentation

9.9.1.1 COL

```
#define COL(  
    a ) this->el_ji[a]
```

Definition at line 24 of file `barraydense-meat.hpp`.

9.9.1.2 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 25 of file barraydense-meat.hpp.

9.9.1.3 POS_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 26 of file barraydense-meat.hpp.

9.9.1.4 ROW

```
#define ROW(  
    a ) this->el_ij[a]
```

Definition at line 23 of file barraydense-meat.hpp.


9.9.1.5 ZERO_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 31 of file barraydense-meat.hpp.

9.10 include/barry/barraydensecell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class `BArrayDenseCell< Cell_Type, Data_Type >`

Macros

- `#define POS(a, b) (a) + (b) * N`

9.10.1 Macro Definition Documentation


9.10.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * N
```

Definition at line 6 of file `barraydensecell-bones.hpp`.

9.11 include/barry/barraydensecell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define POS(a, b) (a) + (b) * dat->N`

9.11.1 Macro Definition Documentation


9.11.1.1 POS

```
#define POS(  
    a,  
    b ) (a) + (b) * dat->N
```

Definition at line 6 of file barraydensecell-meat.hpp.

9.12 include/barry/barraydensecol-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [BArrayDenseCol< Cell_Type, Data_Type >](#)
- class [BArrayDenseCol_const< Cell_Type, Data_Type >](#)

Macros

- #define [POS\(a, b\)](#) (b)*N + (a)
- #define [POS_N\(a, b, c\)](#) (b)*(c) + (a)
- #define [ZERO_CELL](#) static_cast<Cell_Type>(0.0)

9.12.1 Macro Definition Documentation

9.12.1.1 POS

```
#define POS(  
    a,  
    b ) (b)*N + (a)
```

Definition at line 4 of file barraydensecol-bones.hpp.

9.12.1.2 POS_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 5 of file `barraydensecol-bones.hpp`.


9.12.1.3 ZERO_CELL

```
#define ZERO_CELL static_cast<Cell_Type>(0.0)
```

Definition at line 6 of file `barraydensecol-bones.hpp`.

9.13 `include/barry/barraydenserow-bones.hpp` File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class `BArrayDenseRow< Cell_Type, Data_Type >`
- class `BArrayDenseRow_const< Cell_Type, Data_Type >`

Macros

- `#define POS(a, b) (b) * N + (a)`
- `#define POS_N(a, b, c) (b)*(c) + (a)`
- `#define ZERO_CELL static_cast< Cell_Type >(0.0)`

9.13.1 Macro Definition Documentation

9.13.1.1 POS

```
#define POS(  
    a,  
    b ) (b) * N + (a)
```

Definition at line 4 of file barraydenserow-bones.hpp.

9.13.1.2 POS_N

```
#define POS_N(  
    a,  
    b,  
    c ) (b)*(c) + (a)
```

Definition at line 5 of file barraydenserow-bones.hpp.

9.13.1.3 ZERO_CELL

```
#define ZERO_CELL static_cast< Cell_Type >(0.0)
```

Definition at line 6 of file barraydenserow-bones.hpp.

9.14 include/barry/barrayrow-bones.hpp File Reference

Classes

- class [BArrayRow< Cell_Type, Data_Type >](#)
- class [BArrayRow_const< Cell_Type, Data_Type >](#)

9.15 include/barry/barrayrow-meat.hpp File Reference

Macros

- #define [BROW_TYPE\(\)](#) [BArrayRow<Cell_Type, Data_Type>](#)
- #define [BROW_TEMPLATE_ARGS\(\)](#) <typename Cell_Type, typename Data_Type>
- #define [BROW_TEMPLATE\(a, b\)](#) template [BROW_TEMPLATE_ARGS\(\)](#) inline a [BROW_TYPE\(\)](#)::b

Functions

- [BROW_TEMPLATE](#) (void, operator=)(const [BROW_TYPE](#)() &val)
- [BROW_TEMPLATE](#) (void, operator+=)(const [BROW_TYPE](#)() &val)
- [BROW_TEMPLATE](#) (void, operator-=)(const [BROW_TYPE](#)() &val)
- [BROW_TEMPLATE](#) (void, operator*=)(const [BROW_TYPE](#)() &val)
- [BROW_TEMPLATE](#) (void, operator/=(const [BROW_TYPE](#)() &val)

9.15.1 Macro Definition Documentation

9.15.1.1 BROW_TEMPLATE

```
#define BROW_TEMPLATE(  
    a,  
    b )  template BROW\_TEMPLATE\_ARGS() inline a BROW\_TYPE()::b
```

Definition at line 8 of file barrayrow-meat.hpp.

9.15.1.2 BROW_TEMPLATE_ARGS

```
#define BROW_TEMPLATE_ARGS( ) <typename Cell_Type, typename Data_Type>
```

Definition at line 6 of file barrayrow-meat.hpp.

9.15.1.3 BROW_TYPE

```
#define BROW_TYPE( ) BArrayRow<Cell_Type, Data_Type>
```

Definition at line 4 of file barrayrow-meat.hpp.

9.15.2 Function Documentation

9.15.2.1 BROW_TEMPLATE() [1/5]

```
BROW_TEMPLATE (  
    void ,  
    operator* ) const &
```

Definition at line 45 of file barrayrow-meat.hpp.

9.15.2.2 BROW_TEMPLATE() [2/5]

```
BROW_TEMPLATE (
    void ,
    operator+ ) const &
```

Definition at line 25 of file barrayrow-meat.hpp.

9.15.2.3 BROW_TEMPLATE() [3/5]

```
BROW_TEMPLATE (
    void ,
    operator- ) const &
```

Definition at line 34 of file barrayrow-meat.hpp.

9.15.2.4 BROW_TEMPLATE() [4/5]

```
BROW_TEMPLATE (
    void ,
    operator/ ) const &
```

Definition at line 55 of file barrayrow-meat.hpp.

9.15.2.5 BROW_TEMPLATE() [5/5]

```
BROW_TEMPLATE (
    void ,
    operator ) const &
```

Definition at line 11 of file barrayrow-meat.hpp.


9.16 include/barry/barrayvector-bones.hpp File Reference**Classes**

- class [BArrayVector< Cell_Type, Data_Type >](#)
Row or column of a [BArray](#)
- class [BArrayVector_const< Cell_Type, Data_Type >](#)

9.17 include/barry/barrayvector-meat.hpp File Reference

9.18 include/barry/barry-configuration.hpp File Reference

This graph shows which files directly or indirectly include this file:



Configuration MACROS

These are mostly related to performance. The definitions follow:

- `BARRY_USE_UNORDERED_MAP` If specified, then barry is compiled using `std::unordered_map`. Otherwise it will use `std::map` for the arrays.
 - `BARRY_USE_SAFE_EXP` When specified, it will multiply all likelihoods in [Model](#) by $(1/100)/(1/100)$ so that numerical overflows are avoided.
 - `BARRY_USE_ISFINITE` When specified, it will introduce a macro that checks whether the likelihood is finite or not.
 - `printf_barry` If not specified, will be defined as `printf`.
 - `BARRY_DEBUG_LEVEL`, when defined, will make things verbose.
-
- `#define BARRY_SAFE_EXP -100.0`
 - `#define BARRY_ISFINITE(a)`
 - `#define BARRY_CHECK_SUPPORT(x, maxs)`
 - `#define printf_barry printf`
 - `#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t >(std::numeric_limits< size_t >::max() / 2u)`
 - `template<typename Ta, typename Tb>`
`using Map = std::map< Ta, Tb >`

9.18.1 Macro Definition Documentation

9.18.1.1 BARRY_CHECK_SUPPORT

```
#define BARRY_CHECK_SUPPORT(  
    x,  
    maxs )
```

Definition at line 47 of file barry-configuration.hpp.

9.18.1.2 BARRY_ISFINITE

```
#define BARRY_ISFINITE(  
    a )
```

Definition at line 40 of file barry-configuration.hpp.

9.18.1.3 BARRY_MAX_NUM_ELEMENTS

```
#define BARRY_MAX_NUM_ELEMENTS static_cast< size_t >(std::numeric_limits< size_t >::max()  
/2u)
```

Definition at line 55 of file barry-configuration.hpp.

9.18.1.4 BARRY_SAFE_EXP

```
#define BARRY_SAFE_EXP -100.0
```

Definition at line 33 of file barry-configuration.hpp.

9.18.1.5 printf_barry

```
#define printf_barry printf
```

Definition at line 51 of file barry-configuration.hpp.

9.18.2 Typedef Documentation


9.18.2.1 Map

```
template<typename Ta , typename Tb >  
using Map = std::map<Ta,Tb>
```

Definition at line 27 of file barry-configuration.hpp.

9.19 include/barry/barry-debug.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define BARRY_DEBUG_LEVEL 0

9.19.1 Macro Definition Documentation


9.19.1.1 BARRY_DEBUG_LEVEL

```
#define BARRY_DEBUG_LEVEL 0
```

Definition at line 5 of file barry-debug.hpp.

9.20 include/barry/barry-macros.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define BARRY_ZERO Cell<Cell_Type>(0.0)`
- `#define BARRY_ZERO_DENSE static_cast<Cell_Type>(0.0)`
- `#define BARRY_ONE Cell<Cell_Type>(1.0)`
- `#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)`
- `#define BARRY_UNUSED(expr) do { (void)(expr); } while (0);`

9.20.1 Macro Definition Documentation

9.20.1.1 BARRY_ONE

```
#define BARRY_ONE Cell<Cell_Type>(1.0)
```

Definition at line 7 of file barry-macros.hpp.

9.20.1.2 BARRY_ONE_DENSE

```
#define BARRY_ONE_DENSE static_cast<Cell_Type>(1.0)
```

Definition at line 8 of file barry-macros.hpp.

9.20.1.3 BARRY_UNUSED

```
#define BARRY_UNUSED(  
    expr ) do { (void)(expr); } while (0);
```

Definition at line 10 of file barry-macros.hpp.

9.20.1.4 BARRY_ZERO

```
#define BARRY_ZERO Cell<Cell_Type>(0.0)
```

Definition at line 4 of file barry-macros.hpp.

9.20.1.5 BARRY_ZERO_DENSE

```
#define BARRY_ZERO_DENSE static_cast<Cell_Type>(0.0)
```

Definition at line 5 of file barry-macros.hpp.

9.21 include/barry/barry.hpp File Reference

```
#include <iostream>  
#include <cstdint>  
#include <vector>  
#include <unordered_map>  
#include <functional>  
#include <stdexcept>  
#include <cmath>  
#include <map>  
#include <algorithm>  
#include <utility>  
#include <random>  
#include <climits>  
#include <cstdio>  
#include <string>  
#include <cstdint>  
#include <memory>  
#include <regex>  
#include <iterator>  
#include "typedefs.hpp"  
#include "barry-macros.hpp"  
#include "freqtable.hpp"  
#include "cell-bones.hpp"  
#include "cell-meat.hpp"  
#include "barray-bones.hpp"  
#include "barraycell-bones.hpp"  
#include "barray-meat.hpp"  
#include "barraycell-meat.hpp"
```

```
#include "barray-meat-operators.hpp"
#include "barraydense-bones.hpp"
#include "barraydensecell-bones.hpp"
#include "barraydenserow-bones.hpp"
#include "barraydensecol-bones.hpp"
#include "barraydense-meat.hpp"
#include "barraydensecell-meat.hpp"
#include "barraydense-meat-operators.hpp"
#include "counters-bones.hpp"
#include "counters-meat.hpp"
#include "statscounter-bones.hpp"
#include "statscounter-meat.hpp"
#include "support-bones.hpp"
#include "support-meat.hpp"
#include "powerset-bones.hpp"
#include "powerset-meat.hpp"
#include "model-bones.hpp"
#include "model-meat.hpp"
#include "rules-bones.hpp"
#include "rules-meat.hpp"
#include "counters/network.hpp"
Include dependency graph for barry.hpp:
```



Namespaces

- [barry](#)
barry: Your go-to motif accountant
- [barry::counters](#)
Tree class and TreeIterator class.
- [barry::counters::network](#)

Macros

- `#define BARRY_HPP`
- `#define BARRY_VERSION_MAYOR 0`
- `#define BARRY_VERSION_MINOR 1`
- `#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR`
- `#define COUNTER_FUNCTION(a)`
- `#define COUNTER_LAMBDA(a)`
- `#define RULE_FUNCTION(a)`
- `#define RULE_LAMBDA(a)`

9.21.1 Macro Definition Documentation

9.21.1.1 BARRY_HPP

```
#define BARRY_HPP
```

Definition at line 25 of file barry.hpp.

9.21.1.2 BARRY_VERSION

```
#define BARRY_VERSION BARRY_VERSION_MAYOR ## . ## BARRY_VERSION_MINOR
```

Definition at line 29 of file barry.hpp.

9.21.1.3 BARRY_VERSION_MAYOR

```
#define BARRY_VERSION_MAYOR 0
```

Definition at line 27 of file barry.hpp.

9.21.1.4 BARRY_VERSION_MINOR

```
#define BARRY_VERSION_MINOR 1
```

Definition at line 28 of file barry.hpp.

9.21.1.5 COUNTER_FUNCTION

```
#define COUNTER_FUNCTION(  
    a )
```

Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline double (a) (const Array_Type & Array, size_t i, size_t j, Data_Type & data) \  
{
```

Definition at line 88 of file barry.hpp.

9.21.1.6 COUNTER_LAMBDA

```
#define COUNTER_LAMBDA(  
    a )
```

Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Counter_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, size_t i, size_t j, Data_Type & data)
```

Definition at line 91 of file barry.hpp.

9.21.1.7 RULE_FUNCTION

```
#define RULE_FUNCTION(  
    a )
```

Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
inline bool (a) (const Array_Type & Array, size_t i, size_t j, Data_Type & data) \  
{
```

Definition at line 95 of file barry.hpp.

9.21.1.8 RULE_LAMBDA

```
#define RULE_LAMBDA(  
    a )
```

Value:

```
template <typename Array_Type = barry::BArray<>, typename Data_Type = bool> \  
Rule_fun_type<Array_Type, Data_Type> a = \  
[] (const Array_Type & Array, size_t i, size_t j, Data_Type & data)
```

Definition at line 98 of file barry.hpp.

9.22 include/barry/cell-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [Cell< Cell_Type >](#)
Entries in [BArray](#). For now, it only has two members:

9.23 include/barry/cell-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



9.24 include/barry/col-bones.hpp File Reference

9.25 include/barry/counters-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [Counter< Array_Type, Data_Type >](#)
A counter function based on change statistics.
- class [Counters< Array_Type, Data_Type >](#)
Vector of counters.

9.26 include/barry/counters-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define COUNTER_TYPE() Counter<Array_Type,Data_Type>`
- `#define COUNTER_TEMPLATE_ARGS() <typename Array_Type, typename Data_Type>`
- `#define COUNTER_TEMPLATE(a, b) template COUNTER_TEMPLATE_ARGS() inline a COUNTER_TYPE()↔`
::b
- `#define TMP_HASHER_CALL Hasher_fun_type<Array_Type,Data_Type>`
- `#define COUNTERS_TYPE() Counters<Array_Type,Data_Type>`
- `#define COUNTERS_TEMPLATE_ARGS() <typename Array_Type, typename Data_Type>`
- `#define COUNTERS_TEMPLATE(a, b) template COUNTERS_TEMPLATE_ARGS() inline a COUNTERS_TYPE()↔`
::b

Functions

- `COUNTER_TEMPLATE (, Counter)(const Counter< Array_Type`
- `Data_Type init_fun (counter_.init_fun)`
- `Data_Type hasher_fun (counter_.hasher_fun)`
- `Data_Type &&counter_.init_fun (std::move(counter_.init_fun))`
- `Data_Type &&counter_.hasher_fun (std::move(counter_.hasher_fun))`
- `Data_Type &&counter_.data (std::move(counter_.data))`
- `Data_Type &&counter_.name (std::move(counter_.name))`
- `Data_Type &&counter_.desc (std::move(counter_.desc))`
- *Move constructor.*
- `COUNTER_TEMPLATE (COUNTER_TYPE(), operator=)(const Counter< Array_Type`
- `COUNTER_TEMPLATE (COUNTER_TYPE() &, operator=)(Counter< Array_Type`
- `COUNTER_TEMPLATE (double, count)(Array_Type &Array`
- *< Move assignment*
- `return count_fun (Array, i, j, data)`
- `COUNTER_TEMPLATE (double, init)(Array_Type &Array`
- `return init_fun (Array, i, j, data)`
- `COUNTER_TEMPLATE (std::string, get_name)() const`
- `COUNTER_TEMPLATE (std::string, get_description)() const`
- `COUNTER_TEMPLATE (void, set_hasher)(Hasher_fun_type< Array_Type`

- [COUNTER_TEMPLATE](#) ([TMP_HASHER_CALL](#), [get_hasher](#)())
- [COUNTERS_TEMPLATE](#) ([, Counters](#)())
- [COUNTERS_TEMPLATE](#) ([COUNTER_TYPE](#)() &, [operator\[\]](#))([size_t idx](#))
- [Data_Type hasher](#) ([counter_.hasher](#))
- [Data_Type &&counters_ hasher](#) ([std::move\(counters_.hasher\)](#))
- [COUNTERS_TEMPLATE](#) ([COUNTERS_TYPE](#)(), [operator=](#))([const Counters](#)< [Array_Type](#)
- [COUNTERS_TEMPLATE](#) ([COUNTERS_TYPE](#)() &, [operator=](#))([Counters](#)< [Array_Type](#)
- [COUNTERS_TEMPLATE](#) ([void, add_counter](#))([Counter](#)< [Array_Type](#)
- [COUNTERS_TEMPLATE](#) ([std::vector< std::string >, get_names](#)()) [const](#)
- [COUNTERS_TEMPLATE](#) ([std::vector< std::string >, get_descriptions](#)()) [const](#)
- [COUNTERS_TEMPLATE](#) ([std::vector< double >, gen_hash](#))([const Array_Type &array](#)
- [for](#) ([auto &c:data](#))
- [if](#) ([add_dims](#))
- [if](#) ([hasher](#))
- [if](#) ([res.size\(\)](#)==0u) [res.push_back](#)(0.0)
- [COUNTERS_TEMPLATE](#) ([void, add_hash](#))([Hasher_fun_type](#)< [Array_Type](#)

Variables

- [Data_Type & counter_](#)
- [Data_Type &&counter_ noexcept](#)
- [size_t i](#) = [locator->second](#)
- [size_t size_t j](#)
- [Data_Type fun](#)
- [Data_Type counter](#)
- [return](#)
- [Data_Type count_fun_](#)
- [Data_Type Counter_fun_type](#)< [Array_Type, Data_Type](#) > [init_fun_](#)
- [Data_Type Counter_fun_type](#)< [Array_Type, Data_Type](#) > [Hasher_fun_type](#)< [Array_Type, Data_Type](#) > [hasher_fun_](#)
- [Data_Type Counter_fun_type](#)< [Array_Type, Data_Type](#) > [Hasher_fun_type](#)< [Array_Type, Data_Type](#) > [Data_Type data_](#)
- [Data_Type Counter_fun_type](#)< [Array_Type, Data_Type](#) > [Hasher_fun_type](#)< [Array_Type, Data_Type](#) > [Data_Type std::string name_](#)
- [Data_Type Counter_fun_type](#)< [Array_Type, Data_Type](#) > [Hasher_fun_type](#)< [Array_Type, Data_Type](#) > [Data_Type std::string std::string desc_](#)
- [bool add_dims](#)
- [return res](#)
- [Data_Type fun_](#)

9.26.1 Macro Definition Documentation

9.26.1.1 COUNTER_TEMPLATE

```
#define COUNTER_TEMPLATE(
    a,
    b )  template COUNTER_TEMPLATE_ARGS() inline a COUNTER_TYPE()::b
```

Definition at line 8 of file counters-meat.hpp.

9.26.1.2 COUNTER_TEMPLATE_ARGS

```
#define COUNTER_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file counters-meat.hpp.

9.26.1.3 COUNTER_TYPE

```
#define COUNTER_TYPE( ) Counter<Array_Type,Data_Type>
```

Definition at line 4 of file counters-meat.hpp.

9.26.1.4 COUNTERS_TEMPLATE

```
#define COUNTERS_TEMPLATE(  
    a,  
    b )  template COUNTERS_TEMPLATE_ARGS() inline a COUNTERS_TYPE()::b
```

Definition at line 129 of file counters-meat.hpp.

9.26.1.5 COUNTERS_TEMPLATE_ARGS

```
#define COUNTERS_TEMPLATE_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 127 of file counters-meat.hpp.

9.26.1.6 COUNTERS_TYPE

```
#define COUNTERS_TYPE( ) Counters<Array_Type,Data_Type>
```

Definition at line 125 of file counters-meat.hpp.

9.26.1.7 TMP_HASHER_CALL

```
#define TMP_HASHER_CALL Hasher_fun_type<Array_Type,Data_Type>
```

Definition at line 115 of file counters-meat.hpp.

9.26.2 Function Documentation

9.26.2.1 count_fun()

```
return count_fun (
    Array ,
    i ,
    j ,
    data )
```

9.26.2.2 COUNTER_TEMPLATE() [1/9]

```
COUNTER_TEMPLATE (
    Counter ) const
```

9.26.2.3 COUNTER_TEMPLATE() [2/9]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() & ,
    operator )
```

9.26.2.4 COUNTER_TEMPLATE() [3/9]

```
COUNTER_TEMPLATE (
    COUNTER_TYPE() ,
    operator ) const
```

9.26.2.5 COUNTER_TEMPLATE() [4/9]

```
COUNTER_TEMPLATE (
    double ,
    count ) &
```

< Move assignment

9.26.2.6 COUNTER_TEMPLATE() [5/9]

```
COUNTER_TEMPLATE (
    double ,
    init ) &
```

9.26.2.7 COUNTER_TEMPLATE() [6/9]

```
COUNTER_TEMPLATE (
    std::string ,
    get_description ) const
```

Definition at line 107 of file counters-meat.hpp.

9.26.2.8 COUNTER_TEMPLATE() [7/9]

```
COUNTER_TEMPLATE (
    std::string ,
    get_name ) const
```

Definition at line 103 of file counters-meat.hpp.

9.26.2.9 COUNTER_TEMPLATE() [8/9]

```
COUNTER_TEMPLATE (
    TMP_HASHER_CALL ,
    get_hasher )
```

Definition at line 116 of file counters-meat.hpp.

9.26.2.10 COUNTER_TEMPLATE() [9/9]

```
COUNTER_TEMPLATE (
    void ,
    set_hasher )
```

9.26.2.11 COUNTERS_TEMPLATE() [1/9]

```
COUNTERS_TEMPLATE (
    Counters )
```

Definition at line 132 of file counters-meat.hpp.

9.26.2.12 COUNTERS_TEMPLATE() [2/9]

```
COUNTERS_TEMPLATE (
    COUNTER_TYPE() & ,
    operator [ ] )
```

Definition at line 134 of file counters-meat.hpp.

9.26.2.13 COUNTERS_TEMPLATE() [3/9]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() & ,
    operator )
```

9.26.2.14 COUNTERS_TEMPLATE() [4/9]

```
COUNTERS_TEMPLATE (
    COUNTERS_TYPE() ,
    operator ) const
```

9.26.2.15 COUNTERS_TEMPLATE() [5/9]

```
COUNTERS_TEMPLATE (
    std::vector< double > ,
    gen_hash ) const &
```

9.26.2.16 COUNTERS_TEMPLATE() [6/9]

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 213 of file counters-meat.hpp.

9.26.2.17 COUNTERS_TEMPLATE() [7/9]

```
COUNTERS_TEMPLATE (
    std::vector< std::string > ,
    get_names ) const
```

Definition at line 201 of file counters-meat.hpp.

9.26.2.18 COUNTERS_TEMPLATE() [8/9]

```
COUNTERS_TEMPLATE (
    void ,
    add_counter )
```

9.26.2.19 COUNTERS_TEMPLATE() [9/9]

```
COUNTERS_TEMPLATE (
    void ,
    add_hash )
```

9.26.2.20 data()

```
Data_Type&& counter_ data (
    std::move(counter_.data) )
```

9.26.2.21 desc()

```
Data_Type&& counter_ desc (
    std::move(counter_.desc) )
```

Move constructor.

Definition at line 32 of file counters-meat.hpp.

9.26.2.22 for()

```
for (
    auto &c:data )
```

Definition at line 233 of file counters-meat.hpp.

9.26.2.23 hasher() [1/2]

```
Data_Type hasher (  
    counter_.  hasher )
```

Definition at line 141 of file counters-meat.hpp.

9.26.2.24 hasher() [2/2]

```
Data_Type&& counters_ hasher (  
    std::move(counters_.hasher) )
```

Definition at line 144 of file counters-meat.hpp.

9.26.2.25 hasher_fun() [1/2]

```
Data_Type hasher_fun (  
    counter_.  hasher_fun )
```

Definition at line 13 of file counters-meat.hpp.

9.26.2.26 hasher_fun() [2/2]

```
Data_Type&& counter_ hasher_fun (  
    std::move(counter_.hasher_fun) )
```

9.26.2.27 if() [1/3]

```
if (  
    add_dims )
```

Definition at line 248 of file counters-meat.hpp.

9.26.2.28 if() [2/3]

```
if (  
    hasher )
```

Definition at line 255 of file counters-meat.hpp.

9.26.2.29 if() [3/3]

```
if (
    res.  size() == 0u )
```

9.26.2.30 init_fun() [1/3]

```
return init_fun (
    Array ,
    i ,
    j ,
    data )
```

9.26.2.31 init_fun() [2/3]

```
Data_Type init_fun (
    counter_.  init_fun )
```

9.26.2.32 init_fun() [3/3]

```
Data_Type&& counter_ init_fun (
    std::move(counter_.init_fun) )
```

9.26.2.33 name()

```
Data_Type&& counter_ name (
    std::move(counter_.name) )
```

9.26.3 Variable Documentation

9.26.3.1 add_dims

```
bool add_dims
```

Initial value:

```
{
    std::vector<double> res
```

Definition at line 227 of file counters-meat.hpp.

9.26.3.2 count_fun_

Data_Type count_fun_

Definition at line 179 of file counters-meat.hpp.

9.26.3.3 counter

Data_Type counter

Initial value:

```
{  
    data.push_back(counter)
```

Definition at line 170 of file counters-meat.hpp.

9.26.3.4 counter_

Data_Type & counter_

Initial value:

```
{  
    if (this != &counter_) {  
        this->count_fun = counter_.count_fun;  
        this->init_fun = counter_.init_fun;  
        this->hasher_fun = counter_.hasher_fun;  
  
        this->data = counter_.data;  
        this->name = counter_.name;  
        this->desc = counter_.desc;  
    }  
    return *this
```

Definition at line 12 of file counters-meat.hpp.

9.26.3.5 data_

Data_Rule_Dyn_Type Data_Rule_Dyn_Type data_

Initial value:

```
{  
    rules_dyn->add_rule(  
        rule_fun_,  
        data_  
    )
```

Definition at line 182 of file counters-meat.hpp.

9.26.3.6 desc_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> Data←  
_Type std::string std::string desc_
```

Initial value:

```
{  
    data.emplace_back(Counter<Array_Type,Data_Type>(  
        count_fun_,  
        init_fun_,  
        hasher_fun_,  
        data_,  
        name_,  
        desc_  
    ))  
}
```

Definition at line 184 of file counters-meat.hpp.

9.26.3.7 fun

```
Data_Type fun
```

Initial value:

```
{  
    hasher_fun = fun
```

Definition at line 111 of file counters-meat.hpp.

9.26.3.8 fun_

```
Data_Type fun_
```

Initial value:

```
{  
    hasher = fun_
```

Definition at line 270 of file counters-meat.hpp.

9.26.3.9 hasher_fun_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> hasher←  
_fun_
```

Definition at line 181 of file counters-meat.hpp.

9.26.3.10 i

```
const std::vector< double > size_t i = locator->second
```

Definition at line 83 of file counters-meat.hpp.

9.26.3.11 init_fun_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> init_fun_
```

Definition at line 180 of file counters-meat.hpp.

9.26.3.12 j

```
size_t j
```

Initial value:

```
{
    if (count_fun == nullptr)
        return 0.0
```

Definition at line 83 of file counters-meat.hpp.

9.26.3.13 name_

```
Data_Type Counter_fun_type<Array_Type,Data_Type> Hasher_fun_type<Array_Type,Data_Type> Data↔
_Type std::string name_
```

Definition at line 183 of file counters-meat.hpp.

9.26.3.14 noexcept

```
Data_Type &&counters_ noexcept
```

Initial value:

```
{
    if (this != &counter_)
    {
        this->data = std::move(counter_.data);

        this->count_fun = std::move(counter_.count_fun);
        this->init_fun = std::move(counter_.init_fun);
        this->hasher_fun = std::move(counter_.hasher_fun);

        this->name = std::move(counter_.name);
        this->desc = std::move(counter_.desc);
    }
    return *this
```

Definition at line 26 of file counters-meat.hpp.

9.26.3.15 res

```
return res
```

Definition at line 265 of file counters-meat.hpp.


9.26.3.16 return

```
return
```

Definition at line 175 of file counters-meat.hpp.

9.27 include/barry/counters/network-css.hpp File Reference

This graph shows which files directly or indirectly include this file:

**Macros**

- `#define CSS_SIZE()`
- `#define CSS_MATCH_TYPE()`
- `#define CSS_CASE_TRUTH() if ((i < n) && (j < n))`
- `#define CSS_TRUE_CELLS()`
- `#define CSS_CASE_PERCEIVED() else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))`
- `#define CSS_PERCEIVED_CELLS()`
- `#define CSS_CASE_ELSE()`
- `#define CSS_CHECK_SIZE_INIT()`
- `#define CSS_CHECK_SIZE()`
- `#define CSS_APPEND(name)`
- `#define CSS_NET_COUNTER_LAMBDA_INIT()`

Functions

- `template<typename Tnet = Network>`
`void counter_css_partially_false_recip_commi (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
Counts errors of commission.
- `template<typename Tnet = Network>`
`void counter_css_partially_false_recip_omiss (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
Counts errors of omission.
- `template<typename Tnet = Network>`
`void counter_css_completely_false_recip_comiss (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
Counts completely false reciprocity (comission)
- `template<typename Tnet = Network>`
`void counter_css_completely_false_recip_omiss (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
Counts completely false reciprocity (omission)
- `template<typename Tnet = Network>`
`void counter_css_mixed_recip (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
Counts mixed reciprocity errors.
- `template<typename Tnet = Network>`
`void counter_css_census01 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census02 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census03 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census04 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census05 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census06 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census07 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census08 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census09 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`
- `template<typename Tnet = Network>`
`void counter_css_census10 (NetCounters< Tnet > *counters, size_t netsize, const std::vector< size_t > &end_, size_t counter_type=0u)`

9.27.1 Macro Definition Documentation

9.27.1.1 CSS_APPEND

```
#define CSS_APPEND(
    name )
```

Value:

```
std::string name_ = (name);\
for (size_t i = 0u; i < end_.size(); ++i) { \
    std::string tmpname = name_ + " (" + std::to_string(i) + ")" + \
    ((counter_type == 1u) ? " (only perceiver)" : ((counter_type == 2u)? " (only alters)": ""));\
    counters->add_counter(tmp_count, tmp_init, nullptr, \
        NetCounterData({netsize, i == 0u ? netsize : end_[i-1], end_[i], counter_type, i}, {}),\
        tmpname);}
```

Definition at line 81 of file network-css.hpp.

9.27.1.2 CSS_CASE_ELSE

```
#define CSS_CASE_ELSE( )
```

Definition at line 66 of file network-css.hpp.

9.27.1.3 CSS_CASE_PERCEIVED

```
#define CSS_CASE_PERCEIVED( ) else if (((i >= s) && (i < e)) & ((j >= s) && (j < e)))
```

Definition at line 48 of file network-css.hpp.

9.27.1.4 CSS_CASE_TRUTH

```
#define CSS_CASE_TRUTH( ) if ((i < n) && (j < n))
```

Definition at line 32 of file network-css.hpp.

9.27.1.5 CSS_CHECK_SIZE

```
#define CSS_CHECK_SIZE( )
```

Value:

```
for (size_t i = 0u; i < end_.size(); ++i) {\
    if (i == 0u) continue; \
    else if (end_[i] < end_[i-1u]) \
        throw std::logic_error("Endpoints should be specified in order.");}
```

Definition at line 76 of file network-css.hpp.

9.27.1.6 CSS_CHECK_SIZE_INIT

```
#define CSS_CHECK_SIZE_INIT( )
```

Value:

```
/* The indices fall within the network */ \
if ((data.indices.at(0) > Array.ncol()) \
| (data.indices.at(2) > Array.ncol())) \
    throw std::range_error("The network does not match the prescribed size.");
```

Definition at line 70 of file network-css.hpp.

9.27.1.7 CSS_MATCH_TYPE

```
#define CSS_MATCH_TYPE( )
```

Value:

```
if (ctype != 0u) { /* all counts */ \
    if (ctype == 1u) { /* Only if perceiver */ \
        if ((i_ != ego_id) && (j_ != ego_id)) return 0.0; \
    } else if (ctype == 2u) { /* Only if not perceiver */ \
        if ((i_ == ego_id) || (j_ == ego_id)) return 0.0; \
    } \
};
```

Definition at line 22 of file network-css.hpp.

9.27.1.8 CSS_NET_COUNTER_LAMBDA_INIT

```
#define CSS_NET_COUNTER_LAMBDA_INIT( )
```

Value:

```
NETWORK_COUNTER_LAMBDA(tmp_init) {\
    CSS_CHECK_SIZE_INIT() \
    return 0.0; \
};
```

Definition at line 89 of file network-css.hpp.

9.27.1.9 CSS_PERCEIVED_CELLS

```
#define CSS_PERCEIVED_CELLS( )
```

Value:

```
size_t i_ = i - s; \
size_t j_ = j - s; \
CSS_MATCH_TYPE() \
double tji = static_cast<double>(Array(j - s, i - s, false)); \
double pji = static_cast<double>(Array(j, i, false)); \
double tij = static_cast<double>(Array(i - s, j - s, false));
```

Definition at line 55 of file network-css.hpp.

9.27.1.10 CSS_SIZE

```
#define CSS_SIZE( )
```

Value:

```
size_t n      = data.indices[0u]; \
size_t s      = data.indices[1u]; \
size_t e      = data.indices[2u]; \
size_t ctype  = data.indices[3u]; \
size_t ego_id = data.indices[4u]; \
if (ctype > 2) \
    throw std::range_error("Counter type should be 0, 1, or 2.");
```

Definition at line 8 of file network-css.hpp.

9.27.1.11 CSS_TRUE_CELLS

```
#define CSS_TRUE_CELLS( )
```

Value:

```
size_t i_ = i; \
size_t j_ = j; \
CSS_MATCH_TYPE() \
double tji = static_cast<double>(Array(j, i, false)); \
double pij = static_cast<double>(Array(i + s, j + s, false)); \
double pji = static_cast<double>(Array(j + s, i + s, false));
```

Definition at line 39 of file network-css.hpp.

9.27.2 Function Documentation

9.27.2.1 counter_css_census01()

```
template<typename Tnet = Network>
void counter_css_census01 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 324 of file network-css.hpp.

9.27.2.2 counter_css_census02()

```
template<typename Tnet = Network>
void counter_css_census02 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 389 of file network-css.hpp.

9.27.2.3 counter_css_census03()

```
template<typename Tnet = Network>
void counter_css_census03 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 429 of file network-css.hpp.

9.27.2.4 counter_css_census04()

```
template<typename Tnet = Network>
void counter_css_census04 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 469 of file network-css.hpp.

9.27.2.5 counter_css_census05()

```
template<typename Tnet = Network>
void counter_css_census05 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 509 of file network-css.hpp.

9.27.2.6 counter_css_census06()

```
template<typename Tnet = Network>
void counter_css_census06 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 549 of file network-css.hpp.

9.27.2.7 counter_css_census07()

```
template<typename Tnet = Network>
void counter_css_census07 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 589 of file network-css.hpp.

9.27.2.8 counter_css_census08()

```
template<typename Tnet = Network>
void counter_css_census08 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 629 of file network-css.hpp.

9.27.2.9 counter_css_census09()

```
template<typename Tnet = Network>
void counter_css_census09 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 669 of file network-css.hpp.

9.27.2.10 counter_css_census10()

```
template<typename Tnet = Network>
void counter_css_census10 (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Definition at line 709 of file network-css.hpp.

9.27.2.11 counter_css_completely_false_recip_comiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_comiss (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Counts completely false reciprocity (comission)

Definition at line 200 of file network-css.hpp.

9.27.2.12 counter_css_completely_false_recip_omiss()

```
template<typename Tnet = Network>
void counter_css_completely_false_recip_omiss (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Counts completely false reciprocity (omission)

Definition at line 241 of file network-css.hpp.

9.27.2.13 counter_css_mixed_recip()

```
template<typename Tnet = Network>
void counter_css_mixed_recip (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Counts mixed reciprocity errors.

Definition at line 282 of file network-css.hpp.

9.27.2.14 counter_css_partially_false_recip_commi()

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_commi (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```

Counts errors of commission.

Parameters

<i>netsize</i>	Size of the reference (true) network
<i>end_</i>	Vector indicating one past the ending index of each network. (see details)
<i>counter_type</i>	Size_t indicating the type of counter to use. Possible values are: 0: Count all, 1: Only count if perceiver is involved, and 2: Only count if perceiver is not involved.

The *end_* parameter should be of length *N* of *networks* - 1. It is assumed that the first network ends at *netsize*.

Definition at line 107 of file network-css.hpp.

9.27.2.15 counter_css_partially_false_recip_omiss()

```
template<typename Tnet = Network>
void counter_css_partially_false_recip_omiss (
    NetCounters< Tnet > * counters,
    size_t netsize,
    const std::vector< size_t > & end_,
    size_t counter_type = 0u ) [inline]
```


Counts errors of omission.

Definition at line 155 of file network-css.hpp.


9.28 include/barry/counters/network.hpp File Reference

```
#include "network-css.hpp"
```

Include dependency graph for network.hpp:



This graph shows which files directly or indirectly include this file:



Classes

- class [NetworkData](#)
Data class for Networks.
- class [NetCounterData](#)
Data class used to store arbitrary size_t or double vectors.

Macros

- #define [NET_C_DATA_IDX\(i\)](#) (data.indices[i])
- #define [NET_C_DATA_NUM\(i\)](#) (data.numbers[i])

Macros for defining counters

- #define [NETWORK_COUNTER\(a\)](#)
- #define [NETWORK_COUNTER_LAMBDA\(a\)](#)
- #define [NETWORKDENSE_COUNTER_LAMBDA\(a\)](#)

Macros for defining rules

- #define [NETWORK_RULE\(a\)](#)
- #define [NETWORK_RULE_LAMBDA\(a\)](#)

Functions

- `template<typename Tnet = Network>`
`void counter_edges (NetCounters< Tnet > *counters)`
Number of edges.
- `template<typename Tnet = Network>`
`void counter_isolates (NetCounters< Tnet > *counters)`
Number of isolated vertices.
- `template<> void counter_isolates (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_mutual (NetCounters< Tnet > *counters)`
Number of mutual ties.
- `template<typename Tnet = Network>`
`void counter_istar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_istar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ostar2 (NetCounters< Tnet > *counters)`
- `template<> void counter_ostar2 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ttriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ttriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_ctriads (NetCounters< Tnet > *counters)`
- `template<> void counter_ctriads (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_density (NetCounters< Tnet > *counters)`
- `template<typename Tnet = Network>`
`void counter_idegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_idegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_odegree15 (NetCounters< Tnet > *counters)`
- `template<> void counter_odegree15 (NetCounters< NetworkDense > *counters)`
- `template<typename Tnet = Network>`
`void counter_absdiff (NetCounters< Tnet > *counters, size_t attr_id, double alpha=1.0)`
Sum of absolute attribute difference between ego and alter.
- `template<typename Tnet = Network>`
`void counter_diff (NetCounters< Tnet > *counters, size_t attr_id, double alpha=1.0, double tail_head=true)`
Sum of attribute difference between ego and alter to pow(alpha)
- `NETWORK_COUNTER (init_single_attr)`
- `template<typename Tnet = Network>`
`void counter_nodeicov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodeocov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodecov (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_nodematch (NetCounters< Tnet > *counters, size_t attr_id)`
- `template<typename Tnet = Network>`
`void counter_idegree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given in-degree.
- `template<> void counter_idegree (NetCounters< NetworkDense > *counters, std::vector< size_t > d)`
- `template<typename Tnet = Network>`
`void counter_odegree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given out-degree.
- `template<> void counter_odegree (NetCounters< NetworkDense > *counters, std::vector< size_t > d)`

- `template<typename Tnet = Network>`
`void counter_degree (NetCounters< Tnet > *counters, std::vector< size_t > d)`
Counts number of vertices with a given out-degree.

Rules for network models

Parameters

rules	A pointer to a NetRules object (<i>Rules<Network, bool></i>).
-------	---

- `template<typename Tnet = Network>`
`void rules_zerodiag (NetRules< Tnet > *rules)`
Number of edges.

Convenient typedefs for network objects.

- `#define BARRY_ZERO_NETWORK 0.0`
- `#define BARRY_ZERO_NETWORK_DENSE 0`
- `typedef BArray< double, NetworkData > Network`
- `typedef BArrayDense< int, NetworkData > NetworkDense`
- `template<typename Tnet = Network>`
`using NetCounter = Counter< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`
`using NetCounters = Counters< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`
`using NetSupport = Support< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`
`using NetStatsCounter = StatsCounter< Tnet, NetCounterData >`
- `template<typename Tnet >`
`using NetModel = Model< Tnet, NetCounterData >`
- `template<typename Tnet = Network>`
`using NetRule = Rule< Tnet, bool >`
- `template<typename Tnet = Network>`
`using NetRules = Rules< Tnet, bool >`

9.28.1 Macro Definition Documentation

9.28.1.1 BARRY_ZERO_NETWORK

```
#define BARRY_ZERO_NETWORK 0.0
```

Definition at line 85 of file network.hpp.

9.28.1.2 BARRY_ZERO_NETWORK_DENSE

```
#define BARRY_ZERO_NETWORK_DENSE 0
```

Definition at line 86 of file network.hpp.

9.28.1.3 NET_C_DATA_IDX

```
#define NET_C_DATA_IDX(  
    i ) (data.indices[i])
```

Definition at line 74 of file network.hpp.

9.28.1.4 NET_C_DATA_NUM

```
#define NET_C_DATA_NUM(  
    i ) (data.numbers[i])
```

Definition at line 75 of file network.hpp.

9.28.1.5 NETWORK_COUNTER

```
#define NETWORK_COUNTER(  
    a )
```

Value:

```
template<typename Tnet = Network>\  
inline double (a) (const Tnet & Array, size_t i, size_t j, NetCounterData & data)
```

Function for definition of a network counter function

Definition at line 114 of file network.hpp.

9.28.1.6 NETWORK_COUNTER_LAMBDA

```
#define NETWORK_COUNTER_LAMBDA(  
    a )
```

Value:

```
Counter_fun_type<Tnet, NetCounterData> a = \  
    [] (const Tnet & Array, size_t i, size_t j, NetCounterData & data)
```

Lambda function for definition of a network counter function

Definition at line 119 of file network.hpp.

9.28.1.7 NETWORK_RULE

```
#define NETWORK_RULE(  
    a )
```

Value:

```
template<typename Tnet = Network>\  
inline bool (a) (const Tnet & Array, size_t i, size_t j, bool & data)
```

Function for definition of a network counter function

Definition at line 133 of file network.hpp.

9.28.1.8 NETWORK_RULE_LAMBDA

```
#define NETWORK_RULE_LAMBDA(  
    a )
```

Value:

```
Rule_fun_type<Tnet, bool> a = \  
[] (const Tnet & Array, size_t i, size_t j, bool & data)
```

Lambda function for definition of a network counter function

Definition at line 138 of file network.hpp.

9.28.1.9 NETWORKDENSE_COUNTER_LAMBDA

```
#define NETWORKDENSE_COUNTER_LAMBDA(  
    a )
```

Value:

```
Counter_fun_type<NetworkDense, NetCounterData> a = \  
[] (const NetworkDense & Array, size_t i, size_t j, NetCounterData & data)
```

Definition at line 123 of file network.hpp.

9.28.2 Typedef Documentation

9.28.2.1 NetCounter

```
template<typename Tnet = Network>  
using NetCounter = Counter<Tnet, NetCounterData >
```

Definition at line 89 of file network.hpp.

9.28.2.2 NetCounters

```
template<typename Tnet = Network>  
using NetCounters = Counters<Tnet, NetCounterData>
```

Definition at line 92 of file network.hpp.

9.28.2.3 NetModel

```
template<typename Tnet >  
using NetModel = Model<Tnet, NetCounterData>
```

Definition at line 101 of file network.hpp.

9.28.2.4 NetRule

```
template<typename Tnet = Network>  
using NetRule = Rule<Tnet, bool>
```

Definition at line 104 of file network.hpp.

9.28.2.5 NetRules

```
template<typename Tnet = Network>  
using NetRules = Rules<Tnet, bool>
```

Definition at line 107 of file network.hpp.

9.28.2.6 NetStatsCounter

```
template<typename Tnet = Network>  
using NetStatsCounter = StatsCounter<Tnet, NetCounterData>
```

Definition at line 98 of file network.hpp.

9.28.2.7 NetSupport

```
template<typename Tnet = Network>  
using NetSupport = Support<Tnet, NetCounterData >
```

Definition at line 95 of file network.hpp.

9.28.2.8 Network

```
typedef BArray<double, NetworkData> Network
```

Definition at line 82 of file network.hpp.

9.28.2.9 NetworkDense

```
typedef BArrayDense<int, NetworkData> NetworkDense
```

Definition at line 83 of file network.hpp.

9.28.3 Function Documentation

9.28.3.1 rules_zerodiag()


```
template<typename Tnet = Network>  
void rules_zerodiag (  
    NetRules< Tnet > * rules ) [inline]
```

Number of edges.

Definition at line 1381 of file network.hpp.

9.29 include/barry/freqtable.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [FreqTable< T >](#)
Frequency table of vectors.

9.30 include/barry/model-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >](#)
General framework for discrete exponential models. This class allows generating discrete exponential models in the form of a linear exponential model:

9.31 include/barry/model-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define MODEL_TYPE()`
- `#define MODEL_TEMPLATE_ARGS()`
- `#define MODEL_TEMPLATE(a, b) template MODEL_TEMPLATE_ARGS() inline a MODEL_TYPE():b`

Functions

- `double update_normalizing_constant (const double *params, const double *support, size_t k, size_t n)`
- `double likelihood_ (const double *stats_target, const std::vector< double > ¶ms, const double normalizing_constant, size_t n_params, bool log_=false)`
- `MODEL_TEMPLATE (void, store_psets)() noexcept`
- `MODEL_TEMPLATE (std::vector< double >, gen_key)(const Array_Type &Array_)`
- `MODEL_TEMPLATE (void, add_counter)(Counter< Array_Type`
- `MODEL_TEMPLATE (void, set_counters)(Counters< Array_Type`
- `support_fun set_counters (counters)`
- `MODEL_TEMPLATE (void, add_hasher)(Hasher_fun_type< Array_Type`
- `MODEL_TEMPLATE (void, add_rule)(Rule< Array_Type`
- `MODEL_TEMPLATE (void, set_rules)(Rules< Array_Type`
- `support_fun set_rules (rules)`
- `MODEL_TEMPLATE (void, add_rule_dyn)(Rule< Array_Type`
- `MODEL_TEMPLATE (void, set_rules_dyn)(Rules< Array_Type`
- `support_fun set_rules_dyn (rules_dyn)`
- `MODEL_TEMPLATE (size_t, add_array)(const Array_Type &Array_`
- `if (transform_model_fun) = transform_model_fun(&tmp_counts[0u], tmp_counts.size())`
- `else stats_target push_back (counter_fun.count_all())`
- `if (force_new|(locator==keys2support.end()))`
- `arrays2support push_back (locator->second)`
- `return arrays2support size () - 1u`
- `MODEL_TEMPLATE (double, likelihood)(const std`
- `MODEL_TEMPLATE (double, likelihood_total)(const std`
- `MODEL_TEMPLATE (double, get_norm_const)(const std`
- `MODEL_TEMPLATE (const std::vector< Array_Type > *, get_pset)(const size_t &i)`
- `MODEL_TEMPLATE (const std::vector< double > *, get_pset_stats)(const size_t &i)`
- `MODEL_TEMPLATE (void, print_stats)(size_t i) const`
- `MODEL_TEMPLATE (size_t, size)() const noexcept`
- `MODEL_TEMPLATE (size_t, size_unique)() const noexcept`
- `MODEL_TEMPLATE (size_t, nterms)() const noexcept`
- `MODEL_TEMPLATE (size_t, nrules)() const noexcept`
- `MODEL_TEMPLATE (size_t, nrules_dyn)() const noexcept`
- `MODEL_TEMPLATE (size_t, support_size)() const noexcept`
- `MODEL_TEMPLATE (std::vector< std::string >, colnames)() const`
- `MODEL_TEMPLATE (Array_Type, sample)(const Array_Type &Array_`
- `if (locator==keys2support.end())`
- `std::uniform_real_distribution urand (0, 1)`
- `if ((probs.size() > 0u) &&(vec_equal_approx(params, params_last[a])))`
- `temp_stats reserve (params.size())`
- `for (size_t array=0u;array< probs.size();++array)`
- `MODEL_TEMPLATE (double, conditional_prob)(const Array_Type &Array_`
- `A insert_cell (i, j, A.default_val(), true, false)`
- `tmp_counts reserve (counters->size())`
- `for (size_t ii=0u;ii< counters->size();++ii) tmp_counts.push_back(counters -> operator[](ii).count(A, i, j))`
- `return (1.0+std::exp(-vec_inner_prod< double >(¶ms[0u], &tmp_counts[0u], params.size())))`
- `MODEL_TEMPLATE (const std::mt19937 *, get_engine)() const`

- [MODEL_TEMPLATE](#) (std::vector< std::vector< double > > *, get_stats_target)()
- [MODEL_TEMPLATE](#) (std::vector< std::vector< double > > *, get_stats_support)()
- [MODEL_TEMPLATE](#) (std::vector< size_t > *, get_arrays2support)()
- [MODEL_TEMPLATE](#) (std::vector< std::vector< Array_Type > > *, get_pset_arrays)()
- [MODEL_TEMPLATE](#) (std::vector< std::vector< double > > *, get_pset_stats)()
- [MODEL_TEMPLATE](#) (std::vector< std::vector< double > > *, get_pset_probs)()
- [MODEL_TEMPLATE](#) (void, set_transform_model)(std

Variables

- [Data_Counter_Type](#) & counter
- [return](#)
- [Data_Counter_Type](#) count_fun_
- [Data_Counter_Type](#) Counter_fun_type< Array_Type, [Data_Counter_Type](#) > init_fun_
- [Data_Counter_Type](#) Counter_fun_type< Array_Type, [Data_Counter_Type](#) > [Data_Counter_Type](#) data_
- [Data_Counter_Type](#) * counters_
- [Data_Counter_Type](#) fun_
- [Data_Rule_Type](#) & rules
- [Data_Rule_Type](#) * rules_
- [this](#) delete_rules = false
- [Data_Rule_Dyn_Type](#) rule_fun_
- [this](#) rules_dyn = rules_
- [this](#) delete_rules_dyn = false
- bool [force_new](#)
- std::vector< double > [key](#) = counters->gen_hash(Array_)
- [MapVec_type](#)< double, size_t >::const_iterator [locator](#) = keys2support.find([key](#))
- [stats_support_n_arrays](#) [[locator](#)->second]
- const std::vector< double > & [params](#)
- size_t [i](#) = [locator](#)->second
- size_t [a](#) = arrays2support[i]
- double [r](#) = urand(*rengine)
- double [cumprob](#) = 0.0
- size_t [k](#) = [params.size](#)()
- size_t [j](#) = 0u
- std::vector< double > & [probs](#) = pset_probs[a]
- [else](#)
- std::vector< double > [temp_stats](#)
- const std::vector< double > & [stats](#) = pset_stats[a]
- int [i_matches](#) = -1
- [return this](#) pset_arrays [a][j]
- std::vector< double > [tmp_counts](#)
- template [Data_Counter_Type](#)
- template [Data_Rule_Type](#)

9.31.1 Macro Definition Documentation

9.31.1.1 MODEL_TEMPLATE

```
#define MODEL_TEMPLATE(
    a,
    b )  template MODEL_TEMPLATE_ARGS() inline a MODEL_TYPE()::b
```

Definition at line 131 of file model-meat.hpp.

9.31.1.2 MODEL_TEMPLATE_ARGS

```
template MODEL_TEMPLATE_ARGS( )
```

Value:

```
<typename Array_Type, typename Data_Counter_Type,\
typename Data_Rule_Type, typename Data_Rule_Dyn_Type>
```

Definition at line 128 of file model-meat.hpp.

9.31.1.3 MODEL_TYPE

```
template Data_Rule_Dyn_Type * MODEL_TYPE( )
```

Value:

```
Model<Array_Type, Data_Counter_Type, Data_Rule_Type,\
Data_Rule_Dyn_Type>
```

Definition at line 125 of file model-meat.hpp.

9.31.2 Function Documentation

9.31.2.1 for() [1/2]

```
for ( )
```

Definition at line 1317 of file model-meat.hpp.

9.31.2.2 for() [2/2]

```
for (
    size_t ii = 0u; ii < counters->size(); ++ii ) -> operator[](ii).count(A, i, j))
```

9.31.2.3 if() [1/4]

```
if (
    (probs.size() > 0u) &&(vec_equal_approx(params, params_last[a])) )
```

Definition at line 1299 of file model-meat.hpp.

9.31.2.4 if() [2/4]

```
if (
    force_new| locator==keys2support.end() )
```

When computing with the powerset, we need to grow the corresponding vectors on the fly

Definition at line 457 of file model-meat.hpp.

9.31.2.5 if() [3/4]

```
if (
    locator == keys2support.end() )
```

When computing with the powerset, we need to grow the corresponding vectors on the fly

Definition at line 1201 of file model-meat.hpp.

9.31.2.6 if() [4/4]

```
if (
    transform_model_fun ) = transform_model_fun(&tmp_counts[0u], tmp_counts.size())
```

Definition at line 442 of file model-meat.hpp.

9.31.2.7 insert_cell()

```
A insert_cell (
    i ,
    j ,
    A. default_val(),
    true ,
    false )
```

9.31.2.8 likelihood_()

```
double likelihood_ (
    const double * stats_target,
    const std::vector< double > & params,
    const double normalizing_constant,
    size_t n_params,
    bool log_ = false ) [inline]
```

Definition at line 63 of file model-meat.hpp.

9.31.2.9 MODEL_TEMPLATE() [1/33]

```
MODEL_TEMPLATE (
    Array_Type ,
    sample ) const &
```

9.31.2.10 MODEL_TEMPLATE() [2/33]

```
MODEL_TEMPLATE (
    const std::mt19937 * ,
    get_rengine ) const
```

Definition at line 1387 of file model-meat.hpp.

9.31.2.11 MODEL_TEMPLATE() [3/33]

```
MODEL_TEMPLATE (
    const std::vector< Array_Type > * ,
    get_pset ) const &
```

Definition at line 927 of file model-meat.hpp.

9.31.2.12 MODEL_TEMPLATE() [4/33]

```
MODEL_TEMPLATE (
    const std::vector< double > * ,
    get_pset_stats ) const &
```

Definition at line 939 of file model-meat.hpp.

9.31.2.13 MODEL_TEMPLATE() [5/33]

```
MODEL_TEMPLATE (
    double ,
    conditional_prob ) const &
```

9.31.2.14 MODEL_TEMPLATE() [6/33]

```
MODEL_TEMPLATE (
    double ,
    get_norm_const ) const
```

Definition at line 891 of file model-meat.hpp.

9.31.2.15 MODEL_TEMPLATE() [7/33]

```
MODEL_TEMPLATE (
    double ,
    likelihood ) const
```

Definition at line 569 of file model-meat.hpp.

9.31.2.16 MODEL_TEMPLATE() [8/33]

```
MODEL_TEMPLATE (
    double ,
    likelihood_total ) const
```

Definition at line 825 of file model-meat.hpp.

9.31.2.17 MODEL_TEMPLATE() [9/33]

```
MODEL_TEMPLATE (
    size_t ,
    add_array ) const &
```

9.31.2.18 MODEL_TEMPLATE() [10/33]

```
MODEL_TEMPLATE (
    size_t ,
    nrules ) const [noexcept]
```

Definition at line 1065 of file model-meat.hpp.

9.31.2.19 MODEL_TEMPLATE() [11/33]

```
MODEL_TEMPLATE (
    size_t ,
    nrules_dyn ) const [noexcept]
```

Definition at line 1072 of file model-meat.hpp.

9.31.2.20 MODEL_TEMPLATE() [12/33]

```
MODEL_TEMPLATE (
    size_t ,
    nterms ) const [noexcept]
```

Definition at line 1055 of file model-meat.hpp.

9.31.2.21 MODEL_TEMPLATE() [13/33]

```
MODEL_TEMPLATE (
    size_t ,
    size ) const [noexcept]
```

Definition at line 1040 of file model-meat.hpp.

9.31.2.22 MODEL_TEMPLATE() [14/33]

```
MODEL_TEMPLATE (
    size_t ,
    size_unique ) const [noexcept]
```

Definition at line 1047 of file model-meat.hpp.

9.31.2.23 MODEL_TEMPLATE() [15/33]

```
MODEL_TEMPLATE (
    size_t ,
    support_size ) const [noexcept]
```

Definition at line 1079 of file model-meat.hpp.

9.31.2.24 MODEL_TEMPLATE() [16/33]

```
MODEL_TEMPLATE (
    std::vector< double > ,
    gen_key ) const &
```

Definition at line 312 of file model-meat.hpp.

9.31.2.25 MODEL_TEMPLATE() [17/33]

```
MODEL_TEMPLATE (
    std::vector< size_t > * ,
    get_arrays2support )
```

Definition at line 1422 of file model-meat.hpp.

9.31.2.26 MODEL_TEMPLATE() [18/33]

```
MODEL_TEMPLATE (
    std::vector< std::string > ,
    colnames ) const
```

Definition at line 1091 of file model-meat.hpp.

9.31.2.27 MODEL_TEMPLATE() [19/33]

```
MODEL_TEMPLATE (
    std::vector< std::vector< Array_Type > > * ,
    get_pset_arrays )
```

Definition at line 1427 of file model-meat.hpp.

9.31.2.28 MODEL_TEMPLATE() [20/33]

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_pset_probs )
```

Definition at line 1435 of file model-meat.hpp.

9.31.2.29 MODEL_TEMPLATE() [21/33]

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_pset_stats )
```

Definition at line 1431 of file model-meat.hpp.

9.31.2.30 MODEL_TEMPLATE() [22/33]

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_stats_support )
```

Definition at line 1417 of file model-meat.hpp.

9.31.2.31 MODEL_TEMPLATE() [23/33]

```
MODEL_TEMPLATE (
    std::vector< std::vector< double > > * ,
    get_stats_target )
```

Definition at line 1412 of file model-meat.hpp.

9.31.2.32 MODEL_TEMPLATE() [24/33]

```
MODEL_TEMPLATE (
    void ,
    add_counter )
```

9.31.2.33 MODEL_TEMPLATE() [25/33]

```
MODEL_TEMPLATE (
    void ,
    add_hasher )
```

9.31.2.34 MODEL_TEMPLATE() [26/33]

```
MODEL_TEMPLATE (
    void ,
    add_rule )
```

9.31.2.35 MODEL_TEMPLATE() [27/33]

```
MODEL_TEMPLATE (
    void ,
    add_rule_dyn )
```

9.31.2.36 MODEL_TEMPLATE() [28/33]

```
MODEL_TEMPLATE (
    void ,
    print_stats ) const
```

Definition at line 950 of file model-meat.hpp.

9.31.2.37 MODEL_TEMPLATE() [29/33]

```
MODEL_TEMPLATE (
    void ,
    set_counters )
```

9.31.2.38 MODEL_TEMPLATE() [30/33]

```
MODEL_TEMPLATE (
    void ,
    set_rules )
```

9.31.2.39 MODEL_TEMPLATE() [31/33]

```
MODEL_TEMPLATE (
    void ,
    set_rules_dyn )
```

9.31.2.40 MODEL_TEMPLATE() [32/33]

```
MODEL_TEMPLATE (
    void ,
    set_transform_model )
```

Definition at line 1439 of file model-meat.hpp.

9.31.2.41 MODEL_TEMPLATE() [33/33]

```
MODEL_TEMPLATE (
    void ,
    store_psets ) [noexcept]
```

Definition at line 305 of file model-meat.hpp.

9.31.2.42 push_back() [1/2]

```
else stats_target push_back (
    counter_fun. count_all() )
```

9.31.2.43 push_back() [2/2]

```
arrays2support push_back (
    locator-> second )
```

9.31.2.44 reserve() [1/2]

```
tmp_counts reserve (
    counters-> size() )
```

9.31.2.45 reserve() [2/2]

```
temp_stats reserve (
    params. size() )
```

9.31.2.46 return()

```
return (
    1.0+ std::exp-vec_inner_prod< double > (&params[0u], &tmp_counts[0u], params.↵
size()) )
```

9.31.2.47 set_counters()

```
counter_fun set_counters (
    counters )
```

9.31.2.48 set_rules()

```
support_fun set_rules (
    rules )
```

9.31.2.49 set_rules_dyn()

```
support_fun set_rules_dyn (
    rules_dyn )
```

9.31.2.50 size()

```
return arrays2support size ( )
```

9.31.2.51 `update_normalizing_constant()`

```
double update_normalizing_constant (
    const double * params,
    const double * support,
    size_t k,
    size_t n ) [inline]
```

Definition at line 9 of file model-meat.hpp.

9.31.2.52 `urand()`

```
std::uniform_real_distribution urand (
    0 ,
    1 )
```

9.31.3 Variable Documentation

9.31.3.1 `a`

```
size_t a = arrays2support[i]
```

Definition at line 1287 of file model-meat.hpp.

9.31.3.2 `count_fun_`

```
Data_Counter_Type count_fun_
```

Definition at line 327 of file model-meat.hpp.

9.31.3.3 `counter`

```
Data_Counter_Type& counter
```

Initial value:

```
{
    counters->add_counter(counter, Data_Counter_Type())
```

Definition at line 319 of file model-meat.hpp.

9.31.3.4 counters_

`Data_Counter_Type* counters_`

Initial value:

```
{  
    if (delete_counters) {  
        delete counters;  
        delete_counters = false;  
    }  
  
    this->counters = counters_  
}
```

Definition at line 343 of file model-meat.hpp.

9.31.3.5 cumprob

`double cumprob = 0.0`

Definition at line 1292 of file model-meat.hpp.

9.31.3.6 data_

`Data_Rule_Dyn_Type Data_Rule_Dyn_Type data_`

Initial value:

```
{  
  
    counters->add_counter(  
        count_fun_,  
        init_fun_,  
        data_  
    )  
}
```

Definition at line 329 of file model-meat.hpp.

9.31.3.7 Data_Counter_Type

`template Data_Counter_Type`

Definition at line 1407 of file model-meat.hpp.

9.31.3.8 Data_Rule_Type

`template Data_Rule_Type`

Definition at line 1407 of file model-meat.hpp.

9.31.3.9 delete_rules

```
this delete_rules = false
```

Definition at line 386 of file model-meat.hpp.

9.31.3.10 delete_rules_dyn

```
this delete_rules_dyn = false
```

Definition at line 425 of file model-meat.hpp.

9.31.3.11 else

```
else
```

Initial value:

```
{  
    probs.resize(pset_arrays[a].size())
```

Definition at line 1309 of file model-meat.hpp.

9.31.3.12 force_new

```
bool force_new
```

Initial value:

```
{  
    counter_fun.reset_array(&Array_)
```

Definition at line 436 of file model-meat.hpp.

9.31.3.13 fun_

```
Data_Counter_Type fun_
```

Initial value:

```
{  
    counters->add_hash(fun_)
```

Definition at line 360 of file model-meat.hpp.

9.31.3.14 i

```
const std::vector< double > size_t i = locator->second
```

Definition at line 1195 of file model-meat.hpp.

9.31.3.15 i_matches

```
int i_matches = -1
```

Definition at line 1316 of file model-meat.hpp.

9.31.3.16 init_fun_

```
Data_Counter_Type Counter_fun_type<Array_Type,Data_Counter_Type> init_fun_
```

Definition at line 328 of file model-meat.hpp.

9.31.3.17 j

```
const std::vector< double > size_t size_t j = 0u
```

Definition at line 1297 of file model-meat.hpp.

9.31.3.18 k

```
size_t k = params.size()
```

Definition at line 1294 of file model-meat.hpp.

9.31.3.19 key

```
std::vector< double > key = counters->gen_hash(Array_)
```

Definition at line 455 of file model-meat.hpp.

9.31.3.20 locator

```
MapVec_type< double, size_t >::const_iterator locator = keys2support.find(key)
```

Definition at line 456 of file model-meat.hpp.

9.31.3.21 params

```
const std::vector< double > & params
```

Initial value:

```
{  
    if (!this->with_pset)  
        throw std::logic_error("Sampling is only available when store_pset() is active.")
```

Definition at line 1188 of file model-meat.hpp.

9.31.3.22 probs

```
std::vector< double >& probs = pset_probs[a]
```

Definition at line 1298 of file model-meat.hpp.

9.31.3.23 pset_arrays

```
return this pset_arrays[a][j]
```

Definition at line 1350 of file model-meat.hpp.

9.31.3.24 r

```
double r = urand(*rengine)
```

Definition at line 1291 of file model-meat.hpp.

9.31.3.25 return

```
return
```

Definition at line 323 of file model-meat.hpp.

9.31.3.26 rule_fun_

Data_Rule_Dyn_Type rule_fun_

Definition at line 404 of file model-meat.hpp.

9.31.3.27 rules

```
this rules
```

Initial value:

```
{  
    rules->add_rule(rules, Data_Rule_Type())
```

Definition at line 370 of file model-meat.hpp.

9.31.3.28 rules_

Data_Rule_Dyn_Type * rules_

Initial value:

```
{  
    if (delete_rules)  
        delete rules
```

Definition at line 379 of file model-meat.hpp.

9.31.3.29 rules_dyn

```
this rules_dyn = rules_
```

Definition at line 424 of file model-meat.hpp.

9.31.3.30 stats

```
const std::vector< double >& stats = pset_stats[a]
```

Definition at line 1314 of file model-meat.hpp.

9.31.3.31 stats_support_n_arrays

```
stats_support_n_arrays[locator->second]
```

Definition at line 560 of file model-meat.hpp.

9.31.3.32 temp_stats

```
std::vector< double > temp_stats
```

Definition at line 1312 of file model-meat.hpp.

9.31.3.33 tmp_counts


```
std::vector< double > tmp_counts
```

Definition at line 1369 of file model-meat.hpp.

9.32 include/barry/models/defm.hpp File Reference

```
#include <iterator>
#include <regex>
#include "defm/defm-types.hpp"
#include "defm/counters.hpp"
#include "defm/defm-bones.hpp"
#include "defm/defm-meat.hpp"
```

Include dependency graph for defm.hpp:




Namespaces

- [defm](#)


9.33 include/barry/models/defm/counters.hpp File Reference

```
#include "formula.hpp"
```

Include dependency graph for counters.hpp:



This graph shows which files directly or indirectly include this file:



Macros

- #define [MAKE_DEFM_HASHER\(hasher, a, cov\)](#)
- #define [DEFM_RULEDYN_LAMBDA\(a\)](#)
- #define [UNI_SUB\(a\)](#)

Macros for defining counters

- #define [DEFM_COUNTER\(a\)](#) inline double (a) (const [DEFMArray](#) & Array, size_t i, size_t j, [DEFMCounterData](#) & data)
- #define [DEFM_COUNTER_LAMBDA\(a\)](#)

Macros for defining rules

- #define [DEFM_RULE\(a\)](#) inline bool (a) (const [DEFMArray](#) & Array, size_t i, size_t j, bool & data)
- #define [DEFM_RULE_LAMBDA\(a\)](#)

Functions

- void [counter_ones](#) ([DEFMCounters](#) *counters, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr)

Prevalence of ones.

- void [counter_logit_intercept](#) ([DEFMCounters](#) *counters, size_t n_y, std::vector< size_t > which={}, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)

- void [counter_transition](#) ([DEFMCounters](#) *counters, std::vector< size_t > coords, std::vector< bool > signs, size_t m_order, size_t n_y, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)

Prevalence of ones.

- void [counter_transition_formula](#) ([DEFMCounters](#) *counters, std::string formula, size_t m_order, size_t n_y, int covar_index=-1, std::string vname="", const std::vector< std::string > *x_names=nullptr, const std::vector< std::string > *y_names=nullptr)

Prevalence of ones.

- void [counter_fixed_effect](#) ([DEFMCounters](#) *counters, int covar_index, double k, std::string vname="", const std::vector< std::string > *x_names=nullptr)

Prevalence of ones.

Returns true if the cell is free

Parameters

rules	A pointer to a DEFMRules object (Rules < DEFMArray , bool>).
-------	---

- void [rules_markov_fixed](#) ([DEFMRules](#) *rules, size_t markov_order)

Number of edges.

- void [rules_dont_become_zero](#) ([DEFMSupport](#) *support, std::vector< size_t > ids)

Blocks switching a one to zero.

9.33.1 Macro Definition Documentation

9.33.1.1 DEFM_COUNTER

```
#define DEFM_COUNTER(  
    a ) inline double (a) (const DEFMArray & Array, size_t i, size_t j, DEFMCounterData  
& data)
```

Function for definition of a network counter function

Definition at line 39 of file counters.hpp.

9.33.1.2 DEFM_COUNTER_LAMBDA

```
#define DEFM_COUNTER_LAMBDA(  
    a )
```

Value:

```
barry::Counter_fun_type<DEFMArray, DEFMCOUNTERData> a = \  
    [](const DEFMArray & Array, size_t i, size_t j, DEFMCOUNTERData & data) -> double
```

Lambda function for definition of a network counter function

Definition at line 43 of file counters.hpp.

9.33.1.3 DEFM_RULE

```
#define DEFM_RULE(  
    a ) inline bool (a) (const DEFMArray & Array, size_t i, size_t j, bool & data)
```

Function for definition of a network counter function

Definition at line 53 of file counters.hpp.

9.33.1.4 DEFM_RULE_LAMBDA

```
#define DEFM_RULE_LAMBDA(  
    a )
```

Value:

```
barry::Rule_fun_type<DEFMArray, DEFMRULEData> a = \  
    [](const DEFMArray & Array, size_t i, size_t j, DEFMRULEData & data) -> bool
```

Lambda function for definition of a network counter function

Definition at line 57 of file counters.hpp.

9.33.1.5 DEFM_RULEDYN_LAMBDA

```
#define DEFM_RULEDYN_LAMBDA(  
    a )
```

Value:

```
barry::Rule_fun_type<DEFMArray, DEFMRULEDynData> a = \  
    [](const DEFMArray & Array, size_t i, size_t j, DEFMRULEDynData & data) -> bool
```

Lambda function for definition of a network counter function

Definition at line 63 of file counters.hpp.

9.33.1.6 UNI_SUB


```
#define UNI_SUB(  
    a )
```

Value:

```
(\
  ((a) == 0) ? u8"\u2080" : (\
  ((a) == 1) ? u8"\u2081" : (\
  ((a) == 2) ? u8"\u2082" : (\
  ((a) == 3) ? u8"\u2083" : (\
  ((a) == 4) ? u8"\u2084" : (\
  ((a) == 5) ? u8"\u2085" : (\
  ((a) == 6) ? u8"\u2086" : (\
  ((a) == 7) ? u8"\u2087" : (\
  ((a) == 8) ? u8"\u2088" : \
  u8"\u2089" ) ) ) ) ) ) \
)
```

9.34 include/barry/models/geese/counters.hpp File Reference

This graph shows which files directly or indirectly include this file:



Functions

- void [rule_dyn_limit_changes](#) ([PhyloSupport](#) *support, size_t pos, size_t lb, size_t ub, size_t duplication=[Geese::etype_default](#))

Overall functional gains.

- #define [MAKE_DUPL_VARS](#)()
- #define [IS_EITHER](#)() (DATA_AT == [Geese::etype_either](#))
- #define [IS_DUPLICATION](#)() ((DATA_AT == [Geese::etype_duplication](#)) & (DPL))
- #define [IS_SPECIATION](#)() ((DATA_AT == [Geese::etype_speciation](#)) & (!DPL))
- #define [IF_MATCHES](#)()
- #define [IF_NOTMATCHES](#)()
- #define [PHYLO_COUNTER_LAMBDA](#)(a)

Extension of a simple counter.

- #define [PHYLO_RULE_DYN_LAMBDA](#)(a)
- #define [PHYLO_CHECK_MISSING](#)()

- std::string `get_last_name` (size_t d)
- void `counter_overall_gains` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Overall functional gains.
- void `counter_gains` (PhyloCounters *counters, std::vector< size_t > nfun, size_t duplication=Geese::etype_default)

Functional gains for a specific function (nfun).
- void `counter_gains_k_offspring` (PhyloCounters *counters, std::vector< size_t > nfun, size_t k=1u, size_t duplication=Geese::etype_default)

k genes gain function nfun
- void `counter_genes_changing` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)
- void `counter_preserve_pseudogene` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Keeps track of how many pairs of genes preserve pseudostate.
- void `counter_prop_genes_changing` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Keeps track of how many genes are changing (either 0, 1, or 2 if dealing with regular trees.)
- void `counter_overall_loss` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Overall functional loss.
- void `counter_maxfuns` (PhyloCounters *counters, size_t lb, size_t ub, size_t duplication=Geese::etype_default)

Cap the number of functions per gene.
- void `counter_loss` (PhyloCounters *counters, std::vector< size_t > nfun, size_t duplication=Geese::etype_default)

Total count of losses for an specific function.
- void `counter_overall_changes` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Total number of changes. Use this statistic to account for "preservation".
- void `counter_subfun` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Total count of Sub-functionalization events.
- void `counter_cogain` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Co-evolution (joint gain or loss)
- void `counter_longest` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Longest branch mutates (either by gain or by loss)
- void `counter_neofun` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Total number of neofunctionalization events.
- void `counter_pairwise_neofun_singlefun` (PhyloCounters *counters, size_t nfunA, size_t duplication=Geese::etype_default)

Total number of neofunctionalization events $\sum_u \sum_{w < u} [x(u,a)(1 - x(w,a)) + (1 - x(u,a)) * x(w,a)]$ change
stat: $\delta\{x(u,a): 0 \rightarrow 1\} = 1 - 2 * x(w,a)$*
- void `counter_neofun_a2b` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Total number of neofunctionalization events.
- void `counter_co_opt` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Function co-opting.
- void `counter_k_genes_changing` (PhyloCounters *counters, size_t k, size_t duplication=Geese::etype_default)

Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_less_than_p_prop_genes_changing` (PhyloCounters *counters, double p, size_t duplication=Geese::etype_default)

Indicator function. Equals to one if k genes changed and zero otherwise.
- void `counter_gains_from_0` (PhyloCounters *counters, std::vector< size_t > nfun, size_t duplication=Geese::etype_default)

Used when all the functions are in 0 (like the root node prob.)
- void `counter_overall_gains_from_0` (PhyloCounters *counters, size_t duplication=Geese::etype_default)

Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_overall_change` (PhyloCounters *counters, size_t duplication=Geese::etype_default)


Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_preserving` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Used when all the functions are in 0 (like the root node prob.)
- void `counter_pairwise_first_gain` (PhyloCounters *counters, size_t nfunA, size_t nfunB, size_t duplication=Geese::etype_default)

Used when all the functions are in 0 (like the root node prob.)

9.35 include/barry/models/defm/defm-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [DEFM](#)

9.36 include/barry/models/defm/defm-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define [DEFM_RANGES\(a\)](#)
- #define [DEFM_LOOP_ARRAYS\(a\)](#) `for (size_t a = 0u; a < (nobs_i - M_order); ++a)`

Functions

- `std::vector< double > keygen_defm (const DEFMArray &Array_, DEFMCounterData *data)`

9.36.1 Macro Definition Documentation

9.36.1.1 DEFM_LOOP_ARRAYS

```
#define DEFM_LOOP_ARRAYS(  
    a )    for (size_t a = 0u; a < (nobs_i - M_order); ++a)
```

Definition at line 36 of file defm-meat.hpp.

9.36.1.2 DEFM_RANGES

```
#define DEFM_RANGES(  
    a )
```

Value:

```
size_t start_i = start_end[a * 2u];\  
size_t end_i   = start_end[a * 2u + 1u];\  
size_t nobs_i  = end_i - start_i + 1u;
```

Definition at line 31 of file defm-meat.hpp.

9.36.2 Function Documentation


9.36.2.1 keygen_defm()

```
std::vector< double > keygen_defm (  
    const DEFMArray & Array_,  
    DEFMCounterData * data ) [inline]
```

Definition at line 4 of file defm-meat.hpp.

9.37 include/barry/models/defm/defm-types.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [DEFMData](#)
Data class for [DEFM](#) arrays.
- class [DEFMCounterData](#)
Data class used to store arbitrary `size_t` or double vectors.
- class [DEFMRuleData](#)
- class [DEFMRuleDynData](#)

Typedefs

- typedef `barry::BArrayDense< int, DEFMData >` [DEFMArray](#)

Convenient typedefs for network objects.

- typedef `barry::Counter< DEFMArray, DEFMCounterData >` [DEFMCounter](#)
- typedef `barry::Counters< DEFMArray, DEFMCounterData >` [DEFMCounters](#)
- typedef `barry::Support< DEFMArray, DEFMCounterData, DEFMRuleData, DEFMRuleDynData >` [DEFMSupport](#)
- typedef `barry::StatsCounter< DEFMArray, DEFMCounterData >` [DEFMStatsCounter](#)
- typedef `barry::Model< DEFMArray, DEFMCounterData, DEFMRuleData, DEFMRuleDynData >` [DEFMModel](#)
- typedef `barry::Rule< DEFMArray, DEFMRuleData >` [DEFMRule](#)
- typedef `barry::Rules< DEFMArray, DEFMRuleData >` [DEFMRules](#)
- typedef `barry::Rule< DEFMArray, DEFMRuleDynData >` [DEFMRuleDyn](#)
- typedef `barry::Rules< DEFMArray, DEFMRuleDynData >` [DEFMRulesDyn](#)

9.37.1 Typedef Documentation


9.37.1.1 DEFMArrray

```
typedef barry::BArrayDense<int, DEFMData> DEFMArrray
```

Definition at line 5 of file defm-types.hpp.

9.38 include/barry/models/defm/formula.hpp File Reference

This graph shows which files directly or indirectly include this file:



Functions

- void `defm_motif_parser` (std::string formula, std::vector< size_t > &locations, std::vector< bool > &signs, size_t m_order, size_t y_ncol)

Parses a motif formula.

9.38.1 Function Documentation

9.38.1.1 defm_motif_parser()

```
void defm_motif_parser (
    std::string formula,
    std::vector< size_t > & locations,
    std::vector< bool > & signs,
    size_t m_order,
    size_t y_ncol ) [inline]
```

Parses a motif formula.

This function will take the formula and generate the corresponding input for `defm::counter_transition()`. Formulas can be specified in the following ways:

- Intercept effect: {...} No transition, only including the current state.
- Transition effect: {...} > {...} Includes current and previous states.

The general notation is `[0]y[column id]_[row id]`. A preceeding zero means that the value of the cell is considered to be zero. The column id goes between 0 and the number of columns in the array - 1 (so it is indexed from 0,) and the row id goes from 0 to `m_order`.

Intercept effects

Intercept effects only involve a single set of curly brackets. Using the 'greater-than' symbol (i.e., '<') is only for transition effects. When specifying intercept effects, users can skip the `row_id`, e.g., `y0_0` is equivalent to `y0`. If the passed `row_id` is different from the Markov order, i.e., `row_id != m_order`, then the function returns with an error.

Examples:

- `"{y0, 0y1}"` is equivalent to set a motif with the first element equal to one and the second to zero.

Transition effects

Transition effects can be specified using two sets of curly brackets and an greater-than symbol, i.e., `{...} > {...}`. The first set of brackets, which we call LHS, can only hold `row_id` that are less than `m_order`.

Parameters

<i>formula</i>	
<i>locations</i>	
<i>signs</i>	
<i>m_order</i>	
<i>y_ncol</i>	

Definition at line 46 of file `formula.hpp`.

9.39 include/barry/models/geese.hpp File Reference

```
#include "geese/geese-types.hpp"
#include "geese/geese-node-bones.hpp"
#include "geese/geese-bones.hpp"
#include "geese/geese-meat.hpp"
#include "geese/geese-meat-constructors.hpp"
#include "geese/geese-meat-likelihood.hpp"
#include "geese/geese-meat-likelihood_exhaust.hpp"
#include "geese/geese-meat-simulate.hpp"
#include "geese/geese-meat-predict.hpp"
#include "geese/geese-meat-predict_exhaust.hpp"
#include "geese/geese-meat-predict_sim.hpp"
#include "geese/flock-bones.hpp"
#include "geese/flock-meat.hpp"
#include "geese/counters.hpp"
```

Include dependency graph for geese.hpp:




Namespaces

- [geese](#)

9.40 include/barry/models/geese/flock-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [Flock](#)
A [Flock](#) is a group of [Geese](#).


9.41 `include/barry/models/geese/flock-meat.hpp` File Reference

This graph shows which files directly or indirectly include this file:



9.42 `include/barry/models/geese/geese-bones.hpp` File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [Geese](#)
Annotated Phylo [Model](#).

Macros

- `#define INITIALIZED()`

Functions

- `template<typename Ta , typename Tb > std::vector< Ta > vector_caster (const std::vector< Tb > &x)`
- `RULE_FUNCTION (rule_empty_free)`
- `std::vector< double > keygen_full (const PhyloArray &array, const PhyloCounterData *d)`
- `bool vec_diff (const std::vector< size_t > &s, const std::vector< size_t > &a)`

9.42.1 Macro Definition Documentation

9.42.1.1 INITIALIZED

```
#define INITIALIZED( )
```

Value:

```
if (!this->initialized) \
    throw std::logic_error("The model has not been initialized yet.");
```

Definition at line 22 of file geese-bones.hpp.

9.42.2 Function Documentation

9.42.2.1 keygen_full()

```
std::vector< double > keygen_full (
    const PhyloArray & array,
    const PhyloCounterData * d ) [inline]
```

Definition at line 36 of file geese-bones.hpp.

9.42.2.2 RULE_FUNCTION()

```
RULE_FUNCTION (
    rule_empty_free )
```

Definition at line 26 of file geese-bones.hpp.

9.42.2.3 `vec_diff()`

```
bool vec_diff (
    const std::vector< size_t > & s,
    const std::vector< size_t > & a ) [inline]
```

Definition at line 60 of file geese-bones.hpp.


9.42.2.4 `vector_caster()`

```
template<typename Ta , typename Tb >
std::vector< Ta > vector_caster (
    const std::vector< Tb > & x ) [inline]
```

Definition at line 10 of file geese-bones.hpp.

9.43 `include/barry/models/geese/geese-meat-constructors.hpp` File Reference


This graph shows which files directly or indirectly include this file:




9.44 include/barry/models/geese/geese-meat-likelihood.hpp File Reference

```
#include "geese-bones.hpp"
```

Include dependency graph for geese-meat-likelihood.hpp:




This graph shows which files directly or indirectly include this file:




9.45 include/barry/models/geese/geese-meat-likelihood_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:




9.46 include/barry/models/geese/geese-meat-predict.hpp File Reference

This graph shows which files directly or indirectly include this file:




9.47 include/barry/models/geese/geese-meat-predict_exhaust.hpp File Reference

This graph shows which files directly or indirectly include this file:




9.48 include/barry/models/geese/geese-meat-predict_sim.hpp File Reference

This graph shows which files directly or indirectly include this file:




9.49 include/barry/models/geese/geese-meat-simulate.hpp File Reference

This graph shows which files directly or indirectly include this file:




9.50 include/barry/models/geese/geese-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



9.51 include/barry/models/geese/geese-node-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [Node](#)
A single node for the model.

9.52 include/barry/models/geese/geese-types.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [NodeData](#)
Data definition for the `PhyloArray` class.
- class [PhyloCounterData](#)
- class [PhyloRuleDynData](#)

Typedefs

Convenient typedefs for Node objects.

- typedef std::vector< std::pair< size_t, size_t > > [PhyloRuleData](#)
- typedef barry::BArrayDense< size_t, [NodeData](#) > [PhyloArray](#)
- typedef barry::Counter< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounter](#)
- typedef barry::Counters< [PhyloArray](#), [PhyloCounterData](#) > [PhyloCounters](#)
- typedef barry::Rule< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRule](#)
- typedef barry::Rules< [PhyloArray](#), [PhyloRuleData](#) > [PhyloRules](#)
- typedef barry::Rule< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRuleDyn](#)
- typedef barry::Rules< [PhyloArray](#), [PhyloRuleDynData](#) > [PhyloRulesDyn](#)
- typedef barry::Support< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloSupport](#)
- typedef barry::StatsCounter< [PhyloArray](#), [PhyloCounterData](#) > [PhyloStatsCounter](#)
- typedef barry::Model< [PhyloArray](#), [PhyloCounterData](#), [PhyloRuleData](#), [PhyloRuleDynData](#) > [PhyloModel](#)
- typedef barry::PowerSet< [PhyloArray](#), [PhyloRuleData](#) > [PhyloPowerSet](#)

9.52.1 Typedef Documentation

9.52.1.1 PhyloArray

```
typedef barry::BArrayDense<size_t, NodeData> PhyloArray
```

Definition at line 101 of file geese-types.hpp.

9.52.1.2 PhyloCounter

```
typedef barry::Counter<PhyloArray, PhyloCounterData > PhyloCounter
```

Definition at line 102 of file geese-types.hpp.

9.52.1.3 PhyloCounters

```
typedef barry::Counters< PhyloArray, PhyloCounterData> PhyloCounters
```

Definition at line 103 of file geese-types.hpp.

9.52.1.4 PhyloModel

```
typedef barry::Model<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloModel
```

Definition at line 113 of file geese-types.hpp.

9.52.1.5 PhyloPowerSet

```
typedef barry::PowerSet<PhyloArray, PhyloRuleData> PhyloPowerSet
```

Definition at line 114 of file geese-types.hpp.

9.52.1.6 PhyloRule

```
typedef barry::Rule<PhyloArray, PhyloRuleData> PhyloRule
```

Definition at line 105 of file geese-types.hpp.

9.52.1.7 PhyloRuleData

```
typedef std::vector< std::pair< size_t, size_t > > PhyloRuleData
```

Definition at line 98 of file geese-types.hpp.

9.52.1.8 PhyloRuleDyn

```
typedef barry::Rule<PhyloArray, PhyloRuleDynData> PhyloRuleDyn
```

Definition at line 108 of file geese-types.hpp.

9.52.1.9 PhyloRules

```
typedef barry::Rules<PhyloArray, PhyloRuleData> PhyloRules
```

Definition at line 106 of file geese-types.hpp.

9.52.1.10 PhyloRulesDyn

```
typedef barry::Rules<PhyloArray, PhyloRuleDynData> PhyloRulesDyn
```

Definition at line 109 of file geese-types.hpp.

9.52.1.11 PhyloStatsCounter

```
typedef barry::StatsCounter<PhyloArray, PhyloCounterData> PhyloStatsCounter
```

Definition at line 112 of file geese-types.hpp.


9.52.1.12 PhyloSupport

```
typedef barry::Support<PhyloArray, PhyloCounterData, PhyloRuleData, PhyloRuleDynData > PhyloSupport
```

Definition at line 111 of file geese-types.hpp.

9.53 include/barry/powerset-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [PowerSet< Array_Type, Data_Rule_Type >](#)
Powerset of a binary array.


9.54 include/barry/powerset-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



9.55 include/barry/progress.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [Progress](#)
A simple progress bar.

Macros

- `#define` [BARRY_PROGRESS_BAR_WIDTH](#) 80

9.55.1 Macro Definition Documentation


9.55.1.1 BARRY_PROGRESS_BAR_WIDTH

```
#define BARRY_PROGRESS_BAR_WIDTH 80
```

Definition at line 5 of file progress.hpp.

9.56 include/barry/rules-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:



Classes

- class [Rule< Array_Type, Data_Type >](#)
Rule for determining if a cell should be included in a sequence.
- class [Rules< Array_Type, Data_Type >](#)
Vector of objects of class Rule.

Functions

- template<typename Array_Type , typename Data_Type >
bool [rule_fun_default](#) (const Array_Type *array, size_t i, size_t j, Data_Type *dat)

9.56.1 Function Documentation


9.56.1.1 rule_fun_default()

```
template<typename Array_Type , typename Data_Type >
bool rule_fun_default (
    const Array_Type * array,
    size_t i,
    size_t j,
    Data_Type * dat )
```

Definition at line 5 of file rules-bones.hpp.


9.57 include/barry/rules-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



9.58 include/barry/statscounter-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [StatsCounter](#)< [Array_Type](#), [Data_Type](#) >
Count stats for a single Array.

9.59 include/barry/statscounter-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- #define [STATSCOUNTER_TYPE](#)() [StatsCounter](#)<[Array_Type](#),[Data_Type](#)>
- #define [STATSCOUNTER_TEMPLATE_ARGS](#)() <typename [Array_Type](#), typename [Data_Type](#)>
- #define [STATSCOUNTER_TEMPLATE](#)(a, b) template [STATSCOUNTER_TEMPLATE_ARGS](#)() inline a [STATSCOUNTER_TYPE](#)()::b

Functions

- [STATSCOUNTER_TEMPLATE](#) (, [StatsCounter](#))(const [StatsCounter](#)< [Array_Type](#)
- [EmptyArray](#) clear ()
- [STATSCOUNTER_TEMPLATE](#) (,~[StatsCounter](#)())()
- [STATSCOUNTER_TEMPLATE](#) (void, reset_array)(const [Array_Type](#) *Array_)
- [STATSCOUNTER_TEMPLATE](#) (void, add_counter)([Counter](#)< [Array_Type](#)
- [STATSCOUNTER_TEMPLATE](#) (void, set_counters)([Counters](#)< [Array_Type](#)
- [STATSCOUNTER_TEMPLATE](#) (void, count_init)(size_t i
- [current_stats](#) resize (counters->size(), 0.0)
- for (size_t n=0u;n< counters->size();++n) [current_stats](#)[n]
- [STATSCOUNTER_TEMPLATE](#) (void, count_current)(size_t i
- [STATSCOUNTER_TEMPLATE](#) (std::vector< std::string >, get_names)() const
- [STATSCOUNTER_TEMPLATE](#) (std::vector< std::string >, get_descriptions)() const

Variables

- Data_Type & [counter](#)
- [EmptyArray](#) = *Array
- [current_stats](#) = counter.current_stats
- [counters](#) = new [Counters](#)<Array_Type,Data_Type>((*counter.counters))
- [counter_deleted](#) = false
- Data_Type [f_](#)
- [return](#)
- Data_Type * [counters_](#)
- size_t [j](#)

9.59.1 Macro Definition Documentation

9.59.1.1 STATSCOUNTER_TEMPLATE

```
#define STATSCOUNTER_TEMPLATE(  
    a,  
    b )  template STATSCOUNTER\_TEMPLATE\_ARGS( ) inline a STATSCOUNTER\_TYPE()::b
```

Definition at line 8 of file statscounter-meat.hpp.

9.59.1.2 STATSCOUNTER_TEMPLATE_ARGS

```
template STATSCOUNTER\_TEMPLATE\_ARGS( ) <typename Array_Type, typename Data_Type>
```

Definition at line 6 of file statscounter-meat.hpp.

9.59.1.3 STATSCOUNTER_TYPE

```
template Data_Type * STATSCOUNTER\_TYPE( ) StatsCounter<Array_Type,Data_Type>
```

Definition at line 4 of file statscounter-meat.hpp.

9.59.2 Function Documentation

9.59.2.1 clear()

```
EmptyArray clear ( )
```

9.59.2.2 for()

```
for (
    size_t n = 0; n < counters->size(); ++n )
```

9.59.2.3 resize()

```
current_stats resize (
    counters-> size(),
    0, 0 )
```

9.59.2.4 STATSCOUNTER_TEMPLATE() [1/9]

```
STATSCOUNTER_TEMPLATE (
    StatsCounter ) const
```

9.59.2.5 STATSCOUNTER_TEMPLATE() [2/9]

```
STATSCOUNTER_TEMPLATE (
    ~ StatsCounter )
```

Definition at line 27 of file statscounter-meat.hpp.

9.59.2.6 STATSCOUNTER_TEMPLATE() [3/9]

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_descriptions ) const
```

Definition at line 256 of file statscounter-meat.hpp.

9.59.2.7 STATSCOUNTER_TEMPLATE() [4/9]

```
STATSCOUNTER_TEMPLATE (
    std::vector< std::string > ,
    get_names ) const
```

Definition at line 251 of file statscounter-meat.hpp.

9.59.2.8 STATSCOUNTER_TEMPLATE() [5/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    add_counter )
```

9.59.2.9 STATSCOUNTER_TEMPLATE() [6/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_current )
```

9.59.2.10 STATSCOUNTER_TEMPLATE() [7/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    count_init )
```

9.59.2.11 STATSCOUNTER_TEMPLATE() [8/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    reset_array ) const
```

Definition at line 34 of file statscounter-meat.hpp.

9.59.2.12 STATSCOUNTER_TEMPLATE() [9/9]

```
STATSCOUNTER_TEMPLATE (
    void ,
    set_counters )
```

9.59.3 Variable Documentation

9.59.3.1 counter

```
Data_Type& counter
```

Initial value:

```
{  
    Array      = counter.Array
```

Definition at line 12 of file statscounter-meat.hpp.

9.59.3.2 counter_deleted

```
counter_deleted = false
```

Definition at line 23 of file statscounter-meat.hpp.

9.59.3.3 counters

```
counters = new Counters<Array_Type,Data_Type>((*counter.counters))
```

Definition at line 22 of file statscounter-meat.hpp.

9.59.3.4 counters_

```
Data_Type* counters_
```

Initial value:

```
{  
  
    if (!counter_deleted)  
        delete counters
```

Definition at line 53 of file statscounter-meat.hpp.

9.59.3.5 current_stats

```
current_stats = counter.current_stats
```

Definition at line 19 of file statscounter-meat.hpp.

9.59.3.6 EmptyArray

```
EmptyArray = *Array
```

Definition at line 17 of file statscounter-meat.hpp.

9.59.3.7 f_

```
Data_Type f_
```

Initial value:

```
{  
    counters->add_counter(f_)
```

Definition at line 44 of file statscounter-meat.hpp.

9.59.3.8 j

```
size_t j
```

Initial value:

```
{  
  
    if (counters->size() == 0u)  
        throw std::logic_error("No counters added: Cannot count without knowing what to count!")
```

Definition at line 66 of file statscounter-meat.hpp.


9.59.3.9 return

```
return
```

Definition at line 49 of file statscounter-meat.hpp.

9.60 include/barry/support-bones.hpp File Reference

This graph shows which files directly or indirectly include this file:




Classes

- class [Support](#)< [Array_Type](#), [Data_Counter_Type](#), [Data_Rule_Type](#), [Data_Rule_Dyn_Type](#) >
Compute the support of sufficient statistics.

9.61 include/barry/support-meat.hpp File Reference

This graph shows which files directly or indirectly include this file:



Macros

- `#define` [BARRY_SUPPORT_MEAT_HPP](#) 1

9.61.1 Macro Definition Documentation

9.61.1.1 BARRY_SUPPORT_MEAT_HPP


```
#define BARRY_SUPPORT_MEAT_HPP 1
```

Definition at line 2 of file support-meat.hpp.


9.62 include/barry/typedefs.hpp File Reference

```
#include "barry-configuration.hpp"  
#include "barry-debug.hpp"  
#include "progress.hpp"
```

Include dependency graph for typedefs.hpp:



This graph shows which files directly or indirectly include this file:



Classes

- class [Entries< Cell_Type >](#)
A wrapper class to store source, target, val from a [BArray](#) object.
- struct [vecHasher< T >](#)

Namespaces

- [CHECK](#)
Integer constants used to specify which cell should be check.
- [EXISTS](#)
Integer constants used to specify which cell should be check to exist or not.

Typedefs

- typedef std::vector< std::pair< std::vector< double >, size_t > > [Counts_type](#)
- template<typename Cell_Type >
using [Row_type](#) = Map< size_t, Cell< Cell_Type > >
- template<typename Cell_Type >
using [Col_type](#) = Map< size_t, Cell< Cell_Type > * >
- template<typename Ta = double, typename Tb = size_t>
using [MapVec_type](#) = std::unordered_map< std::vector< Ta >, Tb, [vecHasher](#)< Ta > >
- template<typename Array_Type , typename Data_Type >
using [Hasher_fun_type](#) = std::function< std::vector< double >(const Array_Type &, Data_Type *)>
Hasher function used by the counter.
- template<typename Array_Type , typename Data_Type >
using [Counter_fun_type](#) = std::function< double(const Array_Type &, size_t, size_t, Data_Type &)>
Counter and rule functions.
- template<typename Array_Type , typename Data_Type >
using [Rule_fun_type](#) = std::function< bool(const Array_Type &, size_t, size_t, Data_Type &)>

Functions

- std::vector< size_t > [sort_array](#) (const double *v, size_t start, size_t ncols, size_t nrows)
Ascending sorting an array.
- template<typename T >
T [vec_inner_prod](#) (const T *a, const T *b, size_t n)
- template<> double [vec_inner_prod](#) (const double *a, const double *b, size_t n)
- template<typename T >
bool [vec_equal](#) (const std::vector< T > &a, const std::vector< T > &b)
Compares if -a- and -b- are equal.
- template<typename T >
bool [vec_equal_approx](#) (const std::vector< T > &a, const std::vector< T > &b, double eps=1e-100)

Variables

- const int [CHECK::BOTH](#) = -1
- const int [CHECK::NONE](#) = 0
- const int [CHECK::ONE](#) = 1
- const int [CHECK::TWO](#) = 2
- const int [EXISTS::BOTH](#) = -1
- const int [EXISTS::NONE](#) = 0
- const int [EXISTS::ONE](#) = 1
- const int [EXISTS::TWO](#) = 1
- const int [EXISTS::UNKNOWN](#) = -1
- const int [EXISTS::AS_ZERO](#) = 0
- const int [EXISTS::AS_ONE](#) = 1

9.62.1 Typedef Documentation

9.62.1.1 Col_type

```
template<typename Cell_Type >
using Col_type = Map< size_t, Cell<Cell_Type>* >
```

Definition at line 70 of file typedefs.hpp.

9.62.1.2 Counter_fun_type

```
template<typename Array_Type , typename Data_Type >
using Counter_fun_type = std::function<double(const Array_Type &, size_t, size_t, Data_Type
&)>
```

[Counter](#) and rule functions.

Parameters

<i>Array_Type</i>	a BArray
<i>unit, size_t</i>	Focal cell
<i>Data_Type</i>	Data associated with the function, for example, id of the attribute in the Array.

Returns

[Counter_fun_type](#) a double (the change statistic)

[Rule_fun_type](#) a bool. True if the cell is blocked.

Definition at line 187 of file typedefs.hpp.

9.62.1.3 Counts_type

```
typedef std::vector< std::pair< std::vector<double>, size_t > > Counts_type
```

Definition at line 51 of file typedefs.hpp.

9.62.1.4 Hasher_fun_type

```
template<typename Array_Type , typename Data_Type >
using Hasher_fun_type = std::function<std::vector<double>(const Array_Type &, Data_Type *)>
```

Hasher function used by the counter.

Used to characterize the support of the array.

Template Parameters

<i>Array_Type</i>	
-------------------	--

Definition at line 200 of file typedefs.hpp.

9.62.1.5 MapVec_type

```
template<typename Ta = double, typename Tb = size_t>
using MapVec_type = std::unordered_map< std::vector< Ta >, Tb, vecHasher<Ta> >
```

Definition at line 128 of file typedefs.hpp.

9.62.1.6 Row_type

```
template<typename Cell_Type >
using Row_type = Map< size_t, Cell<Cell_Type> >
```

Definition at line 67 of file typedefs.hpp.

9.62.1.7 Rule_fun_type

```
template<typename Array_Type , typename Data_Type >
using Rule_fun_type = std::function<bool(const Array_Type &, size_t, size_t, Data_Type &)>
```

Definition at line 190 of file typedefs.hpp.

9.62.2 Function Documentation

9.62.2.1 sort_array()

```
std::vector< size_t > sort_array (
    const double * v,
    size_t start,
    size_t ncols,
    size_t nrows ) [inline]
```

Ascending sorting an array.

It will sort an array solving ties using the next column. Data is stored column-wise.

Template Parameters

<i>T</i>	
----------	--

Parameters

<i>v</i>	
<i>nrows</i>	

Returns

`std::vector<size_t>` The sorting index.

Definition at line 141 of file typedefs.hpp.

9.62.2.2 `vec_equal()`

```
template<typename T >
bool vec_equal (
    const std::vector< T > & a,
    const std::vector< T > & b ) [inline]
```

Compares if `-a-` and `-b-` are equal.

Parameters

<i>a,b</i>	Two vectors of the same length
------------	--------------------------------

Returns

`true` if all elements are equal.

Definition at line 210 of file typedefs.hpp.

9.62.2.3 `vec_equal_approx()`

```
template<typename T >
bool vec_equal_approx (
    const std::vector< T > & a,
    const std::vector< T > & b,
    double eps = 1e-100 ) [inline]
```

Definition at line 235 of file typedefs.hpp.

9.62.2.4 `vec_inner_prod()` [1/2]

```
template<>
double vec_inner_prod (
    const double * a,
    const double * b,
    size_t n ) [inline]
```

Definition at line 290 of file typedefs.hpp.

9.62.2.5 `vec_inner_prod()` [2/2]

```
template<typename T >
T vec_inner_prod (
    const T * a,
    const T * b,
    size_t n ) [inline]
```

Definition at line 263 of file typedefs.hpp.

9.63 README.md File Reference

Index

- ~BArray
 - BArray< Cell_Type, Data_Type >, [63](#)
- ~BArrayCell
 - BArrayCell< Cell_Type, Data_Type >, [74](#)
- ~BArrayCell_const
 - BArrayCell_const< Cell_Type, Data_Type >, [77](#)
- ~BArrayDense
 - BArrayDense< Cell_Type, Data_Type >, [83](#)
- ~BArrayDenseCell
 - BArrayDenseCell< Cell_Type, Data_Type >, [97](#)
- ~BArrayRow
 - BArrayRow< Cell_Type, Data_Type >, [110](#)
- ~BArrayRow_const
 - BArrayRow_const< Cell_Type, Data_Type >, [112](#)
- ~BArrayVector
 - BArrayVector< Cell_Type, Data_Type >, [115](#)
- ~BArrayVector_const
 - BArrayVector_const< Cell_Type, Data_Type >, [118](#)
- ~Cell
 - Cell< Cell_Type >, [122](#)
- ~ConstBArrayRowIter
 - ConstBArrayRowIter< Cell_Type, Data_Type >, [127](#)
- ~Counter
 - Counter< Array_Type, Data_Type >, [130](#)
- ~Counters
 - Counters< Array_Type, Data_Type >, [135](#)
- ~DEFMCounterData
 - Phylo rules, [43](#)
- ~DEFMData
 - Phylo rules, [43](#)
- ~DEFMRuleDynData
 - Phylo rules, [43](#)
- ~Entries
 - Entries< Cell_Type >, [149](#)
- ~Flock
 - Flock, [151](#)
- ~FreqTable
 - FreqTable< T >, [158](#)
- ~Geese
 - Geese, [164](#)
- ~Model
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [180](#)
- ~NetCounterData
 - NetCounterData, [198](#)
- ~NetworkData
 - NetworkData, [200](#)
- ~Node
 - Node, [203](#)
- ~PhyloRuleDynData
 - PhyloRuleDynData, [212](#)
- ~PowerSet
 - PowerSet< Array_Type, Data_Rule_Type >, [215](#)
- ~Progress
 - Progress, [220](#)
- ~Rule
 - Rule< Array_Type, Data_Type >, [222](#)
- ~Rules
 - Rules< Array_Type, Data_Type >, [225](#)
- ~StatsCounter
 - StatsCounter< Array_Type, Data_Type >, [230](#)
- ~Support
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [235](#)
- a
 - model-meat.hpp, [314](#)
- active
 - Cell< Cell_Type >, [125](#)
- add
 - Cell< Cell_Type >, [123](#), [124](#)
 - FreqTable< T >, [158](#)
- add_array
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [180](#)
- add_counter
 - Counters< Array_Type, Data_Type >, [135](#), [136](#)
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [180](#), [181](#)
 - StatsCounter< Array_Type, Data_Type >, [230](#)
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [235](#)
- add_data
 - Flock, [151](#)
- add_dims
 - counters-meat.hpp, [281](#)
- add_hash
 - Counters< Array_Type, Data_Type >, [136](#)
- add_hasher
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [181](#)

- add_rule
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 181
 - PowerSet< Array_Type, Data_Rule_Type >, 215, 216
 - Rules< Array_Type, Data_Type >, 226
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 235, 236
- add_rule_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 181, 182
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 236
- annotations
 - Node, 204
- Array
 - ConstBArrayRowIter< Cell_Type, Data_Type >, 127
- array
 - Node, 204
 - Phylo rules, 44
- arrays
 - Node, 204
- arrays2support
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 191
- AS_ONE
 - EXISTS, 57
- as_vector
 - FreqTable< T >, 158
- AS_ZERO
 - EXISTS, 57
- at
 - Phylo rules, 39
 - PhyloCounterData, 209
- BArray
 - BArray< Cell_Type, Data_Type >, 62, 63
- BArray< Cell_Type, Data_Type >, 59
 - ~BArray, 63
 - BArray, 62, 63
 - BArrayCell< Cell_Type, Data_Type >, 73
 - BArrayCell_const< Cell_Type, Data_Type >, 73
 - clear, 63
 - col, 63
 - D, 64
 - D_ptr, 64
 - default_val, 64
 - flush_data, 64
 - get_cell, 64
 - get_col_vec, 65
 - get_entries, 65
 - get_row_vec, 65
 - insert_cell, 66
 - is_dense, 66
 - is_empty, 66
 - ncol, 67
 - nnozero, 67
 - nrow, 67
 - operator*=: 67
 - operator(), 67
 - operator+=, 68
 - operator-=, 68
 - operator/=: 69
 - operator=: 69
 - operator==, 69
 - out_of_range, 69
 - print, 69
 - print_n, 70
 - reserve, 70
 - resize, 70
 - rm_cell, 70
 - row, 70
 - set_data, 71
 - swap_cells, 71
 - swap_cols, 71
 - swap_rows, 71
 - toggle_cell, 72
 - toggle_lock, 72
 - transpose, 72
 - visited, 73
 - zero_col, 72
 - zero_row, 72
- barray-meat-operators.hpp
 - BARRAY_TEMPLATE, 246–248
 - BARRAY_TEMPLATE_ARGS, 247, 249
 - BARRAY_TYPE, 247, 249
 - COL, 247
 - for, 249
 - operator(), 249
 - rhs, 249
 - ROW, 247
 - this, 250
- barray-meat.hpp
 - COL, 250
 - ROW, 251
- BARRAY_TEMPLATE
 - barray-meat-operators.hpp, 246–248
- BARRAY_TEMPLATE_ARGS
 - barray-meat-operators.hpp, 247, 249
- BARRAY_TYPE
 - barray-meat-operators.hpp, 247, 249
- BArrayCell
 - BArrayCell< Cell_Type, Data_Type >, 74
- BArrayCell< Cell_Type, Data_Type >, 74
 - ~BArrayCell, 74
 - BArray< Cell_Type, Data_Type >, 73
 - BArrayCell, 74
 - operator Cell_Type, 75
 - operator*=: 75
 - operator+=, 75
 - operator-=, 75

- operator/=[, 75](#)
- operator=[, 75](#)
- operator==[, 76](#)
- BArrayCell_const
 - BArrayCell_const< Cell_Type, Data_Type >[, 77](#)
- BArrayCell_const< Cell_Type, Data_Type >[, 76](#)
 - ~BArrayCell_const[, 77](#)
 - BArray< Cell_Type, Data_Type >[, 73](#)
 - BArrayCell_const[, 77](#)
 - operator Cell_Type[, 77](#)
 - operator!=[, 77](#)
 - operator<[, 77](#)
 - operator<=[, 78](#)
 - operator>[, 78](#)
 - operator>=[, 78](#)
 - operator==[, 78](#)
- BArrayDense
 - BArrayDense< Cell_Type, Data_Type >[, 82, 83](#)
- BArrayDense< Cell_Type, Data_Type >[, 79](#)
 - ~BArrayDense[, 83](#)
 - BArrayDense[, 82, 83](#)
 - BArrayDenseCell< Cell_Type, Data_Type >[, 95, 99](#)
 - BArrayDenseCol< Cell_Type, Data_Type >[, 95, 102](#)
 - BArrayDenseCol_const< Cell_Type, Data_Type >[, 95](#)
 - BArrayDenseRow< Cell_Type, Data_Type >[, 95, 106](#)
 - BArrayDenseRow_const< Cell_Type, Data_Type >[, 95](#)
 - clear[, 83](#)
 - col[, 84](#)
 - colsum[, 84](#)
 - D[, 84](#)
 - D_ptr[, 85](#)
 - default_val[, 85](#)
 - get_cell[, 85](#)
 - get_col_vec[, 85, 86](#)
 - get_data[, 86](#)
 - get_entries[, 86](#)
 - get_row_vec[, 86, 87](#)
 - insert_cell[, 87](#)
 - is_dense[, 87](#)
 - is_empty[, 88](#)
 - ncol[, 88](#)
 - nnozero[, 88](#)
 - nrow[, 88](#)
 - operator*=[, 89](#)
 - operator()[, 88, 89](#)
 - operator+=[, 89](#)
 - operator-=[, 90](#)
 - operator/=[, 90](#)
 - operator=[, 90, 91](#)
 - operator==[, 91](#)
 - out_of_range[, 91](#)
 - print[, 91](#)
 - reserve[, 91](#)
 - resize[, 92](#)
 - rm_cell[, 92](#)
 - row[, 92](#)
 - rowsum[, 92](#)
 - set_data[, 93](#)
 - swap_cells[, 93](#)
 - swap_cols[, 93](#)
 - swap_rows[, 93](#)
 - toggle_cell[, 94](#)
 - toggle_lock[, 94](#)
 - transpose[, 94](#)
 - visited[, 96](#)
 - zero_col[, 94](#)
 - zero_row[, 94](#)
- barraydense-meat-operators.hpp
 - BDENSE_TEMPLATE[, 253, 255](#)
 - BDENSE_TEMPLATE_ARGS[, 253, 255](#)
 - BDENSE_TYPE[, 254, 256](#)
 - COL[, 254](#)
 - POS[, 254](#)
 - POS_N[, 254](#)
 - ROW[, 254](#)
- barraydense-meat.hpp
 - COL[, 256](#)
 - POS[, 256](#)
 - POS_N[, 257](#)
 - ROW[, 257](#)
 - ZERO_CELL[, 257](#)
- BArrayDenseCell
 - BArrayDenseCell< Cell_Type, Data_Type >[, 97](#)
- BArrayDenseCell< Cell_Type, Data_Type >[, 96](#)
 - ~BArrayDenseCell[, 97](#)
 - BArrayDense< Cell_Type, Data_Type >[, 95, 99](#)
 - BArrayDenseCell[, 97](#)
 - BArrayDenseCol< Cell_Type, Data_Type >[, 99, 102](#)
 - BArrayDenseCol_const< Cell_Type, Data_Type >[, 99, 104](#)
 - BArrayDenseRow< Cell_Type, Data_Type >[, 106](#)
 - BArrayDenseRow_const< Cell_Type, Data_Type >[, 109](#)
 - operator Cell_Type[, 97](#)
 - operator*=[, 97](#)
 - operator+=[, 98](#)
 - operator-=[, 98](#)
 - operator/=[, 98](#)
 - operator=[, 98](#)
 - operator==[, 99](#)
- barraydensecell-bones.hpp
 - POS[, 258](#)
- barraydensecell-meat.hpp
 - POS[, 258](#)
- BArrayDenseCell_const< Cell_Type, Data_Type >[, 100](#)
 - BArrayDenseCol< Cell_Type, Data_Type >[, 102](#)
 - BArrayDenseCol_const< Cell_Type, Data_Type >[, 104](#)
 - BArrayDenseRow< Cell_Type, Data_Type >[, 106](#)

- BArrayDenseRow_const< Cell_Type, Data_Type >, 109
- BArrayDenseCol
 - BArrayDenseCol< Cell_Type, Data_Type >, 100
- BArrayDenseCol< Cell_Type, Data_Type >, 100
 - BArrayDense< Cell_Type, Data_Type >, 95, 102
 - BArrayDenseCell< Cell_Type, Data_Type >, 99, 102
 - BArrayDenseCell_const< Cell_Type, Data_Type >, 102
 - BArrayDenseCol, 100
 - begin, 101
 - end, 101
 - operator(), 101
 - size, 101
- barraydensecol-bones.hpp
 - POS, 259
 - POS_N, 259
 - ZERO_CELL, 260
- BArrayDenseCol_const
 - BArrayDenseCol_const< Cell_Type, Data_Type >, 103
- BArrayDenseCol_const< Cell_Type, Data_Type >, 102
 - BArrayDense< Cell_Type, Data_Type >, 95
 - BArrayDenseCell< Cell_Type, Data_Type >, 99, 104
 - BArrayDenseCell_const< Cell_Type, Data_Type >, 104
 - BArrayDenseCol_const, 103
 - begin, 103
 - end, 103
 - operator(), 103
 - size, 104
- BArrayDenseRow
 - BArrayDenseRow< Cell_Type, Data_Type >, 105
- BArrayDenseRow< Cell_Type, Data_Type >, 104
 - BArrayDense< Cell_Type, Data_Type >, 95, 106
 - BArrayDenseCell< Cell_Type, Data_Type >, 106
 - BArrayDenseCell_const< Cell_Type, Data_Type >, 106
 - BArrayDenseRow, 105
 - begin, 105
 - end, 105
 - operator(), 106
 - size, 106
- barraydenserow-bones.hpp
 - POS, 261
 - POS_N, 261
 - ZERO_CELL, 261
- BArrayDenseRow_const
 - BArrayDenseRow_const< Cell_Type, Data_Type >, 107
- BArrayDenseRow_const< Cell_Type, Data_Type >, 107
 - begin, 108
 - end, 108
 - operator(), 108
 - size, 108
- BArrayRow
 - BArrayRow< Cell_Type, Data_Type >, 110
- BArrayRow< Cell_Type, Data_Type >, 109
 - ~BArrayRow, 110
 - BArrayRow, 110
 - operator BArrayRow< Cell_Type, Data_Type >, 110
 - operator*=, 110
 - operator+=, 110
 - operator-=, 110
 - operator/=: 111
 - operator=, 111
 - operator==, 111
- barrayrow-meat.hpp
 - BROW_TEMPLATE, 262, 263
 - BROW_TEMPLATE_ARGS, 262
 - BROW_TYPE, 262
- BArrayRow_const
 - BArrayRow_const< Cell_Type, Data_Type >, 112
- BArrayRow_const< Cell_Type, Data_Type >, 111
 - ~BArrayRow_const, 112
 - BArrayRow_const, 112
 - operator BArrayRow_const< Cell_Type, Data_Type >, 112
 - operator!=, 112
 - operator<, 112
 - operator<=, 113
 - operator>, 113
 - operator>=, 113
 - operator==, 113
- BArrayVector
 - BArrayVector< Cell_Type, Data_Type >, 114
- BArrayVector< Cell_Type, Data_Type >, 113
 - ~BArrayVector, 115
 - BArrayVector, 114
 - begin, 115
 - end, 115
 - is_col, 115
 - is_row, 115
 - operator std::vector< Cell_Type >, 116
 - operator*=, 116
 - operator+=, 116
 - operator-=, 116
 - operator/=: 116
 - operator=, 117
 - operator==, 117
 - size, 117
- BArrayVector_const
 - BArrayVector_const< Cell_Type, Data_Type >, 118
- BArrayVector_const< Cell_Type, Data_Type >, 117
 - ~BArrayVector_const, 118
 - BArrayVector_const, 118

- begin, 119
- end, 119
- is_col, 119
- is_row, 119
- operator std::vector< Cell_Type >, 119
- operator!=, 119
- operator<, 120
- operator<=, 120
- operator>, 120
- operator>=, 120
- operator==, 120
- size, 121
- barry, 55
- barry-configuration.hpp
 - BARRY_CHECK_SUPPORT, 265
 - BARRY_ISFINITE, 265
 - BARRY_MAX_NUM_ELEMENTS, 265
 - BARRY_SAFE_EXP, 265
 - Map, 266
 - printf_barry, 265
- barry-debug.hpp
 - BARRY_DEBUG_LEVEL, 266
- barry-macros.hpp
 - BARRY_ONE, 267
 - BARRY_ONE_DENSE, 267
 - BARRY_UNUSED, 267
 - BARRY_ZERO, 268
 - BARRY_ZERO_DENSE, 268
- barry.hpp
 - BARRY_HPP, 269
 - BARRY_VERSION, 270
 - BARRY_VERSION_MAYOR, 270
 - BARRY_VERSION_MINOR, 270
 - COUNTER_FUNCTION, 270
 - COUNTER_LAMBDA, 270
 - RULE_FUNCTION, 271
 - RULE_LAMBDA, 271
- barry::counters, 55
- barry::counters::network, 56
- BARRY_CHECK_SUPPORT
 - barry-configuration.hpp, 265
- BARRY_DEBUG_LEVEL
 - barry-debug.hpp, 266
- BARRY_HPP
 - barry.hpp, 269
- BARRY_ISFINITE
 - barry-configuration.hpp, 265
- BARRY_MAX_NUM_ELEMENTS
 - barry-configuration.hpp, 265
- BARRY_ONE
 - barry-macros.hpp, 267
- BARRY_ONE_DENSE
 - barry-macros.hpp, 267
- BARRY_PROGRESS_BAR_WIDTH
 - progress.hpp, 344
- BARRY_SAFE_EXP
 - barry-configuration.hpp, 265
- BARRY_SUPPORT_MEAT_HPP
 - support-meat.hpp, 352
- BARRY_UNUSED
 - barry-macros.hpp, 267
- BARRY_VERSION
 - barry.hpp, 270
- BARRY_VERSION_MAYOR
 - barry.hpp, 270
- BARRY_VERSION_MINOR
 - barry.hpp, 270
- BARRY_ZERO
 - barry-macros.hpp, 268
- BARRY_ZERO_DENSE
 - barry-macros.hpp, 268
- BARRY_ZERO_NETWORK
 - network.hpp, 296
- BARRY_ZERO_NETWORK_DENSE
 - network.hpp, 296
- BDENSE_TEMPLATE
 - barraydense-meat-operators.hpp, 253, 255
- BDENSE_TEMPLATE_ARGS
 - barraydense-meat-operators.hpp, 253, 255
- BDENSE_TYPE
 - barraydense-meat-operators.hpp, 254, 256
- begin
 - BArrayDenseCol< Cell_Type, Data_Type >, 101
 - BArrayDenseCol_const< Cell_Type, Data_Type >, 103
 - BArrayDenseRow< Cell_Type, Data_Type >, 105
 - BArrayDenseRow_const< Cell_Type, Data_Type >, 108
 - BArrayVector< Cell_Type, Data_Type >, 115
 - BArrayVector_const< Cell_Type, Data_Type >, 119
 - PhyloCounterData, 209
 - PowerSet< Array_Type, Data_Rule_Type >, 216
 - Rules< Array_Type, Data_Type >, 226
- blengths
 - NodeData, 207
- BOTH
 - CHECK, 56
 - EXISTS, 57
- BROW_TEMPLATE
 - barrayrow-meat.hpp, 262, 263
- BROW_TEMPLATE_ARGS
 - barrayrow-meat.hpp, 262
- BROW_TYPE
 - barrayrow-meat.hpp, 262
- calc
 - PowerSet< Array_Type, Data_Rule_Type >, 216
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 236
- calc_reduced_sequence
 - Geese, 164
- calc_sequence
 - Geese, 165
- Cell
 - Cell< Cell_Type >, 122, 123

- Cell< Cell_Type >, 121
 - ~Cell, 122
 - active, 125
 - add, 123, 124
 - Cell, 122, 123
 - operator Cell_Type, 124
 - operator!=, 124
 - operator=, 124, 125
 - operator==, 125
 - value, 125
 - visited, 125
- Cell_const< Cell_Type >, 126
- change_stats
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 240
- CHECK, 56
 - BOTH, 56
 - NONE, 56
 - ONE, 56
 - TWO, 56
- clear
 - BArray< Cell_Type, Data_Type >, 63
 - BArrayDense< Cell_Type, Data_Type >, 83
 - FreqTable< T >, 158
 - statscounter-meat.hpp, 347
- COL
 - barray-meat-operators.hpp, 247
 - barray-meat.hpp, 250
 - barraydense-meat-operators.hpp, 254
 - barraydense-meat.hpp, 256
- col
 - BArray< Cell_Type, Data_Type >, 63
 - BArrayDense< Cell_Type, Data_Type >, 84
- Col_type
 - typedefs.hpp, 355
- colnames
 - Flock, 152
 - Geese, 165
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 182
- colsum
 - BArrayDense< Cell_Type, Data_Type >, 84
- conditional_prob
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 182
- ConstBArrayRowIter
 - ConstBArrayRowIter< Cell_Type, Data_Type >, 127
- ConstBArrayRowIter< Cell_Type, Data_Type >, 126
 - ~ConstBArrayRowIter, 127
 - Array, 127
 - ConstBArrayRowIter, 127
 - current_col, 128
 - current_row, 128
 - iter, 128
- coordinantes_n_free
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 240
- coordinantes_n_locked
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 241
- coordinates_free
 - PowerSet< Array_Type, Data_Rule_Type >, 218
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 241
- coordinates_locked
 - PowerSet< Array_Type, Data_Rule_Type >, 218
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 241
- count
 - Counter< Array_Type, Data_Type >, 131
- count_all
 - StatsCounter< Array_Type, Data_Type >, 230
- count_current
 - StatsCounter< Array_Type, Data_Type >, 231
- count_fun
 - Counter< Array_Type, Data_Type >, 132
 - counters-meat.hpp, 276
- count_fun_
 - counters-meat.hpp, 281
 - model-meat.hpp, 314
- count_init
 - StatsCounter< Array_Type, Data_Type >, 231
- Counter
 - Counter< Array_Type, Data_Type >, 130
- counter
 - counters-meat.hpp, 282
 - model-meat.hpp, 314
 - statscounter-meat.hpp, 349
- Counter< Array_Type, Data_Type >, 128
 - ~Counter, 130
 - count, 131
 - count_fun, 132
 - Counter, 130
 - data, 132
 - desc, 133
 - get_description, 131
 - get_hasher, 131
 - get_name, 131
 - hasher_fun, 133
 - init, 131
 - init_fun, 133
 - name, 133
 - operator=, 131, 132
 - set_hasher, 132
- counter_
 - counters-meat.hpp, 282
- counter_absdiff
 - Network counters, 26

- counter_co_opt
 - Counting, [17](#)
 - Phylo counters, [48](#)
- counter_cogain
 - Counting, [18](#)
 - Phylo counters, [49](#)
- counter_css_census01
 - network-css.hpp, [289](#)
- counter_css_census02
 - network-css.hpp, [289](#)
- counter_css_census03
 - network-css.hpp, [289](#)
- counter_css_census04
 - network-css.hpp, [290](#)
- counter_css_census05
 - network-css.hpp, [290](#)
- counter_css_census06
 - network-css.hpp, [290](#)
- counter_css_census07
 - network-css.hpp, [290](#)
- counter_css_census08
 - network-css.hpp, [291](#)
- counter_css_census09
 - network-css.hpp, [291](#)
- counter_css_census10
 - network-css.hpp, [291](#)
- counter_css_completely_false_recip_comiss
 - network-css.hpp, [291](#)
- counter_css_completely_false_recip_omiss
 - network-css.hpp, [292](#)
- counter_css_mixed_recip
 - network-css.hpp, [292](#)
- counter_css_partially_false_recip_commi
 - network-css.hpp, [292](#)
- counter_css_partially_false_recip_omiss
 - network-css.hpp, [293](#)
- counter_ctriads
 - Network counters, [27](#)
- counter_degree
 - Network counters, [27](#)
- counter_deleted
 - statscounter-meat.hpp, [350](#)
- counter_density
 - Network counters, [27](#)
- counter_diff
 - Network counters, [28](#)
- counter_edges
 - Network counters, [28](#)
- counter_fixed_effect
 - Network counters, [28](#)
- counter_fun
 - Model< Array_Type, Data_Counter_Type,
 Data_Rule_Type, Data_Rule_Dyn_Type > ,
 [191](#)
- Counter_fun_type
 - typedefs.hpp, [355](#)
- COUNTER_FUNCTION
 - barry.hpp, [270](#)
- counter_gains
 - Counting, [18](#)
 - Phylo counters, [49](#)
- counter_gains_from_0
 - Counting, [18](#)
 - Phylo counters, [49](#)
- counter_gains_k_offspring
 - Counting, [19](#)
 - Phylo counters, [49](#)
- counter_genes_changing
 - Counting, [19](#)
 - Phylo counters, [50](#)
- counter_idegree
 - Network counters, [29](#)
- counter_idegree15
 - Network counters, [29](#)
- counter_isolates
 - Network counters, [29](#), [30](#)
- counter_istar2
 - Network counters, [30](#)
- counter_k_genes_changing
 - Counting, [19](#)
 - Phylo counters, [50](#)
- COUNTER_LAMBDA
 - barry.hpp, [270](#)
- counter_less_than_p_prop_genes_changing
 - Counting, [19](#)
 - Phylo counters, [50](#)
- counter_logit_intercept
 - Network counters, [30](#)
- counter_longest
 - Counting, [20](#)
 - Phylo counters, [50](#)
- counter_loss
 - Counting, [20](#)
 - Phylo counters, [51](#)
- counter_maxfun
 - Counting, [20](#)
 - Phylo counters, [51](#)
- counter_mutual
 - Network counters, [30](#)
- counter_neofun
 - Counting, [20](#)
 - Phylo counters, [51](#)
- counter_neofun_a2b
 - Counting, [21](#)
 - Phylo counters, [51](#)
- counter_nodecov
 - Network counters, [31](#)
- counter_nodeicov
 - Network counters, [31](#)
- counter_nodematch
 - Network counters, [31](#)
- counter_nodecov
 - Network counters, [31](#)
- counter_odegree
 - Network counters, [31](#), [32](#)
- counter_odegree15

- Network counters, [32](#)
- counter_ones
 - Network counters, [32](#)
- counter_ostar2
 - Network counters, [33](#)
- counter_overall_changes
 - Counting, [21](#)
 - Phylo counters, [52](#)
- counter_overall_gains
 - Counting, [21](#)
 - Phylo counters, [52](#)
- counter_overall_gains_from_0
 - Counting, [21](#)
 - Phylo counters, [52](#)
- counter_overall_loss
 - Counting, [22](#)
 - Phylo counters, [52](#)
- counter_pairwise_first_gain
 - Counting, [22](#)
 - Phylo counters, [53](#)
- counter_pairwise_neofun_singlefun
 - Counting, [22](#)
 - Phylo counters, [53](#)
- counter_pairwise_overall_change
 - Counting, [22](#)
 - Phylo counters, [53](#)
- counter_pairwise_preserving
 - Counting, [23](#)
 - Phylo counters, [53](#)
- counter_preserve_pseudogene
 - Counting, [23](#)
 - Phylo counters, [54](#)
- counter_prop_genes_changing
 - Counting, [23](#)
 - Phylo counters, [54](#)
- counter_subfun
 - Counting, [23](#)
 - Phylo counters, [54](#)
- COUNTER_TEMPLATE
 - counters-meat.hpp, [274](#), [276](#), [277](#)
- COUNTER_TEMPLATE_ARGS
 - counters-meat.hpp, [274](#)
- counter_transition
 - Network counters, [33](#)
- counter_transition_formula
 - Network counters, [34](#)
- counter_ttriads
 - Network counters, [34](#)
- COUNTER_TYPE
 - counters-meat.hpp, [275](#)
- Counters
 - Counters< Array_Type, Data_Type >, [134](#), [135](#)
- counters
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [191](#)
 - statscounter-meat.hpp, [350](#)
 - Counters< Array_Type, Data_Type >, [134](#)
 - ~Counters, [135](#)
 - add_counter, [135](#), [136](#)
 - add_hash, [136](#)
 - Counters, [134](#), [135](#)
 - gen_hash, [136](#)
 - get_descriptions, [136](#)
 - get_names, [137](#)
 - operator=, [137](#)
 - operator[], [138](#)
 - size, [138](#)
- counters-meat.hpp
 - add_dims, [281](#)
 - count_fun, [276](#)
 - count_fun_, [281](#)
 - counter, [282](#)
 - counter_, [282](#)
 - COUNTER_TEMPLATE, [274](#), [276](#), [277](#)
 - COUNTER_TEMPLATE_ARGS, [274](#)
 - COUNTER_TYPE, [275](#)
 - COUNTERS_TEMPLATE, [275](#), [277](#)–[279](#)
 - COUNTERS_TEMPLATE_ARGS, [275](#)
 - COUNTERS_TYPE, [275](#)
 - data, [279](#)
 - data_, [282](#)
 - desc, [279](#)
 - desc_, [282](#)
 - for, [279](#)
 - fun, [283](#)
 - fun_, [283](#)
 - hasher, [279](#), [280](#)
 - hasher_fun, [280](#)
 - hasher_fun_, [283](#)
 - i, [283](#)
 - if, [280](#)
 - init_fun, [281](#)
 - init_fun_, [284](#)
 - j, [284](#)
 - name, [281](#)
 - name_, [284](#)
 - noexcept, [284](#)
 - res, [284](#)
 - return, [285](#)
 - TMP_HASHER_CALL, [275](#)
- counters.hpp
 - DEFM_COUNTER, [322](#)
 - DEFM_COUNTER_LAMBDA, [322](#)
 - DEFM_RULE, [323](#)
 - DEFM_RULE_LAMBDA, [323](#)
 - DEFM_RULEDYN_LAMBDA, [323](#)
 - UNI_SUB, [323](#)
- counters_
 - model-meat.hpp, [314](#)
 - statscounter-meat.hpp, [350](#)
- COUNTERS_TEMPLATE
 - counters-meat.hpp, [275](#), [277](#)–[279](#)
- COUNTERS_TEMPLATE_ARGS
 - counters-meat.hpp, [275](#)
- COUNTERS_TYPE

- counters-meat.hpp, 275
- Counting, 13
 - counter_co_opt, 17
 - counter_cogain, 18
 - counter_gains, 18
 - counter_gains_from_0, 18
 - counter_gains_k_offspring, 19
 - counter_genes_changing, 19
 - counter_k_genes_changing, 19
 - counter_less_than_p_prop_genes_changing, 19
 - counter_longest, 20
 - counter_loss, 20
 - counter_maxfun, 20
 - counter_neofun, 20
 - counter_neofun_a2b, 21
 - counter_overall_changes, 21
 - counter_overall_gains, 21
 - counter_overall_gains_from_0, 21
 - counter_overall_loss, 22
 - counter_pairwise_first_gain, 22
 - counter_pairwise_neofun_singlefun, 22
 - counter_pairwise_overall_change, 22
 - counter_pairwise_preserving, 23
 - counter_preserve_pseudogene, 23
 - counter_prop_genes_changing, 23
 - counter_subfun, 23
 - get_last_name, 24
 - IF_MATCHES, 15
 - IF_NOTMATCHES, 15
 - IS_DUPLICATION, 15
 - IS_EITHER, 15
 - IS_SPECIATION, 16
 - MAKE_DEFM_HASHER, 16
 - MAKE_DUPL_VARS, 16
 - PHYLO_CHECK_MISSING, 16
 - PHYLO_COUNTER_LAMBDA, 17
 - PHYLO_RULE_DYN_LAMBDA, 17
- counts
 - Phylo rules, 44
 - PhyloRuleDynData, 212
- Counts_type
 - typedefs.hpp, 355
- covar_sort
 - Phylo rules, 44
- covar_used
 - Phylo rules, 44
- covariates
 - Phylo rules, 44
- CSS_APPEND
 - network-css.hpp, 286
- CSS_CASE_ELSE
 - network-css.hpp, 287
- CSS_CASE_PERCEIVED
 - network-css.hpp, 287
- CSS_CASE_TRUTH
 - network-css.hpp, 287
- CSS_CHECK_SIZE
 - network-css.hpp, 287
- CSS_CHECK_SIZE_INIT
 - network-css.hpp, 287
- CSS_MATCH_TYPE
 - network-css.hpp, 288
- CSS_NET_COUNTER_LAMBDA_INIT
 - network-css.hpp, 288
- CSS_PERCEIVED_CELLS
 - network-css.hpp, 288
- CSS_SIZE
 - network-css.hpp, 288
- CSS_TRUE_CELLS
 - network-css.hpp, 289
- cumprob
 - model-meat.hpp, 315
- current_col
 - ConstBArrayRowIter< Cell_Type, Data_Type >, 128
- current_row
 - ConstBArrayRowIter< Cell_Type, Data_Type >, 128
- current_stats
 - statscounter-meat.hpp, 350
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 241
- D
 - BArray< Cell_Type, Data_Type >, 64
 - BArrayDense< Cell_Type, Data_Type >, 84
 - Rule< Array_Type, Data_Type >, 223
- D_ptr
 - BArray< Cell_Type, Data_Type >, 64
 - BArrayDense< Cell_Type, Data_Type >, 85
- dat
 - Flock, 156
- data
 - Counter< Array_Type, Data_Type >, 132
 - counters-meat.hpp, 279
 - PowerSet< Array_Type, Data_Rule_Type >, 218
- data_
 - counters-meat.hpp, 282
 - model-meat.hpp, 315
- Data_Counter_Type
 - model-meat.hpp, 315
- Data_Rule_Type
 - model-meat.hpp, 315
- default_val
 - BArray< Cell_Type, Data_Type >, 64
 - BArrayDense< Cell_Type, Data_Type >, 85
- DEFM, 139
 - DEFM, 140
 - get_column_major, 140
 - get_ID, 140
 - get_m_order, 140
 - get_model, 141
 - get_n_covars, 141
 - get_n_obs, 141
 - get_n_rows, 141
 - get_n_y, 141

- get_X, 141
- get_X_names, 142
- get_Y, 142
- get_Y_names, 142
- init, 142
- is_motif, 142
- logodds, 142
- motif_census, 143
- print, 143
- set_names, 143
- simulate, 143
- defm, 57
- defm-meat.hpp
 - DEFM_LOOP_ARRAYS, 327
 - DEFM_RANGES, 327
 - keygen_defm, 327
- defm-types.hpp
 - DEFMArray, 328
- DEFM_COUNTER
 - counters.hpp, 322
- DEFM_COUNTER_LAMBDA
 - counters.hpp, 322
- DEFM_LOOP_ARRAYS
 - defm-meat.hpp, 327
- defm_motif_parser
 - formula.hpp, 329
- DEFM_RANGES
 - defm-meat.hpp, 327
- DEFM_RULE
 - counters.hpp, 323
- DEFM_RULE_LAMBDA
 - counters.hpp, 323
- DEFM_RULEDYN_LAMBDA
 - counters.hpp, 323
- DEFMArray
 - defm-types.hpp, 328
- DEFMCounter
 - Phylo rules, 37
- DEFMCounterData, 144
 - Phylo rules, 39
- DEFMCounters
 - Phylo rules, 37
- DEFMData, 144
 - Phylo rules, 39
- DEFMModel
 - Phylo rules, 37
- DEFMRule
 - Phylo rules, 38
- DEFMRuleData, 146
 - Phylo rules, 40
- DEFMRuleDyn
 - Phylo rules, 38
- DEFMRuleDynData, 147
 - Phylo rules, 40
- DEFMRules
 - Phylo rules, 38
- DEFMRulesDyn
 - Phylo rules, 38
- DEFMStatsCounter
 - Phylo rules, 38
- DEFMSupport
 - Phylo rules, 38
- delete_counters
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 192
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 241
- delete_rengine
 - Geese, 172
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 192
- delete_rules
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 192
 - model-meat.hpp, 315
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 242
- delete_rules_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 192
 - model-meat.hpp, 316
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 242
- delete_support
 - Geese, 172
- desc
 - Counter< Array_Type, Data_Type >, 133
 - counters-meat.hpp, 279
- desc_
 - counters-meat.hpp, 282
- directed
 - NetworkData, 200
- duplication
 - Node, 205
 - NodeData, 208
 - PhyloRuleDynData, 212
- else
 - model-meat.hpp, 316
- empty
 - PhyloCounterData, 209
- EmptyArray
 - PowerSet< Array_Type, Data_Rule_Type >, 218
 - statscounter-meat.hpp, 350
- end
 - BArrayDenseCol< Cell_Type, Data_Type >, 101
 - BArrayDenseCol_const< Cell_Type, Data_Type >, 103
 - BArrayDenseRow< Cell_Type, Data_Type >, 105

- BArrayDenseRow_const< Cell_Type, Data_Type >, 108
- BArrayVector< Cell_Type, Data_Type >, 115
- BArrayVector_const< Cell_Type, Data_Type >, 119
- PhyloCounterData, 210
- PowerSet< Array_Type, Data_Rule_Type >, 216
- Progress, 221
- Rules< Array_Type, Data_Type >, 226
- Entries
 - Entries< Cell_Type >, 148
- Entries< Cell_Type >, 148
 - ~Entries, 149
 - Entries, 148
 - resize, 149
 - source, 149
 - target, 149
 - val, 149
- etype_default
 - Geese, 172
- etype_duplication
 - Geese, 172
- etype_either
 - Geese, 172
- etype_speciation
 - Geese, 173
- eval_rules_dyn
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 237
- EXISTS, 57
 - AS_ONE, 57
 - AS_ZERO, 57
 - BOTH, 57
 - NONE, 58
 - ONE, 58
 - TWO, 58
 - UNKNOWN, 58
- f_
 - statscounter-meat.hpp, 351
- first_calc_done
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 192
- Flock, 150
 - ~Flock, 151
 - add_data, 151
 - colnames, 152
 - dat, 156
 - Flock, 151
 - get_counters, 152
 - get_model, 152
 - get_stats_support, 152
 - get_stats_target, 152
 - get_support_fun, 153
 - init, 153
 - initialized, 156
 - likelihood_joint, 153
 - model, 156
 - nfunctions, 156
 - nfuncs, 153
 - nleafs, 154
 - nnodes, 154
 - nterms, 154
 - ntrees, 154
 - operator(), 154
 - parse_polytomies, 155
 - print, 155
 - rengine, 156
 - set_seed, 155
 - support_size, 155
- flush_data
 - BArray< Cell_Type, Data_Type >, 64
- for
 - barray-meat-operators.hpp, 249
 - counters-meat.hpp, 279
 - model-meat.hpp, 304
 - statscounter-meat.hpp, 347
- force_new
 - model-meat.hpp, 316
- formula.hpp
 - defm_motif_parser, 329
- FreqTable
 - FreqTable< T >, 158
- FreqTable< T >, 157
 - ~FreqTable, 158
 - add, 158
 - as_vector, 158
 - clear, 158
 - FreqTable, 158
 - get_data, 159
 - get_index, 159
 - make_hash, 159
 - print, 159
 - reserve, 159
 - size, 160
- fun
 - counters-meat.hpp, 283
- fun_
 - counters-meat.hpp, 283
 - model-meat.hpp, 316
- Geese, 160
 - ~Geese, 164
 - calc_reduced_sequence, 164
 - calc_sequence, 165
 - colnames, 165
 - delete_engine, 172
 - delete_support, 172
 - etype_default, 172
 - etype_duplication, 172
 - etype_either, 172
 - etype_speciation, 173
 - Geese, 163, 164
 - get_annotated_nodes, 165
 - get_annotations, 165
 - get_counters, 165

- get_model, 166
- get_probabilities, 166
- get_rengine, 166
- get_states, 166
- get_support_fun, 166
- inherit_support, 167
- init, 167
- init_node, 167
- initialized, 173
- likelihood, 167
- likelihood_exhaust, 167
- map_to_state_id, 173
- nannotations, 168
- nfunctions, 173
- nfuncs, 168
- nleafs, 168
- nnodes, 168
- nodes, 173
- nterms, 168
- observed_counts, 169
- operator=, 169
- parse_polytomies, 169
- predict, 169
- predict_backend, 170
- predict_exhaust, 170
- predict_exhaust_backend, 170
- predict_sim, 170
- print, 170
- print_nodes, 171
- print_observed_counts, 171
- pset_loc, 173
- reduced_sequence, 174
- sequence, 174
- set_seed, 171
- simulate, 171
- support_size, 171
- update_annotations, 171
- geese, 58
- geese-bones.hpp
 - INITIALIZED, 333
 - keygen_full, 333
 - RULE_FUNCTION, 333
 - vec_diff, 333
 - vector_caster, 334
- geese-types.hpp
 - PhyloArray, 340
 - PhyloCounter, 340
 - PhyloCounters, 340
 - PhyloModel, 340
 - PhyloPowerSet, 340
 - PhyloRule, 341
 - PhyloRuleData, 341
 - PhyloRuleDyn, 341
 - PhyloRules, 341
 - PhyloRulesDyn, 341
 - PhyloStatsCounter, 341
 - PhyloSupport, 342
- gen_hash
 - Counters< Array_Type, Data_Type >, 136
- gen_key
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 183
- get_annotated_nodes
 - Geese, 165
- get_annotations
 - Geese, 165
- get_arrays2support
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 183
- get_cell
 - BArray< Cell_Type, Data_Type >, 64
 - BArrayDense< Cell_Type, Data_Type >, 85
- get_col_vec
 - BArray< Cell_Type, Data_Type >, 65
 - BArrayDense< Cell_Type, Data_Type >, 85, 86
- get_column_major
 - DEFM, 140
- get_counters
 - Flock, 152
 - Geese, 165
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 183
 - PhyloCounterData, 210
 - StatsCounter< Array_Type, Data_Type >, 231
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 237
- get_counts
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 237
- get_current_stats
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 237
- get_data
 - BArrayDense< Cell_Type, Data_Type >, 86
 - FreqTable< T >, 159
 - PowerSet< Array_Type, Data_Rule_Type >, 216
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 238
- get_data_ptr
 - PowerSet< Array_Type, Data_Rule_Type >, 217
- get_description
 - Counter< Array_Type, Data_Type >, 131
 - Rule< Array_Type, Data_Type >, 223
- get_descriptions
 - Counters< Array_Type, Data_Type >, 136
 - Rules< Array_Type, Data_Type >, 226
 - StatsCounter< Array_Type, Data_Type >, 231
- get_entries
 - BArray< Cell_Type, Data_Type >, 65

- BArrayDense< Cell_Type, Data_Type >, 86
- get_hasher
 - Counter< Array_Type, Data_Type >, 131
- get_ID
 - DEFM, 140
- get_index
 - FreqTable< T >, 159
- get_last_name
 - Counting, 24
- get_m_order
 - DEFM, 140
- get_model
 - DEFM, 141
 - Flock, 152
 - Geese, 166
- get_n_covars
 - DEFM, 141
- get_n_obs
 - DEFM, 141
- get_n_rows
 - DEFM, 141
- get_n_y
 - DEFM, 141
- get_name
 - Counter< Array_Type, Data_Type >, 131
 - Rule< Array_Type, Data_Type >, 223
- get_names
 - Counters< Array_Type, Data_Type >, 137
 - Rules< Array_Type, Data_Type >, 227
 - StatsCounter< Array_Type, Data_Type >, 231
- get_norm_const
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 183
- get_parent
 - Node, 203
- get_probabilities
 - Geese, 166
- get_pset
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 183
- get_pset_arrays
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 184
- get_pset_probs
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 184
- get_pset_stats
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 184
- get_rengine
 - Geese, 166
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 184
- get_row_vec
 - BArray< Cell_Type, Data_Type >, 65
 - BArrayDense< Cell_Type, Data_Type >, 86, 87
- get_rules
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 185
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 238
- get_rules_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 185
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 238
- get_seq
 - Rules< Array_Type, Data_Type >, 227
- get_states
 - Geese, 166
- get_stats_support
 - Flock, 152
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 185
- get_stats_target
 - Flock, 152
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 185
- get_support_fun
 - Flock, 153
 - Geese, 166
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 185
- get_X
 - DEFM, 141
- get_X_names
 - DEFM, 142
- get_Y
 - DEFM, 142
- get_Y_names
 - DEFM, 142
- hasher
 - counters-meat.hpp, 279, 280
- hasher_fun
 - Counter< Array_Type, Data_Type >, 133
 - counters-meat.hpp, 280
- hasher_fun_
 - counters-meat.hpp, 283
- Hasher_fun_type
 - typedefs.hpp, 355
- hashes
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 238

- 242
- hashes_initialized
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 242
- i
 - counters-meat.hpp, 283
 - model-meat.hpp, 316
- i_matches
 - model-meat.hpp, 317
- id
 - Node, 205
- idx
 - Phylo rules, 40, 41
- if
 - counters-meat.hpp, 280
 - model-meat.hpp, 304, 305
- IF_MATCHES
 - Counting, 15
- IF_NOTMATCHES
 - Counting, 15
- include/barry/barray-bones.hpp, 245
- include/barry/barray-iterator.hpp, 245
- include/barry/barray-meat-operators.hpp, 246
- include/barry/barray-meat.hpp, 250
- include/barry/barraycell-bones.hpp, 251
- include/barry/barraycell-meat.hpp, 252
- include/barry/barraydense-bones.hpp, 252
- include/barry/barraydense-meat-operators.hpp, 253
- include/barry/barraydense-meat.hpp, 256
- include/barry/barraydensecell-bones.hpp, 257
- include/barry/barraydensecell-meat.hpp, 258
- include/barry/barraydensecol-bones.hpp, 259
- include/barry/barraydenserow-bones.hpp, 260
- include/barry/barrayrow-bones.hpp, 261
- include/barry/barrayrow-meat.hpp, 261
- include/barry/barrayvector-bones.hpp, 263
- include/barry/barrayvector-meat.hpp, 264
- include/barry/barray-configuration.hpp, 264
- include/barry/barray-debug.hpp, 266
- include/barry/barray-macros.hpp, 267
- include/barry/barray.hpp, 268
- include/barry/cell-bones.hpp, 271
- include/barry/cell-meat.hpp, 272
- include/barry/col-bones.hpp, 272
- include/barry/counters-bones.hpp, 272
- include/barry/counters-meat.hpp, 273
- include/barry/counters/network-css.hpp, 285
- include/barry/counters/network.hpp, 293
- include/barry/freqtable.hpp, 300
- include/barry/model-bones.hpp, 301
- include/barry/model-meat.hpp, 301
- include/barry/models/defm.hpp, 320
- include/barry/models/defm/counters.hpp, 321
- include/barry/models/defm/defm-bones.hpp, 326
- include/barry/models/defm/defm-meat.hpp, 326
- include/barry/models/defm/defm-types.hpp, 328
- include/barry/models/defm/formula.hpp, 329
- include/barry/models/geese.hpp, 331
- include/barry/models/geese/counters.hpp, 324
- include/barry/models/geese/flock-bones.hpp, 331
- include/barry/models/geese/flock-meat.hpp, 332
- include/barry/models/geese/geese-bones.hpp, 332
- include/barry/models/geese/geese-meat-constructors.hpp, 334
- include/barry/models/geese/geese-meat-likelihood.hpp, 335
- include/barry/models/geese/geese-meat-likelihood_exhaust.hpp, 336
- include/barry/models/geese/geese-meat-predict.hpp, 336
- include/barry/models/geese/geese-meat-predict_exhaust.hpp, 337
- include/barry/models/geese/geese-meat-predict_sim.hpp, 337
- include/barry/models/geese/geese-meat-simulate.hpp, 338
- include/barry/models/geese/geese-meat.hpp, 338
- include/barry/models/geese/geese-node-bones.hpp, 339
- include/barry/models/geese/geese-types.hpp, 339
- include/barry/powerset-bones.hpp, 342
- include/barry/powerset-meat.hpp, 343
- include/barry/progress.hpp, 343
- include/barry/rules-bones.hpp, 344
- include/barry/rules-meat.hpp, 345
- include/barry/statscounter-bones.hpp, 345
- include/barry/statscounter-meat.hpp, 346
- include/barry/support-bones.hpp, 351
- include/barry/support-meat.hpp, 352
- include/barry/typedefs.hpp, 353
- indices
 - NetCounterData, 198
 - Phylo rules, 44, 45
- inherit_support
 - Geese, 167
- init
 - Counter< Array_Type, Data_Type >, 131
 - DEFM, 142
 - Flock, 153
 - Geese, 167
 - Phylo rules, 45
- init_fun
 - Counter< Array_Type, Data_Type >, 133
 - counters-meat.hpp, 281
- init_fun_
 - counters-meat.hpp, 284
 - model-meat.hpp, 317
- init_node
 - Geese, 167
- init_support
 - PowerSet< Array_Type, Data_Rule_Type >, 217
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 238
- INITIALIZED

- geese-bones.hpp, 333
- initialized
 - Flock, 156
 - Geese, 173
- insert_cell
 - BArray< Cell_Type, Data_Type >, 66
 - BArrayDense< Cell_Type, Data_Type >, 87
 - model-meat.hpp, 305
- is_col
 - BArrayVector< Cell_Type, Data_Type >, 115
 - BArrayVector_const< Cell_Type, Data_Type >, 119
- is_dense
 - BArray< Cell_Type, Data_Type >, 66
 - BArrayDense< Cell_Type, Data_Type >, 87
- IS_DUPLICATION
 - Counting, 15
- IS_EITHER
 - Counting, 15
- is_empty
 - BArray< Cell_Type, Data_Type >, 66
 - BArrayDense< Cell_Type, Data_Type >, 88
- is_leaf
 - Node, 204
- is_motif
 - DEFM, 142
 - Phylo rules, 45
- is_row
 - BArrayVector< Cell_Type, Data_Type >, 115
 - BArrayVector_const< Cell_Type, Data_Type >, 119
- IS_SPECIATION
 - Counting, 16
- is_true
 - Phylo rules, 41
- iter
 - ConstBArrayRowIter< Cell_Type, Data_Type >, 128
- j
 - counters-meat.hpp, 284
 - model-meat.hpp, 317
 - statscounter-meat.hpp, 351
- k
 - model-meat.hpp, 317
- key
 - model-meat.hpp, 317
- keygen_defm
 - defm-meat.hpp, 327
- keygen_full
 - geese-bones.hpp, 333
- keys2support
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 193
- lb
 - PhyloRuleDynData, 213
- likelihood
 - Geese, 167
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 186
- likelihood_
 - model-meat.hpp, 305
- likelihood_exhaust
 - Geese, 167
- likelihood_joint
 - Flock, 153
- likelihood_total
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 187
- locator
 - model-meat.hpp, 317
- logical
 - Phylo rules, 45
- logodds
 - DEFM, 142
- M
 - PowerSet< Array_Type, Data_Rule_Type >, 218
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 242
- MAKE_DEFM_HASHER
 - Counting, 16
- MAKE_DUPL_VARS
 - Counting, 16
- make_hash
 - FreqTable< T >, 159
- Map
 - barry-configuration.hpp, 266
- map_to_state_id
 - Geese, 173
- MapVec_type
 - typedefs.hpp, 356
- max_num_elements
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 243
- Model
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 179
- model
 - Flock, 156
- Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 175
 - ~Model, 180
 - add_array, 180
 - add_counter, 180, 181
 - add_hasher, 181
 - add_rule, 181
 - add_rule_dyn, 181, 182
 - arrays2support, 191
 - colnames, 182

- conditional_prob, 182
- counter_fun, 191
- counters, 191
- delete_counters, 192
- delete_engine, 192
- delete_rules, 192
- delete_rules_dyn, 192
- first_calc_done, 192
- gen_key, 183
- get_arrays2support, 183
- get_counters, 183
- get_norm_const, 183
- get_pset, 183
- get_pset_arrays, 184
- get_pset_probs, 184
- get_pset_stats, 184
- get_engine, 184
- get_rules, 185
- get_rules_dyn, 185
- get_stats_support, 185
- get_stats_target, 185
- get_support_fun, 185
- keys2support, 193
- likelihood, 186
- likelihood_total, 187
- Model, 179
- normalizing_constants, 193
- nrules, 187
- nrules_dyn, 187
- nterms, 187
- operator=, 187
- params_last, 193
- print, 188
- print_stats, 188
- pset_arrays, 193
- pset_probs, 194
- pset_stats, 194
- rengine, 194
- rules, 194
- rules_dyn, 195
- sample, 188
- set_counters, 189
- set_engine, 189
- set_rules, 189
- set_rules_dyn, 189
- set_seed, 189
- set_transform_model, 190
- size, 190
- size_unique, 190
- stats_support, 195
- stats_support_n_arrays, 195
- stats_target, 195
- store_psets, 190
- support_fun, 196
- support_size, 191
- transform_model, 191
- transform_model_fun, 196
- transform_model_term_names, 196
- with_pset, 197
- model-meat.hpp
 - a, 314
 - count_fun_, 314
 - counter, 314
 - counters_, 314
 - cumprob, 315
 - data_, 315
 - Data_Counter_Type, 315
 - Data_Rule_Type, 315
 - delete_rules, 315
 - delete_rules_dyn, 316
 - else, 316
 - for, 304
 - force_new, 316
 - fun_, 316
 - i, 316
 - i_matches, 317
 - if, 304, 305
 - init_fun_, 317
 - insert_cell, 305
 - j, 317
 - k, 317
 - key, 317
 - likelihood_, 305
 - locator, 317
 - MODEL_TEMPLATE, 303, 306–312
 - MODEL_TEMPLATE_ARGS, 304
 - MODEL_TYPE, 304
 - params, 318
 - probs, 318
 - pset_arrays, 318
 - push_back, 312
 - r, 318
 - reserve, 312
 - return, 313, 318
 - rule_fun_, 318
 - rules, 319
 - rules_, 319
 - rules_dyn, 319
 - set_counters, 313
 - set_rules, 313
 - set_rules_dyn, 313
 - size, 313
 - stats, 319
 - stats_support_n_arrays, 319
 - temp_stats, 320
 - tmp_counts, 320
 - update_normalizing_constant, 313
 - urand, 314
- MODEL_TEMPLATE
 - model-meat.hpp, 303, 306–312
- MODEL_TEMPLATE_ARGS
 - model-meat.hpp, 304
- MODEL_TYPE
 - model-meat.hpp, 304
- motif_census
 - DEFM, 143

N

- PowerSet< Array_Type, Data_Rule_Type >, [219](#)
- Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [243](#)
- n_counters
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [243](#)
- n_free
 - PowerSet< Array_Type, Data_Rule_Type >, [219](#)
- n_locked
 - PowerSet< Array_Type, Data_Rule_Type >, [219](#)
- name
 - Counter< Array_Type, Data_Type >, [133](#)
 - counters-meat.hpp, [281](#)
- name_
 - counters-meat.hpp, [284](#)
- nannotations
 - Geese, [168](#)
- narray
 - Node, [205](#)
- ncol
 - BArray< Cell_Type, Data_Type >, [67](#)
 - BArrayDense< Cell_Type, Data_Type >, [88](#)
 - Phylo rules, [41](#)
- NET_C_DATA_IDX
 - network.hpp, [297](#)
- NET_C_DATA_NUM
 - network.hpp, [297](#)
- NetCounter
 - network.hpp, [298](#)
- NetCounterData, [197](#)
 - ~NetCounterData, [198](#)
 - indices, [198](#)
 - NetCounterData, [198](#)
 - numbers, [198](#)
- NetCounters
 - network.hpp, [298](#)
- NetModel
 - network.hpp, [299](#)
- NetRule
 - network.hpp, [299](#)
- NetRules
 - network.hpp, [299](#)
- NetStatsCounter
 - network.hpp, [299](#)
- NetSupport
 - network.hpp, [299](#)
- Network
 - network.hpp, [299](#)
- Network counters, [24](#)
 - counter_absdiff, [26](#)
 - counter_ctriads, [27](#)
 - counter_degree, [27](#)
 - counter_density, [27](#)
 - counter_diff, [28](#)
 - counter_edges, [28](#)
 - counter_fixed_effect, [28](#)
 - counter_idegree, [29](#)
 - counter_idegree15, [29](#)
 - counter_isolates, [29](#), [30](#)
 - counter_istar2, [30](#)
 - counter_logit_intercept, [30](#)
 - counter_mutual, [30](#)
 - counter_nodecov, [31](#)
 - counter_nodeicov, [31](#)
 - counter_nodematch, [31](#)
 - counter_nodeocov, [31](#)
 - counter_odegree, [31](#), [32](#)
 - counter_odegree15, [32](#)
 - counter_ones, [32](#)
 - counter_ostar2, [33](#)
 - counter_transition, [33](#)
 - counter_transition_formula, [34](#)
 - counter_ttriads, [34](#)
 - NETWORK_COUNTER, [34](#)
 - rules_dont_become_zero, [34](#)
 - rules_markov_fixed, [35](#)
- network-css.hpp
 - counter_css_census01, [289](#)
 - counter_css_census02, [289](#)
 - counter_css_census03, [289](#)
 - counter_css_census04, [290](#)
 - counter_css_census05, [290](#)
 - counter_css_census06, [290](#)
 - counter_css_census07, [290](#)
 - counter_css_census08, [291](#)
 - counter_css_census09, [291](#)
 - counter_css_census10, [291](#)
 - counter_css_completely_false_recip_comiss, [291](#)
 - counter_css_completely_false_recip_omiss, [292](#)
 - counter_css_mixed_recip, [292](#)
 - counter_css_partially_false_recip_commi, [292](#)
 - counter_css_partially_false_recip_omiss, [293](#)
 - CSS_APPEND, [286](#)
 - CSS_CASE_ELSE, [287](#)
 - CSS_CASE_PERCEIVED, [287](#)
 - CSS_CASE_TRUTH, [287](#)
 - CSS_CHECK_SIZE, [287](#)
 - CSS_CHECK_SIZE_INIT, [287](#)
 - CSS_MATCH_TYPE, [288](#)
 - CSS_NET_COUNTER_LAMBDA_INIT, [288](#)
 - CSS_PERCEIVED_CELLS, [288](#)
 - CSS_SIZE, [288](#)
 - CSS_TRUE_CELLS, [289](#)
- network.hpp
 - BARRY_ZERO_NETWORK, [296](#)
 - BARRY_ZERO_NETWORK_DENSE, [296](#)
 - NET_C_DATA_IDX, [297](#)
 - NET_C_DATA_NUM, [297](#)
 - NetCounter, [298](#)
 - NetCounters, [298](#)
 - NetModel, [299](#)
 - NetRule, [299](#)
 - NetRules, [299](#)

- NetStatsCounter, 299
- NetSupport, 299
- Network, 299
- NETWORK_COUNTER, 297
- NETWORK_COUNTER_LAMBDA, 297
- NETWORK_RULE, 297
- NETWORK_RULE_LAMBDA, 298
- NetworkDense, 300
- NETWORKDENSE_COUNTER_LAMBDA, 298
- rules_zerodiag, 300
- NETWORK_COUNTER
 - Network counters, 34
 - network.hpp, 297
- NETWORK_COUNTER_LAMBDA
 - network.hpp, 297
- NETWORK_RULE
 - network.hpp, 297
- NETWORK_RULE_LAMBDA
 - network.hpp, 298
- NetworkData, 199
 - ~NetworkData, 200
 - directed, 200
 - NetworkData, 199, 200
 - vertex_attr, 200
- NetworkDense
 - network.hpp, 300
- NETWORKDENSE_COUNTER_LAMBDA
 - network.hpp, 298
- next
 - Progress, 221
- nfunctions
 - Flock, 156
 - Geese, 173
- nfuncs
 - Flock, 153
 - Geese, 168
- nleaves
 - Flock, 154
 - Geese, 168
- nnodes
 - Flock, 154
 - Geese, 168
- nnozero
 - BArray< Cell_Type, Data_Type >, 67
 - BArrayDense< Cell_Type, Data_Type >, 88
- Node, 201
 - ~Node, 203
 - annotations, 204
 - array, 204
 - arrays, 204
 - duplication, 205
 - get_parent, 203
 - id, 205
 - is_leaf, 204
 - narray, 205
 - Node, 202, 203
 - noffspring, 204
 - offspring, 205
 - ord, 205
 - parent, 206
 - probability, 206
 - subtree_prob, 206
 - visited, 206
- NodeData, 207
 - blengths, 207
 - duplication, 208
 - NodeData, 207
 - states, 208
- nodes
 - Geese, 173
- noexcept
 - counters-meat.hpp, 284
- noffspring
 - Node, 204
- NONE
 - CHECK, 56
 - EXISTS, 58
- normalizing_constants
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 193
- nrow
 - BArray< Cell_Type, Data_Type >, 67
 - BArrayDense< Cell_Type, Data_Type >, 88
 - Phylo rules, 41
- nrules
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 187
- nrules_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 187
- nterms
 - Flock, 154
 - Geese, 168
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 187
- ntrees
 - Flock, 154
- num
 - Phylo rules, 41, 42
- numbers
 - NetCounterData, 198
 - Phylo rules, 45, 46
- obs_start
 - Phylo rules, 46
- observed_counts
 - Geese, 169
- offspring
 - Node, 205
- ONE
 - CHECK, 56
 - EXISTS, 58
- operator BArrayRow< Cell_Type, Data_Type >

- BArrayRow< Cell_Type, Data_Type >, 110
- operator BArrayRow_const< Cell_Type, Data_Type >
 - BArrayRow_const< Cell_Type, Data_Type >, 112
- operator Cell_Type
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayCell_const< Cell_Type, Data_Type >, 77
 - BArrayDenseCell< Cell_Type, Data_Type >, 97
 - Cell< Cell_Type >, 124
- operator std::vector< Cell_Type >
 - BArrayVector< Cell_Type, Data_Type >, 116
 - BArrayVector_const< Cell_Type, Data_Type >, 119
- operator!=
 - BArrayCell_const< Cell_Type, Data_Type >, 77
 - BArrayRow_const< Cell_Type, Data_Type >, 112
 - BArrayVector_const< Cell_Type, Data_Type >, 119
 - Cell< Cell_Type >, 124
- operator<
 - BArrayCell_const< Cell_Type, Data_Type >, 77
 - BArrayRow_const< Cell_Type, Data_Type >, 112
 - BArrayVector_const< Cell_Type, Data_Type >, 120
- operator<=
 - BArrayCell_const< Cell_Type, Data_Type >, 78
 - BArrayRow_const< Cell_Type, Data_Type >, 113
 - BArrayVector_const< Cell_Type, Data_Type >, 120
- operator>
 - BArrayCell_const< Cell_Type, Data_Type >, 78
 - BArrayRow_const< Cell_Type, Data_Type >, 113
 - BArrayVector_const< Cell_Type, Data_Type >, 120
- operator>=
 - BArrayCell_const< Cell_Type, Data_Type >, 78
 - BArrayRow_const< Cell_Type, Data_Type >, 113
 - BArrayVector_const< Cell_Type, Data_Type >, 120
- operator*=
 - BArray< Cell_Type, Data_Type >, 67
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayDense< Cell_Type, Data_Type >, 89
 - BArrayDenseCell< Cell_Type, Data_Type >, 97
 - BArrayRow< Cell_Type, Data_Type >, 110
 - BArrayVector< Cell_Type, Data_Type >, 116
- operator()
 - BArray< Cell_Type, Data_Type >, 67
 - barray-meat-operators.hpp, 249
 - BArrayDense< Cell_Type, Data_Type >, 88, 89
 - BArrayDenseCol< Cell_Type, Data_Type >, 101
 - BArrayDenseCol_const< Cell_Type, Data_Type >, 103
 - BArrayDenseRow< Cell_Type, Data_Type >, 106
 - BArrayDenseRow_const< Cell_Type, Data_Type >, 108
 - Flock, 154
 - Phylo rules, 42
 - PhyloCounterData, 210
 - PhyloRuleDynData, 212
 - Rule< Array_Type, Data_Type >, 224
 - Rules< Array_Type, Data_Type >, 227
 - vecHasher< T >, 244
- operator+=
 - BArray< Cell_Type, Data_Type >, 68
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayDense< Cell_Type, Data_Type >, 89
 - BArrayDenseCell< Cell_Type, Data_Type >, 98
 - BArrayRow< Cell_Type, Data_Type >, 110
 - BArrayVector< Cell_Type, Data_Type >, 116
- operator-=
 - BArray< Cell_Type, Data_Type >, 68
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayDense< Cell_Type, Data_Type >, 90
 - BArrayDenseCell< Cell_Type, Data_Type >, 98
 - BArrayRow< Cell_Type, Data_Type >, 110
 - BArrayVector< Cell_Type, Data_Type >, 116
- operator/=
 - BArray< Cell_Type, Data_Type >, 69
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayDense< Cell_Type, Data_Type >, 90
 - BArrayDenseCell< Cell_Type, Data_Type >, 98
 - BArrayRow< Cell_Type, Data_Type >, 111
 - BArrayVector< Cell_Type, Data_Type >, 116
- operator=
 - BArray< Cell_Type, Data_Type >, 69
 - BArrayCell< Cell_Type, Data_Type >, 75
 - BArrayDense< Cell_Type, Data_Type >, 90, 91
 - BArrayDenseCell< Cell_Type, Data_Type >, 98
 - BArrayRow< Cell_Type, Data_Type >, 111
 - BArrayVector< Cell_Type, Data_Type >, 117
 - Cell< Cell_Type >, 124, 125
 - Counter< Array_Type, Data_Type >, 131, 132
 - Counters< Array_Type, Data_Type >, 137
 - Geese, 169
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 187
 - Rules< Array_Type, Data_Type >, 228
- operator==
 - BArray< Cell_Type, Data_Type >, 69
 - BArrayCell< Cell_Type, Data_Type >, 76
 - BArrayCell_const< Cell_Type, Data_Type >, 78
 - BArrayDense< Cell_Type, Data_Type >, 91
 - BArrayDenseCell< Cell_Type, Data_Type >, 99
 - BArrayRow< Cell_Type, Data_Type >, 111
 - BArrayRow_const< Cell_Type, Data_Type >, 113
 - BArrayVector< Cell_Type, Data_Type >, 117
 - BArrayVector_const< Cell_Type, Data_Type >, 120
 - Cell< Cell_Type >, 125
- operator[]
 - Counters< Array_Type, Data_Type >, 138
 - PhyloCounterData, 210
 - PowerSet< Array_Type, Data_Rule_Type >, 217
- ord
 - Node, 205

- out_of_range
 - BArray< Cell_Type, Data_Type >, 69
 - BArrayDense< Cell_Type, Data_Type >, 91
- params
 - model-meat.hpp, 318
- params_last
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 193
- parent
 - Node, 206
- parse_polytomies
 - Flock, 155
 - Geese, 169
- Phylo counters, 47
 - counter_co_opt, 48
 - counter_cogain, 49
 - counter_gains, 49
 - counter_gains_from_0, 49
 - counter_gains_k_offspring, 49
 - counter_genes_changing, 50
 - counter_k_genes_changing, 50
 - counter_less_than_p_prop_genes_changing, 50
 - counter_longest, 50
 - counter_loss, 51
 - counter_maxfun, 51
 - counter_neofun, 51
 - counter_neofun_a2b, 51
 - counter_overall_changes, 52
 - counter_overall_gains, 52
 - counter_overall_gains_from_0, 52
 - counter_overall_loss, 52
 - counter_pairwise_first_gain, 53
 - counter_pairwise_neofun_singlefun, 53
 - counter_pairwise_overall_change, 53
 - counter_pairwise_preserving, 53
 - counter_preserve_pseudogene, 54
 - counter_prop_genes_changing, 54
 - counter_subfun, 54
- Phylo rules, 35
 - ~DEFMCounterData, 43
 - ~DEFMData, 43
 - ~DEFMRuleDynData, 43
 - array, 44
 - at, 39
 - counts, 44
 - covar_sort, 44
 - covar_used, 44
 - covariates, 44
 - DEFMCounter, 37
 - DEFMCounterData, 39
 - DEFMCounters, 37
 - DEFMData, 39
 - DEFMModel, 37
 - DEFMRule, 38
 - DEFMRuleData, 40
 - DEFMRuleDyn, 38
 - DEFMRuleDynData, 40
 - DEFMRules, 38
 - DEFMRulesDyn, 38
 - DEFMStatsCounter, 38
 - DEFMSupport, 38
 - idx, 40, 41
 - indices, 44, 45
 - init, 45
 - is_motif, 45
 - is_true, 41
 - logical, 45
 - ncol, 41
 - nrow, 41
 - num, 41, 42
 - numbers, 45, 46
 - obs_start, 46
 - operator(), 42
 - print, 42
 - rule_dyn_limit_changes, 42
 - X_ncol, 46
 - X_nrow, 46
- PHYLO_CHECK_MISSING
 - Counting, 16
- PHYLO_COUNTER_LAMBDA
 - Counting, 17
- PHYLO_RULE_DYN_LAMBDA
 - Counting, 17
- PhyloArray
 - geese-types.hpp, 340
- PhyloCounter
 - geese-types.hpp, 340
- PhyloCounterData, 208
 - at, 209
 - begin, 209
 - empty, 209
 - end, 210
 - get_counters, 210
 - operator(), 210
 - operator[], 210
 - PhyloCounterData, 209
 - push_back, 210
 - reserve, 210
 - shrink_to_fit, 211
 - size, 211
- PhyloCounters
 - geese-types.hpp, 340
- PhyloModel
 - geese-types.hpp, 340
- PhyloPowerSet
 - geese-types.hpp, 340
- PhyloRule
 - geese-types.hpp, 341
- PhyloRuleData
 - geese-types.hpp, 341
- PhyloRuleDyn
 - geese-types.hpp, 341
- PhyloRuleDynData, 211
 - ~PhyloRuleDynData, 212
 - counts, 212

- duplication, [212](#)
 - lb, [213](#)
 - operator(), [212](#)
 - PhyloRuleDynData, [212](#)
 - pos, [213](#)
 - ub, [213](#)
- PhyloRules
 - geese-types.hpp, [341](#)
- PhyloRulesDyn
 - geese-types.hpp, [341](#)
- PhyloStatsCounter
 - geese-types.hpp, [341](#)
- PhyloSupport
 - geese-types.hpp, [342](#)
- POS
 - barraydense-meat-operators.hpp, [254](#)
 - barraydense-meat.hpp, [256](#)
 - barraydensecell-bones.hpp, [258](#)
 - barraydensecell-meat.hpp, [258](#)
 - barraydensecol-bones.hpp, [259](#)
 - barraydenserow-bones.hpp, [261](#)
- pos
 - PhyloRuleDynData, [213](#)
- POS_N
 - barraydense-meat-operators.hpp, [254](#)
 - barraydense-meat.hpp, [257](#)
 - barraydensecol-bones.hpp, [259](#)
 - barraydenserow-bones.hpp, [261](#)
- PowerSet
 - PowerSet< Array_Type, Data_Rule_Type >, [215](#)
- PowerSet< Array_Type, Data_Rule_Type >, [213](#)
 - ~PowerSet, [215](#)
 - add_rule, [215](#), [216](#)
 - begin, [216](#)
 - calc, [216](#)
 - coordinates_free, [218](#)
 - coordinates_locked, [218](#)
 - data, [218](#)
 - EmptyArray, [218](#)
 - end, [216](#)
 - get_data, [216](#)
 - get_data_ptr, [217](#)
 - init_support, [217](#)
 - M, [218](#)
 - N, [219](#)
 - n_free, [219](#)
 - n_locked, [219](#)
 - operator[], [217](#)
 - PowerSet, [215](#)
 - reset, [217](#)
 - rules, [219](#)
 - rules_deleted, [219](#)
 - size, [217](#)
- predict
 - Geese, [169](#)
- predict_backend
 - Geese, [170](#)
- predict_exhaust
 - Geese, [170](#)
- predict_exhaust_backend
 - Geese, [170](#)
- predict_sim
 - Geese, [170](#)
- print
 - BArray< Cell_Type, Data_Type >, [69](#)
 - BArrayDense< Cell_Type, Data_Type >, [91](#)
 - DEFM, [143](#)
 - Flock, [155](#)
 - FreqTable< T >, [159](#)
 - Geese, [170](#)
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [188](#)
 - Phylo rules, [42](#)
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [239](#)
- print_n
 - BArray< Cell_Type, Data_Type >, [70](#)
- print_nodes
 - Geese, [171](#)
- print_observed_counts
 - Geese, [171](#)
- print_stats
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [188](#)
- printf_barry
 - barry-configuration.hpp, [265](#)
- probability
 - Node, [206](#)
- probs
 - model-meat.hpp, [318](#)
- Progress, [220](#)
 - ~Progress, [220](#)
 - end, [221](#)
 - next, [221](#)
 - Progress, [220](#)
- progress.hpp
 - BARRY_PROGRESS_BAR_WIDTH, [344](#)
- pset_arrays
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [193](#)
 - model-meat.hpp, [318](#)
- pset_loc
 - Geese, [173](#)
- pset_probs
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [194](#)
- pset_stats
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [194](#)
- push_back

- model-meat.hpp, 312
- PhyloCounterData, 210
- r
 - model-meat.hpp, 318
- README.md, 358
- reduced_sequence
 - Geese, 174
- rengine
 - Flock, 156
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 194
- res
 - counters-meat.hpp, 284
- reserve
 - BArray< Cell_Type, Data_Type >, 70
 - BArrayDense< Cell_Type, Data_Type >, 91
 - FreqTable< T >, 159
 - model-meat.hpp, 312
 - PhyloCounterData, 210
- reset
 - PowerSet< Array_Type, Data_Rule_Type >, 217
- reset_array
 - StatsCounter< Array_Type, Data_Type >, 231
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 239
- resize
 - BArray< Cell_Type, Data_Type >, 70
 - BArrayDense< Cell_Type, Data_Type >, 92
 - Entries< Cell_Type >, 149
 - statscounter-meat.hpp, 348
- return
 - counters-meat.hpp, 285
 - model-meat.hpp, 313, 318
 - statscounter-meat.hpp, 351
- rhs
 - barray-meat-operators.hpp, 249
- rm_cell
 - BArray< Cell_Type, Data_Type >, 70
 - BArrayDense< Cell_Type, Data_Type >, 92
- ROW
 - barray-meat-operators.hpp, 247
 - barray-meat.hpp, 251
 - barraydense-meat-operators.hpp, 254
 - barraydense-meat.hpp, 257
- row
 - BArray< Cell_Type, Data_Type >, 70
 - BArrayDense< Cell_Type, Data_Type >, 92
- Row_type
 - typedefs.hpp, 356
- rowsum
 - BArrayDense< Cell_Type, Data_Type >, 92
- Rule
 - Rule< Array_Type, Data_Type >, 222
- Rule< Array_Type, Data_Type >, 221
 - ~Rule, 222
 - D, 223
 - get_description, 223
 - get_name, 223
 - operator(), 224
 - Rule, 222
- rule_dyn_limit_changes
 - Phylo rules, 42
- rule_fun_
 - model-meat.hpp, 318
- rule_fun_default
 - rules-bones.hpp, 344
- Rule_fun_type
 - typedefs.hpp, 356
- RULE_FUNCTION
 - barry.hpp, 271
 - geese-bones.hpp, 333
- RULE_LAMBDA
 - barry.hpp, 271
- Rules
 - Rules< Array_Type, Data_Type >, 225
- rules
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 194
 - model-meat.hpp, 319
 - PowerSet< Array_Type, Data_Rule_Type >, 219
 - Rules< Array_Type, Data_Type >, 224
 - ~Rules, 225
 - add_rule, 226
 - begin, 226
 - end, 226
 - get_descriptions, 226
 - get_names, 227
 - get_seq, 227
 - operator(), 227
 - operator=, 228
 - Rules, 225
 - size, 228
- rules-bones.hpp
 - rule_fun_default, 344
- rules_
 - model-meat.hpp, 319
- rules_deleted
 - PowerSet< Array_Type, Data_Rule_Type >, 219
- rules_dont_become_zero
 - Network counters, 34
- rules_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 195
 - model-meat.hpp, 319
- rules_markov_fixed
 - Network counters, 35
- rules_zerodiag
 - network.hpp, 300
- sample
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, 188

- sequence
 - Geese, [174](#)
- set_counters
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [189](#)
 - model-meat.hpp, [313](#)
 - StatsCounter< Array_Type, Data_Type >, [232](#)
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [239](#)
- set_data
 - BArray< Cell_Type, Data_Type >, [71](#)
 - BArrayDense< Cell_Type, Data_Type >, [93](#)
- set_hasher
 - Counter< Array_Type, Data_Type >, [132](#)
- set_names
 - DEFM, [143](#)
- set_engine
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [189](#)
- set_rules
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [189](#)
 - model-meat.hpp, [313](#)
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [240](#)
- set_rules_dyn
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [189](#)
 - model-meat.hpp, [313](#)
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [240](#)
- set_seed
 - Flock, [155](#)
 - Geese, [171](#)
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [189](#)
- set_transform_model
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [190](#)
- shrink_to_fit
 - PhyloCounterData, [211](#)
- simulate
 - DEFM, [143](#)
 - Geese, [171](#)
- size
 - BArrayDenseCol< Cell_Type, Data_Type >, [101](#)
 - BArrayDenseCol_const< Cell_Type, Data_Type >, [104](#)
 - BArrayDenseRow< Cell_Type, Data_Type >, [106](#)
 - BArrayDenseRow_const< Cell_Type, Data_Type >, [108](#)
 - BArrayVector< Cell_Type, Data_Type >, [117](#)
 - BArrayVector_const< Cell_Type, Data_Type >, [121](#)
 - Counters< Array_Type, Data_Type >, [138](#)
 - FreqTable< T >, [160](#)
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [190](#)
 - model-meat.hpp, [313](#)
 - PhyloCounterData, [211](#)
 - PowerSet< Array_Type, Data_Rule_Type >, [217](#)
 - Rules< Array_Type, Data_Type >, [228](#)
 - StatsCounter< Array_Type, Data_Type >, [232](#)
- size_unique
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [190](#)
- sort_array
 - typedefs.hpp, [356](#)
- source
 - Entries< Cell_Type >, [149](#)
- states
 - NodeData, [208](#)
 - Statistical Models, [24](#)
- stats
 - model-meat.hpp, [319](#)
- stats_support
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [195](#)
- stats_support_n_arrays
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [195](#)
 - model-meat.hpp, [319](#)
- stats_target
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [195](#)
- StatsCounter
 - StatsCounter< Array_Type, Data_Type >, [229](#), [230](#)
- StatsCounter< Array_Type, Data_Type >, [228](#)
 - ~StatsCounter, [230](#)
 - add_counter, [230](#)
 - count_all, [230](#)
 - count_current, [231](#)
 - count_init, [231](#)
 - get_counters, [231](#)
 - get_descriptions, [231](#)
 - get_names, [231](#)
 - reset_array, [231](#)
 - set_counters, [232](#)
 - size, [232](#)
 - StatsCounter, [229](#), [230](#)
- statscounter-meat.hpp

- clear, [347](#)
- counter, [349](#)
- counter_deleted, [350](#)
- counters, [350](#)
- counters_, [350](#)
- current_stats, [350](#)
- EmptyArray, [350](#)
- f_, [351](#)
- for, [347](#)
- j, [351](#)
- resize, [348](#)
- return, [351](#)
- STATSCOUNTER_TEMPLATE, [347–349](#)
- STATSCOUNTER_TEMPLATE_ARGS, [347](#)
- STATSCOUNTER_TYPE, [347](#)
- STATSCOUNTER_TEMPLATE
 - statscounter-meat.hpp, [347–349](#)
- STATSCOUNTER_TEMPLATE_ARGS
 - statscounter-meat.hpp, [347](#)
- STATSCOUNTER_TYPE
 - statscounter-meat.hpp, [347](#)
- store_psets
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [190](#)
- subtree_prob
 - Node, [206](#)
- Support
 - Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [234, 235](#)
- Support< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [232](#)
- ~Support, [235](#)
- add_counter, [235](#)
- add_rule, [235, 236](#)
- add_rule_dyn, [236](#)
- calc, [236](#)
- change_stats, [240](#)
- coordiantes_n_free, [240](#)
- coordiantes_n_locked, [241](#)
- coordinates_free, [241](#)
- coordinates_locked, [241](#)
- current_stats, [241](#)
- delete_counters, [241](#)
- delete_rules, [242](#)
- delete_rules_dyn, [242](#)
- eval_rules_dyn, [237](#)
- get_counters, [237](#)
- get_counts, [237](#)
- get_current_stats, [237](#)
- get_data, [238](#)
- get_rules, [238](#)
- get_rules_dyn, [238](#)
- hashes, [242](#)
- hashes_initialized, [242](#)
- init_support, [238](#)
- M, [242](#)
- max_num_elements, [243](#)
- N, [243](#)
- n_counters, [243](#)
- print, [239](#)
- reset_array, [239](#)
- set_counters, [239](#)
- set_rules, [240](#)
- set_rules_dyn, [240](#)
- Support, [234, 235](#)
- support-meat.hpp
 - BARRY_SUPPORT_MEAT_HPP, [352](#)
- support_fun
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [196](#)
- support_size
 - Flock, [155](#)
 - Geese, [171](#)
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [191](#)
- swap_cells
 - BArray< Cell_Type, Data_Type >, [71](#)
 - BArrayDense< Cell_Type, Data_Type >, [93](#)
- swap_cols
 - BArray< Cell_Type, Data_Type >, [71](#)
 - BArrayDense< Cell_Type, Data_Type >, [93](#)
- swap_rows
 - BArray< Cell_Type, Data_Type >, [71](#)
 - BArrayDense< Cell_Type, Data_Type >, [93](#)
- target
 - Entries< Cell_Type >, [149](#)
- temp_stats
 - model-meat.hpp, [320](#)
- this
 - barray-meat-operators.hpp, [250](#)
- tmp_counts
 - model-meat.hpp, [320](#)
- TMP_HASHER_CALL
 - counters-meat.hpp, [275](#)
- toggle_cell
 - BArray< Cell_Type, Data_Type >, [72](#)
 - BArrayDense< Cell_Type, Data_Type >, [94](#)
- toggle_lock
 - BArray< Cell_Type, Data_Type >, [72](#)
 - BArrayDense< Cell_Type, Data_Type >, [94](#)
- transform_model
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [191](#)
- transform_model_fun
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [196](#)
- transform_model_term_names
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [196](#)

- transpose
 - BArray< Cell_Type, Data_Type >, [72](#)
 - BArrayDense< Cell_Type, Data_Type >, [94](#)
- TWO
 - CHECK, [56](#)
 - EXISTS, [58](#)
- typedefs.hpp
 - Col_type, [355](#)
 - Counter_fun_type, [355](#)
 - Counts_type, [355](#)
 - Hasher_fun_type, [355](#)
 - MapVec_type, [356](#)
 - Row_type, [356](#)
 - Rule_fun_type, [356](#)
 - sort_array, [356](#)
 - vec_equal, [357](#)
 - vec_equal_approx, [357](#)
 - vec_inner_prod, [357](#), [358](#)
- ub
 - PhyloRuleDynData, [213](#)
- UNKNOWN
 - EXISTS, [58](#)
- UNI_SUB
 - counters.hpp, [323](#)
- update_annotations
 - Geese, [171](#)
- update_normalizing_constant
 - model-meat.hpp, [313](#)
- urand
 - model-meat.hpp, [314](#)
- val
 - Entries< Cell_Type >, [149](#)
- value
 - Cell< Cell_Type >, [125](#)
- vec_diff
 - geese-bones.hpp, [333](#)
- vec_equal
 - typedefs.hpp, [357](#)
- vec_equal_approx
 - typedefs.hpp, [357](#)
- vec_inner_prod
 - typedefs.hpp, [357](#), [358](#)
- vecHasher< T >, [243](#)
 - operator(), [244](#)
- vector_caster
 - geese-bones.hpp, [334](#)
- vertex_attr
 - NetworkData, [200](#)
- visited
 - BArray< Cell_Type, Data_Type >, [73](#)
 - BArrayDense< Cell_Type, Data_Type >, [96](#)
 - Cell< Cell_Type >, [125](#)
 - Node, [206](#)
- with_pset
 - Model< Array_Type, Data_Counter_Type, Data_Rule_Type, Data_Rule_Dyn_Type >, [197](#)
- X_ncol
 - Phylo rules, [46](#)
- X_nrow
 - Phylo rules, [46](#)
- ZERO_CELL
 - barraydense-meat.hpp, [257](#)
 - barraydensecol-bones.hpp, [260](#)
 - barraydenserow-bones.hpp, [261](#)
- zero_col
 - BArray< Cell_Type, Data_Type >, [72](#)
 - BArrayDense< Cell_Type, Data_Type >, [94](#)
- zero_row
 - BArray< Cell_Type, Data_Type >, [72](#)
 - BArrayDense< Cell_Type, Data_Type >, [94](#)