

# tcplfit2

January 7, 2020

**Type** Package

**Title** Performs Concentration-Response Modeling on HTS or transcriptomics data

**Version** 0.1.0

**Author** Thomas Sheffield

**Maintainer** Richard Judson <judson.richard@epa.gov>

**Description** This package performs the basic concentration response curve fitting used in the tcpl package. It is a substitute for the original tcplFit function (and sub-functions) and allows a wider variety of concentration-response models. All of the models included in the BMDEExpress package are now part of this package, and the output includes a calculation of the bmd (Benchmark Dose or concentration) value.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.0.2

**Suggests** knitr,  
rmarkdown

**VignetteBuilder** knitr

**Imports** stats,  
future,  
methods,  
numDeriv,  
RColorBrewer,  
future.apply,  
stringr,  
stringi

## R topics documented:

acgnlsobj . . . . .	2
acy . . . . .	3
bmdbounds . . . . .	4

bmdobj	5
cnst	6
concRespCore	7
concRespPlot	9
exp2	10
exp3	10
exp4	11
exp5	11
fitcnst	12
fitexp2	12
fitexp3	13
fitexp4	14
fitexp5	15
fitgnls	16
fithill	17
fitpoly1	18
fitpoly2	19
fitpow	20
gnls	21
gnlsderivobj	21
hillfn	22
hitcont	22
hitcontinner	23
hitlogic	24
hitloginner	24
loggnls	25
loghill	26
mc3	26
nestselect	27
poly1	28
poly2	28
pow	29
tcplFit2.test	29
tcplFit2.test.mc3	29
tcplfit2_core	30
tcplObj	31
toplikelihood	32

<b>Index</b>	<b>34</b>
--------------	-----------

---

acgnlsobj	<i>AC GNLS Objective Function</i>
-----------	-----------------------------------

---

## Description

GNLS objective function set to y for gnls solver.

Usage

acgnlsobj(x, y, tp, ga, p, la, q)

Arguments

- x Concentration.
- y Desired activity level.
- tp Top.
- ga Gain AC50.
- p Gain power.
- la Loss AC50.
- q Loss power.

Value

Difference between GNLS model repsone at x and y.

---

acy	<i>Activity Concentration y</i>
-----	---------------------------------

---

Description

Returns concentration at which model equals y.

Usage

```
acy(  
  y,  
  modpars,  
  type = "hill",  
  returntop = F,  
  returntoploc = F,  
  getloss = F,  
  verbose = F  
)
```

Arguments

- y Activity value at which the concentration is desired. y should be less than the model's top, if there is one, and greater than zero.
- modpars List of named model parameters. Model parameters can include: "a", "b", "ga", "la", "p", "q", "tp". ga and la should NOT be in log units.
- type Model type; must be one of: "exp1", "exp2", "exp3", "exp4", "gnls", "hill", "poly1", "poly2", "pow".

returntop	When TRUE, returns actual top value for gnls. Has no effect for other models.
returntoploc	When TRUE, returns concentration of top for gnls. Has no effect for other models. If top location can't be found, NA is returned.
getloss	When TRUE, returns value on loss side of curve for gnls. Has no effect for other models.
verbose	When TRUE, shows warnings.

### Details

Mathematically inverts model functions of the given type, except for gnls, which is numerically inverted. gnls returns NA when  $y > tp$ . Other options return the actual top (as opposed to theoretical tp) and top location for gnls model. gnls model defaults to giving concentration on gain side. Only one of getloss, returntop, and returntoploc should be TRUE at a time. If top location solution fails for gnls, top is set to tp. Returns NA if gnls numerical solver fails.

### Value

Ouputs concentration at activity y, or gnls top or top concentration, when applicable.

### Examples

```
acy(1, list(ga = 10, tp = 2, p = 3), type = "hill")
acy(1, list(ga = .1, tp = 2, p = 3, q = 3, la = 10), type = "gnls")
acy(1, list(ga = .1, tp = 2, p = 3, q = 3, la = 10), type = "gnls", getloss = TRUE)
acy(1, list(ga = .1, tp = 2, p = 3, q = 3, la = 10), type = "gnls", returntop = TRUE)
acy(1, list(ga = .1, tp = 2, p = 3, q = 3, la = 10), type = "gnls", returntoploc = TRUE)
```

---

bmdbounds

---

*BMD Bounds*


---

### Description

Computes BMDU or BMDL.

### Usage

```
bmdbounds(
  fit_method,
  bmr,
  pars,
  conc,
  resp,
  onesidedp = 0.05,
  bmd = NULL,
  which.bound = "lower"
)
```

**Arguments**

fit_method	Fit method: "exp2", "exp3", "exp4", "exp5", "hill", "gnls", "poly1", "poly2", or "pow".
bmr	Benchmark response.
pars	Named vector of model parameters: a,b,tp,ga,p,la,q,er output by httrfit, and in that order.
conc	Vector of concentrations (NOT in log units).
resp	Vector of responses corresponding to given concentrations.
onesidedp	The one-sided p-value. Default of .05 corresponds to 5 percentile BMDL, 95 percentile BMDU, and 90 percent CI.
bmd	Can optionally input the bmd when already known to avoid unnecessary calculation.
which.bound	Returns BMDU if which.bound = "upper"; returns BMDL if which.bound = "lower".

**Details**

Takes in concentration response fit details and outputs a bmdu or bmdl, as desired. If bmd is not finite, returns NA. If the objective function doesn't change sign or the root finding otherwise fails, it returns NA. These failures are not uncommon since some curves just don't reach the desired confidence level.

**Value**

Returns either the BMDU or BMDL.

**Examples**

```
conc = c(.03, .1, .3, 1, 3, 10, 30, 100)
resp = c(.1, -.1, 0, 1.1, 1.9, 2, 2.1, 1.9)
pars = c(tp = 1.973356, ga = 0.9401224, p = 3.589397, er = -2.698579)
bmdbounds(fit_method = "hill", bmr = .5, pars, conc, resp)
bmdbounds(fit_method = "hill", bmr = .5, pars, conc, resp, which.bound = "upper")
```

---

bmdobj

---

*BMD Objective Function*


---

**Description**

Utility function for bmdbounds

**Usage**

```
bmdobj(bmd, fname, bmr, conc, resp, ps, mll, onesp, partype = 2)
```

Arguments

bmd	Benchmark dose.
fname	Function name: "exp2", "exp3", "exp4", "exp5", "hillfn", "gnls", "poly1", "poly2", or "pow".
bmr	Benchmark response.
conc	Vector of concentrations NOT in log units.
resp	Vector of corresponding responses.
ps	Named list of paramters.
mll	Maximum log-likelihood of winning model.
onesp	One-sided p-value.
partype	Number for parameter type. Type 1 is y-scaling: a or tp. Type 2 is x-scaling: b or ga, when available, a otherwise. Type 3 is power scaling: p when available, then b or ga, then a if no others. Since bmd is linked to the x-scale, type 2 should always be used. Other types can also be vulnerable to underflow/overflow.

Value

Objective function value to find the zero of.

---

cnst	<i>Constant Model</i>
------	-----------------------

---

Description

Constant Model

Usage

cnst(ps, x)

Arguments

ps	Vector of parameters (ignored)
x	Vector of concentrations (regular units)

Value

Vector of model responses

---

concRespCore	<i>Concentration Response Core</i>
--------------	------------------------------------

---

## Description

Core of concentration response curve fitting for pvalue based cutoff. This function calls htrFit to get curve fits, chooses the winning model, extracts the top and ac50, computes the hitcall, and calculates bmd/bmdl/bmdu among other statistics. Nested model selection is used to choose between poly1/poly2, then the model with the lowest AIC (or AICc) is declared the winner. Continuous hitcalls requires tcplfit2\_core to be run with force.fit = T and "cnst" never to be chosen as the winner.

## Usage

```
concRespCore(
  row,
  fitmodels = c("cnst", "hill", "gnls", "poly1", "poly2", "pow", "exp2", "exp3", "exp4",
    "exp5"),
  conthits = T,
  aicc = F,
  force.fit = FALSE,
  bidirectional = TRUE,
  verbose = FALSE,
  do.plot = FALSE
)
```

## Arguments

row	<p>A named list that must include:</p> <ul style="list-style-type: none"> <li>• conc - list of concentrations (not in log units)</li> <li>• resp - list of corresponding responses</li> <li>• bmed - median of noise estimate.</li> <li>• cutoff - noise cutoff</li> <li>• onesd - 1 standard deviation of the noise (for bmd calculation)</li> </ul> <p>Other elements (usually identifiers, like casrn) of row will be attached to the final output.</p>
fitmodels	Vector of model names to use.
conthits	conthits = T uses continuous hitcalls, otherwise they're discrete.
aicc	aicc = T uses corrected AIC to choose winning method; otherwise regular AIC.
force.fit	If TRUE force the fitting to proceed even if there are no points outside of the bounds (default FALSE)
bidirectional	If TRUE allow fitting to happen in both directions (default TRUE)
verbose	If TRUE, write extra output from tcplfit2_core (default FALSE)
do.plot	If TRUE, create a plot in the tcplfit2_core function (default FALSE)

**Value**

One row dataframe containing all concentration-response outputs and statistics and any identifiers from row.

- n\_gt\_cutoff - number of data points above the cutoff
- cutoff - noise cutoff
- fit\_method - curve fit method
- top\_over\_cutoff - top divided by cutoff
- rmse - RMSE of the data points around the best model curve
- a - fitting parameter methods: exp2, exp3, poly1, poly2, pow
- b - fitting parameter methods: exp2, exp3, ploy2
- p - fitting parameter methods: exp3, exp5, gnls, hill, pow
- q - fitting parameter methods: gnls,
- tp - top of the curve
- ga - ac50 for the rising curve in a gnls model or the Hill model
- la - ac50 for the falling curve in a gnls model
- er - fitted error term for plotting error bars
- bmr - benchmark response; level at which bmd is calculated = onesd\*1.349
- bmd - benchmark dose, curve value at bmr
- bmdl - lower limit on the bmd
- bmdu - upper limit on the bmd
- caikwt - one factor used in calculating the continuous hitcall. It is calculated from the formula  $= \exp(-aic(cnst)/2) / (\exp(-aic(cnst)/2) + \exp(-aic(fit\_method)/2))$  and measures how much lower the selected method AIC is than that for the constant model
- mll - anoter factor used in calculating the continuous hitcall =  $\text{length(modpars)} - aic(fit\_method)/2$
- hitcall - the final hitcall, a value ranging from 0 to 1
- top - curve top
- ac50 - curve value at 50% of top, curve value at cutoff
- lc50 - curve value at 50% of top corresponding to the loss side of the gain-loss curve
- ac5 - curve value at 5% of top
- ac10 - curve value at 10% of top
- ac20 - curve value at 20% of top
- acc - curve value at 1 standard deviation
- conc - conc string separated by l's
- resp - response string separated by l's

**Examples**

```
conc = list(.03,.1,.3,1,3,10,30,100)
resp = list(0,.2,.1,.4,.7,.9,.6, 1.2)
row = list(conc = conc, resp = resp, bmed = 0, cutoff = 1, onesd = .5)
concRespCore(row, conthits = TRUE)
concRespCore(row, aicc = TRUE)
```



---

concRespPlot	<i>Concentration Response Plot</i>
--------------	------------------------------------

---

**Description**

Plots a concentration response curve for one sample/endpoint combination. This is a generic function and it is expected that users will make their own versions

**Usage**

```
concRespPlot(row, ymin = -120, ymax = 120, draw.error.arrows = FALSE)
```

**Arguments**

row	<p>Named list containing:</p> <ul style="list-style-type: none"> <li>• conc - conc string separated by  's</li> <li>• resp - response string separated by  's</li> <li>• method - scoring method determines plot bounds</li> <li>• name - chemical name for plot title</li> <li>• cutoff - noise cutoff</li> <li>• bmr - baseline median response; level at which bmd is calculated</li> <li>• er - fitted error term for plotting error bars</li> <li>• a, tp, b, ga, p, la, q - other model parameters for fit curve</li> <li>• fit_method - curve fit method</li> <li>• bmd, bmdl, bmdu - bmd, bmd lower bound, and bmd upper bound</li> <li>• ac50, acc - curve value at 50% of top, curve value at cutoff</li> <li>• top - curve top</li> <li>• other identifiers</li> </ul> <p>Other elements are ignored.</p>
ymin	Minimum value of response for the plot
ymax	Maximum value of response for the plot
draw.error.arrows	If TRUE, draw lines representing the uncertainty in the response estimate, instead of the actual response points

**Details**

row is one row of data from concRespCore

**Value**

No output.

exp2	<i>Exponential 2 Model</i>
<b>Description</b>	
Exponential 2 Model	
<b>Usage</b>	
exp2(ps, x)	
<b>Arguments</b>	
ps	Vector of parameters: a,b,er
x	Vector of concentrations (regular units)
<b>Value</b>	
Vector of model responses	
exp3	<i>Exponential 3 Model</i>

<b>Description</b>	
Exponential 3 Model	
<b>Usage</b>	
exp3(ps, x)	
<b>Arguments</b>	
ps	Vector of parameters: a,b,p,er
x	Vector of concentrations (regular units)
<b>Value</b>	
Vector of model responses	

---

exp4	<i>Exponential 4 Model</i>
------	----------------------------

---

**Description**

Exponential 4 Model

**Usage**

exp4(ps, x)

**Arguments**

- |    |  |
|----|--|
| ps | Vector of parameters: tp,ga,er           |
| x  | Vector of concentrations (regular units) |

**Value**

Vector of model responses

---

exp5	<i>Exponential 5 Model</i>
------	----------------------------

---

**Description**

Exponential 5 Model

**Usage**

exp5(ps, x)

**Arguments**

- |    |  |
|----|--|
| ps | Vector of parameters: tp,ga,p,er         |
| x  | Vector of concentrations (regular units) |

**Value**

Vector of model responses

---

fitcnst

*Constant Model Fit*


---

### Description

Function that fits a constant line and returns generic model outputs.

### Usage

```
fitcnst(conc, resp, nofit = F)
```

### Arguments

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
nofit	If nofit = T, returns formatted output filled with missing values.

### Details

success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. aic, rme, and er are set to NA in case of nofit or failure. pars always equals "er".

### Value

List of five elements: success, aic (Aikaike Information Criteria), rme (root mean square error), er (error parameter), pars (parameter names).

### Examples

```
fitcnst(c(.1,1,10,100), c(1,2,0,-1))
fitcnst(c(.1,1,10,100), c(1,2,0,-1), nofit = TRUE)
```

---

fitexp2

*Exponential 2 Model Fit*


---

### Description

Function that fits to  $f(x) = a \cdot (e^{(x/b)} - 1)$  and returns generic model outputs.

### Usage

```
fitexp2(conc, resp, bidirectional = TRUE, verbose = FALSE, nofit = F)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.

**Details**

Zero background and increasing absolute response are assumed. Parameters are "a" (y scale), "b" (x scale), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fitexp2(c(.1,1,10,100), c(0,.1,1,10))
```

---

fitexp3	<i>Exponential 3 Model Fit</i>
---------	--------------------------------

---

**Description**

Function that fits to  $f(x) = a*(e^{((x/b)^p)} - 1)$  and returns generic model outputs.

**Usage**

```
fitexp3(
  conc,
  resp,
  bidirectional = TRUE,
  verbose = FALSE,
  nofit = F,
  dmin = 0.3
)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.
dmin	Minimum allowed value of p.

**Details**

Zero background and increasing absolute response are assumed. Parameters are "a" (y scale), "b" (x scale), "p" (power), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fitexp3(c(.03,.1,.3,1,3,10,30,100), c(0,0,.1, .2, .4, 1, 4, 50))
```

---

fitexp4	<i>Exponential 4 Model Fit</i>
---------	--------------------------------

---

**Description**

Function that fits to  $f(x) = tp \cdot (1 - 2^{-(x/ga)})$  and returns generic model outputs.

**Usage**

```
fitexp4(conc, resp, bidirectional = TRUE, verbose = FALSE, nofit = F)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.

## Details

Zero background and increasing absolute response are assumed. Parameters are "tp" (top), "ga" (AC50), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

## Value

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

## Examples

```
fitexp4(c(.03,.1,.3,1,3,10,30,100), c(0,0,.1, .2, .5, 1, 1.5, 2))
```

---

fitexp5	<i>Exponential 5 Model Fit</i>
---------	--------------------------------

---

## Description

Function that fits to  $f(x) = tp * (1 - 2^{-(x/ga)^p})$  and returns generic model outputs.

## Usage

```
fitexp5(
  conc,
  resp,
  bidirectional = TRUE,
  verbose = FALSE,
  nofit = F,
  dmin = 0.3
)
```

## Arguments

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.
dmin	Minimum allowed value of p.

## Details

Zero background and increasing absolute response are assumed. Parameters are "tp" (top), "ga" (AC50), "p" (power), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

## Value

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

## Examples

```
fitexp5(c(.03,.1,.3,1,3,10,30,100), c(0,0,.1, .2, .5, 1, 1.5, 2))
```

---

fitgnls	<i>Gain-Loss Model Fit</i>
---------	----------------------------

---

## Description

Function that fits to  $f(x) = tp / [(1 + (ga/x)^p)(1 + (x/la)^q)]$  and returns generic model outputs.

## Usage

```
fitgnls(
  conc,
  resp,
  bidirectional = TRUE,
  verbose = FALSE,
  nofit = F,
  minwidth = 1.5
)
```

## Arguments

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.
minwidth	Minimum allowed distance between gain ac50 and loss ac50 (in log10 units).



## Details

Concentrations are converted internally to log10 units and optimized with  $f(x) = tp / [(1 + 10^{p*(ga-x)}) (1 + 10^{q*(x-la)})]$ , then *ga*, *la*, *ga\_sd*, and *la\_sd* are converted back to regular units before returning. Zero background and increasing initial absolute response are assumed. Parameters are "tp" (top), "ga" (gain AC50), "p" (gain power), "la" (loss AC50), "q" (loss power) and error term "er". *success* = 1 for a successful fit, 0 if optimization failed, and NA if *nofit* = T. *cov* = 1 for a successful hessian inversion, 0 if it fails, and NA if *nofit* = T. *aic*, *rme*, *modl*, *parameters*, and *parameter sds* are set to NA in case of *nofit* or failure.

## Value

Named list containing: *success*, *aic* (Aikaike Information Criteria), *cov* (success of covariance calculation), *rme* (root mean square error), *modl* (vector of model values at given concentrations), *parameters values*, *parameter sd* (standard deviation) estimates, *pars* (vector of parameter names), *sds* (vector of parameter sd names).

## Examples

```
fitgnls(c(.03,.1,.3,1,3,10,30,100), c(0,.3,1, 2, 2.1, 1.5,.8, .2))
```

---

fithill	<i>Hill Model Fit</i>
---------	-----------------------

---

## Description

Function that fits to  $f(x) = tp / [(1 + (ga/x)^p)]$  and returns generic model outputs.

## Usage

```
fithill(conc, resp, bidirectional = TRUE, verbose = FALSE, nofit = F)
```

## Arguments

<i>conc</i>	Vector of concentration values NOT in log units.
<i>resp</i>	Vector of corresponding responses.
<i>bidirectional</i>	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
<i>verbose</i>	If TRUE, gives optimization and hessian inversion details.
<i>nofit</i>	If <i>nofit</i> = T, returns formatted output filled with missing values.

## Details

Concentrations are converted internally to log10 units and optimized with  $f(x) = tp / (1 + 10^{p*(ga-x)})$ , then *ga* and *ga\_sd* are converted back to regular units before returning. Zero background and increasing initial absolute response are assumed. Parameters are "tp" (top), "ga" (gain AC50), "p" (gain power), and error term "er". *success* = 1 for a successful fit, 0 if optimization failed, and NA if *nofit* = T. *cov* = 1 for a successful hessian inversion, 0 if it fails, and NA if *nofit* = T. *aic*, *rme*, *modl*, *parameters*, and *parameter sds* are set to NA in case of *nofit* or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fithill(c(.03,.1,.3,1,3,10,30,100), c(0,0,.1, .2, .5, 1, 1.5, 2))
```

---

fitpoly1

*Polynomial 1 (Linear) Model Fit*


---

**Description**

Function that fits to  $f(x) = a \cdot x$  and returns generic model outputs.

**Usage**

```
fitpoly1(conc, resp, bidirectional = TRUE, verbose = FALSE, nofit = F)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.

**Details**

Zero background and increasing absolute response are assumed. Parameters are "a" (y scale) and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fitpoly1(c(.03,.1,.3,1,3,10,30,100), c(0,.01,.1, .1, .2, .5, 2, 5))
```

---

fitpoly2*Polynomial 2 (Quadratic) Model Fit*

---

**Description**

Function that fits to  $f(x) = a*(x/b + x^2/b^2)$  and returns generic model outputs.

**Usage**

```
fitpoly2(conc, resp, bidirectional = TRUE, verbose = FALSE, nofit = F)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.

**Details**

Zero background and monotonically increasing absolute response are assumed. Parameters are "a" (y scale), "b" (x scale), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fitpoly2(c(.03,.1,.3,1,3,10,30,100), c(0,.01,.1, .1, .2, .5, 2, 8))
```

fitpow

*Power Model Fit***Description**

Function that fits  $\text{tof}(x) = a \cdot x^p$  and returns generic model outputs.

**Usage**

```
fitpow(
  conc,
  resp,
  bidirectional = TRUE,
  verbose = FALSE,
  nofit = F,
  nmin = 0.3
)
```

**Arguments**

conc	Vector of concentration values NOT in log units.
resp	Vector of corresponding responses.
bidirectional	If TRUE, model can be positive or negative; if FALSE, it will be positive only.
verbose	If TRUE, gives optimization and hessian inversion details.
nofit	If nofit = T, returns formatted output filled with missing values.
nmin	Minimum allowed value of p.

**Details**

Zero background and monotonically increasing absolute response are assumed. Parameters are "a" (y scale), "p" (power), and error term "er". success = 1 for a successful fit, 0 if optimization failed, and NA if nofit = T. cov = 1 for a successful hessian inversion, 0 if it fails, and NA if nofit = T. aic, rme, modl, parameters, and parameter sds are set to NA in case of nofit or failure.

**Value**

Named list containing: success, aic (Aikaike Information Criteria), cov (success of covariance calculation), rme (root mean square error), modl (vector of model values at given concentrations), parameters values, parameter sd (standard deviation) estimates, pars (vector of parameter names), sds (vector of parameter sd names).

**Examples**

```
fitpow(c(.03, .1, .3, 1, 3, 10, 30, 100), c(0, .01, .1, .1, .2, .5, 2, 8))
```

gnls	<i>Gain-Loss Model</i>
<b>Description</b>	
Gain-Loss Model	
<b>Usage</b>	
gnls(ps, x)	
<b>Arguments</b>	
ps	Vector of parameters: tp,ga,p,la,q,er
x	Vector of concentrations (regular units)
<b>Value</b>	
Vector of model responses	
gnlsderivobj	<i>GNLS Derivative Objective Function</i>

**Description**

Derivative of the gnls function set to zero for top location solver.

**Usage**

gnlsderivobj(x, tp, ga, p, la, q)

**Arguments**

- x                   Concentration.
- tp                  Top.
- ga                  Gain AC50.
- p                   Gain power.
- la                  Loss AC50.
- q                   Loss power.

**Value**

Value of gnls derivative at x.

---

hillfn	<i>Hill Model</i>
--------	-------------------

---

**Description**

Hill Model

**Usage**

```
hillfn(ps, x)
```

**Arguments**

ps	Vector of parameters: tp,ga,p,er
x	Vector of concentrations (regular units)

**Value**

Vector of model responses

---

hitcont	<i>Continuous Hitcalls</i>
---------	----------------------------

---

**Description**

Wrapper that computes continuous hitcalls for a provided concRespCore input row.

**Usage**

```
hitcont(indf, xs = NULL, ys = NULL, newcutoff, mc.cores = 1)
```

**Arguments**

indf	Dataframe similar to concRespCore input. Must contain "conc" and "resp" columns if xs and ys are not provided. Must contain "top", "ac50", "er", "fit_method", "caikwt", and "mll" columns as well as columns for each model parameter.
xs	List of concentration vectors that can be provided for speed.
ys	List of response vectors that can be provided for speed.
newcutoff	Vector of new cutoff values to use. Length should be equal to rows in indf.
mc.cores	Number of cores to use for large dataframes.

**Details**

indf parameter columns should be NA when not required by fit method. "conc" and "resp" entries should be a single string with values separated by |. Details on indf columns can be found in concRespCore.

**Value**

Vector of hitcalls between 0 and 1 with length equal to indf row number.

---

hitcontinner

*Continuous Hitcalls Inner*


---

**Description**

Calculates continuous hitcall using 3 statistical metrics.

**Usage**

```
hitcontinner(conc, resp, top, cutoff, er, ps, fit_method, caikwt, mll)
```

**Arguments**

conc	Vector of concentrations.
resp	Vector of responses.
top	Model top.
cutoff	Desired cutoff.
er	Model error parameter.
ps	Vector of used model parameters in order: a, tp, b, ga, p, la, q, er.
fit_method	Name of winning fit method (should never be constant).
caikwt	Aikake weight of constant model relative to winning model.
mll	Maximum log-likelihood of winning model.

**Details**

This function is called either directly from concRespCore or via hitcont. Details of how to compute function input are in concRespCore.

**Value**

Continuous hitcall between 0 and 1.

**Examples**

```
conc = c(.03, .1, .3, 1, 3, 10, 30, 100)
resp = c(0, .1, 0, .2, .6, .9, 1.1, 1)
top = 1.023239
er = -3.295307
ps = c(1.033239, 2.453014, 1.592714, er = -3.295307) #tp, ga, p, er
fit_method = "hill"
caikwt = 1.446966e-08
mll = 12.71495
hitcontinner(conc, resp, top, cutoff = 0.8, er, ps, fit_method, caikwt, mll)
hitcontinner(conc, resp, top, cutoff = 1, er, ps, fit_method, caikwt, mll)
hitcontinner(conc, resp, top, cutoff = 1.2, er, ps, fit_method, caikwt, mll)
```

hitlogic

*Hit Logic (Discrete)***Description**

Wrapper that computes discrete hitcalls for a provided concRespCore dataframe.

**Usage**

```
hitlogic(indf, newbmad = NULL, xs = NULL, ys = NULL, newcutoff = NULL)
```

**Arguments**

indf	Dataframe similar to concRespCore input. Must contain "conc" and "resp" columns if xs and ys are not provided. Must contain "cutoff" and "bmad_factor" columns if newbmad is not NULL. Must contain "top" and "ac50" columns. "conc" and "resp" entries should be a single string with values separated by  .
newbmad	(Deprecated) New number of bmads to use for the cutoff.
xs	List of concentration vectors that can be provided for speed.
ys	List of response vectors that can be provided for speed.
newcutoff	Vector of new cutoff values to use. Length should be equal to rows in indf.

**Value**

Vector of hitcalls with length equal to number of rows in indf.

**Examples**

```
conc = rep(".03|.1|.3|1|3|10|30|100",2)
resp = rep("0|0|.1|.1|.5|.5|1|1",2)
indf = data.frame(top = c(1,1), ac50 = c(3,4), conc = conc, resp = resp,
  stringsAsFactors = FALSE)
hitlogic(indf, newcutoff = c(.8,1.2))
```

hitloginner

*Hit Logic Inner (Discrete)***Description**

Contains hit logic, called directly during CR fitting or later through "hitlogic".

**Usage**

```
hitloginner(conc = NULL, resp, top, cutoff, ac50 = NULL)
```



**Arguments**

conc	Vector of concentrations (No longer necessary).
resp	Vector of responses.
top	Model top.
cutoff	Desired cutoff.
ac50	Model AC50 (No longer necessary).

**Details**

The purpose of this function is to keep the actual hit rules in one location so it can be called during CR fitting, and then again after the fact for a variety of cutoffs. Curves fit with constant winning should have top = NA, generating a miss.

**Value**

Outputs 1 for hit, 0 for miss.

**Examples**

```
hitloginner(resp = 1:8, top = 7, cutoff = 5) #hit
hitloginner(resp = 1:8, top = 7, cutoff = 7.5) #miss: top too low
hitloginner(resp = 1:8, top = 9, cutoff = 8.5) #miss: no response> cutoff
hitloginner(resp = 1:8, top = NA, cutoff = 5) #miss: no top (constant)
```

---

loggnls

---

*Log Gain-Loss Model*


---

**Description**

Log Gain-Loss Model

**Usage**

```
loggnls(ps, x)
```

**Arguments**

ps	Vector of parameters: tp,ga,p,la,q,er
x	Vector of concentrations (log10 units)

**Value**

Vector of model responses

loghill

*Log Hill Model***Description**

Log Hill Model

**Usage**

loghill(ps, x)

**Arguments**

ps                      Vector of parameters: tp,ga,p,er  
 x                        Vector of concentrations (log10 units)

**Value**

Vector of model responses

mc3

*Sample concentration-response data set from invitrodb***Description**

A data set containing 100 chemicals worth of data for the Tox21 assay TOX21\_ERa\_BLA\_Agonist\_ratio, which measures response to estrogen receptor agonists. The data can be accessed further through the Comptox Chemicals Dashboard: <https://comptox.epa.gov/dashboard>

**Usage**

mc3

**Format**

An object of class data.frame with 32175 rows and 7 columns.

**Details**

This data is extracted from the database invitrodb, at level 3 (conc-response data)

A data frame with 32175 rows and 6 variables:

- dtxsid - DSSTox generic substance ID
- casrn - Chemical Abstracts Registry Number (CASRN)
- name- chemical name

- spid - sample ID - there can be multiple samples per chemical
- logc -  $\log_{10}(\text{concentration } \mu\text{M})$
- resp - response in
- assay - name of the assay / assay component endpoint ...

---

nestselect

*Nest Select*

---

## Description

Chooses between nested models.

## Usage

```
nestselect(aics, mod1, mod2, dfdiff, pval = 0.05)
```

## Arguments

aics	Named vector of model aics (can include extra models).
mod1	Name of model 1, the model with fewer degrees of freedom.
mod2	Name of model 2, the model with more degrees of freedom.
dfdiff	Absolute difference in number of degrees of freedom (i.e. the difference in parameters).
pval	P-value for nested model test.

## Value

Named aic vector with losing model removed.

## Examples

```
aics = c(-5,-6,-3)
names(aics) = c("poly1", "poly2", "hill")
nestselect(aics, "poly1", "poly2", 1)

aics = c(-5,-7,-3)
names(aics) = c("poly1", "poly2", "hill")
nestselect(aics, "poly1", "poly2", 1)
```

---

poly1	<i>Polynomial 1 Model</i>
-------	---------------------------

---

**Description**

Polynomial 1 Model

**Usage**

poly1(ps, x)

**Arguments**

- |    |  |
|----|--|
| ps | Vector of parameters: a,er               |
| x  | Vector of concentrations (regular units) |

**Value**

Vector of model responses

---

poly2	<i>Polynomial 2 Model</i>
-------	---------------------------

---

**Description**

Polynomial 2 Model

**Usage**

poly2(ps, x)

**Arguments**

- |    |  |
|----|--|
| ps | Vector of parameters: a,b,er             |
| x  | Vector of concentrations (regular units) |

**Value**

Vector of model responses

---

pow	<i>Power Model</i>
-----	--------------------

---

**Description**

Power Model

**Usage**

pow(ps, x)

**Arguments**

ps	Vector of parameters: a,p,er
x	Vector of concentrations (regular units)

**Value**

Vector of model responses

---

tcp1Fit2.test	<i>Run a test of the tcp1oFit2 code</i>
---------------	---

---

**Description**

This is jsut a test routine to show how tcp1Fit2 runs

**Usage**

tcp1Fit2.test()

---

tcp1Fit2.test.mc3	<i>Run a test of the tcp1oFit2 code</i>
-------------------	---

---

**Description**

This function shows how to run multiple chemicals using data from invitrodb

**Usage**

tcp1Fit2.test.mc3()

**Description**

Concentration response curve fitting using the methods from BMDEExpress

**Usage**

```
tcplfit2_core(
  conc,
  resp,
  cutoff,
  force.fit = FALSE,
  bidirectional = TRUE,
  verbose = FALSE,
  do.plot = FALSE,
  fitmodels = c("cnst", "hill", "gnls", "poly1", "poly2", "pow", "exp2", "exp3", "exp4",
    "exp5"),
  ...
)
```

**Arguments**

conc	Vector of concentrations (NOT in log units).
resp	Vector of responses.
cutoff	Desired cutoff. If no absolute responses > cutoff and force.fit = F, will only fit constant model.
force.fit	If force.fit = T, will fit all models regardless of cutoff.
bidirectional	If bidirectional = F, will only give positive fits.
verbose	If verbose = T, will print optimization details and aics.
do.plot	If do.plot = T, will generate a plot comparing model curves.
fitmodels	Vector of model names to try fitting. Missing models still return a skeleton output filled with NAs.
...	Other fitting parameters (deprecated).

**Details**

All models are equal to 0 at 0 concentration (zero background). To add more models in the future, write a fit\_\_\_\_ function, and add the model name to the fitmodels and modelnames vectors.

**Value**

List of N(models) elements, one for each of the models run (up to 10), followed by a last element "modelnames", which is a vector of model names so other functions can easily cycle through the output. For a full list, see the documentation for the individual fitting method functions. For each model there is a sublist with elements including:

- success - was the model successfully fit
- aic - the AIC value
- cov - success of the the covariance matrix calculation
- rme - root mean error of the data around the curve
- modl - vector of model values at the given concentrations
- tp - the top of the curve fit
- ga - the AC50 or Hill paramters
- er - the error term
- ... other paramters specific to the model (see the documentation for the specific models)
- tp\_sd, ga\_sd, p\_sd, etc., the values of the standard deviations of the paramters for the models
- er\_sd - standard deviation of the error term
- pars - the names of the parameters
- sds - the names of the standard deviations of the paramters

**Examples**

```
conc = c(.03, .1, .3, 1, 3, 10, 30, 100)
resp = c(0, .1, 0, .2, .6, .9, 1.1, 1)
output = tcplfit2_core(conc, resp, .8, fitmodels = c("cnst", "hill"), verbose = TRUE,
  do.plot = TRUE)
```

---

 tcplObj

---

*Concentration Response Objective Function*


---

**Description**

Log-likelihood to be maximized during CR fitting.

**Usage**

```
tcplObj(p, conc, resp, fname, errfun = "dt4", err = NULL)
```

Arguments

p	Vector of parameters, must be in order: a, tp, b, ga, p, la, q, er. Does not require names.
conc	Vector of concentrations in log10 units for loghill/loggnls, in regular units otherwise.
resp	Vector of corresponding responses.
fname	Name of model function.
errfun	Which error distribution to assume for each point. "dt4" is the original 4 degrees of freedom t-distribution. "dnorm" is the normal distribution.
err	An optional estimation of error for the given fit.

Details

This function is a generalized version of the log-likelihood estimation functions used in the ToxCast Pipeline (TCPL). Hill model uses fname "loghill" and gnls uses fname "loggnls". Other model functions have the same fname as their model name; i.e. exp2 uses "exp2", etc. errfun = "dnorm" may be better suited to gsva pathway scores than "dt4". Setting err could be used to fix error based on the null data noise distribution instead of fitting the error when maximizing log-likelihood.

Value

Log-likelihood.

Examples

```
conc = c(.03,.1 , .3 , 1 , 3 , 10 , 30 , 100)
resp = c( 0 , 0 , .1 ,.2 , .5 , 1 , 1.5 , 2 )
p = c(tp = 2, ga = 3, p = 4, er = .5)
tcplobj(p,conc,resp,"exp5")

lconc = log10(conc)
tcplobj(p,lconc,resp,"loghill")
```

---

toplikelihood	<i>Top Likelihood</i>
---------------	-----------------------

---

Description

Probability of top being above cutoff.

Usage

```
toplikelihood(fname, cutoff, conc, resp, ps, top, mll)
```



**Arguments**

fname	Model function name (equal to model name except hill which uses "hillfn")
cutoff	Desired cutoff.
conc	Vector of concentrations.
resp	Vector of responses.
ps	Vector of parameters, must be in order: a, tp, b, ga, p, la, q, er
top	Model top.
mll	Winning model maximum log-likelihood.

**Details**

Should only be called by hitcontinner. Uses profile likelihood, similar to bmdbounds. Here, the y-scale type parameter is substituted in such a way that the top equals the cutoff. Then the log-likelihood is compared to the maximum log-likelihood using chisq function to retrieve probability.

**Value**

Probability of top being above cutoff.

**Examples**

```
fname = "hillfn"
conc = c(.03,.1,.3,1,3,10,30,100)
resp = c(0,.1,0,.2,.6,.9,1.1,1)
ps = c(1.033239, 2.453014, 1.592714, er = -3.295307)
top = 1.023239
mll = 12.71495
toplikelihood(fname, cutoff = .8, conc, resp, ps, top, mll)
toplikelihood(fname, cutoff = 1, conc, resp, ps, top, mll)
toplikelihood(fname, cutoff = 1.2, conc, resp, ps, top, mll)
```

# Index

## \*Topic **datasets**

mc3, [26](#)

acgnlsobj, [2](#)  
acy, [3](#)

bmdbounds, [4](#)  
bmdobj, [5](#)

cnst, [6](#)  
concRespCore, [7](#)  
concRespPlot, [9](#)

exp2, [10](#)  
exp3, [10](#)  
exp4, [11](#)  
exp5, [11](#)

fitcnst, [12](#)  
fitexp2, [12](#)  
fitexp3, [13](#)  
fitexp4, [14](#)  
fitexp5, [15](#)  
fitgnls, [16](#)  
fithill, [17](#)  
fitpoly1, [18](#)  
fitpoly2, [19](#)  
fitpow, [20](#)

gnls, [21](#)  
gnlsderivobj, [21](#)

hillfn, [22](#)  
hitcont, [22](#)  
hitcontinner, [23](#)  
hitlogic, [24](#)  
hitloginner, [24](#)

loggnls, [25](#)  
loghill, [26](#)

mc3, [26](#)

nestselect, [27](#)

poly1, [28](#)  
poly2, [28](#)  
pow, [29](#)

tcplFit2.test, [29](#)  
tcplFit2.test.mc3, [29](#)  
tcplfit2\_core, [30](#)  
tcpl0bj, [31](#)  
topllikelihood, [32](#)