

### Problem 1: Loops (10 points)

- a. Consider the Q1a program. Describe, in one sentence, what the Q1a does.

```
public class Q1a
{
    public static void main (String[] args)
    {
        int n = 1000;
        int mySum = 0;

        for (int i = n; i >= 0; i--)
        {
            if (i % 2 == 0)
            {
                mySum += i;
            }
        }
        StdOut.println(mySum);
    }
}
```

- b. Complete the program Q1b that reads a set of integer values into the integer array numbers (already done for you). Then it adds up the positive values in the numbers array until it reads the item 999 (999 is not included in the sum). At that point it prints the sum of those numbers and their average.

Example 1

```
java Q1b 5 -3 8 999 7 1
10
5
```

Example 2

```
java Q1b 5 -3 8 7 1
18
5.25
```

```
public class Q1b
{
    public static void main (String[] args)
    {
        int[] numbers = new int[args.length];
        for (int i = 0; i < args.length; i++) {
            numbers[i] = Integer.parseInt(args[i]);
        }

        // INSERT YOUR CODE HERE
    }
}
```

## Problem 2: Arrays (15 points)

Complete the method `endsInFive(int[][] array, int c)` that takes a 2D-array of integers and an integer value as arguments. `endsInFive` returns the number of values in column `c` that end in 5. It is possible that array is ragged, meaning that the number of columns in each row is different.

For example, 2 is returned if the following 2D-array is passed as the first argument of `endsInFive` and 3 is the second argument. The value 25 and 115 end in five in column 3.

234	34	13	25	
762	2	995		
125	345	54	859	
21	467	15	115	785

```
public static int endsInFive(int[][] array, int c) {  
    // WRITE YOUR CODE HERE  
}
```

### Problem 3: Functions (25 points)

For each of the following three problems, choose the correct output from the box on the right.  
(4 points each)

1)

```
public class Q3a {
    public static void main(String[] args){
        var a = " coming!";
        System.out.println(methodC(methodB(a)));
    }
    public static String methodF(String d){
        return "Thanksgiving " + d;
    }
    public static String methodC(String g){
        return methodF(g);
    }
    public static String methodB(String c){
        String a = "of ";
        return a + "Turkeys ";
    }
}
```

2)

```
public class Q3b {
    public static void main(String[] args){
        var a = "coming!";
        System.out.println(methodC(methodB(a, a), a));
    }

    public static String methodF(String d, String a){
        return "Thanksgiving " + a;
    }
    public static String methodC(String g, String a){
        return methodF(g,a);
    }

    public static String methodB(String c, String b){
        String a = "of ";
        return "Turkeys " + a;
    }
}
```

3)

```
public class Q3c {
    public static void main(String[] args){
        var a = " coming!";
        System.out.println(methodB(methodF(a)));
    }

    public static String methodF(String d){
        return " of Thanksgiving" + d;
    }
    public static String methodC(String g){
        return methodF(g);
    }

    public static String methodB(String c){
        String a = "of ";
        return "Turkeys" + c;
    }
}
```

#2. Two numbers, num1 and num2, are said to be “friendly” if the sum of proper factors of num1 is equal to num2 and the sum of the proper factors of num2 is equal to num1.

The method **main** below is to print either “**Friendly**” or “**Not Friendly**” to indicate whether two integer command line inputs, num1 and num2, are “friendly”. Complete **main** so that it works as intended. You **must** call method `sumOfDivisors` in your solution.

You may assume that the method `sumOfDivisors` returns the sum of the proper factors of its integer parameter.

```
public class Friendly {
    public static void main(String[] args){
        // your code goes here
    }

    /*
    This method returns the sum of the proper divisors of n.
    A proper divisor is a number between 1 and n-1 inclusive that
    Divides into n evenly. YOU DO. NOT HAVE TO WRITE THIS CODE.
    Assume this method works as intended.
    */
    public static int sumOfDivisors(int n){
        //code not shown—do not write this code
    }
}
```

#### Problem 4: Recursion (25 points)

##### Part 1 (15 points)

Consider the following recursive function foo.

```
1  int foo(int a, int b) {  
2    if (a < b)  
3      return 0;  
4    else  
5      return 1 + foo(a-b, b);  
6  }
```

1.A (2 pts) Which line(s) handles the base case?

1.B (3 pts) What is the outcome if foo(0,0) is called?

1.C (2 points) What are the values returned for foo(4,2) and foo(5,3) respectively?

1.D (8 points) Briefly (1-2 lines) explain the purpose of the function foo

**Part 2 (10 points)**

Assume that the function `drawSquare(double x, double y, double halfLen)` draws a square of the specified size, centered at  $(x, y)$ . For example, `drawSquare(0,0,5)` draws a square centered at  $(0,0)$  with each side of length 10.

Consider the following function `foo` defined as

```
public void foo(double x, double y, double len, int n) {  
    if (n<1) return;  
    drawSquare (x, y, len);  
    foo(x-len/2, y-len/2, len/2,n-1);  
    foo(x-len/2, y+len/2, len/2,n-1);  
    foo(x+len/2, y+len/2, len/2,n-1);  
    foo(x+len/2, y-len/2, len/2,n-1);  
}
```

2.A (1 pts) How many squares are drawn if `foo(0,0,5,1)` is called?

2.B (2 pts) How many squares are drawn if `foo(0,0,5,2)` is called?

2.C (2 pts) How many squares will be drawn if `foo(0,0,5,3)` is called?

2.D. (3 pts) How many squares will be drawn if `foo(0,0,5,n)` is called? The answer should be given as a function of  $n$ .

### Problem 5: Object-Oriented Programming (25 points)

Suppose we have a 1-D array of Strings such that:

- Each string records individual scores for different quizzes for one student.
- Each string has the form "d1;d2;d3;...;dn;" where d1 to dn are all double values and they are separated using the character ';'. Note that there is one ';' after the last double value.
- Each string contains the same number of double values.

Write a method that takes a 1-D array of such Strings and an integer n as inputs, where n means the number of double values in each String in the array and returns a 2-D array containing double values. In the two 2-D array, each row records scores of one student and each column contains scores of one exam for all students.

For example, if the parameters are {"1;2;3;4;", "5;6;7;8;", "9;10;11;12;"} and 4, then the output would be a 3\*4 2-D array which has the value {{1.0, 2.0, 3.0, 4.0}, {5.0, 6.0, 7.0, 8.0}, {9.0, 10.0, 11.0, 12.0}}. You are supposed to use the provided String library methods to operate these string values. Here is the documentation for String:

<https://docs.oracle.com/en/java/javase/11/docs/api/java.base/java/lang/String.html>

The method signature is given below:

```
public static double[][] convert(String[] exams, int n)
```