

Variables are containers for storing data values.

In Java, there are different **types** of variables, for example:

- **String** - stores text, such as "Hello". String values are surrounded by double quotes
- **int** - stores integers (whole numbers), without decimals, such as 123 or -123
- **float** - stores floating point numbers, with decimals, such as 19.99 or -19.99
- **char** - stores single characters, such as 'a' or 'B'. Char values are surrounded by single quotes
- **boolean** - stores values with two states: true or false

To create a variable in Java, you need to:

- Choose a **type** (like **int** or **String**)
- Give the variable a **name** (like **x**, **age**, or **name**)
- Optionally assign it a **value** using **=**

```
int myNum = 5;           // Integer (whole number)

float myFloatNum = 5.99f; // Floating point number

char myLetter = 'D';     // Character

boolean myBool = true;   // Boolean

String myText = "Hello"; // String
```

A **Java method** is a collection of statements that are grouped together to perform an operation. When you call the `System.out.println()` method, for example, the system executes several statements in order to display a message on the console.

- **modifier** – It defines the access type of the method and it is optional to use.
- **returnType** – Method may return a value.
- **nameOfMethod** – This is the method name. The method signature consists of the method name and the parameter list.
- **Parameter List** – The list of parameters, it is the type, order, and number of parameters of a method. These are optional, method may contain zero parameters.
- **method body** – The method body defines what the method does with the statements.