

Figure 1: The HH ($\sigma_{\phi\phi,\mathrm{dB}}$, left) and VV ($\sigma_{\theta\theta,\mathrm{dB}}$, right) polarized RCS for the PEC Straight-Blade Fan-Loaded Camera Box at frequency f = 2.56 GHz.



Figure 2: The HH ($\sigma_{\phi\phi,\mathrm{dB}}$, left) and VV ($\sigma_{\theta\theta,\mathrm{dB}}$, right) polarized RCS for the PEC Straight-Blade Fan-Loaded Camera Box at frequency f = 5.12 GHz.



Figure 3: The HH ($\sigma_{\phi\phi,\mathrm{dB}}$, left) and VV ($\sigma_{\theta\theta,\mathrm{dB}}$, right) polarized RCS for the PEC Straight-Blade Fan-Loaded Camera Box at frequency f = 7 GHz.



Figure 4: The HH ($\sigma_{\phi\phi,\mathrm{dB}}$, left) and VV ($\sigma_{\theta\theta,\mathrm{dB}}$, right) polarized RCS for the PEC Straight-Blade Fan-Loaded Camera Box at frequency f = 10.24 GHz.

The above RCS results are that of the reference measurement and simulation data in the Benchmark Suite.

Notes

1. Both the measurement and simulation data are provided at every 0.5° in the azimuthal range.
2. The simulation data were calculated by using the ARCHIE-AIM code, a frequency-domain FFT-accelerated integral-equation solver developed at UT Austin [2]-[4].
3. Due to the target's azimuthal symmetry, similar to other azimuthally symmetric targets in the Benchmark Suite, two theoretically-identical $180°$ measured RCS data sets were obtained from $360°$ of measured RCS data in [1]. Unlike other problem sets in the Benchmark Suite, however, the two halves of the measured data are not averaged to a single measurement reference but provided as two measurement references in the Benchmark Suite to help quantify the minimum uncertainty in measured values [1]. In the above plots, the envelop of the two halves of the measured data are plotted as an uncertainty window that changes with angle.
4. The minimum-uncertainty quantification approach in [1] does not apply at $0°$ and $180°$ because only one set of data exists at these angles, i.e., the two halves of the reference measurement are identical.

References

[1] J. T. Kelley *et al*., "Reproducible measurements of "fan blades in a pipe" CEM benchmark," in *Proc. Antenna Meas. Techn. Assoc. Symp.,* Oct. 2023.

[2] M. F. Wu, G. Kaur, and A. E. Yılmaz, "A multiple-grid adaptive integral method for multi-region problems," *IEEE Trans. Antennas Propag.*, vol. 58, no. 5, pp. 1601-1613, May 2010.

[3] F. Wei and A. E. Yılmaz, "A more scalable and efficient parallelization of the adaptive integral method part I: algorithm," *IEEE Trans. Antennas Propag.*, vol. 62, no.2, pp. 714-726, Feb. 2014.

[4] J. W. Massey, V. Subramanian, C. Liu, and A. E. Yılmaz, "Analyzing UHF band antennas near humans with a fast integral-equation method," in *Proc. EUCAP*, Apr. 2016.