



Wireless Intelligence Report

Team 404 – Prototype

Generated: 2025-10-04 14:19

This report summarises 802.11 frame activity observed during the capture window. Key metrics, basic traffic characteristics, and observed MAC activity are shown below. Intended use: quick situational awareness for troubleshooting, site surveys, and security triage.

Summary: 1 unique MACs • 1 frames observed.

Parameters

Records	1
Time range	2025-09-15 20:07:19 → 2025-09-15 20:07:19
Capture Mode	monitor
App version	0.1.0
Project ID	1
Capture Type	sniff_external
Project Start	2025-09-15 20:07:19
Project Stop	2025-09-15 20:07:19

Key Visuals

No chartable data for this run (capture too short / sample too small).

Frame Size Distribution

Min 0 B • P50 0 B • P95 0 B • P99 0 B • Max 0 B • Frames 1 • Bytes 0

Inter-Arrival Times

Mean 0.00 ms • Median 0.00 ms • P95 0.00 ms

RTS / CTS

RTS: 0 • CTS: 0 • RTS→CTS match rate: 0.0%

Observed MAC Addresses (enhanced)

#	MAC	SSID(s)	Frames (n)	First Seen	Last Seen	Min dBm	Avg dBm	Max dBm	encType	authMode
1	aa:bb:cc:dd:ee:ff	TestSSID	1	2025-09-15 20:07:19	2025-09-15 20:07:19	-48	-48.0	-48	WPA2	PSK

Notes: RSSI in dBm is usually negative; **Max** (closer to 0) ≈ strongest; **Min** (more negative) ≈ weakest. **Frames (n)** is the sample size; rows with n < 5 are low confidence for RSSI statistics.

Per-Frame Details (last 25)

Src MAC	Dst MAC	SSID	encType	Auth	dBm
aa:bb:cc:dd:ee:ff	ff:ee:dd:cc:bb:aa	TestSSID	WPA2	PSK	-48