

# Python advanced class

## Module 5, Classes and objects

- Object oriented design
- Defining a class
- Instantiation
- Dataclasses
- Operator overloading
- Polymorphism
- Inheritance
- Property

## Object oriented design

# The model of a phenomena in the real World

- Most computer programs model some part of things in the real World:
  - Bank account
  - Bet on a race horse
  - A seat in a theater on a particular play night
- These phenomenas has a set of properties and some operations on them
- The idea behind Object Oriented Programming is to model things we need to represent

## Attributes and Methods

- If we want to represent a bank account it will have some attributes and methods to interact with it
- Attributes could be the balance, the contact info of the owner, and the maximum withdrawal at a time
- The methods could be to deposit more money, withdraw money, request a balance statement, or close it
- Some objects has several other objects embedded like a bank has several accounts, a theater has several seats
- Some attributes are related to a single object like the saldo of an account, while other relate to all accounts like currency

# Class vs. Instance/Object

- A class is a representation of a type or a concept like bank accounts
- When a model changes from a type to a particular one we say that we go from class to object
- That process is called instantiation and is forming an object from a set of properties into attributes of the object
- Everything in Python is an object, and every object has a type or class, even classes are objects

# Defining a class

# The class

- A class is defined as a name and optionally another class it inherits from (the class `object` if not specified)
- After the name comes a set of class attributes and methods related to instances of the class

```
In [1]: class BankAccount:
        currency: str = "EUR"

        def deposit(self, amount):
            pass
```

## The `__init__` method

- When an object has been created it should most likely need to receive some data, attributes
- The safest and easiest way to ensure this is to define an initialization method, the `__init__` method
- This sets the attributes the moment the object is created so it never will exist without its data

```
In [2]: class BankAccount:

        def __init__(self, initial_balance, owner):
            self.balance = initial_balance
            self.owner = owner
```

## The `__str__` method

- It is common to want to display an object with key attributes
- If the class defines a `__str__` method, it can just be printed

```
In [3]: class BankAccount:

    def __init__(self, initial_balance, owner):
        self.balance = initial_balance
        self.owner = owner

    def __str__(self):
        return f"BankAccount(balance={self.balance}, owner={self.owner})"
```

## Instantiation

# From class to object

- If we want to have an object of the type BankAccount we must instantiate the class
- This is like calling a function that returns an object
- The instantiation must provide the arguments to the initialization method

```
In [4]: class BankAccount:

    currency: str = "EUR"

    def __init__(self, initial_balance, owner):
        self.balance = initial_balance
        self.owner = owner

    def __str__(self):
        return f"BankAccount(balance={self.balance}, owner={self.owner!r})"

    def deposit(self, amount):
        self.balance += amount

savings = BankAccount(10000, "Ben Birch")
print(savings)

BankAccount(balance=10000, owner='Ben Birch')
```

## Accessing attributes and methods

- The attributes and methods are accessed from the instance object by at dot, `.`
- The `self` variable seen earlier is the actual instance

```
In [5]: savings = BankAccount(10000, "Ben Birch")
print(savings)
savings.deposit(500)
print(savings.balance)

BankAccount(balance=10000, owner='Ben Birch')
10500
```

## isinstance function

- The proper way to determine if an object is an instance of a particular class is the `isinstance` function
- But more often we don't need to know the class but rather if the object conforms to operate like objects of the class

```
In [6]: savings = BankAccount(10000, "Ben Birch")
if isinstance(savings, BankAccount):
    print("It's a bank account")
```

It's a bank account

## Dataclasses

# Dataclasses makes life easier

- Many operations related to checking datatypes making string function can be simplified with dataclasses
- Most classes can easier be defined by using dataclasses

In [7]: `from dataclasses import dataclass, field`

```
@dataclass
class BankAccount:
    balance: int
    owner: str

    def deposit(self, amount):
        self.balance += amount

savings = BankAccount(10000, "Ben Birch")
print(savings)
```

`BankAccount(balance=10000, owner='Ben Birch')`

## Declaring attributes

- Attributes can just be declared immediately after the class declaration
- If an attribute has a reasonable default value it can be set
- If an attribute of a mutable type must be initiated the `field` function must be used

In [8]: `@dataclass`

```
@dataclass
class BankAccount:
    balance: int = 0
    owner: str = None
    transactions: list = field(default_factory=list)

savings = BankAccount(10000, "Ben Birch")
print(savings.transactions)
```

`[]`



## The `__post_init__` method

- If additional operations are necessary after the initialization a `__post_init__` method can be used

```
In [9]: @dataclass
class BankAccount:
    balance: int = 0
    owner: str = None

    def __post_init__(self):
        if self.balance < 0:
            raise ValueError("Can't create an account with negative balance")

try:
    savings = BankAccount(-10000, "Ben Birch")
except ValueError as e:
    print("The account could not be made:", e)
else:
    print(savings.transactions)
```

The account could not be made: Can't create an account with negative balance

## Operator overloading

# Arithmetic operators

- Many types in Python allows adding them with the `+` operator: int, float, str, list, ...
- Two instances of a class can be added, if the class implements the `__add__` method
- Additionally there is `__sub__`, `__mul__`, `__div__`

```
In [10]: @dataclass
class BankAccount:
    balance: int = 0
    owner: str = None

    def __add__(self, other):
        if self.owner != other.owner:
            raise ValueError("Can't add accounts owned by different people")
        return BankAccount(balance = self.balance + other.balance, owner = self.owner)

savings = BankAccount(10000, "Ben Birch")
checking = BankAccount(1500, "Ben Birch")
one_account = savings + checking
print(one_account)
```

```
BankAccount(balance=11500, owner='Ben Birch')
```

# Comparison operators

- If two objects should be comparable for one larger than the other, the `__gt__` must be implemented
- There is likewise `__lt__`, `__ge__`, `__le__`, `__eq__`, `__ne__`, `__contains__`

```
In [11]: @dataclass
class BankAccount:
    balance: int = 0
    owner: str = None

    def __gt__(self, other):
        return self.balance > other.balance

savings = BankAccount(10000, "Ben Birch")
checking = BankAccount(1500, "Ben Birch")
print(savings > checking)
```

```
True
```

# Polymorphism

## Duck typing

- In other languages than Python it is not possible to create lists of unrelated objects
- In Python the strict type checking is done for that, as long as the classes implements methods and attributes need
- This is called duck-typing

```
In [12]: class Duck:
          def walk(self):
              print("Walks like a duck")

          class ScubaDiver:
              def walk(self):
                  print("Walks almost like a duck")

          L1 = [Duck(), Duck(), ScubaDiver(), Duck()]
          for thing in L1:
              thing.walk()
```

```
Walks like a duck
Walks like a duck
Walks almost like a duck
Walks like a duck
```

## A list of shapes

- Imagine a drawing program with different shapes
- When all shapes in the canvas needs re-drawing, each shape can draw itself

```
In [13]: class Triangle:
          pass
          class Square:
              pass
          class Circle:
              pass

          shapes = [Triangle(), Triangle(), Circle(), Square(), Circle()]
          for s in shapes:
              pass # Do stuff with each shape
```

## Inheritance

## A derived class

- A derived class is a specialized class based on a base class
- This could be a bank account for a loan with fixed payments

```
In [14]: class BankAccount:
          pass

          class LoanAccount(BankAccount):
              pass

          loan = LoanAccount()
          print(isinstance(loan, BankAccount))
```

True

## The super function

- A derived class will have most of the same functionality of the base class
- It is often practical to reuse most of the base class methods
- A `super` function will call the base class method of the same name

```
In [15]: class BankAccount:
          def __init__(self, balance, owner):
              self.balance = balance
              self.owner = owner

          class LoanAccount(BankAccount):
              def __init__(self, balance, owner, payment):
                  super().__init__(balance, owner)
                  self.payment = payment

          loan = LoanAccount(-10000, "Dennis Dawson", 1000)
          print(loan.owner, loan.payment)
```

Dennis Dawson 1000

# Property

## Hiding logic behind a property

- A property is a virtual attribute provided by a set of functions

```
In [16]: class Person:
def __init__(self, firstname, lastname):
    self.firstname = firstname
    self.lastname = lastname

def get_fullname(self):
    return self.firstname + " " + self.lastname

def set_fullname(self, name: str):
    parts = name.split(" ")
    self.firstname = parts[0]
    self.lastname = parts[1]

    fullname = property(get_fullname, set_fullname)

p = Person("Dennis", "Dawson")
print(p.fullname)
p.fullname = "Denis Dawsson"
print(p.firstname)
```

```
Dennis Dawson
Denis
```

