

# **GMII VVC** – Quick Reference

NOTE: As of UVVM v3.x, all shared variables have been made protected. This means that any access to shared variables must be done using get- and set-methods. This documentation has not yet been updated with the methods for accessing these variables, but will be very soon. Please refer to section 2 of Avalon\_mm\_vvc\_QuickRef for example usage of protected shared variables

For general information see UVVM Essential Mechanisms located in uvvm\_vvc\_framework/doc. CAUTION: shaded code/description is preliminary



#### gmii\_write (VVCT, vvc\_instance\_idx, channel, data\_array, msg, [scope])

Example: gmii\_write(GMII\_VVCT, 0, TX, v\_data\_array(0 to v\_numBytes-1), "Write v\_numBytes to DUT", C\_SCOPE);

**Example**: gmii\_write(GMII\_VVCT, 0, TX, (x"01", x"02", x"03", x"04"), "Write 4 to DUT");

### gmii\_read (VVCT, vvc\_instance\_idx, channel, [num\_bytes], [TO\_SB,] msg, [scope])

**Example**: gmii\_read(GMII\_VVCT, 1, RX, 10, "Read 10 bytes of data", C\_SCOPE);

**Example**: gmii\_read(GMII\_VVCT, 1, RX, "Read data and store it in the VVC. To be fetched later using fetch\_result()"); gmii\_read(GMII\_VVCT, 1, RX, TO\_SB, "Read data and send to Scoreboard for checking");

### gmii\_expect (VVCT, vvc\_instance\_idx, channel, data\_exp, msg, [ alert\_level, [scope]])

Example: gmii\_expect(GMII\_VVCT, 1, RX, v\_data\_array(0 to v\_numBytes-1), "Expect v\_numBytes from DUT", ERROR, C\_SCOPE);

Example: gmii\_expect(GMII\_VVCT, 1, RX, (x"01", x"02", x"03", x"04"), "Expect 4 bytes from DUT");

gmii\_vvc.vhd



GMII VVC Configuration record 'vvc\_config' -- accessible via shared\_gmii\_vvc\_config

Туре	C_GMII_VVC_CONFIG_DEFAULT
t_inter_bfm_delay	C_GMII_INTER_BFM_DELAY_DEFAULT
natural	C_CMD_QUEUE_COUNT_MAX
natural	C_CMD_QUEUE_COUNT_THRESHOLD
t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY
natural	C_RESULT_QUEUE_COUNT_MAX
natural	C_RESULT_QUEUE_COUNT_THRESHOLD
t_alert_level	C_RESULT_QUEUE_COUNT_THERSHOLD_SEVERITY
t_gmii_bfm_config	C_GMII_BFM_CONFIG_DEFAULT
t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT
	t_inter_bfm_delay natural natural t_alert_level natural natural t_alert_level t_gmii_bfm_config

#### GMII VVC Status record signal 'vvc\_status' -- accessible via shared\_gmii\_vvc\_status

Civili V V C Clarac record digital	TTO_Otatao	accession via criarca_griii_vvo_ctatac
Record element	Туре	
current_cmd_idx	natural	
previous_cmd_idx	natural	
pending_cmd_cnt	natural	

### Common VVC procedures applicable for this VVC

- See UVVM Methods QuickRef for details.

await\_[any]completion()

enable\_log\_msg()

disable\_log\_msg()

fetch\_result()

flush\_command\_queue()

terminate\_current\_command()

terminate\_all\_commands()

insert\_delay()

get\_last\_received\_cmd\_idx()



### VVC target parameters

Name	Туре	Example(s)	Description
VVCT	t_vvc_target_record	GMII_VVCT	VVC target type compiled into each VVC in order to differentiate between VVCs.
vvc_instance_idx	integer	0	Instance number of the VVC.
channel	t_channel	TX, RX	The VVC channel of the VVC instance.

### VVC functional parameters

Name	Туре	Example(s)	Description
data_array	t_slv_array	(x"D0", x"D1", x"D2", x"D3")	An array of bytes containing the data to be written/read.
data_exp			data_array(0) is written/read first, while data_array(data_array'high) is written/read last.
			For clarity, data_array is required to be ascending, for example defined by the test sequencer as follows:
			<pre>variable v_data_array : t_slv_array(0 to C_MAX_BYTES-1)(7 downto 0);.</pre>
num_bytes	positive	16	Number of bytes to be read.
alert_level	t_alert_level	ERROR or TB_WARNING	Set the severity for the alert that may be asserted by the procedure.
msg	string	"Write to DUT"	A custom message to be appended in the log/alert
scope	string	"GMII_VVC"	A string describing the scope from which the log/alert originates.
			In a simple single sequencer typically "GMII_BFM". In a verification component typically "GMII_VVC ".

### VVC entity signals

Name	Type	Description
gmii_vvc_tx_if	t_gmii_tx_if	See GMII BFM documentation.
gmii_vvc_rx_if	t_gmii_rx_if	See GMII BFM documentation.



## VVC entity generic constants

Name	Туре	Default	Description
GC_INSTANCE_IDX	natural	-	Instance number to assign the VVC.
GC_GMII_BFM_CONFIG	t_gmii_bfm_config	C_GMII_BFM_CONFIG_DEFAULT	Configuration for the GMII BFM, see GMII BFM documentation.
GC_CMD_QUEUE_COUNT_MAX	natural	1000	Absolute maximum number of commands in the VVC command queue.
GC_CMD_QUEUE_COUNT_THRESHOLD	natural	950	An alert will be generated when reaching this threshold to indicate that the command queue is almost full. The queue will still accept new commands until it reaches C_CMD_QUEUE_COUNT_MAX.
GC_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	t_alert_level	WARNING	Alert severity which will be used when command queue reaches GC_CMD_QUEUE_COUNT_THRESHOLD.
GC_RESULT_QUEUE_COUNT_MAX	natural	1000	Maximum number of unfetched results before result_queue is full.
GC_RESULT_QUEUE_COUNT_THRESHOLD	natural	950	An alert with severity 'result_queue_count_threshold_severity' will be issued if result queue exceeds this count. Used for early warning if result queue is almost full. Will be ignored if set to 0.
GC RESULT QUEUE COUNT THRESHOLD SEVERITY	t alert level	WARNING	Severity of alert to be initiated if exceeding result gueue, count, threshold



## VVC details

All VVC procedures are defined in vvc\_methods\_pkg (dedicated this VVC), and uvvm\_vvc\_framework\_td\_vvc\_framework\_common\_methods\_pkg (common VVC procedures). It is also possible to send a multicast to all instances of a VVC with ALL\_INSTANCES as parameter for vvc\_instance\_idx.

Note: Every procedure here can be called without the optional parameters enclosed in [].

### 1 VVC procedure details and examples

<u> </u>	
Procedure	Description
gmii_write()	gmii_write (VVCT, vvc_instance_idx, channel, data_array, msg, [scope])
	The gmii_write() VVC procedure adds a write command to the GMII VVC executor queue, which will run as soon as all preceding commands have completed. When the command is
	scheduled to run, the executor calls the GMII BFM gmii_write() procedure, described in the GMII BFM QuickRef.
gmii_read()	gmii_read (VVCT, vvc_instance_idx, channel, [num_bytes], [TO_SB,] msg, [scope])
	The gmii_read() VVC procedure adds a read command to the GMII VVC executor queue, which will run as soon as all preceding commands have completed. When the command is
	scheduled to run, the executor calls the GMII BFM gmii_read() procedure, described in the GMII BFM QuickRef.
	The value received from the DLIT will get be returned in this precedure cell airce it is now blocking for the accuracy/celler, but the received data and metadate will be stored in the
	The value received from the DUT will not be returned in this procedure call since it is non-blocking for the sequencer/caller, but the received data and metadata will be stored in the VVC for a potential future fetch (see example with fetch_result below).
	VVC for a potential ruture fetch (see example with fetch_result below).
	If the option TO_SB is applied, the received data will be sent to the GMII VVC dedicated scoreboard. There, it is checked against the expected value (provided by the testbench).
	in the option 18_05 to application to desirate attaining to desirate accordance and the option and the option at a second attaining to the option of the option and the option at a second attaining to the option attains at a second attaining to the option attaining to the option at a second attaining to the option attaining to the option attaining to the option attaining to the option at a second attaining attaining attaining to the option at a second attaining attaining attaining attaining att
	Example with fetch_result() call: Result is placed in v result
	variable v cmd idx : natural; Command index for the last receive
	variable v result : work.vvc cmd pkg.t vvc result; Result from read (data and metadata)
	()
	gmii_read(GMII_VVCT, 1, RX, "Read data in VVC");
	<pre>v_cmd_idx := get_last_received_cmd_idx(GMII_VVCT, 1, RX);</pre>
	<pre>await_completion(GMII_VVCT, 1, RX, 1 ms, "Wait for read to finish");</pre>
	<pre>fetch_result(GMII_VVCT, 1, RX, v_cmd_idx, v_result, "Fetching result from read operation");</pre>
gmii_expect()	gmii_expect (VVCT, vvc_instance_idx, channel, data_exp, msg, [alert_level, [scope]])
	The gmii_expect() VVC procedure adds an expect command to the GMII VVC executor queue, which will run as soon as all preceding commands have completed. When the
	command is scheduled to run, the executor calls the GMII BFM gmii_expect() procedure, described in the GMII BFM QuickRef.



### 2 VVC Configuration

Record element	Туре	C_GMII_VVC_CONFIG_DEFAULT	Description
inter_bfm_delay	t_inter_bfm_delay	C_GMII_INTER_BFM_DELAY_DEFAULT	Delay between any requested BFM accesses towards the DUT.
			- TIME_START2START: Time from a BFM start to the next BFM start
			(A TB_WARNING will be issued if access
			takes longer than TIME_START2START).
			- TIME_FINISH2START: Time from a BFM end to the next BFM start.
			Any insert_delay() command will add to the above minimum delays, giving for instance the ability to skew the BFM starting time.
cmd_queue_count_max	natural	C_CMD_QUEUE_COUNT_MAX	Maximum pending number in command queue before queue is full. Adding
			additional commands will result in an ERROR.
cmd_queue_count_threshold	natural	C_CMD_QUEUE_COUNT_THRESHOLD	An alert with severity "cmd_queue_count_threshold_severity" will be issued if
			command queue exceeds this count. Used for early warning if command queue
			is almost full. Will be ignored if set to 0.
cmd_queue_count_threshold_severity	t_alert_level	C_CMD_QUEUE_COUNT_THRESHOLD_SEVERITY	Severity of alert to be initiated if exceeding cmd_queue_count_threshold
result_queue_count_max	natural	C_RESULT_QUEUE_COUNT_MAX	Maximum number of unfetched results before result_queue is full.
result_queue_count_threshold	natural	C_RESULT_QUEUE_COUNT_THRESHOLD	An alert with severity 'result_queue_count_threshold_severity' will be issued if
			result queue exceeds this count. Used for early warning if result queue is
			almost full. Will be ignored if set to 0.
result_queue_count_threshold_severity	t_alert_level	C_RESULT_QUEUE_COUNT_THRESHOLD_SEVERITY	Severity of alert to be initiated if exceeding result_queue_count_threshold.
bfm_config	t_gmii_bfm_config	C_GMII_BFM_CONFIG_DEFAULT	Configuration for GMII BFM. See quick reference for GMII BFM.
msg_id_panel	t_msg_id_panel	C_VVC_MSG_ID_PANEL_DEFAULT	VVC dedicated message ID panel. See section 16 of
			uvvm_vvc_framework/doc/UVVM_VVC_Framework_Essential_Mechanisms.pdf
			for how to use verbosity control.

The configuration record can be accessed from the Central Testbench Sequencer through the shared variable array, e.g.:

```
shared_gmii_vvc_config(1).inter_bfm_delay.delay_in_time := 50 ns;
shared gmii vvc config(1).bfm config.clock period := 10 ns;
```

### 3 VVC Status

The current status of the VVC can be retrieved during simulation. This is achieved by reading from the shared variable shared\_gmii\_vvc\_status record from the test sequencer. The record contents can be seen below:

Record element	Туре	Description
current_cmd_idx	natural	Command index currently running
previous_cmd_idx	natural	Previous command index to run
pending_cmd_cnt	natural	Pending number of commands in the command queue



#### 4 Activity watchdog

The VVCs support a centralized VVC activity register which the activity watchdog uses to monitor the VVC activities. The VVCs will register their presence to the VVC activity register at start-up, and report when ACTIVE and INACTIVE, using dedicated VVC activity register methods, and trigger the global\_trigger\_vvc\_activity\_register signal during simulations. The activity watchdog is continuously monitoring the VVC activity register for VVC inactivity and raises an alert if no VVC activity is registered within the specified timeout period.

Include activity\_watchdog(num\_exp\_vvc, timeout, [alert\_level, [msg]]) in the testbench to start using the activity watchdog. Note that setting the exact number of expected VVCs in the VVC activity register can be omitted by setting num exp vvc = 0.

More information can be found in UVVM Essential Mechanisms PDF in the UVVM VVC Framework doc folder.

#### 5 Transaction Info

This VVC supports transaction info, a UVVM concept for distributing transaction information in a controlled manner within the complete testbench environment. The transaction info may be used in many different ways, but the main purpose is to share information directly from the VVC to a DUT model.

|--|

Info field	Туре	Default	Description
operation	t_operation	NO_OPERATION	Current VVC operation, e.g. INSERT_DELAY, POLL_UNTIL, READ, WRITE.
data_array	t_slv_array(0 to 2047)(7 downto 0)	(others => (others => '0'))	An array of bytes containing the data to be written/read.
			data_array(0) is written/read first, while data_array(data_array'high) is written/read last.
vvc_meta	t_vvc_meta	C_VVC_META_DEFAULT	VVC meta data of the executing VVC command.
→ msg	string	u u	Message of executing VVC command.
→ cmd_idx	integer	-1	Command index of executing VVC command.
transaction_status	t_transaction_status	C_TRANSACTION_STATUS_DEFAULT	Set to INACTIVE, IN_PROGRESS, FAILED or SUCCEEDED during a transaction.

See UVVM VVC Framework Essential Mechanisms PDF, section 6, for additional information about transaction types and transaction info usage.

#### 6 Scoreboard

This VVC has built in Scoreboard functionality where data can be routed by setting the TO\_SB parameter in supported method calls, i.e. gmii\_read(). Note that the data is only stored in the scoreboard and not accessible with the fetch\_result() method when the TO\_SB parameter is applied.

See the Generic Scoreboard Quick Reference PDF in the Bitvis VIP Scoreboard document folder for a complete list of available commands and additional information. The GMII scoreboard is accessible from the testbench as a shared variable GMII\_VVC\_SB, located in the vvc\_methods\_pkg.vhd. All of the listed Generic Scoreboard commands are available for the GMII VVC scoreboard using this shared variable.

#### 7 VVC Interface

In this VVC, the interface has been encapsulated in two signal records of type t\_gmii\_tx\_if for the signals going to the DUT and t\_gmii\_rx\_if for the signals coming from the DUT in order to improve readability of the code.



#### 8 Additional Documentation

Additional documentation about UVVM and its features can be found under "/uvvm vvc framework/doc/".

For additional documentation on the GMII standard, please see the GMII BFM QuickRef

### 9 Compilation

The GMII VVC must be compiled with VHDL 2008. It is dependent on the following libraries

- UVVM Utility Library (UVVM-Util), version 2.15.0 and up
- UVVM VVC Framework, version 2.11.0 and up
- GMII BFM
- Bitvis VIP Scoreboard

Before compiling the GMII VVC, assure that uvvm\_vvc\_framework, uvvm\_util and bitvis\_vip\_scorebord have been compiled.

See UVVM Essential Mechanisms located in uvvm\_vvc\_framework/doc for information about compile scripts.

#### Compile order for the GMII VVC:

Compile to library	File	Comment
<u> </u>		
bitvis_vip_gmii	gmii_bfm_pkg.vhd	GMII BFM
bitvis_vip_gmii	transaction_pkg.vhd	GMII transaction package with DTT types, constants, etc.
bitvis_vip_gmii	vvc_cmd_pkg.vhd	GMII VVC command types and operations
bitvis_vip_gmii	/uvvm_vvc_framework/src_target_dependent/td_target_support_pkg.vhd	UVVM VVC target support package, compiled into the GMII VVC library.
bitvis_vip_gmii	/uvvm_vvc_framework/src_target_dependent/td_vvc_framework_common_methods_pkg.vhd	UVVM framework common methods compiled into the GMII VVC library
bitvis_vip_gmii	vvc_methods_pkg.vhd	GMII VVC methods
bitvis_vip_gmii	/uvvm_vvc_framework/src_target_dependent/td_queue_pkg.vhd	UVVM queue package for the VVC
bitvis_vip_gmii	/uvvm_vvc_framework/src_target_dependent/td_vvc_entity_support_pkg.vhd	UVVM VVC entity support compiled into the GMII VVC library
bitvis_vip_gmii	gmii_tx_vvc.vhd	GMII TX VVC
bitvis_vip_gmii	gmii_rx_vvc.vhd	GMII RX VVC
bitvis_vip_gmii	gmii_vvc.vhd	GMII VVC

#### 10 Simulator compatibility and setup

See README.md for a list of supported simulators.

For required simulator setup see UVVM-Util Quick reference.

#### **IMPORTANT**

This is a simplified Verification IP (VIP) for GMII. The given VIP complies with the basic GMII protocol and thus allows a normal access towards a GMII interface. This VIP is not a GMII protocol checker. For a more advanced VIP please contact Bitvis AS at <a href="mailto:support@bitvis.no">support@bitvis.no</a>.



Disclaimer: This IP and any part thereof are provided "as is", without warranty of any kind, express or implied, including but not limited to the warranties of merchantability, fitness for a particular purpose and noninfringement. In no event shall the authors or copyright holders be liable for any claim, damages or other liability, whether in an action of contract, tort or otherwise, arising from, out of or in connection with this IP.