



*


BMS Connector



5V to 3.3V LDO @ 1A Max



Power LEDs



$$R_{5V} = (5V - 2.1V) / (0.5mA) = 5.8k\Omega$$

$$R_{3V3} = (3.3V - 2.1V) / (0.5mA) = 2.4k\Omega$$

WARG

Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT
Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
*

DOCUMENT
LDO.SchDoc

MODIFIED
11/20/2021

ENGINEER
Daniel Puratich


REVIEWER
*



SHEET 1 OF 9

*


microSD Connector

A
Ground DAT1 & DAT2?




		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1			
PROJECT Zeropilot 2.0.PrjPcb, [No Variations]				REVISION ★	
DOCUMENT microSD_Connector.SchDoc				MODIFIED 11/20/2021	
ENGINEER Kiran Surendran		REVIEWER ★		SHEET 3 OF 9	


UART Connectors




I2C Connectors




SWD/SWO Connector




VN-300 Connector



Ultrasonic Connector



MAX3232 Connector




Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT Zeropilot 2.0.PrjPcb, [No Variations]		REVISION *
DOCUMENT H7Connectors.SchDoc		MODIFIED 11/20/2021
ENGINEER Kiran Surendran	REVIEWER *	SHEET 4 OF 9

H7 Bypass Capacitors




VDD Bypass: $(0.1\mu\text{F} \times 16) + (10\mu\text{F} \times 1)$
 VDDLDO Bypass: $4.7\mu\text{F} \times 1$
 VDDUSB Bypass: $(0.1\mu\text{F} \times 1) + (1\mu\text{F} \times 1)$
 Should be placed as close as possible to each VDD pin.





PROJECT Zeropilot 2.0.PrjPcb, [No Variations]		REVISION *
DOCUMENT H7Power.SchDoc		MODIFIED 11/20/2021
ENGINEER Kiran Surendran	REVIEWER *	SHEET 5 OF 9


Zeropilot 2.0



$$R = (3.3V - 2.0V) / (0.5mA) = 2.6k\Omega$$

		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1			
PROJECT				REVISION	
Zeropilot 2.0.PrjPcb, [No Variations]				1	
DOCUMENT				MODIFIED	
H7PartA.SchDoc				11/20/2021	
ENGINEER		REVIEWER		SHEET	
Kiran Surendran		*		6 OF 9	



*




Load Capacitance, CL = 15pF
Assume Cstray = 5pF

$$CL = ((C1 * C2) / (C1 + C2)) + Cstray$$


C1 = C2 = 20pF

		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1			
PROJECT			REVISION		
Zeropilot 2.0.PrjPcb, [No Variations]			*		
DOCUMENT			MODIFIED		
H7PartB.SchDoc			11/17/2021		
ENGINEER		REVIEWER		SHEET	
Kiran Surendran		*		7 OF 9	

PWM Connectors




PPM Connector




*

SWD/SWO Connector



SPI/I2C Connector



Required I2C pullup resistors.

F0 SPI2 / I2C1 header can be switched between the two by soldering or unsoldering the 0ohm resistors. Do not place both at the same time as this will cause a short!

GPIO intended to be used as a 2nd chip select for SPI if needed.

WARG

Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT
Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
*

DOCUMENT
F0Connectors.SchDoc

MODIFIED
11/20/2021


ENGINEER
Daniel Puratich

REVIEWER
*


SHEET 8 OF 9



▲ Add notes detailing pinout once finalized.




F0 Bypass Capacitors



▲ Decoupling capacitor placement guide is found in the datasheet on page 42 of the datasheet.

F0 Debugging LEDs



▲ $R = (3.3V - 2.8V) / (0.5mA) = 1k\Omega$

WARG

Waterloo Aerial Robotics Group
 200 University Ave W
 Waterloo, Ontario, Canada
 N2L 3G1



PROJECT
 Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
 *

DOCUMENT
 F0Chip.SchDoc

MODIFIED
 11/19/2021

ENGINEER
 Daniel Puratich

REVIEWER
 *

SHEET 9 OF 9

