



*


BMS Connector



5V to 3.3V LDO @ 1A Max



Power LEDs



$$R_{5V} = (5V - 2.1V) / (0.5mA) = 5.8k\Omega$$

$$R_{3V3} = (3.3V - 2.1V) / (0.5mA) = 2.4k\Omega$$

WARG

Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT
Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
*

DOCUMENT
LDO.SchDoc

MODIFIED
11/20/2021

ENGINEER
Daniel Puratich


REVIEWER
*



SHEET 1 OF 9

*





microSD Connector

A
Ground DAT1 &
DAT2?





		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1		
PROJECT		REVISION		
Zeropilot 2.0.PrjPcb, [No Variations]		*		
DOCUMENT		MODIFIED		
microSD_Connector.SchDoc		11/20/2021		
ENGINEER		REVIEWER		
Kiran Surendran		*		
SHEET		3 OF 9		


UART Connectors




I2C Connectors




SWD/SWO Connector





VN-300 Connector



Ultrasonic Connector




MAX3232 Connector


		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1			
PROJECT Zeropilot 2.0.PrjPcb, [No Variations]				REVISION ★	
DOCUMENT H7Connectors.SchDoc				MODIFIED 11/21/2021	
ENGINEER Kiran Surendran		REVIEWER ★		SHEET 4 OF 9	

*

H7 Power Pins



H7 Bypass Capacitors



^A VDD Bypass: $(0.1\mu\text{F} \times 16) + (10\mu\text{F} \times 1)$
 VDDLDO Bypass: $4.7\mu\text{F} \times 1$
 VDDUSB Bypass: $(0.1\mu\text{F} \times 1) + (1\mu\text{F} \times 1)$
 Should be placed as close as possible to each VDD pin.

WARG

Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT
Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
*

DOCUMENT
H7Power.SchDoc


MODIFIED
11/20/2021

ENGINEER
Kiran Surendran

REVIEWER
*

SHEET 5 OF 9

Zeropilot 2.0




$$R = (3.3V - 2.0V) / (0.5mA) = 2.6k\Omega$$



Waterloo Aerial Robotics Group
200 University Ave W
Waterloo, Ontario, Canada
N2L 3G1



PROJECT Zeropilot 2.0.PrjPcb, [No Variations]		REVISION 1
DOCUMENT H7PartA.SchDoc		MODIFIED 11/20/2021
ENGINEER Kiran Surendran	REVIEWER *	SHEET 6 OF 9



Load Capacitance, $CL = 15\text{pF}$
 Assume $C_{\text{stray}} = 5\text{pF}$
 $CL = ((C1 * C2) / (C1 + C2)) + C_{\text{stray}}$
 $C1 = C2 = 20\text{pF}$



Waterloo Aerial Robotics Group
 200 University Ave W
 Waterloo, Ontario, Canada
 N2L 3G1



PROJECT
 Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
 *

DOCUMENT
 H7PartB.SchDoc


MODIFIED
 11/17/2021

ENGINEER
 Kiran Surendran


REVIEWER
 *

SHEET 7 OF 9

PWM Connectors




PPM Connector




*


SWD/SWO Connector





I2C Connector




SPI Connector




		Waterloo Aerial Robotics Group 200 University Ave W Waterloo, Ontario, Canada N2L 3G1		
PROJECT		REVISION		
Zeropilot 2.0.PrjPcb, [No Variations]		*		
DOCUMENT		MODIFIED		
F0Connectors.SchDoc		11/21/2021		
ENGINEER		REVIEWER		
Daniel Puratich		*		
		SHEET		8 OF 9



▲ Add notes detailing pinout once finalized.




F0 Bypass Capacitors



▲ Decoupling capacitor placement guide is found in the datasheet on page 42 of the datasheet.

F0 Debugging LEDs



▲ $R = (3.3V - 2.8V) / (0.5mA) = 1k\Omega$

WARG

Waterloo Aerial Robotics Group
 200 University Ave W
 Waterloo, Ontario, Canada
 N2L 3G1



PROJECT
 Zeropilot 2.0.PrjPcb, [No Variations]

REVISION
 *

DOCUMENT
 F0Chip.SchDoc

MODIFIED
 11/19/2021

ENGINEER
 Daniel Puratich

REVIEWER
 *

SHEET 9 OF 9

