

MULTIOBJECTIVE FUZZY APPROACH TO THE VEHICLE ROUTING PROBLEM WITH TIME WINDOWS


Przemysław Wesolek

Marek Kubiak


Poznań University of Technology, Poznań, Poland

Fuzzy VRPTW


Service start times



Models of customer time window



Intuitive uncertain travel times



The problem contains two objectives:

- maximization of satisfaction
- minimization of cost

Motivation

No diversity \rightarrow no choice

- no option for a DM: only one solution (the best one?)
- the best solution is the magic one (w.r.t. one objective)


Unrealistic assumptions

- deterministic parameters, e.g. travel times, are unrealistic
- stochastic models contain too strong assumptions



Pareto Memetic Algorithm

Main loop of the multiobjective evolutionary algorithm

- Choose a direction
- Choose parents
- Recombine
- Do local search
- Update Pareto set




Main results




Advantages

- diversified solutions
- lower cost and satisfaction vs. high cost and satisfaction
- possibility of choice of a solution
- possibility of renegotiation of time windows


Examples of solutions from a Pareto set




routes = 19
sat = 1.0; cost = 1587




routes = 16
sat = 0.68; cost = 1451




routes = 15
sat = 0.13; cost = 1362




Achievement scalarizing functions




Local search: exchange of two customers




Local search: relocation of a customer



Route-based crossover





Common edges preserving crossover




Additional conclusions

Comparison of approximations: coverage C



Comparison of instances:

- clustered instances are easier than random ones
- wide time window \rightarrow easier random instances
- wide time window \rightarrow harder clustered instances



Comparison of crossovers:

- RBX is random, CEPX is deterministic
- RBX is usually better than CEPX
- randomness in RBX is useful

Comparison of approximations: R measure

