MEGARAC® CM-X

Chassis Management Firmware Solution

The MegaRAC CM-X Chassis Management Firmware Solution from AMI implements – and is fully compliant with – the Open Blade Architecture System Management Specification from the Server System Infrastructure (SSI) Forum, an industry organization promoting design guidelines for blade chassis components and interfaces. This group, which aims to expand the product offering available in the market at a price point that appeals to small and medium-sized businesses (SMBs), gathers support from major industry players such as Asus®, Dell®, Intel®, Quanta® and SuperMicro®, among others.

MegaRAC CM-X is a robust Linux® based management stack, including an embedded web server. This solution enables the discovery, health monitoring and management of all modules inside the blade chassis, including compute blades, Baseboard Management Controllers (BMCs), I/O modules, power supplies and cooling devices.

Features:

- Fully compliant with the Open Blade Architecture System Management Specification from the Server System Infrastructure (SSI) Forum
- Blade element discovery, health monitoring & management, including power cycle, blade presence and state change events
- Asset tracking and management for all chassis product data and FRUs
- LED, LCD display and components control

Management functions of MegaRAC CM-X include:

- Power and cooling management
- Chassis initialization
- Blade authentication
- Blade presence hardware detection
- Blade state management
- New blade discovery events
- New Chassis Management Controller (CMC) initialization
- Failover support (optional component)

Discovery is based on universal, standard protocols, such as UPnP, RMCP Ping, SNMP, SLP and WS-Discovery. Management of the chassis components is based on AMI's own MegaRAC Service Processor (SP-X) firmware stack and the IPMI 2.0 protocol.

MegaRAC CM-X supports the Distributed Management Task Force (DMTF) management standards for interoperability, such as the Common Information Model, WS-MAN for management through web services and SMASH-CLP for text line console and scripting.

Features:

- Consolidated Chassis Event Log (CEL)
- Common console for remote KVM (mKVM) and media (vMedia) for all blades
- Serial Over LAN (SOL) proxy service for all compute blades and I/O modules
- Multiple SOL support

MegaRAC CM can be easily customized and extended with AMI's Integrated Development Environment (IDE) for management, MegaRAC Development Studio (DS), based on the widely-used Eclipse® IDE. MegaRAC DS includes Visual Web Developer (VWD), Software Development Kits for CIM, SMASH and WS-MAN software development and an IPMI PDK for the graphical layout of platform sensors.

MegaRAC management products from AMI are designed to provide OEMs with the most advanced technologies, with a special focus on porting tools that preserve investment over time.

Features:

- Centralized firmware image management
- Alert management with SNMP v3 and SMTP-based email alert support
- Optional Active/Passive fail-over configuration

Eclipse® is a registered trademark of Eclipse Foundation Inc. Linux® is a registered trademark of Linus Torvalds in the U.S. and other countries. Asus® is a registered trademark of Asustek Computer, Inc. Dell® is a registered trademark of Dell Inc. Quanta® is a registered trademark of Quanta Computer, Inc. SuperMicro® is a registered trademark of SuperMicro Computer, Inc.

For more information please visit the request form at ami.com/contact

Copyright ©2022 AMI. All rights reserved. Product specifications are subject to change without notice. Products mentioned herein may be trademarks or registered trademarks of their respective companies. No warranties are made, either expressed or implied, with regard to the contents of this work, its merchantability or fitness for a particular use. This publication contains proprietary information and is protected by copyright. AMI reserves the right to update, change and/or modify this product at any time.